

Description

BACKGROUND OF THE INVENTION

5 This invention relates to a power converter such as an inverter and more particularly to a method and apparatus for controlling a power converter which is preferably used for a winding machine for an elevator.

Inverters have been widely used for controlling elevators using induction motors for driving winding machines. Power converters including such inverters have been mainly controlled by analog control systems. Such analog control systems, however, provide several problems including their output fluctuation and limited setting accuracy; the output fluctuation will be caused by the secular changes of several components used in the systems.

In order to solve these problems, several digital control systems have been proposed.

One example thereof is disclosed in JP-A-57-25171. In the system disclosed therein, pulse width data are previously stored, during the absence of the processing by a microcomputer, in a timer externally attached in the bus of the microcomputer, and the microcomputer, when interrupted by the timer, only supplies an actuation instruction to the timer, thereafter performing a scheduled processing, so that the microcomputer doesn't need to perform the output processing. This system permits the microcomputer to concentrate on the processings of the reference to a data table for acquisition of the pulse width data and the data working so that the performance thereof may be improved.

20 Another example is disclosed in an article entitled "Magnetic Flux Type Realtime Processing PWM (Pulse Width Modulation) Control by One-chip Microcomputer" in the Proceedings of the Institute of Electrical Engineers of Japan, Vol. 105, No. 6, pp 531-538, (June 1985), 60-B61. This example is a system of performing a PWM control in a direct connection of an input/output port incorporated in a one-chip microcomputer and a pulse amplifier. This system provides the advantages that the circuit construction is simplified since the timer can be incorporated in the one-chip microcomputer and the distribution circuit can be implemented in software, and the abnormality of the port can be covered in some degree by the self-diagnosis function of the microcomputer.

However, the former system involves the following problems since a timer, distribution circuit, etc. must be externally provided.

30 ① In the system arrangement, required are the timer circuit and the circuit for distributing three-system timer outputs to six switching elements of a power converter of a three-phase A.C. system, and these circuits externally attached may increase the production cost of the system and the possibility of the malfunction thereof due to noise mixing.

35 ② Since the timer and distribution circuits are provided externally from the microcomputer, the selfdiagnosis function of the microcomputer, e.g., watch dog timer doesn't permit their abnormality to be detected. Therefore, another abnormality detection circuit is required for the circuits externally provided.

On the other hand, the latter system involves the problem that because of the increased amount of processing in the microcomputer, the minimum pulse width of the control signals to be supplied to the switching elements of the power converter cannot be reduced less than the interruption processing time in the microcomputer.

40 The reference US-A 4,488,103 discloses a method for generating pulses by PWM control, in which a comparison of a carrier wave with a modulation wave is carried out in digitals with high accuracy, and a PWM pulse train is generated. However, since it is limited to the comparison between the carrier wave and the modulation wave, only the PWM pulse train can be generated. In other words, it is entirely impossible to meet various demands for variations, and it is not flexible. For example, since it is impossible to obtain a PWM pulse which turns on positive and negative elements overlapping with each other, it is used exclusively for a voltage type inverter, and it cannot be used for a current type inverter. Furthermore, it is impossible to adjust non-lap width and to adjust a switching frequency.

50 SUMMARY OF THE INVENTION

An object of this invention is to provide a method and apparatus for controlling a power converter which is capable of solving the aforesaid problems of the prior art and generating pulse outputs with their pulse width being sufficiently narrow, in a simplified circuit construction using a microcomputer.

55 To attain this object, in accordance with this invention, pulse patterns for creating control signals to be supplied to the switching elements of a power converter are previously and successively created, a schedule processing of successively setting, as pairs, the pulse patterns and times when they are to be supplied is executed and the control signals are successively output at the times when they are to be

actually supplied to the switching elements have come. Thus, the control signals can be previously created prior to the times when they are actually required, regardless of the times, so that the microcomputer bears a light burden and pulse outputs with their minimum pulse width being sufficiently narrow can be generated in a simplified system arrangement.

The above and other objects and feature of this invention will become more readily apparent from the following description of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 is a view showing a whole arrangement of one embodiment of this invention;
 Fig. 2 is a flowchart of an event acquisition processing;
 Fig. 3 is a flowchart of an event set processing;
 Fig. 4 is a view for explaining actuation timings;
 Fig. 5 is a flowchart of a mode selection processing;
 Fig. 6 is a view for explaining the modes;
 Fig. 7 is a view for explaining a time set processing;
 Fig. 8 is a timing chart of one example of a signal waveform;
 Fig. 9 is a flowchart of an event set processing;
 Fig. 10 is a flowchart of the operation of an execution controller;
 Fig. 11 is a view for explaining one example of the event set processing;
 Fig. 12 is a view for explaining another example of the event set processing;
 Fig. 13 is flowchart of a phase, conduction-ratio instruction creation processing;
 Fig. 14 is a view for explaining a phase, conduction ratio characteristic;
 Fig. 15 is a flowchart of a power supply interruption processing;
 Fig. 16 is a flowchart of a phase completion interruption processing;
 Fig. 17 is a flowchart of a pulse switching processing;
 Fig. 18 is a timing chart of one example of an actuation timing;
 Fig. 19 is a view for explaining the pulse switching processing;
 Fig. 20 is a flowchart of another example of the pulse switching processing; and
 Fig. 21 is a flowchart of another example of the event set processing.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Now referring to the drawings, detailed explanation will be given for a power converter controlling apparatus according to this invention using the embodiment as shown in the drawings.

Fig. 1 shows a whole arrangement of one embodiment of this invention. In the figure, 1 is a three-phase A.C. power supply; 2 is a capacitor for excess voltage suppression; 3 is a current converter section for performing A.C.-D.C. conversion; 31 to 36 are transistors which constitute the main switching elements of the converter section 3; 4 is a D.C. reactor; 5 is a current converter section for performing D.C.-A.C. conversion; 51 to 56 are transistors which constitute the main switching elements of the converter section 5; 6 is a capacitor for excess voltage suppression; 7 is an induction motor shown as one example of a load; 8 is a D.C. current detector; 9 is a comparator for comparing a primary current instruction i_1^* with a feedback value i_1 ; and 10 and 11 are one-chip microcomputers for supplying pulse patterns (control signals) to the transistors 31 to 36 and 51 to 56. Incidentally, since the one-chip microcomputers 10 and 11 have the same hardware construction, their detailed explanation will be mainly given for the microcomputer 10. Also in this embodiment, transistors are used as the main switching elements but the other elements having a switching function, e.g. GTO (Gate Turn-Off Thyristor) may also be used.

Further, in Fig. 1, 12 is a terminal to which a primary current instruction i_1^* to be applied to a converter control system is supplied; 13 and 14 are terminals to which a frequency instruction ω_1^* and a phase instruction θ^* , which are to be supplied to an inverter control system, are supplied, respectively; and 15 is a signal line for inputting signals for power supply synchronization.

The one-chip microcomputer 10 is constructed by an input port 101, an internal bus 102, a ROM (read-only memory) 103 for storing programs, a pulse width data table, etc., a RAM (random access memory) 104 which is used as a temporary memory or register, an ALU (arithmetic logic unit) 105 for performing arithmetic, etc., an event setting register 107 for setting an event necessary for outputting control signals consisting of predetermined pulse patterns to an output port, a timing setting register 108 for setting the timings when the event is to be enabled, a holding register 109 for concatenating the contents of both registers 107 and 108 and holding them, an associative memory 110 for successively and cyclically storing

some sets of data set in the holding register 109, a timer 111 for outputting actual timings, a comparator section 112 for comparing the timings given by the timer 111 with the timings set in the associative memory 110 and generating outputs when they coincide with each other, an execution controller 113 for output-controlling, in response to the trigger received from the comparator section 112, the set event to the output port 106.

Now, the operation of this embodiment will be explained. Here, the case of inverter control for D.C.-A.C. inverter 5 will be explained.

Fig. 2 is a schematic flowchart of an event acquisition processing program F1000 for acquiring an event or pulse pattern to be generated to the output port 106. First, a frequency instruction ω_1^* and a phase instruction θ^* , which are sent from an external instruction device, are read from the input port 101 (F1100); if ω_1^* and θ^* are calculated within the one-chip microcomputer 10, this port reading is not required. The frequency instruction ω_1^* is integrated for each fixed time (interruption interval) Δt_1 and added to the phase instruction θ^* so as to obtain a total phase θ_T (F1200). There are six modes of pulse pattern provided by dividing an electric angle of 360° into six angle ranges, each of which is 60° . One of the six modes to be outputted is selected in accordance with the total phase θ_T now acquired, that is, the output event decided in accordance with the total phase θ_T is acquired (F1300). The relation between the total phase θ_T and the six modes will be described in detail later (Fig. 5). Finally, the time t_{EN} elapsed until when the pulse pattern is changed during the interruption interval Δt_1 is acquired with reference to a data table using the total phase θ_T (F1400).

Thus, two items, i.e. the event contents and event change timings which are set in the event setting register 107 and the timing setting register 108 are decided.

The two items thus obtained are set in the associative memory 110 provided for an output port control in the flowchart as shown in Fig. 3. More specifically, first, a checking is made on if the event and timing have been set for all six transistors (F2100). If the answer is NO, the associated event is set (F2200) and thereafter the associated event change timing is set (F2300). Thus, the processing of F2000 is ended.

The two processings of F1000 and F2000 mentioned above will be actuated at the timings as shown in Fig. 4. The event setting processing F2000 is actuated in synchronism with first timer interruptions occurred for each Δt_1 . On the other hand, the event acquisition processing F1000 is actuated in synchronism with second timer interruptions, which also occur for each Δt_1 , prior to the first timer interruptions. And the event acquisition processing is completed immediately before the actuation of F2000. This intends to permit the newest data to be used in F2000. Of course, if the redundant time element corresponding to the timer interruption interval may be included, F2000 can be followed by F1000. In this case, the time required for the checking of an interruption is reduced so that the interruption interval Δt_1 can be set to a short time, thereby permitting a high frequency converter to be realized.

Accordingly, in accordance with this embodiment, after predetermined events and timings have been set, the associative memory 110 undertakes the output port control so that the main processor section (ALU 105) is released from the output processing.

Referring to Fig. 5, the decision of pulse patterns in the procession of F1300 will be explained.

In the case of the inverter control in accordance with this embodiment, the pulse pattern is changed for each electric angle of 60° six modes making a tour of 360° are repeated. Therefore, the six modes M1 to M6 each having an interval of 60° are adapted to be selected for the total phase θ_T . The flowchart for this selection is shown in Fig. 5. If the total phase θ_T goes out from the range of 0° to 360° , an area checking is made at the top of F1300 shown in Fig. 2; this area checking adds/subtracts 360° to/from the total phase θ_T to bring back it in the above range.

Fig. 6 shows, for each of the modes M1 to M6, a combination of a transistor which is being always turned on during the interval Δt_1 , a transistor which is being turned on until the generation of the event and thereafter, being turned off, and a transistor which is being turned off until the generation of the event and thereafter being turned on. From the figure, therefore, if the phase θ_T is provided, the associated mode is also provided so that the transistors to be turned on or off can be specified. The matter which is not clear at this time when the processing of F1300 has been completed is only the timings of turn-on or off.

Incidentally, the turn-on/off of the transistors means that their outputs are specified, for example, in such a manner that when the event is set, the turn-on thereof sets a register to "1" while the turn-off thereof set the register to "0".

Referring to Fig. 7, the processing of providing the timings when the event is to be changed (F1400 of Fig. 2) will be explained.

Since the inverter in this embodiment only desires to provide a waveform analogous to a sine wave output, adopted is a system in which the interruption interval is distributed to the ratio of $\sin \theta_T$ to $\sin (60^\circ - \theta_T)$ phase-displaced by 120° therefrom in accordance with the phase θ_T . Namely, the times t_E elapsed until

when the event is generated (or the pulse pattern is changed), which are calculated as a function of the phase θ_T from the following equation, are previously tablated, and searched using the phase θ_T .

$$t_E = \frac{\Delta t_1 \cdot \sin(60^\circ - \theta_T)}{\sin(60^\circ - \theta_T) + \sin \theta_T}$$

Incidentally, this embodiment, which relates to a current source inverter, has a merit that the working of the data table is not required since that inverter has only to act as a switch for converting an original waveform into a sine wave. In the case where this invention is applied to a voltage source inverter, after the searching of the table, the working of the data must be performed considering the amplitude, pulse width, etc.

Fig. 8 shows one example of the port output signals S51 to S56 supplied to the transistors 51 to 56 in accordance with the operation mode.

As seen from the figure, the operation modes M1 to M6 have different electric angles. This is because the timer interruption interval Δt_1 is asynchronous with the frequency instruction ω_1^* , and so can be obviated by controlling Δt_1 so that it varies in accordance with ω_1^* .

Referring to Fig. 9, the event setting processing will be explained. Fig. 9 is a flowchart in which the starting portion at the mode M1 in Fig. 8 is embodied. Although in Fig. 3, the event setting processing has been explained in a loop arrangement for its general explanation, it actually flows in series as shown in Fig. 9.

The flowchart of Fig. 9 shows the event setting processing during the timer interruption interval from a time $t_0 + t_d$ to a time $t_0 + t_d + \Delta t_1$ in Fig. 8. First, when an interruption occurs at the time t_0 , two sets of event setting and timing setting are made for the transistor 55 and 53 so that a turn-on signal is immediately supplied to them (F2410); as shown in Fig. 8 the transistor 55 is always turned on during the mode M1 and the transistor 53 is turned on only until when the event is generated. More specifically, the event setting is performed so that a "1" signal is generated at the ports 5 and 3 corresponding to the transistors 55 and 53 and the timing setting is made by setting the present time t_0 plus a prescribed time t_d in a predetermined register. Then, since those transistors are to be immediately turned on, the prescribed time t_d must be set to an allowable minimum value. In this way, the events and timings are set in the associative memory 110, and thereafter when t_d elapses, the "1" signal will be output to the transistors 55 and 53 along the prescribed schedule.

The reason why the prescribed time t_d is added to the time t_0 is as follows. Some time necessarily elapses until when the event is read out after it has been set in the associative memory 110. Therefore, if the present time t_0 is set without adding the time t_d , the coincidence in the comparator 112 cannot be obtained so that the event cannot be supplied to the output port 106.

Now returning back to the flowchart of Fig. 9, in the processing of F2420, the processing of recognizing the turn-off of the transistors to be in a turn-off state during the mode M1 is carried out on the assumption that the operation mode has been changed because of the abrupt change of the phase instruction θ^* , etc. This processing is also performed by the associative memory 110 like F2410. Since the event to be set is "turn-off", the event setting is made so that a "0" signal is generated at the port 1, 2, 4 and 6.

Next, a scheduled processing of F2430 is performed so that the transistor 53 is turned off at the timing of $t_0 + t_{EN}$. The event to be set is an "0" output at the port 3 and the timing to be set is $t_0 + t_{EN}$.

In the processing of F2440, the scheduled setting is performed so that the transistor 51 is turned on in place of the turn-off of the transistor 53. Although in this embodiment, the turn-off of the transistor 53 and the turn-on of the transistor 51 have been scheduled at the same timing ($t_0 + t_{EN}$), it is also possible to use different times of t_{EN} in F2430 and F2440 for the protection of excess voltage in such a manner that in the current source inverter the "1" periods overlap each other while in the voltage source inverter, a non-overlap period is created.

After the processings of F2410 to F2440 have been performed, the associative memory 110 performs the timing comparison and output control for each predetermined time so that the main processor section (ALU 105) is released from the output processing.

The operation of the execution controller 113 will be explained with reference to the flowchart of Fig. 10.

First, in a processing 1131, checking is made on if a coincidence output has been provided by the comparator 112. This checking is made by the existence of the signal generated by the comparator 112 when the value (real time) of the timer 111 coincides with the contents (set timing), written in the timing

setting register, of the scheduled contents. If the coincidence output is not present, any processing doesn't follow but the operation of the execution controller 113 is returned to its beginning. On the other hand, if the coincidence output is present, the event to be executed is read out in a processing 1132. Namely, when the time elapses to reach the scheduled timing, the event making a pair with the timing is read out. In a processing 1133, the voltage level to be sent to the output port 106. In this embodiment, the output levels corresponding to the turn-on/off of the transistors 51 to 56 are checked. In a processing 1134, checking is made on if any one of the transistors 51 to 56 that is, any one port of the output port 106 is to be supplied with the voltage. Finally, in a processing 1135, the scheduled signal is actually output to the associated port of the output port 106.

In this way, the execution controller serves to control the execution of the event in such a way that when the scheduled time has come, the associated signal is received and the event making a pair therewith is implemented.

Now referring to Figs. 11 and 12, detailed explanation will be given for the setting of plural events at the same port within the same timer interruption.

Fig. 11 (a) and Fig. 11 (b) show two sine waves, sine θ_T and sine $(60^\circ - \theta_T)$ and a pulse pattern S53 to be supplied to the transistor 53 during the period of $t_0 \sim t_0 + \Delta t_1$. In the case of this pulse pattern, as seen from Fig. 11 (b), two settings of a turn-on setting at t_0 and a turn-off setting at $t_0 + t_{EN-1}$ are made for the port 3 during the timer interruption interval Δt_1 . On the other hand, in the case shown in Fig. 12, four turn-on/off settings are made during Δt_1 . More specifically, the timer interruption interval Δt_1 is divided into two half sections, and during the former half section, $\Delta t_{1/2}$ is distributed with a ratio between the sine wave peak values of

$$\theta_{T_{n-1}}$$

at the timing t_0 , while during the latter half section the remaining $\Delta t_{1/2}$ is distributed with a ratio between the sine wave peak values of an estimation value θ_{TE} of θ_T at the timing $t_0 + \Delta t_{1/2}$, which is obtained from θ_{n-1} and θ_{n-2} . This provides the following effect. As understood from the operation state of the microcomputer shown in Fig. 11(c), if the pulse generation interval is reduced, the load ratio of the microcomputer (ratio of the actuation state to the idling state) is increased, so that the timer interruption interval Δt_1 is necessarily limited because of the processing time indispensable to a pulse with arithmetic, etc. This is a serious problem to implement a high frequency power converter using a microcomputer. On the other hand, in this embodiment, plural event setting can be made for the same port during the timer interruption interval Δt_1 , thereby allowing the high frequency power converter to be realized.

Now, explanation will be given for another case of this embodiment when applied for controlling the converter section 3 for performing A.C.-D.C. conversion. The converter control is performed by the microcomputer 11. The converter control is more complicated than the inverter control since the following two operations must be simultaneously performed.

① In the case of the inverter control, synchronization is not entirely required, while in the converter control, the synchronization with a power supply frequency must be taken.

② In the case of the inverter control, a switching operation having a conduction rate (or current flow rate) of 1 has only to be performed while in the case of the converter a pulse width control must be performed considering the conduction ratio of 0 to 1.

First, for the synchronization of ① the phase control, which has been in the conventional thyristor control, is adopted. In this phase control, the event to be supplied to the associative memory is a software timer interruption event in which the microcomputer itself is interrupted (in the case of inverter control, that event was a pulse turn-on/off instructions, 0* and 1*), and the timing to set is a time corresponding to a phase data. Further, when the phase schedule operation has been completed, a series of schedule relative to pulse switching must be initiated.

On the other hand, with respect to ②, considerations must be taken that the table of the time elapsed until when an event is generated, as shown in Fig. 7 is individually provided for several conduction ratios, and if the time elapsed until when the event is generated is comparatively long (i.e. when several processings are performed in a sufficient time), a scheduled processing of setting the succeeding several events and timings is performed.

Main processings in the converter control will be explained with reference to several flowcharts and timing charts.

Fig. 13 shows a flowchart of a phase, conduction ratio instruction creation processing F3000. First, a current difference Δi is taken in the microcomputer 11 from the comparator 9 (Fig. 1) through an A/D (analog-to-digital) converter (not shown) (F3100). A phase instruction Ph^* and conduction ratio instruction γ^* for this current difference, with their characteristics as shown in Fig. 14, are acquired (F3200 and F3300).
 5 These instructions Ph^* and γ^* may be created in an external analog circuit and taken in the microcomputer 11 after the A/D conversion.

Fig. 15 is a flowchart of a power supply interruption processing F4000. It should be noted that if the microcomputer 11 is externally interrupted, for example, by detecting a rising zero-crossing point of the U-phase of a three-phase power supply through the signal line 15 (Fig. 15), this interruption is generated for
 10 each electric angle of 360° . When this interruption occurs, in a processing F4100, the event which generates a variable software-interruption in the microcomputer itself is set. In a processing F4200, the time corresponding to the phase instruction Ph^* acquired in F3200 is set as a timing when the event is to be generated.

In the case of the inverter control mentioned above, the pulse switching processing was actuated by the
 15 timer interruption occurring for each substantially constant time, while in the case of the converter control, it will be actuated after the power interruption processing and the succeeding phase time.

Fig. 16 shows a flowchart of a phase completion interruption processing of F5000. This processing is actuated when the phase time set in the power interruption processing of F4000 has come. First, in F5100, the event of "1" and the timing of the present time t_0 plus a short dummy time t_d are set in the associative
 20 memory for the transistors 33 and 35 to be instantaneously turned on. In F5200, the events of "0" and "1" are set for the transistors 33 and 35 to be subsequently turned off and on; and the timing T_w , which is acquired by referring to the table of conduction rate instructions γ^* and pulse width data, is also set for them. In F5300, an event of self-interruption is set at the above pulse switching timing T_w for the preparation of the subsequent pulse switching. Finally, in F5400 the jumping destination, on a program, of
 25 the subsequent switching processing is previously acquired.

Fig. 17 shows the beginning portion of a pulse switching processing F6000. This beginning portion follows the phase completion interruption processing F5000. First, in F6010, the events of "0" and "1" are set for the transistors 31 and 32, respectively and the timing T_w is also set for them. In F6020, the event which generates the variable software interruption in the microcomputer itself at the timing T_w set in F6010
 30 and its timing T_w are set. In F6030, the jumping destination of the subsequent pulse switching processing F6000. (The reason why F6000 is executed in a sequence processing is that shortening the time required for the judgement of the jumping destination allows the minimum pulse width to be reduced.) In the F6030, the jumping destination is set so that the subsequent pulse switching processing F6000 jumps to the next line of F6030 when it is actuated.

The time schedule in which the aforesaid processings of F4000, F5000 and F6000 are actuated in Fig.
 35 18. As seen from the figure, the power supply processing F4000 is actuated by a power interruption signals which occurs for each electric angle of 360° ; the phase completion interruption processing F5000 which has been scheduled in F4000 is actuated after the time corresponding to the phase data Ph^* ; and the pulse switching processing F6000 is actuated at the turn-on/off timings T_w which have been scheduled in F5000.

Fig. 19 shows a concrete example of the actuation of the pulse switching processing F6000. In Fig. 19,
 40 only the interval of an electric angle of 60° is shown, and the other intervals are omitted since the destination of distributing pulses is only different as in the case of the inverter control.

The conduction rate instruction γ^* may be 0.00 to 1.00, and now $\gamma^* = 0.75$ is taken as an example. Four kinds of γ^* vs. pulse width data table (Tables 1 to 4), which are indicated by a solid line, a dotted line, a
 45 broken line and a one-dot chain line, respectively, are folded back at an electric angle of 30° . F5100, F5200 and F5300 included in the phase completion interruption processing F5000 shown in Fig. 16, which are first actuated, correspond to a mode 1-1 in Fig. 19. In this mode, the transistors 33 and 35 are scheduled to be instantaneously turned on. After T_1 , in a mode 1-2, the transistors 33 and 32 are scheduled to be turned off and turned on, respectively. In the mode 1-1, the turn-off/on time T_1 relative to the value of γ^* can be
 50 decided only by referring to the Table 1, but in the mode 1-2, the turn-off/on time T_2 must be decided by referring to both tables of Tables 1 and 2. Further, if the value of γ^* is comparatively large as in the present example, an inconvenience occurs in modes 1-3, 1-10, etc. More specifically, in the modes 1-3 and 1-10, in some cases, the pulse switching time (i.e. time elapsed until when the modes 1-3 and 1-10 are shifted to the succeeding modes 1-4 and 1-11, respectively) is so short that a sufficient time cannot be obtained to
 55 perform the settings of the schedule of the turn-off/on, of the self-interruption, etc. in the associative memory. Such a phenomenon, if the value of γ^* is small, will occur in the modes of 1-1, 1-3, 1-4, 1-6, 1-7, 1-9, 1-10, 1-12, etc.

In order to overcome such a phenomenon, this embodiment provides in the pulse switching processing F6000 a processing of setting plural turn-off/on schedules in the associative memory, referring to the value of γ^* , during the same timer interruption interval. One example thereof is shown in Fig. 20. First, checking is made on if or not the value of γ^* is small in F6050. If it is small, a judgement that the time of the succeeding mode, i.e. the mode 1-3 is short is made, and the turn-off/on processing to be performed during the succeeding mode 1-3 is completed within the mode 1-2. Therefore, the mode to be executed subsequently to the mode 1-2 is the mode 1-4 so that the jumping destination is set to the mode 1-4 in F6090. The self-interruption is set not after T_2 but after $(T_2 + T_3)$ in F6100, and a next interruption is awaited. On the other hand, if the mode 1-3 is executable since the γ^* is sufficiently large, the processing is performed in the sequence of F6060 and F6070, and the mode jumping is not made.

The aforesaid processing of setting plural turn-off/on schedules in the same timer interruption interval permits the generation of a pulse having so short a pulse width that cannot be generated in the normal interruption processing, thereby extending the possibility of a harmonics reducing control.

In the above explanation, the aforesaid processing have been adapted to the flow from the mode 1-2 to the modes 1-3 and 1-4 but may be also adapted to the other flows relative to the mode having a narrow width.

Further, in relation to the execution controller, a system of individually setting an event to each port has been explained. However, the one-chip microcomputer which can simultaneously set the events to all six ports permits the processing of Fig. 9 to be simplified as shown in Fig. 21. In this case, the number of the microcomputer instructions can be reduced from 16 to 4.

This embodiment provides the following meritorious effects.

1) Since the control system can be directly connected with the I/O port incorporated in one chip or connected with a power converter through a pulse amplifier, its circuit construction is simplified and is highly reliable.

2) The minimum pulse width is not influenced by an interruption processing time (e.g. 90 μ sec) so that it can be reduced to 2 μ sec or so, thus permitting harmonics to be reduced.

3) The pulse patterns are entirely created within one-chip microcomputer and thereafter output so that the abnormality of the patterns is equivalent to that of the chip. The abnormality of the chip can be checked through the self-diagnosis function of the microcomputer (e.g. watch dog timer) so that the entire pulse pattern generator is in a supervisor state, thus making the generator highly reliable.

4) The change of pulse patterns (events) is performed using an internal timer and it can always be scheduled by an output control section including an associative memory. Thus, the ALU section has only to set the events and timings in the registers and is released from the output processing, thus implementing a division system which is capable of executing the user's program during the output processing.

5) The event and timing to be output from the same port can be set many times within the same timer interruption interval so far as the number of storage registers permits. Therefore, the chopping frequency of an inverter or converter can be apparently increased. This permits a power converter for a high frequency and with less ripple to be implement.

Accordingly, in accordance with this invention, the pulse generation in a power converter can be scheduled by a one-chip microcomputer. This permits a low harmonic, high reliability power converter system to be constructed with low cost, and so permits an elevator to be controlled so that it can be operated with sufficiently low noise and low torque ripple.

Claims

1. A method for controlling a power converter in which control signals for operating power converter switching elements are created by a control unit including a microcomputer, comprising the steps of:

setting pulse patterns containing turn-on or turn-off information of the switching elements and containing generating timing information of the turn-on or turn-off events dependent on input signals (ω_1^* , θ^*),

storing in sequence said turn-on or turn-off information in an associative memory in pairs with their corresponding generating timing information in response to a timer interruption signal to said microcomputer,

comparing (112) said generating timings (111) of the events with actual times of a timer independent of said timer interruption signal, and when coincidences between said generating timings and said actual times are obtained, reading out said turn-on or turn-off information corresponding to said generating timings from said memory to successively supply control signals corresponding to the turn-

In order to overcome such a phenomenon, this embodiment provides in the pulse switching processing F6000 a processing of setting plural turn-off/on schedules in the associative memory, referring to the value of γ^* , during the same timer interruption interval. One example thereof is shown in Fig. 20. First, checking is made on if or not the value of γ^* is small in F6050. If it is small, a judgement that the time of the succeeding mode, i.e. the mode 1-3 is short is made, and the turn-off/on processing to be performed during the succeeding mode 1-3 is completed within the mode 1-2. Therefore, the mode to be executed subsequently to the mode 1-2 is the mode 1-4 so that the jumping destination is set to the mode 1-4 in F6090. The self-interruption is set not after T_2 but after $(T_2 + T_3)$ in F6100, and a next interruption is awaited. On the other hand, if the mode 1-3 is executable since the γ^* is sufficiently large, the processing is performed in the sequence of F6060 and F6070, and the mode jumping is not made.

The aforesaid processing of setting plural turn-off/on schedules in the same timer interruption interval permits the generation of a pulse having so short a pulse width that cannot be generated in the normal interruption processing, thereby extending the possibility of a harmonics reducing control.

In the above explanation, the aforesaid processing have been adapted to the flow from the mode 1-2 to the modes 1-3 and 1-4 but may be also adapted to the other flows relative to the mode having a narrow width.

Further, in relation to the execution controller, a system of individually setting an event to each port has been explained. However, the one-chip microcomputer which can simultaneously set the events to all six ports permits the processing of Fig. 9 to be simplified as shown in Fig. 21. In this case, the number of the microcomputer instructions can be reduced from 16 to 4.

This embodiment provides the following meritorious effects.

1) Since the control system can be directly connected with the I/O port incorporated in one chip or connected with a power converter through a pulse amplifier, its circuit construction is simplified and is highly reliable.

2) The minimum pulse width is not influenced by an interruption processing time (e.g. 90 μ sec) so that it can be reduced to 2 μ sec or so, thus permitting harmonics to be reduced.

3) The pulse patterns are entirely created within one-chip microcomputer and thereafter output so that the abnormality of the patterns is equivalent to that of the chip. The abnormality of the chip can be checked through the self-diagnosis function of the microcomputer (e.g. watch dog timer) so that the entire pulse pattern generator is in a supervisor state, thus making the generator highly reliable.

4) The change of pulse patterns (events) is performed using an internal timer and it can always be scheduled by an output control section including an associative memory. Thus, the ALU section has only to set the events and timings in the registers and is released from the output processing, thus implementing a division system which is capable of executing the user's program during the output processing.

5) The event and timing to be output from the same port can be set many times within the same timer interruption interval so far as the number of storage registers permits. Therefore, the chopping frequency of an inverter or converter can be apparently increased. This permits a power converter for a high frequency and with less ripple to be implemented.

Accordingly, in accordance with this invention, the pulse generation in a power converter can be scheduled by a one-chip microcomputer. This permits a low harmonic, high reliability power converter system to be constructed with low cost, and so permits an elevator to be controlled so that it can be operated with sufficiently low noise and low torque ripple.

Claims

1. A method for controlling a power converter in which control signals for operating power converter switching elements are created by a control unit including a microcomputer, comprising the steps of:

setting pulse patterns containing turn-on or turn-off information of the switching elements and containing generating timing information of the turn-on or turn-off events dependent on input signals (ω_1^* , θ^*),

storing in sequence said turn-on or turn-off information in an associative memory in pairs with their corresponding generating timing information in response to a timer interruption signal to said microcomputer,

comparing (112) said generating timings (111) of the events with actual times of a timer independent of said timer interruption signal, and when coincidences between said generating timings and said actual times are obtained, reading out said turn-on or turn-off information corresponding to said generating timings from said memory to successively supply control signals corresponding to the turn-



on or turn-off information to said switching elements.

2. A method according to claim 1, wherein in said storing step said pair of information is stored at least one time for each predetermined time interval.
- 5 3. A method according to claim 2, wherein in said storing step said pair of information is stored a plurality of times for each said predetermined time interval.
- 10 4. A method according to claim 2, wherein said predetermined time interval is initiated synchronously with a timer interruption.
5. A method according to claim 2, wherein said predetermined time interval is a variable time interval.
- 15 6. A method according to claim 1, wherein said power converter includes a plurality of elements, and wherein in said storing step said pair of information is stored in connection with each of said elements.
7. A method according to claim 1, wherein in said storing step said pair of information is stored so that a width of a pulse representing a period of turn on or turn off of said at least one element is minimized.
- 20 8. A method according to claim 1, wherein said storing and calculating steps are executed every predetermined time interval, respectively.
9. A method according to claim 8, wherein said predetermined time interval in said storing step is initiated by one timer interruption, and said predetermined time interval in said calculation step is initiated by another timer interruption occurring prior to said one timer interruption.
- 25 10. An apparatus for controlling a power converter according to claim 1 provided with power converter switching elements (51-56, 31-36) in which at least one control signal created by a microcomputer (10, 11) is applied to the power converter (5, 3) to operate the power converter, characterized by:
 - 30 means (107, 108) for setting pulse patterns consisting of pairs of information including an event information for turning on or off at least one element (51-56, 31-36) and a timing information relating to a time for enabling said event information independent of a prior turn-on or turn-off of said at least one element dependent on input signals (ω , θ),
 - associative memory means (110) for storing said pulse patterns in response to the timer interrupt signal,
 - 35 a timer (111) for outputting a time,
 - means (112) for comparing the time of said timer (111) with said time information in said memory means (110), and
 - means (113) for applying a control signal according to said event information for turning on or turning off said at least one element of said power converter when the time of said timer is coincident with said time of said time information.
 - 40
11. An apparatus according to claim 10, wherein said power converter (3) is an A.C.-D.C. converter.
- 45 12. An apparatus according to claim 11, further comprising means for executing an interruption in synchronism with an A.C. side input power supply.
13. An apparatus according to claim 10, wherein said power converter (5) is a D.C.-A.C. converter.
- 50 14. An apparatus according to claim 13, wherein said D.C.-A.C. converter is a current type converter.
15. An apparatus according to claim 14, further comprising means for calculating a total phase by adding an integrated value of a frequency instruction and a phase instruction and calculating said pair of information in connection with each of said at least one element constituting said power converter in accordance with a peak value of at least two phase voltages of a polyphase A.C.
- 55 16. An apparatus according to claim 15, further comprising means for dividing an electrical angle of 360° into a plurality of modes to enable calculation for each of said modes.



17. An apparatus according to claim 10, wherein said memory means (110) stores said pair of information so that a width of a pulse representing a period of turn on or turn off of said at least one element is minimized.

5 18. An apparatus according to claim 10, further comprising means for calculating said pair of information in connection with said at least one element.

19. An apparatus according to claim 18, wherein said means for calculating enables calculation of said pair of information in accordance with at least one of a frequency instruction, phase instruction, and a
10 voltage.

20. An apparatus according to claim 10, further comprising motor means (7) coupled to an output of said power converter (5).

15 21. An apparatus according to claim 20, further comprising an elevator coupled to said motor means (7) for being driven thereby.

22. An apparatus according to claim 20, wherein said motor means (7) includes an induction motor.

20 Patentansprüche

1. Verfahren zur Regelung eines Leistungswandlers, in dem Regelsignale zur Betätigung von Leistungswandel-Schaltelementen durch eine einen Mikrocomputer umfassende Regeleinheit geschaffen werden, umfassend die Schritte

25 Festlegen von Impuls-Mustern, die Anschalt- und Anschaltinformationen der Schaltelemente und Erzeugungszeitpunktinformationen der An- und Abschaltereignisse abhängig von Eingangssignalen (ω_i, θ_i) enthalten,

Sequentielles Speichern der An- und Anschaltinformationen in einem Assoziativspeicher paarweise zusammen mit der zugehörigen Erzeugungszeitpunktinformation in Antwort auf ein Zeitgeber-Unterbrechungssignal an den Mikrocomputer,

30 Vergleichen (112) der Erzeugungszeitpunkte (111) der Ereignisse mit tatsächlichen Zeiten eines Zeitgebers unabhängig vom Zeitgeber-Unterbrechungssignal und, wenn Übereinstimmung zwischen den erzeugten Zeitpunkten und den tatsächlichen Zeiten gegeben ist, Auslesen der An- und Ausschaltinformation, die den Erzeugungszeiten entsprechen, aus dem Speicher, um nacheinander den An- und
35 Anschaltinformationen entsprechende Steuersignale an die Schaltelemente zu liefern.

2. Verfahren nach Anspruch 1, wobei im Speicherschnitt das Informationspaar zumindest einmal für jedes vorgegebene Zeitintervall gespeichert wird.

40 3. Verfahren nach Anspruch 2, wobei im Speicherschnitt das Informationspaar mehrmals für jedes vorgegebene Zeitintervall gespeichert wird.

4. Verfahren nach Anspruch 2, wobei das vorgegebene Zeitintervall synchron mit einer Zeitgeber-Unterbrechung initiiert wird.

45 5. Verfahren nach Anspruch 2, wobei das vorgegebene Zeitintervall ein veränderliches Zeitintervall ist.

6. Verfahren nach Anspruch 1, wobei der Leistungswandler mehrere Elemente umfaßt, und wobei im Speicherschnitt das Informationspaar im Zusammenhang mit jedem der Elemente gespeichert wird.

50 7. Verfahren nach Anspruch 1, wobei im Speicherschnitt das Informationspaar derartig gespeichert wird, daß eine Impulsbreite, welche die Dauer der An- oder Anschaltung des zumindest einen Elements darstellt, minimiert wird.

55 8. Verfahren nach Anspruch 2, wobei der Speicher- und Berechnungsschritt jeweils in jedem vorgegebenen Zeitintervall ausgeführt wird.



9. Verfahren nach Anspruch 8, wobei das vorgegebene Zeitintervall im Speicherschritt von einer Zeitgeber-Unterbrechung initiiert wird und das vorgegebene Zeitintervall im Berechnungsschritt von einer anderen Zeitgeber-Unterbrechung initiiert wird, die vor der besagten Zeitgeber-Unterbrechung auftritt.
10. Vorrichtung zur Regelung eines Leistungswandlers gemäß Anspruch 1, der mit Leistungswandler-Schaltelementen (51-56, 31-36) versehen ist, wobei zumindest ein von einem Mikroprozessor (10, 11) erzeugtes Regelsignal dem Leistungswandler (5, 3) zu dessen Betrieb zugeführt wird, gekennzeichnet durch
- Einrichtungen (107, 108) zum Setzen von Impulsmustern, die aus Informationspaaren bestehen, welche eine Ereignisinformation zum Anschalten oder Abschalten zumindest eines Elements (51-56, 31-36) und eine Zeitinformation, die sich auf eine Zeit zur Aktivierung der Ereignisinformation unabhängig von einem vorherigen An- oder Abschalten des zumindest einen Elements abhängig von Eingangssignalen (ω, θ) ermöglicht,
- eine Assoziativspeichereinrichtung (110) zur Speicherung der Impulsmuster in Antwort auf das Zeitgeber-Unterbrechungssignal,
- ein Zeitgeber (111) zur Ausgabe einer Zeit,
- eine Einrichtung (112) zum Vergleich der Zeit des Zeitgebers (111) mit der Zeitinformation in der Speichereinrichtung (110), und
- eine Einrichtung (113) zur Anwendung eines Steuersignals gemäß der Ereignisinformation zum An- oder Abschalten des zumindest einen Elements des Leistungswandlers, wenn die Zeit des Zeitgebers mit der Zeit der Zeitinformation übereinstimmt.
11. Vorrichtung nach Anspruch 10, wobei der Leistungswandler (3) ein Wechselstrom/Gleichstrom-Wandler ist.
12. Vorrichtung nach Anspruch 11, die weiterhin eine Einrichtung zur Ausführung einer Unterbrechung synchron mit einer wechselstromseitigen Eingangsstromversorgung umfaßt.
13. Vorrichtung nach Anspruch 10, wobei der Leistungswandler (5) ein Gleichstrom/Wechselstrom-Wandler ist.
14. Vorrichtung nach Anspruch 13, wobei der Gleichstrom/Wechselstrom-Wandler ein Wandler des Strom-Typs ist.
15. Vorrichtung nach Anspruch 14, die ferner eine Einrichtung umfaßt zur Berechnung der Gesamtphase durch Addition eines integrierten Wertes einer Frequenzanweisung und einer Phasenangabe und zur Berechnung des Informationspaares in Verbindung mit jedem des zumindest einen den Leistungswandler bildenden Elements gemäß einem Spitzenwert von zumindest zwei Phasenspannungen eines mehrphasigen Wechselstroms.
16. Vorrichtung nach Anspruch 15, der ferner eine Einrichtung zum Teilen eines elektrischen Winkels von 360° in mehrere Betriebsarten umfaßt, um eine Berechnung für jede der Betriebsarten zu ermöglichen.
17. Vorrichtung nach Anspruch 10, wobei die Speichereinrichtung (110) die Informationspaare derartig speichert, daß eine Impulsweite, die eine An- oder Abschaltdauer des zumindest einen Elements repräsentiert, minimal ist.
18. Vorrichtung nach Anspruch 10, die ferner eine Einrichtung zur Berechnung des Informationspaares in Verbindung mit dem zumindest einen Element umfaßt.
19. Vorrichtung nach Anspruch 18, wobei die Berechnungseinrichtung die Berechnung eines Informationspaares in Übereinstimmung mit einer Frequenzangabe, einer Phasenangabe und/oder einer Spannung berechnet.
20. Vorrichtung nach Anspruch 10, ferner umfassend eine Motoreinrichtung (7), die mit einem Ausgang des Leistungswandlers (5) verbunden ist.



21. Vorrichtung nach Anspruch 20, ferner umfassend einen Aufzug, der mit der Motoreinrichtung (7) zum Antrieb desselben gekoppelt ist.

22. Vorrichtung nach Anspruch 20, wobei die Motoreinrichtung (7) einen Induktionsmotor umfaßt.

5

Revendications

1. Procédé pour commander un convertisseur de puissance, selon lequel des signaux de commande servant à faire fonctionner les éléments de commutation du convertisseur de puissance sont créés par une unité de commande comportant un micro-ordinateur, comprenant les étapes consistant à :
 régler des profils d'impulsions contenant une information d'ouverture ou de fermeture des éléments de commutation et contenant une information de séquence de production des événements de fermeture ou d'ouverture en fonction de signaux d'entrée (ω , θ),
 mémoriser successivement ladite information d'ouverture ou de fermeture dans une mémoire associative, selon des couples, avec l'information de séquence de production qui leur correspond, en réponse à un signal d'interruption de minuterie envoyé audit micro-ordinateur,
 comparer (112) lesdites séquences de production (111) des événements à des durées réelles d'une minuterie indépendamment dudit signal d'interruption de minuterie, et, lorsque des coïncidences sont obtenues entre lesdites séquences de production et lesdites durées réelles, lire ladite information d'ouverture ou de fermeture correspondant auxdites séquences de production à partir de ladite mémoire pour envoyer successivement des signaux de commande correspondant à l'information de fermeture ou d'ouverture, auxdits éléments de commutation.
2. Procédé selon la revendication 1, selon lequel lors de ladite étape de mémorisation, ledit couple d'informations est mémorisé au moins une fois pendant chaque intervalle de temps prédéterminé.
3. Procédé selon la revendication 2, selon lequel lors de ladite étape de mémorisation, ledit couple d'informations est mémorisé une pluralité de fois pendant chaque intervalle de temps prédéterminé.
4. Procédé selon la revendication 2, selon lequel ledit intervalle de temps prédéterminé est déclenché en synchronisme avec une interruption de la minuterie.
5. Procédé selon la revendication 2, selon lequel ledit intervalle de temps prédéterminé est un intervalle de temps variable.
6. Procédé selon la revendication 1, selon lequel ledit convertisseur de puissance comprend une pluralité d'éléments, et dans lequel, pendant ladite étape de mémorisation, ledit couple d'informations est mémorisé en liaison avec chacun desdits éléments.
7. Procédé selon la revendication 1, selon lequel, lors de ladite étape de mémorisation, ledit couple d'informations est mémorisé de telle sorte qu'une durée d'une impulsion représentant une période de fermeture ou d'ouverture d'au moins un élément est réduite au minimum.
8. Procédé selon la revendication 1, selon lequel lesdites étapes de mémorisation et de calcul sont exécutées respectivement pendant chaque intervalle de temps prédéterminé.
9. Procédé selon la revendication 8, selon lequel ledit intervalle de temps prédéterminé pendant ladite étape de mémorisation est déclenché par une première interruption de la minuterie, et que ledit intervalle de temps prédéterminé lors de ladite étape de calcul est déclenché par une autre interruption de la minuterie, qui intervient avant ladite première interruption de la minuterie.
10. Dispositif pour commander un convertisseur de puissance selon la revendication 1, équipé d'éléments de commutation (51-56, 31-36), dans lequel au moins un signal de commande créé par un micro-ordinateur (10, 11) est appliqué au convertisseur de puissance (5, 3) de manière à faire fonctionner ce dernier, caractérisé par :
 des moyens (107, 108) pour régler des profils d'impulsions constitués par des couples d'informations incluant une information d'événements pour l'ouverture ou la fermeture d'au moins un élément (51-56, 31-36) et une information de séquence associée à une durée pour valider ladite information



- d'évènement indépendamment d'une fermeture ou d'une ouverture antérieure dudit élément en fonction de signaux d'entrée (ω^* , θ^*),
 des moyens de mémoire associatifs (110) pour mémoriser lesdits profils d'impulsions en réponse au signal d'interruption de la minuterie,
 5 une minuterie (111) servant à délivrer une durée,
 des moyens (112) pour comparer la durée de ladite minuterie (111) à ladite information de temps présente dans lesdits moyens de mémoire (110), et
 des moyens (113) pour appliquer un signal de commande en fonction de ladite information d'évènement pour fermer ou ouvrir ledit au moins un élément dudit convertisseur de puissance, lorsque
 10 la durée de ladite minuterie coïncide avec ladite durée de ladite information de temps.
11. Dispositif selon la revendication 10, dans lequel ledit convertisseur de puissance (3) est un convertisseur alternatif-continu.
- 15 12. Dispositif selon la revendication 11, comportant en outre des moyens pour exécuter une interruption en synchronisme avec une alimentation en énergie d'entrée sur le côté courant alternatif.
13. Dispositif selon la revendication 10, dans lequel ledit convertisseur de puissance (5) est un convertisseur continu-alternatif.
- 20 14. Dispositif selon la revendication 13, dans lequel ledit convertisseur continu-alternatif est un convertisseur de type de courant.
15. Dispositif selon la revendication 14, comprenant en outre des moyens pour calculer une phase totale par addition d'une valeur intégrée d'une instruction de fréquence et d'une instruction de phase et pour calculer ledit couple d'informations en liaison avec chacun desdits éléments constituant ledit convertisseur de puissance en fonction d'une valeur maximale d'au moins deux tensions de phase d'un courant alternatif polyphasé.
- 25 16. Dispositif selon la revendication 15, comportant en outre des moyens pour diviser un angle électrique de 360° en une pluralité de modes pour permettre le calcul pour chacun desdits modes.
17. Dispositif selon la revendication 10, dans lequel lesdits moyens de mémoire (110) mémorisent ledit couple d'informations de sorte qu'une durée d'une impulsion représentant une période d'ouverture ou de fermeture dudit au moins un élément est réduite au minimum.
- 35 18. Dispositif selon la revendication 10, comprenant en outre des moyens pour calculer ledit couple d'informations en liaison avec ledit élément.
19. Dispositif selon la revendication 18, dans lequel lesdits moyens de calcul permettent le calcul dudit couple d'informations en fonction d'au moins une instruction de fréquence, une instruction de phase et une tension.
- 40 20. Dispositif selon la revendication 10, comportant en outre des moyens en forme de moteur (7) couplés à une sortie dudit convertisseur de puissance (5).
21. Dispositif selon la revendication 20, comportant en outre un élévateur accouplé auxdits moyens en forme de moteur (7) pour être entraîné par ces moyens.
- 50 22. Dispositif selon la revendication 20, dans lequel lesdits moyens en forme de moteur (7) comprennent un moteur à induction.

