

METHOD AND SERVER FOR SEARCHING FOR DATA STREAM DIVIDING POINT BASED ON SERVER

TECHNICAL FIELD

[0001] The present invention relates to the field of information technologies, and in particular,
5 to a method and a server for searching for a data stream dividing point based on a server.

BACKGROUND

[0002] As data amounts keep growing, it becomes a critical challenge to provide sufficient data
storage in the storage field currently. At present, a manner of addressing such a challenge is using a
deduplication technology by means of a redundancy feature of data that needs to be stored, so as to
10 reduce an amount of stored data.

[0003] In an algorithm of eliminating duplicate data based on a content defined chunk (Content
Defined Chunk, CDC) in the prior art, a data stream to be stored is first divided into multiple data
chunks. To divide a data stream into data chunks, a suitable dividing point needs to be found in the
data stream, and data between two adjacent dividing points in the data stream forms one data chunk.
15 A feature value of a data chunk is calculated, so as to find whether data chunks having a same
feature value exist. If the data chunks having a same feature value are found, it is regarded that
duplicate data exists. Specifically, in a technology of eliminating duplicate data based on a content
defined chunk, a sliding window technique (Sliding Window Technique) is applied to search for a
dividing point of a chunk based on content of a file, that is, a Rabin fingerprint of data in a window
20 is calculated to determine a data stream dividing point. It is assumed that a dividing point is
searched for from left to right in a data stream. A fingerprint of data in a sliding window is
calculated each time, and after a modulo operation is performed on a fingerprint value based on a
given integer K, a result of the modulo operation is compared with a given remainder R. If the
result of the modulo operation equals the given remainder R, the right end of the window is a data
25 stream dividing point. Otherwise, the window continues to be slid rightward by one byte, and
calculation and comparison are performed sequentially and cyclically until the end of the data
stream is reached. In a process of eliminating duplicate data based on a content defined chunk, a
large quantity of computing resources need to be consumed to search for a data stream dividing
point, which therefore becomes a bottleneck in improving performance of eliminating duplicate

data.

SUMMARY

[0004] According to a first aspect, an embodiment of the present invention provides a method for searching for a data stream dividing point based on a server, where a rule is preset on the server, where the rule is: for a potential dividing point k , determining M points p_x , a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to M , $M \geq 2$, and A_x and B_x are integers; and the method includes:

(a) determining a point p_{iz} and a window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point p_{iz} for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ; and

when the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point from the point p_{iz} along a direction of searching for a data stream dividing point, where $N \cdot U$ is not greater than $\|B_z\| + \max_x(\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix}[p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

[0005] With reference to the first aspect, in a first possible implementation manner, the rule further includes that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

[0006] With reference to the first possible implementation manner of the first aspect, in a second possible implementation manner, the rule further includes: relative to the potential dividing point k , the at least two points p_e and p_f are in a direction opposite to the direction of searching for a data stream dividing point.

[0007] With reference to the first possible implementation manner or the second possible implementation manner of the first aspect, in a third possible implementation manner, the rule further includes that a distance between the at least two points p_e and p_f is 1 U.

[0008] With reference to the first aspect, or any one of the first to third possible implementation manners of the first aspect, in a fourth possible implementation manner, the determining whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z specifically includes:

determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0009] With reference to the fourth possible implementation manner of the first aspect, in a fifth possible implementation manner, the determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z is specifically: determining, by using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0010] With reference to the first aspect, or any one of the first to fifth possible implementation manners of the first aspect, in a sixth possible implementation manner, when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, where the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

[0011] With reference to the fourth possible implementation manner of the first aspect, in a seventh possible implementation manner, the determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes,

bits corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}, \text{ where}$$

5 when $a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix},$$
 F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

10
$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \dots & h_{F*H,8} \end{pmatrix},$$
 random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF*H} are obtained in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$

15 meets the preset condition C_z .

[0012] According to a second aspect, an embodiment of the present invention provides a method for searching for a data stream dividing point based on a server, where a rule is preset on the server, where the rule is: for a potential dividing point k , determining M windows $W_x [k - A_x, k + B_x]$, and a preset condition C_x corresponding to the window $W_x [k - A_x, k + B_x]$, where x

20 indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers; and

the method includes:

(a) determining a corresponding window $W_{iz} [k_i - A_z, k_i + B_z]$ for a current potential

dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets a preset condition C_z ; and

when the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along a direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x(\|A_x\|)$, so as to obtain a new potential dividing point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix}[k_i - A_x, k_i + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

[0013] With reference to the second aspect, in a first possible implementation manner, the rule further includes that at least two windows $W_{ie}[k_i - A_e, k_i + B_e]$ and $W_{if}[k_i - A_f, k_i + B_f]$ meet conditions $|A_e + B_e| = |A_f + B_f|$ and $C_e = C_f$.

[0014] With reference to the first possible implementation manner of the second aspect, in a second possible implementation manner, the rule further includes that A_e and A_f are positive integers.

[0015] With reference to the first possible implementation manner or the second possible implementation manner of the second aspect, in a third possible implementation manner, the rule further includes $A_e - 1 = A_f$ and $B_e + 1 = B_f$.

[0016] With reference to the second aspect, or any one of the first to third possible implementation manners of the second aspect, in a fourth possible implementation manner, the determining whether at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

determining, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0017] With reference to the fourth possible implementation manner of the second aspect, in a fifth possible implementation manner, the determining, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z is

specifically: determining, by using a hash function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0018] With reference to the second aspect, or any one of the first to fifth possible implementation manners of the second aspect, in a sixth possible implementation manner, when the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the current potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [k_i - A_z, k_i + B_z]$ or a left boundary of a window $W_{ic} [k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point falls within a range of the window $W_{iz} [k_i - A_z, k_i + B_z]$, where the window $W_{ic} [k_i - A_c, k_i + B_c]$ determined for the new potential dividing point is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M windows that are determined for the new potential dividing point according to the rule.

[0019] With reference to the fourth possible implementation manner of the second aspect, in a seventh possible implementation manner, the determining, by using a random function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [k_i - A_z, k_i + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits

corresponding to the F*H bytes can be represented as:

$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}, \text{ where when}$$

$a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \cdots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \cdots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \cdots & V_{aF*H,8} \end{pmatrix}$, $F*H*8$ random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \cdots & h_{F*H,8} \end{pmatrix}$, random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically

5 represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF*H} are obtained

in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF*H} is counted,

and when K is an even number, the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0020] According to a third aspect, an embodiment of the present invention provides a server

10 for searching for a data stream dividing point, where the server includes a central processing unit and a main memory, the central processing unit communicates with the main memory, and a rule is preset on the server, where the rule is: for a potential dividing point k , determining M points p_x ,

a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where x indicates consecutive natural

15 numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers; and

the main memory is configured to store an executable instruction, and the central processing unit executes the executable instruction to perform the following steps:

(a) determining a point p_{iz} and a window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point p_{iz} for a current potential dividing point k_i according to the rule, where i and z are integers,

20 and $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ; and

when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point

25 from the point p_{iz} along a direction of searching for a data stream dividing point, where $N*U$ is

not greater than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix}[p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

[0021] With reference to the third aspect, in a first possible implementation manner, the rule further includes that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

[0022] With reference to the first possible implementation manner of the third aspect, in a second possible implementation manner, the rule further includes: relative to the potential dividing point k , the at least two points p_e and p_f , are in a direction opposite to the direction of searching for a data stream dividing point.

[0023] With reference to the first possible implementation manner or the second possible implementation manner of the third aspect, in a third possible implementation manner, the rule further includes that a distance between the at least two points p_e and p_f is 1 U.

[0024] With reference to the third aspect, or any one of the first to third possible implementation manners, in a fourth possible implementation manner, the central processing unit is specifically configured to:

determine, by using a random function, whether the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0025] With reference to the fourth possible implementation manner of the third aspect, in a fifth possible implementation manner, the central processing unit is specifically configured to determine, by using a hash function, whether the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0026] With reference to the third aspect, or any one of the first to fifth possible implementation manners, in a sixth possible implementation manner, when the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic}[p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point

p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, where the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

[0027] With reference to the fourth possible implementation manner of the third aspect, in a seventh possible implementation manner, the determining, by the central processing unit by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes,

bits corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}, \text{ where}$$

when $a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix},$$
 F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \dots & h_{F*H,8} \end{pmatrix},$$
 random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF*H} are obtained

in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

According to a fourth aspect, an embodiment of the present invention provides a server
 5 for searching for a data stream dividing point, where the server includes a central processing unit and a primary memory, the central processing unit communicates with the primary memory, and a rule is preset on the server, where the rule is: for a potential dividing point k , determining M windows $W_x [k - A_x, k + B_x]$ and a preset condition C_x corresponding to the window $W_x [k - A_x, k + B_x]$, where x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x
 10 are integers; and

the main memory is configured to store an executable instruction, and the central processing unit executes the executable instruction to perform the following steps:

- (a) determining a corresponding window $W_{iz} [k_i - A_z, k_i + B_z]$ for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$;
- 15 (b) determining whether at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets a preset condition C_z ; and

when the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along a direction of searching for a data stream
 20 dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x (\|A_x\|)$, so as to obtain a new potential dividing point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix} [k_i - A_x, k_i + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

25 **[0028]** With reference to the fourth aspect, in a first possible implementation manner, the rule further includes that at least two windows $W_{ie} [k_i - A_e, k_i + B_e]$ and $W_{if} [k_i - A_f, k_i + B_f]$ meet conditions $|A_e + B_e| = |A_f + B_f|$ and $C_e = C_f$.

[0029] With reference to the first possible implementation manner of the fourth aspect, in a second possible implementation manner, the rule further includes that A_e and A_f are positive
 30 integers.

[0030] With reference to the first possible implementation manner or the second possible implementation manner of the fourth aspect, in a third possible implementation manner, the rule further includes $A_e - 1 = A_f$ and $B_e + 1 = B_f$.

[0031] With reference to the fourth aspect, or any one of the first to third possible implementation manners, in a fourth possible implementation manner, the central processing unit is specifically configured to:

determine, by using a random function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0032] With reference to the fourth possible implementation manner of the fourth aspect, in a fifth possible implementation manner, the central processing unit is specifically configured to determine, by using a hash function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0033] With reference to the fourth aspect, or any one of the first to fifth possible implementation manners, in a sixth possible implementation manner, when the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the current potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [k_i - A_z, k_i + B_z]$ or a left boundary of a window $W_{ic} [k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point falls within a range of the window $W_{iz} [k_i - A_z, k_i + B_z]$, where the window $W_{ic} [k_i - A_c, k_i + B_c]$ determined for the new potential dividing point is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M windows that are determined for the new potential dividing point according to the rule.

[0034] With reference to the fourth possible implementation manner of the fourth aspect, in a seventh possible implementation manner, the determining, by the central processing unit by using a random function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [k_i - A_z, k_i + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as

$a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits

corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F^*H,1} & a_{F^*H,2} & \dots & a_{F^*H,8} \end{pmatrix}$$
, where when

$a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$

5 from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF^*H,1} & V_{aF^*H,2} & \dots & V_{aF^*H,8} \end{pmatrix}$$
, F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F^*H,1} & h_{F^*H,2} & \dots & h_{F^*H,8} \end{pmatrix}$$
, random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically

10 represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF^*H} are obtained

in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF^*H} is counted,

and when K is an even number, the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0035] According to a fifth aspect, an embodiment of the present invention provides a server for

15 searching for a data stream dividing point, where a rule is preset on the server, where the rule is: for

a potential dividing point k , determining M points p_x , a window $W_x [p_x - A_x, p_x + B_x]$

corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x -$

$A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x

are integers; and

20 the server includes: a determining unit, configured to perform step (a):

(a) determining a point p_{iz} and a window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the

point p_{iz} for a current potential dividing point k_i according to the rule, where i and z are integers,

and $1 \leq z \leq M$; and

a judging and processing unit, configured to: determine whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ;

when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skip N minimum units U for searching for a data stream dividing point from the point p_{iz} along a direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, where the determining unit performs step (a) for the new potential dividing point; and

when at least a part of data in each window $W_{ix} [p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , select the current potential dividing point k_i as a data stream dividing point.

[0036] With reference to the fifth aspect, in a first possible implementation manner, the rule further includes that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

[0037] With reference to the first possible implementation manner of the fifth aspect, in a second possible implementation manner, the rule further includes: relative to the potential dividing point k , the at least two points p_e and p_f are in a direction opposite to the direction of searching for a data stream dividing point.

[0038] With reference to the first possible implementation manner or the second possible implementation manner of the fifth aspect, in a third possible implementation manner, the rule further includes that a distance between the at least two points p_e and p_f is 1 U.

[0039] With reference to the fifth aspect, or any one of the first to third possible implementation manners, in a fourth possible implementation manner, the judging and processing unit specifically determines, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0040] With reference to the fourth possible implementation manner of the fifth aspect, in a fifth possible implementation manner, the judging and processing unit is specifically configured to determine, by using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0041] With reference to the fifth aspect, or any one of the first to fifth possible implementation manners, in a sixth possible implementation manner, the judging and processing unit is configured

to: when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skip the N minimum units U for searching for a data stream dividing point from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, where the determining unit performs step (a) for the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, where the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

[0042] With reference to the fourth possible implementation manner of the fifth aspect, in a seventh possible implementation manner, that the judging processing unit is specifically configured to determine, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes,

bits corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}, \text{ where}$$

when $a_{m,n} = 1$, $V_{am,n} = 1$, and when $a_{m,n} = 0$, $V_{am,n} = -1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix},$$
 F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F^*H,1} & h_{F^*H,2} & \dots & h_{F^*H,8} \end{pmatrix}, \text{ random numbers in an } m\text{th row of the matrix } V_a \text{ and an } m\text{th row of}$$

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF^*H} are obtained

in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF^*H} is counted,

5 and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0043] According to a sixth aspect, an embodiment of the present invention provides a server for searching for a data stream dividing point, where a rule is preset on the server, where the rule is: for a potential dividing point k , determining M windows $W_x [k - A_x, k + B_x]$ and a preset
10 condition C_x corresponding to the window $W_x [k - A_x, k + B_x]$, where x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers; and

the server includes: a determining unit, configured to perform step (a):

(a) determining a corresponding window $W_{iz} [k_i - A_z, k_i + B_z]$ for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$; and

15 a judging and processing unit, configured to determine whether at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets a preset condition C_z ;

when the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skip N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along a direction of searching for a data stream dividing
20 point, where $N * U$ is not greater than $\|B_z\| + \max_x (\|A_x\|)$, so as to obtain a new potential dividing point, and perform step (a); and

when at least a part of data in each window $W_{ix} [k_i - A_x, k_i + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , select the current potential dividing point k_i as a data stream dividing point.

25 **[0044]** With reference to the sixth aspect, in a first possible implementation manner, the rule further includes that at least two windows $W_{ie} [k_i - A_e, k_i + B_e]$ and $W_{if} [k_i - A_f, k_i + B_f]$ meet conditions $|A_e + B_e| = |A_f + B_f|$ and $C_e = C_f$.

[0045] With reference to the first possible implementation manner of the sixth aspect, in a second possible implementation manner, the rule further includes that A_e and A_f are positive integers.

[0046] With reference to the first possible implementation manner or the second possible implementation manner of the sixth aspect, in a third possible implementation manner, the rule further includes $A_e - 1 = A_f$ and $B_e + 1 = B_f$.

[0047] With reference to the sixth aspect, or any one of the first to third possible implementation manners, in a fourth possible implementation manner, the judging and processing unit is specifically configured to:

determine, by using a random function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0048] With reference to the fourth possible implementation manner of the sixth aspect, in a fifth possible implementation manner, the judging and processing unit is specifically configured to determine, by using a hash function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0049] With reference to the sixth aspect, or any one of the first to fifth possible implementation manners, in a sixth possible implementation manner, the judging and processing unit is configured to: when the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skip the N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, the determining unit performs step (a) for the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [k_i - A_z, k_i + B_z]$ or a left boundary of a window $W_{ic} [k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point falls within a range of the window $W_{iz} [k_i - A_z, k_i + B_z]$, where the window $W_{ic} [k_i - A_c, k_i + B_c]$ determined for the new potential dividing point is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M windows that are determined for the new potential dividing point according to the rule.

[0050] With reference to the fourth possible implementation manner of the sixth aspect, in a seventh possible implementation manner, that the judging and processing unit determines, by using

a random function, whether the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [k_i - A_z, k_i + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}, \dots$, and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits

corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}$$
, where when

$a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}, \dots$, and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix}$$
, F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \dots & h_{F*H,8} \end{pmatrix}$$
, random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, $S_{a1}, S_{a2}, \dots$, and S_{aF*H} are obtained

in a same way, a quantity K of values greater than 0 among $S_{a1}, S_{a2}, \dots$, and S_{aF*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0051] According to a seventh aspect, an embodiment of the present invention provides a computer-readable storage medium, where the computer-readable storage medium is configured to store an executable instruction, a server executes the executable instruction to search for a data stream dividing point, and a rule is preset on the server, where the rule is: for a potential dividing point k , determining M points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where x

indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers; and

the server executes the executable instruction to perform the following steps:

(a) according to the rule, for a current potential dividing point k_i , determining a point

p_{iz} and a window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point p_{iz} for a current potential

5 dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$

meets a preset condition C_z ; and

when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the

preset condition C_z , skipping N minimum units U for searching for a data stream dividing point

10 from the point p_{iz} along a direction of searching for a data stream dividing point, where $N \cdot U$ is

not greater than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing

point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix} [p_{ix} - A_x, p_{ix} + B_x]$ of M windows of

the current potential dividing point k_i meets the preset condition C_x , selecting the current

15 potential dividing point k_i as a data stream dividing point.

[0052] With reference to the seventh aspect, in a first possible implementation manner, the rule

further includes that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e =$

C_f .

[0053] With reference to the first possible implementation manner of the seventh aspect, in a

20 second possible implementation manner, the rule further includes: relative to the potential dividing

point k , the at least two points p_e and p_f are in a direction opposite to the direction of

searching for a data stream dividing point.

[0054] With reference to the first possible implementation manner or the second possible

implementation manner of the seventh aspect, in a third possible implementation manner, the rule

25 further includes that a distance between the at least two points p_e and p_f is 1 U.

[0055] With reference to the seventh aspect, or any one of the first to third possible

implementation manners of the seventh aspect, in a fourth possible implementation manner, the

determining, by the server, whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$

meets the preset condition C_z specifically includes:

determining, by the server by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0056] With reference to the fourth possible implementation manner of the seventh aspect, in a fifth possible implementation manner, the determining, by the server by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically includes:

determining, by the server by using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0057] With reference to the seventh aspect, or any one of the first to fifth possible implementation manners of the seventh aspect, in a sixth possible implementation manner, when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, where the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

[0058] With reference to the fourth possible implementation manner of the seventh aspect, in a seventh possible implementation manner, the determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes,

bits corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F^*H,1} & a_{F^*H,2} & \dots & a_{F^*H,8} \end{pmatrix}, \text{ where}$$

when $a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}, \dots$, and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$5 \quad \begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF^*H,1} & V_{aF^*H,2} & \dots & V_{aF^*H,8} \end{pmatrix}, \text{ F*H*8 random numbers are selected from random numbers}$$

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F^*H,1} & h_{F^*H,2} & \dots & h_{F^*H,8} \end{pmatrix}, \text{ random numbers in an mth row of the matrix } V_a \text{ and an mth row of}$$

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF^*H} are obtained

10 in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF^*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0059] According to an eighth aspect, an embodiment of the present invention provides a computer-readable storage medium, where the computer-readable storage medium is configured to store an executable instruction, a server executes the executable instruction to search for a data stream dividing point, and a rule is preset on the server, where the rule is: for a potential dividing point k , determining M windows $W_x [k - A_x, k + B_x]$ and a preset condition C_x corresponding to the window $W_x [k - A_x, k + B_x]$, where x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers; and the server executes the executable instruction to perform

20 the following steps:

(a) determining a corresponding window $W_{iz} [k_i - A_z, k_i + B_z]$ for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets

a preset condition C_z ; and

when the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along a direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x(\|A_x\|)$, so as to obtain a new potential dividing point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix}[k_i - A_x, k_i + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

10 **[0060]** With reference to the eighth aspect, in a first possible implementation manner, the rule further includes that at least two windows $W_{ie}[k_i - A_e, k_i + B_e]$ and $W_{if}[k_i - A_f, k_i + B_f]$ meet conditions $|A_e + B_e| = |A_f + B_f|$ and $C_e = C_f$.

[0061] With reference to the first possible implementation manner of the eighth aspect, in a second possible implementation manner, the rule further includes that A_e and A_f are positive integers.

[0062] With reference to the first possible implementation manner or the second possible implementation manner of the eighth aspect, in a third possible implementation manner, the rule further includes $A_e - 1 = A_f$ and $B_e + 1 = B_f$.

20 **[0063]** With reference to the eighth aspect, or any one of the first to third possible implementation manners of the eighth aspect, in a fourth possible implementation manner, the determining, by the server, whether at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

determining, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

25 **[0064]** With reference to the fourth possible implementation manner of the eighth aspect, in a fifth possible implementation manner, the determining, by the server by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z is specifically: determining, by the server by using a hash function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

30 **[0065]** With reference to the eighth aspect, or any one of the first to fifth possible

implementation manners of the eighth aspect, in a sixth possible implementation manner, when the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the current potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic}[k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz}[k_i - A_z, k_i + B_z]$ or a left boundary of a window $W_{ic}[k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point falls within a range of the window $W_{iz}[k_i - A_z, k_i + B_z]$, where the window $W_{ic}[k_i - A_c, k_i + B_c]$ determined for the new potential dividing point is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M windows that are determined for the new potential dividing point according to the rule.

[0066] With reference to the fourth possible implementation manner of the eighth aspect, in a seventh possible implementation manner, the determining, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz}[k_i - A_z, k_i + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits

corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \cdots & a_{1,8} \\ a_{2,1} & a_{2,2} & \cdots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \cdots & a_{F*H,8} \end{pmatrix}, \text{ where when}$$

$a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \cdots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \cdots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \cdots & V_{aF*H,8} \end{pmatrix}, \text{ F*H*8 random numbers are selected from random numbers}$$

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F^*H,1} & h_{F^*H,2} & \dots & h_{F^*H,8} \end{pmatrix}, \text{ random numbers in an } m\text{th row of the matrix } V_a \text{ and an } m\text{th row of}$$

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF^*H} are obtained

in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF^*H} is counted,

5 and when K is an even number, the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0067] In the embodiments of the present invention, a data stream dividing point is searched for by determining whether at least a part of data in a window of M windows meets a preset condition, and when the at least a part of data in the window does not meet the preset condition, a length of
10 $N*U$ is skipped, so as to obtain a next potential dividing point, thereby improving efficiency of searching for a data stream dividing point.

BRIEF DESCRIPTION OF DRAWINGS

[0068] FIG. 1 is a schematic diagram of an application scenario according to an embodiment of the present invention;

15 **[0069]** FIG. 2 is a schematic diagram of a data stream dividing point;

[0070] FIG. 3 is a schematic diagram of searching for a data stream dividing point;

[0071] FIG. 4 is a schematic diagram of a method according to an embodiment of the present invention;

20 **[0072]** FIG. 5 and FIG. 6 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0073] FIG. 7 and FIG. 8 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0074] FIG. 9 and FIG. 10 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

25 **[0075]** FIG. 11, FIG. 12, and FIG. 13 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0076] FIG. 14 and FIG. 15 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0077] FIG. 16 and FIG. 17 are schematic diagrams of determining whether at least a part of

data in a window meets a preset condition;

[0078] FIG. 18 is a structural diagram of a deduplication server;

[0079] FIG. 19 is a structural diagram of a deduplication server;

[0080] FIG. 20 is a schematic diagram of a method according to an embodiment of the present invention;

[0081] FIG. 21 and FIG. 22 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0082] FIG. 23 and FIG. 24 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0083] FIG. 25 and FIG. 26 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0084] FIG. 27, FIG. 28, and FIG. 29 are schematic diagrams of an implementation manner of searching for a data stream dividing point;

[0085] FIG. 30 and FIG. 31 are schematic diagrams of an implementation manner of searching for a data stream dividing point; and

[0086] FIG. 32 and FIG. 33 are schematic diagrams of determining whether at least a part of data in a window meets a preset condition.

DESCRIPTION OF EMBODIMENTS

[0087] With ongoing progress of storage technologies, amounts of generated data grow increasingly, and a large amount of data has raised the highest requirement for storage capacity. Purchase costs of IT equipment increase along with storage capacity. To mitigate the demand conflict between the amounts of data and the storage capacity and lower purchase costs of IT equipment, a technology of eliminating duplicate data is introduced to the field of data storage.

[0088] A use scenario of an embodiment of the present invention is a data backup scenario.

Data backup is a process of making, by using a backup server, a backup of data onto another storage medium to prevent data loss due to various reasons. FIG. 1 shows an architecture of a data backup system. The data backup system includes clients (101a, 101b, ..., and 101n), a backup server 102, a duplicate data elimination server (referred to as a deduplication server or a duplication elimination server for short) 103, and storage devices (104a, 104b, ..., and 104n). The clients (101a, 101b, ..., and 101n) may be application servers, work stations or the like. The backup server 102 is configured to make a backup of data generated by the clients. The deduplication server 103 is configured to execute a task of eliminating duplicate data for backup data. The storage devices (104a, 104b, ..., and 104n) serve as storage media that store data from which duplicate data has been

eliminated, and may be storage media such as disk arrays and tape libraries. The clients (101a, 101b, ..., and 101n), the backup server 102, the duplicate data elimination server 103, and the storage devices (104a, 104b, ..., and 104n) may be connected in a manner such as by using a switch, a local area network, the Internet, or an optical fiber. The foregoing devices may be located at a same site, or may be located at different sites. The backup server 102, the duplication elimination server 103, and the storage devices (104a, 104b, ..., and 104n) may be independent physical devices, or may be physically integrated into a whole in specific implementation, or the backup server 102 and the duplication elimination server 103 are integrated into a whole, or the duplication elimination server 103 and the storage devices (104a, 104b, ..., and 104n) are integrated into a whole, or the like.

[0089] The deduplication server 103 performs an operation of eliminating duplicate data on a data stream of backup data, where the operation generally includes the following steps:

(1) searching for a data stream dividing point: searching for a data stream dividing point in a data stream according to a specific algorithm;

(2) performing division according to the found data stream dividing point to obtain data chunks;

(3) calculating a feature value of each data chunk: calculating the feature value of the data chunk, which serves as a feature for identifying the data chunk; and adding the feature value obtained by means of calculation to a data chunk feature list of a file corresponding to the data stream, where an SHA-1 or MD5 algorithm is generally used to calculate a feature value of a data chunk;

(4) detecting a same data chunk: comparing the feature value of the data chunk obtained by means of calculation with a feature value that already exists in the data chunk feature list to determine whether an identical data chunk exists; and

(5) eliminating duplicate data block: if it is found by detecting a same data chunk that a feature value the same as that of the data chunk exists in the data chunk feature list, skipping storage of the data chunk or determining whether to store the data chunk according to a storage quantity of duplicate data chunks that is determined according to a backup policy.

[0090] It can be known, from the step of performing, by the deduplication server 103, the operation of eliminating duplicate data on a data stream of backup data, that the search for a data stream dividing point, serving as a key step in the operation of eliminating duplicate data, directly determines performance of duplicate data elimination.

[0091] In an embodiment of the present invention, the deduplication server 103 receives a backup file sent by the backup server 102, and performs processing of eliminating duplicate data on

the file. A backup file to be processed is usually presented in the form of a data stream on the deduplication server 103. When the deduplication server 103 searches for a dividing point in a data stream, a minimum unit for searching for a data stream dividing point usually needs to be determined. Specifically, as shown in FIG. 2, for example, a potential dividing point k_1 is located between two consecutive minimum units, whose sequence numbers are 1 and 2, for searching for a data stream dividing point. A potential dividing point refers to a point for which it needs to be determined whether the point can serve as a data stream dividing point. When the point k_1 is a data stream dividing point, in a direction of searching for a data stream dividing point shown by an arrow in FIG. 2, a next potential dividing point k_7 is searched for, that is, a point located between two consecutive minimum units, whose sequence numbers are 7 and 8, for searching for a data stream dividing point. When the potential dividing point k_7 is a data stream dividing point, data between the two adjacent data stream dividing points k_1 , and k_7 is 1 data chunk. The minimum unit for searching for a data stream dividing point may specifically be determined according to an actual requirement, and here 1 byte (Byte) is used as an example, that is, all the minimum units, whose sequence numbers are 1, 2, 7, and 8, for searching for a data stream dividing point have a size of 1 byte. The direction of searching for a data stream dividing point shown in FIG. 2 usually represents a search direction from a file header to a file trailer or a direction from a file trailer to a file header, and in this embodiment, the search direction from a file header to a file trailer is used as an example.

[0092] In a scenario of eliminating duplicate data, a smaller data chunk generally indicates a higher rate of eliminating duplicate data and an easier way to find a duplicate data chunk, but a larger amount of metadata generated from that; moreover, after a data chunk diminishes to a degree, the rate of eliminating duplicate data no longer increases, but the amount of metadata increases rapidly. Therefore, a size of a data chunk may be controlled. In actual applications, a minimum value of a data chunk, for example, 4 KB (4096 bytes), is usually set; in consideration of the rate of eliminating duplicate data at the same time, a maximum value of a data chunk is also set, that is, the size of a data chunk cannot exceed the maximum value, for example, 12 KB (12288 bytes). A specific implementation manner is shown in FIG. 3. The deduplication server 103 searches for a data stream dividing point along the direction shown by the arrow. k_a is a currently found data stream dividing point, and from k_a , a next potential dividing point is searched for in the direction of searching for a data stream dividing point. To meet the requirement of a minimum data chunk, usually starting from a data stream dividing point, a size of the minimum data chunk is skipped along a direction of searching for a data stream dividing point, and the search starts from an end

position of the minimum data chunk, that is, the end position of the minimum data chunk serves as a next potential dividing point k_i . In this embodiment of the present invention, a minimum data chunk of 4 KB, that is, $4*1024=4096$ bytes may be first skipped from the point k_a along the direction of searching for a data stream dividing point. 4096 bytes are skipped from the point k_a along the direction of searching for a data stream dividing point, and the point k_i is obtained at an end position of a 4096th byte to serve as a potential dividing point. For example, k_i is located between two consecutive minimum units, whose sequence numbers are 4096 and 4097, for searching for a data stream dividing point. Still using FIG. 3 as an example, k_a is a currently found data stream dividing point, and a next data stream dividing point is searched for along the direction shown in FIG. 3. If no next data stream dividing point is found after a maximum value of a data chunk is exceeded, starting from the point k_a in the direction of searching for a data stream dividing point, a point k_z at which the maximum value of a data chunk is reached serves as the next data stream dividing point and forced division is performed.

[0093] An embodiment of the present invention provides a method for searching for a data stream dividing point based on a deduplication server, which, as shown in FIG. 4, includes:

[0094] A rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining M points p_x , a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers, where a distance between p_x and the potential dividing point k is d_x minimum units for searching for a data stream dividing point, the minimum unit for searching for a data stream dividing point is represented as U, and in this embodiment, $U=1$ byte. In an implementation manner shown in FIG. 3, about a value of M, in one implementation manner, a value of $M*U$ is not greater than a preset maximum distance between two adjacent data stream dividing points, that is, a preset maximum length of a data chunk. It is determined whether at least a part of data in a window $W_z[p_z - A_z, p_z + B_z]$ corresponding to a point p_z meets a preset condition C_z , where, z is an integer, $1 \leq z \leq M$, and $(p_z - A_z)$ and $(p_z + B_z)$ represent two boundaries of the window W_z . When it is determined that at least a part of data in a window $W_z[p_z - A_z, p_z + B_z]$ of any one point p_z does not meet the preset condition C_z , N bytes are skipped from the point p_z corresponding to the window $W_z[p_z - A_z, p_z + B_z]$ that does not meet the preset condition along a direction of searching for a data

stream dividing point, where $N \leq \|B_z\| + \max_x (\|A_x\| + \|(k - p_x)\|)$, where $\|(k - p_x)\|$ represents a distance between any point of the M points p_x and the potential dividing point k , $\max_x (\|A_x\| + \|(k - p_x)\|)$ represents a maximum value of a sum of an absolute value of the distance between the any point of the M points p_x and the potential dividing point k and an absolute value of A_x corresponding to the any point, and $\|B_z\|$ represents an absolute value of B_z in $W_z[p_z - A_z, p_z + B_z]$. A principle for setting a value of N is specifically introduced in the following embodiments. When it is determined that at least a part of data in each window $W_x[p_x - A_x, p_x + B_x]$ of the M windows meets the preset condition C_x , the potential dividing point k is a data stream dividing point.

10 **[0095]** Specifically, for a current potential dividing point k_i , the following steps are performed according to the rule:

[0096] Step 401: Determine a point p_{iz} and a window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point p_{iz} for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$.

15 **[0097]** Step 402: Determine whether at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ;

when the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skip N minimum units U for searching for a data stream dividing point from the point p_{iz} along a direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, and perform step 401; and

when at least a part of data in each window $W_{ix}[p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , select the current potential dividing point k_i as a data stream dividing point.

25 **[0098]** Further, the rule further includes that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

[0099] The rule further includes: relative to the potential dividing point k , the at least two points p_e and p_f are in a direction opposite to the direction of searching for a data stream

dividing point.

[0100] The rule further includes that a distance between the at least two points p_e and p_f is 1 U.

[0101] The determining whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$

5 meets a preset condition C_z specifically includes:

determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0102] The determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z is specifically: determining, by

10 using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

[0103] When the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are

skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as

15 to obtain the new potential dividing point, and according to the rule, a left boundary of a window

$W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left

boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, where

20 the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

[0104] In this embodiment of the present invention, a data stream dividing point is searched for by determining whether at least a part of data in a window of M windows meets a preset condition,

25 and when the at least a part of data in the window does not meet the preset condition, a length of $N*U$ is skipped, where $N*U$ is not greater than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a next potential dividing point, thereby improving efficiency of searching for a data stream dividing point.

[0105] In a process of eliminating duplicate data, to ensure an even size of a data chunk, a size

30 of an average data chunk (also referred to as an average chunk) is considered. That is, while limits

on a size of a minimum data chunk and a size of a maximum data chunk are met, the size of the average data chunk is determined to ensure an even size of an obtained data chunk. A probability (represented as $P(n)$) of finding a data stream dividing point depends on two factors, that is, the quantity M of the points p_x and a probability that at least a part of data in the window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x meets the preset condition C_x , where the former affects a length for skipping, the latter affects a probability of skipping, and the two together affect the size of the average chunk. Generally, when the size of the average chunk is fixed, as the quantity M of the points p_x increases, the probability that at least a part of data in a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to a single point p_x meets the preset condition C_x also increases. For example, the rule preset on the deduplication server 103 is: for a potential dividing point k , determining 11 points p_x , where x indicates consecutive natural numbers from 1 to 11 separately, and a probability that at least a part of data in a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to any point p_x of the 11 points meets the preset condition C_x is $1/2$. Another group of rules preset on the deduplication server 103 is: selecting 24 points p_x for the potential dividing point k , where x indicates consecutive natural numbers from 1 to 24 separately, and a probability that at least a part of data in a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to any point p_x of the 24 points meets the preset condition C_x is $3/4$. For the setting of a probability that at least a part of data in a specific window $W_x[p_x - A_x, p_x + B_x]$ meets the preset condition C_x , reference may be made to the description of the part of determining whether the at least a part of data in the window $W_x[p_x - A_x, p_x + B_x]$ meets the preset condition C_x . $P(n)$ depends on the two factors, that is, the quantity M of points p_x and the probability that at least a part of data in the window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x meets the preset condition C_x , and $P(n)$ represents a probability that no data stream dividing point is found after n minimum units for searching for a data stream dividing point in a search from a start position/previous data stream dividing point of a data stream. A process of calculating $P(n)$ that depends on the two factors is actually an n -step Fibonacci sequence, which is described below in detail. After $P(n)$ is obtained, $1-P(n)$ is a distribution function of a data stream dividing point, and $(1-P(n))-(1-P(n-1))=P(n-1)-P(n)$ is a probability that a data stream dividing point is found at an n th point, that is, a density function of a data stream dividing point. Integration $\sum_{n=4*1024}^{12*1024} n \times (P(n-1) - P(n))$ may be performed according to

the density function of a data stream dividing point, so as to obtain an expected length of a data stream dividing point, that is, the size of the average chunk, where 4*1024 (bytes) represents a length of the minimum data chunk, and 12*1024 (bytes) represents a length of the maximum data chunk.

5 **[0106]** On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 5, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 points p_x , a window $W_x[p_x - A_x, p_x + B_x]$ (window W_x for short) corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$, where $A_1 = A_2 = A_3 = A_4 = A_5 = A_6 = A_7 = A_8 =$
10 $A_9 = A_{10} = A_{11} = 169$, $B_1 = B_2 = B_3 = B_4 = B_5 = B_6 = B_7 = B_8 = B_9 = B_{10} = B_{11} = 0$, and $C_1 = C_2 = C_3 = C_4 =$
 $C_5 = C_6 = C_7 = C_8 = C_9 = C_{10} = C_{11}$. A distance between the point p_x and the potential dividing point k is d_x bytes. Specifically, a distance between a point p_1 and the potential dividing point k is 0 byte, a distance between a point p_2 and the potential dividing point k is 1 byte, a distance between a point p_3 and the potential dividing point k is 2 bytes, a distance between a point p_4
15 and the potential dividing point k is 3 bytes, a distance between a point p_5 and the potential dividing point k is 4 bytes, a distance between a point p_6 and the potential dividing point k is 5 bytes, a distance between a point p_7 and the potential dividing point k is 6 bytes, a distance between a point p_8 and the potential dividing point k is 7 bytes, a distance between a point p_9 and the potential dividing point k is 8 bytes, a distance between a point p_{10} and the potential
20 dividing point k is 9 bytes, a distance between a point p_{11} and the potential dividing point k is 10 bytes, and relative to the potential dividing point k , all the points $p_2, p_3, p_4, p_5, p_6, p_7, p_8, p_9, p_{10}$, and p_{11} are in a direction opposite to a direction of searching for a data stream dividing point. k_a is a data stream dividing point, and the direction of searching for a data stream dividing point shown in FIG. 5 is from left to right. After a minimum data chunk of 4 KB is
25 skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i , and a point p_{ix} is determined for the potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 5, 11 points are determined for the potential dividing point k_i , and are $p_{i1}, p_{i2},$
30 $p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} separately, and windows corresponding to

the points $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} are $W_{i1}[p_{i1}-169, p_{i1}]$, $W_{i2}[p_{i2}-169, p_{i2}]$, $W_{i3}[p_{i3}-169, p_{i3}]$, $W_{i4}[p_{i4}-169, p_{i4}]$, $W_{i5}[p_{i5}-169, p_{i5}]$, $W_{i6}[p_{i6}-169, p_{i6}]$, $W_{i7}[p_{i7}-169, p_{i7}]$, $W_{i8}[p_{i8}-169, p_{i8}]$, $W_{i9}[p_{i9}-169, p_{i9}]$, $W_{i10}[p_{i10}-169, p_{i10}]$, and $W_{i11}[p_{i11}-169, p_{i11}]$ respectively. The foregoing windows are separately referred to as

5 $W_{i1}, W_{i2}, W_{i3}, W_{i4}, W_{i5}, W_{i6}, W_{i7}, W_{i8}, W_{i9}, W_{i10}$, and W_{i11} for short. A distance between the point p_{ix} and the potential dividing point k_i is d_x bytes. Specifically, a distance between p_{i1} and k_i is 0 byte, a distance between p_{i2} and k_i is 1 byte, a distance between p_{i3} and k_i is 2 bytes, a distance between p_{i4} and k_i is 3 bytes, a distance between p_{i5} and k_i is 4 bytes, a distance between p_{i6} and k_i is 5 bytes, a distance between p_{i7} and k_i is 6

10 bytes, a distance between p_{i8} and k_i is 7 bytes, a distance between p_{i9} and k_i is 8 bytes, a distance between p_{i10} and k_i is 9 bytes, a distance between p_{i11} and k_i is 10 bytes, and relative to the potential dividing point k_i , all $p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 , it

15 is determined whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , it is determined whether at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it

20 is determined whether at least a part of data in $W_{i7}[p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[p_{i11}-169, p_{i11}]$ meets a preset condition

25 C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset

condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, for example, as shown in FIG. 6, at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ does not meet the corresponding preset condition C_5 , N bytes are skipped from the point p_{i5} along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_5\| + \max_x(\|A_x\| + \|(k_i - p_{ix})\|)$. In an implementation manner shown in FIG. 6, the N bytes that are skipped are not greater than 179 bytes, and in this embodiment, $N=11$, so as to obtain a next potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According to the rule preset on the deduplication server 103 in the implementation manner shown in FIG. 5, 11 points are determined for the potential dividing point k_j , and are $p_{j1}, p_{j2}, p_{j3}, p_{j4}, p_{j5}, p_{j6}, p_{j7}, p_{j8}, p_{j9}, p_{j10}$, and p_{j11} separately, and windows corresponding to the points $p_{j1}, p_{j2}, p_{j3}, p_{j4}, p_{j5}, p_{j6}, p_{j7}, p_{j8}, p_{j9}, p_{j10}$, and p_{j11} are determined, and are $W_{j1}[p_{j1}-169, p_{j1}], W_{j2}[p_{j2}-169, p_{j2}], W_{j3}[p_{j3}-169, p_{j3}], W_{j4}[p_{j4}-169, p_{j4}], W_{j5}[p_{j5}-169, p_{j5}], W_{j6}[p_{j6}-169, p_{j6}], W_{j7}[p_{j7}-169, p_{j7}], W_{j8}[p_{j8}-169, p_{j8}], W_{j9}[p_{j9}-169, p_{j9}], W_{j10}[p_{j10}-169, p_{j10}]$, and $W_{j11}[p_{j11}-169, p_{j11}]$ respectively. A distance between p_{jx} and the potential dividing point k_j is d_x bytes. Specifically, a distance between p_{j1} and k_j is 0 byte, a distance between p_{j2} and k_j is 1 byte, a distance between p_{j3} and k_j is 2 bytes, a distance between p_{j4} and k_j is 3 bytes, a distance between p_{j5} and k_j is 4 bytes, a distance between p_{j6} and k_j is 5 bytes, a distance between p_{j7} and k_j is 6 bytes, a distance between p_{j8} and k_j is 7 bytes, a distance between p_{j9} and k_j is 8 bytes, a distance between p_{j10} and k_j is 9 bytes, a distance between p_{j11} and k_j is 10 bytes, and relative to the potential dividing point k_j , all $p_{j1}, p_{j2}, p_{j3}, p_{j4}, p_{j5}, p_{j6}, p_{j7}, p_{j8}, p_{j9}, p_{j10}$, and p_{j11} are in a direction opposite to the direction of searching for a data stream dividing point. In the implementation manner shown in FIG. 6, when the 11th window $W_{j11}[p_{j11}$

-169, p_{j11}] is determined for the potential dividing point k_j , to ensure that a range between the potential dividing point k_i and the potential dividing point k_j all fall within a determining range, in this implementation manner, it may be ensured that a left boundary of the window $W_{j11}[p_{j11}$ -169, $p_{j11}]$ coincides with a right boundary p_{i5} of $W_{i5}[p_{i5}$ -169, $p_{i5}]$ or falls within a range of $W_{i5}[p_{i5}$ -169, $p_{i5}]$, where the point p_{j11} determined for the potential dividing point k_j is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the potential dividing point k_j according to the rule. Therefore, within such a limit, when the at least a part of data in $W_{i5}[p_{i5}$ -169, $p_{i5}]$ does not meet the preset condition C_5 , a distance for skipping from p_{i5} along the direction of searching for a data stream dividing point is not greater than $\|B_5\| + \max_x(\|A_x\| + \|(k_i - p_{ix})\|)$, where $M=11$, and $11*U$ is not greater than $\max_x(\|A_x\| + \|(k_i - p_{ix})\|)$, and therefore, a distance for skipping from p_{i5} along the direction of searching for a data stream dividing point is not greater than 179. It is determined whether at least a part of data in $W_{j1}[p_{j1}$ -169, $p_{j1}]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[p_{j2}$ -169, $p_{j2}]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[p_{j3}$ -169, $p_{j3}]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[p_{j4}$ -169, $p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}$ -169, $p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}$ -169, $p_{j6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}$ -169, $p_{j7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}$ -169, $p_{j8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}$ -169, $p_{j9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}$ -169, $p_{j10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}$ -169, $p_{j11}]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data in the window W_{j1} meets the preset

condition C_1 , the at least a part of data in the window W_{j_2} meets the preset condition C_2 , the at least a part of data in the window W_{j_3} meets the preset condition C_3 , the at least a part of data in the window W_{j_4} meets the preset condition C_4 , the at least a part of data in the window W_{j_5} meets the preset condition C_5 , the at least a part of data in the window W_{j_6} meets the preset condition C_6 , the at least a part of data in the window W_{j_7} meets the preset condition C_7 , the at least a part of data in the window W_{j_8} meets the preset condition C_8 , the at least a part of data in the window W_{j_9} meets the preset condition C_9 , the at least a part of data in the window $W_{j_{10}}$ meets the preset condition C_{10} , and the at least a part of data in the window $W_{j_{11}}$ meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103, whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, 11 bytes are skipped in a manner the same as that of k_i to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0107] In the implementation manner shown in FIG. 5, according to the rule preset on the deduplication server 103, starting from determining whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 , when it is determined that the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 , it is determined that the at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 , it is determined that the at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets the preset condition C_3 , it is determined that the at least a part of data in $W_{i4}[p_{i4}-169, p_{i4}]$ meets the preset condition C_4 , and it is determined that the at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , 10 bytes are skipped from the point p_{i5} along the direction of searching for a data stream dividing point, and a new potential dividing point is obtained at an end position of a 10th byte, which is represented as k_g here for differentiation from other potential dividing points. According to the rule preset on the


deduplication server 103, 11 points p_{gx} are determined for the potential dividing point k_g , where x indicates consecutive natural numbers from 1 to 11 separately, and are p_{g1} , p_{g2} , p_{g3} , p_{g4} , p_{g5} , p_{g6} , p_{g7} , p_{g8} , p_{g9} , p_{g10} , and p_{g11} separately, and windows corresponding to the points p_{g1} , p_{g2} , p_{g3} , p_{g4} , p_{g5} , p_{g6} , p_{g7} , p_{g8} , p_{g9} , p_{g10} , and p_{g11} are determined, and are $W_{g1}[p_{g1}$
5 $-169, p_{g1}]$, $W_{g2}[p_{g2}-169, p_{g2}]$, $W_{g3}[p_{g3}-169, p_{g3}]$, $W_{g4}[p_{g4}-169, p_{g4}]$, $W_{g5}[p_{g5}-169, p_{g5}]$, $W_{g6}[p_{g6}-169, p_{g6}]$, $W_{g7}[p_{g7}-169, p_{g7}]$, $W_{g8}[p_{g8}-169, p_{g8}]$, $W_{g9}[p_{g9}-169, p_{g9}]$, W_{g10}
 $[p_{g10}-169, p_{g10}]$, and $W_{g11}[p_{g11}-169, p_{g11}]$ respectively. A distance between p_{gx} and the potential dividing point k_g is d_x bytes. Specifically, a distance between p_{g1} and k_g is 0 byte, a distance between p_{g2} and k_g is 1 byte, a distance between p_{g3} and k_g is 2 bytes, a distance
10 between p_{g4} and k_g is 3 bytes, a distance between p_{g5} and k_g is 4 bytes, a distance between p_{g6} and k_g is 5 bytes, a distance between p_{g7} and k_g is 6 bytes, a distance between p_{g8} and k_g is 7 bytes, a distance between p_{g9} and k_g is 8 bytes, a distance between p_{g10} and k_g is 9 bytes, a distance between p_{g11} and k_g is 10 bytes, and relative to the potential dividing point k_g , all p_{g2} , p_{g3} , p_{g4} , p_{g5} , p_{g6} , p_{g7} , p_{g8} , p_{g9} , p_{g10} , and p_{g11} are in a direction opposite to the
15 direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{g1}[p_{g1}-169, p_{g1}]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{g2}[p_{g2}-169, p_{g2}]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{g3}[p_{g3}-169, p_{g3}]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{g4}[p_{g4}-169, p_{g4}]$ meets the preset condition C_4 , it is determined whether at
20 least a part of data in $W_{g5}[p_{g5}-169, p_{g5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{g6}[p_{g6}-169, p_{g6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{g7}[p_{g7}-169, p_{g7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{g8}[p_{g8}-169, p_{g8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{g9}[p_{g9}-169, p_{g9}]$ meets the preset condition C_9 ,
25 it is determined whether at least a part of data in $W_{g10}[p_{g10}-169, p_{g10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{g11}[p_{g11}-169, p_{g11}]$ meets the preset condition C_{11} . Therefore, the point p_{g11} corresponding to the potential dividing point k_g coincides with the point p_{i5} corresponding to the potential dividing point k_i , the window W_{g11}

$[p_{g11}-169, p_{g11}]$ corresponding to the point p_{g11} coincides with the window $W_{i5}[p_{i5}-169, p_{i5}]$ corresponding to the point p_{i5} , and $C_5=C_{11}$; therefore, for the potential dividing point k_i , when it is determined that the at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , the potential dividing point k_g obtained by skipping 10 bytes from the point p_{i5} along the direction of searching for a data stream dividing point still does not meet a condition of serving as a data stream dividing point. Therefore, if repeated calculation exists when 10 bytes are skipped from the point p_{i5} along the direction of searching for a data stream dividing point, then repeated calculation can be reduced and efficiency is higher when 11 bytes are skipped from the point p_{i5} along the direction of searching for a data stream dividing point. Therefore, a speed of searching for a data stream dividing point is increased. When a probability that at least a part of data in the window $W_x[p_x-A_x, p_x+B_x]$ corresponding to the point p_x that is determined according to the preset rule meets the preset condition C_x is 1/2, that is, a probability of executing skipping is 1/2, at most 179 bytes can be skipped each time.

[0108] In this implementation manner, a preset rule is: for a potential dividing point k , determining 11 points p_x , a window $W_x[p_x-A_x, p_x+B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x-A_x, p_x+B_x]$, where x indicates consecutive natural numbers from 1 to 11 separately, where a probability that at least a part of data in the window $W_x[p_x-A_x, p_x+B_x]$ corresponding to the point p_x meets the preset condition is 1/2, and $P(n)$ can be calculated by using the two factors, that is, the quantity of points p_x and the probability that at least a part of data in the window $W_x[p_x-A_x, p_x+B_x]$ corresponding to the point p_x meets the preset condition. Moreover, $A_1=A_2=A_3=A_4=A_5=A_6=A_7=A_8=A_9=A_{10}=A_{11}=169$, $B_1=B_2=B_3=B_4=B_5=B_6=B_7=B_8=B_9=B_{10}=B_{11}=0$, and $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$, where a distance between p_x and the potential dividing point k is d_x bytes. Specifically, a distance between p_1 and the potential dividing point k is 0 byte, a distance between p_2 and k is 1 byte, a distance between p_3 and k is 2 bytes, a distance between p_4 and k is 3 bytes, a distance between p_5 and k is 4 bytes, a distance between p_6 and k is 5 bytes, a distance between p_7 and k is 6 bytes, a distance between p_8 and k is 7 bytes, a distance between p_9 and k is 8 bytes, a distance between p_{10} and k is 9 bytes, a distance between p_{11} and k is 10 bytes, and relative to the potential dividing point k , all $p_2, p_3, p_4,$

$p_5, p_6, p_7, p_8, p_9, p_{10}$, and p_{11} are in a direction opposite to the direction of searching for a data stream dividing point. Therefore, whether the potential dividing point k is a data stream dividing point depends on whether it exists that at least a part of data in each window of windows corresponding to the 11 consecutive points meets the preset condition C_x . After a minimum chunk length of 4096 bytes is skipped from a start position/previous data stream dividing point of a data stream, a 4086th point is found by going back by 10 bytes in a direction opposite to the direction of searching for a data stream dividing point, and no data stream dividing point exists at the point; therefore, $P(4086)=1$, and $P(4087)=1, \dots, P(4095)=1$, and so on. At an 4096th point, that is, a point which is used to obtain the minimum chunk, with a probability of $(1/2)^{11}$, at least a part of data in each window of the windows corresponding to the 11 points meets the preset condition C_x . Hence, with a probability of $(1/2)^{11}$, a data stream dividing point exists; with a probability of $1-(1/2)^{11}$, no data stream dividing point exists; therefore $P(11)=1-(1/2)^{11}$.

[0109] At an n th point, there may be 12 cases of obtaining $P(n)$ by means of recursion.



[0110] Case 1: With a probability of $1/2$, at least a part of data in a window corresponding to the n th point does not meet a preset condition; in this case, with a probability of $P(n-1)$, 11 consecutive points do not exist among $(n-1)$ points before the n th point, where at least a part of data in each window of windows corresponding to the 11 consecutive points separately meets a preset condition. Therefore, $P(n)$ includes $1/2 \cdot P(n-1)$. A case in which the at least a part of data in the window

corresponding to the n th point does not meet the preset condition, and 11 consecutive points exist among the $(n-1)$ points before the n th point, where at least a part of data in each window of windows corresponding to the 11 consecutive points separately meets the preset condition, is not related to $P(n)$.

5 **[0111]** Case 2: With a probability of $1/2$, at least a part of data in a window corresponding to the n th point meets a preset condition, and with the probability of $1/2$, at least a part of data in a window corresponding to an $(n-1)$ th point does not meet a preset condition; in this case, with a probability of $P(n-2)$, 11 consecutive points do not exist among $(n-2)$ points before the $(n-1)$ point, where at least a part of data in each window of windows corresponding to 11 consecutive points
10 separately meets a preset condition. Therefore, $P(n)$ includes $1/2 * 1/2 * P(n-2)$. A case in which the at least a part of data in the window corresponding to the n th point meets the preset condition, the at least a part of data in the window corresponding to the $(n-1)$ th point does not meet the preset condition, and 11 consecutive points exist among the $(n-2)$ points before the $(n-1)$ th point, where at least a part of data in each window of windows corresponding to the 11 consecutive points
15 separately meets the preset condition, is not related to $P(n)$.

[0112] According to the foregoing description, case 11: With a probability of $(1/2)^{10}$, at least a part of data in windows corresponding to n th to $(n-9)$ th points meets a preset condition, and with a probability of $1/2$, at least a part of data in a window corresponding to an $(n-10)$ th point does not meet a preset condition; in this case, with a probability of $P(n-11)$, 11 consecutive points do not
20 exist among $(n-11)$ points before the $(n-10)$ point, where at least a part of data in each window of windows corresponding to the 11 consecutive points separately meets a preset condition. Therefore, $P(n)$ includes $(1/2)^{10} * 1/2 * P(n-11)$. A case in which the at least a part of data in the windows corresponding to the n th to $(n-9)$ th points meets the preset condition, the at least a part of data in the window corresponding to the $(n-10)$ th point does not meet the preset condition, and 11 consecutive
25 points exist among the $(n-11)$ points before the $(n-10)$ th point, where at least a part of data in each window of windows corresponding to the 11 consecutive points separately meets the preset condition, is not related to $P(n)$.

[0113] Case 12: With a probability of $(1/2)^{11}$, at least a part of data in windows corresponding to n th to $(n-10)$ th points meets a preset condition, and this case is not related to $P(n)$.

30 **[0114]** Therefore, $P(n) = 1/2 * P(n-1) + (1/2)^2 * P(n-2) + \dots + (1/2)^{11} * P(n-11)$. Another preset rule is: for a potential dividing point k , determining 24 points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to 24 separately, where a probability that at least a part of data in the window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the

point p_x meets the preset condition C_x is $3/4$, and $P(n)$ can be calculated by using the two factors, that is, the quantity of points p_x and the probability that at least a part of data in the window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x meets the preset condition. Moreover, $A_1 = A_2 = A_3 = A_4 = A_5 = A_6 = A_7 = A_8 = A_9 = A_{10} = A_{11} = 169$, $B_1 = B_2 = B_3 = B_4 = B_5 = B_6 = B_7 = B_8 = B_9 = B_{10} = B_{11} = 0$, and $C_1 = C_2 = C_3 = C_4 = C_5 = C_6 = C_7 = C_8 = C_9 = \dots = C_{22} = C_{23} = C_{24}$, where a distance between p_x and the potential dividing point k is d_x bytes. Specifically, a distance between p_1 and the potential dividing point k is 0 byte, a distance between p_2 and k is 1 byte, a distance between p_3 and k is 2 bytes, a distance between p_4 and k is 3 bytes, a distance between p_5 and k is 4 bytes, a distance between p_6 and k is 5 bytes, a distance between p_7 and k is 6 bytes, a distance between p_8 and k is 7 bytes, a distance between p_9 and k is 8 bytes, ..., a distance between p_{22} and k is 21 bytes, a distance between p_{23} and k is 22 bytes, a distance between p_{24} and k is 23 bytes, and relative to the potential dividing point k , all $p_2, p_3, p_4, p_5, p_6, p_7, p_8, p_9, \dots, p_{22}, p_{23}$, and p_{24} are in a direction opposite to the direction of searching for a data stream dividing point. Therefore, whether the potential dividing point k is a data stream dividing point depends on whether it exists that at least a part of data in each window of windows corresponding to the 24 consecutive points meets the preset condition C_x , and calculation can be performed by using the following formulas:

$$P(4073)=1, P(4074)=1, \dots, P(4095)=1, P(4096)=1-(3/4)^{24}, \text{ and}$$

$$P(n)=1/4 \cdot P(n-1)+1/4 \cdot (3/4) \cdot P(n-2)+\dots+1/4 \cdot (3/4)^{23} \cdot P(n-24).$$

[0115] After calculation, $P(5 \cdot 1024)=0.78$, $P(11 \cdot 1024)=0.17$, and $P(12 \cdot 1024)=0.13$. That is, if no data stream dividing point is found with a probability of 13% after a search proceeds to a point at a distance of 12 KB from a start position/previous data stream dividing point of a data stream, and forced division is performed. A density function of a data stream dividing point is obtained by using this probability, and after integration, it is obtained that on average, a data stream dividing point is found after a search proceeds to a point at a distance about 7.6 KB from the start position/previous data stream dividing point of the data stream, that is, an average chunk length is about 7.6 KB. Different from that at least a part of data in windows corresponding to 11 consecutive points meets a preset condition with a probability of $1/2$, a conventional CDC algorithm can achieve an effect of an average chunk length being 7.6 KB only when one window meets a condition with a probability of $1/2^{12}$.

[0116] On the basis of the search for a data stream dividing point shown in FIG. 3, in an

implementation manner shown in FIG. 7, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to 11 separately, where a probability that at least a part of data in the window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x meets the preset condition C_x is $1/2$, $A_1 = A_2 = A_3 = A_4 = A_5 = A_6 = A_7 = A_8 = A_9 = A_{10} = A_{11} = 169$, $B_1 = B_2 = B_3 = B_4 = B_5 = B_6 = B_7 = B_8 = B_9 = B_{10} = B_{11} = 0$, and $C_1 = C_2 = C_3 = C_4 = C_5 = C_6 = C_7 = C_8 = C_9 = C_{10} = C_{11}$, where a distance between p_x and the potential dividing point k is d_x bytes. Specifically, a distance between p_1 and the potential dividing point k is 2 bytes, a distance between p_2 and k is 3 bytes, a distance between p_3 and k is 4 bytes, a distance between p_4 and k is 5 bytes, a distance between p_5 and k is 6 bytes, a distance between p_6 and k is 7 bytes, a distance between p_7 and k is 8 bytes, a distance between p_8 and k is 9 bytes, a distance between p_9 and k is 10 bytes, a distance between p_{10} and k is 1 byte, a distance between p_{11} and k is 0 byte, and relative to the potential dividing point k , all $p_1, p_2, p_3, p_4, p_5, p_6, p_7, p_8, p_9$, and p_{10} are in a direction opposite to a direction of searching for a data stream dividing point. k_a is a data stream dividing point, and the direction of searching for a data stream dividing point shown in FIG. 7 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i , and a point p_{ix} is determined for the potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 7, according to the preset rule, 11 points are determined for the potential dividing point k_i , and are $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} separately, and windows corresponding to the points $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} are $W_{i1} [p_{i1} - 169, p_{i1}]$, $W_{i2} [p_{i2} - 169, p_{i2}]$, $W_{i3} [p_{i3} - 169, p_{i3}]$, $W_{i4} [p_{i4} - 169, p_{i4}]$, $W_{i5} [p_{i5} - 169, p_{i5}]$, $W_{i6} [p_{i6} - 169, p_{i6}]$, $W_{i7} [p_{i7} - 169, p_{i7}]$, $W_{i8} [p_{i8} - 169, p_{i8}]$, $W_{i9} [p_{i9} - 169, p_{i9}]$, $W_{i10} [p_{i10} - 169, p_{i10}]$, and $W_{i11} [p_{i11} - 169, p_{i11}]$ respectively. A distance between the point p_{ix} and the potential dividing point k_i is d_{ix} bytes. Specifically, a distance between p_{i1} and k_i is 2 bytes, a distance between p_{i2} and k_i is 3

bytes, a distance between p_{i3} and k_i is 4 bytes, a distance between p_{i4} and k_i is 5 bytes, a distance between p_{i5} and k_i is 6 bytes, a distance between p_{i6} and k_i is 7 bytes, a distance between p_{i7} and k_i is 8 bytes, a distance between p_{i8} and k_i is 9 bytes, a distance between p_{i9} and k_i is 10 bytes, a distance between p_{i10} and k_i is 1 byte, a distance between p_{i11} and k_i is 0 byte, and relative to the potential dividing point k_i , all p_{i1} , p_{i2} , p_{i3} , p_{i4} , p_{i5} , p_{i6} , p_{i7} , p_{i8} , p_{i9} , and p_{i10} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets a preset condition C_1 , it is determined whether at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , it is determined whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9} [p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11} [p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, as shown in FIG. 8, that the at least a part of data in $W_{i3} [p_{i3}-169,$

p_{i3}] does not meet the preset condition C_3 and 11 bytes are skipped from the point p_{i3} along a direction of searching for a data stream dividing point is used as an example for description. As shown in FIG. 8, when it is determined that W_3 does not meet a preset condition, from p_3 that serves as a start point, N bytes are skipped along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_3\| + \max_x(\|A_x\| + \|(k_i - p_{ix})\|)$. In the implementation manner shown in FIG. 6, N bytes are skipped, and specifically are not greater than 179 bytes, and in this embodiment, N=11. A next potential dividing point is obtained at an end position of an 11th byte. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According to the rule preset on the deduplication server

103, 11 points are determined for the potential dividing point k_j , and are p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} separately, and windows corresponding to the points p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} are determined, and are $W_{j1}[p_{j1}-169, p_{j1}]$, $W_{j2}[p_{j2}-169, p_{j2}]$, $W_{j3}[p_{j3}-169, p_{j3}]$, $W_{j4}[p_{j4}-169, p_{j4}]$, $W_{j5}[p_{j5}-169, p_{j5}]$, $W_{j6}[p_{j6}-169, p_{j6}]$, $W_{j7}[p_{j7}-169, p_{j7}]$, $W_{j8}[p_{j8}-169, p_{j8}]$, $W_{j9}[p_{j9}-169, p_{j9}]$, $W_{j10}[p_{j10}-169, p_{j10}]$, and $W_{j11}[p_{j11}-169, p_{j11}]$ respectively. A distance between p_{jx} and the potential dividing point k_j is d_x bytes. Specifically, a distance between p_{j1} and k_j is 2 bytes, a distance between p_{j2} and k_j is 3 bytes, a distance between p_{j3} and k_j is 4 bytes, a distance between p_{j4} and k_j is 5 bytes, a distance between p_{j5} and k_j is 6 bytes, a distance between p_{j6} and k_j is 7 bytes, a distance between p_{j7} and k_j is 8 bytes, a distance between p_{j8} and k_j is 9 bytes, a distance between p_{j9} and k_j is 10 bytes, a distance between p_{j10} and k_j is 1 byte, a distance between p_{j11} and k_j is 0 byte, and relative to the potential dividing point k_j , all p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , and p_{j10} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets the preset condition C_6 , it is determined

whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103, whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, 11 bytes are skipped in a manner the same as that of k_i to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point. Certainly, implementation of the method is restricted by a length of the maximum data chunk and a size of a file forming the data stream, which

is not described herein again.

[0117] On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 9, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where $A_1 = A_2 = A_3 = A_4 = A_5 = A_6 = A_7 = A_8 = A_9 = A_{10} = A_{11} = 169$, $B_1 = B_2 = B_3 = B_4 = B_5 = B_6 = B_7 = B_8 = B_9 = B_{10} = B_{11} = 0$, and $C_1 = C_2 = C_3 = C_4 = C_5 = C_6 = C_7 = C_8 = C_9 = C_{10} = C_{11}$. A distance between p_x and the potential dividing point k is d_x bytes. Specifically, a distance between p_1 and the potential dividing point k is 3 bytes, a distance between p_2 and k is 2 bytes, a distance between p_3 and k is 1 byte, a distance between p_4 and k is 0 byte, a distance between p_5 and k is 1 byte, a distance between p_6 and k is 2 bytes, a distance between p_7 and k is 3 bytes, a distance between p_8 and k is 4 bytes, a distance between p_9 and k is 5 bytes, a distance between p_{10} and k is 6 bytes, a distance between p_{11} and k is 7 bytes, all $p_5, p_6, p_7, p_8, p_9, p_{10}$, and p_{11} are, relative to the potential dividing point k , in a direction opposite to a direction of searching for a data stream dividing point, and all p_1, p_2 , and p_3 are, relative to the potential dividing point k , in the direction of searching for a data stream dividing point. k_a is a data stream dividing point, and the direction of searching for a data stream dividing point shown in FIG. 9 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i , and a point p_{ix} is determined for the potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 9, 11 points are determined for a potential dividing point k_i , and are $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} separately, and windows corresponding to the points $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} are $W_{i1} [p_{i1} - 169, p_{i1}]$, $W_{i2} [p_{i2} - 169, p_{i2}]$, $W_{i3} [p_{i3} - 169, p_{i3}]$, $W_{i4} [p_{i4} - 169, p_{i4}]$, $W_{i5} [p_{i5} - 169, p_{i5}]$, $W_{i6} [p_{i6} - 169, p_{i6}]$, $W_{i7} [p_{i7} - 169, p_{i7}]$, $W_{i8} [p_{i8} - 169, p_{i8}]$, $W_{i9} [p_{i9} - 169, p_{i9}]$, $W_{i10} [p_{i10} - 169, p_{i10}]$, and $W_{i11} [p_{i11} - 169, p_{i11}]$ respectively. A distance between p_{ix} and the potential dividing point k_i is d_x bytes. Specifically, a distance between p_{i1} and k_i is 3 bytes, a distance between p_{i2} and k_i is 2 bytes, a distance between p_{i3} and k_i is 1 byte, a

distance between p_{i4} and k_i is 0 byte, a distance between p_{i5} and k_i is 1 byte, a distance between p_{i6} and k_i is 2 bytes, a distance between p_{i7} and k_i is 3 bytes, a distance between p_{i8} and k_i is 4 bytes, a distance between p_{i9} and k_i is 5 bytes, a distance between p_{i10} and k_i is 6 bytes, a distance between p_{i11} and k_i is 7 bytes, all p_{i5} , p_{i6} , p_{i7} , p_{i8} , p_{i9} , p_{i10} , and p_{i11} are, relative to the potential dividing point k_i , in a direction opposite to the direction of searching for a data stream dividing point, and all p_{i1} , p_{i2} , and p_{i3} are, relative to the potential dividing point k_i , in the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets a preset condition C_1 , it is determined whether at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , it is determined whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9} [p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11} [p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, for

example, as shown in FIG. 10, at least a part of data in $W_{i7}[p_{i7}-169, p_{i7}]$ does not meet a corresponding preset condition, N bytes are skipped from the point p_{i7} along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_4\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$. In an implementation manner shown in FIG. 10, N bytes that are skipped are specifically not greater than 179 bytes, and in this embodiment, specifically, N=8, so as to obtain a new potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According to the rule preset on the deduplication server 103 in the implementation manner shown in FIG. 9, 11 points are determined for the potential dividing point k_j , and are $p_{j1}, p_{j2}, p_{j3}, p_{j4}, p_{j5}, p_{j6}, p_{j7}, p_{j8}, p_{j9}, p_{j10}$, and p_{j11} separately, and windows corresponding to the points $p_{j1}, p_{j2}, p_{j3}, p_{j4}, p_{j5}, p_{j6}, p_{j7}, p_{j8}, p_{j9}, p_{j10}$, and p_{j11} are determined, and are $W_{j1}[p_{j1}-169, p_{j1}], W_{j2}[p_{j2}-169, p_{j2}], W_{j3}[p_{j3}-169, p_{j3}], W_{j4}[p_{j4}-169, p_{j4}], W_{j5}[p_{j5}-169, p_{j5}], W_{j6}[p_{j6}-169, p_{j6}], W_{j7}[p_{j7}-169, p_{j7}], W_{j8}[p_{j8}-169, p_{j8}], W_{j9}[p_{j9}-169, p_{j9}], W_{j10}[p_{j10}-169, p_{j10}]$, and $W_{j11}[p_{j11}-169, p_{j11}]$ respectively. A distance between p_{jx} and the potential dividing point k_j is d_x bytes. Specifically, a distance between p_{j1} and k_j is 3 bytes, a distance between p_{j2} and k_j is 2 bytes, a distance between p_{j3} and k_j is 1 byte, a distance between p_{j4} and k_j is 0 byte, a distance between p_{j5} and k_j is 1 byte, a distance between p_{j6} and k_j is 2 bytes, a distance between p_{j7} and k_j is 3 bytes, a distance between p_{j8} and k_j is 4 bytes, a distance between p_{j9} and k_j is 5 bytes, a distance between p_{j10} and k_j is 6 bytes, a distance between p_{j11} and k_j is 7 bytes, all $p_{j5}, p_{j6}, p_{j7}, p_{j8}, p_{j9}, p_{j10}$, and p_{j11} are, relative to the potential dividing point k_j , in a direction opposite to the direction of searching for a data stream dividing point, and all p_{j1}, p_{j2} , and p_{j3} are, relative to the potential dividing point k_j , in the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a

part of data in $W_{j_6}[p_{j_6}-169, p_{j_6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j_7}[p_{j_7}-169, p_{j_7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j_8}[p_{j_8}-169, p_{j_8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j_9}[p_{j_9}-169, p_{j_9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j_{10}}[p_{j_{10}}-169, p_{j_{10}}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j_{11}}[p_{j_{11}}-169, p_{j_{11}}]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data in the window W_{j_1} meets the preset condition C_1 , the at least a part of data in the window W_{j_2} meets the preset condition C_2 , the at least a part of data in the window W_{j_3} meets the preset condition C_3 , the at least a part of data in the window W_{j_4} meets the preset condition C_4 , the at least a part of data in the window W_{j_5} meets the preset condition C_5 , the at least a part of data in the window W_{j_6} meets the preset condition C_6 , the at least a part of data in the window W_{j_7} meets the preset condition C_7 , the at least a part of data in the window W_{j_8} meets the preset condition C_8 , the at least a part of data in the window W_{j_9} meets the preset condition C_9 , the at least a part of data in the window $W_{j_{10}}$ meets the preset condition C_{10} , and the at least a part of data in the window $W_{j_{11}}$ meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103, whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, 8 bytes are skipped in a manner the same as that of k_i to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0118] On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 11, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where $A_1 = A_2 = A_3 = A_4 = A_5 = A_6 = A_7 = A_8 = A_9 = A_{10} = 169$, $A_{11} = 182$, $B_1 = B_2 = B_3 = B_4 = B_5 = B_6 = B_7 = B_8 = B_9 = B_{10} = B_{11} = 0$, and $C_1 = C_2 = C_3 = C_4 = C_5 = C_6 = C_7 = C_8 = C_9 = C_{10} \neq C_{11}$. A distance between p_x and the potential dividing point k is d_x bytes. Specifically, a distance between p_1 and the potential dividing point k is 0 byte, a distance between p_2 and k is 1 byte, a distance between p_3 and k is 2 bytes, a distance between p_4 and k is 3 bytes, a distance between p_5 and k is 4 bytes, a distance between p_6 and k is 5 bytes, a distance between p_7 and k is 6 bytes, a distance between p_8 and k is 7 bytes, a distance between p_9 and k is 8 bytes, a distance between p_{10} and k is 1 byte, a distance between p_{11} and k is 3 bytes, all $p_2, p_3, p_4, p_5, p_6, p_7, p_8$, and p_9 are, relative to the potential dividing point k , in a direction opposite to a direction of searching for a data stream dividing point, and both p_{10} and p_{11} are, relative to the potential dividing point k , in the direction of searching for a data stream dividing point. k_a is a data stream dividing point, and the direction of searching for a data stream dividing point shown in FIG. 11 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i , and a point p_{ix} is determined for the potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 11, 11 points are determined for the potential dividing point k_i , and are $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} separately, and windows corresponding to the points $p_{i1}, p_{i2}, p_{i3}, p_{i4}, p_{i5}, p_{i6}, p_{i7}, p_{i8}, p_{i9}, p_{i10}$, and p_{i11} are $W_{i1} [p_{i1} - 169, p_{i1}]$, $W_{i2} [p_{i2} - 169, p_{i2}]$, $W_{i3} [p_{i3} - 169, p_{i3}]$, $W_{i4} [p_{i4} - 169, p_{i4}]$, $W_{i5} [p_{i5} - 169, p_{i5}]$, $W_{i6} [p_{i6} - 169, p_{i6}]$, $W_{i7} [p_{i7} - 169, p_{i7}]$, $W_{i8} [p_{i8} - 169, p_{i8}]$, $W_{i9} [p_{i9} - 169, p_{i9}]$, $W_{i10} [p_{i10} - 169, p_{i10}]$, and $W_{i11} [p_{i11} - 182, p_{i11}]$ respectively. A distance between p_{ix} and the potential dividing point k_i is d_x bytes. Specifically, a distance between p_{i1} and k_i is 0 byte, a distance between p_{i2} and k_i is 1 byte, a distance between p_{i3} and k_i is 2 bytes, a

distance between p_{i4} and k_i is 3 bytes, a distance between p_{i5} and k_i is 4 bytes, a distance between p_{i6} and k_i is 5 bytes, a distance between p_{i7} and k_i is 6 bytes, a distance between p_{i8} and k_i is 7 bytes, a distance between p_{i9} and k_i is 8 bytes, a distance between p_{i10} and k_i is 1 byte, a distance between p_{i11} and k_i is 3 bytes, all p_{i2} , p_{i3} , p_{i4} , p_{i5} , p_{i6} , p_{i7} , p_{i8} , and p_{i9} are relative to the potential dividing point k_i , in a direction opposite to the direction of searching for a data stream dividing point, and both p_{i10} and p_{i11} are, relative to the potential dividing point k_i , in the direction of searching for a data stream dividing point. It is determined whether at least a part of data in the $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 , it is determined whether at least a part of data in the $W_{i2}[p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , it is determined whether at least a part of data in the $W_{i3}[p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in the $W_{i4}[p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in the $W_{i5}[p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in the $W_{i6}[p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in the $W_{i7}[p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in the $W_{i8}[p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in the $W_{i9}[p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in the $W_{i10}[p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in the $W_{i11}[p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential

dividing point k_i is a data stream dividing point. When it is determined that the at least a part of data in the window W_{i11} does not meet the preset condition C_{11} , 1 byte is skipped from the potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain a new potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. When the at least a part of data in any window of the 10 windows W_{i1} , W_{i2} , W_{i3} , W_{i4} , W_{i5} , W_{i6} , W_{i7} , W_{i8} , W_{i9} , and W_{i10} does not meet the corresponding preset condition, for example, $W_{i4}[p_{i4}-169, p_{i4}]$ shown in FIG. 12, N bytes are skipped from the point p_{i4} along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_4\| + \max_x(\|A_x\| + \|(k_i - p_{ix})\|)$. In an implementation manner shown in FIG. 12, the N bytes that are skipped are specifically not greater than 179, and in this embodiment, specifically, N=9, so as to obtain a new potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According to the rule preset on the deduplication server 103 in the implementation manner shown in FIG. 11, 11 points are determined for the potential dividing point k_j , and are p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} separately, and windows corresponding to the points p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} are determined, and are $W_{j1}[p_{j1}-169, p_{j1}]$, $W_{j2}[p_{j2}-169, p_{j2}]$, $W_{j3}[p_{j3}-169, p_{j3}]$, $W_{j4}[p_{j4}-169, p_{j4}]$, $W_{j5}[p_{j5}-169, p_{j5}]$, $W_{j6}[p_{j6}-169, p_{j6}]$, $W_{j7}[p_{j7}-169, p_{j7}]$, $W_{j8}[p_{j8}-169, p_{j8}]$, $W_{j9}[p_{j9}-169, p_{j9}]$, $W_{j10}[p_{j10}-169, p_{j10}]$, and $W_{j11}[p_{j8}-182, p_{j8}]$ respectively. A distance between p_{jx} and the potential dividing point k_j is d_x bytes. Specifically, a distance between p_{j1} and k_j is 0 byte, a distance between p_{j2} and k_j is 1 byte, a distance between p_{j3} and k_j is 2 bytes, a distance between p_{j4} and k_j is 3 bytes, a distance between p_{j5} and k_j is 4 bytes, a distance between p_{j6} and k_j is 5 bytes, a distance between p_{j7} and k_j is 6 bytes, a distance between p_{j8} and k_j is 7 bytes, a distance between p_{j9} and k_j is 8 bytes, a distance between p_{j10} and k_j is 1 byte, a distance between p_{j11} and k_j is 3 bytes, all p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , and p_{j9} are, relative to the potential dividing point k_j , in a direction opposite to the direction of searching for a data stream dividing point, and both p_{j10} and p_{j11} are, relative to the potential dividing point k_j , in the direction of searching for a data stream dividing point. It is determined whether at least a part of data in the $W_{j1}[p_{j1}-169, p_{j1}]$ meets the

preset condition C_1 , it is determined whether at least a part of data in the $W_{j_2}[p_{j_2}-169, p_{j_2}]$ meets the preset condition C_2 , it is determined whether at least a part of data in the $W_{j_3}[p_{j_3}-169, p_{j_3}]$ meets the preset condition C_3 , it is determined whether at least a part of data in the $W_{j_4}[p_{j_4}-169, p_{j_4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in the $W_{j_5}[p_{j_5}-169, p_{j_5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in the $W_{j_6}[p_{j_6}-169, p_{j_6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in the $W_{j_7}[p_{j_7}-169, p_{j_7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in the $W_{j_8}[p_{j_8}-169, p_{j_8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in the $W_{j_9}[p_{j_9}-169, p_{j_9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in the $W_{j_{10}}[p_{j_{10}}-169, p_{j_{10}}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in the $W_{j_{11}}[p_{j_{11}}-182, p_{j_{11}}]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data in the window W_{j_1} meets the preset condition C_1 , the at least a part of data in the window W_{j_2} meets the preset condition C_2 , the at least a part of data in the window W_{j_3} meets the preset condition C_3 , the at least a part of data in the window W_{j_4} meets the preset condition C_4 , the at least a part of data in the window W_{j_5} meets the preset condition C_5 , the at least a part of data in the window W_{j_6} meets the preset condition C_6 , the at least a part of data in the window W_{j_7} meets the preset condition C_7 , the at least a part of data in the window W_{j_8} meets the preset condition C_8 , the at least a part of data in the window W_{j_9} meets the preset condition C_9 , the at least a part of data in the window $W_{j_{10}}$ meets the preset condition C_{10} , and the at least a part of data in the window $W_{j_{11}}$ meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and it is determined, according to the rule preset on the deduplication server 103, whether the next potential dividing point is a data stream dividing point. When it is determined that the potential

dividing point k_j is not a data stream dividing point, a next potential dividing point is obtained in a manner the same as that of k_i , and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0119] On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 13, a rule that is preset on a deduplication server 103 is: for a potential dividing point k , determining 11 points p_x , a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to 11 separately, where a probability that at least a part of data in the window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x meets a preset condition is $1/2$, $A_1 = A_2 = A_3 = A_4 = A_5 = A_6 = A_7 = A_8 = A_9 = A_{10} = A_{11} = 169$, $B_1 = B_2 = B_3 = B_4 = B_5 = B_6 = B_7 = B_8 = B_9 = B_{10} = B_{11} = 0$, and $C_1 = C_2 = C_3 = C_4 = C_5 = C_6 = C_7 = C_8 = C_9 = C_{10} = C_{11}$, where a distance between p_x and the potential dividing point k is d_x bytes.

Specifically, a distance between p_1 and the potential dividing point k is 0 byte, a distance between p_2 and k is 2 bytes, a distance between p_3 and k is 4 bytes, a distance between p_4 and k is 6 bytes, a distance between p_5 and k is 8 bytes, a distance between p_6 and k is 10 bytes, a distance between p_7 and k is 12 bytes, a distance between p_8 and k is 14 bytes, a distance between p_9 and k is 16 bytes, a distance between p_{10} and k is 18 bytes, a distance between p_{11} and k is 20 bytes, and relative to the potential dividing point k , all p_2 , p_3 , p_4 , p_5 , p_6 , p_7 , p_8 , p_9 , p_{10} , and p_{11} are in a direction opposite to a direction of searching for a data stream dividing point. k_a is a data stream dividing point, and the direction of searching for a data stream dividing point shown in FIG. 13 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i , and a point p_{ix} is determined for the potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 13, according to the preset rule, 11 points are determined for the potential dividing point k_i , and are p_{i1} , p_{i2} , p_{i3} , p_{i4} , p_{i5} , p_{i6} , p_{i7} , p_{i8} , p_{i9} , p_{i10} , and p_{i11} separately, and windows corresponding to the points p_{i1} , p_{i2} , p_{i3} , p_{i4} , p_{i5} , p_{i6} ,

p_{i7} , p_{i8} , p_{i9} , p_{i10} , and p_{i11} are $W_{i1} [p_{i1}-169, p_{i1}]$, $W_{i2} [p_{i2}-169, p_{i2}]$, $W_{i3} [p_{i3}-169, p_{i3}]$, $W_{i4} [p_{i4}-169, p_{i4}]$, $W_{i5} [p_{i5}-169, p_{i5}]$, $W_{i6} [p_{i6}-169, p_{i6}]$, $W_{i7} [p_{i7}-169, p_{i7}]$, $W_{i8} [p_{i8}-169, p_{i8}]$, $W_{i9} [p_{i9}-169, p_{i9}]$, $W_{i10} [p_{i10}-169, p_{i10}]$, and $W_{i11} [p_{i11}-169, p_{i11}]$ respectively. A distance between p_{ix} and the potential dividing point k_i is d_x bytes.

- 5 Specifically, a distance between p_{i1} and k_i is 0 byte, a distance between p_{i2} and k_i is 2 bytes, a distance between p_{i3} and k_i is 4 bytes, a distance between p_{i4} and k_i is 6 bytes, a distance between p_{i5} and k_i is 8 bytes, a distance between p_{i6} and k_i is 10 bytes, a distance between p_{i7} and k_i is 12 bytes, a distance between p_{i8} and k_i is 14 bytes, a distance between p_{i9} and k_i is 16 bytes, a distance between p_{i10} and k_i is 18 bytes, a distance between p_{i11} and k_i
- 10 is 20 bytes, and relative to the potential dividing point k_i , all p_{i2} , p_{i3} , p_{i4} , p_{i5} , p_{i6} , p_{i7} , p_{i8} , p_{i9} , p_{i10} , and p_{i11} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets a preset condition C_1 , it is determined whether at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , it is determined whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset
- 15 condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [p_{i8}-169, p_{i8}]$ meets a preset
- 20 condition C_8 , it is determined whether at least a part of data in $W_{i9} [p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11} [p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset
- 25 condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at

least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, for example, as shown in FIG. 14, the at least a part of data in W_{i4} [$p_{i4}-169$, p_{i4}] does not meet the preset condition C_4 , a next potential dividing point is selected. For differentiation from the potential dividing point k_i , the next potential dividing point is represented as k_j here, where k_j is located on the right of k_i , and a distance between k_j and k_i is 1 byte. As shown in FIG. 14, according to the rule preset on the deduplication server 103, 11 points are determined for the potential dividing point k_j , and are p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} separately, and windows corresponding to the points p_{j1} , p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} are determined, and are W_{j1} [$p_{j1}-169$, p_{j1}], W_{j2} [$p_{j2}-169$, p_{j2}], W_{j3} [$p_{j3}-169$, p_{j3}], W_{j4} [$p_{j4}-169$, p_{j4}], W_{j5} [$p_{j5}-169$, p_{j5}], W_{j6} [$p_{j6}-169$, p_{j6}], W_{j7} [$p_{j7}-169$, p_{j7}], W_{j8} [$p_{j8}-169$, p_{j8}], W_{j9} [$p_{j9}-169$, p_{j9}], W_{j10} [$p_{j10}-169$, p_{j10}], and W_{j11} [$p_{j11}-169$, p_{j11}] respectively, where $A_1=A_2=A_3=A_4=A_5=A_6=A_7=A_8=A_9=A_{10}=A_{11}=169$, $B_1=B_2=B_3=B_4=B_5=B_6=B_7=B_8=B_9=B_{10}=B_{11}=0$, and $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$. A distance between p_{jx} and the potential dividing point k_j is d_x bytes. Specifically, a distance between p_{j1} and k_j is 0 byte, a distance between p_{j2} and k_j is 2 bytes, a distance between p_{j3} and k_j is 4 bytes, a distance between p_{j4} and k_j is 6 bytes, a distance between p_{j5} and k_j is 8 bytes, a distance between p_{j6} and k_j is 10 bytes, a distance between p_{j7} and k_j is 12 bytes, a distance between p_{j8} and k_j is 14 bytes, a distance between p_{j9} and k_j is 16 bytes, a distance between p_{j10} and k_j is 18 bytes, a distance between p_{j11} and k_j is 20 bytes, and relative to the potential dividing point k_j , all p_{j2} , p_{j3} , p_{j4} , p_{j5} , p_{j6} , p_{j7} , p_{j8} , p_{j9} , p_{j10} , and p_{j11} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in W_{j1} [$p_{j1}-169$, p_{j1}] meets the preset condition C_1 , it is determined whether at least a part of data in W_{j2} [$p_{j2}-169$, p_{j2}] meets the preset condition C_2 , it is determined whether at least a part of data in W_{j3} [$p_{j3}-169$, p_{j3}] meets the preset condition C_3 , it is determined whether at least a part of

data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point. When it is determined that the at least a part of data in any window of the windows $W_{j1}, W_{j2}, W_{j3}, W_{j4}, W_{j5}, W_{j6}, W_{j7}, W_{j8}, W_{j9}, W_{j10}$, and W_{j11} does not meet the preset condition, for example, as shown in FIG. 15, when the at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ does not meet the preset condition C_3 , the point p_{i4} is located on the left of the point p_{j3} relative to the direction of searching for a data stream dividing point, and 21 bytes are skipped from the point p_{i4} along the direction of searching for a data stream dividing point, so as to obtain a next potential dividing point. For differentiation from the potential dividing points k_i and k_j , the next potential dividing point is represented as k_l . According to the rule preset on the deduplication server 103 in the implementation manner shown in FIG. 13, 11 points are determined for the potential dividing point k_l , and are $p_{l1}, p_{l2}, p_{l3}, p_{l4}, p_{l5}, p_{l6}, p_{l7}, p_{l8}, p_{l9}, p_{l10}$, and p_{l11} separately, windows corresponding to the

points $p_{11}, p_{12}, p_{13}, p_{14}, p_{15}, p_{16}, p_{17}, p_{18}, p_{19}, p_{110}$, and p_{111} are $W_{11}[p_{11}-169, p_{11}]$, $W_{12}[p_{12}-169, p_{12}]$, $W_{13}[p_{13}-169, p_{13}]$, $W_{14}[p_{14}-169, p_{14}]$, $W_{15}[p_{15}-169, p_{15}]$, $W_{16}[p_{16}-169, p_{16}]$, $W_{17}[p_{17}-169, p_{17}]$, $W_{18}[p_{18}-169, p_{18}]$, $W_{19}[p_{19}-169, p_{19}]$, $W_{110}[p_{110}-169, p_{110}]$, and $W_{111}[p_{111}-169, p_{111}]$ respectively, where a distance between p_{lx} and the potential dividing point k_l is d_x bytes. Specifically, a distance between p_{11} and the potential dividing point k_l is 0 byte, a distance between p_{12} and k_l is 2 bytes, a distance between p_{13} and k_l is 4 bytes, a distance between p_{14} and k_l is 6 bytes, a distance between p_{15} and k_l is 8 bytes, a distance between p_{16} and k_l is 10 bytes, a distance between p_{17} and k_l is 12 bytes, a distance between p_{18} and k_l is 14 bytes, a distance between p_{19} and k_l is 16 bytes, a distance between p_{110} and k_l is 18 bytes, a distance between p_{111} and k_l is 20 bytes, and relative to the potential dividing point k_l , all $p_{12}, p_{13}, p_{14}, p_{15}, p_{16}, p_{17}, p_{18}, p_{19}, p_{110}$, and p_{111} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{11}[p_{11}-169, p_{11}]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{12}[p_{12}-169, p_{12}]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{13}[p_{13}-169, p_{13}]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{14}[p_{14}-169, p_{14}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{15}[p_{15}-169, p_{15}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{16}[p_{16}-169, p_{16}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{17}[p_{17}-169, p_{17}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{18}[p_{18}-169, p_{18}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{19}[p_{19}-169, p_{19}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{110}[p_{110}-169, p_{110}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{111}[p_{111}-169, p_{111}]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{11} meets the preset condition C_1 , the at least a part of data in the window W_{12} meets the preset condition C_2 , the at least a part of data in the window W_{13} meets the preset condition C_3 , the at least a part of data in the window W_{14} meets the preset condition C_4 , the at least a part of data in the window W_{15} meets the preset condition C_5 , the at least a part of data in the window W_{16} meets the preset condition C_6 , the at least a part of data in the window W_{17}

meets the preset condition C_7 , the at least a part of data in the window W_{l8} meets the preset condition C_8 , the at least a part of data in the window W_{l9} meets the preset condition C_9 , the at least a part of data in the window W_{l10} meets the preset condition C_{10} , and the at least a part of data in the window W_{l11} meets the preset condition C_{11} , the current potential dividing point k_l is a data stream dividing point. When the at least a part of data in any window of the windows W_{l1} , W_{l2} , W_{l3} , W_{l4} , W_{l5} , W_{l6} , W_{l7} , W_{l8} , W_{l9} , W_{l10} , and W_{l11} does not meet the preset condition, a next potential dividing point is selected. For differentiation from the potential dividing points k_i , k_j , and k_l , the next potential dividing point is represented as k_m , where k_m is located on the right of k_l , and a distance between k_m and k_l is 1 byte. According to the rule preset on the deduplication server 103 in the embodiment shown in FIG. 13, 11 points are determined for the potential dividing point k_m , and are p_{m1} , p_{m2} , p_{m3} , p_{m4} , p_{m5} , p_{m6} , p_{m7} , p_{m8} , p_{m9} , p_{m10} , and p_{m11} separately, and windows corresponding to the points p_{m1} , p_{m2} , p_{m3} , p_{m4} , p_{m5} , p_{m6} , p_{m7} , p_{m8} , p_{m9} , p_{m10} , and p_{m11} are $W_{m1}[p_{m1}-169, p_{m1}]$, $W_{m2}[p_{m2}-169, p_{m2}]$, $W_{m3}[p_{m3}-169, p_{m3}]$, $W_{m4}[p_{m4}-169, p_{m4}]$, $W_{m5}[p_{m5}-169, p_{m5}]$, $W_{m6}[p_{m6}-169, p_{m6}]$, $W_{m7}[p_{m7}-169, p_{m7}]$, $W_{m8}[p_{m8}-169, p_{m8}]$, $W_{m9}[p_{m9}-169, p_{m9}]$, $W_{m10}[p_{m10}-169, p_{m10}]$, and $W_{m11}[p_{m11}-169, p_{m11}]$ respectively, where a distance between p_{mx} and the potential dividing point k_m is d_x bytes. Specifically, a distance between p_{m1} and the potential dividing point k_m is 0 byte, a distance between p_{m2} and k_m is 2 bytes, a distance between p_{m3} and k_m is 4 bytes, a distance between p_{m4} and k_m is 6 bytes, a distance between p_{m5} and k_m is 8 bytes, a distance between p_{m6} and k_m is 10 bytes, a distance between p_{m7} and k_m is 12 bytes, a distance between p_{m8} and k_m is 14 bytes, a distance between p_{m9} and k_m is 16 bytes, a distance between p_{m10} and k_m is 18 bytes, a distance between p_{m11} and k_m is 20 bytes, and relative to the potential dividing point k_m , all p_{m2} , p_{m3} , p_{m4} , p_{m5} , p_{m6} , p_{m7} , p_{m8} , p_{m9} , p_{m10} , and p_{m11} are in a direction opposite to the direction of searching for a data stream dividing point. It is determined whether at least a part of data in $W_{m1}[p_{m1}-169, p_{m1}]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{m2}[p_{m2}-169, p_{m2}]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{m3}[p_{m3}-169, p_{m3}]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{m4}[p_{m4}-169, p_{m4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in W_{m5}

$[p_{m5}-169, p_{m5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{m6}[p_{m6}-169, p_{m6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{m7}[p_{m7}-169, p_{m7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{m8}[p_{m8}-169, p_{m8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{m9}[p_{m9}-169, p_{m9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{m10}[p_{m10}-169, p_{m10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{m11}[p_{m11}-169, p_{m11}]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{m1} meets the preset condition C_1 , the at least a part of data in the window W_{m2} meets the preset condition C_2 , the at least a part of data in the window W_{m3} meets the preset condition C_3 , the at least a part of data in the window W_{m4} meets the preset condition C_4 , the at least a part of data in the window W_{m5} meets the preset condition C_5 , the at least a part of data in the window W_{m6} meets the preset condition C_6 , the at least a part of data in the window W_{m7} meets the preset condition C_7 , the at least a part of data in the window W_{m8} meets the preset condition C_8 , the at least a part of data in the window W_{m9} meets the preset condition C_9 , the at least a part of data in the window W_{m10} meets the preset condition C_{10} , and the at least a part of data in the window W_{m11} meets the preset condition C_{11} , the current potential dividing point k_m is a data stream dividing point. When the at least a part of data in any window does not meet the preset condition, skipping is executed according to the solution described above, so as to obtain a next potential dividing point, and it is determine whether the next potential dividing point is a data stream dividing point.

[0120] An embodiment of the present invention provides a method for determining whether at least a part of data in a window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets a preset condition C_z . In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets the preset condition C_z , and the implementation manner shown in FIG. 5 is used as an example. According to a rule preset on a deduplication server 103, a point p_{i1} and a window $W_{i1}[p_{i1}-169, p_{i1}]$ corresponding to the point p_{i1} are determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 . As shown in FIG. 16, W_{i1} represents the window $W_{i1}[p_{i1}-169, p_{i1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$

meets the preset condition C_1 . In FIG. 16, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the 255

5 bytes, and therefore, bits corresponding to the 255 bytes may be represented as:

$$\begin{pmatrix} a_{1,1} & a_{1,2} & \cdots & a_{1,8} \\ a_{2,1} & a_{2,2} & \cdots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{255,1} & a_{255,2} & \cdots & a_{255,8} \end{pmatrix}, \text{ where when } a_{m,n}=1, V_{am,n}=1, \text{ and when } a_{m,n}=0, V_{am,n}=-1, \text{ where } a_{m,n}$$

represents any one of $a_{m,1}$, ..., and $a_{m,8}$, and a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the 255 bytes, and may be

represented as:
$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \cdots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \cdots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{a255,1} & V_{a255,2} & \cdots & V_{a255,8} \end{pmatrix}.$$
 A large quantity of random numbers is selected to

10 form a matrix, and once being formed, the matrix formed by the random numbers remains unchanged. For example, 255*8 random numbers are selected from random numbers that follow specific distribution (normal distribution is used as an example here) to form a matrix R:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,8} \end{pmatrix}, \text{ where random numbers of an mth row of the matrix } V_a \text{ and an mth}$$

row of the matrix R are multiplied and products are added to obtain a value, which is specifically
15 represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$. S_{a1} , S_{a2} , ..., and S_{a255} are obtained according to the method, and a quantity K of values meeting a specific condition (being greater than 0 is used as an example here) among S_{a1} , S_{a2} , ..., and S_{a255} is counted. Because the matrix R follows normal distribution, S_{am} still follows normal distribution as the matrix R does. According to a probability theory, a probability that a random number in normal distribution is greater than 0 is
20 1/2; a probability that each value among S_{a1} , S_{a2} , ..., and S_{a255} is greater than 0 is 1/2, and

therefore, K meets binomial distribution: $P(k=n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$. According to a counting result, it is determined whether the quantity K of values greater than 0 among S_{a1} ,

S_{a_2} , ..., and $S_{a_{255}}$ is an even number; a probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . When K is an odd number, it indicates that the at least a part of data in $W_{i1}[p_{i1}-169,$

5 $p_{i1}]$ does not meet the preset condition C_1 . C_1 here refers to that the quantity K, which is obtained according to the foregoing manner, of values greater than 0 among S_{a_1} , S_{a_2} , ..., and $S_{a_{255}}$ is an even number. In the implementation manner shown in FIG. 5, for $W_{i1}[p_{i1}-169, p_{i1}]$, $W_{i2}[p_{i2}-169, p_{i2}]$, $W_{i3}[p_{i3}-169, p_{i3}]$, $W_{i4}[p_{i4}-169, p_{i4}]$, $W_{i5}[p_{i5}-169, p_{i5}]$, $W_{i6}[p_{i6}-169, p_{i6}]$, $W_{i7}[p_{i7}-169, p_{i7}]$, $W_{i8}[p_{i8}-169, p_{i8}]$, $W_{i9}[p_{i9}-169, p_{i9}]$, $W_{i10}[p_{i10}-169,$
10 $p_{i10}]$, and $W_{i11}[p_{i11}-169, p_{i11}]$, the windows are the same in size, that is, all the windows have a size of 169 bytes, and manners of determining whether at least a part of data in a window meets a preset condition are also the same. For details, refer to the foregoing description of determining whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, as shown in FIG. 16, "" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i2}[p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $b_{m,1}$, ..., and $b_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits corresponding to the 255 bytes may be represented as:

20
$$\begin{pmatrix} b_{1,1} & b_{1,2} & \cdots & b_{1,8} \\ b_{2,1} & b_{2,2} & \cdots & b_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ b_{255,1} & b_{255,2} & \cdots & b_{255,8} \end{pmatrix}, \text{ where when } b_{m,n}=1, V_{bm,n}=1, \text{ and when } b_{m,n}=0, V_{bm,n}=-1, \text{ where}$$

$b_{m,n}$ represents any one of $b_{m,1}$, ..., and $b_{m,8}$, and a matrix V_b is obtained according to a conversion relationship between $b_{m,n}$ and $V_{bm,n}$ from the bits corresponding to the 255 bytes, and

may be represented as:
$$\begin{pmatrix} V_{b1,1} & V_{b1,2} & \cdots & V_{b1,8} \\ V_{b2,1} & V_{b2,2} & \cdots & V_{b2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{b255,1} & V_{b255,2} & \cdots & V_{b255,8} \end{pmatrix}.$$
 A manner of determining whether at least a

part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition is the same as a manner of determining
25 whether at least a part of data in the window $W_{i2}[p_{i2}-169, p_{i2}]$ meets a preset condition;

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,8} \end{pmatrix}$$

therefore the matrix R is used: $\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,8} \end{pmatrix}$, and random numbers of an mth row of the matrix V_b and the mth row of the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{bm} = V_{bm,1} * h_{m,1} + V_{bm,2} * h_{m,2} + \dots + V_{bm,8} * h_{m,8}$. S_{b1} , S_{b2} , ..., and S_{b255} are obtained according to the method, and a quantity K of values meeting a specific condition (being greater than 0 is used as an example here) among S_{b1} , S_{b2} , ..., and S_{b255} is counted. Because the matrix R follows normal distribution, S_{bm} still follows normal distribution as the matrix R does. According to the probability theory, the probability that a random number in normal distribution is greater than 0 is 1/2; a probability that each value among S_{b1} , S_{b2} , ..., and S_{b255} is greater than 0 is 1/2, and therefore, K meets binomial distribution:

10 $P(k = n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$. According to a counting result, it is determined whether the quantity K of values greater than 0 among S_{b1} , S_{b2} , ..., and S_{b255} is an even number; the probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 . When K is an odd number, it indicates that the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ does not meet the preset condition C_2 . C_2 here refers to that the quantity K, which is obtained according to the foregoing manner, of values greater than 0 among S_{b1} , S_{b2} , ..., and S_{b255} is an even number. In the implementation manner shown in FIG. 3, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 .

20 **[0121]** Therefore, as shown in FIG. 16, "" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Then, the method for determining whether at least a part of data in the windows $W_{i1} [p_{i1}-169, p_{i1}]$ and $W_{i2} [p_{i2}-169, p_{i2}]$ meets a preset condition is used to determine whether the at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets the preset condition C_3 . In the implementation manner shown in FIG. 5, the at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets the preset condition. As shown in FIG. 16, ""

represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Then, the method for determining whether at least a part of data in windows $W_{i1} [p_{i1}-169, p_{i1}]$, $W_{i2} [p_{i2}-169, p_{i2}]$, and $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition is used to determine whether the at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets the preset condition C_4 . In the implementation manner shown in FIG. 5, the at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets the preset condition C_4 . As shown in FIG. 16, "田" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Then, the method for determining whether at least a part of data in the windows $W_{i1} [p_{i1}-169, p_{i1}]$, $W_{i2} [p_{i2}-169, p_{i2}]$, $W_{i3} [p_{i3}-169, p_{i3}]$, and $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition is used to determine whether the at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets the preset condition C_5 . In the implementation manner shown in FIG. 5, the at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 .

[0122] When the at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , 11 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a next potential dividing point k_j is obtained at an end position of an 11th byte. As shown in FIG. 6, according to the rule preset on the deduplication server 103, a point p_{j1} and a window $W_{j1} [p_{j1}-169, p_{j1}]$ corresponding to the point p_{j1} are determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1} [p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, as shown in FIG. 17, W_{j1} represents the window $W_{j1} [p_{j1}-169, p_{j1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{j1} [p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $a_{m,1}'$, ..., and

$a_{m,8}'$, representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits

corresponding to the 255 bytes may be represented as: $\begin{pmatrix} a_{1,1}' & a_{1,2}' & \dots & a_{1,8}' \\ a_{2,1}' & a_{2,2}' & \dots & a_{2,8}' \\ \vdots & \vdots & \vdots & \vdots \\ a_{255,1}' & a_{255,2}' & \dots & a_{255,8}' \end{pmatrix}$, where when

$a_{m,n}'=1$, $V_{am,n}'=1$, and when $a_{m,n}'=0$, $V_{am,n}'=-1$, where $a_{m,n}'$ represents any one of $a_{m,1}'$, ..., and $a_{m,8}'$, and a matrix V_a' is obtained according to a conversion relationship between $a_{m,n}'$ and

5 $V_{am,n}'$ from the bits corresponding to the 255 bytes, and may be represented as:

$\begin{pmatrix} V_{a1,1}' & V_{a1,2}' & \dots & V_{a1,8}' \\ V_{a2,1}' & V_{a2,2}' & \dots & V_{a2,8}' \\ \vdots & \vdots & \vdots & \vdots \\ V_{a255,1}' & V_{a255,2}' & \dots & V_{a255,8}' \end{pmatrix}$. A manner of determining whether at least a part of data in the

window $W_{j1}[p_{j1}-169, p_{j1}]$ meets a preset condition is the same as a manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition.

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \dots & h_{255,8} \end{pmatrix}$$

Therefore, the matrix R is used: and random numbers of an mth row of

10 the matrix V_a' and the mth row of the matrix R are multiplied and products are added to obtain a

value, which is specifically represented as $S_{am}' = V_{am,1}' * h_{m,1} + V_{am,2}' * h_{m,2} + \dots + V_{am,8}' * h_{m,8}$. S_{a1}' ,

S_{a2}' , ..., and S_{a255}' are obtained according to the method, and a quantity K of values meeting a

specific condition (being greater than 0 is used as an example here) among S_{a1}' , S_{a2}' , ..., and

S_{a255}' is counted. Because the matrix R follows normal distribution, S_{am}' still follows normal

15 distribution as the matrix R does. According to the probability theory, the probability that a random

number in normal distribution is greater than 0 is 1/2; a probability that each value among S_{a1}' ,

S_{a2}' , ..., and S_{a255}' is greater than 0 is 1/2, and therefore, K meets binomial distribution:

$$P(k=n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$$

. According to a counting result, it is determined whether

the quantity K of values greater than 0 among S_{a1}' , S_{a2}' , ..., and S_{a255}' is an even number; the

20 probability that a random number in binomial distribution is an even number is 1/2, and therefore,

K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at

least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . When K is an odd number, it indicates that the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ does not meet the preset condition C_1 .

[0123] A manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets

the preset condition C_2 is the same as a manner of determining whether at least a part of data in

$W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . Therefore, as shown in FIG. 17, "

represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent

selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so

as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $b_{m,1}'$, ...,

and $b_{m,8}'$, representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits

corresponding to the 255 bytes may be represented as:
$$\begin{pmatrix} b_{1,1}' & b_{1,2}' & \dots & b_{1,8}' \\ b_{2,1}' & b_{2,2}' & \dots & b_{2,8}' \\ \vdots & \vdots & \vdots & \vdots \\ b_{255,1}' & b_{255,2}' & \dots & b_{255,8}' \end{pmatrix}$$
, where when

$b_{m,n}'=1$, $V_{bm,n}'=1$, and when $b_{m,n}'=0$, $V_{bm,n}'=-1$, where $b_{m,n}'$ represents any one of $b_{m,1}'$, ..., and

$b_{m,8}'$, and a matrix V_b' is obtained according to a conversion relationship between $b_{m,n}'$ and

$V_{bm,n}'$ from the bits corresponding to the 255 bytes, and may be represented as:

$$\begin{pmatrix} V_{b1,1} & V_{b1,2} & \dots & V_{b1,8} \\ V_{b2,1} & V_{b2,2} & \dots & V_{b2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{b255,1} & V_{b255,2} & \dots & V_{b255,8} \end{pmatrix}$$
. Manners of determining whether at least a part of data in windows

$W_2[p_2-169, p_2]$ and $W_2[q_2-169, q_2]$ meets a preset condition are the same, and therefore the

matrix R is still used:
$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \dots & h_{255,8} \end{pmatrix}$$
. Random numbers of an mth row of the matrix

V_b' and the mth row of the matrix R are multiplied and products are added to obtain a value, which

is specifically represented as $S_{bm}' = V_{bm,1}' * h_{m,1} + V_{bm,2}' * h_{m,2} + \dots + V_{bm,8}' * h_{m,8}$. S_{b1}' , S_{b2}' , ..., and

S_{b255}' are obtained according to the method, and a quantity K of values meeting a specific

condition (being greater than 0 is used as an example here) among S_{b1}' , S_{b2}' , ..., and S_{b255}' is counted. Because the matrix R follows normal distribution, S_{bm}' still follows normal distribution as the matrix R does. According to the probability theory, the probability that a random number in normal distribution is greater than 0 is 1/2; a probability that each value among S_{b1}' , S_{b2}' , ..., and S_{b255}' is greater than 0 is 1/2, and therefore, K meets binomial distribution:

$$P(k = n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$$

. According to a counting result, it is determined whether the quantity K of values greater than 0 among S_{b1}' , S_{b2}' , ..., and S_{b255}' is an even number; the probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . When K is an odd number, it indicates that the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ does not meet the preset condition C_2 . Similarly, a manner of determining whether at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets a preset condition C_{11} , which are not described herein again.

[0124] Still using the implementation manner shown in FIG. 5 as an example, a method for determining whether at least a part of data in a window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets a preset condition C_z is provided. In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets the preset condition

C_z . According to a rule preset on a deduplication server 103, a point p_{i1} and a window $W_{i1}[p_{i1}-169, p_{i1}]$ corresponding to p_{i1} are determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 . As shown in FIG. 16, W_{i1} represents the window $W_{i1}[p_{i1}-169, p_{i1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . In FIG. 16, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes "■". In one implementation manner, a hash function is used to calculate the 5 selected bytes, and values obtained by means of calculation by using the hash function are in fixed and even distribution. If a value obtained by means of calculation by using the hash function is an even number, it is determined that the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 , that is, C_1 represents that a value obtained by means of calculation by using the hash function and according to the foregoing manner is an even number. Therefore, a probability that at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition is 1/2. In the implementation manner shown in FIG. 5, it is determined, by using a hash function, whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets a preset condition C_2 , whether at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , whether at least a part of data in $W_{i4}[p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , and whether at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ meets a preset condition C_5 . For specific implementation, reference may be made to the description of the manner of determining, by using a hash function, whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 in the implementation manner shown in FIG. 5, which is not described herein again.

[0125] When the at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , 11 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of an 11th byte. As shown in FIG. 6, according to the rule preset on the deduplication server 103, a point p_{j1} and a window $W_{j1}[p_{j1}-169, p_{j1}]$ corresponding to the point p_{j1} are determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore,

as shown in FIG. 17, W_{j1} represents the window $W_{j1}[p_{j1}-169, p_{j1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes "■". The 5 bytes selected from the window $W_{j1}[p_{j1}-169, p_{j1}]$ are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, a manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . Therefore, as shown in FIG. 17, "⊠" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes "⊠". Selected 5 bytes are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . In FIG. 17, a manner of determining whether at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . Therefore, as shown in FIG. 17, "▨" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 , and there are 42 bytes between two adjacent selected bytes "▨". Selected 5 bytes are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . In FIG. 17, a manner of determining whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 is the same as a manner of determining whether at least a part of data in the window $W_{i4}[p_{i4}-169, p_{i4}]$ meets the preset condition C_4 . Therefore, as shown in FIG. 17, "▩" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , and there are 42 bytes between two adjacent selected bytes "▩". Selected 5 bytes are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 . According to the foregoing method, it is determined whether at least a part of data in

$W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets a preset condition C_{11} , which are not described herein again.

[0126] Using the implementation manner shown in FIG. 5 as an example, a method for determining whether at least a part of data in a window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets a preset condition C_z is provided. In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets the preset condition C_z . According to a rule preset on a deduplication server 103, a point p_{i1} and a window $W_{i1}[p_{i1}-169, p_{i1}]$ corresponding to p_{i1} are determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 . As shown in FIG. 16, W_{i1} represents the window $W_{i1}[p_{i1}-169, p_{i1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . In FIG. 16, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1, a_2, a_3, a_4 , and a_5 respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_r of a_1, a_2, a_3, a_4 , and a_5 meets $0 \leq a_r \leq 255$. a_1, a_2, a_3, a_4 , and a_5 form a 1*5 matrix. 256*5 random numbers are selected from random numbers that

follow binomial distribution to form a matrix R that is represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,5} \end{pmatrix}.$$

[0127] The matrix R is searched for a corresponding value according to the value of a_1 and a column in which a_1 is located. For example, if $a_1=36$, and a_1 is located in a 1st column, a

value corresponding to $h_{36,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_2 and a column in which a_2 is located. For example, if $a_2=48$, and a_2 is located in a 2nd column, a value corresponding to $h_{48,2}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_3 and a column in which a_3 is located. For example, if $a_3=26$, and a_3 is located in a 3rd column, a value corresponding to $h_{26,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_4 and a column in which a_4 is located. For example, if $a_4=26$, and a_4 is located in a 4th column, a value corresponding to $h_{26,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_5 and a column in which a_5 is located. For example, if $a_5=88$, and a_5 is located in a 5th column, a value corresponding to $h_{88,5}$ is searched for. $S_1 = h_{36,1} + h_{48,2} + h_{26,3} + h_{26,4} + h_{88,5}$, and because the matrix R follows binomial distribution, S_1 also follows binomial distribution. When S_1 is an even number, the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 ; when S_1 is an odd number, the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ does not meet the preset condition C_1 . A probability that S_1 is an even number is 1/2, and C_1 represents that S_1 that is obtained by means of calculation according to the foregoing manner is an even number. In the embodiment shown in FIG. 5, the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . As shown in FIG. 16, "☒" represents 1 byte separately selected when it is determined whether at least a part of data in a window $W_{i2} [p_{i2}-169, p_{i2}]$ meets a preset condition C_2 . In FIG. 16, bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "☒" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1, b_2, b_3, b_4 , and b_5 respectively. Because 1 byte is formed by 8 bits, each byte "☒" serves as a value, and any b_r of b_1, b_2, b_3, b_4 , and b_5 meets $0 \leq b_r \leq 255$. b_1, b_2, b_3, b_4 , and b_5 form a 1*5 matrix. In this implementation manner, manners of determining whether at least a part of data in W_{i1} and W_{i2} meets a preset condition are the same, and therefore, the matrix R is still used. The matrix R is searched for a corresponding value according to the value of b_1 and a column in which b_1 is located. For example, if $b_1=66$, and b_1 is located in a 1st column, a value corresponding to $h_{66,1}$ is searched for. The matrix R is searched for a

corresponding value according to the value of b_2 and a column in which b_2 is located. For example, if $b_2=48$, and b_2 is located in a 2nd column, a value corresponding to $h_{48,2}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_3 and a column in which b_3 is located. For example, if $b_3=99$, and b_3 is located in a 3rd column, a value corresponding to $h_{99,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_4 and a column in which b_4 is located. For example, if $b_4=26$, and b_4 is located in a 4th column, a value corresponding to $h_{26,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_5 and a column in which b_5 is located. For example, if $b_5=90$, and b_5 is located in a 5th column, a value corresponding to $h_{90,5}$ is searched for. $S_2 = h_{66,1} + h_{48,2} + h_{99,3} + h_{26,4} + h_{90,5}$, and because the matrix R follows binomial distribution, S_2 also follows binomial distribution. When S_2 is an even number, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 ; when S_2 is an odd number, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ does not meet the preset condition C_2 . A probability that S_2 is an even number is 1/2. In the embodiment shown in FIG. 5, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 . By using the same rule, separately, it is determined whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9} [p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11} [p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . In the implementation manner shown in FIG. 5, the at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , 11 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of an 11th byte. As shown in FIG. 6, according to the rule preset on the deduplication

server 103, a point p_{j1} and a window $W_{j1}[p_{j1}-169, p_{j1}]$ corresponding to the point p_{j1} are determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, as shown in FIG. 17, W_{j1} represents the window $W_{j1}[p_{j1}-169, p_{j1}]$, and it is determined whether the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1' , a_2' , a_3' , a_4' , and a_5' respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_r' of a_1' , a_2' , a_3' , a_4' , and a_5' meets $0 \leq a_r' \leq 255$. a_1' , a_2' , a_3' , a_4' , and a_5' form a 1*5 matrix. The manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as the manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 , and therefore, the matrix R is still used, and is represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,5} & h_{255,5} & \cdots & h_{255,5} \end{pmatrix}.$$

[0128] The matrix R is searched for a corresponding value according to the value of a_1' and a column in which a_1' is located. For example, if $a_1'=16$, and a_1' is located in a 1st column, a value corresponding to $h_{16,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_2' and a column in which a_2' is located. For example, if $a_2'=98$, and a_2' is located in a 2nd column, a value corresponding to $h_{98,2}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_3' and a column in which a_3' is located. For example, if $a_3'=56$, and a_3' is located in a 3rd column, a value corresponding to $h_{56,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_4' and a column in which a_4' is located. For example, if $a_4'=36$, and a_4' is located in a 4th column, a value corresponding to $h_{36,4}$ is searched for. The matrix R is searched for a

corresponding value according to the value of a_5' and a column in which a_5' is located. For example, if $a_5'=99$, and a_5' is located in a 5th column, a value corresponding to $h_{99,5}$ is searched for. $S_1' = h_{16,1} + h_{98,2} + h_{56,3} + h_{36,4} + h_{99,5}$, and because the matrix R follows binomial distribution, S_1' also follows binomial distribution. When S_1' is an even number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 ; when S_1' is an odd number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ does not meet the preset condition C_1 . A probability that S_1' is an even number is 1/2.

[0129] A manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in

10 $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . Therefore, as shown in FIG. 17, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. Selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "" whose
15 sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1' , b_2' , b_3' , b_4' , and b_5' respectively. Because 1 byte is formed by 8 bits, each byte "" serves as a value, and any b_r' of b_1' , b_2' , b_3' , b_4' , and b_5' meets $0 \leq b_r' \leq 255$. b_1' , b_2' , b_3' , b_4' and b_5' form a 1*5 matrix. The matrix R the same as that used when it is determined whether the at least a part of data in the window $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is
20 used. The matrix R is searched for a corresponding value according to the value of b_1' and a column in which b_1' is located. For example, if $b_1'=210$, and b_1' is located in a 1st column, a value corresponding to $h_{210,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_2' and a column in which b_2' is located. For example, if $b_2'=156$, and b_2' is located in a 2nd column, a value corresponding to $h_{156,2}$ is searched for. The matrix R is
25 searched for a corresponding value according to the value of b_3' and a column in which b_3' is located. For example, if $b_3'=144$, and b_3' is located in a 3rd column, a value corresponding to $h_{144,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_4' and a column in which b_4' is located. For example, if $b_4'=60$, and b_4' is located in a 4th

column, a value corresponding to $h_{60,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_5' and a column in which b_5' is located. For example, if $b_5'=90$, and b_5' is located in a 5th column, a value corresponding to $h_{90,5}$ is searched for. $S_2' = h_{210,1} + h_{156,2} + h_{144,3} + h_{60,4} + h_{90,5}$. The same as the determining condition of S_2 , when S_2' is an even number, the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and when S_2' is an odd number, the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ does not meet the preset condition C_2 . A probability that S_2' is an even number is 1/2.

[0130] Similarly, a manner of determining whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets the preset condition C_{11} , which are not described herein again.

[0131] Using the implementation manner shown in FIG. 5 as an example, a method for determining whether at least a part of data in a window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets a preset condition C_z is provided. In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets the preset condition C_z . According to a rule preset on a deduplication server 103, a point p_{i1} and a window $W_{i1}[p_{i1}-169, p_{i1}]$ corresponding to p_{i1} are determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 . As shown in FIG. 16, W_{i1} represents the window $W_{i1}[p_{i1}-169, p_{i1}]$, and 5 bytes are selected to

determine whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 .

In FIG. 16, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1, a_2, a_3, a_4 , and a_5 respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_s of a_1, a_2, a_3, a_4 , and a_5 meets $0 \leq a_s \leq 255$. a_1, a_2, a_3, a_4 , and a_5 form a 1*5 matrix. 256*5 random numbers are selected from random numbers that follow

binomial distribution to form a matrix R that is represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,5} & h_{255,5} & \cdots & h_{255,5} \end{pmatrix} \cdot 256*5$$

random numbers are selected from random numbers that follow binomial distribution to form a

matrix G that is represented as:

$$\begin{pmatrix} g_{0,1} & g_{0,2} & \cdots & g_{0,5} \\ g_{1,1} & g_{1,2} & \cdots & g_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ g_{255,5} & g_{255,5} & \cdots & g_{255,5} \end{pmatrix}.$$

[0132] According to the value of a_1 and a column in which a_1 is located, for example, $a_1=36$, and a_1 is located in a 1st column, the matrix R is searched for a value corresponding to $h_{36,1}$, and the matrix G is searched for a value corresponding to $g_{36,1}$. According to the value of a_2 and a column in which a_2 is located, for example, $a_2=48$, and a_2 is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{48,2}$, and the matrix G is searched for a value corresponding to $g_{48,2}$. According to the value of a_3 and a column in which a_3 is located, for example, $a_3=26$, and a_3 is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{26,3}$, and the matrix G is searched for a value corresponding to $g_{26,3}$. According to the value of a_4 and a column in which a_4 is located, for example, $a_4=26$, and a_4 is located in a 4th column, the matrix R is searched for a value corresponding to $h_{26,4}$, and the matrix G is searched for a value corresponding to $g_{26,4}$. According to the value of a_5 and a column in which a_5 is located, for example, $a_5=88$, and a_5 is located in a 5th column, the matrix R is searched for a value corresponding to $h_{88,5}$, and the matrix G is searched for a value corresponding to $g_{88,5}$.

$S_{1h} = h_{36,1} + h_{48,2} + h_{26,3} + h_{26,4} + h_{88,5}$, and because the matrix R follows binomial distribution, S_{1h}

also follows binomial distribution. $S_{1g} = g_{36,1} + g_{48,2} + g_{26,3} + g_{26,4} + g_{88,5}$, and because the matrix G follows binomial distribution, S_{1g} also follows binomial distribution. When one of S_{1h} and S_{1g} is an even number, the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 ; when both S_{1h} and S_{1g} are odd numbers, the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ does not meet the preset condition C_1 , and C_1 indicates that one of S_{1h} and S_{1g} obtained according to the foregoing method is an even number. Because both S_{1h} and S_{1g} follow binomial distribution, a probability that S_{1h} is an even number is 1/2, a probability that S_{1g} is an even number is 1/2, and a probability that one of S_{1h} and S_{1g} is an even number is $1-1/4=3/4$. Therefore, a probability that the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 is 3/4. In the embodiment shown in FIG. 5, the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . In the implementation manner shown in FIG. 5, for $W_{i1} [p_{i1}-169, p_{i1}]$, $W_{i2} [p_{i2}-169, p_{i2}]$, $W_{i3} [p_{i3}-169, p_{i3}]$, $W_{i4} [p_{i4}-169, p_{i4}]$, $W_{i5} [p_{i5}-169, p_{i5}]$, $W_{i6} [p_{i6}-169, p_{i6}]$, $W_{i7} [p_{i7}-169, p_{i7}]$, $W_{i8} [p_{i8}-169, p_{i8}]$, $W_{i9} [p_{i9}-169, p_{i9}]$, $W_{i10} [p_{i10}-169, p_{i10}]$, and $W_{i11} [p_{i11}-169, p_{i11}]$, the windows are the same in size, that is, all the windows have a size of 169 bytes, and meanwhile manners of determining whether at least a part of data in a window meets a preset condition are also the same. For details, refer to the foregoing description of determining whether the at least a part of data in $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, as shown in FIG. 16, "" represents 1 byte separately selected when it is determined whether at least a part of data in the window $W_{i2} [p_{i2}-169, p_{i2}]$ meets a preset condition C_2 . In FIG. 16, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1 , b_2 , b_3 , b_4 , and b_5 respectively. Because 1 byte is formed by 8 bits, each byte "" serves as a value, and any b_s of b_1 , b_2 , b_3 , b_4 , and b_5 meets $0 \leq b_s \leq 255$. b_1 , b_2 , b_3 , b_4 , and b_5 form a 1*5 matrix. In this implementation manner, manners of determining whether at least a part of data in each window meets a preset condition are the same, and therefore, the same matrices R and G are still used. According to the value of b_1 and a column in which b_1 is located, for example, $b_1=66$, and b_1 is located in a 1st column, the matrix R is searched for a value

corresponding to $h_{66,1}$, and the matrix G is searched for a value corresponding to $g_{66,1}$. According to the value of b_2 and a column in which b_2 is located, for example, $b_2=48$, and b_2 is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{48,2}$, and the matrix G is searched for a value corresponding to $g_{48,2}$. According to the value of b_3 and a column in which b_3 is located, for example, $b_3=99$, and b_3 is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{99,3}$, and the matrix G is searched for a value corresponding to $g_{99,3}$. According to the value of b_4 and a column in which b_4 is located, for example, $b_4=26$, and b_4 is located in a 4th column, the matrix R is searched for a value corresponding to $h_{26,4}$, and the matrix G is searched for a value corresponding to $g_{26,4}$. According to the value of b_5 and a column in which b_5 is located, for example, $b_5=90$, and b_5 is located in a 5th column, the matrix R is searched for a value corresponding to $h_{90,5}$, and the matrix G is searched for a value corresponding to $g_{90,5}$. $S_{2h} = h_{66,1} + h_{48,2} + h_{99,3} + h_{26,4} + h_{90,5}$, and because the matrix R follows binomial distribution, S_{2h} also follows binomial distribution. $S_{2g} = g_{66,1} + g_{48,2} + g_{99,3} + g_{26,4} + g_{90,5}$, and because the matrix G follows binomial distribution, S_{2g} also follows binomial distribution.

When one of S_{2h} and S_{2g} is an even number, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 ; when both S_{2h} and S_{2g} are odd numbers, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ does not meet the preset condition C_2 . A probability that one of S_{2h} and S_{2g} is an even number is 3/4. In the embodiment shown in FIG. 5, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 . By using the same rule, separately, it is determined whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9} [p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} ,

and it is determined whether at least a part of data in $W_{i11}[p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . In the implementation manner shown in FIG. 5, the at least a part of data in $W_{i5}[p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , 11 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of an 11th byte. As shown in FIG. 6, according to the rule preset on the deduplication server 103, a point p_{j1} and a window $W_{j1}[p_{j1}-169, p_{j1}]$ corresponding to the point p_{j1} are determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, as shown in FIG. 17, W_{j1} represents the window $W_{j1}[p_{j1}-169, p_{j1}]$, and it is determined whether the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1' , a_2' , a_3' , a_4' , and a_5' respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_s' of a_1' , a_2' , a_3' , a_4' , and a_5' meets $0 \leq a_s' \leq 255$. a_1' , a_2' , a_3' , a_4' , and a_5' form a 1*5 matrix. The matrices R and G the same as those used when it is determined whether the at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$

meets the preset condition C_1 are used, and are represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,5} & h_{255,5} & \cdots & h_{255,5} \end{pmatrix} \text{ and}$$

20 $\begin{pmatrix} g_{0,1} & g_{0,2} & \cdots & g_{0,5} \\ g_{1,1} & g_{1,2} & \cdots & g_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ g_{255,5} & g_{255,5} & \cdots & g_{255,5} \end{pmatrix}$ respectively.

[0133] According to the value of a_1' and a column in which a_1' is located, for example, $a_1' = 16$, and a_1' is located in a 1st column, the matrix R is searched for a value corresponding to $h_{16,1}$, and the matrix G is searched for a value corresponding to $g_{16,1}$. According to the value of a_2' and a column in which a_2' is located, for example, $a_2' = 98$, and a_2' is located in a 2nd column, the

matrix R is searched for a value corresponding to $h_{98,2}$, and the matrix G is searched for a value corresponding to $g_{98,2}$. According to the value of a_3' and a column in which a_3' is located, for example, $a_3'=56$, and a_3' is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{56,3}$, and the matrix G is searched for a value corresponding to $g_{56,3}$. According to the value of a_4' and a column in which a_4' is located, for example, $a_4'=36$, and a_4' is located in a 4th column, the matrix R is searched for a value corresponding to $h_{36,4}$, and the matrix G is searched for a value corresponding to $g_{36,4}$. According to the value of a_5' and a column in which a_5' is located, for example, $a_5'=99$, and a_5' is located in a 5th column, the matrix R is searched for a value corresponding to $h_{99,5}$, and the matrix G is searched for a value corresponding to $g_{99,5}$. $S_{1h}' = h_{16,1} + h_{98,2} + h_{56,3} + h_{36,4} + h_{99,5}$, and because the matrix R follows binomial distribution, S_{1h}' also follows binomial distribution. $S_{1g}' = g_{16,1} + g_{98,2} + g_{56,3} + g_{36,4} + g_{99,5}$, and because the matrix G follows binomial distribution, S_{1g}' also follows binomial distribution. When one of S_{1h}' and S_{1g}' is an even number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 ; when both S_{1h}' and S_{1g}' are odd numbers, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ does not meet the preset condition C_1 . A probability that one of S_{1h}' and S_{1g}' is an even number is 3/4.

[0134] A manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . Therefore, as shown in FIG. 17, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. In FIG. 17, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1' , b_2' , b_3' , b_4' , and b_5' respectively. Because 1 byte is formed by 8 bits, each byte "" serves as a value, and any b_s' of b_1' , b_2' , b_3' , b_4' and b_5' meets $0 \leq b_s' \leq 255$. b_1' , b_2' , b_3' , b_4' , and b_5' form a 1*5 matrix. The matrices R and G the same as those used when it is

determined whether the at least a part of data in the window $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 are used. According to the value of b_1' and a column in which b_1' is located, for example, $b_1'=210$, and b_1' is located in a 1st column, the matrix R is searched for a value corresponding to $h_{210,1}$, and the matrix G is searched for a value corresponding to $g_{210,1}$.

5 According to the value of b_2' and a column in which b_2' is located, for example, $b_2'=156$, and b_2' is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{156,2}$, and the matrix G is searched for a value corresponding to $g_{156,2}$. According to the value of b_3' and a column in which b_3' is located, for example, $b_3'=144$, and b_3' is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{144,3}$, and the matrix G is searched for a value

10 corresponding to $g_{144,3}$. According to the value of b_4' and a column in which b_4' is located, for example, $b_4'=60$, and b_4' is located in a 4th column, the matrix R is searched for a value corresponding to $h_{60,4}$, and the matrix G is searched for a value corresponding to $g_{60,4}$. According to the value of b_5' and a column in which b_5' is located, for example, $b_5'=90$, and b_5' is located in a 5th column, the matrix R is searched for a value corresponding to $h_{90,5}$, and the matrix

15 G is searched for a value corresponding to $g_{90,5}$. $S_{2h}' = h_{210,1} + h_{156,2} + h_{144,3} + h_{60,4} + h_{90,5}$, $S_{2g}' = g_{210,1} + g_{156,2} + g_{144,3} + g_{60,4} + g_{90,5}$. When one of S_{2h}' and S_{2g}' is an even number, the at least a part of data in $W_{j2} [p_{j2}-169, p_{j2}]$ meets the preset condition C_2 ; when both S_{2h}' and S_{2g}' are odd numbers, the at least a part of data in $W_{j2} [p_{j2}-169, p_{j2}]$ does not meet the preset condition C_2 . A probability that one of S_{2h}' and S_{2g}' is an even number is 3/4.

20 **[0135]** Similarly, a manner of determining whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3} [p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4} [p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5} [p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined

25 whether at least a part of data in $W_{j6} [p_{j6}-169, p_{j6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7} [p_{j7}-169, p_{j7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8} [p_{j8}-169, p_{j8}]$ meets the preset condition C_8 ,

it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets the preset condition C_{11} , which are not described herein again.

5 **[0136]** Using the implementation manner shown in FIG. 5 as an example, a method for determining whether at least a part of data in a window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets a preset condition C_z is provided. In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets the preset condition C_z . According to a rule preset on a deduplication server 103, a point p_{i1} and a window $W_{i1}[p_{i1}$
10 $-169, p_{i1}]$ corresponding to p_{i1} are determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets a preset condition C_1 . As shown in FIG. 16, W_{i1} represents the window $W_{i1}[p_{i1}-169, p_{i1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 .
In FIG. 16, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1
15 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are regarded as 40 sequential bits, which are represented as $a_1, a_2, a_3, a_4, \dots$, and a_{40} separately. For any a_t of $a_1, a_2, a_3, a_4, \dots$, and a_{40} , when $a_t=0$, $V_{at}=-1$, and when $a_t=1$, $V_{at}=1$. According to a correspondence between a_t and V_{at} , $V_{a1}, V_{a2}, V_{a3}, V_{a4}, \dots$, and V_{a40} are generated. 40 random numbers are selected
20 from random numbers that follow normal distribution, and are represented as: $h_1, h_2, h_3, h_4, \dots$, and h_{40} separately. $S_a = V_{a1} * h_1 + V_{a2} * h_2 + V_{a3} * h_3 + V_{a4} * h_4 + \dots + V_{a40} * h_{40}$. Because $h_1, h_2, h_3, h_4, \dots$, and h_{40} follow normal distribution, S_a also follows normal distribution. When S_a is a positive number, the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 ; when S_a is a negative number or 0, the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ does not
25 meet the preset condition C_1 . A probability that S_a is a positive number is 1/2. In the embodiment shown in FIG. 5, the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . As shown in FIG. 16, "▣" represents 1 byte separately selected when it is determined whether at least a part of data in a window $W_{i2}[p_{i2}-169, p_{i2}]$ meets a preset

condition C_2 . In FIG. 16, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "", whose sequence numbers are 170, 128, 86, 44, and 2 are regarded as 40 sequential bits, which are represented as $b_1, b_2, b_3, b_4, \dots$, and b_{40} separately. For any b_t of $b_1, b_2, b_3, b_4, \dots$, and b_{40} , when $b_t=0$, $V_{bt}=-1$, and when $b_t=1$, $V_{bt}=1$. $V_{b1}, V_{b2}, V_{b3}, V_{b4}, \dots$, and V_{b40} are generated according to a correspondence between b_t and V_{bt} . A manner of determining whether at least a part of data in the window $W_{i1} [p_{i1}-169, p_{i1}]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 , and therefore, the same random numbers are used: $h_1, h_2, h_3, h_4, \dots$, and h_{40} . $S_b = V_{b1} * h_1 + V_{b2} * h_2 + V_{b3} * h_3 + V_{b4} * h_4 + \dots + V_{b40} * h_{40}$. Because $h_1, h_2, h_3, h_4, \dots$, and h_{40} follow normal distribution, S_b also follows normal distribution. When S_b is a positive number, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 ; when S_b is a negative number or 0, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ does not meet the preset condition C_2 . A probability that S_b is a positive number is 1/2. In the embodiment shown in FIG. 5, the at least a part of data in $W_{i2} [p_{i2}-169, p_{i2}]$ meets the preset condition C_2 . By using the same rule, separately, it is determined whether at least a part of data in $W_{i3} [p_{i3}-169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4}-169, p_{i4}]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [p_{i6}-169, p_{i6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [p_{i7}-169, p_{i7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [p_{i8}-169, p_{i8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9} [p_{i9}-169, p_{i9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [p_{i10}-169, p_{i10}]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11} [p_{i11}-169, p_{i11}]$ meets a preset condition C_{11} . In the implementation manner shown in FIG. 5, the at least a part of data in $W_{i5} [p_{i5}-169, p_{i5}]$ does not meet the preset condition C_5 , 11 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of an 11th byte. As

shown in FIG. 6, according to the rule preset on the deduplication server 103, a point p_{j1} and a window $W_{j1}[p_{j1}-169, p_{j1}]$ corresponding to the point p_{j1} are determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as the manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, as shown in FIG. 17, W_{j1} represents the window $W_{j1}[p_{j1}-169, p_{j1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are regarded as 40 sequential bits, which are represented as a_1' , a_2' , a_3' , a_4' , ..., and a_{40}' separately. For any a_i' of a_1' , a_2' , a_3' , a_4' , ..., and a_{40}' , when $a_i'=0$, $V_{ai}'=-1$, and when $a_i'=1$, $V_{ai}'=1$. V_{a1}' , V_{a2}' , V_{a3}' , V_{a4}' , ..., and V_{a40}' are generated according to a correspondence between a_i' and V_{ai}' . The manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as the manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 , and therefore, the same random numbers are used: h_1 , h_2 , h_3 , h_4 , ..., and h_{40} . $S_a' = V_{a1}' * h_1 + V_{a2}' * h_2 + V_{a3}' * h_3 + V_{a4}' * h_4 + \dots + V_{a40}' * h_{40}$. Because h_1 , h_2 , h_3 , h_4 , ..., and h_{40} follow normal distribution, S_a' also follows normal distribution. When S_a' is a positive number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 ; when S_a' is a negative number or 0, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ does not meet the preset condition C_1 . A probability that S_a' is a positive number is 1/2.

[0137] The manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in

$W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 . Therefore, as shown in FIG. 17, "▣" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. In FIG. 17, selected bytes are represented as sequence numbers 170, 128, 86, 44, and

2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "  " whose sequence numbers are 170, 128, 86, 44, and 2 are regarded as 40 sequential bits, which are represented as b_1' , b_2' , b_3' , b_4' , ..., and b_{40}' separately. For any b_t' of b_1' , b_2' , b_3' , b_4' , ..., and b_{40}' , when $b_t'=0$, $V_{bt}'=-1$, and when $b_t'=1$, $V_{bt}'=1$. V_{b1}' , V_{b2}' , V_{b3}' , V_{b4}' , ..., and V_{b40}' are generated according to a correspondence between b_t' and V_{bt}' . The manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is the same as the manner of determining whether at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and therefore, the same random numbers are used: h_1 , h_2 , h_3 , h_4 , ..., and h_{40} . $S_b' = V_{b1}' * h_1 + V_{b2}' * h_2 + V_{b3}' * h_3 + V_{b4}' * h_4 + \dots + V_{b40}' * h_{40}$. Because h_1 , h_2 , h_3 , h_4 , ..., and h_{40} follow normal distribution, S_b' also follows normal distribution. When S_b' is a positive number, the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 ; when S_b' is a negative number or 0, the at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ does not meet the preset condition C_2 . A probability that S_b' is a positive number is 1/2.

[0138] Similarly, a manner of determining whether at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets the preset condition C_{11} , which are not described herein again.

[0139] Still using the implementation manner shown in FIG. 5 as an example, a method for determining whether at least a part of data in a window $W_{iz}[p_{iz}-A_z, p_{iz}+B_z]$ meets a preset

condition C_z is provided. In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z . According to a rule preset on a deduplication server 103, a point p_{i1} and a window $W_{i1} [p_{i1} - 169, p_{i1}]$ corresponding to p_{i1} are determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1} [p_{i1} - 169, p_{i1}]$ meets a preset condition C_1 . As shown in FIG. 16, W_{i1} represents the window $W_{i1} [p_{i1} - 169, p_{i1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1} [p_{i1} - 169, p_{i1}]$ meets the preset condition C_1 . In FIG. 16, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. Each of the bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 is converted into 1 decimal number, the range of which is $0-(2^{40}-1)$. An even distribution random number generator is used to generate 1 designated value for each decimal number in $0-(2^{40}-1)$, and a correspondence R between each decimal number in $0-(2^{40}-1)$ and the designated value is recorded. Once being designated, a designated value corresponding to a decimal number remains unchanged, and the designated value follows even distribution. If the designated value is an even number, the at least a part of data in $W_{i1} [p_{i1} - 169, p_{i1}]$ meets the preset condition C_1 ; if the designated value is an odd number, the at least a part of data in $W_{i1} [p_{i1} - 169, p_{i1}]$ does not meet the preset condition C_1 . C_1 represents that the designated value obtained according to the foregoing method is an even number. Because a probability that a random number in even distribution is an even number is $1/2$, a probability that the at least a part of data in $W_{i1} [p_{i1} - 169, p_{i1}]$ meets the preset condition C_1 is $1/2$. In the implementation manner shown in FIG. 5, by using the same rule, separately, it is determined whether at least a part of data in $W_{i2} [p_{i2} - 169, p_{i2}]$ meets a preset condition C_2 , it is determined whether at least a part of data in $W_{i3} [p_{i3} - 169, p_{i3}]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [p_{i4} - 169, p_{i4}]$ meets a preset condition C_4 , and it is determined whether at least a part of data in $W_{i5} [p_{i5} - 169, p_{i5}]$ meets a preset condition C_5 , which are not described herein again.

[0140] When the at least a part of data in $W_{i5} [p_{i5} - 169, p_{i5}]$ does not meet the preset condition C_5 , 11 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of an 11th byte. As shown in FIG. 6, according to the rule preset on the deduplication server 103, a point

p_{j1} and a window $W_{j1}[p_{j1}-169, p_{j1}]$ corresponding to the point p_{j1} are determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . Therefore, the same correspondence R between each decimal number in $0-(2^{40}-1)$ and a designated value is used. As shown in FIG. 17, W_{j1} represents the window $W_{j1}[p_{j1}-169, p_{j1}]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 . In FIG. 17, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes "■". Each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 is converted into 1 decimal number, and R is searched for a designated value corresponding to the decimal number. If the designated value is an even number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 ; if the designated value is an odd number, the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ does not meet the preset condition C_1 . Because a probability that a random number in even distribution is an even number is $1/2$, a probability that the at least a part of data in $W_{j1}[p_{j1}-169, p_{j1}]$ meets the preset condition C_1 is $1/2$. Similarly, a manner of determining whether at least a part of data in $W_{i2}[p_{i2}-169, p_{i2}]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2}[p_{j2}-169, p_{j2}]$ meets the preset condition C_2 , and a manner of determining whether at least a part of data in $W_{i3}[p_{i3}-169, p_{i3}]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[p_{j3}-169, p_{j3}]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[p_{j4}-169, p_{j4}]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[p_{j5}-169, p_{j5}]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[p_{j6}-169, p_{j6}]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[p_{j7}-169, p_{j7}]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[p_{j8}-169, p_{j8}]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[p_{j9}-169, p_{j9}]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[p_{j10}-169, p_{j10}]$ meets a preset condition

C_{10} , and it is determined whether at least a part of data in $W_{j11}[p_{j11}-169, p_{j11}]$ meets a preset condition C_{11} , which are not described herein again.

[0141] The deduplication server 103 in the embodiment of the present invention shown in FIG. 1 refers to an apparatus that can implement a technical solution described in an embodiment of the present invention, and as shown in FIG. 18, usually includes a central processing unit, a primary memory, and an input/output interface. The central processing unit, the primary memory, and the input/output interface communicate with each other. The main memory stores an executable instruction, and the central processing unit executes the executable instruction stored in the primary memory, so as to perform a specific function, for example, searching for a data stream dividing point described in FIG. 4 to FIG. 17 in the embodiments of the present invention. Therefore, as shown in FIG. 19, according to the embodiments of the present invention shown in FIG. 4 to FIG. 17, for the deduplication server 103, a rule is preset on the deduplication server 103, where the rule is: for a potential dividing point k , determining M points p_x , a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to M , $M \geq 2$, and A_x and B_x are integers. The deduplication server 103 includes a determining unit 1901 and a judging and processing unit 1902. The determining unit 1901 is configured to perform step (a): (a) determining a point p_{iz} and a window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point p_{iz} for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$. The judging and processing unit 1902 is configured to: determine whether at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ;

when the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skip N minimum units U for searching for a data stream dividing point from the point p_{iz} along a direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x(\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, where the determining unit performs step (a) for the new potential dividing point; and when at least a part of data in each window $W_{ix}[p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , select the current potential dividing point k_i as a data stream dividing point.

[0142] Further, the rule further includes that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$. Further, the rule further includes: relative to the potential dividing

point k , the at least two points p_e and p_f are in a direction opposite to the direction of searching for a data stream dividing point.

[0143] Further, the rule further includes that a distance between the at least two points p_e and p_f is 1 U.

5 **[0144]** Further, the judging and processing unit 1902 is specifically configured to determine, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z . Specifically, the judging and processing unit 1902 is specifically configured to determine, by using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z . Specifically, that the judging and processing
10 unit 1902 is specifically configured to determine, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are
15 denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes,

bits corresponding to the F*H bytes may be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}, \text{ where}$$

when $a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

20
$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix},$$
 F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \dots & h_{F*H,8} \end{pmatrix},$$
 random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically

represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF*H} are obtained in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

5 **[0145]** Further, the judging and processing unit 1902 is configured to: when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skip the N minimum units U for searching for a data stream dividing point from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and the determining unit 1901 performs step (a) for the new potential dividing point, where
10 and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, where the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the
15 direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

[0146] According to the method for searching for a data stream dividing point based on a server in the embodiments of the present invention shown in FIG. 4 to FIG. 17, a point p_{ix} and a window $W_{ix} [p_{ix} - A_x, p_{ix} + B_x]$ corresponding to the point p_{ix} are determined for a potential dividing
20 point k_i , where x indicates consecutive natural numbers from 1 to M separately, and $M \geq 2$. It may be determined in parallel whether at least a part of data in each window of M windows meets a preset condition C_x , or it may be determined sequentially whether at least a part of data in windows meets a preset condition, or it may be first determined that at least a part of data in a window $W_{i1} [p_{i1} - A_1, p_{i1} + B_1]$ meets a preset condition C_1 , then it is determined that at least a
25 part of data in $W_{i2} [p_{i2} - A_2, p_{i2} + B_2]$ meets a preset condition C_2 , until it is determined that at least a part of data in $W_{im} [p_{im} - A_m, p_{im} + B_m]$ meets a preset condition C_m . Other windows in this embodiment are determined in a same manner as the above, which is not described again.

[0147] In addition, according to the embodiments of the present invention shown in FIG. 4 to FIG. 17, in actual applications, a rule is preset on the deduplication server 103, where the rule is: for
30 a potential dividing point k , determining M points p_x , a window $W_x [p_x - A_x, p_x + B_x]$

corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to M separately, and $M \geq 2$. In the preset rule, $A_1, A_2, A_3, \dots$, and A_m may be not all equal, $B_1, B_2, B_3, \dots$, and B_m may be not all equal, and $C_1, C_2, C_3, \dots$, and C_M may also be not all the same. In the implementation manner shown in FIG. 5, for windows $W_{i1}[p_{i1}-169, p_{i1}]$, $W_{i2}[p_{i2}-169, p_{i2}]$, $W_{i3}[p_{i3}-169, p_{i3}]$, $W_{i4}[p_{i4}-169, p_{i4}]$, $W_{i5}[p_{i5}-169, p_{i5}]$, $W_{i6}[p_{i6}-169, p_{i6}]$, $W_{i7}[p_{i7}-169, p_{i7}]$, $W_{i8}[p_{i8}-169, p_{i8}]$, $W_{i9}[p_{i9}-169, p_{i9}]$, $W_{i10}[p_{i10}-169, p_{i10}]$, and $W_{i11}[p_{i11}-169, p_{i11}]$, the windows are the same in size, that is, all the windows have a size of 169 bytes, and meanwhile manners of determining whether at least a part of data in a window meets a preset condition are also the same. For details, refer to the foregoing description of determining whether the at least a part of data in $W_{i1}[p_{i1}-169, p_{i1}]$ meets the preset condition C_1 . However, in the implementation manner shown in FIG. 11, the windows $W_{i1}[p_{i1}-169, p_{i1}]$, $W_{i2}[p_{i2}-169, p_{i2}]$, $W_{i3}[p_{i3}-169, p_{i3}]$, $W_{i4}[p_{i4}-169, p_{i4}]$, $W_{i5}[p_{i5}-169, p_{i5}]$, $W_{i6}[p_{i6}-169, p_{i6}]$, $W_{i7}[p_{i7}-169, p_{i7}]$, $W_{i8}[p_{i8}-169, p_{i8}]$, $W_{i9}[p_{i9}-169, p_{i9}]$, $W_{i10}[p_{i10}-169, p_{i10}]$, and $W_{i11}[p_{i11}-182, p_{i11}]$ may be different in size, and meanwhile the manners of determining whether at least a part of data in a window meets a preset condition may also be different. In all the embodiments, according to the rule preset on the deduplication server 103, a manner of determining whether at least a part of data in the window W_{i1} meets the preset condition C_1 is certainly the same as a manner of determining whether at least a part of data in a window W_{j1} meets the preset condition C_1 , a manner of determining whether at least a part of data in W_{i2} meets the preset condition C_2 is certainly the same as a manner of determining whether at least a part of data in W_{j2} meets the preset condition C_2 , ..., and a manner of determining whether at least a part of data in a window W_{iM} meets a preset condition C_M is certainly the same as a manner of determining whether at least a part of data in a window W_{jM} meets the preset condition C_M , which are not described herein again. Meanwhile, according to the embodiments of the present invention shown in FIG. 4 to FIG. 17, although $M=11$ is used as an example, the value of M is not limited to 11 according to an actual requirement, and a person skilled in the art determines the value of M according to the description in the embodiments of the present invention.

[0148] According to the embodiments of the present invention shown in FIG. 4 to FIG. 17, the rule is preset on the deduplication server 103, k_a, k_i, k_j, k_l , and k_m are potential dividing

points obtained in the search for a dividing point along a direction of searching for a data stream dividing point, and k_a , k_i , k_j , k_l , and k_m all follow the rule. The window $W_x [p_x - A_x, p_x + B_x]$ in this embodiment of the present invention represents a specific range, and data is selected in the specific range to determine whether the data meets the preset condition C_x . Specifically, in the specific range, a part of data may be selected or all data may be selected to determine whether the data meets the preset condition C_x . Reference may be made to the window $W_x [p_x - A_x, p_x + B_x]$ for the concept of a window specifically used in this embodiment of the present invention, which is not described herein again.

[0149] According to the embodiments of the present invention shown in FIG. 4 to FIG. 17, in the window $W_x [p_x - A_x, p_x + B_x]$, $(p_x - A_x)$ and $(p_x + B_x)$ represent two boundaries of the window $W_x [p_x - A_x, p_x + B_x]$, where $(p_x - A_x)$ represents a boundary, which is in a direction opposite to the direction of searching for a data stream dividing point relative to the point p_x , of the window $W_x [p_x - A_x, p_x + B_x]$, and $(p_x + B_x)$ represents a boundary, which is in the direction of searching for a data stream dividing point relative to the point p_x , of the window $W_x [p_x - A_x, p_x + B_x]$. Specifically, in the embodiment of the present invention, the direction of searching for a data stream dividing point shown in FIG. 3 to FIG. 15 is from left to right; therefore, $(p_x - A_x)$ represents a boundary (that is, a left boundary), which is in a direction opposite to the direction of searching for a data stream dividing point relative to the point p_x , of the window $W_x [p_x - A_x, p_x + B_x]$, and $(p_x + B_x)$ represents a boundary (that is, a right boundary), which is in the direction of searching for a data stream dividing point relative to the point p_x , of the window $W_x [p_x - A_x, p_x + B_x]$. If the direction of searching for a data stream dividing point shown in FIG. 3 to FIG. 15 is from right to left, $(p_x - A_x)$ represents a boundary (that is, a right boundary), which is in a direction opposite to the direction of searching for a data stream dividing point relative to the point p_x , of the window $W_x [p_x - A_x, p_x + B_x]$, and $(p_x + B_x)$ represents a boundary (that is, a left boundary), which is in the direction of searching for a data stream dividing point relative to the point p_x , of the window $W_x [p_x - A_x, p_x + B_x]$.

[0150] A person of ordinary skill in the art may be aware that, in conjunction with various exemplary units and algorithm steps described in the embodiments of the present invention, a key feature in the embodiments of the present invention may be combined with other technologies and presented in a more complex form; however, the key feature of the present invention is still included. An alternative dividing point may be used in a real environment. For example, in an

implementation manner, according to a rule preset on a deduplication server 103, 11 points p_x are determined for a potential dividing point k_i , where x indicates consecutive natural numbers from 1 to 11, and a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to p_x and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$ are determined. When at least a part of data in each window $W_x[p_x - A_x, p_x + B_x]$ of 11 windows meets the preset condition C_x , the potential dividing point k_i is a data stream dividing point. When no dividing point is found when a set maximum data chunk is exceeded, a preset rule for the alternative point may be used in this case. The preset rule for the alternative point is similar to the rule preset on the deduplication server 103, and the preset rule for the alternative point is: for example, for a potential dividing point k_i , 10 points p_x are determined, where x indicates consecutive natural numbers from 1 to 10, and a window $W_x[p_x - A_x, p_x + B_x]$ corresponding to p_x and a preset condition C_x corresponding to the window $W_x[p_x - A_x, p_x + B_x]$ are determined. When at least a part of data in each window $W_x[p_x - A_x, p_x + B_x]$ of 10 windows meets the preset condition C_x , the potential dividing point k_i is a data stream dividing point; when no data stream dividing point is found when a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0151] A rule is preset on the deduplication server 103, and in the rule, M points are determined for a potential dividing point k. It is not necessarily required that there be a potential dividing point k in advance, and the potential dividing point k may be determined by using the determined M points.

[0152] An embodiment of the present invention provides a method for searching for a data stream dividing point based on a deduplication server, which, as shown in FIG. 20, includes:

[0153] A rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k, determining M windows $W_x[k - A_x, k + B_x]$ and a preset condition C_x corresponding to the window $W_x[k - A_x, k + B_x]$, where x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers. In the implementation manner shown in FIG. 3, about a value of M, in one implementation manner, a value of $M \cdot U$ is not greater than a preset maximum distance between two adjacent data stream dividing points, that is, a preset maximum length of a data chunk. It is determined whether at least a part of data in a window $W_z[k - A_z, k + B_z]$ meets a preset condition C_z , where, z is an integer, $1 \leq z \leq M$, and $(k - A_z)$ and $(k + B_z)$ separately represent two

boundaries of the window W_z . When it is determined that at least a part of data in any one window $W_z[k - A_z, k + B_z]$ does not meet the preset condition C_z , N bytes are skipped from the potential dividing point k along a direction of searching for a data stream dividing point, where $N \leq \|B_z\| + \max_x(\|A_x\|)$. $\|B_z\|$ represents an absolute value of B_z in $W_z[k - A_z, k + B_z]$, $\max_x(\|A_x\|)$ represents a maximum value among the absolute value of A_x in the M windows, and a principle of determining a value of N is specifically introduced in the following embodiments. When it is determined that at least a part of data in each window $W_x[k - A_x, k + B_x]$ of the M windows meets the preset condition C_x , the potential dividing point k is a data stream dividing point.

10 **[0154]** Specifically, for a current potential dividing point k_i , the following steps are performed according to the rule:

[0155] Step 2001: Determine a corresponding window $W_{iz}[k_i - A_z, k_i + B_z]$ for the current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$.

[0156] Step 2002: Determine whether at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z ;

when the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skip N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along the direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x(\|A_x\|)$, so as to obtain a new potential dividing point, and perform step 2001; and

when at least a part of data in each window $W_{ix}[k_i - A_x, k_i + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , select the current potential dividing point k_i as a data stream dividing point.

[0157] Further, the rule further includes that at least two windows $W_{ie}[k_i - A_e, k_i + B_e]$ and $W_{if}[k_i - A_f, k_i + B_f]$ meet conditions $|A_e + B_e| = |A_f + B_f|$, and $C_e = C_f$. Further, the rule further includes that A_e and A_f are positive integers. Still further, the rule further includes $A_e - 1 = A_f$ and $B_e + 1 = B_f$. $|A_e + B_e|$ represents a size of the window W_{ie} , and $|A_f + B_f|$ represents a size of the window W_{if} .

[0158] Further, the determining whether at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes: determining, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z . Still further, the determining, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z is specifically: determining, by using a hash function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0159] When the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the current potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point. According to the rule, a left boundary of a window $W_{ic}[k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz}[k_i - A_z, k_i + B_z]$ or a left boundary of a window $W_{ic}[k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point falls within a range of the window $W_{iz}[k_i - A_z, k_i + B_z]$, where the window $W_{ic}[k_i - A_c, k_i + B_c]$ determined for the new potential dividing point is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M windows that are determined for the new potential dividing point according to the rule.

[0160] In this embodiment of the present invention, a data stream dividing point is searched for by determining whether at least a part of data in a window of M windows meets a preset condition, and when the at least a part of data in the window does not meet the preset condition, a length of $N*U$ is skipped, where $N*U$ is not greater than $\|B_z\| + \max_x(\|A_x\|)$, so as to obtain a next potential dividing point, thereby improving efficiency of searching for a data stream dividing point.

[0161] In a process of eliminating duplicate data, to ensure an even size of a data chunk, a size of an average data chunk (also referred to as an average chunk) is considered. That is, while limits on a size of a minimum data chunk and a size of a maximum data chunk are met, the size of the average data chunks is determined to ensure an even size of an obtained data chunk. A probability (represented as $P(n)$) of finding a data stream dividing point depends on two factors, that is, the quantity M of the windows $W_x[k - A_x, k + B_x]$ and a probability that at least a part of data in the window $W_x[k - A_x, k + B_x]$ meets a preset condition, where the former affects a length for

skipping, the latter affects a probability of skipping, and the two together affect the size of the average chunk. Generally, when the size of the average chunk is fixed, as the quantity of $W_x[k - A_x, k + B_x]$ increases, the probability that at least a part of data in a single window $W_x[k - A_x, k + B_x]$ meets a preset condition also increases. For example, a rule is preset on the deduplication server 103, and the rule is: for a potential dividing point k , determining 11 windows $W_x[k - A_x, k + B_x]$, where x indicates consecutive natural numbers from 1 to 11 separately, and a probability that at least a part of data in any window $W_x[k - A_x, k + B_x]$ of the 11 windows meets a preset condition is $1/2$. Another group of rules preset on the deduplication server 103 is: determining 24 windows $W_x[k - A_x, k + B_x]$ for the potential dividing point k , where x indicates consecutive natural numbers from 1 to 24 separately, and a probability that at least a part of data in any window $W_x[k - A_x, k + B_x]$ of the 24 windows meets the preset condition C_x is $3/4$. For the setting of a probability that at least a part of data in a specific window $W_x[k - A_x, k + B_x]$ meets a preset condition, reference may be made to the description of the part of determining whether at least a part of data in the window $W_x[k - A_x, k + B_x]$ meets a preset condition. $P(n)$ depends on the two factors, that is, the quantity M of windows $W_x[k - A_x, k + B_x]$ and the probability that at least a part of data in the window $W_x[k - A_x, k + B_x]$ meets a preset condition, and $P(n)$ represents: a probability that no data stream dividing point is found after n minimum units for searching for a data stream dividing point in a search from a start position or a previous data stream dividing point of a data stream. A process of calculating $P(n)$ that depends on the two factors is actually an n -step Fibonacci sequence, which is described below in detail. After $P(n)$ is obtained, $1 - P(n)$ is a distribution function of a data stream dividing point, and $(1 - P(n)) - (1 - P(n-1)) = P(n-1) - P(n)$ is a probability that a data stream dividing point is found at a distance of n minimum units for searching for a data stream dividing point, that is, a density function of a data stream dividing point.

Integration $\sum_{n=4*1024}^{12*1024} n \times (P(n-1) - P(n))$ may be performed according to the density function of a data stream dividing point, so as to obtain an expected length of a data stream dividing point, that is, the size of the average chunk, where $4*1024$ (bytes) represents a length of the minimum data chunk, and $12*1024$ (bytes) represents a length of the maximum data chunk.

[0162] On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 21, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 windows $W_x[k - A_x, k + B_x]$ and a preset condition C_x corresponding to the window $W_x[k - A_x, k + B_x]$, where x indicates consecutive

natural numbers from 1 to 11, and A_x and B_x are integers. $A_1=169$, $B_1=0$; $A_2=170$, $B_2=-1$; $A_3=171$, $B_3=-2$; $A_4=172$, $B_4=-3$; $A_5=173$, $B_5=-4$; $A_6=174$, $B_6=-5$; $A_7=175$, $B_7=-6$; $A_8=176$, $B_8=-7$; $A_9=177$, $B_9=-8$; $A_{10}=178$, $B_{10}=-9$; $A_{11}=179$, $B_{11}=-10$. $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$. Therefore, the 11 windows are $W_1[k-169, k]$, $W_2[k-170, k-1]$, $W_3[k-171, k-2]$, $W_4[k-172, k-3]$, $W_5[k-173, k-4]$, $W_6[k-174, k-5]$, $W_7[k-175, k-6]$, $W_8[k-176, k-7]$, $W_9[k-177, k-8]$, $W_{10}[k-178, k-9]$, and $W_{11}[k-179, k-10]$. k_a is a data stream dividing point, and a direction of searching for a data stream dividing point shown in FIG. 21 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i .

According to the rule preset on the deduplication server 103, a window $W_{ix}[k_i - A_x, k_i + B_x]$ is determined for the potential dividing point k_i , and in this embodiment, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 21, 11 windows are determined for the potential dividing point k_i , and are $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, $W_{i4}[k_i-172, k_i-3]$, $W_{i5}[k_i-173, k_i-4]$, $W_{i6}[k_i-174, k_i-5]$, $W_{i7}[k_i-175, k_i-6]$, $W_{i8}[k_i-176, k_i-7]$, $W_{i9}[k_i-177, k_i-8]$, $W_{i10}[k_i-178, k_i-9]$, and $W_{i11}[k_i-179, k_i-10]$ separately. It is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i-174, k_i-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{i7}[k_i-175, k_i-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i-176, k_i-7]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[k_i-177, k_i-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i-178, k_i-9]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[k_i-179, k_i-10]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2}

meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, for example, $W_{i5}[k_i-173, k_i-4]$ shown in FIG. 22, N bytes are skipped from the potential dividing point k_i along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_5\| + \max_x(\|A_x\|)$. In an implementation manner shown in FIG. 22, the N bytes that are skipped are not greater than 183 bytes, and in this embodiment, $N=7$, so as to obtain a new potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point here is represented as k_j here. According to the implementation manner shown in FIG. 21, a rule is preset on the deduplication server 103, where the rule is: determining a window $W_{jx}[k_j-A_x, k_j+B_x]$ for the potential dividing point k_j , where in this embodiment, x indicates consecutive natural numbers from 1 to 11 separately. 11 windows are determined for the potential dividing point k_j , and are $W_{j1}[k_j-169, k_j]$, $W_{j2}[k_j-170, k_j-1]$, $W_{j3}[k_j-171, k_j-2]$, $W_{j4}[k_j-172, k_j-3]$, $W_{j5}[k_j-173, k_j-4]$, $W_{j6}[k_j-174, k_j-5]$, $W_{j7}[k_j-175, k_j-6]$, $W_{j8}[k_j-176, k_j-7]$, $W_{j9}[k_j-177, k_j-8]$, $W_{j10}[k_j-178, k_j-9]$, and $W_{j11}[k_j-179, k_j-10]$ separately. As shown in FIG. 22, when the 11th window $W_{j11}[k_j-179, k_j-10]$ is determined for the potential dividing point, to ensure that a range between the potential dividing point k_i and the potential dividing point k_j completely falls within a determining range, in this implementation manner, it may be ensured that a left boundary of the window $W_{j11}[k_j-179, k_j-10]$ coincides with a right boundary (k_i-4) of the window $W_{i5}[k_i-173, k_i-4]$, or falls within a range of the window $W_{i5}[k_i-173, k_i-4]$, where the window $W_{j11}[k_j-179, k_j-10]$ is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of the 11 windows that are

determined for the potential dividing point k_j according to the rule. Therefore, within such a limit, when at least a part of data in the window $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , a distance for skipping from the potential dividing point k_i along the direction of searching for a data stream dividing point is not greater than $\|B_5\| + \max_x(\|A_x\|)$. It is determined whether at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next

potential dividing point, and according to the rule preset on the deduplication server 103, it is determined whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, a next potential dividing point is obtained in a manner the same as that of k_i , and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0163] In the implementation manner shown in FIG. 21, according to the rule preset on the deduplication server 103, starting from determining whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 , when it is determined the at least a part of data in $W_{i1}[k_i-169, k_i]$, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$, the at least a part of data in $W_{i3}[k_i-171, k_i-2]$, and the at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meet the preset conditions C_1, C_2, C_3 , and C_4 respectively, and it is determined that the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does

not meet the preset condition C_5 , 6 bytes are skipped from the potential dividing point k_i along the direction of searching for a data stream dividing point, and a new potential dividing point is obtained at an end position of a 6th byte. For differentiation from other potential dividing points, the new potential dividing point is represented as k_g here. According to the rule preset on the deduplication server 103, 11 windows are determined for the potential dividing point k_g , and are


$W_{g1}[k_g-169, k_g]$, $W_{g2}[k_g-170, k_g-1]$, $W_{g3}[k_g-171, k_g-2]$, $W_{g4}[k_g-172, k_g-3]$, $W_{g5}[k_g-173, k_g-4]$, $W_{g6}[k_g-174, k_g-5]$, $W_{g7}[k_g-175, k_g-6]$, $W_{g8}[k_g-176, k_g-7]$, $W_{g9}[k_g-177, k_g-8]$, $W_{g10}[k_g-178, k_g-9]$, and $W_{g11}[k_g-179, k_g-10]$ separately. It is determined whether at least a part of data in $W_{g1}[k_g-169, k_g]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{g2}[k_g-170, k_g-1]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{g3}[k_g-171, k_g-2]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{g4}[k_g-172, k_g-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{g5}[k_g-173, k_g-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{g6}[k_g-174, k_g-5]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{g7}[k_g-175, k_g-6]$ meets a preset condition C_7 , it

is determined whether at least a part of data in $W_{g8}[k_g-176, k_g-7]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{g9}[k_g-177, k_g-8]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{g10}[k_g-178, k_g-9]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{g11}[k_g-179, k_g-10]$ meets a preset condition C_{11} . The window $W_{g11}[k_g-179, k_g-10]$ coincides with the window $W_{i5}[k_i-173, k_i-4]$, and $C_5=C_{11}$; therefore, when it is determined that the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , a potential dividing point k_g obtained by skipping T bytes from the potential dividing point k_i along the direction of searching for a data stream dividing point still does not meet a condition for serving as a data stream dividing point. Therefore, if repeated calculation exists when 6 bytes are skipped from the potential dividing point k_i along the direction of searching for a data stream dividing point, then repeated calculation can be reduced and efficiency is higher when 7 bytes are skipped from the potential dividing point k_i along the direction of searching for a data stream dividing point. Therefore, a speed of searching for a data stream dividing point is increased. When a probability that at least a part of data in the window $W_x[k-A_x, k+B_x]$ that is determined according to the preset rule meets the preset condition C_x is 1/2, that is, a probability of executing skipping is 1/2, at most $\|B_{11}\| + \|A_{11}\| = 189$ bytes can be skipped each time.

[0164] In this implementation manner, a preset rule is that: 11 windows $W_x[k-A_x, k+B_x]$ are determined for a potential dividing point k and at least a part of data in the window $W_x[k-A_x, k+B_x]$ meets a preset condition C_x , where a probability that at least a part of data in $W_x[k-A_x, k+B_x]$ meets the preset condition C_x is 1/2, where x indicates consecutive natural numbers from 1 to 11 separately, and A_x and B_x are integers. $A_1=169, B_1=0; A_2=170, B_2=-1; A_3=171, B_3=-2; A_4=172, B_4=-3; A_5=173, B_5=-4; A_6=174, B_6=-5; A_7=175, B_7=-6; A_8=176, B_8=-7; A_9=177, B_9=-8; A_{10}=178, B_{10}=-9; A_{11}=179, B_{11}=-10$. $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$. That is, 11 windows are selected for the potential dividing point k, and the 11 windows are consecutive; P(n) can be calculated by using the two factors, that is, the quantity of windows and the probability that at least a part of data in the window $W_x[p_x-A_x, p_x+B_x]$ meets the preset condition C_x . A manner of selecting the 11 windows and the determining that at least a part of data in each window of the 11 windows meets the preset condition C_x follow the rule preset on the

deduplication server 103, and therefore, whether the potential dividing point k is a data stream dividing point depends on whether it exists that at least a part of data in each window of 11 consecutive windows meets the preset condition C_x . A gap between two bytes is referred to as one point. $P(n)$ represents a probability that 11 consecutive windows meeting a condition do not exist among n consecutive windows, that is, a probability that no data stream dividing point exists. After a minimum chunk size of 4 KB is skipped from a file header/previous dividing point, a 4086th point is found by going back by 10 bytes in a direction opposite to the direction of searching for a data stream dividing point, and no data stream dividing point exists at the point; therefore, $P(4086)=1$, and $P(4087)=1$, ..., $P(4095)=1$, and so on. At an 4096th point, that is, a point which is used to obtain the minimum chunk, with a probability of $(1/2)^{11}$, at least a part of data in each window of the 11 windows meets the preset condition C_x . Hence, with a probability of $(1/2)^{11}$, a data stream dividing point exists; with a probability of $1-(1/2)^{11}$, no data stream dividing point exists; therefore $P(4096)=1-(1/2)^{11}$.

[0165] In an n th window, there may be 12 cases of obtaining $P(n)$ by means of recursion.



[0166] Case 1: With a probability of $1/2$, at least a part of data in the n th window does not meet a preset condition; in this case, with a probability of $P(n-1)$, 11 consecutive windows do not exist among $(n-1)$ windows before the n th window, where at least a part of data in each window of the 11 consecutive windows meets a preset condition. Therefore, $P(n)$ includes $1/2 \cdot P(n-1)$. A case in which the at least a part of data in the n th window does not meet the preset condition, and 11 consecutive windows exist among the $(n-1)$ windows before the n th window, where at least a part of data in each window of the 11 consecutive windows meets the preset condition, is not related to $P(n)$.

[0167] Case 2: With a probability of $1/2$, at least a part of data in the n th window meets a preset

condition, and with the probability of $1/2$, at least a part of data in an $(n-1)$ th window does not meet a preset condition; in this case, with a probability of $P(n-2)$, 11 consecutive windows do not exist among $(n-2)$ windows before the $(n-1)$ th window, where at least a part of data in each window of the 11 consecutive windows meets a preset condition. Therefore, $P(n)$ includes $1/2 * 1/2 * P(n-2)$. A case in which the at least a part of data in the n th window meets the preset condition, the at least a part of data in the $(n-1)$ th point window does not meet the preset condition, and 11 consecutive windows exist among the $(n-2)$ windows before the $(n-1)$ th window, where at least a part of data in each window of the 11 consecutive windows meets the preset condition, is not related to $P(n)$.

[0168] According to the foregoing description, case 11: With a probability of $(1/2)^{10}$, at least a part of data in n th to $(n-9)$ th windows meets a preset condition, and with a probability of $1/2$, at least a part of data in an $(n-10)$ th window does not meet a preset condition; in this case, with a probability of $P(n-11)$, 11 consecutive windows do not exist among $(n-11)$ windows before the $(n-10)$ th window, where at least a part of data in each window of the 11 consecutive windows meets a preset condition. Therefore, $P(n)$ includes $(1/2)^{10} * 1/2 * P(n-11)$. A case in which the at least a part of data in the n th to $(n-9)$ th windows meets the preset condition, the at least a part of data in the $(n-10)$ th window does not meet the preset condition, and 11 consecutive windows exist among the $(n-11)$ windows before the $(n-10)$ th window, where at least a part of data in each window of the 11 consecutive windows meets the preset condition, is not related to $P(n)$.

[0169] Case 12: With a probability of $(1/2)^{11}$, at least a part of data in n th to $(n-10)$ windows meets a preset condition is, and this case is not related to $P(n)$.

[0170] Therefore, $P(n) = 1/2 * P(n-1) + (1/2)^2 * P(n-2) + \dots + (1/2)^{11} * P(n-11)$. Another preset rule is: for a potential dividing point k , 24 windows $W_x[k - A_x, k + B_x]$ and a preset condition C_x corresponding to the window $W_x[k - A_x, k + B_x]$ are determined, where x indicates consecutive natural numbers from 1 to 11, $A_1=169, B_1=0; A_2=170, B_2=-1; A_3=171, B_3=-2; A_4=172, B_4=-3; A_5=173, B_5=-4; A_6=174, B_6=-5; A_7=175, B_7=-6; A_8=176, B_8=-7; A_9=177, B_9=-8; A_{10}=178, B_{10}=-9; A_{11}=179, B_{11}=-10, \dots$, and $A_{24}=192, B_{24}=-23$. $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=\dots=C_{24}$. A probability that at least a part of data in the window $W_x[k - A_x, k + B_x]$ meets the preset condition C_x is $3/4$, and $P(n)$ can be calculated by using the two factors, that is, the quantity of windows and the probability that at least a part of data in the window $W_x[p_x - A_x, p_x + B_x]$ meets the preset condition C_x .

[0171] Therefore, whether the potential dividing point k is a data stream dividing point depends on whether it exists that at least a part of data in each window of the 24 consecutive

windows meets the preset condition C_x , and calculation can be performed by using the following formulas:

$$P(1)=1, P(2), \dots, P(23)=1, P(24)=1-(3/4)^{24}, \text{ and}$$

$$P(n)=1/4 \cdot P(n-1)+1/4 \cdot (3/4) \cdot P(n-2)+\dots+1/4 \cdot (3/4)^{23} \cdot P(n-24).$$

5 **[0172]** After calculation, $P(5 \cdot 1024)=0.78$, $P(11 \cdot 1024)=0.17$, and $P(12 \cdot 1024)=0.13$. That is, no data stream dividing point is found with a probability of 13% after a search proceeds to a point at a distance of 12 KB from a start position/previous data stream dividing point of a data stream, and forced division is performed. A density function of a data stream dividing point is obtained by using this probability, and after integration, it is obtained that on average, a data stream dividing point is found after a search proceeds to a point at a distance about 7.6 KB from the start position/previous data stream dividing point of the data stream, that is, an average chunk length is about 7.6 KB. Different from that at least a part of data in 11 consecutive windows meets a preset condition with a probability of 1/2, a conventional CDC algorithm can achieve an effect of an average chunk length being 7.6 KB only when one window meets a condition with a probability of $1/2^{12}$.

15 **[0173]** On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 23, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 windows $W_x[k - A_x, k + B_x]$ and a preset condition C_x corresponding to the window $W_x[k - A_x, k + B_x]$, where x indicates consecutive natural numbers from 1 to 11, and A_x and B_x are integers. A probability that at least a part of data in the window $W_x[k - A_x, k + B_x]$ meets the preset condition C_x is 1/2. $A_1=171$, $B_1=-2$; $A_2=172$, $B_2=-3$; $A_3=173$, $B_3=-4$; $A_4=174$, $B_4=-5$; $A_5=175$, $B_5=-6$; $A_6=176$, $B_6=-7$; $A_7=177$, $B_7=-8$; $A_8=178$, $B_8=-9$; $A_9=179$, $B_9=-10$; $A_{10}=170$, $B_{10}=-1$; $A_{11}=169$, $B_{11}=0$. $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$. k_a is a data stream dividing point, and a direction of searching for a data stream dividing point shown in FIG. 23 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i . According to the rule preset on the deduplication server 103, for the potential dividing point k_i , $W_{ix}[k_i - A_x, k_i + B_x]$ and the preset condition C_x corresponding to the window $W_{ix}[k_i - A_x, k_i + B_x]$ are determined, where x indicates consecutive natural numbers from 1 to 11. Determined 11 windows are $W_{i1}[k_i - 171, k_i - 2]$, $W_{i2}[k_i - 172, k_i - 3]$, $W_{i3}[k_i - 173, k_i - 4]$, $W_{i4}[k_i - 174, k_i - 5]$, $W_{i5}[k_i - 175, k_i - 6]$, $W_{i6}[k_i - 176, k_i - 7]$, $W_{i7}[k_i - 177, k_i - 8]$, $W_{i8}[k_i - 178, k_i - 9]$, $W_{i9}[k_i - 179, k_i - 10]$, $W_{i10}[k_i - 170, k_i - 11]$, and $W_{i11}[k_i - 169, k_i - 12]$.

$k_i - 1]$, and $W_{i11}[k_i - 169, k_i]$ separately. It is determined whether at least a part of data in $W_{i1}[k_i - 171, k_i - 2]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{i2}[k_i - 172, k_i - 3]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{i3}[k_i - 173, k_i - 4]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i - 174, k_i - 5]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i - 175, k_i - 6]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i - 176, k_i - 7]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{i7}[k_i - 177, k_i - 8]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i - 178, k_i - 9]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[k_i - 179, k_i - 10]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i - 170, k_i - 1]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[k_i - 169, k_i]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, as shown in FIG. 24, that the at least a part of data in $W_{i3}[p_{i3} - 169, p_{i3}]$ does not meet the preset condition C_3 , 11 bytes are skipped from a point p_{i3} along a direction of searching for a data stream dividing point is used as an example for description. As shown in FIG. 24, when it is determined that W_{i3} does not meet the preset condition C_3 , from k_i that serves as a start point, N bytes are skipped along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_3\| + \max_x(\|A_x\|)$. In this embodiment, N=7, and a next potential dividing point is obtained at an end position of a 7th byte.

For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According to the rule preset on the deduplication server 103, for the potential dividing point k_j , 11 windows $W_{jx}[k_j - A_x, k_j + B_x]$ are determined, and are $W_{j1}[k_j - 171, k_j - 2]$, $W_{j2}[k_j - 172, k_j - 3]$, $W_{j3}[k_j - 173, k_j - 4]$, $W_{j4}[k_j - 174, k_j - 5]$, $W_{j5}[k_j - 175, k_j - 6]$, $W_{j6}[k_j - 176, k_j - 7]$, $W_{j7}[k_j - 177, k_j - 8]$, $W_{j8}[k_j - 178, k_j - 9]$, $W_{j9}[k_j - 179, k_j - 10]$, $W_{j10}[k_j - 170, k_j - 1]$, and $W_{j11}[k_j - 169, k_j]$ separately. It is determined whether at least a part of data in $W_{j1}[k_j - 171, k_j - 2]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[k_j - 172, k_j - 3]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[k_j - 173, k_j - 4]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[k_j - 174, k_j - 5]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j - 175, k_j - 6]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j - 176, k_j - 7]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j - 177, k_j - 8]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j - 178, k_j - 9]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j - 179, k_j - 10]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j - 170, k_j - 1]$ meets the preset condition C_{10} and it is determined whether at least a part of data in $W_{j11}[k_j - 169, k_j]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset

condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and according to the rule preset on the deduplication server 103, it is determined whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, a next potential dividing point is obtained in a manner the same as that of k_i , and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point. Certainly, implementation of the method is restricted by a length of the maximum data chunk and a size of a file forming the data stream, which is not described herein again.

[0174] On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 25, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 windows $W_x[k-A_x, k+B_x]$ and a preset condition C_x corresponding to the window $W_x[k-A_x, k+B_x]$, where x indicates consecutive natural numbers from 1 to 11. $A_1=166, B_1=3; A_2=167, B_2=2; A_3=168, B_3=1; A_4=169, B_4=0; A_5=170, B_5=-1; A_6=171, B_6=-2; A_7=172, B_7=-3; A_8=173, B_8=-4; A_9=174, B_9=-5; A_{10}=175, B_{10}=-6; A_{11}=176, B_{11}=-7. C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$, and 11 windows are $W_1[k-166, k+3], W_2[k-167, k+2], W_3[k-168, k+1], W_4[k-169, k], W_5[k-170, k-1], W_6[k-171, k-2], W_7[k-172, k-3], W_8[k-173, k-4], W_9[k-174, k-5], W_{10}[k-175, k-6],$ and $W_{11}[k-176, k-7]$ separately. k_a is a data stream dividing point, and a direction of searching for a data stream dividing point shown in FIG. 25 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, for the potential dividing point k_i , 11 windows $W_{ix}[k-A_x, k+B_x]$ and the preset condition C_x corresponding to the window $W_{ix}[k-A_x, k+B_x]$ are determined,

where x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 25, for the potential dividing point k_i , the 11 windows that are determined are $W_{i1} [k_i - 166, k_i + 3]$, $W_{i2} [k_i - 167, k_i + 2]$, $W_{i3} [k_i - 168, k_i + 1]$, $W_{i4} [k_i - 169, k_i]$, $W_{i5} [k_i - 170, k_i - 1]$, $W_{i6} [k_i - 171, k_i - 2]$, $W_{i7} [k_i - 172, k_i - 3]$, $W_{i8} [k_i - 173, k_i - 4]$, $W_{i9} [k_i - 174, k_i - 5]$, $W_{i10} [k_i - 175, k_i - 6]$, and $W_{i11} [k_i - 176, k_i - 7]$ separately. It is determined whether at least a part of data in $W_{i1} [k_i - 166, k_i + 3]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{i2} [k_i - 167, k_i + 2]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{i3} [k_i - 168, k_i + 1]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{i4} [k_i - 169, k_i]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{i5} [k_i - 170, k_i - 1]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{i6} [k_i - 171, k_i - 2]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{i7} [k_i - 172, k_i - 3]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{i8} [k_i - 173, k_i - 4]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{i9} [k_i - 174, k_i - 5]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{i10} [k_i - 175, k_i - 6]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11} [k_i - 176, k_i - 7]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, for example, $W_{i7} [k_i - 172, k_i - 3]$ shown in FIG. 26, N bytes are skipped from the

potential dividing point k_i along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_7\| + \max_x(\|A_x\|)$. In an implementation manner shown in FIG. 26, the N bytes which are skipped are not greater than 185 bytes, and in this embodiment, N=5, so as to obtain a new potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According to the rule preset on the deduplication server 103 in the implementation manner shown in FIG. 25, for the potential dividing point k_j , 11 windows are determined, and are $W_{j1}[k_j-166, k_j+3]$, $W_{j2}[k_j-167, k_j+2]$, $W_{j3}[k_j-168, k_j+1]$, $W_{j4}[k_j-169, k_j]$, $W_{j5}[k_j-170, k_j-1]$, $W_{j6}[k_j-171, k_j-2]$, $W_{j7}[k_j-172, k_j-3]$, $W_{j8}[k_j-173, k_j-4]$, $W_{j9}[k_j-174, k_j-5]$, $W_{j10}[k_j-175, k_j-6]$, and $W_{j11}[k_j-176, k_j-7]$ separately. It is determined whether at least a part of data in $W_{j1}[k_j-166, k_j+3]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[k_j-167, k_j+2]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[k_j-168, k_j+1]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[k_j-169, k_j]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-170, k_j-1]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-171, k_j-2]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-172, k_j-3]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-173, k_j-4]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-174, k_j-5]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-175, k_j-6]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-176, k_j-7]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset

condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and according to the rule preset on the deduplication server 103, it is determined whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, a next potential dividing point is obtained in a manner the same as that of k_i , and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0175] On the basis of the search for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 27, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 windows $W_x[k-A_x, k+B_x]$ and a preset condition C_x corresponding to the window $W_x[k-A_x, k+B_x]$, where x indicates consecutive natural numbers from 1 to 11. $A_1=169$, $B_1=0$; $A_2=170$, $B_2=-1$; $A_3=171$, $B_3=-2$; $A_4=172$, $B_4=-3$; $A_5=173$, $B_5=-4$; $A_6=174$, $B_6=-5$; $A_7=175$, $B_7=-6$; $A_8=176$, $B_8=-7$; $A_9=177$, $B_9=-8$; $A_{10}=168$, $B_{10}=1$; $A_{11}=179$, $B_{11}=3$. $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10} \neq C_{11}$, and 11 windows are $W_1[k-169, k]$, $W_2[k-170, k-1]$, $W_3[k-171, k-2]$, $W_4[k-172, k-3]$, $W_5[k-173, k-4]$, $W_6[k-174, k-5]$, $W_7[k-175, k-6]$, $W_8[k-176, k-7]$, $W_9[k-177, k-8]$, $W_{10}[k-168, k+1]$, and $W_{11}[k-179, k+3]$ separately. k_a is a data stream dividing point, and a direction of searching for a data stream dividing point shown in FIG. 27 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, for the potential dividing point k_i , a window $W_{ix}[k_i-A_x, k_i+B_x]$ is determined, where x indicates consecutive natural numbers from 1 to 11 separately. In the

implementation manner shown in FIG. 27, for the potential dividing point k_i , 11 windows that are determined are $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, $W_{i4}[k_i-172, k_i-3]$, $W_{i5}[k_i-173, k_i-4]$, $W_{i6}[k_i-174, k_i-5]$, $W_{i7}[k_i-175, k_i-6]$, $W_{i8}[k_i-176, k_i-7]$, $W_{i9}[k_i-177, k_i-8]$, $W_{i10}[k_i-168, k_i+1]$, and $W_{i11}[k_i-179, k_i+3]$ separately. It is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i-174, k_i-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{i7}[k_i-175, k_i-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i-176, k_i-7]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[k_i-177, k_i-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i-168, k_i+1]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[k_i-179, k_i+3]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9} meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When it is determined that the at least a part of data in the window W_{i11} does not meet the preset condition C_{11} , 1 byte is skipped from the potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain a new potential dividing point. For differentiation from

the potential dividing point k_i , the new potential dividing point is represented as k_j here. When the at least a part of data in any window the the 10 windows W_{i1} , W_{i2} , W_{i3} , W_{i4} , W_{i5} , W_{i6} , W_{i7} , W_{i8} , W_{i9} , and W_{i10} does not meet the corresponding preset condition, for example, W_{i4} [k_i -172, k_i -3] shown in FIG. 28, N bytes are skipped from the point k_i along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_4\| + \max_x (\|A_x\|)$. In an implementation manner shown in FIG. 28, the N bytes that are skipped are not greater than 182 bytes, and in this embodiment, N=6, so as to obtain a new potential dividing point. For differentiation from the potential dividing point k_i , the new potential dividing point is represented as k_j here. According the rule preset on the deduplication server 103 in the implementation manner shown in FIG. 27, windows determined for the potential dividing point k_j are $W_{j1}[k_j-169, k_j]$, $W_{j2}[k_j-170, k_j-1]$, $W_{j3}[k_j-171, k_j-2]$, $W_{j4}[k_j-172, k_j-3]$, $W_{j5}[k_j-173, k_j-4]$, $W_{j6}[k_j-174, k_j-5]$, $W_{j7}[k_j-175, k_j-6]$, $W_{j8}[k_j-176, k_j-7]$, $W_{j9}[k_j-177, k_j-8]$, $W_{j10}[k_j-168, k_j+1]$, and $W_{j11}[k_j-179, k_j+3]$ separately. It is determined whether at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-168, k_j+1]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j+3]$ meets the preset condition C_{11} . Certainly, in this embodiment of the present invention, the rule is also followed when it is determined whether the potential dividing point k_a is a data stream dividing point, specific implementation is not described again, and reference may be made to the description of determining the potential dividing point k_i . When it is determined that the at least a part of data

in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point, and data between k_j and k_a forms 1 data chunk. Meanwhile, a minimum chunk size of 4 KB is skipped in a manner the same as that of k_a to obtain a next potential dividing point, and according to the rule preset on the deduplication server 103, it is determined whether the next potential dividing point is a data stream dividing point. When it is determined that the potential dividing point k_j is not a data stream dividing point, a next potential dividing point is obtained in a manner the same as that of k_i , and it is determined, according to the rule preset on the deduplication server 103 and the foregoing method, whether the next potential dividing point is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0176] On the basis of the searching for a data stream dividing point shown in FIG. 3, in an implementation manner shown in FIG. 29, a rule is preset on a deduplication server 103, where the rule is: for a potential dividing point k , determining 11 windows $W_x [p_x - A_x, p_x + B_x]$ and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, where x indicates consecutive natural numbers from 1 to 11 separately, where a probability that at least a part of data in the window $W_x [p_x - A_x, p_x + B_x]$ meets a preset condition is 1/2. $A_1=169$, $B_1=0$; $A_2=171$, $B_2=-2$; $A_3=173$, $B_3=-4$; $A_4=175$, $B_4=-6$; $A_5=177$, $B_5=-8$; $A_6=179$, $B_6=-10$; $A_7=181$, $B_7=-12$; $A_8=183$, $B_8=-14$; $A_9=185$, $B_9=-16$; $A_{10}=187$, $B_{10}=-18$; $A_{11}=189$, $B_{11}=-20$. $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$, and the 11 windows are $W_1[k-169, k]$, $W_2[k-171, k-2]$, $W_3[k-173, k-4]$, $W_4[k-175, k-6]$, $W_5[k-177, k-8]$, $W_6[k-179, k-10]$, $W_7[k-181, k-12]$, W_8

$[k-183, k-14]$, $W_9[k-185, k-16]$, $W_{10}[k-187, k-18]$, and $W_{11}[k-189, k-20]$ separately. k_a is a data stream dividing point, and a direction of searching for a data stream dividing point shown in FIG. 29 is from left to right. After a minimum data chunk of 4 KB is skipped from the data stream dividing point k_a , an end position of the minimum data chunk of 4 KB serves as a next potential dividing point k_i , and a point p_{ix} is determined for the potential dividing point k_i . In this embodiment, according to the rule preset on the deduplication server 103, x indicates consecutive natural numbers from 1 to 11 separately. In the implementation manner shown in FIG. 29, according to the preset rule, 11 windows determined for the potential dividing point k_i are $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-171, k_i-2]$, $W_{i3}[k_i-173, k_i-4]$, $W_{i4}[k_i-175, k_i-6]$, $W_{i5}[k_i-177, k_i-8]$, $W_{i6}[k_i-179, k_i-10]$, $W_{i7}[k_i-181, k_i-12]$, $W_{i8}[k_i-183, k_i-14]$, $W_{i9}[k_i-185, k_i-16]$, $W_{i10}[k_i-187, k_i-18]$, and $W_{i11}[k_i-189, k_i-20]$ separately. It is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{i2}[k_i-171, k_i-2]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{i3}[k_i-173, k_i-4]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i-175, k_i-6]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-177, k_i-8]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i-179, k_i-10]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{i7}[k_i-181, k_i-12]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i-183, k_i-14]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[k_i-185, k_i-16]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i-187, k_i-18]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[k_i-189, k_i-20]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{i1} meets the preset condition C_1 , the at least a part of data in the window W_{i2} meets the preset condition C_2 , the at least a part of data in the window W_{i3} meets the preset condition C_3 , the at least a part of data in the window W_{i4} meets the preset condition C_4 , the at least a part of data in the window W_{i5} meets the preset condition C_5 , the at least a part of data in the window W_{i6} meets the preset condition C_6 , the at least a part of data in the window W_{i7} meets the preset condition C_7 , the at least a part of data in the window W_{i8} meets the preset condition C_8 , the at least a part of data in the window W_{i9}

meets the preset condition C_9 , the at least a part of data in the window W_{i10} meets the preset condition C_{10} , and the at least a part of data in the window W_{i11} meets the preset condition C_{11} , the current potential dividing point k_i is a data stream dividing point. When the at least a part of data in any window of the 11 windows does not meet the corresponding preset condition, for example, as shown in FIG. 30, the at least a part of data in $W_{i4}[k_i-175, k_i-6]$ does not meet the preset condition C_4 , a next potential dividing point is selected. For differentiation from the potential dividing point k_i , the next potential dividing point is represented as k_j here, where k_j is located on the right of k_i , and a distance between k_j and k_i is 1 byte. As shown in FIG. 30, according to the rule preset on the deduplication server 103, for the potential dividing point k_j , 11 windows are determined, and are $W_{j1}[k_j-169, k_j]$, $W_{j2}[k_j-171, k_j-2]$, $W_{j3}[k_j-173, k_j-4]$, $W_{j4}[k_j-175, k_j-6]$, $W_{j5}[k_j-177, k_j-8]$, $W_{j6}[k_j-179, k_j-10]$, $W_{j7}[k_j-181, k_j-12]$, $W_{j8}[k_j-183, k_j-14]$, $W_{j9}[k_j-185, k_j-16]$, $W_{j10}[k_j-187, k_j-18]$, and $W_{j11}[k_j-189, k_j-20]$ separately, where $C_1=C_2=C_3=C_4=C_5=C_6=C_7=C_8=C_9=C_{10}=C_{11}$. It is determined whether at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{j2}[k_j-171, k_j-2]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{j3}[k_j-173, k_j-4]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{j4}[k_j-175, k_j-6]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-177, k_j-8]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-179, k_j-10]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-181, k_j-12]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-183, k_j-14]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-185, k_j-16]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-187, k_j-18]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-189, k_j-20]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{j1} meets the preset condition C_1 , the at least a part of data in the window W_{j2} meets the preset condition C_2 , the at least a part of data in the window W_{j3} meets the preset condition

C_3 , the at least a part of data in the window W_{j4} meets the preset condition C_4 , the at least a part of data in the window W_{j5} meets the preset condition C_5 , the at least a part of data in the window W_{j6} meets the preset condition C_6 , the at least a part of data in the window W_{j7} meets the preset condition C_7 , the at least a part of data in the window W_{j8} meets the preset condition C_8 , the at least a part of data in the window W_{j9} meets the preset condition C_9 , the at least a part of data in the window W_{j10} meets the preset condition C_{10} , and the at least a part of data in the window W_{j11} meets the preset condition C_{11} , the current potential dividing point k_j is a data stream dividing point. When it is determined that the at least a part of data in any window of the windows W_{j1} , W_{j2} , W_{j3} , W_{j4} , W_{j5} , W_{j6} , W_{j7} , W_{j8} , W_{j9} , W_{j10} , and W_{j11} does not meet a preset condition, for example, as shown in FIG. 31, when the at least a part of data in $W_{j3}[k_j-173, k_j-4]$ does not meet the preset condition C_3 , k_j is located on the right of k_i and N bytes are skipped from k_i along the direction of searching for a data stream dividing point, where the N bytes are not greater than $\|B_4\| + \max_x(\|A_x\|)$. In the implementation manner shown in FIG. 28, the N bytes are not greater than 195 bytes, and in this embodiment, N=15, so as to obtain a next potential dividing point. For differentiation from the potential dividing points k_i and k_j , the next potential dividing point is represented as k_l . According to the rule preset on the deduplication server 103 in the implementation manner in FIG. 29, for the potential dividing point k_l , 11 windows are determined, and are $W_{l1}[k_l-169, k_l]$, $W_{l2}[k_l-171, k_l-2]$, $W_{l3}[k_l-173, k_l-4]$, $W_{l4}[k_l-175, k_l-6]$, $W_{l5}[k_l-177, k_l-8]$, $W_{l6}[k_l-179, k_l-10]$, $W_{l7}[k_l-181, k_l-12]$, $W_{l8}[k_l-183, k_l-14]$, $W_{l9}[k_l-185, k_l-16]$, $W_{l10}[k_l-187, k_l-18]$, and $W_{l11}[k_l-189, k_l-20]$ separately. It is determined whether at least a part of data in $W_{l1}[k_l-169, k_l]$ meets the preset condition C_1 , it is determined whether at least a part of data in $W_{l2}[k_l-171, k_l-2]$ meets the preset condition C_2 , it is determined whether at least a part of data in $W_{l3}[k_l-173, k_l-4]$ meets the preset condition C_3 , it is determined whether at least a part of data in $W_{l4}[k_l-175, k_l-6]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{l5}[k_l-177, k_l-8]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{l6}[k_l-179, k_l-10]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{l7}[k_l-181, k_l-12]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{l8}[k_l-183, k_l-14]$ meets the

preset condition C_8 , it is determined whether at least a part of data in $W_{l9}[k_l-185, k_l-16]$ meets
 the preset condition C_9 , it is determined whether at least a part of data in $W_{l10}[k_l-187, k_l-18]$
 meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{l11}[k_l-189,$
 $k_l-20]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the
 5 window W_{l1} meets the preset condition C_1 , the at least a part of data in the window W_{l2} meets
 the preset condition C_2 , the at least a part of data in the window W_{l3} meets the preset condition
 C_3 , the at least a part of data in the window W_{l4} meets the preset condition C_4 , the at least a part
 of data in the window W_{l5} meets the preset condition C_5 , the at least a part of data in the window
 W_{l6} meets the preset condition C_6 , the at least a part of data in the window W_{l7} meets the preset
 10 condition C_7 , the at least a part of data in the window W_{l8} meets the preset condition C_8 , the at
 least a part of data in the window W_{l9} meets the preset condition C_9 , the at least a part of data in
 the window W_{l10} meets the preset condition C_{10} , and the at least a part of data in the window
 W_{l11} meets the preset condition C_{11} , the current potential dividing point k_l is a data stream
 dividing point. When the at least a part of data in any window of the windows $W_{l1}, W_{l2}, W_{l3},$
 15 $W_{l4}, W_{l5}, W_{l6}, W_{l7}, W_{l8}, W_{l9}, W_{l10},$ and W_{l11} does not meet a preset condition, a next
 potential dividing point is selected. For differentiation from the potential dividing points $k_i, k_j,$
 and k_l , the next potential dividing point is represented as k_m , where k_m is located on the right of
 k_l , and a distance between k_m and k_l is 1 byte. According to the rule preset on the deduplication
 server 103 in the embodiment shown in FIG. 29, 11 windows determined for the potential dividing
 20 point k_m are $W_{m1}[k_m-169, k_m], W_{m2}[k_m-171, k_m-2], W_{m3}[k_m-173, k_m-4], W_{m4}[k_m-175,$
 $k_m-6], W_{m5}[k_m-177, k_m-8], W_{m6}[k_m-179, k_m-10], W_{m7}[k_m-181, k_m-12], W_{m8}[k_m-183,$
 $k_m-14], W_{m9}[k_m-185, k_m-16], W_{m10}[k_m-187, k_m-18],$ and $W_{m11}[k_m-189, k_m-20]$ separately.
 It is determined whether at least a part of data in $W_{m1}[k_m-169, k_m]$ meets the preset condition C_1 ,
 it is determined whether at least a part of data in $W_{m2}[k_m-171, k_m-2]$ meets the preset condition
 25 C_2 , it is determined whether at least a part of data in $W_{m3}[k_m-173, k_m-4]$ meets the preset
 condition C_3 , it is determined whether at least a part of data in $W_{m4}[k_m-175, k_m-6]$ meets the
 preset condition C_4 , it is determined whether at least a part of data in $W_{m5}[k_m-177, k_m-8]$ meets
 the preset condition C_5 , it is determined whether at least a part of data in $W_{m6}[k_m-179, k_m-10]$

meets the preset condition C_6 , it is determined whether at least a part of data in $W_{m7}[k_m-181, k_m-12]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{m8}[k_m-183, k_m-14]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{m9}[k_m-185, k_m-16]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{m10}[k_m-187, k_m-18]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{m11}[k_m-189, k_m-20]$ meets the preset condition C_{11} . When it is determined that the at least a part of data in the window W_{m1} meets the preset condition C_1 , the at least a part of data in the window W_{m2} meets the preset condition C_2 , the at least a part of data in the window W_{m3} meets the preset condition C_3 , the at least a part of data in the window W_{m4} meets the preset condition C_4 , the at least a part of data in the window W_{m5} meets the preset condition C_5 , the at least a part of data in the window W_{m6} meets the preset condition C_6 , the at least a part of data in the window W_{m7} meets the preset condition C_7 , the at least a part of data in the window W_{m8} meets the preset condition C_8 , the at least a part of data in the window W_{m9} meets the preset condition C_9 , the at least a part of data in the window W_{m10} meets the preset condition C_{10} , and the at least a part of data in the window W_{m11} meets the preset condition C_{11} , the current potential dividing point k_m is a data stream dividing point. When the at least a part of data in any window does not meet a preset condition, skipping is executed according to the solution described above to obtain a next potential dividing point, and it is determined whether the next potential dividing point is a data stream dividing point.

[0177] An embodiment of the present invention provides a method for determining whether at least a part of data in a window $W_{iz}[k_i-A_z, k_i+B_z]$ meets a preset condition C_z . In this embodiment, it is determined, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i-A_z, k_i+B_z]$ meets the preset condition C_z , and the implementation manner shown in FIG. 21 is used as an example. According to a rule preset on a deduplication server 103, a window $W_{i1}[k_i-169, k_i]$ is determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets a preset condition C_1 . As shown in FIG. 32, W_{i1} represents the window $W_{i1}[k_i-169, k_i]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . In FIG. 32, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The selected

5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits

corresponding to the 255 bytes may be represented as: $\begin{pmatrix} a_{1,1} & a_{1,2} & \cdots & a_{1,8} \\ a_{2,1} & a_{2,2} & \cdots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{255,1} & a_{255,2} & \cdots & a_{255,8} \end{pmatrix}$, where when

5 $a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, and a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the 255 bytes, and may be represented as:

$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \cdots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \cdots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{a255,1} & V_{a255,2} & \cdots & V_{a255,8} \end{pmatrix}$. A large quantity of random numbers is selected to form a matrix.

Once being formed, the matrix formed by the random numbers remains unchanged. For example,
10 255*8 random numbers are selected from random numbers that follow specific distribution (normal

distribution is used as an example here) to form a matrix R: $\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,8} \end{pmatrix}$, where

random numbers of an mth row of the matrix V_a and an mth row of the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am}=V_{am,1}*h_{m,1}+$
 $V_{am,2}*h_{m,2}+...+V_{am,8}*h_{m,8}$. S_{a1} , S_{a2} , ..., and S_{a255} are obtained according to the method, and a

15 quantity K of values meeting a specific condition (being greater than 0 is used as an example here) among S_{a1} , S_{a2} , ..., and S_{a255} is counted. Because the matrix R follows normal distribution, S_{am} still follows normal distribution as the matrix R does. According to a probability theory, a probability that a random number in normal distribution is greater than 0 is 1/2; a probability that each value among S_{a1} , S_{a2} , ..., and S_{a255} is greater than 0 is 1/2, and therefore, K meets

20 binomial distribution: $P(k=n)=C_{255}^n(\frac{1}{2})^n(\frac{1}{2})^{255-n}=C_{255}^n(\frac{1}{2})^{255}$. According to a counting result, it is determined whether the quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{a255} is an even number; a probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates

that the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . When K is an odd number, it indicates that the at least a part of data in $W_1[k_i-169, k_i]$ does not meet the preset condition C_1 . C_1 here refers to that the quantity K, which is obtained according to the foregoing manner, of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{a255} is an even number. In the

implementation manner shown in FIG. 21, for $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, $W_{i4}[k_i-172, k_i-3]$, $W_{i5}[k_i-173, k_i-4]$, $W_{i6}[k_i-174, k_i-5]$, $W_{i7}[k_i-175, k_i-6]$, $W_{i8}[k_i-176, k_i-7]$, $W_{i9}[k_i-177, k_i-8]$, $W_{i10}[k_i-178, k_i-9]$, and $W_{i11}[k_i-179, k_i-10]$, the windows are the same in size, that is, all the windows have a size of 169 bytes, and meanwhile, manners of determining whether at least a part of data in a window meets a preset condition are also the same.

For details, refer to the foregoing description of determining whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 32, "" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i2}[k_i-170, k_i-1]$ meets a preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $b_{m,1}$, ..., and $b_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits corresponding to the 255 bytes

may be represented as:
$$\begin{pmatrix} b_{1,1} & b_{1,2} & \cdots & b_{1,8} \\ b_{2,1} & b_{2,2} & \cdots & b_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ b_{255,1} & b_{255,2} & \cdots & b_{255,8} \end{pmatrix},$$
 where when $b_{m,n}=1$, $V_{bm,n}=1$, and when $b_{m,n}$

$=0$, $V_{bm,n}=-1$, where $b_{m,n}$ represents any one of $b_{m,1}$, ..., and $b_{m,8}$, and a matrix V_b is obtained according to a conversion relationship between $b_{m,n}$ and $V_{bm,n}$ from the bits corresponding to the

255 bytes, and may be represented as:
$$\begin{pmatrix} V_{b1,1} & V_{b1,2} & \cdots & V_{b1,8} \\ V_{b2,1} & V_{b2,2} & \cdots & V_{b2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{b255,1} & V_{b255,2} & \cdots & V_{b255,8} \end{pmatrix}.$$
 A manner of determining

whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets a preset condition is the same as a manner of determining whether at least a part of data in the window $W_{i2}[k_i-170, k_i-1]$ meets a preset

$$\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,8} \end{pmatrix}$$

condition; therefore the matrix R is used: and random numbers of an mth row of the matrix V_b and the mth row of the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{bm} = V_{bm,1} * h_{m,1} + V_{bm,2} * h_{m,2} + \dots + V_{bm,8} * h_{m,8}$. $S_{b1}, S_{b2}, \dots$, and S_{b255} are obtained according to the method, and a quantity K of values meeting a specific condition (being greater than 0 is used as an example here) among $S_{b1}, S_{b2}, \dots$, and S_{b255} is counted. Because the matrix R follows normal distribution, S_{bm} still follows normal distribution as the matrix R does. According to the probability theory, the probability that a random number in normal distribution is greater than 0 is 1/2; a probability that each value among $S_{b1}, S_{b2}, \dots$, and S_{b255} is greater than 0 is 1/2, and therefore, K meets binomial distribution:

$$P(k = n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$$

According to a counting result, it is determined whether the quantity K of values greater than 0 among $S_{b1}, S_{b2}, \dots$, and S_{b255} is an even number; the probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at least a part of data in $W_{i2} [k_i - 170, k_i - 1]$ meets the preset condition C_2 . When K is an odd number, it indicates that the at least a part of data in $W_{i2} [k_i - 170, k_i - 1]$ does not meet the preset condition C_2 . C_2 here refers to that the quantity K, which is obtained according to the foregoing manner, of values greater than 0 among $S_{b1}, S_{b2}, \dots$, and S_{b255} is an even number. In the implementation manner shown in FIG. 21, the at least a part of data in $W_{i2} [k_i - 170, k_i - 1]$ meets the preset condition C_2 .

[0178] Therefore, as shown in FIG. 32, "" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i3} [k_i - 171, k_i - 2]$ meets a preset condition C_3 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Then, the method for determining whether at least a part of data in the windows $W_{i1} [k_i - 169, k_i]$ and $W_{i2} [k_i - 170, k_i - 1]$ meets a preset condition is used to determine whether at least a part of data in $W_{i3} [k_i - 171, k_i - 2]$ meets the preset condition C_3 . In the implementation manner shown in FIG. 21, the at least a

part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition. As shown in FIG. 32, "" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i4}[k_i-172, k_i-3]$ meets a preset condition C_4 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Then, the method for determining whether at least a part of data in the windows $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, and $W_{i3}[k_i-171, k_i-2]$ meets a preset condition is used to determine whether the at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets the preset condition C_4 . In the implementation manner shown in FIG. 21, the at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets the preset condition C_4 . As shown in FIG. 32, "" represents 1 byte selected when it is determined whether at least a part of data in the window $W_{i5}[k_i-173, k_i-4]$ meets a preset condition C_5 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Then, the method for determining whether at least a part of data in the windows $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, and $W_{i4}[k_i-172, k_i-3]$ meets a preset condition is used to determine whether the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets the preset condition C_5 . In the implementation manner shown in FIG. 21, the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 .

[0179] When the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , 7 bytes are skipped from a point p_{i5} along a direction of searching for a data stream dividing point, and a next potential dividing point k_j is obtained at an end position of a 7th byte. As shown in FIG. 22, according to the rule preset on the deduplication server 103, a window $W_{j1}[k_j-169, k_j]$ is determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 33, W_{j1} represents a window, and 5 bytes are selected to determine whether the at least a part of data in the window meets the preset condition C_1 . In FIG. 33, "" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $a_{m,1}'$, ...,

and $a_{m,8}'$, representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits

corresponding to the 255 bytes may be represented as: $\begin{pmatrix} a_{1,1}' & a_{1,2}' & \dots & a_{1,8}' \\ a_{2,1}' & a_{2,2}' & \dots & a_{2,8}' \\ \vdots & \vdots & \vdots & \vdots \\ a_{255,1}' & a_{255,2}' & \dots & a_{255,8}' \end{pmatrix}$, where when

$a_{m,n}'=1$, $V_{am,n}'=1$, and when $a_{m,n}'=0$, $V_{am,n}'=-1$, where $a_{m,n}'$ represents any one of $a_{m,1}'$, ..., and $a_{m,8}'$, and a matrix V_a' is obtained according to a conversion relationship between $a_{m,n}'$ and

5 $V_{am,n}'$ from the bits corresponding to the 255 bytes, and may be represented as:

$\begin{pmatrix} V_{a1,1}' & V_{a1,2}' & \dots & V_{a1,8}' \\ V_{a2,1}' & V_{a2,2}' & \dots & V_{a2,8}' \\ \vdots & \vdots & \vdots & \vdots \\ V_{a255,1}' & V_{a255,2}' & \dots & V_{a255,8}' \end{pmatrix}$. A manner of determining whether at least a part of data in the

window meets a preset condition is the same as a manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets a preset condition. Therefore the matrix R is used:

$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \dots & h_{255,8} \end{pmatrix}$, and random numbers of an mth row of the matrix V_a' and the mth row

10 of the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am}' = V_{am,1}' * h_{m,1} + V_{am,2}' * h_{m,2} + \dots + V_{am,8}' * h_{m,8}$. S_{a1}' , S_{a2}' , ..., and S_{a255}' are

obtained according to the method, and a quantity K of values meeting a specific condition (being greater than 0 is used as an example here) among S_{a1}' , S_{a2}' , ..., and S_{a255}' is counted. Because the matrix R follows normal distribution, S_{am}' still follows normal distribution as the matrix R

15 does. According to the probability theory, the probability that a random number in normal distribution is greater than 0 is 1/2; a probability that each value among S_{a1}' , S_{a2}' , ..., and S_{a255}' is greater than 0 is 1/2, and therefore K meets binomial distribution:

$P(k=n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$. According to a counting result, it is determined whether

the quantity K of values greater than 0 among S_{a1}' , S_{a2}' , ..., and S_{a255}' is an even number; the

20 probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . When K is an odd number,

it indicates that the at least a part of data in $W_{j1}[k_j-169, k_j]$ does not meet the preset condition C_1 .

[0180] A manner of determining whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in W_{j2}

5 $[k_j-170, k_j-1]$ meets the preset condition C_2 . Therefore, as shown in FIG. 33, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. Selected 5 bytes of data are used repeatedly 51 times to obtain 255 bytes in total, so as to increase randomness. Each byte thereof is formed by 8 bits, which are denoted as $b_{m,1}'$, ..., and $b_{m,8}'$,
10 representing the 1st bit to the 8th bit of an mth byte in the 255 bytes, and therefore, bits

corresponding to the 255 bytes may be represented as:
$$\begin{pmatrix} b_{1,1}' & b_{1,2}' & \dots & b_{1,8}' \\ b_{2,1}' & b_{2,2}' & \dots & b_{2,8}' \\ \vdots & \vdots & \vdots & \vdots \\ b_{255,1}' & b_{255,2}' & \dots & b_{255,8}' \end{pmatrix}$$
, where when

$b_{m,n}'=1$, $V_{bm,n}'=1$, and when $b_{m,n}'=0$, $V_{bm,n}'=-1$, where $b_{m,n}'$ represents any one of $b_{m,1}'$, ..., and $b_{m,8}'$, and a matrix V_b' is obtained according to a conversion relationship between $b_{m,n}'$ and $V_{bm,n}'$ from the bits corresponding to the 255 bytes, and may be represented as:

15
$$\begin{pmatrix} V_{b1,1} & V_{b1,2} & \dots & V_{b1,8} \\ V_{b2,1} & V_{b2,2} & \dots & V_{b2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{b255,1} & V_{b255,2} & \dots & V_{b255,8} \end{pmatrix}$$
. A manner of determining whether at least a part of data in the window

$W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_1 , and therefore the

matrix R is still used:
$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \dots & h_{255,8} \end{pmatrix}$$
. Random numbers of an mth row of the matrix V_b'

and the mth row of the matrix R are multiplied and products are added to obtain a value, which is
20 specifically represented as $S_{bm}' = V_{bm,1}' * h_{m,1} + V_{bm,2}' * h_{m,2} + \dots + V_{bm,8}' * h_{m,8}$. S_{b1}' , S_{b2}' , ..., and S_{b255}' are obtained according to the method, and a quantity K of values meeting a specific

condition (being greater than 0 is used as an example here) among S_{b1}' , S_{b2}' , ..., and S_{b255}' is counted. Because the matrix R follows normal distribution, S_{bm}' still follows normal distribution as the matrix R does. According to the probability theory, the probability that a random number in normal distribution is greater than 0 is 1/2; a probability that each value among S_{b1}' , S_{b2}' , ..., and S_{b255}' is greater than 0 is 1/2, and therefore K meets binomial distribution:

$$P(k = n) = C_{255}^n \left(\frac{1}{2}\right)^n \left(\frac{1}{2}\right)^{255-n} = C_{255}^n \left(\frac{1}{2}\right)^{255}$$

According to a counting result, it is determined whether the quantity K of values greater than 0 among S_{b1}' , S_{b2}' , ..., and S_{b255}' is an even number; the probability that a random number in binomial distribution is an even number is 1/2, and therefore, K meets a condition with a probability of 1/2. When K is an even number, it indicates that the at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 . When K is an odd number, it indicates that the at least a part of data in $W_{j2}[k_j-170, k_j-1]$ does not meet the preset condition C_2 . Similarly, a manner of determining whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets a preset condition C_{11} , which are not described herein again.

[0181] In this embodiment, it is determined, by using a random function, whether at least a part of data in a window $W_{iz}[k_i - A_z, k_i + B_z]$ meets a preset condition C_z . The implementation manner shown in FIG. 21 is still used as an example. According to a rule preset on a deduplication server 103, a window $W_{i1}[k_i-169, k_i]$ is determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . As

shown in FIG. 32, W_{i1} represents the window $W_{i1}[k_i-169, k_i]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . In FIG. 32, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes "■". In one implementation manner, a hash function is used to calculate the selected 5 bytes, and values obtained by means of calculation by using the hash function are in fixed and even distribution. If a value obtained by means of calculation by using the hash function is an even number, it is determined that the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . That is, C_1 represents that a value obtained according to the foregoing manner and by means of calculation by using the hash function is an even number. Therefore, a probability that at least a part of data in $W_{i1}[k_i-169, k_i]$ meets a preset condition is 1/2. In the implementation manner shown in FIG. 21, it is determined, by using a hash function, whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets a preset condition C_2 , whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets a preset condition C_3 , whether at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets a preset condition C_4 , and whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets a preset condition C_5 . For specific implementation, reference may be made to the description of the manner of determining, by using a hash function, whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 in the implementation manner shown in FIG. 21, which is not described herein again.

[0182] When the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , 7 bytes are skipped from the potential dividing point k_i along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of a 7th byte. As shown in FIG. 22, according to the rule preset on the deduplication server 103, a window $W_{j1}[k_j-169, k_j]$ is determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 33, W_{j1} represents the window $W_{j1}[k_j-169, k_j]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . In FIG. 33, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes "■". The 5 bytes selected from

the window $W_{j1}[k_j-169, k_j]$ are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . In FIG. 33, a manner of determining whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 . Therefore, as shown in FIG. 33, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes "". Selected 5 bytes are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 . In FIG. 33, a manner of determining whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . Therefore, as shown in FIG. 33, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 , and there are 42 bytes between two adjacent selected bytes "". Selected 5 bytes are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . In FIG. 33, a manner of determining whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 is the same as a manner of determining whether at least a part of data in the window $W_{i4}[k_i-172, k_i-3]$ meets the preset condition C_4 . Therefore, as shown in FIG. 33, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , and there are 42 bytes between two adjacent selected bytes "". Selected 5 bytes are calculated by using a hash function. If an obtained value is an even number, the at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 . According to the foregoing method, it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets a

preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets a preset condition C_{11} , which are not described herein again.

5 **[0183]** In this embodiment, it is determined, by using a random function, whether at least a part of data in a window $W_{iz}[k_i-A_z, k_i+B_z]$ meets a preset condition C_z . The implementation manner shown in FIG. 21 is used as an example. According to a rule preset on a deduplication server 103, a window $W_{i1}[k_i-169, k_i]$ is determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . As
 10 shown in FIG. 32, W_{i1} represents the window $W_{i1}[k_i-169, k_i]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . In FIG. 32, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented
 15 as a_1, a_2, a_3, a_4 , and a_5 respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_r of a_1, a_2, a_3, a_4 , and a_5 meets $0 \leq a_r \leq 255$. a_1, a_2, a_3, a_4 , and a_5 form a 1*5 matrix. 256*5 random numbers are selected from random numbers that follow

binomial distribution to form a matrix R that is represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,5} & h_{255,5} & \cdots & h_{255,5} \end{pmatrix}.$$

[0184] The matrix R is searched for a corresponding value according to the value of a_1 and a
 20 column in which a_1 is located. For example, if $a_1=36$, and a_1 is located in a 1st column, a value corresponding to $h_{36,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_2 and a column in which a_2 is located. For example, if $a_2=48$, and a_2 is located in a 2nd column, a value corresponding to $h_{48,2}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_3 and a column in which a_3 is
 25 located. For example, if $a_3=26$, and a_3 is located in a 3rd column, a value corresponding to $h_{26,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_4

and a column in which where a_4 is located. For example, if $a_4=26$, and a_4 is located in a 4th column, a value corresponding to $h_{26,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_5 and a column in which a_5 is located. For example, if $a_5=88$, and a_5 is located in a 5th column, a value corresponding to $h_{88,5}$ is searched

5 for. $S_1 = h_{36,1} + h_{48,2} + h_{26,3} + h_{26,4} + h_{88,5}$, and because the matrix R follows binomial distribution, S_1 also follows binomial distribution. When S_1 is an even number, the at least a part of data in W_{i1} $[k_i-169, k_i]$ meets the preset condition C_1 ; when S_1 is an odd number, the at least a part of data in $W_{i1}[k_i-169, k_i]$ does not meet the preset condition C_1 . A probability that S_1 is an even number is 1/2, and C_1 represents that S_1 that is obtained by means of calculation according to the

10 foregoing manner is an even number. In the embodiment shown in FIG. 21, the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . As shown in FIG. 32, "⊠" represents 1 byte separately selected when it is determined whether at least a part of data in the window $W_{i2}[k_i-170, k_i-1]$ meets a preset condition C_2 . In FIG. 32, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected

15 bytes. The bytes "⊠" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1, b_2, b_3, b_4 , and b_5 respectively. Because 1 byte is formed by 8 bits, each byte "⊠" serves as a value, and any b_r of b_1, b_2, b_3, b_4 , and b_5 meets $0 \leq b_r \leq 255$. b_1, b_2, b_3, b_4 and b_5 form a 1*5 matrix. In this implementation manner, manners of determining whether at least a part of data in W_{i1} and W_{i2} meets a preset condition are the

20 same, and therefore the matrix R is still used. The matrix R is searched for a corresponding value according to the value of b_1 and a column in which b_1 is located. For example, if $b_1=66$, and b_1 is located in a 1st column, a value corresponding to $h_{66,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_2 and a column in which b_2 is located. For example, if $b_2=48$, and b_2 is located in a 2nd column, a value corresponding to $h_{48,2}$ is searched

25 for. The matrix R is searched for a corresponding value according to the value of b_3 and a column in which b_3 is located. For example, if $b_3=99$, and b_3 is located in a 3rd column, a value corresponding to $h_{99,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_4 and a column in which b_4 is located. For example, if $b_4=26$, and

b_4 is located in a 4th column, a value corresponding to $h_{26,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_5 and a column in which b_5 is located. For example, if $b_5=90$, and b_5 is located in a 5th column, a value corresponding to $h_{90,5}$ is searched for. $S_2 = h_{66,1} + h_{48,2} + h_{99,3} + h_{26,4} + h_{90,5}$, and because the matrix R follows binomial distribution, S_2 also follows binomial distribution. When S_2 is an even number, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 ; when S_2 is an odd number, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ does not meet the preset condition C_2 . A probability that S_2 is an even number is 1/2. In the embodiment shown in FIG. 21, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 . By using the same rule, separately, it is determined whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i-174, k_i-5]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7}[k_i-175, k_i-6]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i-176, k_i-7]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[k_i-177, k_i-8]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i-178, k_i-9]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[k_i-179, k_i-10]$ meets a preset condition C_{11} . In the implementation manner shown in FIG. 21, the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , 7 bytes are skipped from the potential dividing point k_i along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of a 7th byte. As shown in FIG. 22, according to the rule preset on the deduplication server 103, a window $W_{j1}[k_j-169, k_j]$ is determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 33, W_{j1} represents the window $W_{j1}[k_j-169, k_j]$, and it is determined whether the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . In FIG. 33, each of bytes "■" whose

sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1' , a_2' , a_3' , a_4' , and a_5' respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_r' of a_1' , a_2' , a_3' , a_4' , and a_5' meets $0 \leq a_r' \leq 255$. a_1' , a_2' , a_3' , a_4' , and a_5' form a 1*5 matrix. The manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as the manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, the matrix R is still used,

and is represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,5} \end{pmatrix}.$$

[0185] The matrix R is searched for a corresponding value according to the value of a_1' and a column in which a_1' is located. For example, if $a_1'=16$, and a_1' is located in a 1st column, a value corresponding to $h_{16,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_2' and a column in which a_2' is located. For example, if $a_2'=98$, and a_2' is located in a 2nd column, a value corresponding to $h_{98,2}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_3' and a column in which a_3' is located. For example, if $a_3'=56$, and a_3' is located in a 3rd column, a value corresponding to $h_{56,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_4' and a column in which a_4' is located. For example, if $a_4'=36$, and a_4' is located in a 4th column, a value corresponding to $h_{36,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of a_5' and a column in which a_5' is located. For example, if $a_5'=99$, and a_5' is located in a 5th column, a value corresponding to $h_{99,5}$ is searched for. $S_1' = h_{16,1} + h_{98,2} + h_{56,3} + h_{36,4} + h_{99,5}$, and because the matrix R follows binomial distribution, S_1' also follows binomial distribution. When S_1' is an even number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 ; when S_1' is an odd number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ does not meet the preset condition C_1 . A probability that S_1' is an even number is 1/2.

[0186] A manner of determining whether at least a part of data in $W_{i2} [k_i - 170, k_i - 1]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2} [k_j - 170, k_j - 1]$ meets the preset condition C_2 . Therefore, as shown in FIG. 33, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2} [k_j - 170, k_j - 1]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. Selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1' , b_2' , b_3' , b_4' , and b_5' respectively. Because 1 byte is formed by 8 bits, each byte "" serves as a value, and any b_r' of b_1' , b_2' , b_3' , b_4' , and b_5' meets $0 \leq b_r' \leq 255$. b_1' , b_2' , b_3' , b_4' , and b_5' form a 1*5 matrix. The matrix R the same as that used when it is determined whether the at least a part of data in the window $W_{i2} [k_i - 170, k_i - 1]$ meets the preset condition C_2 is used. The matrix R is searched for a corresponding value according to the value of b_1' and a column in which b_1' is located. For example, if $b_1' = 210$, and b_1' is located in a 1st column, a value corresponding to $h_{210,1}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_2' and a column in which b_2' is located. For example, if $b_2' = 156$, and b_2' is located in a 2nd column, a value corresponding to $h_{156,2}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_3' and a column in which b_3' is located. For example, if $b_3' = 144$, and b_3' is located in a 3rd column, a value corresponding to $h_{144,3}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_4' and a column in which b_4' is located. For example, if $b_4' = 60$, and b_4' is located in a 4th column, a value corresponding to $h_{60,4}$ is searched for. The matrix R is searched for a corresponding value according to the value of b_5' and a column in which b_5' is located. For example, if $b_5' = 90$, and b_5' is located in a 5th column, a value corresponding to $h_{90,5}$ is searched for. $S_2' = h_{210,1} + h_{156,2} + h_{144,3} + h_{60,4} + h_{90,5}$. The same as the determining condition of S_2 , when S_2' is an even number, the at least a part of data in $W_{j2} [k_j - 170, k_j - 1]$ meets the preset condition C_2 , and when S_2' is an odd number, the at least a part of data in $W_{j2} [k_j - 170, k_j - 1]$ does not meet the preset condition C_2 . A probability that S_2' is an even number is 1/2.

[0187] Similarly, a manner of determining whether at least a part of data in $W_{j3}[k_i-171, k_i-2]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets the preset condition C_{11} , which are not described herein again.

[0188] In this embodiment, it is determined, by using a random function, whether at least a part of data in a window $W_{iz}[k_i - A_z, k_i + B_z]$ meets a preset condition C_z . The implementation manner shown in FIG. 21 is used as an example. According to a rule preset on a deduplication server 103, a window $W_{i1}[k_i-169, k_i]$ is determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets a preset condition C_1 . As shown in FIG. 32, W_{i1} represent the window $W_{i1}[k_i-169, k_i]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . In

FIG. 32, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1, a_2, a_3, a_4 , and a_5 respectively. Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_s of a_1, a_2, a_3, a_4 , and a_5 meets $0 \leq a_s \leq 255$. a_1, a_2, a_3, a_4 and a_5 form a 1*5 matrix. 256*5 random numbers are selected from random numbers that follow

binomial distribution to form a matrix R that is represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,1} & h_{255,2} & \cdots & h_{255,5} \end{pmatrix} \cdot 256*5$$

random numbers are selected from random numbers that follow binomial distribution to form a

matrix G that is represented as:

$$\begin{pmatrix} g_{0,1} & g_{0,2} & \cdots & g_{0,5} \\ g_{1,1} & g_{1,2} & \cdots & g_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ g_{255,5} & g_{255,5} & \cdots & g_{255,5} \end{pmatrix}.$$

[0189] According to the value of a_1 and a column in which a_1 is located, for example, a_1 =36, and a_1 is located in a 1st column, the matrix R is searched for a value corresponding to $h_{36,1}$,

5 and the matrix G is searched for a value corresponding to $g_{36,1}$. According to the value of a_2 and a column in which a_2 is located, for example, a_2 =48, and a_2 is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{48,2}$, and the matrix G is searched for a value corresponding to $g_{48,2}$. According to the value of a_3 and a column in which a_3 is located, for example, a_3 =26, and a_3 is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{26,3}$, and the matrix G is searched for a value corresponding to $g_{26,3}$. According

10 to the value of a_4 and a column in which a_4 is located, for example, a_4 =26, and a_4 is located in a 4th column, the matrix R is searched for a value corresponding to $h_{26,4}$, and the matrix G is searched for a value corresponding to $g_{26,4}$. According to the value of a_5 and a column in which a_5 is located, for example, a_5 =88, and a_5 is located in a 5th column, the matrix R is searched for a value corresponding to $h_{88,5}$, and the matrix G is searched for a value corresponding to $g_{88,5}$.

$S_{1h} = h_{36,1} + h_{48,2} + h_{26,3} + h_{26,4} + h_{88,5}$, and because the matrix R follows binomial distribution, S_{1h} also follows binomial distribution. $S_{1g} = g_{36,1} + g_{48,2} + g_{26,3} + g_{26,4} + g_{88,5}$, and because the matrix G follows binomial distribution, S_{1g} also follows binomial distribution. When one of S_{1h} and S_{1g} is an even number, the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 ;

20 when both S_{1h} and S_{1g} are odd numbers, the at least a part of data in $W_{i1}[k_i-169, k_i]$ does not meet the preset condition C_1 , and C_1 indicates that one of S_{1h} and S_{1g} obtained according to the foregoing method is an even number. Because both S_{1h} and S_{1g} follow binomial distribution, a probability that S_{1h} is an even number is 1/2, a probability that S_{1g} is an even number is 1/2, and a probability that one of S_{1h} and S_{1g} is an even number is 1-1/4=3/4. Therefore, a probability

25 that the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 is 3/4. In the embodiment shown in FIG. 21, the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset

condition C_1 . In the implementation manner shown in FIG. 21, for $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, $W_{i4}[k_i-172, k_i-3]$, $W_{i5}[k_i-173, k_i-4]$, $W_{i6}[k_i-174, k_i-5]$, $W_{i7}[k_i-175, k_i-6]$, $W_{i8}[k_i-176, k_i-7]$, $W_{i9}[k_i-177, k_i-8]$, $W_{i10}[k_i-178, k_i-9]$, and $W_{i11}[k_i-179, k_i-10]$, the windows are the same in size, that is, all the windows have a size of 169 bytes, and meanwhile manners of determining whether at least a part of data in a window meets a preset condition are also the same. For details, refer to the foregoing description of determining whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 32, "⊠" represents 1 byte separately selected when it is determined whether at least a part of data in the window $W_{i2}[k_i-170, k_i-1]$ meets a preset condition C_2 . In FIG. 32, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "⊠" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1 , b_2 , b_3 , b_4 , and b_5 respectively. Because 1 byte is formed by 8 bits, each byte "⊠" serves as a value, and any b_s of b_1 , b_2 , b_3 , b_4 and b_5 meets $0 \leq b_s \leq 255$. b_1 , b_2 , b_3 , b_4 , and b_5 form a 1*5 matrix. In this implementation manner, manners of determining whether at least a part of data in each window meets a preset condition are the same, and therefore the same matrices R and G are still used. According to the value of b_1 and a column in which b_1 is located, for example, $b_1=66$, and b_1 is located in a 1st column, the matrix R is searched for a value corresponding to $h_{66,1}$, and the matrix G is searched for a value corresponding to $g_{66,1}$. According to the value of b_2 and a column in which b_2 is located, for example, $b_2=48$, and b_2 is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{48,2}$, and the matrix G is searched for a value corresponding to $g_{48,2}$. According to the value of b_3 and a column in which b_3 is located, for example, $b_3=99$, and b_3 is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{99,3}$, and the matrix G is searched for a value corresponding to $g_{99,3}$. According to the value of b_4 and a column in which b_4 is located, for example, $b_4=26$, and b_4 is located in a 4th column, the matrix R is searched for a value corresponding to $h_{26,4}$, and the matrix G is searched for a value corresponding to $g_{26,4}$. According to the value of b_5 and a column in which b_5 is located, for example, $b_5=90$, and b_5 is located in a 5th column, the matrix R is searched for a value corresponding to $h_{90,5}$, and the matrix G is searched for a value corresponding to $g_{90,5}$.

$S_{2h} = h_{66,1} + h_{48,2} + h_{99,3} + h_{26,4} + h_{90,5}$, and because the matrix R follows binomial distribution, S_{2h} also follows binomial distribution. $S_{2g} = g_{66,1} + g_{48,2} + g_{99,3} + g_{26,4} + g_{90,5}$, and because the matrix G follows binomial distribution, S_{2g} also follows binomial distribution. When one of S_{2h} and S_{2g} is an even number, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 ;

5 when both S_{2h} and S_{2g} are odd numbers, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ does not meet the preset condition C_2 . A probability that one of S_{2h} and S_{2g} is an even number is 3/4. In the embodiment shown in FIG. 21, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 . By using the same rule, separately, it is determined whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets a preset condition C_3 , it is determined whether at least a part of

10 data in $W_{i4}[k_i-172, k_i-3]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i-174, k_i-5]$ meets a preset condition C_6 , it is determined whether at least a part of data in $W_{i7}[k_i-175, k_i-6]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i-176, k_i-7]$ meets a preset condition C_8 , it is determined whether at least a part of

15 data in $W_{i9}[k_i-177, k_i-8]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i-178, k_i-9]$ meets a preset condition C_{10} , and it is determined whether at least a part of data in $W_{i11}[k_i-179, k_i-10]$ meets a preset condition C_{11} . In the implementation manner shown in FIG. 21, the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , 7 bytes are skipped from the potential dividing point k_i along a direction of

20 searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of a 7th byte. As shown in FIG. 22, according to the rule preset on the deduplication server 103, a window $W_{j1}[k_j-169, k_j]$ is determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the

25 window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 33, W_{j1} represents the window $W_{j1}[k_j-169, k_j]$, and it is determined whether the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . In FIG. 33, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two

adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are converted into decimal values that are represented as a_1' , a_2' , a_3' , a_4' , and a_5' respectively.

Because 1 byte is formed by 8 bits, each byte "■" serves as a value, and any a_s' of a_1' , a_2' , a_3' , a_4' , and a_5' meets $0 \leq a_s' \leq 255$. a_1' , a_2' , a_3' , a_4' and a_5' form a 1*5 matrix. The

5 matrices R and G the same as those used when it is determined whether the at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 are used, and are represented as:

$$\begin{pmatrix} h_{0,1} & h_{0,2} & \cdots & h_{0,5} \\ h_{1,1} & h_{1,2} & \cdots & h_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ h_{255,5} & h_{255,5} & \cdots & h_{255,5} \end{pmatrix} \text{ and } \begin{pmatrix} g_{0,1} & g_{0,2} & \cdots & g_{0,5} \\ g_{1,1} & g_{1,2} & \cdots & g_{1,5} \\ \vdots & \vdots & \vdots & \vdots \\ g_{255,5} & g_{255,5} & \cdots & g_{255,5} \end{pmatrix} \text{ respectively.}$$

[0190] According to the value of a_1' and a column in which a_1' is located, for example, a_1' =16, and a_1' is located in a 1st column, the matrix R is searched for a value corresponding to $h_{16,1}$,

10 and the matrix G is searched for a value corresponding to $g_{16,1}$. According to the value of a_2' and a column in which a_2' is located, for example, a_2' =98, and a_2' is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{98,2}$, and the matrix G is searched for a value corresponding to $g_{98,2}$. According to the value of a_3' and a column in which a_3' is located, for example, a_3' =56, and a_3' is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{56,3}$, and the matrix G is searched for a value corresponding to $g_{56,3}$. According

15 to the value of a_4' and a column in which a_4' is located, for example, a_4' =36, and a_4' is located in a 4th column, the matrix R is searched for a value corresponding to $h_{36,4}$, and the matrix G is searched for a value corresponding to $g_{36,4}$. According to the value of a_5' and a column in which a_5' is located, for example, a_5' =99, and a_5' is located in a 5th column, the matrix R is searched for a value corresponding to $h_{99,5}$, and the matrix G is searched for a value corresponding

20 to $g_{99,5}$. $S_{1h}' = h_{16,1} + h_{98,2} + h_{56,3} + h_{36,4} + h_{99,5}$, and because the matrix R follows binomial distribution, S_{1h}' also follows binomial distribution. $S_{1g}' = g_{16,1} + g_{98,2} + g_{56,3} + g_{36,4} + g_{99,5}$, and because the matrix G follows binomial distribution, S_{1g}' also follows binomial distribution. When one of S_{1h}' and S_{1g}' is an even number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 ; when both S_{1h}' and S_{1g}' are odd numbers, the at least a part of data in W_{j1}
25 $[k_j-169, k_j]$ does not meet the preset condition C_1 . A probability that one of S_{1h}' and S_{1g}' is

an even number is 3/4.

[0191] A manner of determining whether at least a part of data in $W_{i2} [k_i - 170, k_i - 1]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2} [k_j - 170, k_j - 1]$ meets the preset condition C_2 . Therefore, as shown in FIG. 33, "⊠" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2} [k_j - 170, k_j - 1]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. In FIG. 33, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "⊠" whose sequence numbers are 170, 128, 86, 44, and 2 are converted into decimal values that are represented as b_1' , b_2' , b_3' , b_4' , and b_5' respectively. Because 1 byte is formed by 8 bits, each byte "⊠" serves as a value, and any b_s' of b_1' , b_2' , b_3' , b_4' , and b_5' meets $0 \leq b_s' \leq 255$. b_1' , b_2' , b_3' , b_4' , and b_5' form a 1*5 matrix. The matrices R and G the same as those used when it is determined whether the at least a part of data in the window $W_{i2} [k_i - 170, k_i - 1]$ meets the preset condition C_2 are used. According to the value of b_1' and a column in which b_1' is located, for example, $b_1' = 210$, and b_1' is located in a 1st column, the matrix R is searched for a value corresponding to $h_{210,1}$, and the matrix G is searched for a value corresponding to $g_{210,1}$. According to the value of b_2' and a column in which b_2' is located, for example, $b_2' = 156$, and b_2' is located in a 2nd column, the matrix R is searched for a value corresponding to $h_{156,2}$, and the matrix G is searched for a value corresponding to $g_{156,2}$. According to the value of b_3' and a column in which b_3' is located, for example, $b_3' = 144$, and b_3' is located in a 3rd column, the matrix R is searched for a value corresponding to $h_{144,3}$, and the matrix G is searched for a value corresponding to $g_{144,3}$. According to the value of b_4' and a column in which b_4' is located, for example, $b_4' = 60$, and b_4' is located in a 4th column, the matrix R is searched for a value corresponding to $h_{60,4}$, and the matrix G is searched for a value corresponding to $g_{60,4}$. According to the value of b_5' and a column in which b_5' is located, for example, $b_5' = 90$, and b_5' is located in a 5th column, the matrix R is searched for a value corresponding to $h_{90,5}$, and the matrix G is searched for a value corresponding to $g_{90,5}$. $S_{2h}' = h_{210,1} + h_{156,2} + h_{144,3} + h_{60,4} + h_{90,5}$, and $S_{2g}' = g_{210,1} + g_{156,2} + g_{144,3} + g_{60,4} + g_{90,5}$. When one of S_{2h}' and S_{2g}' is an even number, the at least a part of data in $W_{j2} [k_j$

-170, k_j-1] meets the preset condition C_2 ; when both S_{2h}' and S_{2g}' are odd numbers, the at least a part of data in $W_{j2}[k_j-170, k_j-1]$ does not meet the preset condition C_2 . A probability that one of S_{2h}' and S_{2g}' is an even number is 3/4.

[0192] Similarly, a manner of determining whether at least a part of data in $W_{j3}[k_i-171, k_i-2]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets the preset condition C_{11} , which are not described herein again.

[0193] In this embodiment, it is determined, by using a random function, whether at least a part of data in the window $W_{iz}[k_i-A_z, k_i+B_z]$ meets the preset condition C_z . The implementation manner shown in FIG. 21 is used as an example. According to a rule preset on a deduplication server 103, a window $W_{i1}[k_i-169, k_i]$ is determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets a preset condition C_1 . As shown in FIG. 32, W_{i1} represents the window $W_{i1}[k_i-169, k_i]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . In FIG. 32, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are regarded as 40 sequential bits, which are represented as $a_1, a_2, a_3, a_4, \dots$, and a_{40} separately. For any a_t of $a_1, a_2, a_3, a_4, \dots$, and a_{40} , when $a_t=0$, $V_{at}=-1$, and when $a_t=1$, $V_{at}=1$. According to a correspondence between a_t and V_{at} , $V_{a1}, V_{a2}, V_{a3}, V_{a4}, \dots$, and V_{a40} are generated. 40 random numbers are selected from

random numbers that follow normal distribution, and are represented as: $h_1, h_2, h_3, h_4, \dots$, and h_{40} separately. $S_a = V_{a1} * h_1 + V_{a2} * h_2 + V_{a3} * h_3 + V_{a4} * h_4 + \dots + V_{a40} * h_{40}$. Because $h_1, h_2, h_3, h_4, \dots$, and h_{40} follow normal distribution, S_a also follows normal distribution. When S_a is a positive number, the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 ; when S_a is a negative number or 0, the at least a part of data in $W_{i1}[k_i-169, k_i]$ does not meet the preset condition C_1 . A probability that S_a is a positive number is 1/2. In the embodiment shown in FIG. 21, the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . As shown in FIG. 32, "⊠" represents 1 byte separately selected when it is determined whether at least a part of data in a window $W_{i2}[k_i-170, k_i-1]$ meets a preset condition C_2 . In FIG. 32, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "⊠" whose sequence numbers are 170, 128, 86, 44, and 2 are regarded as 40 sequential bits, which are represented as $b_1, b_2, b_3, b_4, \dots$, and b_{40} separately. For any b_t of $b_1, b_2, b_3, b_4, \dots$, and b_{40} , when $b_t=0$, $V_{bt}=-1$, and when $b_t=1$, $V_{bt}=1$. According to a correspondence between b_t and V_{bt} , $V_{b1}, V_{b2}, V_{b3}, V_{b4}, \dots$, and V_{b40} are generated. A manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 . Therefore, the same random numbers are used: $h_1, h_2, h_3, h_4, \dots$, and h_{40} , and $S_b = V_{b1} * h_1 + V_{b2} * h_2 + V_{b3} * h_3 + V_{b4} * h_4 + \dots + V_{b40} * h_{40}$. Because $h_1, h_2, h_3, h_4, \dots$, and h_{40} follow normal distribution, S_b also follows normal distribution. When S_b is a positive number, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 ; when S_b is a negative number or 0, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ does not meet the preset condition C_2 . A probability that S_b is a positive number is 1/2. In the embodiment shown in FIG. 21, the at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 . By using the same rule, separately it is determined whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets a preset condition C_5 , it is determined whether at least a part of data in $W_{i6}[k_i-174, k_i-5]$ meets a preset condition C_6 , it is determined

whether at least a part of data in $W_{i7}[k_i-175, k_i-6]$ meets a preset condition C_7 , it is determined whether at least a part of data in $W_{i8}[k_i-176, k_i-7]$ meets a preset condition C_8 , it is determined whether at least a part of data in $W_{i9}[k_i-177, k_i-8]$ meets a preset condition C_9 , it is determined whether at least a part of data in $W_{i10}[k_i-178, k_i-9]$ meets a preset condition C_{10} , and it is

5 determined whether at least a part of data in $W_{i11}[k_i-179, k_i-10]$ meets a preset condition C_{11} . In the implementation manner shown in FIG. 21, the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , 7 bytes are skipped from the potential dividing point k_i along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of a 7th byte. As shown in FIG. 22, according to the rule preset on the

10 deduplication server 103, a window $W_{j1}[k_j-169, k_j]$ is determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as the manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, as shown in FIG. 33, W_{j1} represents the window $W_{j1}[k_j-169, k_j]$, and 5 bytes are selected to determine whether

15 at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . In FIG. 33, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 in FIG. 33 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. The bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 are regarded as 40 sequential bits, which are represented as a_1' , a_2' , a_3' , a_4' , ..., and a_{40}' separately. For any a_t' of a_1' , a_2' , a_3' , a_4' , ..., and a_{40}' , when

20 $a_t'=0$, $V_{at}'=-1$, and when $a_t'=1$, $V_{at}'=1$. According to a correspondence between a_t' and V_{at}' , V_{a1}' , V_{a2}' , V_{a3}' , V_{a4}' , ..., and V_{a40}' are generated. The manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as the manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, the same random numbers are used: h_1 , h_2 , h_3 , h_4 , ..., and h_{40} .

25 $S_a' = V_{a1}' * h_1 + V_{a2}' * h_2 + V_{a3}' * h_3 + V_{a4}' * h_4 + ... + V_{a40}' * h_{40}$. Because h_1 , h_2 , h_3 , h_4 , ..., and h_{40} follow normal distribution, S_a' also follows normal distribution. When S_a' is a positive number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 ; when S_a' is a negative number or 0, the at least a part of data in $W_{j1}[k_j-169, k_j]$ does not meet the preset

condition C_1 . A probability that S_a' is a positive number is $1/2$.

[0194] The manner of determining whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 . Therefore, as shown in FIG. 33, "" represents 1 byte selected when it is determined whether the at least a part of data in the window $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 , and there are 42 bytes between two adjacent selected bytes. In FIG. 33, selected bytes are represented as sequence numbers 170, 128, 86, 44, and 2 separately, and there are 42 bytes between two adjacent selected bytes. The bytes "" whose sequence numbers are 170, 128, 86, 44, and 2 are regarded as 40 sequential bits, which are represented as b_1' , b_2' , b_3' , b_4' , ..., and b_{40}' separately. For any b_t' of b_1' , b_2' , b_3' , b_4' , ..., and b_{40}' , when $b_t'=0$, $V_{bt}'=-1$, and when $b_t'=1$, $V_{bt}'=1$. According to a correspondence between b_t' and V_{bt}' , V_{b1}' , V_{b2}' , V_{b3}' , V_{b4}' , ..., and V_{b40}' are generated. The manner of determining whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 is the same as the manner of determining whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 . Therefore, the same random numbers are used: h_1 , h_2 , h_3 , h_4 , ..., and h_{40} , and $S_b' = V_{b1}' * h_1 + V_{b2}' * h_2 + V_{b3}' * h_3 + V_{b4}' * h_4 + ... + V_{b40}' * h_{40}$. Because h_1 , h_2 , h_3 , h_4 , ..., and h_{40} follow normal distribution, S_b' also follows normal distribution. When S_b' is a positive number, the at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 ; when S_b' is a negative number or 0, the at least a part of data in $W_{j2}[k_j-170, k_j-1]$ does not meet the preset condition C_2 . A probability that S_b' is a positive number is $1/2$.

[0195] Similarly, a manner of determining whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j-7]$ meets the preset condition C_8 ,

it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets the preset condition C_{11} , which are not described herein again.

5 **[0196]** In this embodiment, it is determined, by using a random function, whether at least a part of data in a window $W_{iz}[k_i - A_z, k_i + B_z]$ meets a preset condition C_z . The implementation manner shown in FIG. 21 is still used as an example. According to a rule preset on a deduplication server 103, for the potential dividing point k_i , a window $W_{i1}[k_i-169, k_i]$ is determined for a potential dividing point k_i , and it is determined whether at least a part of data in $W_{i1}[k_i-169, k_i]$ meets a preset condition C_1 . As shown in FIG. 32, W_{i1} represents the window $W_{i1}[k_i-169, k_i]$, and 5 bytes are selected to determine whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . In FIG. 32, each of bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes. Each of the bytes "■" whose sequence numbers are 169, 127, 85, 43, and 1 is converted into 1 decimal number, the range of which is $0-(2^{40}-1)$. An even distribution random number generator is used to generate 1 designated value for each decimal number in $0-(2^{40}-1)$, and a correspondence R between each decimal number in $0-(2^{40}-1)$ and the designated value is recorded. Once being designated, a designated value corresponding to a decimal number remains unchanged, and the designated value follows even distribution. If the designated value is an even number, the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 ; if the designated value is an odd number, the at least a part of data in $W_{i1}[k_i-169, k_i]$ does not meet the preset condition C_1 . C_1 represents that the designated value obtained according to the foregoing method is an even number. Because a probability that a random number in even distribution is an even number is $1/2$, a probability that the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 is $1/2$.

15 In the implementation manner shown in FIG. 21, by using the same rule, separately, it is determined whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets a preset condition C_2 , it is determined whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets a preset condition C_3 , it is determined whether at least a part of data in $W_{i4}[k_i-172, k_i-3]$ meets a preset condition C_4 , it is determined whether at least a part of data in $W_{i5}[k_i-173, k_i-4]$ meets a preset condition C_5 , which are not described herein again.

20

25

30

[0197] When the at least a part of data in $W_{i5}[k_i-173, k_i-4]$ does not meet the preset condition C_5 , 7 bytes are skipped from the potential dividing point k_i along a direction of searching for a data stream dividing point, and a current potential dividing point k_j is obtained at an end position of a 7th byte. As shown in FIG. 22, according to the rule preset on the deduplication server 103, a window $W_{j1}[k_j-169, k_j]$ is determined for the potential dividing point k_j . A manner of determining whether at least a part of data in the window $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is the same as a manner of determining whether at least a part of data in the window $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . Therefore, the same correspondence R between each decimal number in $0-(2^{40}-1)$ and a designated value is used. As shown in FIG. 33, W_{j1} represents the window, and 5 bytes are selected to determine whether the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 . In FIG. 33, "■" represents 1 selected byte, and there are 42 bytes between two adjacent selected bytes "■". Each of bytes "■" whose sequence numbers 169, 127, 85, 43, and 1 is converted into 1 decimal number, and R is searched for a designated value corresponding to the decimal number. If the designated value is an even number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 ; if the designated value is an odd number, the at least a part of data in $W_{j1}[k_j-169, k_j]$ does not meet the preset condition C_1 . Because a probability that a random number in even distribution is an even number is $1/2$, a probability that the at least a part of data in $W_{j1}[k_j-169, k_j]$ meets the preset condition C_1 is $1/2$. Similarly, a manner of determining whether at least a part of data in $W_{i2}[k_i-170, k_i-1]$ meets the preset condition C_2 is the same as a manner of determining whether at least a part of data in $W_{j2}[k_j-170, k_j-1]$ meets the preset condition C_2 , and a manner of determining whether at least a part of data in $W_{i3}[k_i-171, k_i-2]$ meets the preset condition C_3 is the same as a manner of determining whether at least a part of data in $W_{j3}[k_j-171, k_j-2]$ meets the preset condition C_3 . Similarly, it is determined whether at least a part of data in $W_{j4}[k_j-172, k_j-3]$ meets the preset condition C_4 , it is determined whether at least a part of data in $W_{j5}[k_j-173, k_j-4]$ meets the preset condition C_5 , it is determined whether at least a part of data in $W_{j6}[k_j-174, k_j-5]$ meets the preset condition C_6 , it is determined whether at least a part of data in $W_{j7}[k_j-175, k_j-6]$ meets the preset condition C_7 , it is determined whether at least a part of data in $W_{j8}[k_j-176, k_j$

-7] meets the preset condition C_8 , it is determined whether at least a part of data in $W_{j9}[k_j-177, k_j-8]$ meets the preset condition C_9 , it is determined whether at least a part of data in $W_{j10}[k_j-178, k_j-9]$ meets the preset condition C_{10} , and it is determined whether at least a part of data in $W_{j11}[k_j-179, k_j-10]$ meets the preset condition C_{11} , which are not described herein again.

5 **[0198]** The deduplication server 103 in the embodiment of the present invention shown in FIG. 1 refers to an apparatus that can implement a technical solution described in an embodiment of the present invention, and as shown in FIG. 18, usually includes a central processing unit, a primary memory, and an input/output interface. The central processing unit, the primary memory, and the input/output interface communicate with each other. The main memory stores an executable instruction, and the central processing unit executes the executable instruction stored in the main memory to perform a specific function, so that the deduplication server 103 has a specific function, for example, searching for a data stream dividing point described in FIG. 20 to FIG. 33 in the embodiments of the present invention. Therefore, as shown in FIG. 19, according to the embodiments of the present invention shown in FIG. 20 to FIG. 33, for the deduplication server 103, 10 a rule is preset on the deduplication server 103, where the rule is: for a potential dividing point k , determining M windows $W_x[k-A_x, k+B_x]$ and a preset condition C_x corresponding to the window $W_x[k-A_x, k+B_x]$, where x indicates consecutive natural numbers from 1 to M , $M \geq 2$, and A_x and B_x are integers.

[0199] The deduplication server 103 includes a determining unit 1901 and a judging and processing unit 1902. The determining unit 1901 is configured to perform step (a): 20

(a) determining a corresponding window $W_{iz}[k_i-A_z, k_i+B_z]$ for a current potential dividing point k_i according to the rule, where i and z are integers, and $1 \leq z \leq M$.

[0200] The judging and processing unit 1902 is configured to: determine whether at least a part of data in the window $W_{iz}[k_i-A_z, k_i+B_z]$ meets a preset condition C_z ;

25 when the at least a part of data in the window $W_{iz}[k_i-A_z, k_i+B_z]$ does not meet the preset condition C_z , skip N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along a direction of searching for a data stream dividing point, where $N*U$ is not greater than $\|B_z\| + \max_x(\|A_x\|)$, so as to obtain a new potential dividing point, where the determining unit 1901 performs step (a) for the new potential dividing point; and 30

when at least a part of data in each window $W_{ix}[k_i-A_x, k_i+B_x]$ of M windows of the

current potential dividing point k_i meets the preset condition C_x , select the current potential dividing point k_i as a data stream dividing point.

[0201] Further, the rule further includes that at least two windows $W_{ie}[k_i - A_e, k_i + B_e]$ and $W_{if}[k_i - A_f, k_i + B_f]$ meet conditions $|A_e + B_e| = |A_f + B_f|$ and $C_e = C_f$. Further, the rule further includes that A_e and A_f are positive integers. Further, the rule further includes $A_e - 1 = A_f$ and $B_e + 1 = B_f$.

[0202] Further, the judging and processing unit 1902 is specifically configured to determine, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z . Still further, the judging and processing unit 1902 specifically determines, by using a hash function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0203] Further, the judging and processing unit 1902 is configured to: when the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ does not meet the preset condition C_z , skip the N minimum units U for searching for a data stream dividing point from the current potential dividing point k_i along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and the determining unit 1901 performs step (a) for the new potential dividing point, where according to the rule, a left boundary of a window $W_{ic}[k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz}[k_i - A_z, k_i + B_z]$ or a left boundary of a window $W_{ic}[k_i - A_c, k_i + B_c]$ that is determined for the new potential dividing point falls within a range of the window $W_{iz}[k_i - A_z, k_i + B_z]$, where the window $W_{ic}[k_i - A_c, k_i + B_c]$ determined for the new potential dividing point is a window ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M windows that are determined for the new potential dividing point according to the rule.

[0204] Further, that the judging and processing unit 1902 determines, by using a random function, whether the at least a part of data in the window $W_{iz}[k_i - A_z, k_i + B_z]$ meets the preset condition C_z specifically includes:

selecting F bytes in the window $W_{iz}[k_i - A_z, k_i + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, where $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits

corresponding to the F*H bytes may be represented as: $\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F^*H,1} & a_{F^*H,2} & \dots & a_{F^*H,8} \end{pmatrix}$, where when

$a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, where $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is represented as:

5 $\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF^*H,1} & V_{aF^*H,2} & \dots & V_{aF^*H,8} \end{pmatrix}$, F*H*8 random numbers are selected from random numbers

following normal distribution to form a matrix R, the matrix R is represented as:

$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F^*H,1} & h_{F^*H,2} & \dots & h_{F^*H,8} \end{pmatrix}$, random numbers in an mth row of the matrix V_a and an mth row of

the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF^*H} are obtained

10 in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF^*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [k_i - A_z, k_i + B_z]$ meets the preset condition C_z .

[0205] According to the method for searching for a data stream dividing point based on a server in the embodiments of the present invention shown in FIG. 20 to FIG. 33, a window $W_{ix} [k_i - A_x,$

15 $k_i + B_x]$ is determined for a potential dividing point k_i , where, x indicates consecutive natural numbers from 1 to M separately, and $M \geq 2$. It may be determined in parallel whether at least a part of data in each window of M windows meets a preset condition C_x , or it may be determined sequentially whether at least a part of data in windows meets a preset condition, or it may be first determined that at least a part of data in a window $W_{i1} [p_{i1} - A_1, p_{i1} + B_1]$ meets a preset

20 condition C_1 , then it is determined that at least a part of data in $W_{i2} [p_{i2} - A_2, p_{i2} + B_2]$ meets a preset condition C_2 , until it is determined that at least a part of data in $W_{im} [p_{im} - A_m, p_{im} + B_m]$ meets a preset condition C_m . Other windows in this embodiment are determined in a same manner

as the above, which is not described again.

[0206] In addition, according to the embodiments of the present invention shown in FIG. 20 to FIG. 33, a rule is preset on the deduplication server 103, where the rule is: determining M windows $W_x[k-A_x, k+B_x]$ for a potential dividing point k and a preset condition C_x corresponding to the window $W_x[k-A_x, k+B_x]$, where x indicates consecutive natural numbers from 1 to M separately, and $M \geq 2$. In the preset rule, $A_1, A_2, A_3, \dots$, and A_m may be not all equal, $B_1, B_2, B_3, \dots$, and B_m may be not all equal, and $C_1, C_2, C_3, \dots$, and C_M may also be not all the same. In the implementation manner shown in FIG. 21, for $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, $W_{i4}[k_i-172, k_i-3]$, $W_{i5}[k_i-173, k_i-4]$, $W_{i6}[k_i-174, k_i-5]$, $W_{i7}[k_i-175, k_i-6]$, $W_{i8}[k_i-176, k_i-7]$, $W_{i9}[k_i-177, k_i-8]$, $W_{i10}[k_i-178, k_i-9]$, and $W_{i11}[k_i-179, k_i-10]$, the windows are the same in size, that is, all the windows have a size of 169 bytes, and meanwhile manners of determining whether at least a part of data in a window meets a preset condition are also the same. For details, refer to the foregoing description of determining whether the at least a part of data in $W_{i1}[k_i-169, k_i]$ meets the preset condition C_1 . However, in the implementation manner shown in FIG. 11, the windows $W_{i1}[k_i-169, k_i]$, $W_{i2}[k_i-170, k_i-1]$, $W_{i3}[k_i-171, k_i-2]$, $W_{i4}[k_i-172, k_i-3]$, $W_{i5}[k_i-173, k_i-4]$, $W_{i6}[k_i-174, k_i-5]$, $W_{i7}[k_i-175, k_i-6]$, $W_{i8}[k_i-176, k_i-7]$, $W_{i9}[k_i-177, k_i-8]$, $W_{i10}[k_i-168, k_i+1]$, and $W_{i11}[k_i-179, k_i+3]$ may be different in size, and meanwhile the manners of determining whether at least a part of data in a window meets a preset condition may also be different. In all embodiments, according to the rule preset on the deduplication server 103, a manner of determining whether at least a part of data in the window W_{i1} meets the preset condition C_1 is certainly the same as a manner of determining whether at least a part of data in a window W_{j1} meets the preset condition C_1 , a manner of determining whether at least a part of data in W_{i2} meets the preset condition C_2 is certainly the same as a manner of determining whether at least a part of data in W_{j2} meets the preset condition $C_2, \dots$, and a manner of determining whether at least a part of data in a window W_{iM} meets a preset condition C_M is certainly the same as a manner of determining whether at least a part of data in a window W_{jM} meets the preset condition C_M , which are not described herein again.

[0207] According to the embodiments of the present invention shown in FIG. 20 to FIG. 33, the rule is preset on the deduplication server 103, k_a, k_i, k_j, k_l , and k_m are potential dividing points obtained in the search for a dividing point along a direction of searching for a data stream

dividing point, and k_a , k_i , k_j , k_l , and k_m all follow the rule. In this embodiment of the present invention, the window $W_x[k-A_x, k+B_x]$ represents a specific range, and data is selected in the specific range to determine whether the data meets the preset condition C_x . Specifically, in the specific range, a part of data may be selected or all data may be selected to determine whether the data meets the preset condition C_x . Reference may be made to the window $W_x[k-A_x, k+B_x]$ for the concept of a window specifically used in this embodiment of the present invention, which is not described herein again.

[0208] In the window $W_x[k-A_x, k+B_x]$, $(k-A_x)$ and $(k+B_x)$ represent two boundaries of the window $W_x[k-A_x, k+B_x]$, where $(k-A_x)$ represents a boundary, which is in a direction opposite to the direction of searching for a data stream dividing point relative to the potential dividing point k , of the window $W_x[k-A_x, k+B_x]$, and $(k+B_x)$ represents a boundary, which is in the direction of searching for a data stream dividing point relative to the potential dividing point k , of the window $W_x[k-A_x, k+B_x]$. Specifically, in the embodiment of the present invention, the direction of searching for a data stream dividing point shown in FIG. 20 to FIG. 33 is from left to right; therefore, $(k-A_x)$ represents a boundary (that is, a left boundary), which is in a direction opposite to the direction of searching for a data stream dividing point relative to the potential dividing point k , of the window $W_x[k-A_x, k+B_x]$, and $(k+B_x)$ represents a boundary (that is, a right boundary), which is in the direction of searching for a data stream dividing point relative to the potential dividing point k , of the window $W_x[k-A_x, k+B_x]$. If the direction of searching for a data stream dividing point shown in FIG. 20 to FIG. 33 is from right to left, $(k-A_x)$ represents a boundary (that is, a right boundary), which is in a direction opposite to the direction of searching for a data stream dividing point relative to the potential dividing point k , of the window $W_x[k-A_x, k+B_x]$, and $(k+B_x)$ represents a boundary (that is, a left boundary), which is in the direction of searching for a data stream dividing point relative to the potential dividing point k , of the window $W_x[k-A_x, k+B_x]$.

[0209] A person of ordinary skill in the art may be aware that, in conjunction with various exemplary units and algorithm steps described in FIG. 20 to FIG. 33 of the embodiments of the present invention, a key feature in the embodiments of the present invention may be combined with other technologies and presented in a more complex form; however, the key feature of the present invention is still included. An alternative dividing point may be used in a real environment. For example, in an implementation manner, according to a rule preset on a deduplication server 103, for a potential dividing point k_i , 11 windows $W_x[k-A_x, k+B_x]$ and a preset condition C_x

corresponding to the window $W_x[k-A_x, k+B_x]$ are determined, where x indicates consecutive natural numbers from 1 to 11. When at least a part of data in each window $W_x[k-A_x, k+B_x]$ of the 11 windows meets the preset condition C_x , the potential dividing point k_i is a data stream dividing point. When no dividing point is found after a set maximum data chunk is exceeded, a
5 preset rule for the alternative point may be used. The preset rule for the alternative point is similar to the rule preset on the deduplication server 103, and the preset rule for the alternative point is: for example, for a potential dividing point k_i , determining 10 windows $W_x[k-A_x, k+B_x]$ and a preset condition C_x corresponding to the window $W_x[k-A_x, k+B_x]$, where x indicates consecutive natural numbers from 1 to 10. When it is determined that at least a part of data in each window W_x
10 $[k-A_x, k+B_x]$ of the 10 windows meets the preset condition C_x , the potential dividing point k_i is a data stream dividing point. When no data stream dividing point is found after a set maximum data chunk is exceeded, an end position of the maximum data chunk serves as a forced dividing point.

[0210] According to the embodiments of the present invention shown in FIG. 20 to FIG. 33, a rule is preset on the deduplication server 103, and in the rule, M windows are determined for a
15 potential dividing point k . It is not necessarily required that there be a potential dividing point k in advance, and the potential dividing point k may be determined by using the determined M windows.

[0211] A person of ordinary skill in the art may be aware that, in combination with the examples described in the embodiments disclosed in this specification, units and algorithm steps may be implemented by electronic hardware or a combination of computer software and electronic
20 hardware. Whether the functions are performed by hardware or software depends on particular applications and design constraint conditions of the technical solutions. A person skilled in the art may use different methods to implement the described functions for each particular application, but it should not be considered that the implementation goes beyond the scope of the present invention.

[0212] It may be clearly understood by a person skilled in the art that, for the purpose of
25 convenient and brief description, for a detailed working process of the foregoing system, apparatus, and unit, reference may be made to a corresponding process in the foregoing method embodiments, and details are not described herein again.

[0213] In the several provided embodiments, it should be understood that the disclosed system and method may be implemented in other manners. For example, the described apparatus
30 embodiment is merely exemplary. For example, the unit division is merely logical function division and may be other division in actual implementation. For example, a plurality of units or components may be combined or integrated into another system, or some features may be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or

communication connections may be implemented through some interfaces. The indirect couplings or communication connections between the apparatuses or units may be implemented in electronic, mechanical, or other forms.

[0214] The units described as separate parts may or may not be physically separate, and parts displayed as units may or may not be physical units, may be located in one position, or may be distributed on a plurality of network units. Some or all of the units may be selected according to actual needs to achieve the objectives of the solutions of the embodiments.

[0215] In addition, functional units in the embodiments of the present invention may be integrated into one processing unit, or each of the units may exist alone physically, or two or more units are integrated into one unit.

[0216] When the functions are implemented in the form of a software functional unit and sold or used as an independent product, the functions may be stored in a computer-readable non-volatile storage medium. Based on such an understanding, the technical solutions of the present invention essentially, or the part contributing to the prior art, or some of the technical solutions may be implemented in a form of a software product. The software product is stored in a non-volatile storage medium, and includes several instructions for instructing a computer device (which may be a personal computer, a server, or a network device) to perform all or some of the steps of the methods described in the embodiments of the present invention. The foregoing non-volatile storage medium includes: any medium that can store program code, such as a USB flash drive, a removable hard disk, a read-only memory (Read-Only Memory, ROM), a magnetic disk, or an optical disc.

[0217] The foregoing descriptions are merely specific implementation manners of the present invention, but are not intended to limit the protection scope of the present invention. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in the present invention shall fall within the protection scope of the present invention. Therefore, the protection scope of the present invention shall be subject to the protection scope of the claims.

CLAIMS

1. A method performed by a processor configured to execute instructions stored in memory, the method for selecting for a data stream dividing point to break a large amount of data into a plurality of blocks of data according to a rule, wherein the rule comprising: for a potential dividing point k ,
5 determining M points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window $W_x [p_x - A_x, p_x + B_x]$, wherein x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x and B_x are integers, the method comprising:

10 (a) determining a point p_{iz} and a window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point p_{iz} for a current potential dividing point k_i according to the rule, wherein i and z are integers, and $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ; and

15 when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point from the point p_{iz} along a direction of searching for a data stream dividing point, wherein $N*U$ is not greater than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, and performing step (a); and

20 (c) when at least a part of data in each window $W_{ix} [p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

2. The method according to claim 1, wherein the rule further comprises that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

25 3. The method according to claim 2, wherein the rule further comprises: relative to the potential dividing point k , the at least two points p_e and p_f are in a direction opposite to the direction of searching for a data stream dividing point.

4. The method according to claim 2, wherein the rule further comprises that a distance between

the at least two points p_e and p_f is 1 U.

5. The method according to claim 1, wherein determining, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

6. The method according to claim 5, wherein determining, by using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

7. The method according to claim 1, wherein when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, wherein the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

8. The method according to claim 5, wherein selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, wherein $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits corresponding to the F*H bytes can be represented as:

$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}, \text{ wherein when } a_{m,n}=1, V_{am,n}=1, \text{ and when } a_{m,n}=0, V_{am,n}=-1, \text{ wherein}$$

$a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits corresponding to the F*H bytes, the matrix V_a is

represented as: $\begin{pmatrix} V_{a1,1} & V_{a1,2} & \cdots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \cdots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF^*H,1} & V_{aF^*H,2} & \cdots & V_{aF^*H,8} \end{pmatrix}$, F^*H^*8 random numbers are selected from random

numbers following normal distribution to form a matrix R, the matrix R is represented as:

$\begin{pmatrix} h_{1,1} & h_{1,2} & \cdots & h_{1,8} \\ h_{2,1} & h_{2,2} & \cdots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F^*H,1} & h_{F^*H,2} & \cdots & h_{F^*H,8} \end{pmatrix}$, random numbers in an m th row of the matrix V_a and an m th row of

the matrix R are multiplied and products are added to obtain a value, which is specifically
 5 represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF^*H} are obtained in
 a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF^*H} is counted, and
 when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets
 the preset condition C_z .

9. A server for searching for a data stream dividing point according to a rule, wherein the rule
 10 comprising: for a potential dividing point k , determining M points p_x , a window $W_x [p_x - A_x, p_x + B_x]$
 corresponding to the point p_x , and a preset condition C_x corresponding to the window W_x
 $[p_x - A_x, p_x + B_x]$, wherein x indicates consecutive natural numbers from 1 to M, $M \geq 2$, and A_x
 and B_x are integers, the server comprises a central processing unit and a memory for storing
 computer instructions, wherein the central processing unit communicates with the memory to
 15 retrieve and execute the computer instructions to perform the steps of:

(a) determining a point p_{iz} and a window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ corresponding to the point
 p_{iz} for a current potential dividing point k_i according to the rule, wherein i and z are integers, and
 $1 \leq z \leq M$;

(b) determining whether at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets a
 20 preset condition C_z ; and

when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset
 condition C_z , skipping N minimum units U for searching for a data stream dividing point from the
 point p_{iz} along a direction of searching for a data stream dividing point, wherein $N*U$ is not greater
 than $\|B_z\| + \max_x (\|A_x\| + \|(k_i - p_{ix})\|)$, so as to obtain a new potential dividing point, and

performing step (a); and

(c) when at least a part of data in each window $W_{ix} [p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

5 10. The server according to claim 9, wherein the rule further comprises that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

11. The server according to claim 10, wherein the rule further comprises: relative to the potential dividing point k , the at least two points p_e and p_f are in a direction opposite to the direction of searching for a data stream dividing point.

10 12. The server according to claim 10, wherein the rule further comprises that a distance between the at least two points p_e and p_f is 1 U.

13. The server according to claims 9, wherein the central processing unit is specifically configured to determine, by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

15 14. The server according to claim 13, wherein the central processing unit is specifically configured to determine, by using a hash function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

15. The server according to claim 9, wherein when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, wherein the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

16. The server according to claim 13, wherein the determining, by the central processing unit by using a random function, whether the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z specifically comprises:

selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, wherein $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}$, ..., and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits

corresponding to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}$$
, wherein when

$a_{m,n}=1$, $V_{am,n}=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, wherein $a_{m,n}$ represents any one of $a_{m,1}$, ..., and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits

corresponding to the F*H bytes, the matrix V_a is represented as:
$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix}$$
,

F*H*8 random numbers are selected from random numbers following normal distribution to form a

matrix R, the matrix R is represented as:
$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \dots & h_{F*H,8} \end{pmatrix}$$
, random numbers in an mth

row of the matrix V_a and an mth row of the matrix R are multiplied and products are added to obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} ,

S_{a2} , ..., and S_{aF*H} are obtained in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

17. A non-transitory computer-readable storage medium, wherein the computer-readable storage medium is configured to store executable instructions that, when executed by a processors, prompts the processor to search for a data stream dividing point according to a rule, wherein the rule comprising: for a potential dividing point k , determining M points p_x , a window $W_x [p_x - A_x, p_x + B_x]$ corresponding to the point p_x , and a preset condition C_x corresponding to the window

$W_x[p_x - A_x, p_x + B_x]$, wherein x indicates consecutive natural numbers from 1 to M , $M \geq 2$, and A_x and B_x are integers, and,:

(a) determining p_{iz} and a window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ corresponding to p_{iz} for a current potential dividing point k_i according to the rule, wherein i and z are integers, and $1 \leq z \leq M$;

5 (b) determining whether at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets a preset condition C_z ; and

when the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , skipping N minimum units U for searching for a data stream dividing point from the point p_{iz} along a direction of searching for a data stream dividing point, wherein $N \cdot U$ is not greater
10 than $\| B_z \| + \max_x(\| A_x \| + \| (k_i - p_{ix}) \|)$, so as to obtain a new potential dividing point, and performing step (a); and

(c) when at least a part of data in each window $W_{ix}[p_{ix} - A_x, p_{ix} + B_x]$ of M windows of the current potential dividing point k_i meets the preset condition C_x , selecting the current potential dividing point k_i as a data stream dividing point.

15 18. The non-transitory computer-readable storage medium according to claim 17, wherein the rule further comprises that at least two points p_e and p_f meet conditions $A_e = A_f$, $B_e = B_f$, and $C_e = C_f$.

19. The non-transitory computer-readable storage medium according to claim 18, wherein the rule further comprises: relative to the potential dividing point k , the at least two points p_e and p_f
20 are in a direction opposite to the direction of searching for a data stream dividing point.

20. The non-transitory computer-readable storage medium according to claim 18, wherein the rule further comprises that a distance between the at least two points p_e and p_f is 1 U .

21. The non-transitory computer-readable storage medium according to claim 17, wherein determining, by the server by using a random function, whether the at least a part of data in the
25 window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

22. The non-transitory computer-readable storage medium according to claim 21, wherein determining, by the server by using a hash function, whether the at least a part of data in the window $W_{iz}[p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

23. The non-transitory computer-readable storage medium according to claim 17, wherein

when the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ does not meet the preset condition C_z , the N minimum units U for searching for a data stream dividing point are skipped from the point p_{iz} along the direction of searching for a data stream dividing point, so as to obtain the new potential dividing point, and according to the rule, a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point coincides with a right boundary of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ or a left boundary of a window $W_{ic} [p_{ic} - A_c, p_{ic} + B_c]$ corresponding to a point p_{ic} that is determined for the new potential dividing point falls within a range of the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, wherein the point p_{ic} determined for the new potential dividing point is a point ranking the first in a sequence, which is obtained according to the direction of searching for a data stream dividing point, of M points that are determined for the new potential dividing point according to the rule.

24. The non-transitory computer-readable storage medium according to claim 21, wherein selecting F bytes in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$, and using the F bytes repeatedly H times to obtain F*H bytes in total, wherein $F \geq 1$, each byte is formed by 8 bits, which are denoted as $a_{m,1}, \dots$, and $a_{m,8}$, representing the 1st bit to the 8th bit of an mth byte in the F*H bytes, bits corresponding

to the F*H bytes can be represented as:
$$\begin{pmatrix} a_{1,1} & a_{1,2} & \dots & a_{1,8} \\ a_{2,1} & a_{2,2} & \dots & a_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ a_{F*H,1} & a_{F*H,2} & \dots & a_{F*H,8} \end{pmatrix}$$
, wherein when $a_{m,n}=1$, $V_{am,n}$

$=1$, and when $a_{m,n}=0$, $V_{am,n}=-1$, wherein $a_{m,n}$ represents any one of $a_{m,1}, \dots$, and $a_{m,8}$, a matrix V_a is obtained according to a conversion relationship between $a_{m,n}$ and $V_{am,n}$ from the bits

corresponding to the F*H bytes, the matrix V_a is represented as:
$$\begin{pmatrix} V_{a1,1} & V_{a1,2} & \dots & V_{a1,8} \\ V_{a2,1} & V_{a2,2} & \dots & V_{a2,8} \\ \vdots & \vdots & \vdots & \vdots \\ V_{aF*H,1} & V_{aF*H,2} & \dots & V_{aF*H,8} \end{pmatrix}$$
,

F*H*8 random numbers are selected from random numbers following normal distribution to form a

matrix R, the matrix R is represented as:
$$\begin{pmatrix} h_{1,1} & h_{1,2} & \dots & h_{1,8} \\ h_{2,1} & h_{2,2} & \dots & h_{2,8} \\ \vdots & \vdots & \vdots & \vdots \\ h_{F*H,1} & h_{F*H,2} & \dots & h_{F*H,8} \end{pmatrix}$$
, random numbers in an mth

row of the matrix V_a and an mth row of the matrix R are multiplied and products are added to

obtain a value, which is specifically represented as $S_{am} = V_{am,1} * h_{m,1} + V_{am,2} * h_{m,2} + \dots + V_{am,8} * h_{m,8}$, S_{a1} , S_{a2} , ..., and S_{aF*H} are obtained in a same way, a quantity K of values greater than 0 among S_{a1} , S_{a2} , ..., and S_{aF*H} is counted, and when K is an even number, the at least a part of data in the window $W_{iz} [p_{iz} - A_z, p_{iz} + B_z]$ meets the preset condition C_z .

5