



159159

UUUUUZ



000000

DESCRIPTION

NEEDLE SELECTOR FOR KNITTING MACHINE,
AND NEEDLE SELECTING MODULE FINGER

5 TECHNICAL FIELD

The present invention relates to a needle selector for a knitting machine and, more particularly, to a needle selection finger formed by combining a plurality of members, and a needle selector for a
10 knitting machine which uses it.

BACKGROUND ART

In a knitting machine such as a circular knitting machine or weft knitting machine, vertical motions of
15 the working needle are selected on the basis of a knitting procedure stored in a storage such as a floppy disk, to knit a fabric of a desired knit texture. Various types of needle selectors are used for selecting the vertical motions of the working needle.

20 Before describing the needle selector according to the present invention, the outline of needle selection in a knitting machine will be explained with reference to a circular knitting machine schematically illustrated in Figs. 4A to 4C.

25 Fig. 4A is a schematic perspective view for explaining the basic knitting mechanism of a circular knitting machine. As illustrated in Fig. 4A, the

circular knitting machine has a knitting cylinder 1 rotatable in the direction indicated by an arrow A. A plurality of vertical grooves (not shown) are formed in the outer surface of the knitting cylinder 1 along its longitudinal axis. Working needles 2 are arranged slidably in the vertical grooves. Usually, needle selection jacks 12 are arranged under the working needles 2 to be able to abut against the lower parts of the working needles 2. A cylinder-shaped cam base 15a is stationarily arranged under the knitting cylinder 1. A plurality of raising cams 15 with predetermined shapes are arranged on the upper part of the cam base 15a at predetermined intervals.

The basic principle of knitting will be briefly described. When each working needle 2 on the rotating knitting cylinder 1 is thrust upward by the corresponding raising cam 15 through the needle selection jack 12, it projects from the upper surface of the knitting cylinder 1. A yarn 5 fed from a yarn bobbin 6 is supplied to the hook of the projecting working needle 2, thus forming a yarn loop. Then, the working needle 2 is lowered by a known mechanism (not shown), so one stitch is formed. Therefore, control operation of forming a stitch by selecting whether vertical motion is to be applied to the working needle 2, or allowing advance to the next knitting step without forming a stitch can be performed. As a result,

a desired fabric can be knitted. In order to provide such motions to the working needles, in the knitting machine, the needle selection jacks 12 are usually arranged in contact with the lower parts of the working
5 needles 2. The vertical motions of the working needles are controlled, by selectively engaging the needle selection jacks 12 and raising cams 15, by using a needle selector 3, operating on the basis of information from a controller 4 with a built-in storage
10 that stores a knitting procedure.

Next, a case wherein piezoelectric bodies are used as needle selection means will be described with reference to Figs. 4B and 4C which show the relationship among the working needles 2, needle
15 selection jacks 12, and needle selector 3. Figs. 4B and 4C are schematic views that facilitate understanding of the operation of the needle selection means with ease.

A piezoelectric body 7 can be either curved as shown in Fig. 4B, or curved as shown in Fig. 4C, in the direction opposite to that shown in Fig. 4B, depending on how a voltage is applied to it. A finger 9 is arranged at the tip of the piezoelectric body 7 to be linked to it. In Figs. 4B and 4C, the piezoelectric
25 body 7, finger 9, and raising cam 15 are positioned within the surface of the drawing, and the working needle 2 and needle selection jack 12 move circularly

together with the knitting cylinder 1 (not shown) from the top to the bottom of the surface of the drawing (or in the reverse direction). The needle selection jack 12 can swing about a fulcrum 12a as the center. A
 5 needle selection butt 13 (upper part) and raising cam butt 14 (lower part) project sideways from the needle selection jack 12 as shown in Figs. 4B and 4C.

When the piezoelectric body 7 is curved as shown in Fig. 4B, the needle selection butt 13 of the needle
 10 selection jack 12 which moves circularly hits the finger 9. As a result, the needle selection jack 12 is thrust clockwise about the fulcrum 12a as the center, and the raising cam butt 14 of the needle selection jack 12 cannot engage with the raising cam 15.
 15 Therefore, the needle selection jack 12 is not thrust upward by the raising cam 15, and accordingly the working needle 2 is not thrust upward.

When the piezoelectric body 7 is curved as shown in Fig. 4C, the finger 9 at its tip does not hit the
 20 needle selection butt 13 of the needle selection jack 12 which moves circularly together with the knitting cylinder 1. Hence, the needle selection jack 12 remains in the vertical direction, and accordingly the raising cam butt 14 at the lower end of the needle
 25 selection jack 12 engages with the raising cam 15. Therefore, the needle selection jack 12 is thrust upward along the inclined surface of the raising cam 15,

and accordingly the working needle 2 is also thrust upward.

A member indicated by reference numeral 25 in Figs. 4B and 4C is a finger pivot stopper formed by
5 part of the frame of the needle selector. When the position of the member 25 is appropriately determined, the finger 9 engages with the needle selection butt 13 reliably, so the finger 9 is prevented from drifting over contact with the needle selection butt 13.

10 In this manner, selective engagement of the needle selection butt 13 of the needle selection jack 12 with the finger 9 at the tip of the piezoelectric body 47 enables the working needle 2 to move upward freely as desired and thereby enables a knit fabric of
15 any desired knit texture to be knit.

Fig. 5 shows the relationship between the piezoelectric body 7 and finger 9 of this piezoelectric needle selector 3.

As shown in Fig. 5, the finger 9 is arranged to
20 be movable relative to the piezoelectric body 7 having a bimorph piezoelectric element. Power is applied to the piezoelectric body 7 to actuate the finger 9. This motion of the finger 9 causes the working needles of the knitting machine to be selected (more specifically,
25 via the needle selection jack 12), and knitting of a fabric with a predetermined knit texture is made possible. The rear end of the piezoelectric body 7 is

movably supported via a spherical body, i.e., a rotary body 20, by a support 21 or a concave part 22 of a housing. The tip of the piezoelectric body 7 is movably linked via a rotary body 16 into a U-shaped
5 groove 17 (to be referred to as a slit 17 hereinafter) at the rear end of the finger 9. The piezoelectric body 7 is arranged with its predetermined position between the rear end and the tip of the piezoelectric body 7 being pinched by a rotary body 23 rotatably
10 fitted to a support 24 or the housing.

As shown in Fig. 5, the finger 9 is supported at its intermediate portion 9b by a support 10b through a pin 18. Hence, when the piezoelectric body 7 flexes, its motion vertically moves a rear end (piezoelectric
15 body engaging portion) 9a of the finger 9. As a result, the finger 9 swings about the pin 18, serving as the pivot support point of the finger 9, as the center, so a bar-shaped portion 9c of the finger 9 projecting through an opening 11 of a support 10a swings, and
20 consequently a tip 9d moves vertically. The vertical motion of the tip 9d causes the rising motion of the working needle 2 described above to be selected.

Fig. 6A is a side view of a conventionally known finger 9, and Fig. 6B is a front view of the same. As
25 shown in Figs. 6A and 6B, the finger 9 is comprised of a bar-shaped thin elongated member 9c extending from a butt abutting surface 9d at its tip to reach a central

portion 9b having a pivot support point 18a, and a piezoelectric body engaging portion 9a extending from the central portion 9b in the other direction. The pivot support point 18a is on a longitudinal axis $9X_1$ of the bar-like thin elongated member. The piezoelectric body engaging portion 9a has a slit 17 to accommodate a curved motion end 16 of the piezoelectric body.

As shown in Figs. 6A and 6B, the conventionally known finger 9 is formed of a material, integral from its butt abutting surface 9d on the knitting cylinder-side tip to the piezoelectric body engaging portion 9a of the needle selector.

The shape, size, and the like of the finger 9, however, change depending on the type of the knitting machine, the type of the needle selector, and the knit texture of the fabric to be knitted by this knitting machine. The manufacturer of the needle selector for the knitting machine copes with this situation by preparing very many types of fingers in stock.

In view of this, it has been discussed to form a predetermined finger in the following manner. The operatively downstream portions (to be referred to as finger members in the following description) of fingers which have butt abutting surfaces engageable with the needle selection jacks of the knitting cylinder and the operatively upstream portions (to be referred to as

finger holding members in the following description) of the fingers which have the piezoelectric body engaging portions for the needle selector are fabricated by separate manufacturing steps, and are kept in stock. A
5 finger holding member and finger member are appropriately selected and combined in accordance with the type of the knitting machine in which the finger is to be used, and with the knit texture of the target fabric, thus forming the predetermined finger. This
10 can greatly reduce the number of the types of fingers to be kept in stock.

A finger (to be referred to as a module finger hereinafter) which is formed by combining a finger holding member and finger member to match the object is
15 recently known. An example of the module finger will be described hereinafter with reference to Figs. 7A and 7B showing perspective views.

A module finger 30a shown in Fig. 7A is comprised of a finger member 31a and finger holding member 40a.
20 The finger member 31a is comprised of a butt abutting portion 33a having a butt abutting surface 32a at its tip, and a support 34a extending like a bar from the butt abutting portion 33a. The finger holding member 40a has a metal plate slit 44a at its lower part to
25 form a piezoelectric body engaging portion 45a. A connecting plate 46 is connected to the upper side of the slit 44a.

The finger member 31a and finger holding member 40a of the module finger 30a shown in Fig. 7A are connected using a synthetic resin after the lower part of the support 34a of the finger member 31a and the connecting plate 46 above the finger holding member 40a are manually arranged to oppose each other. Namely, a connecting portion 51 is formed from the synthetic resin.

The module finger 30a obtained with this method cannot be used for high-speed rotation, since the positional relationship between the butt abutting surface 32a and piezoelectric body engaging portion 45a is low. Furthermore, the complicated manual operation using the synthetic resin increases the cost.

A module finger 30b shown in Fig. 7B is comprised of a metal finger member 31b substantially identical with the finger member 31a shown in Fig. 7A, and a synthetic resin finger holding member 40b. The module finger shown in Fig. 7B is manufactured in the following manner. More specifically, first, the finger member 31b is manufactured with high precision by using a metal material, and is kept in stock. When fabricating a specific module finger 30b, a finger member 31b with a structure suitable for the knit texture of the fabric is selected. A mold corresponding to the structure of the target finger holding member 40b is loaded in an injection molder,

and the finger member 31b is arranged at a predetermined position in the mold of the injection molder. Then, a synthetic resin is injected.

5 The module finger 30b shown in Fig. 7B, which is obtained in accordance with the above method, has excellent size precision. Regarding the manufacture of the module finger 30b, the expensive injection molder must be operated by a skilled operator. This increases the cost of the obtained module finger.

10 Although a demand for a module finger with which the stock of the fingers can be decreased and which can be manufactured to meet the situation has arisen, such a module finger is substantially difficult to become popular.

15 It is an object of the present invention to solve the problems of the conventionally known module finger and to provide a new module finger with which fingers that need to have various types of shapes can be supplied quickly as required at a low cost.

20

DISCLOSURE OF INVENTION

In order to achieve the above object, a needle selector for a knitting machine according to the present invention has the following arrangement.

25 More specifically, there is provided a needle selector for a knitting machine, in which a plurality of needle selection jacks each having at least one butt

projecting therefrom are swingably fitted in a plurality of vertical grooves in an outer surface of a knitting cylinder such that working needles in contact with the jacks move vertically, characterized in that

5 the needle selector comprises a module finger for selectively engaging with the needle selection jacks of the knitting machine so as to swing the needle selection jacks, and a driving member for pivoting the module finger on the basis of a predetermined knitting
10 procedure,

the module finger having

a finger member having a butt abutting portion with a butt abutting surface at a tip thereof, and a support extending from the butt abutting portion, and

15 a finger holding member having a connecting portion, at one end thereof, where part of the support of the finger member is mounted so the finger member can be positioned, an engaging portion, at the other end thereof, to be engageable with the driving member
20 of the needle selector for the knitting machine, and a pivot support arranged between the two ends to provide a module finger pivot support point, and

the finger member and said finger holding member being combined to each other so that a positioning
25 state obtained by mounting part of the support of the finger member on the connecting portion of the finger holding member is maintained.

A needle selection module finger according to the present invention for achieving the above object has the following arrangement.

More specifically, there is provided a needle
5 selection module finger for a needle selector for a knitting machine, which comprises a finger member and a finger holding member,

wherein the finger member has a butt abutting portion with a butt abutting surface at a tip thereof,
10 and a support extending from the butt abutting portion,

the finger holding member has a connecting portion, at one end thereof, where part of the support of the finger member is mounted so the finger member can be positioned, and an engaging portion, at the
15 other end thereof, to be engageable with a driving member of the needle selector for the knitting machine, and

the module finger further comprises

combining means for combining the finger member
20 and the finger holding member to each other so that a positioning state obtained by mounting part of the support of the finger member on the connecting portion of the finger holding member is maintained.

Furthermore, a method of manufacturing a needle
25 selection module finger according to the present invention for achieving the above object comprises the steps of

manufacturing a finger member having a butt abutting portion with a butt abutting surface at a tip thereof, and a support extending from the butt abutting portion,

5 manufacturing a finger holding member having a connecting portion, at one end thereof, where part of the support of the finger member is mounted so the finger member can be positioned, and an engaging portion, at the other end thereof, to be engageable
10 with a driving member of a needle selector for a knitting machine, and

positioning the finger member and the finger holding member by mounting part of the support of the finger member on the connecting portion of the finger
15 holding member, and combining the finger member and the finger holding member such that a positioning state thereof is maintained.

The needle selection module finger having the above arrangements according to the present invention
20 can be used in various types of needle selectors for a knitting machine.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a perspective view showing an example
25 of a module finger used in a needle selector for a knitting machine according to an embodiment of the present invention;

Fig. 2A is a front view showing an example of a finger member 31 for the module finger shown in Fig. 1;

Fig. 2B is a side view of the finger member 31 for the module finger shown in Fig. 2A;

5 Fig. 3A is a front view showing an example of a finger holding member 40 for the module finger shown in Fig. 1;

Fig. 3B is a side view of the finger holding member 40 shown in Fig. 3A;

10 Fig. 3C is a plan view of the finger holding member 40 shown in Fig. 3A;

Fig. 4A is a schematic perspective view of an entire knitting machine to explain the knitting function of the knitting machine;

15 Fig. 4B is a view for explaining the knitting function of the knitting machine in a state wherein the finger of the needle selector engages with the needle selection pad of the needle selection jack.

Fig. 4C is a view for explaining the knitting function of the knitting machine in a state wherein the finger of the needle selector does not engage with the needle selection pad of the needle selection jack;

20 Fig. 5 is a side sectional view showing the operational relationship between the piezoelectric body and the finger in the needle selector for the knitting machine;

Fig. 6A is a side view showing an example of a

conventionally known finger;

Fig. 6B is a front view of the finger of Fig. 6A;

Fig. 7A is a view showing a conventional module
finger formed by combining two members, i.e., a finger
5 member and a finger holding member in a case wherein
the two members are connected to each other with a
resin; and

Fig. 7B is a view showing a conventional module
finger formed by combining two members, i.e., a finger
10 member and a finger holding member in a case wherein a
module finger is obtained by burying a metal finger
member in a resin finger holding member by using an
injection molder.

15 BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will be described in detail
with reference to accompanying drawings showing an
embodiment of the present invention.

Fig. 1 shows in a perspective view showing an
20 example of a module finger used in a needle selector
for a knitting machine according to this embodiment.
As shown in Fig. 1, a module finger 30 of this
embodiment is comprised of a finger member 31 and
finger holding member 40.

25 Figs. 2A and 2B are views showing an example of
the finger member 31, in which Fig. 2A is a front view,
and Fig. 2B is a side view. Figs. 3A to 3C are views

showing an example of the finger holding member 40, in which Fig. 3A is a front view, Fig. 3B is a side view of the finger member of Fig. 3A, and Fig. 3C is a plan view.

5 As shown in Fig. 1 and Figs. 2A and 2B, the finger member 31 is comprised of a butt abutting portion 33 having a butt abutting surface 32 at its tip, and a support 34 projecting like a bar from the butt abutting portion 33. The support 34 has at its lower
10 part a projection 35 extending to the right and an inserting projection 36 extending to the left in the example of Fig. 2A. The projection 35 has a hole 37 corresponding to a hole 37a of the finger holding member 40. The finger member 31 is formed of a flat
15 plate with a uniform thickness, as shown in the side view of Fig. 2B.

 As shown in Fig. 1 and Figs. 3A to 3C, the finger holding member 40 is formed of a plastic main body 41 fabricated with an injection molding. A connecting
20 portion 41 to be connected to the finger member 31 is formed at the upper part (the finger member 31 side) of the finger holding member 40. A piezoelectric body engaging portion 45 to engage with a piezoelectric body
7 is formed at the lower part of the finger holding
25 member 40 on the opposite side to the connecting portion 41. The connecting portion 41 has a concave part 42 to accommodate part of the support 34 of the

finger member 31 described above. An insertion type concave part 42a where the inserting projection 36 of the finger member 31 is to be inserted is formed on the left side of the concave part 42. The projection 35 of the finger member 31 is to be accommodated in the upper right portion of the concave part 42. When the inserting projection 36 of the finger member 31 is fitted in the insertion type concave part 42a of the finger holding member 40, the two members 31 and 40 are positioned relative to each other. With the two members 31 and 40 being combined in this manner, the finger holding member 40 has the hole 37a at a position corresponding to the hole 37 of the finger member.

The finger member 31 and finger holding member 40 having the structures described above are assembled together by inserting the finger member 31 toward the insertion type concave part 42a of the finger holding member 40 in a direction indicated by an arrow C in Figs. 1 and 3C. At this time, when the inserting projection 36 of the finger member 31 is inserted in the insertion type concave part 42a of the finger holding member 40, the two members are positioned.

In this manner, when the two members 31 and 40 are combined, the hole 37 of the finger member 31 and the hole 37a of the finger holding member 40 are aligned on one straight line. When a pin-shaped member 50 is inserted through the holes 37 and 37a, the two

members 31 and 40 are connected integrally. The pin-shaped member also helps in positioning the two members 31 and 40.

As shown in Figs. 1 and 3B, a pivot support 43 is formed between the connecting portion 41 and piezoelectric body engaging portion 45. The pivot support 43 is a fulcrum portion where a pin 18 (see Fig. 5) is inserted so the module finger 30 swings. The piezoelectric body engaging portion 45 has a slit 44 as shown in Fig. 3C. The slit 44 is a space where a tip 16 of the piezoelectric body 7 on the module finger 30 side slides along with the swing motion of the piezoelectric body 7. The piezoelectric body engaging portion 45 is a portion which engages with the tip 16 of the piezoelectric body 7. These portions are conventionally known structures in the arrangement of the finger, as described in Fig. 5, and a detailed description thereof will accordingly be omitted.

The module finger shown in Fig. 1, Figs. 2A and 2B, and Figs. 3A to 3C is merely an example of the module finger of the present invention, and can be modified in various manners. For example, in the module finger 30 shown in Fig. 1, the finger member 31 and finger holding member 40 may be integrally combined to each other without using the pin-shaped member 50 but with an adhesive or by ultrasonic welding. In this case, the two members are positioned by inserting the

inserting projection 36 of the finger actuating member 31 into the insertion type concave part 42a of the finger holding member 40.

As described above, the concave part 42 and
5 insertion type concave part 42a for accommodating at least some lower part (35, 36) of the support 34 of the module finger 30 are formed in one end of the finger holding member 40. The respective members have the holes 37 and 37a so as to form a hole extending through
10 the support 34 and connecting portion 41 when the support is inserted and positioned in these concave parts. As shown in Fig. 1, with the finger member 31 and finger holding member 40 being positioned, the pin-shaped member 50 is inserted in the through hole
15 formed by the holes 37 and 37a, so that the finger member 31 and finger holding member 40 are integrally connected to each other. With this arrangement, the positional relationship between the butt abutting portion 32 of the finger member 31 and the
20 piezoelectric body engaging portion 45 of the finger holding member 40 (or the positional relationship between the butt abutting portion 32 and the pivot support 43 of the finger holding member 40) is
25 determined by inserting the supports (35, 36) of the module finger 30 in the concave part 42 and insertion type concave part 42a of the finger holding member 40. Furthermore, when the pin-shaped member 50 is arranged

in the holes (37a, 37) extending through the connecting portion 41 of the finger holding member 40 and the projection 35 of the finger member 31, the finger member 31 and finger holding member 40 can be
5 positioned more reliably, and the finger member 31 and finger holding member 40 are integrally connected to each other.

Positioning of the finger holding member 40 and finger member 31 by means of the concave parts (42, 42a) and the supports (35, 36) is not limited to the
10 above embodiment, but can be modified in various manners. In fine, this positioning is achieved by forming at least one portion where part of the finger member and part of the finger holding member are
15 combined to each other face to face, such that the positional relationship between the butt abutting surface of the finger member and the piezoelectric body engaging portion (or pivot support) of the finger holding member relative to each other is defined
20 accurately.

In the manufacture of the above finger module, a plurality of finger members 31 are manufactured and kept in stock for the respective types so as to cope with the knit textures of various types of fabrics. A
25 plurality of types of finger holding members 40 are manufactured and kept in stock in accordance with the specification of the needle selector where the finger

module is to be built. Finger members are selected in accordance with the target knit texture, and finger holding members are selected in accordance with the needle selector where they are to be built. The
5 selected finger members and finger holding members are assembled, combined, and integrated as described with reference to Fig. 1, Figs. 2A and 2B, and Figs. 3A to 3C. As a result, various types of finger modules can be provided.

10 As the knitting cylinder rotates, the butt abutting surfaces at the tips of the finger members come into intermittent contact with the butts of a large number of needle selection jacks at a high speed. Accordingly, the finger members are preferably made of
15 a metal having high impact resistance and high wear resistance.

The finger holding member engages with one end of the piezoelectric body by its piezoelectric body engaging portion, and receives the swing motion of the
20 piezoelectric body. At this time, since the finger holding member and piezoelectric body engage with each other in continuous contact, the finger holding member requires high shape precision, but does not require high impact resistance or high wear resistance unlike
25 the finger member. Accordingly, a relatively inexpensive resin material, e.g., a plastic material, having high workability is preferably used to form the

finger holding member.

As described above, the module finger according to the present invention is formed by fabricating a finger member and finger holding member, which have
5 different performances required in the manufacture and operation, using separate materials, and by combining them. Consequently, various many types of fingers can be formed by combination of a comparatively small number of types of finger members and finger holding
10 members. Since a simple and reliable integral connecting method is employed, a new demand for a high quality finger can be coped with quickly at a relatively low cost.

CLAIMS

1. A needle selector for a knitting machine,
characterized in that a plurality of needle selection
jacks each having at least one butt projecting
5 therefrom are swingably fitted in a plurality of
vertical grooves in an outer surface of a knitting
cylinder such that working needles in contact with said
jacks move vertically,

said needle selector comprises a module finger
10 for selectively engaging with the needle selection
jacks of the knitting machine so as to swing the needle
selection jacks, and a driving member for pivoting said
module finger on the basis of a predetermined knitting
procedure,

15 said module finger having

a finger member having a butt abutting portion
with a butt abutting surface at a tip thereof, and a
support extending from the butt abutting portion, and

a finger holding member having a connecting
20 portion, at one end thereof, where part of the support
of said finger member is mounted so the finger member
can be positioned, an engaging portion, at the other
end thereof, to be engageable with the driving member
of the needle selector for the knitting machine, and a
25 pivot support arranged between the two ends to provide
a pivot support point for said module finger, and

said finger member and said finger holding member

being combined to each other so that a positioning state obtained by mounting part of the support of said finger member on the connecting portion of said finger holding member is maintained.

5 2. The needle selector for the knitting machine according to claim 1, characterized in that the driving member for pivoting comprises a piezoelectric body.

 3. A needle selection module finger for a needle selector for a knitting machine, characterized
10 by comprising
 a finger member and a finger holding member,
 wherein said finger member has a butt abutting portion with a butt abutting surface at a tip thereof, and a support extending from said butt abutting portion,
15 said finger holding member has a connecting portion, at one end thereof, where part of the support of said finger member is mounted so said finger member can be positioned, and an engaging portion, at the other end thereof, to be engageable with a driving
20 member of the needle selector for the knitting machine, and

 the module finger further comprises
 combining means for combining said finger member and said finger holding member to each other so that a
25 positioning state obtained by mounting part of the support of said finger member on the connecting portion of said finger holding member is maintained.

4. The needle selection module finger according to claim 3, characterized in that said finger holding member has a pivot support, at a position between the two ends, which is to serve as a center of pivot of the
5 module finger.

5. The needle selection module finger according to claim 3, characterized in that said combining means combines said finger member and said finger holding member to each other with an adhesive.

10 6. The needle selection module finger according to claim 3, characterized in that said combining means combines the support of said finger member to said finger holding member in accordance with ultrasonic welding by employing positioning means as well.

15 7. The needle selection module finger according to claim 3, characterized in that said connecting portion has a concave part which receives at least part of a lower part of the support of said finger member, and

20 said combining means has a hole extending through a concave part of said finger holding member and the support of said finger member accommodated in the concave part, and a pin-shaped member is arranged in this hole, so that said finger member and said finger
25 holding member are combined to each other.

8. The needle selection module finger according to claim 7, characterized in that an inserting

projection is formed at a tip of the support of said finger member, an insertion type concave part having an inner surface that can hold the inserting projection of said finger member is formed at a tip of the concave part of said finger holding member, and the inserting projection is inserted in the insertion type concave part, so that said finger member is positioned with respect to said finger holding member.

9. The needle selection module finger according to claim 3, characterized in that said finger member is made of a metal.

10. The needle selection module finger according to claim 3, characterized in that said finger member is made of a resin.

11. A method of manufacturing a needle selection module finger, characterized by comprising the steps of manufacturing a finger member having a butt abutting portion with a butt abutting surface at a tip thereof, and a support extending from the butt abutting portion,

manufacturing a finger holding member having a connecting portion, at one end thereof, where part of the support of the finger member is mounted so the finger member can be positioned, and an engaging portion, at the other end thereof, to be engageable with a driving member of a needle selector for a knitting machine, and

positioning the finger member and the finger holding member by mounting part of the support of the finger member on the connecting portion of the finger holding member, and combining the finger member and the finger holding member such that a positioning state thereof is maintained.

12. The method of manufacturing the needle selection module finger according to claim 11, characterized in that

the step of manufacturing the finger member comprises the step of manufacturing and storing finger members made of a plurality of types of metals to correspond to a plurality of types of knit patterns, and

the step of combining comprises the step of assembling and fixing the finger holding member and a finger member which is selected in accordance with a knit pattern.

13. The method of manufacturing the needle selection module finger according to claim 11, characterized in that

the step of manufacturing the finger holding member comprises the step of manufacturing and storing a plurality of types of finger holding members in accordance with types of needle selectors with plastic injection molds, and

the step of combining comprises the step of

assembling and fixing a finger member selected in accordance with a knit pattern and a finger holding member selected in accordance with a type of a knitting machine.