

Method for the transport and storage of phenol

The invention relates to a method for the transport and storage of phenol.

Phenol is a base product of petrochemistry, of which more than 5 million metric tons are produced per year worldwide. Phenol serves as starting product for numerous intermediates and finished products. A large proportion of the phenol is further processed to form phenol-formaldehyde resins. In addition, bisphenol A (2,2'-di-(4-hydroxyphenyl)propane) is prepared from phenol and acetone to a great extent, since bisphenol A has become of increasing importance as a starting product for polycarbonates and epoxide resins.

Phenol has a melting or solidification point of 41 °C; it is therefore solid at the usual ambient temperatures. However, phenol is handled in solid form only in insignificantly small amounts. Phenol is customarily transported and stored as a liquid at temperatures above its solidification point. In order to keep the phenol liquid, the piping, transshipment facilities and the storage and transport vessels are customarily insulated against heat losses. An additional heating means is generally also required. Thermally insulated, heatable transport and storage systems are therefore usually used.

The vessel material used is generally steel. Phenol has a tendency to discolor owing to oxidation products of phenol. If the phenol is to remain colorless for as long as possible, systems made of stainless steel are used.

During the storage and transport of liquid phenol, care must be taken to keep the temperature below 70 °C, since the lower explosive limit for phenol/air mixtures is reached at a saturation temperature of approximately 73 °C. At storage temperatures above the flash point, the gas space in the vessel must be rendered inert by complex measures, e.g. by introducing nitrogen gas.

Another known commercial form of phenol is a mixture of phenol with water,

in which case, by addition of water, in theory, a solidification point of the phenol/water mixture can be set between 0°C and 41°C. However, in practice, only the concentration range of 8 to 10% by weight of water in the mixture is employed. If more water is added to the system, it divides into a water-rich and a phenol-rich phase. The phenol/water system has a miscibility gap (cf. Ullmanns Encyklopädie der technischen Chemie [Ullmanns Encyclopaedia of Industrial Chemistry], 4th edition, 1979, vol. 18, p.177) below 69°C. A mixture of phenol with approximately 10% by weight of water has a solidification point of approximately 13.5°C; a mixture with 20% by weight of water has a solidification point of approximately 5°C. The miscibility gap of the phenol/water system at 10°C is between phenol contents of 7% by weight and 75% by weight. However, depending on climatic conditions, temperatures of 0°C and below can also occur during transport and storage of phenol. Therefore, even the addition of water to the phenol does not avoid the need in every case for the use of heatable thermally insulated vessels. Furthermore, the water, depending on the phenol application, must generally be removed from the phenol again later by complex means.

The object of the present invention is therefore to provide a method for the transport and storage of phenol in the liquid phase which does not require the use of heatable thermally insulated systems under conventional transport and storage conditions.

This object is achieved according to the invention by a method for the transport and storage of phenol as claimed in patent claim 1, which involves adding up to 70% by weight of acetone to the liquid phenol. Preferably, the acetone content in the phenol/acetone mixture is between 20 and 60% by weight, particularly preferably between 45 and 55% by weight. The mixtures thus obtained can be stored or transhipped and transported as liquid phase without additional heating and thermal insulation under appropriate climatic conditions.

The phenol/acetone system does not have a miscibility gap, and mixtures

having solidification points below 0°C may be readily established. A mixture of phenol with 15% by weight of acetone, for example, has a solidification point of approximately 20°C; at 50% by weight of acetone a solidification point of approximately 0°C is produced, and at 70% by weight of acetone, -40°C. Phenol/acetone mixtures containing 20 to 60% by weight of acetone have solidification points between +17°C and -20°C; in the case of phenol/acetone mixtures containing 45 to 55% by weight of acetone, the solidification points are between +5°C and -10°C.

By adding acetone to phenol, mixtures may be established by this means at any time whose solidification point is so low that the mixture is always liquid under preset transport and storage conditions. As a result, complex heatable and/or thermally insulated transport and storage systems become unnecessary. This leads not only to considerable cost savings, but additionally considerably increases the flexibility in logistics, since no special tanks are necessary. Since the storage and transport of phenol in the liquid phase can be performed as described by the method according to the invention at ambient temperature and thus at considerably lower temperatures than hitherto, the tendency of the phenol to discolor owing to oxidation by atmospheric oxygen also decreases.

During the transport of pure liquid phenol, in addition, there is always the risk of freezing due to, for example, failure of the auxiliary heating or damage to the thermal insulation, for which reason relatively long transport distances are avoided. When phenol which has solidified is thawed out again, moreover, quality deterioration due to discoloration very frequently occurs. These defects are reliably avoided by using the method according to the invention for the phenol transport.

The conventional ambient temperatures for the transport or storage of phenol are roughly between -20°C and +35°C, so that phenol/acetone mixtures having an acetone content up to 70% by weight are sufficient to keep the product liquid at all times. This not only simplifies the storage of phenol in, for example, tanks or the transport in tank trucks, tank cars, tanker ships etc,

the transport in pipelines over relatively large distances is also facilitated and sometimes even made possible for the first time. Transporting phenol by pipeline over relatively long routes has frequently failed in the past owing to the fact that it was not economically efficient on account of the necessity for heated and insulated piping. In the case of pipes laid below ground, in addition, water must be kept away from the insulation, or an expensive water-impermeable insulation must be chosen.

In the case of transport of phenol/acetone mixtures by pipeline, the insulation can be omitted completely. By changing the acetone content, moreover, the solidification point of the mixture can be adapted to the external conditions for a short time. For interruptions in the transport operation, a more acetone-rich mixture can also be charged into the pipe, which covers all extreme external conditions.

Later removal of the acetone to produce pure phenol can be omitted for those phenol applications in which phenol and acetone are in any case used together, that is, in particular, for example in the further processing of phenol to bisphenol A, which is of importance economically and by volume. The transshipment and transport of a phenol/acetone mixture lends itself perfectly to just this type of application. In this case also great advantages in terms of costs and flexibility are achieved; and the acetone added need not be removed for the further processing.

The tank farm capacity at the receiver/further processor can be designed to be correspondingly smaller. This decreases the capital costs and the current assets of bisphenol A plants.

Just-in-time delivery agreements are also simpler to organize, in particular if the distance between supplier and customer enables the use of a pipeline connection.

The transport of a mixture of phenol and acetone offers advantages not only when both substances are in any case required in the following production

operation.

The mixture of substances can be stocked in distribution centers which are easily accessible to the customer by means of this invention. Acetone can be released from the mixture at any time as required as a pure substance by simple distillation. Likewise, pure phenol can be re-isolated as required by distilling off the acetone. Thus, it is possible to have both pure substances available at any time within easy reach of the customer, and at the same time to utilize the other said advantages of transport and storage of the mixture of substances.

If the phenol is prepared by the Hock process, acetone is produced as coupling product and is thus generally available in a sufficient amount for the employment of the method according to the invention. Employing the method according to the invention is therefore particularly simple and advantageous if the phenol is produced by the Hock process.

The method according to the invention is described in more detail by the following examples, without being restricted thereto:

Example 1:

Transport of phenol by road and rail in central Europe in summer

If the phenol is diluted with acetone until the mixture contains 40% by weight of acetone, a solidification point of 8°C is produced. This mixture is not at risk of freezing in the summer months in central Europe. The transshipment facilities themselves do not need to be heated and insulated, and the transport containers likewise not. This not only introduces cost savings, but additionally increases the flexibility in logistics.

Example 2:

Transport of phenol by road and rail in eastern Europe in winter

In eastern Europe, temperatures of -20°C must be expected in winter. A mixture containing 60% by weight of acetone does not solidify until -20°C . In particular because of the long transport routes, eliminating the risk of freezing offers great advantages. When phenol which has solidified is thawed out again, moreover, quality deterioration due to discoloration very frequently occurs. This problem is avoided when the method according to the invention is used.

Example 3:

Tank storage in central Europe

If pure phenol is stored in tanks, the tanks must be insulated and heated. In an appropriate mixture with acetone, uninsulated tanks can be used, which not only reduces the costs, but simultaneously also ensures flexibility in tank usage. 55% by weight of acetone in the mixture decrease the solidification point to as low as -11°C .

Example 4:

Transport by ship

If pure phenol is transported by ship, insulation from the surrounding water is particularly important, since the cooling action of water is considerably greater than that of air. Shipments in uninsulated ship's tanks are simpler to organize and, in addition, cheaper than shipments in insulated and heatable ship's tanks. In order to achieve a solidification point below 0°C , a mixture containing 50% by weight of acetone must be established.

Example 5:

Underground pipeline transport over 5 km

In an actual case, a continuous transport by pipeline of pure phenol over 5

km in Belgium was studied in comparison with an alternative transport by ship. The transport of pure phenol by pipeline proved to be uneconomical. However, if instead a phenol/acetone mixture containing at least 45% by weight of acetone is transported, laying an uninsulated underground pipe is sufficient. Continuous transport by pipeline becomes more economical by this means than transport by ship. The calculated payback time is less than 2 years.

Example 6:

Overground transport by pipeline over 2 km

For a project in the southern USA, transport by pipeline from the ship's landing stage to the tank farm 1.5 km away was investigated. The pipe is intended to be used for unloading and loading ships. The construction costs for a heated and insulated DN 200 pipe are approximately 50% higher than for an uninsulated pipe for an acetone/phenol mixture, with a second pipe for acetone not yet having been included in the calculation.

Example 7:

Transport by pipeline over 20 km

Transport of pure phenol by pipeline in a heated and insulated pipe is considerably more expensive than an alternative transport using vehicles or ships. In addition, only with considerable expenditure could the faultless functioning of the heating and insulation of the pipeline be ensured. Therefore, a project of this type also fails due to technical problems.

In this actual case, as an alternative, an uninsulated DN 80 pipe was used as the basis for the phenol transport according to the invention, which pipe is laid on an existing substructure. If 50,000 metric tons per year of a mixture of phenol containing 55% by weight of acetone are transported, the mixture remains liquid down to -10°C . The transport cost advantage with respect to

land vehicles gives a payback time of considerably less than 2 years.

Example 8:

Recovery of phenol and acetone from the transport/storage mixture

Phenol and acetone are very easy to separate by distillation. In a continuous distillation column, pure acetone can be produced as top product and pure phenol as bottom product. In a distillation column operated batchwise, pure acetone can be distilled off as the first fraction. The second fraction contains a mixture which can be recycled to the feed tank. Pure phenol remains as bottom product.

Combined storage and separation plants of this type can be used anywhere in regional markets.



Claims:

1. A method for the transport and storage of phenol, which comprises adding up to 70% by weight of acetone to the liquid phenol.
2. The method as claimed in claim 1, wherein 20 to 60% by weight of acetone are added to the phenol.
3. The method as claimed in claim 2, wherein 45 to 55% by weight of acetone are added to the phenol.
4. The method as claimed in at least one of the preceding claims, wherein the transport or storage vessels are not constructed so as to be heatable and/or are not constructed so as to be thermally insulated.
5. The method as claimed in at least one of the preceding claims, wherein the phenol is prepared by the Hock process.
6. The use of transport mixtures of phenol and acetone for the preparation of bisphenol A.

Abstract:**Method for the transport and storage of phenol**

Phenol has a solidification point of 41°C . Since phenol is generally stored and transported in liquid form, heatable, thermally insulated transport and storage systems are necessary.

By the addition according to the invention of up to 70% by weight of acetone to the phenol, the solidification point of the phenol/acetone mixture can be decreased to -40°C , as a result of which the transport and storage of phenol become possible without heatable and/or thermally insulated systems.

Transport of phenol.