

CLAIMS:

1. A method for measuring one or more dependent variables of an incident radiation within intervals of an independent variable comprising the steps of:
 - collecting the incident radiation to be measured;
 - 5 directing more than half of incident radiation in each interval into one of at least two distinct paths with a spatial modulator or a temporal modulator, said modulator undergoing a sequence of configurations such that each member of the sequence directs a different combination of incident radiation within intervals into each path;
 - 10 wherein the sum of radiation intensity for all distinct paths is at least 60% of the total incident radiation;
 - measuring the total intensity of radiation in each path with a detector for each modulator configuration to provide a plurality of detector outputs;
 - analyzing the detector outputs statistically to obtain information relating
 - 15 to the dependent variables of the radiation to be measured.
2. The method according to claim 1 wherein said modulator cycles through a sequence of M configurations, in each configuration dividing incident radiation into N portions according to the position and/or time the radiation is incident on the modulator, and directing a majority of each portion of incident radiation into
- 20 one of P distinct paths; wherein P is greater than or equal to two and less than N and wherein M is greater than or equal to N and the modulator configuration

sequence includes at least two configurations for which a majority of each portion is directed into different paths.

3. The method according to claim 1 wherein the radiation is spatially separated by source location, wavelength, phase or polarization and
5 directed into $N > 2$ different regions to be characterized into a measurement surface and wherein the modulator is a spatial modulator placed at said measurement surface.

4. The method according to claim 1 wherein the radiation is temporally separated using a gate modulator.

10 5. The method according to claim 4 wherein the radiation is temporally divided into $N > 2$ portions using a gate modulator which is modulated according to said sequence.

6. The method according to any preceding claim wherein the sequence of configurations of the modulator are chosen such that a matrix
15 representation of the sequence of configurations Z has the property that $Z^T Z$ is non-singular; wherein Z has MP rows and N columns, and wherein each row of Z represents the measurement at one detector and each column of Z represents one range of independent parameter and the elements of Z represent the fraction of particle flux from each range for said row.

20 7. The method according to any preceding claim wherein the radiation is spatially separated by an independent property chosen from the set of source location, wavelength, phase or polarization and directed into $N > 2$ different

regions to be characterized into a measurement surface and wherein the modulator is a spatial modulator placed at said measurement surface.

8. The method according to any preceding claim wherein the radiation is spatially separated by an independent property where the independent
5 property is time and radiation is temporally separated using a gate modulator.

9. The method according to claim 7 or 8 wherein the number of different configurations of the modulator is greater than or equal to the number of divisions of the independent property.

10. A method according to any preceding claim wherein the
10 modulator configuration sequence includes at least two configurations for each division in which a majority of radiation within that division is directed into different paths.

11. A method according to any preceding claim wherein each path has a plurality of detectors and wherein each detector measures radiation travelling
15 along the path within a different energy range.

12. A method according to any preceding claim wherein each detector measures radiation from a different region of origin.

13. A method according to any preceding claim wherein the radiation to be measured is from one of the following: a dispersive spectrometer; a
20 Fourier Transform spectrometer; an imaging spectrometer; an interference pattern; a diffractometer; from Raman scattering; a grain kernel, time of flight mass spectrometer, florescent decay, a flow cell for measuring fluid flow, light reflected

from particles under analysis, an interference pattern generated by radiation reflected from a vibrating energized solid material and radiation reflected from a reference surface.

14. A method according to any preceding claim wherein the spatial
5 modulator is one of: refractive, reflective, diffractive.

15. A method according to any preceding claim wherein the detector on each path produces an analog voltage and that analog voltage has a base voltage level subtracted prior to conversion to digital form.

16. The method of any preceding claim where the radiation is
10 comprised of particles selected from the list of photons, electrons, positrons, sub-atomic particles, protons, neutrons, ions, atoms or molecules.

17. The method of any preceding claim wherein the sum of radiation intensity measured for all distinct directions is at least 90% of the total radiation intensity incident on the measurement surface.

18. The method of any preceding claim wherein the sum of radiation
15 intensity measured for all distinct directions is substantially 100% of the total radiation intensity incident on the measurement surface.

19. The method of any preceding claim wherein the modulator directs radiation into at least three directions.

20. The method of any preceding claim wherein the modulator
20 produces cyclic permutations of a base mask with at least two distinct regions.

21. The method of claim 20 wherein the modulator causes each region of the base mask to direct substantially all of the radiation incident upon that region into a distinct direction.

22. The method of claim 19 wherein at least one region of a base mask of the modulator directs a portion of radiation incident upon that region into a first direction and at least some of the radiation incident upon that region into a different distinct direction.

23. The method of any one of claims 20 to 22 wherein at least one region of the modulator is translated or rotated during a measurement such that at least a portion of a base mask region of the modulator passes through at least two measurement regions.

24. The method of any one of claims 20 to 23 wherein the fraction of the radiation directed into each distinct direction for each measurement region is calculated as the time weighed geometric fraction that the mask region is directing radiation into that direction.

25. The method of any one of claims 20 to 24 wherein the base mask is a Hadamard mask or a pseudo-random mask.

26. The method of any one of claims 20 to 25 wherein the modulator produces a cyclic permutation of the base mask and at least a portion of the mask characteristics are determined by motion of the mask during a measurement period.

27. The method of any one of claims 20 to 26 wherein at least one element of the modulator has at least two different configurations.

28. The method of any one of claims 20 to 27 wherein the modulator comprises dynamic Toeplitz masks and the resolution is varied by
5 changing the sampling rate.

29. The method of any preceding claim wherein each detector output is normalized to the sum of the detector outputs.

30. The method of any preceding claim wherein the properties of the radiation to be measured are obtained by multivariate least squares analysis.

10 31. The method of any preceding claim wherein the information in the radiation to be measured is obtained by multivariate statistical analysis of the raw detector outputs or the normalized detector outputs.

32. The method of any preceding claim wherein the information in the radiation to be measured is obtained by correlation analysis of the raw detector
15 outputs or the normalized detector outputs.

33. The method of any preceding claim wherein the radiation pattern with N regions is analyzed by statistical analysis to find a smaller number m of latent variables in a spectrum; making m measurements, and using statistical analysis to infer the value of each latent variable.

20 34. The method of any preceding claim wherein the total intensity of the radiation summed over all detectors varies for at least some of the spatial modulator configurations; and at each modulator configuration, a raw intensity value

is generated at each detector; wherein the total intensity for the modulator configuration is $C = \text{SUM}(\text{detector intensities } d_i)$ where the data vector is loaded with the values $d_i' = d_i/C$ so that this normalization compensates for changes in the intensity.

5 35. The method of any preceding claim wherein a bandpass filter limits the range of wavelengths propagating through the detection system to establish boundary conditions for the analysis system.

 36. The method of claim 34 wherein the bandpass filter is used to optimize the instrument sensitivity for detection of a particular analyte by weighting
10 the contribution of different spectral bands in proportion to the significance of that band.

 37. The method according to any preceding claim wherein an intensity of the radiation varies for each of a plurality of samples, at each time sample, a raw intensity value is generated at a first detector A and at a second
15 detector B, wherein the total intensity in the time step is $C = A + B$ where the data vector is loaded with the values $a' = A/C$ and $b' = B/C$ so that this normalization compensates for changes in the intensity.

 38. The method according to any preceding claim including dividing the incident radiation into N packets, each packet containing radiation with a
20 different value of a first property; separating said radiation packets temporally or spatially using a temporal or spatial modulator and varying the modulator using a modulation sequence to direct at least N different combinations of incident radiation

packets into at least two distinct paths; including the steps of estimating the time weighted contribution of each band to the total intensity received by each detector in each measurement and setting the coefficients of the Z matrix to explicitly model the time weighted contributions.

- 5 39. The method according to any preceding claim the spatial modulator and associated optics and detectors are in relative motion with respect to the source of radiation to be measured and the relative motion produces the desired modulation.

10

15