[0001] METHOD AND APPARATUS FOR SELECTIVELY ENABLING RECEPTION OF DOWNLINK SIGNALING CHANNELS

[0002] FIELD OF INVENTION

[0003] The present invention is related to a wireless communication system including a wireless transmit/receive unit (WTRU) and at least one Node-B. More particularly, the present invention is a method and apparatus for selectively enabling reception of downlink (DL) enhanced uplink (EU) signaling channels established between the WTRU and the Node-B(s).

[0004] BACKGROUND

[0005] Methods for improving uplink (UL) coverage, throughput and transmission latency are being investigated in Release 6 (R6) of the 3rd Generation Partnership Project (3GPP). In order to successfully implement these methods, the scheduling and assigning of UL radio resources have been moved from a radio network controller (RNC) to a Node-B such that the Node-B can make decisions and manage UL radio resources on a short-term basis more efficiently than the RNC, even if the RNC retains overall control over the Node-B.

[0006] EU operation requires transmitting information such as UL channel allocations and transmission feedback information to the WTRU via DL EU signaling channels. The WTRU monitors the DL EU signaling channels for the reception of channel allocations and transmission feedback information.

[0007] A method and apparatus is desired for controlling reception of the DL EU signaling channels such that they are enabled only when required.

[0008] SUMMARY

[0009] The present invention is a method and apparatus for selectively enabling reception of at least one DL EU signaling channel used for EU operation. During the operation of an enhanced dedicated channel (E-DCH), a

WTRU monitors at least one DL EU signaling channel established between the WTRU and at least one Node-B only when it is necessary, based on the WTRU's knowledge of at least one established standard procedure. The WTRU coordinates and consolidates DL signaling channel reception requirements of a plurality of channel allocation and/or data transmission procedures carried out by the WTRU in accordance with the established standard procedure. The WTRU determines whether to enable reception of at least one specific DL signaling channel based on the consolidated DL signaling channel reception requirements.

[0010] In accordance with the present invention, the WTRU does not have to continuously enable the reception of the DL EU signaling channel during EU operation. Instead, the WTRU may selectively turn on and off, (i.e., enable and disable), reception of at least one specific DL EU signaling channel, thus reducing WTRU processing requirements and reducing the probability of misinterpretation of DL signaling.

[0010a] According to a first aspect of the present invention, there is provided a method for channel resource allocation implemented in a wireless transmit/receive unit (WTRU) comprising: sending, by the WTRU, an enhanced uplink (EU) channel allocation request via an uplink (UL) EU channel used for sending enhanced dedicated channel (E-DCH) data; receiving, by the WTRU, channel allocation information via a downlink (DL) EU signaling channel in response to sending the channel allocation request; and determining, by the WTRU, whether to selectively enable the DL EU signaling channel according to at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the DL EU signaling channel in accordance with a preconfigured schedule.

[0010b] According to a second aspect of the present invention, there is provided a method for channel resource allocation implemented in a wireless transmit/receive unit (WTRU), comprising: sending, by the WTRU, an enhanced uplink (EU) channel allocation request including enhanced dedicated channel (E-DCH) data via at least one uplink (UL) channel; receiving, by the WTRU, channel allocation information and data feedback information via respective downlink (DL) signaling channels in response to sending the channel allocation request including E-DCH data; and determining, by the WTRU, whether to utilize at least one of the respective DL signaling channels according to at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the at least one respective DL signaling channel in accordance with a preconfigured schedule.

[0010c] According to a third aspect of the present invention, there is provided a method for channel resource allocation implemented in a wireless transmit/receive unit (WTRU) comprising: transmitting, by the WTRU, an enhanced uplink (EU) channel allocation request over an uplink (UL) EU channel, wherein the allocation request includes scheduling information; monitoring, by the WTRU, a plurality of downlink (DL) EU signaling channels according to at least one predetermined signaling procedure; receiving, by the WTRU, UL channel allocation information through at least one of the DL EU signaling channels; and selectively enabling, by the WTRU, at least one of the DL EU signaling channels according to the at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the at least one DL EU signaling channel in accordance with a preconfigured schedule.

[0010d] According to a fourth aspect of the present invention, there is provided a wireless transmit/receive unit (WTRU) for use in a wireless communication system to selectively enable reception of at least one downlink (DL) signaling channel, the WTRU comprising: a transmitter configured to send a channel allocation request; a receiver configured to enable reception of at least one DL signaling channel in order to receive expected channel allocation information, wherein the expected channel allocation information is responsive to the channel allocation request sent by the WTRU; and the receiver further configured to disable reception of at least one DL signaling channel on at least one condition of that reception of channel allocation information is not expected or reception of the DL signaling channel is not required.

[0010e] According to a fifth aspect of the present invention there is provided a wireless transmit/receive unit (WTRU) for use in a wireless communication system to selectively enable reception of at least one downlink (DL) signaling channel, the WTRU comprising: a receiver configured to enable reception of at least one DL signaling channel in order to receive expected data transmission feedback information in response to data sent by the WTRU; and the receiver further configured to disable reception of at least one DL signaling channel on at least one condition of that reception of data transmission feedback information is not expected or the DL signaling channel is not required.

[0010f] According to a sixth aspect of the present invention, there is provided a method performed by a wireless transmit/receive unit (WTRU) to selectively enable reception of at least one downlink (DL) signaling channel, the method comprising: sending a channel allocation request; enabling reception of at least one DL signaling channel in order to receive expected channel allocation information, wherein the expected channel allocation information is responsive to the channel allocation request sent by the WTRU; and disabling reception of at least one DL signaling channel on at least one condition of that reception of channel allocation information is not expected or reception of the DL signaling channel is not required.

[0010g] According to a seventh aspect of the present invention, there is provided a method performed by a wireless transmit/receive unit (WTRU) to selectively enable reception of at least one downlink (DL) signaling channel, the method comprising: enabling reception of at least one DL signaling channel in order to receive expected data transmission feedback information in response to data sent by the WTRU; and disabling reception of at least one DL signaling channel on at least one condition of that reception of data transmission feedback information is not expected or the DL signaling channel is not required.

[0010h] According to an eighth aspect of the present invention, there is provided a wireless communication device for use in a wireless communication system, the wireless communication device comprising: a transmitter configured to transmit configuration information to a wireless transmit/receive unit (WTRU), wherein the configuration information indicates that the WTRU is to periodically receive channel scheduling information; the transmitter further configured to transmit channel scheduling information over a downlink (DL) enhanced uplink (EU) signaling channel to the WTRU in time periods that the WTRU is to periodically receive the channel scheduling information; and a receiver configured to receive a channel allocation request from the WTRU; the transmitter further configured to transmit channel allocation information over the DL EU signaling channel in response to the received channel allocation request, wherein the channel scheduling information is configured to enable the WTRU to selectively enable the DL EU signaling channel according to at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the DL EU signaling channel in accordance with a preconfigured schedule.

[0011] BRIEF DESCRIPTION OF THE DRAWINGS

[0012] A more detailed understanding of the invention may be had from the following description of a preferred example, given by way of example and to be understood in conjunction with the accompanying drawing wherein:

[0013] Figure 1 is a block diagram of a wireless communication system operating in accordance with the present invention;

[0014] Figure 2 is a flow diagram of a process including method steps for selectively enabling reception of at least one DL EU signaling channel during EU operation when the WTRU sends an EU channel allocation request and is expecting to receive scheduling information in accordance with one embodiment of the present invention; and

[0015] Figure 3 is a flow diagram of a process including method steps for selectively enabling reception of at least one DL EU signaling channel when the WTRU sends E-DCH data and is expecting to receive feedback information in accordance with another embodiment of the present invention.

[0016] DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] Hereafter, the terminology "WTRU" includes but is not limited to a user equipment (UE), a mobile station, a fixed or mobile subscriber unit, a pager, or any other type of device capable of operating in a wireless environment. When referred to hereafter, the terminology "Node-B" includes but is not limited to a base station, a site controller, an access point or any other type of interfacing device in a wireless environment.

[0018] The features of the present invention may be incorporated into an integrated circuit (IC) or be configured in a circuit comprising a multitude of interconnecting components.

[0019] Figure 1 is a block diagram of a wireless communication system 100 operating in accordance with the present invention. The system 100 includes a WTRU 102, at least one Node-B 104 and an RNC 106. The WTRU 102 includes an E-DCH data buffer 112, a physical reception control entity 114, a receiver 116, a transmitter 118, a processor 120 and a standards database 122.

[0020] The transmitter 118 in the WTRU 102 transmits an EU channel allocation request, (i.e., a rate request), to the Node-B(s) 104 through a UL EU channel 108 for EU transmission to the Node-B 104. The EU channel allocation request may include scheduling information. The scheduling information may include traffic volume measurement (TVM) information of E-DCH data stored in the buffer 112 of the WTRU 102 and available EU transmit power information.

[0021] After the EU channel allocation request is transmitted, the receiver 116 in the WTRU 102 monitors a plurality of DL EU signaling channels 110_1, 110_2,..., 110_N for channel allocation information via the physical reception control entity 114. The Node-B(s) 104 responds to the EU channel allocation request with UL channel allocation information through one of the DL EU signaling channels $110_{1\text{-}N}$.

[0022] The system 100 is configured such that both UL signaling and E-DCH data are transmitted from the WTRU 102 to the Node-B(s) 104 via the UL EU channel 108. After receiving scheduling information for channel allocation from the Node-B(s) 104 through at least one of the DL EU signaling channels

110_{1-N}, the transmitter 118 in the WTRU 102 transmits E-DCH data through the allocated UL EU channel 108. The receiver 116 in the WTRU 102 then monitors the DL EU signaling channel(s)
110_{1-N} for expected E-DCH data feedback information.

[0023] In response to receiving the E-DCH data, the Node-B(s) 104 transmits E-DCH data feedback information to the WTRU 102 through the DL EU signaling channels 110_{1-N}. The feedback information includes either an acknowledgement (ACK) message or a non-acknowledgement (NACK) message, depending on the success or failure of the Node-B(s) 104 decoding the E-DCH data sent over the UL EU channel 108 by the WTRU 102. The Node-B(s) 104 may also transmit further channel allocation information in response to the E-DCH data transmission. Such further information may be included in the feedback information or may be sent as a separate transmission over the DL EU signaling channels 110_{1-N}.

[0024] The status of active EU procedures in the WTRU 102 may used to provide input to the physical reception control entity 114 of the WTRU 102. The physical reception control entity 114 communicates with a physical layer process to selectively enable and disable reception of the DL EU signaling channels 110_{1-N}.

[0025] In accordance with the present invention, the physical reception control entity 114 in the WTRU 102 disables reception, (i.e., ceases monitoring), of the DL EU signaling channels 110_{1-N} when it is not required by EU signaling procedures known to the WTRU 102. During periods when the WTRU 102 is not required to receive the DL EU signaling channels 110_{1-N}, the processing requirements and power consumption of the WTRU 102 are reduced, and the possibility of false interpretation of DL signaling is avoided.

[0026] Figure 2 is a flow diagram of a process 200 including method steps for selectively enabling reception of at least one DL EU signaling channel 110_{1-N} during EU transmission in accordance with the present invention. In step 202, the WTRU 102 is configured by the RNC 106 for E-DCH operation, whereby the UL EU channel 108 and the DL EU signaling channel(s) 110_{1-N} are established

between the WTRU 102 and the Node-B(s) 104. The WTRU 102 is not required to enable the reception of its DL EU signaling channel(s) 110_{1-N} immediately following configuration in the WTRU 102. Thus, the physical reception control entity 114 in the WTRU 102 disables reception of DL EU signal channel(s) 110_{1-N}.

[0027] Still referring to Figure 2, after the WTRU 102 is configured for E-DCH operation at step 202, the WTRU 102 monitors its buffer 112 of E-DCH data (step 204). If, at step 206, it is determined by the WTRU 102 that there is no E-DCH data in the buffer 112, the WTRU 102 continues to monitor the buffer 112, and reception of the DL EU signaling channels 110_{1-N} remains disabled at step 204. If, at step 206, it is determined by the WTRU 102 that there is E-DCH data waiting (i.e., queued) for transmission via the UL EU channel 108, the WTRU 102 transmits an EU channel allocation request with or without E-DCH data to the Node-B(s) 104 via the UL EU channel 108 and enables reception of at least one DL EU signaling channel 110_{1-N} (step 208). The WTRU 102 may optionally enable reception of DL EU signaling channel(s) 110_{1-N} after a predetermined or calculated delay. The EU channel allocation request may include scheduling information such as TVM information and available EU transmit power information.

[0028] Operation of E-DCH requires radio resource allocations to be scheduled and signaled by the Node-B(s) 104 to the WTRU 102 in response to an EU channel allocation request transmitted by the WTRU 102. According to established signaling procedures, the WTRU 102 keeps track of when E-DCH data transmission scheduling information including EU channel allocations is required or expected to be received from the Node-B(s) on at least one DL EU signaling channel 110_{1-N} based on information indicating when the EU channel allocation request was transmitted by the WTRU 102 (step 210).

[0029] In step 212, the WTRU 102 receives the required or expected scheduling information from the Node-B(s) over the DL EU signaling channel(s) 110_{1-N} and then, if not required by any one entity, the physical reception control entity 114 disables reception of DL EU signaling channel(s) 110_{1-N}. Optionally,

in step 214, the WTRU 102 schedules reception of DL EU signaling channel(s) 110_{1-N} based on periodically received DL EU signaling channel scheduling information if configured. Reception of specific DL EU signaling channel(s) 110_{1-N} is enabled, depending on which EU signaling procedures are active in the WTRU 102.

[0030] Figure 3 is a flow diagram of a process 300 including method steps for selectively enabling reception of the DL EU signaling channels 110_{1-N} when the WTRU 102 sends E-DCH data and is expecting to receive feedback information in accordance with another embodiment of the present invention. In step 302, the WTRU 102 is configured by the RNC 106 for E-DCH operation whereby the UL EU channel 108 and the DL EU signaling channel(s) 110_{1-N} are established between the WTRU 102 and the Node-B(s) 104. The WTRU 102 is not required to enable the reception of its DL EU signaling channel(s) 110_{1-N} immediately following the E-DCH operation configuration of the WTRU 102. Thus, the physical reception control entity 114 in the WTRU 102 disables reception of DL EU signal channel(s) 110_{1-N}.

[0031] Still referring to Figure 3, after the WTRU 102 is configured to perform an E-DCH operation at step 302, the WTRU 102 monitors its buffer 112 of E-DCH data (step 304). If at step 306 it is determined by the WTRU 102 that there is no E-DCH data in the buffer 112, the WTRU 102 continues to monitor the buffer 112, and reception of the DL EU signaling channel(s) 110_{1-N} remains disabled at step 304.

[0032] Steps 308, 310, 312 and 314 of process 300 may be performed for each of a plurality of several hybrid-automatic repeat request (H-ARQ) processes operating in parallel in the WTRU. If at step 306 it is determined by the WTRU 102 that there is E-DCH data waiting (i.e., queued) for transmission via the UL EU channel 108, for each H-ARQ process, the WTRU 102 transmits E-DCH data with or without an EU channel allocation request to the Node-B(s) 104 via the UL EU channel 108 and enables reception of DL EU signaling channel(s) 110_{1-N} (step 308). The WTRU 102 may optionally enable reception of DL EU signaling channel(s) 110_{1-N} after a predetermined or calculated delay.

[0033] According to established signaling procedures, the WTRU 102 keeps track of when feedback information is required or expected to be received from the Node-B(s) 104 for each H-ARQ process (step 310). In step 312, the WTRU receives feedback information from the Node-B(s) 104 and disables reception of the DL EU signaling channel(s) $110_{1\text{-}N}$ if not required by any one entity. Optionally, in step 314, the WTRU 102 schedules reception of the DL EU signaling channel(s) $110_{1\text{-}N}$ based on periodically received feedback information if configured. Reception of specific DL EU signaling channel(s) $110_{1\text{-}N}$ is enabled, depending on which EU signaling procedures are active in the WTRU 102.

[0034] The WTRU 102 keeps track of when scheduling information including EU channel allocations is expected to be received on DL EU signaling channels $110_{1\text{-}N}$ based on information indicating when the WTRU 102 transmitted the E-DCH data. DL EU signaling channels $110_{1\text{-}N}$ are also used to provide the WTRU 102 feedback information from the Node-B(s) 104 for E-DCH transmissions. Since feedback transmitted to the WTRU is in response to a specific action of the WTRU, the time of feedback information reception at the WTRU can be accurately determined by the WTRU. Feedback information transmitted by the Node-B(s) 104 via the DL EU signaling channel(s) $110_{1\text{-}N}$ may consist of H-ARQ acknowledgements and/or UL channel allocation information. One example of WTRU reception of feedback channels could be H-ARQ information channels (HICHs) and relative grant channels (RGCHs) or absolute grant channels (AGCH) in 3GPP.

[0035] The H-ARQ operation may be either synchronous or asynchronous. In synchronous operation, the WTRU 102 knows exactly when the WTRU 102 may receive the feedback (ACK or NACK) via DL EU signaling channel(s) $110_{1\text{-}N}$ and the WTRU 102 enables reception of the DL EU signaling channel(s) $110_{1\text{-}N}$ in accordance with a preconfigured schedule. With asynchronous H-ARQ operation, the WTRU enables reception of the DL EU signaling channel(s) $110_{1\text{-}N}$ for a predetermined time period following the EU transmission for receiving the feedback.

[0036] Channel allocation feedback may also be transmitted to the WTRU 102 from the Node-B(s) 104 on DL EU signaling channel(s) 110_{1-N}. The WTRU 102 may also enable reception of DL EU signaling channel(s) 110_{1-N} for this channel allocation feedback information. EU channel allocation procedures known to the WTRU 102 allow the WTRU 102 to schedule reception of this information. The channel allocation feedback may either be synchronized with the H-ARQ feedback, send over a predetermined period, or have a specified periodic repetition that the WTRU 102 can schedule reception for.

[0037] If the WTRU 102 does not send a channel allocation request to the Node-B(s) 104, but all previous EU data transmission requests sent by the WTRU 102 have been serviced by the Node-B(s) 104, and feedback information was received from the Node-B for all outstanding H-ARQ transmissions, then the WTRU 102 disables the reception of the DL EU signaling channel(s) 110_{1-N}.

[0038] In one embodiment, the WTRU 102 sends at least one channel allocation request to a plurality of Node-Bs 104 via at least one UL channel 108, and the Node-Bs send channel allocation information to the WTRU 102 via respective downlink (DL) signaling channels 110_{1-N} in response to receiving the channel allocation request.

[0039] The processor 120 in the WTRU 102 coordinates and consolidates DL signaling channel reception requirements of a plurality of channel allocation procedures carried out by the WTRU 102 in accordance with at least one established standard procedure stored in the standards database 122, and determines whether or not to enable reception of specific ones of the DL signaling channels 110_{1-N} based on the consolidated DL signaling channel reception requirements. The standards database 120 is in communication with the processor 120 and provides the processor 120 with information associated with at least one established standard procedure. The transmitter 118 is in communication with the processor 120 and sends at least one channel allocation request to the Node-Bs 104 via at least one UL channel 108. The receiver 116 is in communication with the processor 120 and receives channel allocation information from the Node-Bs 104 over the DL signaling channels 110_{1-N}. The

physical reception control entity 114 is in communication with the processor 120 and the receiver 116. The physical reception control entity 114 enables or disables reception of specific ones of the DL signaling channels 110_{1-N} based on the determination made by the processor 120.

[0040] In another embodiment, the WTRU 102 sends at least one data transmission to a plurality of Node-Bs 104 via at least one UL channel 108, and the Node-Bs 104 send data transmission feedback information to the WTRU 102 via respective downlink (DL) signaling channels 110_{1-N} in response to receiving the data transmission.

[0041] The processor 120 in the WTRU 102 coordinates and consolidates DL signaling channel reception requirements of a plurality of data transmission procedures carried out by the WTRU in accordance with at least one established standard procedure stored in the standards database 122, and determines whether or not to enable reception of specific ones of the DL signaling channels 110_{1-N} based on the consolidated DL signaling channel reception requirements. The E-DCH data buffer 112 is in communication with the processor 120 and queues data to be included in at least one data transmission sent by the WTRU 102 to the Node-Bs 104 via at least one UL channel 108. The transmitter 118 is in communication with the processor and sends the at least one data transmission to the Node-Bs 104. The receiver 116 is in communication with the processor 120 and receives data transmission feedback information from the Node-Bs 104 over the DL signaling channels 110_{1-N}. The physical reception control entity 114 is in communication with the processor 120 and the receiver 116. The physical reception control entity 114 enables or disables reception of specific ones of the DL signaling channels 110_{1-N} based on the determination made by the processor 120.

[0042] In yet another embodiment, the WTRU 102 sends at least one channel allocation request and E-DCH data to a plurality of Node-Bs 104 via at least one UL channel 108, and the Node-Bs send channel allocation information and data feedback information associated with the E-DCH data to the WTRU 102

via respective downlink (DL) signaling channels 110_{1-N} in response to receiving the at least one channel allocation request and E-DCH data.

[0043] The processor 120 in the WTRU 102 coordinates and consolidates DL signaling channel reception requirements of a plurality of channel allocation procedures and data transmission procedures carried out by the WTRU 102 in accordance with at least one established standard procedure stored in the standards database 122, and determines whether or not to enable reception of specific ones of the DL signaling channels 110_{1-N} based on the consolidated DL signaling channel reception requirements. The standards database 120 is in communication with the processor 120 and provides the processor 120 with information associated with at least one established standard procedure. The transmitter 118 is in communication with the processor 120 and sends at least one channel allocation request and E-DCH data to the Node-Bs 104 via at least one UL channel 108. The receiver 116 is in communication with the processor 120 and receives channel allocation information from the Node-Bs 104 over the DL signaling channels 110_{1-N}. The physical reception control entity 114 is in communication with the processor 120 and the receiver 116. The physical reception control entity 114 enables or disables reception of specific ones of the DL signaling channels 110_{1-N} based on the determination made by the processor 120.

[0044] Although the features and elements of the present invention are described in the preferred embodiments in particular combinations, each feature or element can be used alone without the other features and elements of the preferred embodiments or in various combinations with or without other features and elements of the present invention.

* * *

Claims

1. A method for channel resource allocation implemented in a wireless transmit/receive unit (WTRU) comprising:

sending, by the WTRU, an enhanced uplink (EU) channel allocation request via an uplink (UL) EU channel used for sending enhanced dedicated channel (E-DCH) data;

receiving, by the WTRU, channel allocation information via a downlink (DL) EU signaling channel in response to sending the channel allocation request; and

determining, by the WTRU, whether to selectively enable the DL EU signaling channel according to at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the DL EU signaling channel in accordance with a preconfigured schedule.

2. A method for channel resource allocation implemented in a wireless transmit/receive unit (WTRU), comprising:

sending, by the WTRU, an enhanced uplink (EU) channel allocation request including enhanced dedicated channel (E-DCH) data via at least one uplink (UL) channel;

receiving, by the WTRU, channel allocation information and data feedback information via respective downlink (DL) signaling channels in response to sending the channel allocation request including E-DCH data; and

determining, by the WTRU, whether to utilize at least one of the respective DL signaling channels according to at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the at least one respective DL signaling channel in accordance with a preconfigured schedule.

3. A method for channel resource allocation implemented in a wireless transmit/receive unit (WTRU) comprising:

transmitting, by the WTRU, an enhanced uplink (EU) channel allocation request over an uplink (UL) EU channel, wherein the allocation request includes scheduling information;

monitoring, by the WTRU, a plurality of downlink (DL) EU signaling channels according to at least one predetermined signaling procedure;

receiving, by the WTRU, UL channel allocation information through at least one of the DL EU signaling channels; and

selectively enabling, by the WTRU, at least one of the DL EU signaling channels according to the at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the at least one DL EU signaling channel in accordance with a preconfigured schedule.

4. The method of claim 3 further comprising:

transmitting a plurality of UL signaling data; and

transmitting enhanced dedicated channel (E-DCH) data through the UL EU channel.

5. The method of claim 3 further comprising:

monitoring the DL EU signaling channels for enhanced dedicated channel (E-DCH) data feedback information; and

receiving E-DCH data feedback information through the DL EU signaling channels including either a positive acknowledgement (ACK) message or a negative acknowledgement (NACK) message.

6. The method of claim 3 further comprising:

monitoring the DL EU signaling channels for enhanced dedicated channel (E-DCH) channel resource allocation information; and

receiving E-DCH channel resource allocation information through the DL EU signaling channels including at least one of a Relative Grant (RG) and Absolute Grant (AG).

7. The method of claim 3, wherein the scheduling information includes any one of the following:

traffic volume measurement information of enhanced dedicated channel (E-DCH) data stored in a buffer; and

available EU transmit power information.

8. The method of claim 4 further comprising:

receiving further channel allocation information in response to the transmitted E-DCH data.

9. The method of claim 3 further comprising:

disabling reception of the DL EU signaling channels on a condition that the DL EU signaling channels are not required by the at least one predetermined signaling procedure.

10. The method of claim 3, wherein the channel allocation information includes any one of the following:

a channelization code; and

an allowed transmit power.

11. The method of claim 1, wherein the DL EU signaling channel is a relative grant channel or an absolute grant channel.

12. The method of claim 2, wherein the at least one respective DL signaling channel is a relative grant channel or an absolute grant channel.

13. The method of claim 3, wherein the at least one DL EU signaling channel is a relative grant channel or an absolute grant channel.

14. A wireless transmit/receive unit (WTRU) for use in a wireless communication system to selectively enable reception of at least one downlink (DL) signaling channel, the WTRU comprising:

a transmitter configured to send a channel allocation request;

a receiver configured to enable reception of at least one DL signaling channel in order to receive expected channel allocation information, wherein the expected channel allocation information is responsive to the channel allocation request sent by the WTRU; and

the receiver further configured to disable reception of at least one DL signaling channel on at least one condition of that reception of channel allocation information is not expected or reception of the DL signaling channel is not required.

15. The WTRU of claim 14 wherein the receiver further configured to enable reception of the at least one DL signaling channel for a predetermined time or time period.

16. The WTRU of claim 14 wherein the receiver further configured to enable or disable reception of the at least one DL signaling channel on a periodic basis.

17. The WTRU of claim 14 wherein the transmitter further configured to send the channel allocation request over an uplink (UL) channel.

18. A wireless transmit/receive unit (WTRU) for use in a wireless communication system to selectively enable reception of at least one downlink (DL) signaling channel, the WTRU comprising:

a receiver configured to enable reception of at least one DL signaling channel in order to receive expected data transmission feedback information in response to data sent by the WTRU; and

the receiver further configured to disable reception of at least one DL signaling channel on at least one condition of that reception of data transmission feedback information is not expected or the DL signaling channel is not required.

19. The WTRU of claim 18 wherein the receiver further configured to enable reception of the at least one DL signaling channel for a predetermined time or time period.

20. The WTRU of claim 18 wherein the receiver further configured to enable or disable reception of the at least one DL signaling channel on a periodic basis.

21. The WTRU of claim 18 wherein the expected data transmission feedback information includes an acknowledge (ACK) message or a non-acknowledge (NACK) message.

22. A method performed by a wireless transmit/receive unit (WTRU) to selectively enable reception of at least one downlink (DL) signaling channel, the method comprising:

sending a channel allocation request;

enabling reception of at least one DL signaling channel in order to receive expected channel allocation information, wherein the expected channel allocation information is responsive to the channel allocation request sent by the WTRU; and

disabling reception of at least one DL signaling channel on at least one condition of that reception of channel allocation information is not expected or reception of the DL signaling channel is not required.

23. A method performed by a wireless transmit/receive unit (WTRU) to selectively enable reception of at least one downlink (DL) signaling channel, the method comprising:

enabling reception of at least one DL signaling channel in order to receive expected data transmission feedback information in response to data sent by the WTRU; and

disabling reception of at least one DL signaling channel on at least one condition of that reception of data transmission feedback information is not expected or the DL signaling channel is not required.

24. A wireless communication device for use in a wireless communication system, the wireless communication device comprising:

a transmitter configured to transmit configuration information to a wireless transmit/receive unit (WTRU), wherein the configuration information indicates that the WTRU is to periodically receive channel scheduling information;

the transmitter further configured to transmit channel scheduling information over a downlink (DL) enhanced uplink (EU) signaling channel to the WTRU in time periods that the WTRU is to periodically receive the channel scheduling information; and

a receiver configured to receive a channel allocation request from the WTRU;

the transmitter further configured to transmit channel allocation information over the DL EU signaling channel in response to the received channel allocation request,

wherein the channel scheduling information is configured to enable the WTRU to selectively enable the DL EU signaling channel according to at least one predetermined signaling procedure using at least one synchronous hybrid automatic repeat request (HARQ) process that enables reception of the DL EU signaling channel in accordance with a preconfigured schedule.

25. The wireless communication device of claim 24, wherein the wireless communication device is a base station, a Node-B, or an Access Point (AP).

METHOD AND APPARATUS FOR SELECTIVELY ENABLING RECEPTION OF DOWNLINK SIGNALING CHANNELS

Abstract

In a wireless communication system (100) including a wireless transmit/receive unit, WTRU (102) and at least one node-B (104), at least one downlink channel, DL (110) is selectively established between the WTRU (102) and the node-B (104) by means of uplink signaling channel, UL (108). WTRU (102) monitors and consolidates DL signaling channels (110) in accordance with one established standard procedure.

Fig. 1