

CRYPTOGRAPHIC SYSTEM AND METHODOLOGY FOR SECURING SOFTWARE CRYPTOGRAPHY

TECHNICAL FIELD

5

The present application relates generally to cryptographic systems and, more particularly, to methods for securing such systems when implemented in software.

BACKGROUND OF THE INVENTION

10

The usage of mobile devices, including both mobile phones and tablet computers, for network communications as well as for the storage and processing of personal information is rapidly growing. Cryptography forms the basis for securing users' sensitive information as they are transmitted between or stored on such devices.

15

Currently, there are two broad approaches to securing user information on such devices. Conventionally, Hardware Security Modules (HSMs) that provide for secure, tamper-proof containers for cryptographic processing perform these operations in hardware, isolated from software applications. The first documented HSM was described in US Patent 4,168,396, Sept 18, 1979, and was designed for copy protection of personal computer software. This concept was later extended to a hardware module providing data security (US Patent 4,352,952, Mar 3, 1980). Examples of present HSMs include "smart cards" built into both contact cards (ISO/IEC 7810 and 7816 standards) as well as contactless cards (ISO/IEC 14443 standard).

25

In mobile phones and other computing devices, such HSMs are typically not present or not accessible to software applications, and cryptography is performed within the host operating system, isolated using operating system mechanisms. However, an attacker or hacker who has gained access to the operating system has many techniques available to overcome these mechanisms, and therefore gain access to the user's information.

30

Virtual machines have been used as a means to separate execution between a host computing device, and guest operating system within the virtual machine. This has been used for security in order to enforce security policies (US Patent 2005/0257243, Dec 29, 2005), to prevent a compromised guest operating system
5 from being able to affect the host (US Patent 7,409,719, Dec 21, 2004), and to allow only trusted media player applications to access encrypted media on DVDs (US Patent 7,516,331, Nov 26, 2003). However, none of these attempts to protect the information within the virtual machine when executed on an open software platform such as a mobile phone or desktop operating system.

10

Based on the above and foregoing, it can be appreciated that there is a need for a cryptosystem having methodology for securing software cryptography from an unauthorised observer or attacker who has gained access to the operating system of a computing device, particularly when the computing device does not have the
15 means to secure cryptographic information in a separate Hardware Security Module. The present invention fulfils this and other needs in the art.

SUMMARY OF THE INVENTION

20 A cryptographic system and methodology constructed in accordance with the present invention comprises a secure software sandbox operating as a cryptographic sandbox, with a tamper-proof virtual layer surrounding the sandbox to protect the sandbox from reverse engineering, debugging, or tampering. A plurality of applications may communicate with the sandbox to request for cryptographic
25 operations to be performed, and to retrieve the results of the cryptographic operations from the sandbox.

BRIEF DESCRIPTION OF THE DRAWINGS

30 **FIG. 1** illustrates a block diagram of the processing system of a device performing systems and methods in accordance with an embodiment of this invention.

FIG. 2 illustrates a block diagram of components of the cryptographic system in accordance with an embodiment of this invention.

FIG. 3 illustrates a flow diagram of a start-up process of a cryptographic system in accordance with an embodiment of this invention.

FIG. 4 illustrates a flow diagram of a process for accessing encrypted storage in accordance with an embodiment of this invention.

FIG. 5 illustrates a flow diagram of a process for trusted access of cryptographic system to operating system functions in accordance with an embodiment of this invention.

FIG. 6 illustrates a flow diagram of a process performed by the cryptographic system to securely check for updates in accordance with an embodiment of this invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

The following description will focus on an embodiment in accordance with the present invention, which is typically operative in an environment providing application software running under Apple iPhone® or Google Android® operating systems. However, embodiments in accordance with this invention are not limited to any one particular application or any particular environment. Indeed, those skilled in the art will find that the systems and methods of the present invention may be advantageously applied to a variety of system and application software, including security tokens, software cryptography, and network encryption. Moreover, embodiments in accordance with the present invention may be performed in a variety of different platforms, including other mobile phone operating systems such as RIM Blackberry®, Microsoft® Windows Phone, and the like, other operating systems such as Apple Mac OS®, Microsoft® Windows, UNIX, and other operating environments such as web browsers and embedded devices, and the like. Therefore, the description of the shown embodiment in accordance with the present invention that follows is for purposes of illustration and not limitation.

The processes for providing methods and systems in accordance with this invention are executed by a device, such as, but not limited to a mobile telephone, tablet, netbook, laptop, or other processing system. The relevant components in a device that perform the processes in accordance with an embodiment of the invention are shown in FIG. 1. One skilled in the art will recognize that the device may include other components that are omitted for brevity without departing from this invention. The device **1** includes a processor **5**, a non-volatile memory **10**, and a volatile memory **15**. The processor **5** is a processor, microprocessor, controller, or a combination of processors, microprocessor, and/or controllers that performs instructions stored in the volatile memory **15** or non-volatile memory **10** to manipulate data stored in the memory. The non-volatile memory **10** can store the processor instructions utilized to configure the processor **5** to perform processes including processes in accordance with embodiments of the invention and/or data for the processes being utilized. In other embodiments, the device software and/or firmware can be stored in any of a variety of computer readable media appropriate to a specific application. Although a specific device is illustrated in Figure 1, any of a variety of devices configured to store encrypted cryptographic data and perform cryptographic operations can be utilized in accordance with embodiments of the invention.

A cryptographic system and methodology constructed in accordance with an embodiment of the present invention is provided as shown in FIG. 2. In the described embodiment, a cryptographic sandbox **108** provides a method for securely storing and processing cryptographic keys and data for a plurality of client applications **104**, with a tamper-proof virtual layer **110** within the sandbox to protect the processing and data from unauthorised observers. The cryptographic sandbox **108** may comprise both a secure virtual processor **109** as well as a secure virtual storage **119** in order to allow the client applications **104** to both perform secure processing as well as secure storage.

The cryptographic sandbox **108** may include a cryptographic virtual machine **109** to act as the secure virtual processor. The cryptographic virtual machine may include a secure cryptographic module **115** to perform cryptographic operations, including

storing, retrieving, and processing the cryptographic keys and data. These cryptographic operations may include publicly available cryptographic routines, including symmetric key cryptography such as AES, asymmetric key cryptographic such as RSA, hashing functions such as SHA-1, SHA-2, and HMAC, as well as
5 pseudo-random number generation and key generation functions. This virtual machine may receive requests **106** from a plurality of client applications to perform these cryptographic operations by securely processing these cryptographic operations within the virtual machine and sending the results of these cryptographic operations as a response **107** back to the clients. This virtual machine may also be
10 used to perform other non-cryptographic but security-critical processing functions.

The virtual machine **109** may comprise a virtual machine interpreter **111** and a set of virtual machine codes **112**. These virtual machine codes may be based on a 32-bit RISC instruction set architecture built solely for the purpose of execution within the
15 virtual machine interpreter. This instruction set architecture may include Assembly instructions required for a general purpose computer processor, including instructions for memory handling, function calling, results comparison, binary arithmetic, and integer arithmetic. The virtual machine and underlying operating system **101** may be executed on a computer processor **124**. This computer
20 processor may comprise a general-purpose central processing unit within a mobile phone. The underlying operating system may comprise a mobile phone operating system. The virtual machine interpreter may further include obfuscation techniques **114** to obscure its operations from the underlying operating system and any unauthorised observers therein. These obfuscation techniques may include a
25 technique to dynamically change the execution flow in response to changes in the underlying operating system. This technique may involve a system function callback handler passed to the virtual machine in order for the virtual machine to execute functions from the underlying operating system and detect whether these changes have occurred. The system function callback handler may provide access from the
30 virtual machine to the underlying operating system's file system, processes, and memory. The system function callback handler may provide access to system fingerprinting functions such as retrieving of device identifiers in the underlying operating system. The virtual machine will then determine based on the changes, if any, what the new execution flow should be.

The virtual machine may provide a means for secure encrypted storage **119** of cryptographic keys and data within the virtual machine. The secure storage may additionally be used to store other non-cryptographic but security-critical data. This means may be provided by writing **117** to and reading **118** from the encrypted storage. This encrypted file may be stored within the operating system's file system or within a trusted storage provided by the operating system. The file may be encrypted by the virtual machine using a symmetric block cipher such as AES using an AES key. This AES key may be based on a secret key known only to the virtual machine. This AES key may be based on a password entered by the user through the client application. This AES key may be generated based on hardware and software identifiers extracted from the underlying device. This AES key may be generated based on a response from a remote server.

The client applications may send the request to the virtual machine and receive the results of the cryptographic operations from the virtual machine through a sandbox interface **105**. The interface may comprise either a programming interface such as a software library or a network interface such as a TCP/IP network connection. This interface may comprise a set of program function calls for the client applications to perform cryptographic or security-critical functions within the virtual machine. These function calls may include function calls normally made to the underlying operating system for such functions. These function calls may also include function calls for additional functions performed specifically by the virtual machine. These function calls may be transparently intercepted by the virtual machine so that the client applications can continue to use the native function calls exposed by the underlying operating system.

The virtual machine interpreter may also provide a function **123** to securely update the set of virtual machine codes from a trusted party **122**. The codes may be signed by the trusted party and verified by the virtual machine before the updating process is allowed to replace the set of virtual machine codes used by the virtual machine. The virtual machine interpreter may provide secure access **103** to functions **102** in the underlying operating system. This access may be protected by the use of techniques to detect when the functions have been modified or moved by an external

observer. These techniques may include an anti-hooking technique, which may include a check that the function address has not been changed. These techniques may include an analysis of the time taken for the function to return a result, which may include a check that the function does not take longer than a certain amount of time to return a result. These techniques may additionally include a technique to vary the execution path so that an attacker cannot easily spoof the time taken, as the time taken will vary with each execution. This technique may involve executing a random number of instructions within the virtual machine in between checking the system time such that the length of the execution path will vary with each execution and the time taken will also vary with each execution. This technique may also involve executing different types of instructions within the virtual machine, with the time taken for each type of instruction known to the virtual machine codes, such that the execution path will incorporate different instructions each execution and the time taken will vary with each execution.

The tamper-proof virtual layer **110** may protect the virtual machine from reverse engineering by storing the set of virtual machine codes in an encrypted form, and decrypting these instructions at runtime to allow normal operation of the virtual machine. The encryption and decryption may be achieved through self-modifying virtual machine codes. The virtual machine interpreter may decrypt these self-modifying virtual machine codes by executing them within the virtual machine. There may be more than one round of self-modification performed by the virtual machine codes to further delay attempts at reverse engineering. There may be different cryptographic data and algorithms used at each round of self-modification. The self-modifying codes may involve different decryption routines with stored decryption keys, which decrypt a block of code from an encrypted form back into the plaintext form, before passing execution control to the decrypted codes. The self-modifying codes may also involve replacing sets of instruction sequences with other sets of instruction sequences that achieve the same execution result.

The tamper-proof virtual layer may protect the virtual machine from runtime analysis by employing techniques **116** to prevent debugging of the virtual machine. These techniques may include a technique to prevent a debugger from being attached to the virtual machine. These techniques may include a technique to detect when the

use of a debugger is being attempted through the use of self-debugging calls. These techniques may include a technique to redirect execution of the virtual machine when a debugger is used by exploiting differences in processor execution under a debugger. The tamper-proof virtual layer may detect tampering of the virtual machine through the use of multiple layers of security within the virtual machine code. These layers may include a layer with additional tamper checks within the virtual machine. These tamper checks may include a check of unique device identifiers to ensure that the virtual machine has not been copied to an unauthorized machine. These tamper checks may include a check of the native operating environment functions to ensure that these functions have not been modified. These tamper checks may include a check of the operating environment to ensure that the environment has not been modified. These tamper checks may include a check of the application memory to ensure that the application has not been modified. The tamper-proof virtual layer may provide a function to respond to tampering of the virtual machine. This function may include the zeroing of information within the virtual machine. This function may include the processing of a different set of cryptographic data or algorithms.

The tamper-proof virtual layer may intersperse the techniques for protecting against reverse engineering and the techniques for protecting against runtime analysis so as to render either form of analysis ineffective. This may include a technique to intersperse the techniques for runtime analysis with techniques for reverse engineering that require time-consuming manual reverse engineering for an attacker to bypass. This may include a technique to separate the techniques for reverse engineering with techniques for runtime analysis that prevent automated runtime analysis. This may include a technique to repeat these techniques multiple times within the tamper-proof virtual layer such that the total analysis time required would be infeasible.

FIG. 3 illustrates how this cryptographic system is started in accordance with an embodiment of the invention. The computer processor **124'** starts the underlying operating system **101'**, which then executes the client applications **104'**. The client applications can send requests **106'** and receive responses **107'** through a sandbox interface **105'** that starts and provides access to the cryptographic sandbox **108'**.

Within the sandbox, the cryptographic virtual machine **109'** is started when the application starts, which loads the tamper-proof virtual layer **110'**. The virtual machine then loads the encrypted codes **112'** which provide the secure cryptographic functions **115'**, and performs runtime decryption **113'** using the virtual machine interpreter **111'**, which unwraps the obfuscation layer **114'** in the encrypted codes. The codes then provide the anti-debugging techniques **116'** to be executed in the virtual machine.

FIG. 4 illustrates how the cryptographic system accesses the encrypted storage in accordance with embodiment. The virtual machine interpreter **111'**, after starting up, performs encrypted writes **117'** to and encrypted reads **118'** from an encrypted storage **119'**. The encrypted reads and encrypted writes may use an AES key stored in the encrypted codes. The information in the encrypted storage may comprise other cryptographic keys **120'** or other cryptographic data **121'**.

FIG. 5 illustrates how the cryptographic system has trusted access to operating system functions in accordance with an embodiment of this invention. The virtual machine interpreter **111'**, after starting up, verifies functions **102'** from the underlying operating system **101'** before calling these functions in order to ensure trusted access **103'** to these functions is possible. This function verification may comprise function pointer checks.

FIG. 6 illustrates how the cryptographic system securely checks for updates in accordance with an embodiment of this invention. The virtual machine interpreter **111'**, after starting up, connects to a trusted party **112'**. This connection may comprise a secure socket layer (SSL) connection. If the trusted party indicates that an update is available, the virtual machine interpreter will download a new set of encrypted codes **112'** for use in the virtual machine.

CLAIMS

1. A product for providing cryptography to applications being performed on a device comprising:

instructions for directing a processing unit to:

provide a cryptographic sandbox that includes:

a virtual cryptographic machine that performs cryptographic operations,

a sandbox interface that receives requests for cryptographic operations from a client application and transmits results of the cryptographic operations performed by the virtual cryptographic machine to the client application; and

a media readable by the processing unit to store the instructions.

2. The product of claim 1 wherein the instructions for providing the cryptographic sandbox further comprise instructions for the cryptographic sandbox to include:

a secure virtual storage for storing cryptographic keys and data.

3. The product of claim 1 wherein the secure virtual storage is within a memory space of the virtual cryptographic machine.

4. The product of claim 1 wherein the secure virtual storage is outside the virtual cryptographic machine.

5. The product of claim 1 wherein the instructions for providing a sandbox including a virtual cryptographic machine further comprise instructions to provide the virtual cryptographic machine with a virtual machine interpreter that obfuscates operation of the virtual cryptographic machine from an underlying operating system.

6. The product of claim 5 wherein the instructions for providing the virtual machine interpreter includes instructions for directing the processing unit to:
- receive a function call from an underlying operating system in the machine interpreter,
- 5 verify the function call with the machine interpreter, and
- perform the function call in the virtual cryptographic machine in response to the function call being verified.
7. The product of claim 1 wherein the instructions for providing the cryptographic sandbox further comprise instructions to provide the virtual cryptographic machine with a cryptographic module that performs the cryptographic operations.
- 10
8. The product of claim 1 wherein the instructions for providing the cryptographic sandbox include providing a tamper proof layer within the virtual cryptographic machine that protects the cryptographic processing and data from unauthorized users.
- 15
9. The product of claim 8 wherein the instructions for providing the tamper proof layer include instructions that provide a set of virtual machine codes in an encrypted form that are decrypted at runtime to allow normal operation of the virtual cryptographic machine
- 20
10. The product of claim 1 wherein the instructions for providing the cryptographic sandbox further comprise instructions for directing the processing unit to provide the virtual cryptographic machine with anti-debugging techniques to prevent debugging the virtual cryptographic machine.
- 25
11. The product of claim 1 wherein the instructions for providing the cryptographic sandbox further comprise instructions directing the processing unit to:
- 30 establish a secure connection to a trusted party,
- determine whether an update is available, and
- upload the update to memory.

12. A method for providing a virtual cryptographic sandbox for performing cryptographic operations in a device with a processing system comprising:

receiving a request to perform a cryptographic operation from an application in a sandbox interface performed by the processing system;

performing the cryptographic operation using a virtual cryptographic machine being performed by the processing system, and

transmitting a result of the cryptographic operation using the sandbox interface.

13. The method of claim 12 further comprising:

storing encrypted keys and data and an encrypted storage, and

accessing the encrypted keys and data to perform the cryptographic operation.

14. The method of claim 13 wherein the encrypted storage is within a memory space of the virtual cryptographic machine.

15. The method of claim 13 wherein the encrypted storage is within a memory space of an underlying operating system.

16. The method of claim 12 further comprising:

obfuscating the operation of the virtual cryptographic machine from an underlying operating system.

17. The method of claim 16 further comprising:

receiving a function call from an underlying operating system in the machine interpreter,

verifying the function call with the machine interpreter, and

performing the function call in the virtual cryptographic machine in response to the function call being verified.

18. The method of claim 12 further comprising:

performing the cryptographic operations in a cryptographic module of virtual cryptographic machine.

19. The method of claim 12 further comprising:

providing a tamper proof layer within the virtual cryptographic machine
that protects the cryptographic processing and data from unauthorized users.

5

20. The method of claim 12 further comprising:

providing the virtual cryptographic machine with anti-debugging
techniques to prevent debugging the virtual cryptographic machine.

10

21. The method of claim 12 further comprising:

establishing a secure connection to a trusted party;
determining whether an update for the cryptographic sandbox is
available; and
uploading the update to memory.

15

20

25

30