

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F04B 43/08 // F04C 5/00, F01C 5/04		A1	(11) International Publication Number: WO 97/11275
			(43) International Publication Date: 27 March 1997 (27.03.97)
(21) International Application Number: PCT/IB96/00924		(81) Designated States: CN, JP, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 11 September 1996 (11.09.96)			
(30) Priority Data: 95202542.7 20 September 1995 (20.09.95) EP		Published With international search report.	
(34) Countries for which the regional or international application was filed: NL et al.			
(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).			
(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).			
(72) Inventors: VAN HEUMEN, Emanuel, Laurentius, Gerardus, Maria; C. Wichmannstraat 28, NL-5612 RM Eindhoven (NL). DIJKSMAN, Johan, Frederik; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). ZOETELIEF, Wilhelmus, Frederikus; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			
(74) Agent: CUPPENS, Hubertus, M., M.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).			

(54) Title: PUMP AND METHOD FOR MANUFACTURING THE PUMP

(57) Abstract

The pump (1) comprises a chamber (2) having an inlet opening (22) and an outlet opening (21). The chamber (2) extends between a first main wall (30) and a second main wall (40). The first main wall (30) is a triangular bottom wall of a body (3). The second main wall (40) is a part of a triangular bottom wall of a tub (4). The body (3) is tiltable relative to the tub (4) so that the volume of the chamber (2) is variable. The pump (1) comprises an outlet valve for blocking the outlet opening (21) when the volume of the chamber (2) is increased and an inlet valve for blocking the inlet opening (22) when the volume of the chamber (2) is reduced. The outlet valve is formed by a first portion (31) of the body (3). This first portion (31) of the body blocks the outlet opening when the body is urged against the outlet opening (21). The inlet valve is formed by a second portion (32) of the body (3). This second portion (32) of the body blocks the inlet opening when the body is urged against the outlet opening (21).

