

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Description

FIELD OF THE INVENTION

The invention relates generally to reduced keyboard systems, and more specifically to reduced keyboard systems using the same memory mapping as the conventional QWERTY or QWERTY-type keyboard using a database engine to resolve ambiguous keystrokes and, functional keys to replicate the typing experience. This reduced keyboard system is also designed for fast typing with 2 hands or 2 thumbs for application in mobile devices, mobile phones, handhelds, PDAs and pocket computers, and the 10 key design is adapted especially for implementation on more advanced input devices, like a glove entry system or an optical pad entry system.

BACKGROUND OF THE INVENTION

One of the advents of the new era is the surge of online text based communication. Online text based communication, started with the computers and the Internet and continued to gain acceptance and popularity with Short Message Service (SMS). Email is now a de facto form of communication for both personal and business purposes and compact electronic devices are getting smaller, have more functionalities and are more integrated. The singular direction headed by mobile phones, handhelds, PDAs and pocket computers is that it must have online text based communication in one form or another, be it emails, SMS or instant messaging (IM).

As devices get smaller, one of the major challenges is to shrink the full QWERTY or QWERTY-like keyboard to a small yet still usable size, or to look at alternate forms of text input, like pen-based text input, handwriting recognition, voice recognition or keyboard alternatives. Pen-based text input is like typing with one finger on a full keyboard, necessitating AI to help predict the words, handwriting recognition is slow at best with a long learning cycle, voice recognition is still in its infant stage and it is the software this time that takes a long time to learn and alternative keyboards are passé, finding its niche mostly under special circumstances like cord keyboards for the handicapped.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Speed and efficiency wise, keyboard entry is still the fastest and most convenient for text based communication. One of the huge barriers to alternative keyboards though is learning curve, but an even larger issue is acceptance and how strongly the QWERTY and QWERTY-like keyboard has endeared itself to the populace. Many "better" keyboard configurations have appeared like the Dvorak keyboard but its adopters are an elite minority. Thus, with the heavy and increasing demand for online text based communication, many device manufacturers are forced to using a miniature full-sized QWERTY keyboard. The miniature keyboard, though visually appealing, leaves much to be desired for anything more than casual text input as the keys are too small and too close together.

There have been various attempts to improve the QWERTY keyboard. Basically, there are 2 main schools of keyboard reduction; the QWERTY keyboard reduction methods and the methods associated with the, already reduced 9 keys, numeric phone pad. Of the 2, the methods associated with the numeric phone pad looks, to the applicant, to be the most advanced and comprehensive for the treatment of multi-character keys (keys assigned with more than one character or symbol), covering both word- or block-based predictive text input , such as those described in U.S. Pat. No. 5,818,437; 5,945,928; 5,953,541; 6,011,554; 6,286,064 and 6,307,549, and the more conventional unambiguous text input methods of multi-tap, two-stroke or multiple-stroke interpretation, like in U.S. Pat. No. 6,011,554 and 6,307,549.

The main problems with the numeric phone pad methods are that they neither are QWERTY compatible nor are they specifically designed for rapid typing or double-typing (double-handed and/or double-thumbed). This is because the centre of their design is on the numeric phone pad and not the QWERTY or QWERTY-type keyboard.

In the present invention, the foundation of design is with the QWERTY and QWERTY-type keyboards, as it is felt that the increasing demands for mobile text input (being able to send text messages everywhere and on the go) will place text input on a much higher priority than numeric input, because of the intensity and extensiveness of usage. Thus, with the merging of the mobile phone and PDA functionalities, even traditional numeric-gearred apparatus like the mobile phone will need a typing enabled (as similar to QWERTY typing as possible) text-input function.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Prior art QWERTY keyboard reduction methods range from chord type keyboards and ergonomic arrangement of keys, as that disclosed in U.S. Pat. Nos. 5,017,030; 4,847,799; 4,824,268; 4,579,470; 3,945,482; 5,790,103 and U.S. Pat. Application No. 20010006587, are either too difficult to learn (chord), not QWERTY compatible, not intuitive enough for fast learning, uses too many keys, do not have strong multi-character keys treatment (needs colour coding, additional control keys or are two-stroke interpretations) and/or advocates single hand typing.

Thus, births the inspiration for the concept keyboard that not only reduces the number of keys to 10 or 12, but continues to utilise the same memory mapping as the QWERTY or QWERTY-type configuration, and allowing for double-typing (double-handed and/or double-thumbbed), thus making it both fast to learn, and fast to input. The concept keyboard uses an intuitive database engine to resolve the ambiguity of the set of characters that each multifunction key represents, by matching words in a word library which are indexed to a unique keystroke sequence.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

SUMMARY OF THE INVENTION

Design considerations for the modern keyboard was for fast fluid text input using a reduced keyboard system, so as to fit into smaller mobile devices like handhelds, PDAs, mobile phones and pocket PCs. The requirements were for fast adoption and thus a low learning curve, and be QWERTY or QWERTY-type compatible, which includes keyboards in other languages like the French keyboard and the German keyboard. Because of the increase in demand for extended textual input, the reduced keyboard system has to be provisioned for 2 handed or 2 thumbbed typing (to send text messages everywhere and on the go even when there are no places to lay down the keyboard) to facilitate speedy and extended usage.

To make the reduced keyboard system easy to learn and QWERTY or QWERTY-type compatible, it uses the same memory mapping as per the usage of a conventional keyboard. Thus, the reduced keyboard system either uses the same visual mapping (same relative physical location of the character keys) of the conventional keyboard or the same finger mapping (i.e. for touch typing) of the conventional keyboard.

For the 10-keys, visual mapping, reduced keyboard system, 6 of the keys are used for character assignments. Each of the keys represents a section of a conventional keyboard divided into 6 sections. Each row of the conventional keyboard composes of 2 sections by dividing the row in the centre and splitting it into 2 sections per row. Since the character keys in a conventional keyboard occupy 3 rows, thus 6 sections are derived from this visual bisecting of the conventional keyboard.

The 6 keys are further arranged in the same mapping as the divided sections on the conventional keyboard (i.e. in 2 columns and 3 rows). The columns could either be straight or angled (more ergonomically arranged), and situated to be used by the middle 3 fingers of both hands or by 2 thumbs, one hand per column.

5 of the 6 keys are further assigned numerals in a half-decimal system. This means that they are assigned 2 numerals, one is a base from 1 to 5 and another is the base plus 5, with 10 being 0.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

The alternative number is selected by a tap-and-cycle method (e.g. Cycle key) or using a separate auxiliary key in tandem with the assigned key (e.g. Shift key). Thus, the numerals from 0 to 9 are fully represented on the reduced keyboard system.

The 6 keys are still further assigned mode changing functions, like caps mode, predictive non-intuitive text input mode and numerals input mode, which are activated by pressing-and-holding the assigned keys.

For the 12-keys, finger mapping, reduced keyboard system, 8 of the keys are used for character assignments. Each of the keys represents the same characters assigned to the fingers for touch typing on a conventional keyboard. In touch typing, the keyboard is mapped to 8 fingers, thus 8 keys are used to represent the characters in the finger map.

The 8 keys are further arranged in the same resting placing (home keys) of the fingers for touch typing on the conventional keyboard (i.e. one row or one row in 2 halves). The row could either be straight or v-shaped (more ergonomically arranged), and situated to be used by the 4 fingers of both hands or by 2 thumbs, one hand on each side of the row. The row need not be continuous and can be separated to be more easily accessible by both hands (i.e. one row in 2 columns).

5 of the 8 keys are further assigned numerals in a half-decimal system. This means that they are assigned 2 numerals, one is a base from 1 to 5 and another is the base plus 5, with 10 being 0. The alternative number is selected by a tap-and-cycle method (e.g. Cycle key) or using a separate auxiliary key in tandem with the assigned key (e.g. Shift key). Thus, the numerals from 0 to 9 are fully represented on the reduced keyboard system.

The 8 keys are still further assigned mode changing functions, like caps mode, predictive non-intuitive text input mode and numerals input mode, which are activated by pressing-and-holding the assigned keys.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

The reduced keyboard system resolves the ambiguity of the set of characters that each multifunction key represents, by matching words in a word library which are indexed to a unique keystroke sequence (intuitive text input mode), or characters in a character library which are indexed to a unique keystroke and digraph association (predictive non-intuitive text input mode), using an intuitive database engine.

The intuitive database engine further refines the order of the words stored per unique keystroke sequence, in the word library, by placing the last used or selected word in front (i.e. first in the queue of choice/list of words to be selected).

The intuitive database engine still further refines the order of the characters stored per unique keystroke and digraph association, in the character library, by placing the last used or selected character in front (i.e. first in the queue of choice/list of characters to be selected).

New words inputted using the predictive non-intuitive text input mode, are able to be automatically added to the word library. This capability together with the capability to reorder the words stored per unique keystroke sequence from most recently used to least recently used or not used, enables the intuitive database engine to be constantly learning and personalising itself to the user.

The reduced keyboard system is further enhanced by the inclusion of 4 keys to represent spacebar, shift, backspace and cycle key.

The spacebar and backspace operates much like the conventional keyboard but with additional features and modes being possible to be activated when pressed-and-held or when used in tandem with the shift key.

The shift key operates much like the conventional keyboard in the capitalisation of characters when used in tandem with a character key, but also as a numeral selector for the half-decimal system and also as a mode changer or performing additional functions when used in tandem with the

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

spacebar, backspace and cycle key. The shift key could also be used to activate new features and modes when pressed-and-held.

The cycle key is used to cycle through a list of choices determined by the intuitive database engine that corresponds to a keystroke sequence (for a word in intuitive text input mode), keystroke and digraph association (for a character in predictive non-intuitive text input mode), keystroke (for a numeral in numerals input mode), and symbols and punctuations keystroke activation (for symbols and punctuations in both text input and numerals input mode).

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows how a QWERTY, and likewise a QWERTY-type, keyboard is mapped visually by the user, and how it could be segmented into 6 sections and the segmented characters assigned into 6 multi-character keys.

FIG. 2 shows how a QWERTY, and likewise a QWERTY-type, keyboard maps 8 fingers for touch typing, and how the same finger mapping could be assigned into 8 multi-character keys.

FIG. 3 shows how the multi-character keys for the VM reduced keyboard system could be arranged in the same visual arrangement as the segmented 6 sections (2 columns and 3 rows) for the conventional QWERTY or QWERTY-type keyboard.

FIG. 3a shows the front view of the preferred embodiment of a keyboard and display of a handheld device in accordance with the present invention, showing an example of how the VM reduced keyboard system (10 keys), using the same visual mapping (physical location of characters) as used for visual typing on a conventional keyboard, could be implemented on a mobile device.

FIG. 4 shows how the multi-character keys for the FM reduced keyboard system could be arranged in the same finger resting arrangement (8 columns and 1 row) as the QWERTY or QWERTY-type keyboard.

FIG. 4a shows the front view of the preferred embodiment of a keyboard and display of a handheld device in accordance with the present invention, showing an example of how the FM reduced keyboard system (12 keys), using the same finger mapping as used for touch typing on a conventional keyboard, could be implemented on a mobile device.

FIG. 5 shows how the numerals for a half-decimal system could be assigned to 5 of the 6 multi-character keys for a VM reduced keyboard system together with an additional assignment of numeral 0 to another multi-character key.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

FIG. 6 shows how the numerals for a half-decimal system could be assigned to 5 of the 8 multi-character keys for a FM reduced keyboard system together with an additional assignment of numeral 0 to another multi-character key.

FIG. 7 shows how the multi-character keys could be assigned with mode changing options of predictive non-intuitive text input mode, caps lock mode, and numerals input mode (num lock) on a VM reduced keyboard system.

FIG. 8 shows how the multi-character keys could be assigned with mode changing options of predictive non-intuitive text input mode, caps lock mode, and numerals input mode (num lock) on a FM reduced keyboard system.

FIG. 9 shows the perspective view of the possible embodiment of a glove input device and display of a text input device in accordance with the present invention, showing an example of how the reduced keyboard system using the visual mapping (10 keys) could be implemented on a glove input device.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

DETAILED DESCRIPTION OF THE INVENTION

Throughout this description, the preferred embodiment and examples shown should be considered as exemplars, rather than as limitations on the present invention.

The reduced keyboard system is a concept keyboard design that uses a minimum of keys to represent the entire QWERTY or QWERTY-type keyboard, which includes keyboards in other languages like the French keyboard and the German keyboard, by employing an intuitive database engine. The idea and purpose of the invention is to have a keyboard design that uses a minimum of keys for text and numerals input, uses the same memory mapping (for the user) as that required for QWERTY or QWERTY-type keyboards, allows for fast typing with 2 hands and/or 2 thumbs, be able to accommodate commonly used keyboard functions like shift and backspace and easily adoptable or used with any word library and character library. The obvious application for the invention would be for small, medium devices like mobile devices, PDAs, handhelds, Pocket PCs, mobile phones, console devices or in places or situations where textual input is restricted and also for keypad-less devices like glove input devices.

Mapping

There are 2 preferred memory (user) mapping configurations to the reduced keyboard system, and for which patent rights are hereby claimed. One is for users that have visually mapped (remembers the physical location of the character keys) out the QWERTY or QWERTY-type keyboard and the other for typists that have mapped their fingers to the QWERTY or QWERTY-type keyboard configuration.

The reduced keyboard system maps the keys such that existing users of the QWERTY or QWERTY-type keyboard that either visually map (VM) the keyboard layout or finger map (FM) the keys, are able to quickly adapt to the new keyboard without the necessity of having go through a long learning cycle. Prior art alternatives for a simplified text input system usually necessitate a longer

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

learning cycle or does not utilise the same memory mapping used for typing on a conventional keyboard (e.g. handwriting recognition, Symbol writing systems where the user write characters by drawing shapes and symbols on a pad, and tap-on-QWERTY pen based input systems).

Prior art QWERTY keyboard reduction methods range from chord type keyboards and ergonomic arrangement of keys, as that disclosed in U.S. Pat. Nos. 5,017,030; 4,847,799; 4,824,268; 4,579,470 and 3,045,482 are either too difficult to learn (chord) or are not QWERTY compatible. Keyboard designs that attempted to be QWERTY compatible, like those in U.S. Pat. No. 5,790,103 and U.S. Pat. Application No. 20010006587, are either not intuitive enough for fast learning, continues to use too many keys, do not have strong multi-character keys treatment (needs colour coding, additional control keys or are two-stroke interpretations) and/or advocates single hand typing. The present invention, not only utilises the same typing memory for the user (both typist and non-typist), as used when typing on a QWERTY keyboard, but the arrangement of keys is also heavily suited to use or complement that memory. This makes the present invention very intuitive to type and very easy to learn.

Visual Mapping (VM) Reduced Keyboard System

FIG. 1 shows how a QWERTY, and likewise a QWERTY-type, keyboard is mapped visually by the user, and how it could be segmented into 6 sections and the segmented characters assigned into 6 multi-character keys.

Thus, for the VM reduced keyboard system, the multi-character keys could be mapped as follows for a QWERTY keyboard:

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Key5 - ZXCV

Key6 - BNM

There are no restrictions to how the keyboard is divided into the 6 segments. The reduced keyboard system is able to function with any configuration of the multi-character keys and thus the essential purpose of the segmentation is for the user to retain and use the same memory mapping as he would if he was typing using a visual mapping of a conventional keyboard. Thus, the multi-character keys for the VM reduced keyboard system could also be mapped as:

Key1 - QWERTY

Key2 - UIOP

Key3 - ASDF

Key4 - GHJKL

Key5 - ZXC

Key6 - VBNM

There are also no restrictions on the multi-character keys to not being able to share character assignments. This is especially true for the segment border characters that could be assigned to either the left or right multi-character keys. Thus, the multi-character keys could be assigned the same segment border characters. This is easily handled by the word library database by having the same word indexed to 2 possible keystroke sequences. Thus, the multi-character keys for the VM reduced keyboard system could also be mapped as (underlined characters are segment border characters):

Key1 - QWERTY

Key2 - TYUIOP

Key3 - ASDFGH

Key4 - GHJKL

Key5 - ZXCVB

Key6 - VBNM

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Finger Mapping (FM) Reduced Keyboard System

For the FM reduced keyboard system, the keys are mapped as per the finger assignments for touch typing on a QWERTY or QWERTY-type keyboard. FIG. 2 shows how a QWERTY, and likewise a QWERTY-type, keyboard maps 8 fingers for touch typing, and how the same finger mapping could be assigned into 8 multi-character keys. Thus, in the FM reduced keyboard system, the multi-character keys could be mapped as follows for a QWERTY keyboard:

Table 1

Key1	Key2	Key3	Key4	Key5	Key6	Key7	Key8
Q	W	E	R T	Y U	I	O	P
A	S	D	F G	H J	K	L	
Z	X	C	V B	N M			

Arrangement of multi-character keys

There are 2 crucial consequences in the arrangement of the multi-character keys. One is to complement the memory (for the user) mapping as discussed above. Thus, for a VM reduced keyboard system, the arrangement of the multi-character keys is similar to the arrangement of the segmented 6 sections of the QWERTY or QWERTY-type keyboard. FIG. 3 shows how the multi-character keys for the VM reduced keyboard system could be arranged in the same visual arrangement as the segmented 6 sections (2 columns and 3 rows) for the conventional QWERTY or QWERTY-type keyboard.

For the FM reduced keyboard system, the layout or arrangement of the multi-character keys is similar to the placement of the fingers, when at rest, on a conventional keyboard. FIG. 4 shows how the multi-character keys for the FM reduced keyboard system could be arranged in the same finger resting arrangement (8 columns and 1 row) as the QWERTY or QWERTY-type keyboard.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

The arrangement of the multi-character keys thus reinforces the same memory mapping used by the user when typing on a conventional keyboard and optimises the VM or FM assignments of the multi-character keys.

The second consideration or consequence for the arrangement of the multi-character keys is to allow the implementation of the reduced keyboard system for efficient and fast double-handed and/or double-thumbed typing. Double-handed typing is not catered for in most prior art alternatives for a simplified text input system, except for a miniaturised QWERTY keyboard, which is unwieldy for double-handed typing. This is especially important when textual input features more frequently in modern device usage. For extensive and fast textual input, double-handed typing is still the fastest and most efficient method compared to alternatives like pen-based input, handwriting recognition, and numeric phone keypad based input.

FIG. 3a shows how the multi-character keys could be arranged on a handheld device that uses the same visual memory mapping as used for visual typing on a conventional keyboard, and also allowing for double-handed or double-thumbed typing. FIG. 4a shows how the multi-character keys could be arranged on a handheld device that uses the same finger mapping as used for touch typing on a conventional keyboard, and also allowing for double-handed or double-thumbed typing.

Non-Textual and Auxiliary Keys

To complement the multi-character keys, non-textual and auxiliary keys are added to the reduced keyboard system. A preferred embodiment of the non-textual and auxiliary keys would be four non-textual or auxiliary keys to be added to the 6 multi-character keys in the VM reduced keyboard system to make it a 10-keys reduced keyboard system, or added to the 8 multi-character keys in the FM reduced keyboard system to make it a 12-keys reduced keyboard system.

The four non-textual or auxiliary keys to be added are spacebar, backspace, shift and cycle keys. FIG. 3 and FIG3a shows how the non-textual and auxiliary keys could be arranged on a

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

keyboard and a handheld device respectively, that uses the same visual memory mapping as used for visual typing on a conventional keyboard, and also allowing for double-handed or double-thumbed typing. FIG. 4 and FIG 4a shows how the non-textual and auxiliary keys could be arranged on a keyboard and a handheld device respectively, that uses the same finger mapping as used for touch typing on a conventional keyboard, and also allowing for double-handed or double-thumbed typing.

The functions of these 4 keys cover a very wide spectrum of functions especially because of the way they could work in tandem with each other. The preferred functions of the various keys individually and in tandem could include:

Table 2

Keystroke or Keystroke Sequence	Function(s)
Spacebar	Spacebar
Backspace	Undo the last character, punctuation, object, symbol or spacebar inputted.
Cycle	Cycle forward (through other objects if available)
Shift + backspace	Cycle backward or reverse cycle (through other objects if available)
Shift	No effect on its own, has to work in tandem with another key
Shift + multi-character keys (in text input mode)	Capitalise the text character that is inputted if not in caps lock mode and vice versa
Shift + multi-character keys (in numerals input mode)	The alternate numeral is selected for the 2 numerals assigned to any multi-character key

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Shift + cycle	The first object in the punctuation & symbols list is inputted (different list of objects for numerals input mode and text input mode)
Shift + spacebar	Carriage return

Of the 4 auxiliary keys, only the cycle key and spacebar is mandatory. Thus, essentially, the reduced keyboard system could function with just 6 or 8 multi-character keys and 2 non-textual or auxiliary keys. Functions like punctuations, carriage return, and backspace could be replicated by modes changing. In retrospect, even the cycle and spacebar function could be replaced by mode changes, but it would counterman what the invention is trying to achieve for fluid, fast and conventional keyboard-like typing.

Typing Modes and Mode Changing

The reduced keyboard system also caters for a multitude of modes like caps lock, intuitive text input mode, predictive non-intuitive text input mode and numerals input mode (num lock). The versatility and flexibility of the reduced keyboard system is enhanced by the mode changing process. The preferred embodiment is for the default mode to be intuitive text input mode.

Mode changing is performed by pressing a mode change assigned key and holding it for an extended period. Pressing-and-holding the same key a second time will undo the mode change and revert the reduced keyboard system to the previous state (mode). The preferred timing and period for the key to be held before a mode change function is performed instead of the normal function of the key is about 1 sec. Any key could be assigned a mode change function, on top of their normal function. The reduced keyboard system is able to differentiate between a normal tap and an extended press-and-hold, by sensing the length of the signal input from an input key, button or input point.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

The preferred embodiment of the reduced keyboard system would be to have the multi-character keys assigned with the mode changing functions of (with the default mode being intuitive text input mode):

- a) changing from intuitive text input mode to predictive non-intuitive text input mode, and vice versa when pressed-and-held a second time
- b) changing from text input mode to numerals input mode (num lock), and vice versa when pressed-and-held a second time
- c) changing to and from caps lock mode during text input mode

FIG. 7 shows how the multi-character keys could be assigned with mode changing options of predictive non-intuitive text input mode, caps lock mode, and numerals input mode (num lock) on a VM reduced keyboard system. FIG. 8 shows how the multi-character keys could be assigned with mode changing options of predictive non-intuitive text input mode, caps lock mode, and numerals input mode (num lock) on a FM reduced keyboard system.

Capitalising and Backspace

Capitalising letters is very similar to the conventional QWERTY or QWERTY-type keyboard. By pressing the shift key and the multi-character key during text input mode (without caps lock), the displayed letter would be in capitals.

“Caps Lock” mode is activated by pressing-and-holding down the caps lock mode assigned key. To switch back to the normal mode, press-and-hold the same key again. In caps lock mode, every character input displayed will be in capitals, unless the shift key is pressed in tandem which would cause a non-capitalised character to be displayed.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Backspace function is again very similar to that for the conventional QWERTY or QWERTY-type keyboard and performed by pressing the backspace key, which will undo the previous character, numeral, symbol, punctuation, object or spacebar input.

Cycling and Lists

When a character, word, object, plurality of objects, numeral, symbol, or punctuation is displayed as one of a list of possible characters, words, objects, plurality of objects, numerals, symbols, or punctuations, subsequent (next possible) characters, words, objects, plurality of objects, numerals, symbols, or punctuations are selected and displayed by pressing the cycle (or cycle forward) key. The cycling process is in a loop, thus, when the last character, word, object, plurality of objects, numeral, symbol, or punctuation is selected and displayed, and the cycle key is pressed again, the first character, word, object, plurality of objects, numeral, symbol, or punctuation will be selected and displayed.

The selection and displayed character, word, object, plurality of objects, numeral, symbol, or punctuation can also be reversed cycled (cycling the character, word, object, plurality of objects, numeral, symbol, or punctuation in the reverse order), and for which patent rights are hereby claimed, if a cycle backward (or reverse cycle) function is implemented (e.g. shift + backspace). Reverse cycling is also in a loop, thus, when the first character, word, object, plurality of objects, numeral, symbol, or punctuation is selected and displayed, and the reverse cycle key (or key combination) is pressed again, the last character, word, object, plurality of objects, numeral, symbol, or punctuation will be selected and displayed.

Lists of characters, words, objects, plurality of objects, numerals, symbols, or punctuations in the reduced keyboard system could either be fixed or learning. Fixed lists will not have the ordering of the characters, words, objects, plurality of objects, numerals, symbols, or punctuations changed on selecting and accepting of a character, word, object, plurality of objects, numeral, symbol, or punctuation. The order of the characters, words, objects, plurality of objects, numerals, symbols, or punctuations could be determined in the beginning for the reduced keyboard system based on how

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

commonly used are the individual characters, words, objects, plurality of objects, numerals, symbols, or punctuations in relation to the other characters, words, objects, plurality of objects, numerals, symbols, or punctuations in the list.

In the preferred embodiment of the reduced keyboard system, fixed lists are used for the symbols database for text input mode, symbols database for numerals input mode and for first character input in predictive non-intuitive text input mode.

An example of what the symbols database could contain and how it could be ordered, for text input are as shown within the quotient marks:

".,|,|?|!|'|@|:|;|'|(|)|'|&|_" where "|" are separators.

An example of what the symbols database could contain and how it could be ordered, for numerals input are as shown within the quotient marks:

".,|,|+|_|*|/|=|(|)|\$|%|#|<|>" where "|" are separators.

The list for first character of a word input in predictive non-intuitive mode is described in detail in Character Library Database.

Learning lists have the characters, words, objects, plurality of objects, numerals, symbols, or punctuations in the list ordered from most recently used to least recently used or not used. Every time a character, word, object, plurality of objects, numeral, symbol, or punctuation in a learning list is selected and accepted, the character, word, object, plurality of objects, numeral, symbol, or punctuation is placed in the front of the list.

Word Library Database

Building the word library database for the intuitive database engine is very simple and easily accommodates and uses any word library for words used on QWERTY or QWERTY-type keyboards.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Using any word library, a word library database is easily built that indexes keystroke sequence, as per the assigned multi-character keys, and the words in the word library.

E.g. 1(a) for a VM reduced keyboard system that assigned the characters to the six multi-character keys in the following manner:

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCV

Key6 - BNM

Words like "error", "errors", "tree", "were", "if" and "of" would be built into the word library database as (where "|" are separators):

Keystroke Sequence	Word(s)
Key1, Key1, Key1, Key1	tree were
Key1, Key1, Key1, Key2, Key1	error
Key1, Key1, Key1, Key2, Key1, Key3	errors
Key2, Key3	if of

E.g. 1(b) for a VM reduced keyboard system that assigned the characters to the six multi-character keys in the following manner (different multi-character keys assigned the same border segment characters, shown as underlined characters):

Key1 - QWERTI

Key2 - YTUIOP

Key3 - ASDFGH

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Key4 - GHJKL

Key5 - ZXCVB

Key6 - VBNM

Words like "error", "errors", "tree", "were", "if" and "of" would be built into the word library database as (where "|" are separators):

Keystroke Sequence	Word(s)
Key1, Key1, Key1, Key1	tree were
Key1, Key1, Key1, Key2, Key1	error
Key1, Key1, Key1, Key2, Key1, Key3	errors
Key2, Key1, Key1, Key1	tree were
Key2, Key3	if of

Prior art ambiguous text input methods, using multi-character keys, such as those described in U.S. Pat. Nos. 5,818,437; 5,945,928; 5,953,541; 6,011,554; 6,286,064 and 6,307,549, have the words sharing the same keystroke sequence ordered in order of decreasing frequency of use, or uses extra auxiliary keys for text input. When frequency of use is utilised as a means of ordering, this would mean at least one more parameter or field per word, compared to the present invention, to keep track of. With a few thousand words in a typical language, this would require a much larger storage space for the database. Also, an additional logic needs be employed for saving the additional information and keeping track of the extra parameter or field. In the case of using an extra auxiliary key for text input, this would make the typing process less intuitive, slows down typing and requires a steeper learning curve, which is contrary to the objectives of the present invention which aims to replicate the smoothness and fluidity of typing on the conventional keyboard. Prior art methods that offer look-ahead capabilities and possible word alternatives, as described in U.S. Pat. No. 6,204,848, also detracts from fluid conventional typing significantly and necessitates additional training, keys (for the word selection) and finger movements (switch from typing to word selecting).

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Intuitive Text Input method

The concept is simple, by using multi-character keys to represent several characters (letters), a user need only press the key that contains the letter he wants once and on forming the word, the intuitive database engine will pick the first word that is indexed to the keystroke sequence, from a built word library database.

If no characters, word or words match or are stored for the keystroke sequence, the next possible "future" keystroke sequence (i.e. keystroke sequence that contains the input keystroke as a subset or sub-keystroke) is located and the first word indexed to that "future" keystroke sequence is picked, displaying the number of characters, up to the number of input keystroke. If there are no next possible "future" keystroke sequence available, then pressing on the keystroke has no effect.

If the word is not what the user intends, the user simply cycles through a list of choices, or if the word does not exist in the word library, type in the new word via the predictive non-intuitive text input mode (discussed later) once, and the new word will be thereafter present in the word library database.

E.g. 2 (Using the same character assignments for the 6 multi-character keys in a VM reduced keyboard system as E.g. 1(a)) and only the words "error", "errors", "tree", "were", "if" and "of" are present in the word library database.

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCV

Key6 - BNM

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Keystroke Sequence	Word(s)
Key1, Key1, Key1, Key1	tree were
Key1, Key1, Key1, Key2, Key1	error
Key1, Key1, Key1, Key2, Key1, Key3	errors
Key2, Key3	if of

User presses Key1:

No word is indexed to keystroke sequence Key1. Database engine searches for the next possible "future" keystroke sequence, which is Key1, Key1, Key1, Key1. The word "tree" (which is first in the order) is picked and the word is displayed up to the number of keystroke inputs which is 1.

Display shows "t" (no cycling is possible)

User presses another Key1 (total Key1, Key1):

No word is indexed to keystroke sequence Key1, Key1. Database engine searches for the next possible "future" keystroke sequence, which is Key1, Key1, Key1, Key1. The word "tree" (which is first in the order) is picked and the word is displayed up to the number of keystroke inputs which is 2.

Display shows "tr" (no cycling is possible)

User presses another Key1 (total Key1, Key1, Key1):

No word is indexed to keystroke sequence Key1, Key1, Key1. Database engine searches for the next possible "future" keystroke sequence, which is Key1, Key1, Key1, Key1. The word "tree" (which is first in the order) is picked and the word is displayed up to the number of keystroke inputs which is 3.

Display shows "tre" (no cycling is possible)

User presses another Key1 (total Key1, Key1, Key1, Key1):

There is a word indexed to keystroke sequence Key1, Key1, Key1, Key1. The word "tree" (which is first in the order) is picked.

Display shows "tree" (cycling is possible. On cycling, the word "were" will be displayed. Cycling another time will cause the word "tree" to be displayed again)

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

User tries to press another Key1 (total Key1, Key1, Key1, Key1, Key1):

No word is indexed to keystroke sequence Key1, Key1, Key1, Key1, Key1. A database engine search for the next possible “future” keystroke sequence, and finds none. There is no effect in pressing that Key1.

Display still shows “tree” (cycling is possible. On cycling, the word “were” will be displayed. Cycling another time will cause the word “tree” to be displayed again)

Behind the simple concept is a powerful intuitive database engine that enhances the performance of the reduced keyboard system and intuitive text input.

Intuitive Word Database Engine (Intuitive text input mode)

Intuitive text input mode is used when typing words that are in the word library database. The library is restricted to whatever word library was used to build the word library database and any new words added to the word library database.

The intuitive engine intuitively deduces the word/s that a user is looking for and presents them to the user. If the first word presented is not the correct choice, the user will be able to cycle (choose another word) through the other possibilities by using the cycle key or reverse cycle key (or key combination).

The intuitive word database engine performs the intuitive deduction by arranging the list of words assigned to a keyboard sequence in the order from most recently used to least recently used or not used (i.e. learning list), and for which patent rights are hereby claimed. This significantly reduces the number of times users need to cycle and also the amount of words they need to cycle through to reach the word they want. This also helps to keep, the first few word choices presented to the user in-line with the context of the current conversation, whereby certain words are used very often in a particular topic of discussion (the word will be made to appear first in-queue for that discussion topic) but not in other topics (the word will then be relegated behind new word choices).

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

The power of learning lists and the intuitive word database engine is that by ordering objects by their recentness of usage instead of other prior art methods like most frequently used and most commonly used, the invention is able to achieve two key things. One is that obscure words that are used in the current context of the conversation are able to be presented to the top of the list instantly, thus reducing the amount of cycling required. The second is that frequently used words that are not used in the current context of the conversation is quickly moved down the list, so that it would not be presented as the first few word choices, and thus again reducing the amount of cycling required to select the desired word.

Character Library Database

The character library database is used for predictive non-intuitive text input. The character library database for the intuitive database engine is very simple to build and easily accommodates and uses the character library for languages used on QWERTY or QWERTY-type keyboards (i.e. listing of all characters used for the language). Using any character library, a character library database is easily built that indexes keystroke (not keystroke sequence like the word library database), as per the assigned multi-character keys and the digraph association with the characters assigned to the multi-character key.

Digraph Association

Digraph association is the association of a keystroke and the previous character inputted. Thus, if there are 6 multi-character keys as in the VM reduced keyboard system and 26 characters total for the language (e.g. 26 letters for the English language), then each association between a keystroke (multi-character key) and a character is called a digraph association. In this case, there would be $26 \text{ multiplied by } 6 = 156$ digraph associations.

The logic employed by using digraph association is that some characters are more likely to follow a particular character than another. Thus, the invention uses digraph association, between previous characters and keystrokes, as an index key for the character library database to which are

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

assigned the characters in the character list assigned to a keystroke or multi-character key. In this way, when a keystroke is inputted, the character library database would reference to the digraph association between the keystroke and the previous character inputted and then present the character list in the order stored for that digraph association.

E.g. 3 Example of how digraph association is used for a VM QWERTY reduced keyboard system.

Assume that the character assignments for the multi-character keys are

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCV

Key6 – BNM

They are thus 26 characters in total and 6 multi-character keys. This would mean that there are 156 digraph associations in total. The character database that is built could then look like (where “|” are separators and “x”, Key“y” is the digraph association between keystroke, Key“y” and a previous inputted character, “x”):

Digraph Association	Characters
a, Key1	r t q e w
a, Key2	i u y p o
a, Key3	d s a f g
a, Key4	h l k j
a, Key5	z c v x
a, Key6	n m b
b, Key1	r e t w q

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

b, Key2	o i u p y
.	
.	
.	
z, Key5	c v x z
z, Key6	n m b

Thus, if a user inputs or selects the character "a" and then presses key 1, the character "r" would be selected and displayed first (by referencing to digraph association a, Key1). If the user presses the cycle key (cycle forward) repeatedly, he would then be presented, in place of the character "r", the characters "t", "q", "e", "w", "r", "t", "q"... respectively and sequentially.

As it can be seen in the example, Key2 has a different digraph association with the previous inputted character "a" compared to the digraph association it has with previous inputted character "b". In this example, the letter "i" is most likely to follow a previous input character of "a", while the letter "o" is most likely to follow a previous input character of "b".

By indexing the character library database to digraph association, the database engine will more accurately predict the character required by the user, when the ambiguous multi-character key is pressed in predictive non-intuitive text input mode.

Tap-and-Cycle Method

Characters in the predictive non-intuitive text input mode are selected using the tap-and-cycle method. As can be seen in E.g. 3, the user first taps on the multi-character key, and he is presented with the first object for that digraph association and keystroke. If it is not the character the user wants, the user proceeds with cycling through the list using the cycle key or reverse cycle key (or key combination). The user accepts the character being selected and displayed by pressing any multi-character key, spacebar, symbol, punctuation or inputting any character, characters, word, numeral or object.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

The tap-and-cycle method is superior to other unambiguous multi-character key input method like the multi-tap method, where a user repeatedly taps on the same multi-character key to select through the character list assigned to the multi-character key. This is because when 2 subsequent characters to be inputted are assigned to the same multi-character key, the multi-tap method must either employ a time delay so that multi-tapping on the same multi-character key again would yield a new character instead of the normal cycling function, or the user must press a character acceptance key (to accept the first character) before multi-tapping the same multi-character key again for the second character.

In the tap-and cycle method, a user typing 2 characters that are assigned to the same multi-character key, simply taps the multi-character key, cycle with the cycle or reverse cycle key, and then tap on the multi-character key again and cycle with the cycle or reverse cycle key again. There is no need for the implementation of a time delay or character acceptance key.

Prior art methods for unambiguous text input, using multi-character keys, uses multi-tap, two-stroke or multiple-stroke interpretation, like in U.S. Pat. Nos. 6,011,554; 6,307,549, or auxiliary multi-tap (an auxiliary key is used with multi-tap), as described in U.S. Pat. No. 6,219,731. The reduced keyboard system is easily compatible with any of these methods, but the preferred embodiment is with the tap-and-cycle method as cycling (namely the cycle key) is already used for intuitive text input as well as for symbols and punctuations input, and numerals input.

Character Learning Engine

Digraph association could be further enhanced by making the character library database "learning" as well. This means that whenever a character is selected and accepted by the user, the character moves to the front of the character list for that particular digraph association and keystroke. Thus, for each digraph association with the keystroke, the characters or symbols assigned to the same multi-character key (keystroke), are arranged in the order from most recently used to least recently used or not used (i.e. learning list) for that digraph association, and for which patent rights are hereby claimed.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

E.g. 4 Example of how the learning engine works for a VM QWERTY reduced keyboard system.

Assume that the character assignments for the multi-character keys are

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCV

Key6 – BNM

Assume that the character list corresponding to the digraph association for Key1 and the previous input character "a" is:

Digraph Association	Characters
a, Key1	r t q e w

When a user selects and inputs the character "a" followed by pressing Key1, the character "r" would be selected and displayed first. If the user cycles to the next character "t" and accepts it by pressing any multi-character key, spacebar, symbol, punctuation or inputting any character, characters, word, numeral or object. The character "t" would then be moved to the front of the character list corresponding to the digraph association and keystroke. In this case the character list corresponding to the digraph association for Key1 and the previous input character "a" would now be re-ordered to:

Digraph Association	Characters
a, Key1	t r q e w

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Setting-up the Digraph Association Character Library Database

To optimise the power in using digraph association, the character library database for digraph association could be easily set-up in the beginning, before the learning engine sets in, by arranging the characters in the character list in order of most commonly used character to least commonly used, for all characters in the language. This most common letter used list could be obtained easily in any preferred or referenced statistic. By using a simple common letter used list to set-up the database, the process of setting-up the database would be made very simple, fast and effective as all character list related to the same multi-character key would be the same, regardless of digraph association. Digraph association will be optimised later with the character learning engine.

An example of the characters in the English language (QWERTY) arranged in order of most commonly used character to least commonly used character could be:

E,T,A,O,I,N,S,H,R,D,L,C,U,M,W,F,G,Y,P,B,V,K,J,X,Q,Z

For setting-up the digraph association character library database, there is no difference in the ordering of the character list assigned to a multi-character key, between the different digraph associations with the same multi-character key. All of the characters or objects in the character list will be initially ordered from most commonly used character or object in the language to least commonly used character or object in the language.

Prior art methods that look into prefix association, as disclosed in U.S. Pat. No. 6,219,731, is tied very much to mathematical statistics and probability, and also linked to various levels of prefix association and even positional considerations. All of these increase the burden for storage of the database, as well as the logic employed to utilise and to set-up the database. The present invention simplifies and optimises the entire process for both usage and set-up, by having the character library database tied to only digraph association (level 1 prefix) and ordered from most recently used to least recently used or not used (i.e. learning list), by means of a character learning engine. In the preferred embodiment, the character library database not only retains the very powerful predictive nature of digraph association, but is also capable of being improved with every usage and/or personalised to

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

the user by means of the character learning engine without any heavy emphasis on statistics, probability or permutation.

E.g. 5 Example of how the character library database, for digraph association, could be set-up for a VM QWERTY reduced keyboard system.

Assume that the character assignments for the multi-character keys are

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCv

Key6 – BNM

Assume that the most common used letter arranged to the least common used letter is:

E,T,A,O,I,N,S,H,R,D,L,C,U,M,W,F,G,Y,P,B,V,K,J,X,Q,Z

Since for the set-up, the character list is only dependent on the character assignment to the multi-character keys and the commonness of the characters, and not to the digraph association, the initial digraph association character library database would like (where “|” are separators):

Digraph Association	Characters
a, Key1	e t r w q
a, Key2	o i u y p
a, Key3	a s d f g
a, Key4	h k j
a, Key5	c v x z
a, Key6	n m b

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

b, Key1	e t r w q
b, Key2	o i u y p
., ...	...
., ...	...
., ...	...
z, Key5	c v x z
z, Key6	n m b

First Character of a Word

For the first character of a word inputted in predictive non-intuitive text mode, there are no digraph association as there is no previous character inputted.

In the character library database, the character list, for first characters of a word, are indexed to keystrokes only (no digraph association) as per their assignment to their multi-character keys. In the preferred embodiment of the reduced keyboard system, character lists with digraph association are *learning lists* while character lists without digraph association (e.g. first characters of a word) are *fixed lists* (see section *Cycle and Lists*).

The character library database, for first character of a word, is built from a first letter frequency list, comprising of all the characters in the language and how common or frequently they are used as the first character of a word, and the character assignments to the multi-character keys. The first letter frequency list could be easily obtained in any preferred or referenced statistic.

An example of the characters in the English language (QWERTY) arranged in order of most commonly used first character of a word could be:

T, O, A, W, B, C, D, S, F, M, R, H, I, Y, E, G, L, N, Q, U, J, K, P, V, X, Z

E.g. 6 Example of how the character library database, for first character of a word, could be built for a VM QWERTY reduced keyboard system.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Assume that the character assignments for the multi-character keys are

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCV

Key6 – BNM

Assume that the most common used first letter of a word arranged to the least common used first letter of a word is:

T, O, A, W, B, C, D, S, F, M, R, H, I, Y, E, G, L, N, Q, U, J, K, P, V, X, Z

The character library database, for first character of a word, would look like (where “|” are separators):

Keystroke	Characters
Key1	T W R E Q
Key2	O I Y U P
Key3	A D S F G
Key4	H L J K
Key5	C V X Z
Key6	B M N

Because the character list for the first character of a word, is a fixed list, first characters that are inputted using predictive non-intuitive text input method, and that are relatively less common first characters of a word like “q” and “z” would require 3 or more presses of the cycle key. Alternatives to the tap-and-cycle method could be employed, like the two stroke interpretation, for the first character of a word input, which limits the maximum number of keystrokes to identify an unambiguous character

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

to two strokes, with the first keystroke selecting the character list and the second keystroke identifying the actual character in the character list. The preferred embodiment of the reduced keyboard system is for only the tap-and-cycle method to be implemented, as this reduces the learning curve and confusion for the user, and since cycling is already implemented throughout the system, the tap-and-cycle method is thus much more in synch with the reduced keyboard system than any other unambiguous text input method.

Predictive Non-Intuitive Text Input method

Whenever a new word that does not exist in the current library is required to be entered, or should the user choose not to use the word library database, the user will need to switch to predictive non-intuitive text input mode. This is done simply by pressing-and-holding the predictive non-intuitive mode assigned key. To switch back to intuitive text input mode, press-and-hold the same key again.

The concept is simple, by using multi-character keys to represent several characters (letters), a user need only press the key that contains the letter he wants and the predictive database engine will pick the first character that is indexed to the keystroke, from a built character library database. and if the first choice of letter is not the correct one, to cycle through the other letter choices by using the same cycling key or reverse cycling key (or key combination) used in intuitive text input mode. This is as per the tap-and-cycle method. The strength of this design is that the user need not be worried that the next letter is assigned to the same multi-character key. The user simply types one multi-character key, cycles with cycle key or reverse cycle key (or key combination) if necessary; and types another multi-character key, be it the same multi-character key or another, cycle and repeat.

The character selected and displayed for the user for a multi-character keystroke, is predicted by the predictive database engine, and is derived from the first character of a word character library or the digraph association character library, depending if the character inputted is the first character of a word or not. The character library database engine searches the appropriate library, indexes to the

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

corresponding keystroke or digraph association and displays the first object or character in the corresponding character list.

E.g. 7 Example of how the word “abba” is typed in predictive non-intuitive text input mode.

Assume that the character assignments for the multi-character keys are

Key1 - QWERT

Key2 - YUIOP

Key3 - ASDFG

Key4 - HJKL

Key5 - ZXCV

Key6 – BNM

Assume that the character library database, for first character of a word, to be (where “|” are separators):

Keystroke	Characters
Key1	T W R E Q
Key2	O I Y U P
Key3	A D S F G
Key4	H L J K
Key5	C V X Z
Key6	B M N

Assume that the digraph association for the preceding (previous input) characters “a” and “b” to be (where “|” are separators):

Digraph Association	Characters
a, Key1	r t q e w

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

a, Key2	i u y p o
a, Key3	d s a f g
a, Key4	h k j
a, Key5	z c v x
a, Key6	n m b
b, Key1	r e t w q
b, Key2	o i u p y
b, Key3	a s d f g
b, Key4	h k j
b, Key5	c v x z
b, Key6	n m b

User presses Key3:

Since this is the first character of a word, the first character of a word character library is used and the first object cross-referenced to the keystroke Key3 is the character "a"

Display shows "a" (cycling is possible but since this is the character the user wants, the user goes on to type the next character)

User presses Key6 (total Key3, Key6):

Since this is not the first character of a word, the digraph association character library is used and the first object cross-referenced to the digraph association a, Key6 is the character "n"

Display shows "an" (cycling is possible)

User presses cycle key once

Display shows "am" (cycling is possible)

User presses cycle key again

Display shows "ab" (cycling is possible. Cycling another time will cause the characters "an" to be displayed again but since this is the character the user wants, the user goes on to type the next character)

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

User presses another Key6 (total Key3, Key6, Cycle, Cycle, Key6):

Since the character "b" (for the previous character input) is selected and accepted (by inputting another (this) character) in the character list corresponding to the digraph association for Key6 and the previous input character "a" (i.e. a, Key6), the character list for the digraph association is now reordered by the character learning engine from

a, Key6	n m b
to	
a, Key6	b n m

as character "b" is now the most recently used character in the character list for the digraph association a, Key6.

Since this input is not the first character of a word, the digraph association character library is used and the first object cross-referenced to the digraph association b, Key6 is the character "n"

Display shows "abn" (cycling is possible)

User presses cycle key once

Display shows "abm" (cycling is possible)

User presses cycle key again

Display shows "abb" (cycling is possible. Cycling another time will cause the characters "abn" to be displayed again but since this is the character the user wants, the user goes on to type the next character)

User presses Key3 (total Key3, Key6, Cycle, Cycle, Key6, Cycle, Cycle, Key3):

Since the character "b" (for the previous character input) is selected and accepted (by inputting another (this) character) in the character list corresponding to the digraph association for Key6 and the previous input character "b" (i.e. b, Key6), the character list for the digraph association is now reordered by the character learning engine from

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

b, Key6	n m b
to	
b, Key6	b n m

as character "b" is now the most recently used character in the character list for the digraph association b, Key6.

Since this input is not the first character of a word, the digraph association character library is used and the first object cross-referenced to the digraph association b, Key3 is the character "a"

Display shows "abba" (cycling is possible)

User presses spacebar to accept word.

If the user inputs the word "abba" again using predictive non-intuitive text input, the keystroke sequence would then be Key3, Key6, Key6, Key3 (total of 4 keystrokes) compared to the first time which was Key3, Key6, Cycle, Cycle, Key6, Cycle, Cycle, Key3 (total of 8 keystrokes), because of the reordering of the character lists for the 2 digraph associations by the character learning engine (provided that no further reordering was done to the 2 digraph associations).

Behind the simple concept is a powerful predictive database engine that enhances the performance of the reduced keyboard system and predictive non-intuitive text input.

Predictive Character Database Engine (Predictive Non-Intuitive text input mode)

Note that the predictive character database engine could be the same database engine as the intuitive word database engine, but just described or termed differently because of the differences in nature of its tasks and functions. In the preferred embodiment they are both referring to the same engine, collectively called the database engine or intuitive database engine.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Predictive non-intuitive text input mode is used when a user is typing words that are not in the word library database. In this mode, the character library database is used instead of the word library database. The user types in the word by typing characters unambiguously through a method known as tap-and-cycle. When a user presses a multi-character key, only the characters assigned to the multi-character key will be presented to the user. The power of the predictive engine is that it can predicatively deduce which character/s to be presented to the user first, unlike most unambiguous multi-character text input methods that always present the character list in a fixed order.

The disadvantage of a predictive engine behind unambiguous multi-character text input is that touch typing is not fully possible, but the huge reduction in key presses will more than outweigh the deficiency of the ability to touch type.

The predictive character database engine performs the prediction deduction by arranging the list of characters assigned to a multi-character key, in an order dependent on the digraph association of the characters assigned to the multi-character key and the preceding (previous inputted) character. The order of characters is in the order from most recently used after the preceding character to least recently used or not used following the preceding (previous inputted) character (i.e. learning list). This significantly reduces the number of times users need to cycle and also the amount of characters they need to cycle through to reach the character they want. Thus, making non-intuitive text input mode typing predictive. Digraph association works because among all the characters assigned to a multi-character key, some of the characters are more likely to proceed after a previous inputted character than the others, and this likelihood is constantly updated by the database engine.

In the preferred embodiment, before any digraph association is learnt, the database engine arranges the character list of each multi-character key and its digraph associations, based on any statistical analysis of the characters usage for that particular language (e.g. English for QWERTY keyboard), from the most commonly used to the least commonly used.

When no digraph association is present (e.g. first character of a word), the database engine arranges the character list of each multi-character key, based on any statistical analysis of the

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

characters usage for that particular language (e.g. English for QWERTY keyboard) from the most common first letters of words to the least common first letters of words.

When a character, word, or plurality of objects is formed in predictive non-intuitive text input mode, by typing a non-textual character or inputting an auxiliary function like spacebar or carriage return, the database engine will check to see if the character, word or plurality of objects is present in the word library. If the word does not exist in the word library, the new word could be automatically added to the word library and the new word will be thereafter present in the word library database.

All these designs and processes help make predictive non-intuitive text input faster, more user friendly, and even predictive.

Admittedly, predictive non-intuitive text input is much slower than intuitive text input, but the occurrence and necessity of non-intuitive mode typing is minimal and one-time only as the word will be captured in the library and made available in intuitive text input mode the next time round.

Word Library Growth and Control

When a new word is typed and accepted in predictive non-intuitive text input mode, it could be automatically added to the word library. The database engine first, checks to see if the keystroke sequence corresponding to the new word already exists in the word library database. If the keystroke sequence already exists, then it checks to see if the word is currently residing in the word library database. If the word already exists, then nothing else is done. If the word does not exist as one of the objects, corresponding to the keystroke sequence, in the word library, the new word is then added to the front of the list of objects and would be selected and displayed first when next the keystroke sequence is inputted in intuitive text input mode. If no keystroke sequence, corresponding to the new word, exists in the word library database, a new unique keystroke sequence is then created in the word library database with the new word as the first object the index key (i.e. unique keystroke sequence) contains.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Because the word library database may not be able to expand indefinitely, some form of control may be necessary to keep the word library database to a manageable or practical size. There are a few methods to this like keeping track on how frequently each word in the library is being used and delete the least used word first so that another word could be added. This will necessitate additional information to be kept in the word library database and will increase the memory storage requirements as well as processing requirements. For the preferred embodiment of the reduced keyboard system, a limit could first be set to the number of words that could be added to the word library database. If the number is about to be exceeded, then the database engine would search for the unique keystroke sequence with the most objects, and delete the last object associated with the keystroke sequence (least recently used word for that keystroke sequence), so that the new word could be saved, recorded or stored into the word library database.

Half-Decimal System

A half-decimal system is where the full decimal representation (0,1,2,3,4,5,6,7,8,9) is represented with half the number of keys. Thus, 5 keys are all that is needed to represent the 10 numerals. Each of the 5 keys would represent 2 values. The first numeral value is from 1 to 5, while the second numeral value is from 6 to 0 respectively. The pairing of the two numerals is based on a simple principle of adding 5 to the first value the key represents, where the value 10 is reduced to represent the numeral 0. The numerals database would thus look something like (where "|" are separators):

Table 3

Keystroke	Numerals
Key1	1 6
Key2	2 7
Key3	3 8
Key4	4 9
Key5	5 0

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Since there are 6 multi-character keys in the VM reduced keyboard system and 8 multi-character keys in the FM reduced keyboard system, 5 of the multi-character keys are assigned 2 numeral values as per Table 3. The first numeral values are selected and displayed when the multi-character keys are pressed in numerals input mode. To select the alternate numeral values, an auxiliary key like the shift is used in tandem with the multi-character key press or the cycle key could be used.

Arrangement of Numeral Assigned Keys

The choice of which multi-character keys to be assigned what pair of numeral values is preferably based on achieving an orderly arrangement, intuitiveness and ease of use. An optional assignment of the numeral 0 to a 6th multi-character key could also be implemented to facilitate the use (press only one key instead of two keys in tandem or cycling) of the very popular numeral.

FIG. 5 shows how the numerals for a half-decimal system could be assigned to 5 of the 6 multi-character keys for a VM reduced keyboard system together with an additional assignment of numeral 0 to another multi-character key. FIG. 6 shows how the numerals for a half-decimal system could be assigned to 5 of the 8 multi-character keys for a FM reduced keyboard system together with an additional assignment of numeral 0 to another multi-character key.

Practically, the reduced keyboard system is not restricted to only using the half-decimal system, especially for implementation on devices or apparatus that are heavy on numeral pad usage like the mobile phone. In such cases, extra buttons or keys could be fitted or implemented to cater for a full range of numerals, achieving the full range from 0 to 9 with just a single keystroke.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Numerals Input Mode

To input numbers, a user will need to switch to the numerals input (num lock) mode. This is done simply by pressing-and-holding the numerals mode assigned key. To switch back to text input mode, press-and-hold the same key again.

In numerals input mode, the user need just press the numeral assigned multi-character keys for 1 to 5 once to unambiguously select and display the numeral. To select and display the numerals 6 to 0, the user will need to press-and-hold the shift key and press the respective numeral assigned multi-character keys at the same time (together), or use the cycle key. Alternatively, if the numeral 0 is assigned to a 6th multi-character key, selecting and displaying the numeral 0 only requires pressing the numeral assigned multi-character key once.

Symbols and Punctuations

Symbols and punctuations are selected and displayed by pressing the shift key and cycle key together. The preferred embodiment of the reduced keyboard system will contain two different symbols database, one for text input and another for numerals input. The reason for having two symbols database is because both text input and numerals input modes use different sets of symbols and punctuations and different frequencies of the said symbols and punctuations. Thus, the symbols in the symbols database for text input will be arranged in the order from most used symbol or punctuation for text input to least used symbol or punctuation for text input. Respectively, the symbols in the symbols database for numerals input will be arranged in the order from most used symbol or punctuation for numerals input to least used symbol or punctuation for numerals input. Both symbols database are preferred to be fixed lists (see section *Cycle and Lists*). The symbols and punctuations frequency list for both text input and numerals input could be obtained in any preferred or referenced statistic.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Examples of what the symbols database, for both text input and numerals input, could contain and their respective ordering of objects can be found in *Cycle and Lists*. On pressing the shift key and cycle key together, the first object in the appropriate symbols database will be selected and displayed. A user can cycle through the symbols and punctuations list by pressing the cycle key or reverse cycle key (or key combination). Typing any characters, numerals, spacebar or even another symbol or punctuation (by pressing the shift key and cycle key together again) will accept the symbol or punctuation and normal typing is resumed.

Conclusion

In conclusion, the essence of the present invention is to utilise the same mapping used for typing on the conventional keyboard, be it visual mapping or finger mapping, while recreating the typing feel and speed of conventional keyboard typing, by facilitating double-handed or double-thumbed typing. Although the reference for the reduced keyboard system is mainly to QWERTY and QWERTY-type keyboards, the teachings of the present system could easily be extended to any conventional keyboard (e.g. Dvorak keyboard) that could be reduced to lesser keys, by employing the same visual mapping or finger mapping and key arrangements, and using the intuitive text input and predictive non-intuitive text input methods to resolve the keystrokes or keystroke sequences of the multi-character keys. In this way, the reduced keyboard system is applicable to most languages that can be represented by a conventional keyboard or conventional means of typing. Numerous embodiments of the teachings of the present invention beyond those specifically described here are possible and which do not extend beyond the scope of those teachings, which scope is defined by the appended claims. In particular, it is obvious even to one not skilled in the art that these teachings are not limited to the standard ambiguous code or to applications only in mobile devices or conventional devices requiring text input, but are well suited for other applications and embodiments, even "futuristic" (less conventional) ones like glove text input devices, shown in FIG. 9, and optical or movement recognition input devices, or any electronic device requiring a means to input a string of non-random characters. It is also obvious that the text input methodology described here could easily be mixed-and-matched with other well-known word completion mechanisms to further reduce the

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

number of keystrokes required for some varieties of text input. It is further obvious that not all the methodology and mechanisms need be implemented to complete the reduced keyboard system as long as its essence remains and main text input functions are intact, thus allowing for the omission of certain methodologies and mechanisms to reduce cost, software size, implementation requirements and/or even some good-to-have (but not critical) functionalities.

Patent Literature Referenced

U.S. Pat. No. 3,945,482, Orthogonal input keyboards, Inventors: Einbinder, and Harvey, Mar 23, 1976.

U.S. Pat. No. 4,579,470, Keyboard with keys concentrated in clusters, Inventors: Casey, and Cullen, Apr 1, 1986.

U.S. Pat. No. 4,824,268, Ergonomic Keyboard, Inventor: Diernisse H. V., Apr 25, 1989.

U.S. Pat. No. 4,847,799, Keyboard apparatus having separate working areas with thumb-operated shifting of key functions, Inventors: Morita; Masasuke; Shimada; Toshio; Kitazaki, and Toshiro, Jul 11, 1989.

U.S. Pat. No. 5,017,030, Ergonomically Designed Keyboard, Inventors: Crews, and Jay A., May 21, 1991.

U.S. Pat. No. 5,790,103, Ergonomic Keyboard Entry System, Inventors: Willner, and Michael A., Aug 4, 1998.

U.S. Pat. No. 5,818,437, Reduced keyboard disambiguating system, Inventors: Grover; Dale L.; King; Martin T.; Kushler and Clifford A., Oct 6, 1998.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

U.S. Pat. No. 5,945,928, Reduced keyboard disambiguating system for the Korean language,
Inventors: Kushler; Clifford A.; Kim, and Jin Bong, Aug 31, 1999.

U.S. Pat. No. 5,953,541, Disambiguating system for disambiguating ambiguous input sequences by
displaying objects associated with the generated input sequences in the order of decreasing
frequency of use, Inventors: King; Martin T.; Grover; Dale L.; Kushler; Clifford A.; Grunbock, and
Cheryl A., Sep 14, 1999.

U.S. Pat. No. 6,011,554, Reduced keyboard disambiguating system, Inventors: King; Martin T.;
Grover; Dale L.; Kushler; Clifford A.; Grunbock, and Cheryl A., Jan 4, 2000.

U.S. Pat. No. 6,204,848, Data entry apparatus having a limited number of character keys and method,
Inventors: Nowlan; Steven; Ebrahimi; Ali; Whaley; David Richard; Demartines; Pierre; Balakrishnan,
and Sreeram, Mar 20, 2001.

U.S. Pat. No. 6,219,731, Method and apparatus for improved multi-tap text input, Inventors: Gutowitz,
and Howard, Apr 17, 2001.

U.S. Pat. No. 6,286,064, Reduced keyboard and method for simultaneous ambiguous and
unambiguous text input, Inventors: King; Martin T.; Grover; Dale L.; Kushler, and Clifford A., Sep 4,
2001.

U.S. Pat. No. 6,307,549, Reduced keyboard disambiguating system, Inventors: King; Martin T.;
Grover; Dale L.; Kushler, Clifford A.; Grunbock, and Cheryl A., Oct 23, 2001.

U.S. Application No. 20010006587, Keyboard arrangement, Inventors: Keinonen Turkka; Wikberg
Harri, and Silfverberg Miika, Jul 5, 2001.

Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

Claims

The invention claimed is:

- 1. A device, apparatus, or component for inputting text comprising ten keys, buttons or input points, wherein each key is allocated a data value, set of data values or a function; and a display window.**
- 2. A device, apparatus, or component for inputting text comprising twelve keys, buttons or input points, wherein each key is allocated a data value, set of data values or a function; and a display window.**
- 3. A device, apparatus, or component as claimed in claim 1 or claim 2, further comprising or have access to a word library database containing characters, or a plurality of objects, including textual objects that are completed words, each of the plurality of objects being associated with an input keystroke sequence, for intuitive text input.**
- 4. A device, apparatus, or component as claimed in claim 1 or claim 2, further comprising or have access to a symbols database containing symbols and punctuations for text input and symbols and punctuations for numerals input.**
- 5. A device, apparatus, or component as claimed in claim 1 or claim 2, further comprising or have access to a character library database containing characters, or objects, each of the object being associated with an input keystroke and digraph association, for predictive non-intuitive text input.**
- 6. A device, apparatus, or component as claimed in claim 1 or claim 2 wherein 4 of the keys are allocated functions of backspace, spacebar, shift and cycling.**
- 7. A device, apparatus, or component as claimed in claim 1 wherein 6 of the keys are allocated a set of characters and numerals, and mode change functions.**
- 8. A device, apparatus, or component as claimed in claim 2 wherein 8 of the keys are allocated a set of characters and numerals and mode change functions.**



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

9. A device, apparatus, or component as claimed in claim 7 wherein: the allocation of the set of characters for the 6 keys is based on the visual arrangement of the characters, for languages on a conventional keyboard (e.g. QWERTY keyboard for the English language), comprising:

a plurality of multifunction keys, said plurality of multifunction keys including a set of 6 multifunction character keys being arranged in 2 columns (need not be straight columns, can be angled columns) and 3 rows (idea being the alphabetic characters of a conventional keyboard being split into 6 parts consisting of 2 columns and 3 rows), each column to be located under the middle 3 fingers of each hand (for 2 hand typing) or within reach of each thumb (for 2 thumb typing), each of said set of multifunction character keys being operative to generate an alphabetic character output function, said set of multifunction keys including:

a first character key located under a user's second or fourth finger tip of the left hand for generating output functions representing at least the alphabetic characters Q, W, E, R, and T;

a second character key located under a user's middle finger tip of the left hand for generating output functions representing at least the alphabetic characters A, S, D, F, and G;

a third character key located under a user's fourth or second finger tip of the left hand for generating output functions representing at least the alphabetic characters Z, X, C, and V;

a fourth character key located under a user's second or fourth finger tip of the right hand for generating output functions representing at least the alphabetic characters Y, U, I, O, and P;

a fifth character key located under a user's middle finger tip of the right hand for generating output functions representing at least the alphabetic characters H, J, K, and L;

a sixth character key located under a user's fourth or second finger tip of the right hand for generating output functions representing at least the alphabetic characters B, N, and M;

10. A device, apparatus, or component as claimed in claim 8 wherein: the allocation of the set of characters for the 8 keys is based on the character-finger assignment for 8 finger touch typing (excluding the assignments for the thumbs which is for the spacebar), for languages on a conventional keyboard (e.g. QWERTY keyboard for the English language), comprising:



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

a plurality of multifunction keys, said plurality of multifunction keys including a set of 8 multifunction character keys being arranged in 8 columns and 1 row (need not be a straight row, can be an angled row or v-shaped row), each column to be located under the 4 fingers of each hand (for 2 hand typing) or within reach of each thumb (for 2 thumb typing), each of said set of multifunction character keys being operative to generate an alphabetic character output function, said set of multifunction keys including:

a first character key located under a user's first finger tip of the left hand for generating output functions representing at least the alphabetic characters Q, A, and Z;

a second character key located under a user's second finger tip of the left hand for generating output functions representing at least the alphabetic characters W, S, and X;

a third character key located under a user's middle finger tip of the left hand for generating output functions representing at least the alphabetic characters E, D, and C;

a fourth character key located under a user's fourth finger tip of the left hand for generating output functions representing at least the alphabetic characters R, F, V, T, G, and B;

a fifth character key located under a user's fourth finger tip of the right hand for generating output functions representing at least the alphabetic characters Y, H, N, U, J, and M;

a sixth character key located under a user's middle finger tip of the right hand for generating output functions representing at least the alphabetic characters I, and K;

a seventh character key located under a user's second finger tip of the right hand for generating output functions representing at least the alphabetic characters O, and L;

an eighth character key located under a user's first finger tip of the right hand for generating output functions representing at least the alphabetic character P;

11. A device, apparatus, or component as claimed in claim 7 or claim 8 wherein to input a character; the key, button or input point that represents the character need only be pressed or used once using a intuitive text input method comprising the steps of:



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- (a) accepting an input keystroke from the key, button or input point;**
- (b) if the input keystroke corresponds to a normal tap or use of one of the keys, buttons or input points assigned with a set of characters, then:**
 - 1) display the first character, characters or word, in the word library database, matching or stored for the keystroke sequence; or**
 - 2) if no characters, word or words match or are stored for the keystroke sequence;**
 - a. find the next possible future keystroke sequence (i.e. keystroke sequence that contains the input keystroke as a subset or sub-keystroke);**
 - b. display the first few characters, up to the number of input keystroke, for the first word matching or stored for the future possible keystroke sequence (if there are no possible future keystroke sequence, there will be no effect); and**
 - 3) continuing at step (a);**
- (c) if the input keystroke corresponds to a extended tap (e.g. press-and-hold) or prolonged use of one of the keys, button or input points assigned with a set of characters, then:**
 - 1) a mode change is performed. A mode change could be;**
 - a. mode change from intuitive text input mode to predictive non-intuitive text input mode; or**
 - b. mode change to and from caps lock mode and non-caps lock mode, then continuing at step (a); or**
 - c. mode change from intuitive text input mode to numerals input mode;**
- (d) if the input keystroke corresponds to spacebar, then:**
 - 1) a space is displayed;**
 - 2) any previous inputted character, characters, word or plurality of objects is presumed accepted by the user and remains on the display;**



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- 3) the accepted character, characters, word or plurality of objects is moved to the front of the objects stored in the word library database, for the same keystroke sequence; and
- 4) continuing at step (a)
- (e) if the input keystroke corresponds to backspace, then:
 - 1) the previous text input keystroke or spacebar keystroke is undone; and
 - 2) continuing at step (a)
- (f) if the input keystroke corresponds to cycling, then:
 - 1) any previous inputted character, characters, symbol, word or plurality of objects is cycled to the next character, symbol, word or plurality of objects stored in the same keystroke sequence (cycle forward); and
 - 2) continuing at step (a)
- (g) if the input keystroke corresponds to shift and the keystroke is held while inputting another keystroke, then:
 - 1) if the other input keystroke corresponds to a normal tap or use of one of the keys, buttons or input points assigned with a set of characters, then:
 - a. the displayed character as determined in step (b) will be in capitals if in non-caps lock mode, or in low caps if in caps lock mode; and
 - b. continuing at step (a)
 - 2) if the other input keystroke corresponds to spacebar, then:
 - a. carriage return function is executed and the cursor on the display will proceed to the next line;
 - b. any previous inputted character, characters, word or plurality of objects is presumed accepted by the user and remains on the display;




Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- c. the accepted character, characters, word or plurality of objects is moved to the front of the objects stored in the word library database, for the same keystroke sequence; and
 - d. continuing at step (a);
- 3) if the other input keystroke corresponds to cycling, then:
 - a. display the first symbol, punctuation or object in the text input symbol database;
 - b. any previous inputted character, characters, word or plurality of objects is presumed accepted by the user and remains on the display;
 - c. the accepted character, characters, word or plurality of objects is moved to the front of the objects stored in the word library database, for the same keystroke sequence; and
 - d. continuing at step (a)
- 4) if the other input keystroke corresponds to backspace, then:
 - a. any previous inputted character, characters, symbol, word or plurality of objects is cycled to the previous character, symbol, word or plurality of objects stored in the same keystroke sequence (cycle backward); and
 - b. continuing at step (a)
- 12. A device, apparatus, or component as claimed in claim 7 or claim 8 wherein to input a character unambiguously; the key, button or input point that represents the character need to be pressed once and the cycle key used, if necessary, one or more times, using a predictive non-intuitive text input method comprising the steps of:
 - (a) accepting an input keystroke from the key, button or input point;
 - (b) if the input keystroke corresponds to a normal tap or use of one of the keys, buttons or input points assigned with a set of characters, then:



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- 1) display the first character, in the character library database, matching or stored for the keystroke, and matching or stored for the digraph association if it is not the first character of a word;
 - 2) any previous inputted character or object is presumed accepted by the user and remains on the display;
 - 3) the accepted character or object is moved to the front of the objects stored in the character library database, for the same keystroke, and digraph association if it is not the first character of a word; and
 - 4) continuing at step (a);
- (c) if the input keystroke corresponds to a extended tap (e.g. press-and-hold) or prolonged use of one of the keys, button or input points assigned with a set of characters, then:
- 1) a mode change is performed. A mode change could be;
 - a. mode change from predictive non-intuitive text input mode to intuitive text input mode; or
 - b. mode change to and from caps lock mode and non-caps lock mode, then continuing at step (a); or
 - c. mode change from predictive non-intuitive text input mode to numerals input mode;
- (d) if the input keystroke corresponds to spacebar, then:
- 1) a space is displayed;
 - 2) any previous inputted character or object is presumed accepted by the user and remains on the display;
 - 3) the accepted character or object is moved to the front of the objects stored in the character library database, for the same keystroke, and digraph association if it is not the first character of a word; and
 - 4) continuing at step (a)



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

(e) if the input keystroke corresponds to backspace, then:

- 1) the previous text input keystroke or spacebar keystroke is undone; and**
- 2) continuing at step (a)**

(f) if the input keystroke corresponds to cycling, then:

- 1) any previous inputted character or object is cycled to the next character or object stored in the same keystroke, and digraph association if it is not the first character of a word (cycle forward); and**
- 2) continuing at step (a)**

(g) if the input keystroke corresponds to shift and the keystroke is held while inputting another keystroke, then:

- 1) if the other input keystroke corresponds to a normal tap or use of one of the keys, buttons or input points assigned with a set of characters, then:**
 - a. the displayed character as determined in step (b) will be in capitals if in non-caps lock mode, or in low caps if in caps lock mode; and**
 - b. continuing at step (a)**
- 2) if the other input keystroke corresponds to spacebar, then:**
 - a. carriage return function is executed and the cursor on the display will proceed to the next line;**
 - b. any previous inputted character or object is presumed accepted by the user and remains on the display;**
 - c. the accepted character or object is moved to the front of the object stored in the character library database, for the same keystroke, and digraph association if it is not the first character of a word; and**



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- d. continuing at step (a);
- 3) if the other input keystroke corresponds to cycling, then:
- a. display the first symbol, punctuation or object in the text input symbol database;
 - b. any previous inputted character or object is presumed accepted by the user and remains on the display;
 - c. the accepted character or object is moved to the front of the objects stored in the character library database, for the same keystroke, and digraph association if it is not the first character of a word; and
 - d. continuing at step (a)
- 4) if the other input keystroke corresponds to backspace, then:
- a. any previous inputted character or object is cycled to the previous character or object stored in the same keystroke, and digraph association if it is not the first character of a word (cycle backward); and
 - b. continuing at step (a)
13. A device, apparatus, or component as claimed in claim 7 wherein: the allocation of the numerals on the 6 keys is based on a half-decimal system wherein: each numeral assigned key would represent 2 numerals with one numeral being a base from 1 to 5 and another numeral being the base plus 5, with 10 being rounded to 0 (e.g. one key could be assigned values 1 and 6 and another could be assigned 5 and 0).
14. A device, apparatus, or component as claimed in claim 8 wherein: the allocation of the numerals on the 8 keys is based on a half-decimal system wherein: each numeral assigned key would represent 2 numerals with one numeral being a base from 1 to 5 and another numeral being the base plus 5, with 10 being rounded to 0 (e.g. one key could be assigned values 1 and 6 and another could be assigned 5 and 0).



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

15. A device, apparatus, or component as claimed in claim 13 or claim 14 wherein to input a numeral; the key, button or input point that represents the numeral need to be pressed or used once or with the shift key, or using the cycle key, using a half-decimal numeral input method comprising the steps of:

- (a) accepting an input keystroke from the key, button or input point;**
- (b) if the input keystroke corresponds to a normal tap or use of one of the keys, buttons or input points assigned with a set of numerals, then:**
 - 1) display the first numeral matching or stored for the keystroke; and**
 - 2) continuing at step (a);**
- (c) if the input keystroke corresponds to a extended tap (e.g. press-and-hold) or prolonged use of one of the keys, button or input points assigned with a set of numerals, then:**
 - 1) mode change from numerals input mode to the previous text input mode;**
- (d) if the input keystroke corresponds to spacebar, then:**
 - 1) a space is displayed; and**
 - 2) continuing at step (a)**
- (e) if the input keystroke corresponds to backspace, then:**
 - 1) the previous numeral input keystroke or spacebar keystroke is undone; and**
 - 2) continuing at step (a)**
- (f) if the input keystroke corresponds to shift and the keystroke is held while inputting another keystroke, then:**
 - 1) if the other input keystroke corresponds to a normal tap or use of one of the keys, buttons or input points assigned with a set of numerals, then:**



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing
Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- a. display the second numeral matching or stored for the keystroke; and
 - b. continuing at step (a)
- 2) if the other input keystroke corresponds to spacebar, then:
- a. carriage return function is executed and the cursor on the display will proceed to the next line; and
 - b. continuing at step (a);
- 3) if the other input keystroke corresponds to cycling, then:
- a. display the first symbol, punctuation or object in the numerals input symbol database; and
 - b. continuing at step (a)
- (g) if the input keystroke corresponds to cycling, then:
- a. any previous inputted numeral or object is cycled to the next numeral or object stored in the same keystroke; and
 - b. continuing at step (a)
16. A device, apparatus, or component as claimed in claim 12 wherein to store new character, characters, word or plurality of objects into the word library database using the predictive non-intuitive text input method comprising the steps of:
- (a) inputting a character, characters, word or plurality of objects using the predictive non-intuitive text input method
 - (b) accepting the character, characters, word or plurality of objects by inputting a non textual object or auxiliary function like a symbol, punctuation, numeral, spacebar or carriage return, then:
 - 1) if the keystroke sequence corresponding to the character, characters, word or plurality of objects matches any keystroke sequence in the word library database and the word already exists in the word library database; then



Invention Title: Reduced Keyboard System that emulates QWERTY-type mapping and typing

Inventors: Ng Edwin; Ken Tan Chin Foo; Julian Oh Joo Seng

- a. continuing at step (a)
- 2) if the keystroke sequence corresponding to the character, characters, word or plurality of objects matches any keystroke sequence in the word library database and the word does not exist in the word library database; then
 - a. the accepted character, characters, word or plurality of objects is written, stored or recorded, at the front of the objects, in the word library database, for the same keystroke sequence; and
- b. continuing at step (a)
- 3) if the keystroke sequence corresponding to the character, characters, word or plurality of objects does not match any keystroke sequence in the word library database; then
 - a. the keystroke sequence corresponding to the character, characters, word or plurality of objects is written, stored or recorded into the word library database;
 - b. the accepted character, characters, word or plurality of objects is written, stored or recorded in the word library database, for the same keystroke sequence;
- c. continuing at step (a)

