

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 December 2001 (13.12.2001)

PCT

(10) International Publication Number
WO 01/95316 A2

(51) International Patent Classification⁷: **G11B 5/84**

(21) International Application Number: PCT/US01/17518

(22) International Filing Date: 31 May 2001 (31.05.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/208,886 2 June 2000 (02.06.2000) US

(71) Applicant: **SEAGATE TECHNOLOGY LLC** [US/US];
920 Disc Drive, Scotts Valley, CA 95066 (US).

(72) Inventor: **OLIM, Moshe**; 7210 Green Ridge Drive, Eden
Prairie, MN 55346 (US).

(74) Agents: **BOHN, David, C.** et al.; Westman, Champlin &
Kelly, P.A., Suite 1600 - International Centre, 900 Second
Avenue South, Minneapolis, MN 55402-3319 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL,
TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR CLEANING DISC DRIVE COMPONENTS



(57) **Abstract:** An apparatus (138, 200; 400) adapted to clean an exposed surface of a microstructure device (144, 304) such as a disc or head for a disc drive. The apparatus includes a fixture (187, 302) with a mounting surface adapted to receive the microstructure device. A cleaning fluid (140) covers the exposed surface. A slider bearing (146, 340) coupled to a resilient mount (154) flies over the exposed surface. A cleaning line (147, 308) on the exposed surface adjacent the slider bearing is subject to flow of the cleaning fluid. The flow can be generated by relative motion between the device and the slider bearing or generated by a nozzle (338).