

ABSTRACT

REFRIGERATOR

A refrigerator includes: a refrigerator body having a storage compartment in the refrigerator body, the storage compartment having an opening on a front side of the storage compartment; a drawer type door provided at the opening of the storage compartment, and configured to open and close the storage compartment; first support parts provided to left and right side walls of the storage compartment, and extending in a first direction being a depth direction of the refrigerator body; second support parts provided to the left and right side walls of the storage compartment, disposed above the first support parts, and extending in the first direction; a pair of left and right frames fixed to a back side of the door, extending in the first direction from the back side, and moving, with an opening and closing operation of the door, in the first direction in a state of being guided by the first support parts; a first accommodation container including a first accommodation container body with an open upper side and first flange portions, the first accommodation container body being disposed in the storage compartment, the first flange portions being provided to left and right side portions of the first accommodation container body, protruding outward in directions away from each other from the left and right side portions of the first accommodation container body, and moving, with the opening and closing operation of the door, in the first direction in a state of being supported by the pair of left and right frames; a second accommodation container including a second accommodation container body with an open upper side and second flange portions, the second accommodation container body being disposed in the storage compartment, the second flange portions being provided to left and right side portions of the second accommodation container body and protruding outward in directions away from each other from the left and right side portions of the second accommodation container body; and a third accommodation container including a third accommodation container body with an open upper side and third flange portions, the third accommodation container body being disposed in the storage

compartment, the third flange portions being provided to left and right side portions of the third accommodation container body and protruding outward in directions away from each other from the left and right side portions of the third accommodation container body, wherein when the second accommodation container is located above the first accommodation container in a state in which the first accommodation container is pulled out of the storage compartment, the second accommodation container is supported by the first accommodation container, when the second accommodation container is located in the storage compartment in the state in which the first accommodation container is pulled out of the storage compartment, the second flange portions are supported by the second support parts, and when the third accommodation container is located in the storage compartment in a state in which the first accommodation container and the second accommodation container are pulled out of the storage compartment, the third flange portions are supported by the second support parts.

Fig.5