

FRACTURING WITH TELESCOPING MEMBERS AND SEALING THE ANNULAR SPACE

Inventors: Bennett M. Richard and Yang Xu

FIELD OF THE INVENTION

[0001] The field of the invention is fracturing and more particularly a method for fracturing in open hole without external zone isolators and more particularly with an ability to seal the annulus without a traditional cementing job.

BACKGROUND OF THE INVENTION

[0002] There are two commonly used techniques to fracture in a completion method. FIG. 1 shows a borehole **10** that has a casing string **12** that is cemented **14** in the surrounding annulus **16**. This is normally done through a cementing shoe (not shown) at the lower end of the casing string **12**. In many cases if further drilling is contemplated, the shoe is milled out and further drilling progresses. After the string **12** is cemented and the cement **14** sets a perforating gun (not shown) is run in and fired to make perforations **18** that are then fractured with fluid delivered from the surface followed by installation and setting of packer or bridge plug **20** to isolate perforations **18**. After that the process is repeated where the gun perforates followed by fracturing and followed by setting yet another packer or bridge plug above the recently made and fractured perforations. In sequence, perforation and packer/bridge plug pairs **22, 24; 26, 28; 30, 32; and 34** are put in place in the well **10** working from the bottom **36** toward the well surface **38**.

[0003] A variation of this scheme is to eliminate the perforation by putting into the casing wall telescoping members that can be selectively extended through the cement before the cement sets to create passages into the formation and to bridge the cemented annulus. The use of extendable members to replace the perforation process is illustrated in USP 4,475,729. Once the members are extended, the annulus is cemented and the filtered passages are opened through the extending members so that in this particular case the well can be used in injection service. While the perforating is eliminated with the extendable members the cost of a cementing job plus rig time can be very high and in some locations the logistical complications of the well site can add to the cost.

[0004] More recently, external packers that swell in well fluids or that otherwise can be set such as **40**, **42**, **44**, **46**, and **48** in FIG. 2 can be set on the exterior of the string **49** to isolate zones **50**, **52**, **54**, and **56** where there is a valve, typically a sliding sleeve **58**, **60**, **62** and **64** in the respective zones. The string **49** is hung off the casing **66** and is capped at its lower end **67**. Using a variety of known devices for shifting the sleeves, they can be opened in any desired order so that the annular spaces **68**, **70**, **72** and **74** can be isolated between two packers so that pressurized frac fluid can be delivered into the annular space and still direct pressure into the surrounding formation. This method of fracturing involves proper packer placement when making up the string and delays to allow the packers to swell to isolate the zones. There are also potential uncertainties as to whether all the packers have attained a seal so that the developed pressure in the string is reliably going to the intended zone with the pressure delivered into the string **49** at the surface. Some examples of swelling packer are USP 7,441,596; 7,392,841 and 7,387,158.

[0005] In some instances the telescoping members have been combined with surrounding sleeves of a swelling material to better seal the extended ends of the telescoping members to the formation while still leaving open the remainder of the annular space to the formation in a given zone. Some examples of this design are USP 7,387,165 and USP 7,422,058. US Publication 2008/0121390 shows a spiral projection that can swell and/or be expanded into wellbore contact and leave passageways in between the projections for delivery of cement.

[0006] What is needed and provided by the method of the present invention is a technique to pinpoint the applied frac pressure to the desired formation while dispensing with expensive procedures such as cementing and annulus packers where the formation characteristics are such as that the hole will retain its integrity. The pressure in the string is delivered through extendable conduits that go into the formation. Given banks of conduits are coupled with an isolation device so that only the bank or banks in interest that are to be fractured at any given time are selectively open. The delivered pressure through the extended conduits goes right to the formation and

bypasses the annular space in between. Beyond that the string exterior can have a covering of a swelling material such as rubber or a shape memory polymer, either of which can fill the annular gap and replace the traditional and expensive cement job. Those and other features of the present invention will be more readily understood to those skilled in the art from a review of the description of the preferred embodiment and the associated FIGS. 3-10 while understanding that the full scope of the invention is determined by the literal and equivalent scope of the appended claims.

SUMMARY OF THE INVENTION

[0007] A fracturing operation is done in open hole. The annular space is spanned by telescoping members that are located behind isolation valves. A given bank of telescoping members can be uncovered and the telescoping members extended to span the annular space and engage the formation in a sealing manner. Pressurized fracturing fluid can be pumped through the telescoped passages and the portion of the desired formation fractured. In a proper formation, cementing is not needed to maintain wellbore integrity. The telescoping members can optionally have screens. Normally, the nature of the formation is such that gravel packing is also not required. A production string can be inserted into the string with the telescoping devices and the formation portions of interest can be produced through the selectively exposed telescoping members. In formations that need annular space isolation, the string in a preferred embodiment can have an external material that grows to seal the annular space in lieu of a traditional cementing operation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a prior art system of cementing a casing and sequentially perforating and setting internal packers or bridge plugs to isolate the zones as they are perforated and fractured;

[0009] FIG. 2 is another prior art system using external swelling packers in the annular space to isolate zones that are accessible with a sliding sleeve valve;

[0010] FIG. 3 shows the method of the present invention using extendable passages into the formation that are selectively accessed with a

valve so that the formation can be fractured directly from the string while bypassing the annular open hole space; and

[0011] FIG. 4 is a detailed view of a telescoping passage in the extended position;

[0012] FIGS. 5a and 5b show a telescoping member extended with a sliding sleeve and opened for formation access at the same time;

[0013] FIGS. 6a and 6b show a running string with extendable devices for extending the telescoping passages to the formation;

[0014] FIG. 7 is an embodiment showing the run in position of an assembly with sealing between the telescoping members that can seal the annulus in lieu of cementing;

[0015] FIG. 8 is the view of FIG. 7 with the annulus sealed;

[0016] FIG. 9 is the view of FIG. 8 with a telescoping passage extended; and

[0017] FIG. 10 is the view of FIG. 9 with all the telescoping passages extended.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0018] FIG. 3 illustrates one embodiment of the invention where the formation has the characteristics that make annular space isolation between the assemblies **108** optional. The preferred embodiment with annular space isolation is shown in FIGS. 7-10.

[0019] FIG. 3 illustrates an open hole **100** below a casing **102**. A liner **104** is hung off casing **102** using a liner hanger **106**. A fracturing assembly **108** is typical of the others illustrated in the FIG. 3 and those skilled in the art will appreciate that any number of assemblies **108** can be used which are for the most part similar but can be varied to accommodate actuation in a desired sequence as will be explained below. As shown in FIG. 4 each assembly **108** has a closure device that is preferably a sliding sleeve **110** that can be optionally operable with a ball **114** landing on a seat **112**. In one embodiment, the seats and balls that land on them are all different sizes and the sleeves can be closed in a bottom up sequence by first landing smaller balls on smaller seats that are on the lower assemblies **108** and progressively dropping larger balls that will land on different seats to close the valve **110**.

[0020] The array of telescoping members **116** selectively covered by a valve **110** can be in any number or array or size as needed in the application for the expected flow rates for fracturing or subsequent production. The telescoping assembly **116** is shown in the retracted position in FIG. 3 while telescoping members **116'** are shown in the same FIG. 3 in the extended position against the borehole wall **100**. In the preferred embodiment all the telescoping assemblies **116** are initially obstructed with a plug **118** so that internal pressure in the liner **104** will result in telescoping extension between or among members in each assembly, such as **120** and **122** or however many relatively moving segments are needed depending on the width of the annular gap that has to be crossed to get the leading ends **124** into the formation so that directed pressure will penetrate the formation and not go into the open annulus **126**. The plugs **118** are there to allow all the assemblies **116** to extend in response to the valves **110** at each assembly **116** being open and pressure applied inside the liner **104**. Once all the telescoping assemblies are extended, the plugs **118** in each can be removed. This can be done in many ways but one way is to use plugs that can disappear such as aluminum alloy plugs that will dissolve in an introduced fluid. Each or some of the assemblies can have a screen material **128** in the through passage that forms after extension and after removal of the plug **118**.

[0021] The valve **110** associated with each telescoping assembly **116** can also be operated with a sleeve shifter tool in any desired order. Each valve can have a unique profile that can be engaged by a shifting tool on the same or in separate trips to expedite the fracturing with one valve **110** and its associated telescoping array **116** ready for fracturing or more than one valve **110** and telescoping array **116**.

[0022] As another alternative for closing the valve **110** articulated ball seats can be used that accept a ball of a given diameter and allow the valve **110** to be operated and the ball to pass after moving the seat where such seat movement configures a another seat in another valve **110** to form to accept another object that has the same diameter as the first dropped object and yet operate a different valve **110**. Other techniques can be used to allow more than one valve to be operated in a single trip in the well. For example an articulated

shifting tool can be run in and actuated so that on the way out or into the well it can open or close one or more than one valve either based on unique engagement profiles at each valve, which is preferably a sliding sleeve or even with common shifting profiles using the known location of each valve and shifting tool actuation before reaching a specific valve that needs shifting.

[0023] Alternatively rupture discs set to break at different pressure ratings can be used to sequence which telescoping passages will open at a given pressure and in a particular sequence. However, once a rupture disc is broken to open flow through a bank of telescoping passages, those passages cannot be closed again when another set of discs are broken for access to another zone. With sliding sleeves all the available volume and pressure can be directed to a predetermined bank of passages but with rupture discs there is less versatility if particular zones are to be fractured in isolation.

[0024] The above method of the present invention allows fracturing in open hole with direction of the fracture fluid into the formation without the need for annular barriers and in a proper formation the fracturing can take place in open hole without cementing the liner. Such a technique in combination with valves at most or all of the telescoping assemblies allows the fracturing to pin done in the needed locations and in the desired order. After fracturing, some or all the valves can be closed to either shut in the whole well where fracturing took place or to selectively open one or more locations for production through the liner and into a production string (not shown). The resulting method described above saves the cost of cementing and the cost of annulus barriers and allows the entire process to the point of the fracturing job to be done in less time than the prior methods such as those described in FIGS. 1 and 2.

[0025] While telescoping assemblies are discussed as the preferred embodiment other designs are envisioned that can effectively span the gap of the surrounding annulus in a manner to engage the formation in a manner that facilitates pressure transmission and reduces pressure or fluid loss into the surrounding annulus. Those skilled in the art will appreciate that ~~this~~ the above described method is focused on well consolidated formations where hole collapse is not a significant issue. In other applications, described below, the

bottom hole assembly will also feature a swelling material or a shape memory polymer to fill the surrounding annular space **126** described above and left open in the above described embodiment.

[0026] One alternative to extending the assemblies **116** hydraulically is to do it mechanically. As shown as **130** in Figure 5, the telescoping units are retracted into the casing so as not to extend beyond its outside diameter **132** when installed. When sliding sleeve **134** shifts in FIG. 5b, such as when ball **138** lands on seat **140** the sliding sleeve **134** has a taper **136** which applies mechanical force onto the telescoping units **130** and extends them to touch the formation as shown as **131**. Although a sliding sleeve is preferred, any mechanical devices can be used to mechanically extend the telescoping units. One example, shown in FIGS. 6a and 6b, is to use a running string **142** with collapsible pushers **144** to push out the telescoping units as shown in FIGS. 6a and 6b. The pushers can be extended with internal pressure or by another means. In this case, a closure device is optional.

[0027] Another alternative to pushing out the assemblies **116** with pressure using telescoping components is to incorporate expansion of the liner **104** to get the assemblies to the surrounding formation. This can be with a combination of a telescoping assembly coupled with tubular expansion. The expansion of the liner can be with a swage whose progress drives out the assemblies that can be internal to the liner **104** during run in. Alternatively, the expansion can be done with pressure that not only expands the liner but also extends the assemblies **116**.

[0028] Optionally, the leading ends of the outermost telescoping segment **122** can be made hard and sharp such as with carbide or diamond inserts to assist in penetration into the formation as well as sealing against it. The leading end can be castellated or contain other patterns of points to aid in penetration into the formation.

[0029] FIG. 7 is identical to FIG. 3 but with one major difference. There are still a plurality of spaced apart fracturing assemblies **108** that have valves **110** telescoping assemblies **116**. In FIGS. 7-10 there are sealing members **200** that have a small dimension for run in as shown in FIG. 7 and that grow in the borehole **202** until they seal it off. The annular spaces **126**

shown in FIG. 7 are closed off in FIG. 8 as the sealing members get larger preferably by swelling. The sealing members **200** can swell in the presence of well fluids such as hydrocarbons when they are made of rubber, for example. They can also incorporate a cover that delays the swelling to allow time to get the assembly into position in the wellbore. These covers can be dissolved by well fluids for example. The sealing members **200** can also be formed from a shape memory polymer that in the presence of well fluids or heat artificially added with a heater or by inducing a chemical reaction that is exothermic, for example and all schematically represented by arrow **204**, will swell to seal the annular spaces **126**. In this manner a very expensive cement job can be avoided. In formations where it is beneficial to seal the annular space apart from the access locations to the formation from assemblies **108**, the use of the members **200** is an economical way to seal without the cost and logistical issues involved in a cementing job. This is an even more significant factor in offshore wells where the logistics of conducting a cementing job grow far more complex and therefore expensive.

[0030] FIG. 9 shows one set of the telescoping members **116** extended as the fracturing starts in the manner described above, while FIG. 10 illustrates all the telescoping assemblies **116** extended and the annular space **126** sealed by members **200** with breaks around the extended telescoping assemblies **116**.

[0031] The above description is illustrative of the preferred embodiment and many modifications may be made by those skilled in the art without departing from the invention whose scope is to be determined from the literal and equivalent scope of the claims below:

We claim:

1. A formation fracturing method, comprising:
running a completion string that comprises a plurality of wall passages into open hole;
spanning an annulus around said string with at least some of said passages that engage the formation while leaving said annulus substantially open to the formation;
delivering pressurized fluid through at least one of said passages to fracture the formation;
sealing said annulus before or after said delivering with at least one seal supported by said completion string when said seal on said completion string is run into said open hole.
2. The method of claim 1, comprising:
making said seal enlarge to a sealing position from delivery into said open hole.
3. The method of claim 1, comprising:
selectively closing access to at least one of said passages from within said string.
4. The method of claim 3, comprising:
using a valve member for said selectively closing access.
5. The method of claim 4, comprising:
providing a plurality of spaced sliding sleeves as said valve members for selectively opening or isolating a plurality of passages associated with each sliding sleeve.
6. The method of claim 5, comprising:
sequentially fracturing through a plurality of passages associated with at least two sliding sleeves, said sleeves selected to be sequentially open so that different groups of passages associated with different sliding sleeves can be used to fracture in any required order.
7. The method of claim 5, comprising:
keeping only one sliding sleeve open while delivering pressurized fluid to the passages associated with said open sliding sleeve.
8. The method of claim 7, comprising:
closing said open sliding sleeve and opening another sliding sleeve that is located uphole from the closed sliding sleeve;

sequentially closing and then opening sleeves in an uphole direction until pressurized fluid is delivered through all said passages.

9. The method of claim 7, comprising:
closing said open sliding sleeve and opening another sliding sleeve that is located downhole from the closed sliding sleeve;
sequentially closing and then opening sleeves in a downhole direction until pressurized fluid is delivered through all said passages.
10. The method of claim 7, comprising:
opening all said sliding sleeves and taking production through said passages.
11. The method of claim 5, comprising:
providing a sharp or hardened treatment on said leading end to facilitate said penetrating.
12. The method of claim 4, comprising:
lengthening or shifting said passages into contact with the formation using said valve member.
13. The method of claim 1, comprising:
lengthening or shifting said passages into contact with the formation.
14. The method of claim 13, comprising:
forming said passages from relative movable telescoping members.
15. The method of claim 14, comprising:
initially internally blocking said passages; building pressure in said blocked passages to relatively move said telescoping members.
16. The method of claim 15, comprising:
removing the blockage from said passages after extending them into formation contact.
17. The method of claim 16, comprising:
dissolving or removing the blockage using a fluid in the well.

18. The method of claim 13, comprising:
engaging said passages with an extendable member on a second string run into said completion string to extend or shift said passages to the formation.
19. The method of claim 1, comprising:
mechanically or hydraulically extending or shifting said passages into sealing contact with the formation.
20. The method of claim 1, comprising:
expanding said string to shorten the distance said passages have to span to contact the formation.
21. The method of claim 20, comprising:
using a swage to expand said string.
22. The method of claim 20, comprising:
extending or shifting said passages by expanding said string.
23. The method of claim 20, comprising:
extending or shifting said passages independently of expansion of said string.
24. The method of claim 23, comprising:
expanding said string after fully extending or shifting said passages.
25. The method of claim 1, comprising:
spanning said annulus with all of said passages by extending or shifting them at about the same time.
26. The method of claim 1, comprising:
placing a leading end of said passages in sealing contact with the formation.
27. The method of claim 26, comprising:
penetrating the formation with said leading end.
28. A formation fracturing method, comprising:
running a completion string that comprises a plurality of wall passages into open hole;

spanning an annulus around said string with at least some of said passages that engage the formation while leaving said annulus substantially open to the formation;

delivering pressurized fluid through at least one of said passages to fracture the formation;

sealing said annulus before or after said delivering with at least one seal supported by said completion string when it is run into said open hole;

making said seal enlarge to a sealing position from delivery into said open hole;

making said seal enlarge by exposure to well fluids in said open hole.

29. The method of claim 28, comprising:

using the temperature of well fluids or heat artificially added in said open hole to enlarge said seal.

30. A formation fracturing method, comprising:

running a completion string that comprises a plurality of wall passages into open hole;

spanning an annulus around said string with at least some of said passages that engage the formation while leaving said annulus substantially open to the formation;

delivering pressurized fluid through at least one of said passages to fracture the formation;

sealing said annulus before or after said delivering with at least one seal supported by said completion string when it is run into said open hole;

making said seal enlarge to a sealing position from delivery into said open hole; using rubber or a shape memory polymer for said seal.

31. A formation fracturing method, comprising:

running a completion string that comprises a plurality of wall passages into open hole;

spanning an annulus around said string with at least some of said passages that engage the formation while leaving said annulus substantially open to the formation;

delivering pressurized fluid through at least one of said passages to fracture the formation;

sealing said annulus before or after said delivering with at least one seal supported by said completion string when it is run into said open hole;

making said seal enlarge to a sealing position from delivery into said open hole;

using a plurality of spaced apart seals as said at least one seal where said spacing represents the location of said wall passages that engage the formation;

substantially sealing said annulus around said passages by swelling of said seals.