

DESCRIPTION

OPHTHALMIC LENS

5 Technical Field

[0001] The present invention relates to an ophthalmic lens.

Background Art

[0002] As the near-sighted population increases, so does the severely near-sighted
10 population. It is well known that severe near-sightedness can lead to blindness.
For this reason, an increase in severe near-sightedness is a serious social problem,
and there is widespread demand for a treatment method for suppressing the
progression of near-sightedness.

[0003] Several methods have been proposed to suppress the progression of near-
15 sightedness leading to severe near-sightedness. Examples of optical near-
sightedness progression suppressing methods include a method of using
ophthalmic lenses such as eyeglasses or contact lenses (soft contact lenses,
orthokeratology).

[0004] Patent Document 1 describes an eyeglass lens that exhibits an effect of
20 suppressing the progression of refractive error such as near-sightedness
(hereinafter also referred to as a near-sightedness progression suppressing effect)
by adding later-described monochromatic aberration. This eyeglass lens is also
referred to as a near-sightedness progression suppressing lens. Specifically, for
example, a spherical minute convex portion having a diameter of about 1 mm is
25 formed on the convex surface that is the object-side surface of the eyeglass lens.

[0005] A luminous flux, which is a bundle of light rays that are incident on the
eyeglass lens and pass through a pupil due to light rays passing through the
minute convex portions in the eyeglass lens described in Patent Document 1
(hereinafter, "luminous flux" is assumed to have the same meaning) is focused at a
30 plurality of positions on the overfocus side in the optical axis direction relative to a

predetermined position on the retina. This suppresses the progression of near-sightedness.

[0006] In the present specification, the overfocus side refers to the direction of approaching an object to be visually recognized in the optical axis direction using the retina as a reference, and the underfocus side refers to the opposite direction to the overfocus side, which is the direction away from the object to be visually recognized in the optical axis direction using the retina as a reference. If the optical power is excessively positive, the light is focused on the overfocus side, and if it is insufficient, the light is focused on the underfocus side.

[0007] On the other hand, Patent Document 2 describes longitudinal chromatic aberration in which light having a red wavelength is focused rearward of light having blue and green wavelengths ([0041] in Patent Document 2). Also, it is described that in animal testing, light having a red wavelength lengthens the eye axis and causes the progression of near-sightedness ([0008] and [0049] in Patent Document 2). It is described that, on the contrary, light having a blue wavelength has an effect of suppressing the progression of near-sightedness ([0054] in Patent Document 2).

[0008] Also, Patent Document 2 describes that light having blue and green wavelengths is used to suppress the progression of near-sightedness ([0035] in Patent Document 2). Specifically, it is described that an optical filter is provided on the eyeglass lens to form peaks of light intensity in a wavelength range of 460 to 490 nm and a wavelength range of about 490 to 550 nm, and to set the light intensity in the wavelength range of about 550 to 700 nm to 1% or less ([Claim 1], [Claim 5], [Claim 6], and [0032] of Patent Document 2).

[0009] Patent Document 3 discloses an ophthalmic lens system that controls longitudinal chromatic aberration so as to cause negative and/or inverted longitudinal chromatic aberration in the eye ([0002] in Patent Document 3). This ophthalmic lens system includes a first lens and a second lens ([0008] in Patent Document 3).

[0010] Patent Document 3 describes that a first lens and a second lens are

selected such that when light passes through an ophthalmic lens system having a positive or zero power, the light on the long wavelength side is focused at a position close to the ophthalmic lens system ([0008] in Patent Document 3).

[0011] Patent Document 3 describes that when light passes through an

5 ophthalmic lens system with a negative power, the first lens and the second lens are selected such that the light on the short wavelength side is focused at a position close to the ophthalmic lens system by making the absolute value larger than longitudinal chromatic aberration caused by the eye ([0008] in Patent Document 3).

10

Citation List

Patent Documents

[0012] Patent Document 1: US Patent Application Laid-Open Publication No. 2017/0131567

15 Patent Document 2: WO 2012/044256 Pamphlet

Patent Document 3: WO 2018/152596 Pamphlet

Summary of Invention

Technical Problem

20 [0013] The method described in Patent Document 2 relates to wavelength filtering. On the other hand, no consideration has been given to longitudinal chromatic aberration caused by the eyeglass lens itself. Longitudinal chromatic aberration depends on the prescription power. With the method described in Patent Document 2, there is a risk that no matter how much a wavelength is
25 filtered, the near-sightedness progression suppressing effect cannot be exhibited unless the longitudinal chromatic aberration of the eyeglass lens itself is appropriately generated.

[0014] The method described in Patent Document 3 is that the first lens and the second lens constituting the ophthalmic lens system cause longitudinal chromatic
30 aberration that changes the focus position of light of each wavelength. On the

other hand, in the method described in Patent Document 3, the focus position of
aluminous flux having a wavelength on the short wavelength side in the bundle of
visible light rays that pass through the ophthalmic lens system and pass through
the pupil moves to the overfocus side. At the same time, the focus position of a
5 luminous flux having a wavelength on the long wavelength side moves to the
underfocus side.

[0015] That is, the method described in Patent Document 3 can increase the near-
sightedness progression suppressing effect and at the same time increase the
factors that inhibit the near-sightedness progression suppressing effect (e.g.,
10 FIGURE 63 of Patent Document 3).

[0016] One embodiment of the present invention aims to reduce the number of
factors that inhibit an effect of suppressing the progression of near-sightedness or
far-sightedness (hereinafter collectively referred to as a refractive error in the
present specification), while exhibiting the suppressing effect due to longitudinal
15 chromatic aberration.

Solution to Problem

[0017] The inventors of the present invention have focused on an ophthalmic lens
constituted by a plurality of lenses as described in Patent Document 3. Then, they
20 focused on an apochromat, which is used in microscopes and the like that are
similarly constituted by multiple lenses.

[0018] An achromat, which is the predecessor of the apochromat, indicates C-d-F
correction in which axial chromatic aberration for the C'-line (wavelength 644 nm),
which is red wavelength light, and the F'-line (wavelength 480 nm), which is blue
25 wavelength light, are corrected, and spherical aberration and coma aberration are
minimized at the d-line (wavelength 588 nm), which is yellow wavelength light.
This correction is also called "achromatization" and is a linear functional chromatic
aberration correction.

[0019] Since an achromat corrects chromatic aberration only for light of two types
30 of wavelength, chromatic aberration remains overall. This residual chromatic

aberration is called a secondary spectrum.

[0020] Apochromat refers to correcting chromatic aberration of light of a wavelength of another color in addition to the red and blue wavelengths. Also, apochromat refers to reducing the above-described secondary spectrum. This correction is also called “superachromatization” and is a quadratic functional chromatic aberration correction.

[0021] Usually, in a microscope or the like, an apochromat aims to remove chromatic aberration. On the other hand, the inventors of the present invention have found that the technique of apochromat is applied to an ophthalmic lens according to one aspect of the present invention so as to increase chromatic aberration instead of removing it. Specifically, the inventors of the present invention have come up with a method of defining a partial dispersion ratio relationship that is different from that of the conventional apochromat between the g-line and the F'-line between the above-described plurality of lenses.

[0022] A first aspect of the present invention is

an ophthalmic lens including two lens elements 1 and 2 having powers with different signs,

in which when an Abbe number (e-line reference) of the lens element 1 having a power with a smaller absolute value is v_{e1} , and an Abbe number (e-line reference) of the other lens element 2 is v_{e2} , Formula 1 below is satisfied, and

$$v_{e1} < v_{e2} \quad \dots (\text{Formula 1})$$

when a partial dispersion ratio $P_{gF'1}$ between a g-line and an F'-line in the lens element 1 having the power with the smaller absolute value, and a partial dispersion ratio $P_{gF'2}$ between a g-line and an F'-line in the other lens element 2 are set, Formula 2 below is satisfied.

$$P_{gF'1} > P_{gF'2} \quad \dots (\text{Formula 2}).$$

[0023] A second aspect of the present invention is the aspect described in the first aspect,

in which when the absolute value of the power of the lens element 1 is D1 and the absolute value of the power of the lens element 2 is D2, Formula 3 below is

satisfied.

$$(D1/v_{e1}) < (D2/v_{e2}) \quad \dots (\text{Formula 3})$$

[0024] A third aspect of the present invention is the aspect described in the first or second aspect,

5 in which when the absolute value of the power of the lens element 1 is D1 and the absolute value of the power of the lens element 2 is D2, Formula 4 below is satisfied.

$$\{D1 \times (1 + 3 \times P_{gF1}) / v_{e1}\} > \{D2 \times (1 + 3 \times P_{gF2}) / v_{e2}\} \quad \dots (\text{Formula 4})$$

[0025] A fourth aspect of the present invention is the aspect described in any one
10 of the first to third aspects,

 in which the power of the lens element 1 is positive, and the power of the lens element 2 is negative.

[0026] A fifth aspect of the present invention is the aspect described in any one of the first to third aspects,

15 in which the power of the lens element 1 is negative, and the power of the lens element 2 is positive.

[0027] A sixth aspect of the present invention is the aspect according to any one of the first to fifth aspects, including:

20 a first refractive region having a first refractive power obtained based on a prescription for correcting refractive error of an eye; and

 a plurality of second refractive regions that have a refractive power different from the first refractive power, and have a function of focusing on a position outside of a retina of the eye so as to suppress progression of the refractive error of the eye,

25 in which the second refractive regions are formed as respective independent regions near a central portion of the ophthalmic lens, and

 the first refractive region is formed outside of the regions in which the second refractive regions are formed.

[0028] A seventh aspect of the present invention is the aspect according to any
30 one of the first to sixth aspects,

in which the ophthalmic lens is an eyeglass lens.

[0029] Another aspect of the present invention is as follows.

The power of the lens element 1 is positive, the power of the lens element 2 is negative, the prescription power of the ophthalmic lens is negative, and the ophthalmic lens is a minus lens.

[0030] Another aspect of the present invention is as follows.

The power of the lens element 1 is negative, the power of the lens element 2 is positive, the prescription power of the ophthalmic lens is positive, and the ophthalmic lens is a plus lens.

[0031] Another aspect of the present invention is as follows.

“An ophthalmic lens including two lens elements having powers with different signs,

in which, for light with a wavelength on the long wavelength side in visible light, longitudinal chromatic aberration is set to near zero, and

for light with a wavelength on the short wavelength side in visible light, longitudinal chromatic aberration is increased (due to a secondary spectrum), and the power is higher than the prescribed power.”

Near zero refers to a state in which the absolute value of the power difference per 80 nm of the wavelength range is 0.01 D or less. This is a localization of the state in which the absolute value of the power difference in the wavelength range from the g-line to the C'-line is 0.02 D or less when the e-line is used as a reference.

[0032] Another aspect of the present invention is as follows.

Ophthalmic lenses exclude intraocular lenses (so-called IOLs). An ophthalmic lens is also referred to as a lens worn on the outside of the eyeball.

Advantageous Effects of Invention

[0033] According to one working example of the present invention, it is possible to reduce the number of factors that hinder the refractive error progression suppressing effect while exhibiting the suppressing effect due to longitudinal

chromatic aberration.

Brief Description of Drawings

[0034] FIG. 1(a) is a schematic side cross-sectional view of a minus lens according
5 to Comparative Example 1. FIG. 1(b) is a schematic side cross-sectional view of the
minus lens for suppressing the progression of near-sightedness according to
Working Examples 1 and 2.

FIG. 2 is a schematic side cross-sectional view of an eyeglass lens including
a first refractive region and a second refractive region described in Patent
10 Document 1 according to a modified example, and the inside of the balloon is an
enlarged view.

FIG. 3 is a schematic side cross-sectional view of a plus lens for
suppressing far-sightedness progression according to a modified example.

FIG. 4 is a plot showing changes in the power of the eyeglass lens due to
15 light of each wavelength in Comparative Example 1 and Working Examples 1 and
2 when the horizontal axis is the wavelength [nm] and the vertical axis is the
power [D]. Note that a plot showing the critical significance of the preferred
example is also shown in the drawing.

20 Description of Embodiments

[0035] Hereinafter, one aspect of the present invention will be described. The
following description is exemplary and the invention is not limited to the
illustrated embodiments. Note that in this specification, “to” indicates being a
predetermined numerical value or more and a predetermined numerical value or
25 less.

[0036] Also, the wavelengths of the C'-line, F'-line, and the like stated below are
Fraunhofer line wavelengths, and although the wavelength values are rounded
after the decimal point, it is possible to refer to the Fraunhofer line wavelengths
when accurate values are to be used.

30 [0037] [Ophthalmic lens according to one aspect of the present invention]

The ophthalmic lens according to one aspect of the present invention is a refractive error progression suppressing lens. The specific configuration is as follows.

“An ophthalmic lens including two lens elements 1 and 2 having powers
5 with different signs,

in which when an Abbe number (e-line reference) of the lens element 1 having a power with a smaller absolute value is v_{e1} , and an Abbe number (e-line reference) of the other lens element 2 is v_{e2} , Formula 1 below is satisfied, and

$$v_{e1} < v_{e2} \quad \dots (\text{Formula 1})$$

10 when a partial dispersion ratio P_{gF1} between a g-line and an F'-line in the lens element 1 having the power with the smaller absolute value, and a partial dispersion ratio P_{gF2} between a g-line and an F'-line in the other lens element 2 are set, Formula 2 below is satisfied.

$$P_{gF1} > P_{gF2} \quad \dots (\text{Formula 2})$$

15 [0038] There is no particular limitation on the mode of the “ophthalmic lens” as long as it functions as a near-sightedness progression suppressing lens. Eyeglass lenses or contact lenses (i.e., lenses worn outside the eyeball) are examples of ophthalmic lenses. Although the ophthalmic lens described in the present specification may include an intraocular lens (a so-called IOL), the intraocular lens
20 may be excluded from the ophthalmic lens. In one aspect of the present invention, an eyeglass lens is illustrated as an example.

[0039] The eyeglass lens has an object-side surface and an eyeball-side surface.

The “object-side surface” is a surface located on the object side when eyeglasses including the eyeglass lens are worn by the wearer, and is a so-called outer

25 surface. The “eyeball-side surface” is the opposite, that is, the surface located on the eyeball side when the eyeglasses including the eyeglass lens are worn by the wearer, and is the so-called inner surface. In one aspect of the present invention, the object-side surface is a convex surface, and the eyeball-side surface is a concave surface. That is, the eyeglass lens in one aspect of the present invention is a

30 meniscus lens.

[0040] The “object-side surface side” includes, for example, the outermost surface of the object-side surface of the eyeglass lens, includes the object-side surface of the lens base material that is the base of the eyeglass lens, and includes the object-side surface of the hard coat layer or the like provided on the lens base material. The same applies to the “eyeball-side surface side”.

[0041] The “power” of lens elements 1 and 2 refers to the refractive power when light passes through each lens element. Since the lens elements 1 and 2 are merely constituent parts of the eyeglass lens, the powers of the lens elements 1 and 2 are different from the prescription power of the eyeglass lens itself.

[0042] As the name implies, “visible light” is light that is visible to humans, and is defined in the present specification as light having a wavelength in the range of 360 to 830 nm based on JIS Z 8120 optical terminology.

[0043] The “short wavelength side” refers to the short wavelength side of the wavelength range of visible light, refers to less than half the value of the above-described wavelength range, and is less than 595 nm in the above-described wavelength range. The short wavelength side is also referred to as the blue light side.

[0044] The “long wavelength side” refers to the long wavelength side of the wavelength range of visible light, refers to half or more of the value of the above-described wavelength range, and is 595 nm or more in the above-described wavelength range. The long wavelength side is also called the red light side.

[0045] The eyeglass lens according to one aspect of the present invention includes two lens elements 1 and 2 having powers with different signs. Also, the powers of the lens elements 1 and 2 have mutually different absolute values. As shown in FIGURE 15 of Patent Document 3 and FIG. 1(b) of the present application according to one working example of the present invention, the power of one lens element is positive and the power of the other lens element is negative. Also, in the eyeglass lens according to one aspect of the present invention, the lens elements 1 and 2 are joined to each other.

[0046] There is no particular limitation on the “lens element” as long as positive

or negative power can be realized with a combination of the object-side surface and the eyeball-side surface and the refractive index. There is also no particular limitation on the material of the lens element, and the material used as the lens base material may also be used thereas. Also, in the upper paragraph, an example
 5 in which the lens elements 1 and 2 are joined was given, but the present invention is not limited thereto. For example, the lens elements 1 and 2 may also be arranged via an interlayer film. In that case, the ophthalmic lens may be manufactured in accordance with the content described in Japanese Patent Application Laid-Open Publication No. 2013-160994.

[0047] Note that if the interlayer film is extremely thin, the interlayer film has the approximate interface shape of the lens elements 1 and 2. In that case, the object-side surface and the eyeball-side surface of the interlayer film are almost the same, and positive or negative power is not realized. In terms of numeric values, whether the power provided by the interlayer film is zero or not, the
 15 absolute value of the power is at most 0.12 D. In this case, the interlayer film is not included in the lens element.

[0048] In one aspect of the present invention, a case where the lens elements 1 and 2 are joined is illustrated as an example, but one of the lens elements 1 and 2 may also be in the form of a layer. For example, if the lens element 2 is a lens base
 20 material, the lens element 1 may also be a film laminated on the lens base material.

[0049] In the eyeglass lens according to one aspect of the present invention, when the Abbe number (e-line reference) of the lens element 1 having a power with a smaller absolute value is v_{e1} , and the Abbe number (e-line reference) of the other
 25 lens element 2 is v_{e2} , the following Formula 1 is satisfied. The e-line has a wavelength of 546 nm.

$$v_{e1} < v_{e2} \quad \dots (\text{Formula 1})$$

[0050] Then, when a partial dispersion ratio $P_{gF'1}$ between the g-line and the F'-line in the lens element 1 having the power with the smaller absolute value, and a
 30 partial dispersion ratio $P_{gF'2}$ between the g-line (wavelength 436 nm) and the F'-

line (wavelength 480 nm) in the other lens element 2 are set, the following Formula 2 is satisfied.

$$P_{gF^1} > P_{gF^2} \quad \dots (\text{Formula 2})$$

[0051] The partial dispersion ratio is a value obtained by dividing the partial

5 dispersion by the main dispersion, and in the present specification, a value obtained by subtracting the refractive index n_C at the C'-line (wavelength 644 nm) from the refractive index n_F at the F'-line (wavelength 480 nm) is used as the main dispersion. When n_g is the refractive index at the g-line (wavelength 436 nm) and n_F is the refractive index at the F'-line (wavelength 480 nm), P_{gF} is expressed by
10 the following formula.

$$P_{gF} = (n_g - n_F) / (n_F - n_C) \quad \dots (\text{Formula 3})$$

That is, P_{gF^1} represents the partial dispersion ratio between the g-line and the F'-line in the lens element 1, and P_{gF^2} represents the partial dispersion ratio between the g-line and the F'-line in the lens element 2.

15 [0052] By combining the above-described lens elements 1, 2, Formula 1, and Formula 2, as shown in the plots of Working Examples 1 and 2 shown in later-described FIG. 4, the focus position of a luminous flux with a wavelength on the short wavelength side among a bundle of visible light rays that pass through the eyeglass lens and pass through the pupil moves significantly to the overfocus side
20 compared to Comparative Example 1 (single lens made of crown glass). On the other hand, the focus position of aluminous flux with a wavelength on the long wavelength side does not change much compared to Comparative Example 1 (single lens made of crown glass) and approaches the retina.

[0053] That is, in the case of the eyeglass lens according to one aspect of the
25 present invention, when the refractive error progression suppressing effect is exhibited due to longitudinal chromatic aberration, the number of factors that hinder the suppressing effect is reduced. Furthermore, since the number of factors that hinder the suppressing effect in the longitudinal chromatic aberration itself is reduced, it is not necessary to provide filtering (a so-called wavelength filter) as
30 described in Patent Document 2. As a result, it is also not necessary to

significantly reduce the luminous flux with a wavelength on the short wavelength side, and it is possible to suppress a decrease in resolution.

[0054] [Details of eyeglass lens according to one aspect of the present invention]

Hereinafter, further specific examples, preferred examples, and modified
5 examples of one aspect of the present invention will be described.

[0055] The type of the eyeglass lens according to one aspect of the present invention is not particularly limited, and examples thereof include a single focus lens. The eyeglass lens according to one aspect of the present invention is a single focus lens corresponding to an object distance of an intermediate distance (1 m to
10 40 cm) or a near distance (40 cm to 10 cm). Of course, the technical idea of the present invention can be applied even to a single focus lens corresponding to an infinite distance, but as one aspect of the present invention, a single focus lens corresponding to a medium-near distance will be illustrated as an example.

[0056] Note that the eyeglass lens according to one aspect of the present invention
15 may also be a bifocal lens having two focal points or a trifocal lens having three focal points. Also, the eyeglass lens may be a progressive refractive power lens including a near portion corresponding to a near distance, a far portion corresponding to a distance farther than the near distance, and an intermediate portion having a progressive action connecting the near portion and the far
20 portion.

[0057] It is preferable that when the absolute value of the power of the lens element 1 is D1 and the absolute value of the power of the lens element 2 is D2, Formula 3 below is satisfied.

$$(D1/v_{e1}) < (D2/v_{e2}) \quad \dots (\text{Formula 3})$$

25 [0058] By satisfying Formula 3, chromatic aberration on the retina of the luminous flux with a wavelength “other than” the wavelength on the short wavelength side among the bundle of visible light rays that pass through the eyeglass lens and pass through the pupil is reduced compared to when the eye is naked.

30 [0059] It is preferable that when the absolute value of the power of the lens

element 1 is D1 and the absolute value of the power of the lens element 2 is D2, Formula 4 below is satisfied.

$$\{D1 \times (1 + 3 \times P_{gF1}) / v_{e1}\} > \{D2 \times (1 + 3 \times P_{gF2}) / v_{e2}\} \quad \dots (\text{Formula 4})$$

[0060] By satisfying Formula 4, chromatic aberration of blue light having a wavelength of 453 nm (defocusing of the e-line, i.e., light with a wavelength of 546 nm) is increased compared to when the eye is naked. The wavelength of 453 nm is a wavelength at which the sensitivity of S-cone cells exceeds the sensitivity of other cone cells and rod cells, and thereby light on the shorter wavelength side is more likely to be strongly perceived as blue light by the S-cone cells. Accordingly, it is preferable to give an action of focusing light in front of the retina at a short wavelength of 453 nm or less.

[0061] The derivation process of Formula 4 above will be described.

First, Formula 4 relates to the secondary spectrum mentioned in [Solution to the Problem]. That is, Formula 4 is a specific example for increasing longitudinal chromatic aberration, which is the exact opposite of superachromatization such as apochromat, and focusing the light in front of the retina on the short wavelength side (g-line to F'-line).

[0062] The plot of chromatic aberration ΔD , which is a secondary spectrum, is a quadratic function with respect to the reciprocal of the wavelength (set as K). The quadratic function is set as $\Delta D = aK^2 + bK + c$. In addition, the following formula is set.

- Condition that provides positive chromatic aberration with blue light (defocusing with respect to the e-line)

$$\{a(1/453)^2 + b(1/453) + c\} - \{a(1/546)^2 + b(1/546) + c\} > 0 \quad \dots (\text{Formula 5})$$

- Relational expression of chromatic aberration of F'-line and C'-line (primary chromatic aberration)

$$\{a(1/480)^2 + b(1/480) + c\} - \{a(1/644)^2 + b(1/644) + c\} > \{(D1/v_{e1}) - (D2/v_{e2})\} \quad \dots (\text{Formula 6})$$

- Relational expression of chromatic aberration (secondary spectrum) of g-line and F'-line

$$\{a(1/453)^2+b(1/453)^2+c\}-\{a(1/480)^2+b(1/480)^2+c\}>\{(D1/v_{e1})\times P_{gF1}-$$

$$(D2/v_{e2})\times P_{gF2}\} \quad \dots(\text{Formula 7})$$

[0063] When Formula 6 and Formula 7 are substituted into Formula 5, Formula 8 below is obtained.

$$5 \quad \{(D1/v_{e1})-(D2/v_{e2})\}+3.01\times\{(D1/v_{e1})\times P_{gF1}\}-\{(D2/v_{e2})\times P_{gF2}\}>0 \quad \dots(\text{Formula 8})$$

[0064] The above-described Formula 4 is obtained by rounding down the decimals in Formula 8.

$$\{D1\times(1+3\times P_{gF1})/v_{e1}\}>\{D2\times(1+3\times P_{gF2})/v_{e2}\} \quad \dots(\text{Formula 4})$$

[0065] If the power of the lens element 1 is positive and the power of the lens
 10 element 2 is negative, the near-sightedness progression suppressing effect can be obtained. In this case, preferably, the prescription power of the ophthalmic lens is negative, and the ophthalmic lens is a minus lens. This is because people who need the near-sightedness progression suppressing effect are often already near-sighted, and a minus lens can correct this near-sightedness.

15 [0066] Incidentally, the prescription data of the wearer information is written on a lens bag (a specification sheet in the case of contact lenses). That is, if there is a lens bag, it is possible to specify the lens as an ophthalmic lens based on the prescription data of the wearer information. Also, an ophthalmic lens is usually in a set with a lens bag or a specification sheet. For this reason, the technical idea of
 20 the present invention is reflected in an ophthalmic lens to which a lens bag or a specification sheet is attached, and the same applies to a set of a lens bag and an ophthalmic lens.

[0067] If the power of the lens element 1 is negative and the power of the lens
 25 element 2 is positive, a far-sightedness progression suppressing effect can be obtained. In this case, preferably, the prescription power of the ophthalmic lens is positive, and the ophthalmic lens is a plus lens. This is because people who need the far-sightedness progression suppressing effect are often already far-sighted, and a plus lens can correct this far-sightedness. The far-sightedness progression suppressing effect will be described in [Modified Examples].

30 [0068] Hereinafter, a further specific configuration of the eyeglass lens according

to one aspect of the present invention will be described.

[0069] The eyeglass lens is constituted by including a lens base material, a wavelength filter formed on the convex side of the lens base material, a hard coat film formed on each of the convex side and the concave side of the lens base material, and an antireflection film (AR film) formed on the surface of each hard coat film. Note that in addition to the hard coat film and the antireflection film, other films may further be formed on the eyeglass lens.

[0070] (Lens base material)

The lens base material is made of, for example, a thermosetting resin material such as polycarbonate, CR-39, thiourethane, allyl, acrylic, or epithio. Among these, polycarbonate is preferable. Note that another resin material according to which a desired refractive index is obtained may also be selected as the resin material constituting the lens base material. Also, a lens base material made of inorganic glass may be used instead of the resin material. In one aspect of the present invention, a case is mainly illustrated in which sawtooth-shaped portions are provided on the eyeball-side surface of the lens base material, and the sawtooth-shaped portions are arranged in a plurality of concentric ring shapes centered about the lens center (geometric center or optical center) of the eyeglass lens.

[0071] (Hard coat film)

The hard coat film is formed using, for example, a thermoplastic resin or a UV curable resin. The hard coat film can be formed using a method of immersing the lens base material in a hard coat liquid, spin-coating, or the like. By performing coating with such a hard coat film, the durability of the eyeglass lens can be improved.

[0072] (Anti-reflection film)

The anti-reflection film is formed by, for example, forming a film of an anti-reflection agent such as ZrO_2 , MgF_2 , or Al_2O_3 through vacuum deposition. Due to the coating of such an anti-reflection film, the visibility of an image through the eyeglass lens can be improved. Note that by controlling the material and film

thickness of the anti-reflection film, it is possible to control the spectral transmittance, and it is also possible to give the anti-reflection film a function of a wavelength filter.

[0073] [Modified Examples]

5 Although one aspect of the present invention has been described above, the above-described contents of the disclosure indicate an exemplary aspect of the present invention. That is, the technical scope of the present invention is not limited to the above-described exemplary aspect, and can be modified in various ways without departing from the gist thereof.

10 [0074] Due to the effect provided by one aspect of the present invention, the number of factors that hinder the refractive error progression suppressing effect is reduced. For this reason, it is not necessary to provide the filtering (a so-called wavelength filter) as described in Patent Document 2, which is preferable. On the other hand, there is no reason to exclude the provision of the wavelength filter
15 from the technical idea of the present invention.

[0075] The ophthalmic lens according to one aspect of the invention is not limited to being constituted by only the lens elements 1 and 2. Other lens elements may also be combined as long as the effect that one aspect of the present invention is to provide can be exhibited.

20 [0076] As described in Patent Document 1, the technical idea of the present invention can be applied to an eyeglass lens, and further to an ophthalmic lens, in which a plurality of minute convex portions are formed. Specifically, the ophthalmic lens according to one aspect of the present invention further includes the following configurations.

25 [0077] “A first refractive region having a first refractive power obtained based on a prescription for correcting refractive error of an eye; and

 a plurality of second refractive regions that have a refractive power different from the first refractive power, and have a function of focusing on a position outside of a retina of the eye so as to suppress progression of the refractive
30 error of the eye are included,

in which the second refractive regions are formed as respective independent regions near a central portion of the ophthalmic lens, and

the first refractive region is formed outside of the regions in which the second refractive regions are formed.”

5 [0078] FIG. 2 is a schematic side cross-sectional view of an eyeglass lens including a first refractive region and a second refractive region described in Patent Document 1 according to a modified example, and the inside of the balloon is an enlarged view.

[0079] FIG. 2(a) shows a state in which a film in which minute convex portions
10 (second refractive regions) described in Patent Document 1 are formed is laminated on the object-side surface of the lens element 2, which is a lens base material and has a positive power. Although the eyeglass lens as a whole is a plus lens, it has a near-sightedness progression suppressing effect since the defocus power due to the minute convex portions is exhibited.

15 [0080] FIG. 2(b) shows a state in which minute convex portions are formed on the object-side surface of the lens element 2, which is a lens base material and has a negative power. Then, a state is shown in which a film is laminated so as to embed the minute convex portions on the object-side surface so that the influence of the minute convex portions does not appear on the outermost surface of the eyeglass
20 lens.

[0081] In this state, the outermost surface of the eyeglass lens is smooth. Even if the outermost surface is smooth, the near-sightedness progression suppressing effect can be obtained as long as the shapes of the convex portions and concave portions at the interface portion inside of the eyeglass lens and the difference in
25 the refractive index of the two types of surface base materials that sandwich the interface portion are set appropriately.

[0082] Note that, as shown in the enlarged view in FIG. 2(b), the portion of the film corresponding to the minute convex portion (second refractive region) has a shape and a thickness that provide a negative power. That is, the lens element in
30 the present specification need only have a positive or negative power at at least a

portion thereof.

[0083] FIG. 2(c) shows a state in which minute convex portions are formed on the object-side surface of the lens element 2, which is a lens base material and has a negative power. Also, a state is shown in which a film (lens element 1) is laminated on the object-side surface so that the influence of the minute convex portion appears on the outermost surface of the eyeglass lens. Note that, as shown in the enlarged view in FIG. 2(c), the portion of the film corresponding to the minute convex portions (second refractive region) has a shape and a thickness that provide a negative power.

[0084] Since the convex regions, which are the minute convex portions, follow the convex regions of the lens base material, similarly to those convex regions, the convex regions are arranged in island shapes at equal intervals in a circumferential direction and an axial direction around the lens center, that is, in a state of being aligned regularly near the lens center.

[0085] Each convex region is configured as follows, for example. The diameter of the convex region is preferably about 0.8 to 2.0 mm. The protruding height (protruding amount) of the convex region is preferably about 0.1 to 10 μm , and preferably about 0.7 to 0.9 μm . The radius of curvature of the convex region is preferably a spherical shape that is 50 to 250 mmR, and preferably about 86 mmR. With such a configuration, it is preferable that the refractive power of the convex region is set to be about 2.00 to 5.00 diopters greater than the refractive power of the region where the convex region is not formed.

[0086] The other contents relating to the first refractive region and the second refractive region described in Patent Document 1 refer to all of the contents described in Patent Document 1, and thus the description is omitted here.

[0087] FIG. 3 is a schematic side cross-sectional view of a plus lens for suppressing the progression of far-sightedness according to a modified example.

[0088] The technical idea of the eyeglass lens of one aspect of the present invention can also be applied to an eyeglass lens having a far-sightedness progression suppressing function. Specifically, longitudinal chromatic aberration is

provided so as to have the effect of converging the luminous flux at a position B', which is farther from the object side than a position A on the retina (that is, on the underfocus side behind the position A) in the forward direction of light travel.

That is, contrary to the above-described one aspect of the present invention, the

5 focus position of the luminous flux having a wavelength on the long wavelength side among the bundle of visible light rays that pass through the eyeglass lens and pass through the pupil is moved to the underfocus side by the secondary spectrum. This can be achieved when the power of the lens element 1 is negative and the power of the lens element 2 is positive. Preferably, the prescription power of the
10 ophthalmic lens is positive. Also, when the content of Patent Document 1 is applied and the far-sightedness progression suppressing function is to be provided, "convex" may be read as "concave".

[0089] It is also possible to summarize one aspect of the present invention as follows.

15 "An ophthalmic lens including two lens elements having powers with different signs,

in which, for light with a wavelength on the long wavelength side in visible light, longitudinal chromatic aberration is set to near zero, and

for light with a wavelength on the short wavelength side in visible light,
20 longitudinal chromatic aberration is increased (due to a secondary spectrum), and the power is higher than the prescribed power."

Near zero refers to a state in which the absolute value of the power difference per 80 nm of the wavelength range is 0.01 D or less. This is a localization of the state in which the absolute value of the power difference in the
25 wavelength range from the g-line to the C'-line is 0.02 D or less when the e-line is used as a reference.

[Working Examples]

[0090] Next, working examples will be shown, and the present invention will be specifically described. Of course, the present invention is not limited to the
30 following working examples.

[0091] <Comparative Example 1>

FIG. 1(a) is a schematic side cross-sectional view of the minus lens according to Comparative Example 1.

[0092] An eyeglass lens with a prescription power, that is, a spherical power S , of
 5 -4.0 D and an astigmatic power of zero was designed. That is, this eyeglass lens is a single focus minus lens. Also, this eyeglass lens is the lens base material itself, and no film such as a hard coat layer is formed thereon. The lens base material is crown glass, and its refractive index (e-line reference) is 1.525. Also, the Abbe number (e-line reference) was 58.62, and the partial dispersion ratio between the
 10 g-line and the F'-line was 0.541.

[0093] FIG. 4 is a plot showing changes in the power of the eyeglass lens due to each wavelength light in Comparative Example 1 and Working Examples 1 and 2 when the horizontal axis is the wavelength [nm] and the vertical axis is the power [D]. Note that a plot showing the critical significance of the preferred example is
 15 also shown in the drawing.

[0094] Note that in Comparative Example 1 and Working Examples 1 and 2 described later (and furthermore, a plot of the critical significance of a preferred example), the plot was set such that the power of the eyeglass lens when the e-line (wavelength 546 nm) passes therethrough is -4.0 D. This is called an e-line
 20 reference.

[0095] <Working Example 1>

FIG. 1(b) is a schematic side cross-sectional view of the minus lens for suppressing the progression of near-sightedness according to Working Examples 1 and 2.

25 [0096] Working Examples 1 and 2 are eyeglass lenses for suppressing the progression of near-sightedness. The lens elements 1 and 2 according to Working Example 1 were set as follows. n_{e1} is the refractive index of the lens element 1 with reference to the e-line, and n_{e2} is the refractive index of the lens element 2 with reference to the e-line.

30 Lens element 1: Power is positive

n_{e1} : 2.0009

v_{e1} : 16.72

P_{gF1} : 0.666

D1: 4.1 [D]

5 Lens element 2: Power is negative

n_{e2} : 1.8656

v_{e2} : 30.23

P_{gF2} : 0.598

D2: -8.1 [D]

10 [0097] <Working Example 2>

The lens elements 1 and 2 according to Working Example 2 were set as follows. Note that Working Example 2 is a preferable example that satisfies Formula 4 above.

Lens element 1: Power is positive

15 n_{e1} : 2.0009

v_{e1} : 16.72

P_{gF1} : 0.666

D1: 4.8 [D]

Lens element 2: Power is negative

20 n_{e2} : 1.8656

v_{e2} : 30.23

P_{gF2} : 0.598

D2: -8.8 [D]

[0098] <Critical significance of preferred example>

25 The lens elements 1 and 2 related to the critical significance of the preferred example satisfying Formula 3 above were set as follows.

Lens element 1: Power is positive

n_{e1} : 2.0009

v_{e1} : 16.72

30 P_{gF1} : 0.666

D1: 5.8 [D]

Lens element 2: Power is negative

n_{e2} : 1.8656

v_{e2} : 30.23

5 P_{gF2} : 0.598

D2: -9.8 [D]

[0099] <Review>

As shown in FIG. 4, in Working Examples 1 and 2, a light ray on the short wavelength side (a light ray having a wavelength smaller than 546 nm) was shifted in the direction in which the power is positive, compared to Comparative Example 1. This indicates that the focus position of the luminous flux on the short wavelength side that passes through the eyeglass lens and passes through the pupil moves to the overfocus side.

[0100] On the contrary, the light on the long wavelength side (i.e., the light on the red light side, or light rays having a wavelength greater than 546 nm) was shifted in the direction in which the power is negative. This indicates that when the effect of suppressing the progression of refractive error is exhibited due to longitudinal chromatic aberration, the number of factors that hinder the suppressing effect was reduced.

[0101] In Working Example 2, the effect of moving the luminous flux focus position on the short wavelength side to the front of the retina is greater than that in Working Example 1. At the same time, in Working Example 2, the focus position of the luminous flux on the long wavelength side can be brought closer to the retina than in Working Example 1. If the focus position of the luminous flux on the long wavelength side is on the underfocus side, the near-sightedness progression suppressing effect is hindered. On the other hand, bringing the focus position of the luminous flux on the long wavelength side closer to the retina means reducing this inhibitory factor.

[0102] Regarding the plot of the critical significance of the preferred example, in the plot, the focus position of the luminous flux on the long wavelength side that

passes through the eyeglass lens and passes through the pupil moves to the underfocus side. This plot is a plot obtained in the case where Formula 3 above is made into an equation. Ultimately, it is preferable to adopt a combination of lens elements 1 and 2 such that the plot is arranged between that plot and the plot of

5 Comparative Example 1. That is, it is preferable to satisfy Formula 3 above.
[0103] [Summary]

The following is a summary of the “ophthalmic lens” disclosed in the present disclosure.

A working example of the present disclosure is as follows.

10 “An ophthalmic lens including two lens elements 1 and 2 having powers with different signs,

in which when an Abbe number (e-line reference) of the lens element 1 having a power with a smaller absolute value is v_{e1} , and an Abbe number (e-line reference) of the other lens element 2 is v_{e2} , Formula 1 below is satisfied, and

15 $v_{e1} < v_{e2}$... (Formula 1)

when a partial dispersion ratio P_{gF1} between a g-line and an F'-line in the lens element 1 having the power with the smaller absolute value, and a partial dispersion ratio P_{gF2} between a g-line and an F'-line in the other lens element 2 are set, Formula 2 below is satisfied.

20 $P_{gF1} > P_{gF2}$... (Formula 2)”

CLAIMS

1. An ophthalmic lens including two lens elements 1 and 2 having powers with different signs,

5 wherein when an Abbe number (e-line reference) of the lens element 1 having a power with a smaller absolute value is v_{e1} , and an Abbe number (e-line reference) of the other lens element 2 is v_{e2} , Formula 1 below is satisfied, and

$$v_{e1} < v_{e2} \quad \dots (\text{Formula 1})$$

10 when a partial dispersion ratio P_{gF1} between a g-line and an F'-line in the lens element 1 having the power with the smaller absolute value, and a partial dispersion ratio P_{gF2} between a g-line and an F'-line in the other lens element 2 are set, Formula 2 below is satisfied.

$$P_{gF1} > P_{gF2} \quad \dots (\text{Formula 2})$$

15 2. The ophthalmic lens according to claim 1,

wherein when the absolute value of the power of the lens element 1 is $D1$ and the absolute value of the power of the lens element 2 is $D2$, Formula 3 below is satisfied.

$$(D1/v_{e1}) < (D2/v_{e2}) \quad \dots (\text{Formula 3})$$

20

3. The ophthalmic lens according to claim 1 or 2,

wherein when the absolute value of the power of the lens element 1 is $D1$ and the absolute value of the power of the lens element 2 is $D2$, Formula 4 below is satisfied.

25
$$\{D1 \times (1 + 3 \times P_{gF1}) / v_{e1}\} > \{D2 \times (1 + 3 \times P_{gF2}) / v_{e2}\} \quad \dots (\text{Formula 4})$$

4. The ophthalmic lens according to any one of claims 1 to 3,

wherein the power of the lens element 1 is positive, and the power of the lens element 2 is negative.

30

5. The ophthalmic lens according to any one of claims 1 to 3,
wherein the power of the lens element 1 is negative, and the power of the
lens element 2 is positive.

5 6. The ophthalmic lens according to any one of claims 1 to 5, comprising
a first refractive region having a first refractive power obtained based on a
prescription for correcting refractive error of an eye; and
a plurality of second refractive regions that have a refractive power
different from the first refractive power, and have a function of focusing on a
10 position outside of a retina of the eye so as to suppress progression of the refractive
error of the eye,
wherein the second refractive regions are formed as respective independent
regions near a central portion of the ophthalmic lens, and
the first refractive region is formed outside of the regions in which the
15 second refractive regions are formed.

7. The ophthalmic lens according to any one of claims 1 to 6,
wherein the ophthalmic lens is an eyeglass lens.