



(51) International Patent Classification:
C08J 3/24 (2006.01)

(21) International Application Number:
PCT/EP2011/059073

(22) International Filing Date:
1 June 2011 (01.06.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10164586.9 1 June 2010 (01.06.2010) EP

(71) Applicant (for all designated States except US):
EDILON) (SEDRA B.V. [NL/NL]; 23, Nijverheidsweg,
Haarlem, 2031 CN (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VAN DER
HOUWEN, Gerrit, Marinus [NL/NL]; Gerrit van
Heesstraat 11, NL-2023 EL Haarlem (NL).
KERKHOVEN, Pieter, Joost [NL/NL]; 16, Van der
Waaalslaan, NL-2105 TD Heemstede (NL). KOTERIS,
Stefanus, Jacobus, Maria [NL/NL]; 181, Van Lin-
schotenlaan, NL-1212 DT Hilversum (NL).

(74) Agent: ZEESTRATEN, A.W.J.; P.O. Box 3241,
NL-2280 GE Rijswijk (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: POLYMER COMPOSITION, METHOD FOR APPLYING SUCH COMPOSITION AND USE OF SUCH COMPO-
SITION IN RAILWAY TRACK STRUCTURES

(57) Abstract: A polymer composition comprises a) a component 1 comprising a silane-terminated prepolymer; and b) a compo-
nent 2 comprising water; and c) a component 3 comprising a silanol condensation catalyst. The composition is packaged in at least
two separate packages prior to application, wherein no package contains all three components 1 and 2 and 3. In the composition
water is present in an amount of 0.01 to 10 pbw per 100 pbw of prepolymer present in the composition, and the apparent viscosi-
ties of each of the packages is at most 95 Pa.s (Brookfield viscosity (A/6/10)) according to ISO 2555 at 23 °C. The composition
may suitably applied to railway track structures for the dampening of noise and vibrations of rails.

