

5 AUTOMATIC LANDING SYSTEM FOR VERTICAL TAKEOFF/LANDING
AIRCRAFT, VERTICAL TAKEOFF/LANDING AIRCRAFT, AND CONTROL
METHOD FOR LANDING OF VERTICAL TAKEOFF/LANDING AIRCRAFT

Technical Field

10 [0001]

The present invention relates to an automatic landing system for a vertical take-off and landing aircraft, a vertical take-off and landing aircraft, and a landing control method for a vertical take-off and landing aircraft.

Background Art

15

[0002]

In the past, techniques for guiding a vertical take-off and landing aircraft to a target location have been known. For example, Patent Document 1 discloses an automatic take-off and landing system configured to calculate a positional relationship between a take-off and target landing and a flight body based on an image of the take-off and target landing captured by an imaging device mounted on the flight body, and control take-off and landing of the flight body based on the calculation result.

Citation List

25

Patent Literature

[0003]

Patent Document 1: JP 2012-071645 A

Summary of Invention

30

Technical Problem

[0004]

The automatic take-off and landing system described in Patent Document 1 can capture a target landing point by image processing and can land a vertical take-off and landing aircraft such as a flight body on the target landing point. However, Patent Document 1 does not describe details of the process until the vertical take-off and landing aircraft is caused to land on the target landing point. In order to avoid interference with surrounding objects or the like when landing the vertical take-off and landing aircraft, more accurate landing control is required.

40

[0005]

5 In light of the foregoing, an object of the present invention is to more accurately land a vertical take-off and landing aircraft on a target landing point.

Solution to Problem

[0006]

10 In order to solve the problem described above and to achieve the object, an automatic landing system for a vertical take-off and landing aircraft according to the present invention includes an imaging device mounted on a vertical take-off and landing aircraft, a relative-position acquisition unit configured to perform image processing on an image, of a marker provided to a target landing point, captured by the imaging device and configured to acquire a
15 relative position between the vertical take-off and landing aircraft and the target landing point, a relative-altitude acquisition unit configured to acquire a relative altitude between the vertical take-off and landing aircraft and the target landing point, and a control unit configured to control the vertical take-off and landing aircraft in a plurality of control modes such that the relative position becomes zero, wherein the plurality of control modes include a hovering mode and a landing mode, the hovering mode is executed within a first threshold value at which the relative position is within a range of the target landing point, the relative altitude of the vertical take-off and landing aircraft is lowered to a
20 predetermined relative altitude, and when a predetermined condition including a condition that the relative position is within a predetermined threshold value that is less than the first threshold value is satisfied, the control mode is shifted to the landing mode, and in the landing mode, the relative altitude of the vertical take-off and landing aircraft is further lowered to land the vertical
25 take-off and landing aircraft on the target landing point.
30 take-off and landing aircraft on the target landing point.

[0007]

 In order to solve the above-described problem and to achieve the object, a vertical take-off and landing aircraft according to the present invention includes the automatic landing system for the vertical take-off and landing
35 aircraft.

[0008]

 In order to solve the above-described problem and to achieve the object, a landing control method for a vertical take-off and landing aircraft according to the present invention includes performing image processing on an image, of a
40 marker provided to a target landing point, captured by an imaging device mounted on the vertical take-off and landing aircraft, and acquiring a relative position between the vertical take-off and landing aircraft and the target landing

5 point, acquiring a relative altitude between the vertical take-off and landing
aircraft and the target landing point, and controlling the vertical take-off and
landing aircraft in a plurality of control modes such that the relative position
becomes zero, wherein the plurality of control modes include a hovering mode
and a landing mode, the hovering mode is executed within a first threshold
10 value at which the relative position is within a range of the target landing point,
the relative altitude of the vertical take-off and landing aircraft is lowered to a
predetermined relative altitude, and when a predetermined condition including a
condition that the relative position is within a predetermined threshold value
that is less than the first threshold value is satisfied, the control mode is shifted
15 to the landing mode, and in the landing mode, the relative altitude of the
vertical take-off and landing aircraft is further lowered to land the vertical
take-off and landing aircraft on the target landing point.

Advantageous Effects of Invention

20 [0009]

The automatic landing system for the vertical take-off and landing
aircraft, the vertical take-off and landing aircraft, and the landing control
method for the vertical take-off and landing aircraft according to the present
invention provide the effect of being able to more accurately land the vertical
25 take-off and landing aircraft on a target landing point.

Brief Description of Drawings

[0010]

FIG. 1 is a schematic configuration diagram illustrating an example of an
30 automatic landing system for a vertical take-off and landing aircraft according
to a first embodiment.

FIG. 2 is an explanatory diagram illustrating a state where the vertical
take-off and landing aircraft according to the first embodiment travels toward a
target landing point.

35 FIG. 3 is an explanatory diagram illustrating an example of a marker
provided at a target landing point.

FIG. 4 is a flowchart illustrating an example of a processing procedure of
a landing control method for a vertical take-off and landing aircraft according to
the first embodiment.

40 FIG. 5 is an explanatory diagram illustrating a landing operation of the
vertical take-off and landing aircraft according to the first embodiment.

FIG. 6 is a flowchart illustrating an example of a processing procedure in an approach mode.

FIG. 7 is a flowchart illustrating an example of a processing procedure in a high altitude hovering mode.

FIG. 8 is a flowchart illustrating an example of a processing procedure in a low altitude hovering mode.

FIG. 9 is a flowchart illustrating an example of a processing procedure in a landing mode.

FIG. 10 is a flowchart illustrating an example of relative position calculation processing.

FIG. 11 is a schematic configuration diagram illustrating an example of an automatic landing system for a vertical take-off and landing aircraft according to a second embodiment.

FIG. 12 is a flowchart illustrating an example of a processing procedure in a high altitude hovering mode according to the second embodiment.

FIG. 13 is a flowchart illustrating an example of a processing procedure in a low altitude hovering mode according to the second embodiment.

FIG. 14 is a schematic configuration diagram illustrating an example of an automatic landing system for a vertical take-off and landing aircraft according to a third embodiment.

FIG. 15 is a flowchart illustrating an example of a processing procedure in a high altitude hovering according to the third embodiment.

FIG. 16 is a flowchart illustrating an example of a processing procedure in a low altitude hovering according to the third embodiment.

Description of Embodiments

[0011]

Detailed descriptions of embodiments of an automatic landing system for a vertical take-off and landing aircraft, a vertical take-off and landing aircraft, and a landing control method for a vertical take-off and landing aircraft according to the present invention will be given below based on the drawings. Note that, the invention is not limited to the embodiments.

[0012]

First Embodiment

FIG. 1 is a schematic configuration diagram illustrating an example of an automatic landing system for a vertical take-off and landing aircraft according to a first embodiment, and FIG. 2 is an explanatory diagram illustrating a state where the vertical take-off and landing aircraft according to the first

5 embodiment travels toward a target landing point. A vertical take-off and
landing aircraft 1 according to the first embodiment is a flight body (for
example, a helicopter or a drone) that serves as a rotorcraft. In the present
embodiment, the vertical take-off and landing aircraft 1 is an unmanned aircraft.
Note that the vertical take-off and landing aircraft 1 may be a flight body
10 capable of traveling forward, traveling backward, turning, traveling laterally,
and hovering, or may be a manned aircraft. Also, in a case where the vertical
take-off and landing aircraft 1 is an unmanned aircraft, when remote manual
control is performed while flight of the unmanned aircraft is controlled on
automatic pilot, flight control based on the remote manual control is prioritized.
15 Similarly, in a case where the vertical take-off and landing aircraft 1 is a
manned aircraft, when manual control is performed while flight of the manned
aircraft is controlled on automatic pilot, flight control based on the manual
control is prioritized. This vertical take-off and landing aircraft 1 is equipped
with an automatic landing system 100, its flight is controlled by the automatic
20 landing system 100, and the vertical take-off and landing aircraft 1 lands on a
target landing point 2 illustrated in FIG. 2.

[0013]

Target Landing Point

In the present embodiment, the target landing point 2 is provided on a
25 marine vessel 5, as illustrated in FIG. 2. Thus, the vertical take-off and landing
aircraft 1 lands on (boards) the marine vessel 5 serving as a movable body that
moves on water. However, the target landing point 2 is not limited to the marine
vessel 5, and may be provided on a vehicle or the like serving as a movable
body that moves on the ground, may be provided on a facility that does not
30 move, or may be provided on the ground. Note that, the marine vessel 5
includes a securing device (not illustrated) for securing the vertical take-off and
landing aircraft 1 when the vertical take-off and landing aircraft 1 is caused to
land on the target landing point 2.

[0014]

35 The target landing point 2 is provided with a marker 7 that allows the
vertical take-off and landing aircraft 1 to capture a position of the target landing
point 2. FIG. 3 is an explanatory diagram illustrating an example of a marker
provided at a target landing point. As illustrated, the marker 7 is an AR marker
that made up of two colors of black and white, for example, and is a square
40 marker. Note that the marker 7 is not limited to the AR marker, and may be a
marker with which the position of the target landing point 2 can be captured by
image processing, or may be, for example, an H mark or an R mark indicating

5 the landing point of a heliport or the like. Furthermore, a plurality of markers having different shapes may be provided on the marine vessel 5 as the marker 7, and the vertical take-off and landing aircraft 1 may be guided to the target landing point 2 corresponding to any of the different markers 7.

[0015]

10 Marine Vessel

As illustrated in FIG. 1, the marine vessel 5 includes a navigation system 70, a data transmission device 80, and an operation display unit 90. The navigation system 70 is, for example, an inertial navigation system (INS), and acquires attitude angles in a pitch direction and a roll direction, a ship heading, velocity, acceleration, position coordinates in a geographic coordinate system, and the like, of the marine vessel 5. Note that in the present embodiment, the navigation system 70 is described with the inertial navigation system being employed, but the navigation system 70 is not particularly limited thereto and any kind of navigation system 70 may be used. Furthermore, in the present embodiment, the navigation system 70 is an inertial navigation system including a global positioning system (GPS) serving as a position measuring unit in order to more accurately measure a position. Although the present embodiment will deal with a case of employing an inertial navigation system including the GPS, the present invention is not particularly limited to the GPS, and it is only required that the position measuring unit is capable of measuring a position with high accuracy. For example, a quasi-zenith satellite system may be used, or the position measuring unit such as the GPS may be omitted provided that a position can be accurately measured by using only the navigation system 70. Furthermore, the navigation system 70 may acquire at least some of various types of data by using a sensor. The data transmission device 80 is provided in the automatic landing system 100 to be described below, and exchanges various signals by wireless communication with a data transmission device 40 mounted on the vertical take-off and landing aircraft 1. The operation display unit 90 is a user interface that enables an operator aboard the marine vessel 5 to identify a control status and to input various types of instructions. Examples of the instructions to be input by the operator by using the operation display unit 90 include a transition instruction in a control mode to be described later. Details of the transition instruction will be described below. The instruction input via the operation display unit 90 is transmitted from the data transmission device 80 to the data transmission device 40. Additionally, the control status of the vertical take-off and landing aircraft 1 is transmitted from the data transmission device 40 to the data transmission device

5 80. In other words, the data transmission device 40 and the data transmission device 80 are capable of bi-directional communication.

[0016]

Automatic Landing System

10 The automatic landing system 100 for the vertical take-off and landing aircraft 1 according to the first embodiment is a system for controlling the position of the vertical take-off and landing aircraft 1 in order to land the vertical take-off and landing aircraft 1 on the target landing point 2 during flight. The automatic landing system 100 is mounted on the vertical take-off and landing aircraft 1. The automatic landing system 100 includes a camera 10, a
15 navigation system 20, a control unit 30, and the data transmission device 40, as illustrated in FIG. 1.

[0017]

Imaging Device

20 The camera 10 is an imaging device mounted on the vertical take-off and landing aircraft 1 by using a gimbal (not illustrated). The camera 10 may be a monocular camera, a compound eye camera, an infrared camera, or the like, as long as the marker 7 can be imaged. The camera 10 is provided to image the marker 7 provided at the target landing point 2 from the vertical take-off and landing aircraft 1. The camera 10 is capable of adjusting an imaging direction
25 by using the gimbal (not illustrated). In the present embodiment, the camera 10 is controlled by the control unit 30 such that a coverage area (an angle of view) B (see FIG. 2) of the camera 10 is directed downward in a vertical direction, as an example. Note that the camera 10 may be controlled by the control unit 30 such that the coverage area B is directed diagonally forward with respect to the
30 vertical direction. In addition, in the camera 10, the gimbal may be omitted and the camera 10 may be fixed directly under the body of the vertical take-off and landing aircraft 1 such that the imaging direction is directed downward in the vertical direction, for example.

[0018]

35 Navigation System

As with the navigation system 70, the navigation system 20 is, for example, an inertial navigation system including a GPS. Note that, as with the navigation system 70, the navigation system 20 is not particularly limited and may be an inertial navigation system including a position measuring unit such
40 as the GPS, or may be an inertial navigation system in which a position measuring unit such as the GPS is omitted. The navigation system 20 including the GPS acquires attitude angles in a pitch direction and a roll direction of the

5 vertical take-off and landing aircraft 1, an aircraft heading, an aircraft velocity
 and an aircraft acceleration of the vertical take-off and landing aircraft 1,
 position coordinates in a geographic coordinate system, and the like. Note that
 the navigation system 20 may include an attitude angle sensor that detects the
 attitude angles of the vertical take-off and landing aircraft 1, a velocity
 10 detection sensor that detects the aircraft velocity of the vertical take-off and
 landing aircraft 1, an acceleration detection sensor that detects aircraft
 acceleration of the vertical take-off and landing aircraft 1, and a sensor that
 detects the aircraft heading of the vertical take-off and landing aircraft 1. The
 navigation system 20 outputs the acquired attitude angles, aircraft velocity,
 15 aircraft acceleration, and position coordinates of the vertical take-off and
 landing aircraft 1 to the control unit 30.
 [0019]

The automatic landing system 100 also includes an altitude sensor 25
 that detects an altitude of the vertical take-off and landing aircraft 1 from the
 20 ground surface or water surface, as illustrated in FIG. 1. The altitude sensor 25
 is, for example, a laser altimeter, and measures a relative altitude Δh (see FIG.
 2) from the vertical take-off and landing aircraft 1 to the target landing point 2.
 Note that, as the altitude sensor 25, a radio altimeter may be used, a barometric
 altimeter may be used, or any altimeter may be used. These altimeters may also
 25 be applied in combination as appropriate, depending on the usage environment,
 that is, in order to measure an altitude from the ground surface or an altitude
 from the sea surface. The altitude sensor 25 outputs the detected relative
 altitude Δh of the vertical take-off and landing aircraft 1 to the control unit 30.
 Note that the altitude sensor 25 measures the altitude of the vertical take-off and
 30 landing aircraft 1 and outputs the altitude to the control unit 30, and the control
 unit 30 may calculate the relative altitude Δh (see FIG. 2) to the target landing
 point 2 based on the altitude of the vertical take-off and landing aircraft 1 by
 using a guidance calculation unit 34 that will be described below. Further, the
 automatic landing system 100 is not limited to the altitude sensor 25, and the
 35 relative altitude Δh between the vertical take-off and landing aircraft 1 and the
 marine vessel 5 may be calculated by performing image processing on an image
 including the marker 7 captured by the camera 10 by using an image processing
 unit 32 that will be described below.
 [0020]

40 Control Unit

The control unit 30 includes the image processing unit 32, the guidance
 calculation unit 34, and a flight control unit 36. Note that the control unit 30

5 includes an imaging control unit (not illustrated) configured to control the imaging direction of the camera 10 by using the gimbal (not illustrated) provided on the vertical take-off and landing aircraft 1. In the present embodiment, as described above, the coverage area B of the camera 10 is adjusted to be directed directly below in the vertical direction.

10 [0021]

Image Processing Unit

The image processing unit 32 performs image processing on an image captured by the camera 10 to calculate the center (Cx, Cy) of the marker 7, that is, the target landing point 2 (see FIG. 3). Here, the center (Cx, Cy) is a
 15 coordinate point in a camera-fixed coordinate system with the center of the image captured by the camera 10 serving as an origin, and can be calculated based on the number of pixels from the center of the image. Specifically, as illustrated in FIG. 3, the image processing unit 32 identifies two diagonals Ld extending between corners of the marker 7 by image processing, and determines
 20 the point of intersection between the two identified diagonals Ld as the center (Cx, Cy) of the marker 7. Note that the target landing point 2 is not limited to the center (Cx, Cy) of the marker 7, and may be any of the four corners of the marker 7, or may be a position offset from the center of the marker 7.

[0022]

25 Note that the image processing unit 32 may identify only one diagonal Ld, and may determine a center position of the length of the identified diagonal Ld as the center (Cx, Cy) of the marker 7. Additionally, the image processing unit 32 may identify two or more diagonals Ld, and may determine an average position of the center positions of the lengths of the identified diagonals Ld as
 30 the center (Cx, Cy) of the marker 7. Furthermore, when the image processing unit 32 performs trapezoidal correction on the marker 7, which has a square shape, by using a function obtained by projection transformation, the image processing unit 32 may calculate the center (Cx, Cy) of the square shape based on the function. At this time, the trapezoidal correction may be performed by
 35 using the coordinate points of the four corners of the marker 7 or the coordinate points of each of the points on boundaries marked by black and white of the marker 7, and the other coordinate points may be calculated by interpolation. The image processing unit 32 outputs the calculated center (Cx, Cy) of the marker 7 to the guidance calculation unit 34.

40 [0023]

Additionally, as described above, the image processing unit 32 may calculate the relative altitude Δh between the vertical take-off and landing

5 aircraft 1 and the marine vessel 5 by performing image processing on an image including the marker 7 captured by the camera 10. Furthermore, the image processing unit 32 may calculate a ship heading of the marine vessel 5 by performing image processing on the image including the marker 7 captured by the camera 10 to identify an orientation of the marker 7, and then correlating the
 10 orientation with an aircraft heading of the vertical take-off and landing aircraft 1 acquired by the navigation system 20. Note that a marker for calculating the ship heading may be separately provided on the marine vessel 5.

[0024]

Guidance calculation unit

15 The guidance calculation unit 34 calculates control amounts of the vertical take-off and landing aircraft 1 for guiding the vertical take-off and landing aircraft 1 to the target landing point 2. The control amounts are control amounts for adjusting the aircraft velocity, attitude angles, attitude rates, and the like of the vertical take-off and landing aircraft 1. In order to calculate the
 20 control amounts, the guidance calculation unit 34 calculates a relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2 and a relative velocity between the vertical take-off and landing aircraft 1 and the target landing point 2.

[0025]

25 The guidance calculation unit 34 calculates the relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2 based on the center (Cx, Cy) of the marker 7 calculated by the image processing unit 32, an azimuth of the camera 10, namely, an aircraft heading of the vertical take-off and landing aircraft 1, and an altitude of the vertical
 30 take-off and landing aircraft 1 (the relative altitude Δh with respect to the target landing point 2). Note that in the present embodiment, the azimuth of the camera 10 and the aircraft heading of the vertical take-off and landing aircraft 1 are matched with each other, but the present invention is not particularly limited thereto, and the azimuth of the camera 10 and the aircraft heading of the vertical
 35 take-off and landing aircraft 1 need not be matched with each other. As described above, the image processing unit 32 and the guidance calculation unit 34 function as a relative-position acquisition unit that acquires the relative position between the vertical take-off and landing aircraft 1 and the target landing point 2. The relative position (X, Y) is a distance between the vertical
 40 take-off and landing aircraft 1 and the target landing point 2 in a horizontal direction. More specifically, the guidance calculation unit 34 converts the center (Cx, Cy) of the marker 7 in the camera-fixed coordinate system

5 calculated by the image processing unit 32, based on the aircraft heading of the
vertical take-off and landing aircraft 1 and the altitude of the vertical take-off
and landing aircraft 1 (the relative altitude Δh with respect to the target landing
point 2), into the relative position between the vertical take-off and landing
aircraft 1 and the target landing point 2 in a ship inertial reference frame, and
10 further converts the converted relative position into the relative position (X, Y)
between the vertical take-off and landing aircraft 1 and the target landing point
2 in an aircraft inertial reference frame. At this time, the guidance calculation
unit 34 may directly convert the center (Cx, Cy) of the marker 7 into the
relative position (X, Y) between the vertical take-off and landing aircraft 1 and
15 the target landing point 2 in the aircraft inertial reference frame based on the
aircraft heading of the vertical take-off and landing aircraft 1 and the altitude of
the vertical take-off and landing aircraft 1 (the relative altitude Δh with respect
to the target landing point 2). Note that the ship inertial reference frame is a
coordinate system having, with the target landing point 2 serving as an origin, a
20 direction along the ship heading of the marine vessel 5, a direction orthogonal
to the ship heading of the marine vessel 5 in a horizontal direction, and
orthogonal axes being in a vertical direction. Furthermore, as illustrated in FIG.
2, the aircraft inertial reference frame is a coordinate system in which, with the
vertical take-off and landing aircraft 1 serving as an origin, a direction along the
25 aircraft heading of the vertical take-off and landing aircraft 1 serves as an X
axis, a direction orthogonal to the aircraft heading of the vertical take-off and
landing aircraft 1 in the horizontal direction serves as a Y axis, and the vertical
direction serves as a Z axis.

[0026]

30 Furthermore, the guidance calculation unit 34 calculates a relative
position (X_{GPS} , Y_{GPS}) between the vertical take-off and landing aircraft 1 and
the target landing point 2 based on position coordinates in the geographic
coordinate system of the vertical take-off and landing aircraft 1 acquired by the
navigation system 20 and position coordinates in the geographic coordinate
35 system of the marine vessel 5 acquired by the navigation system 70 of the
marine vessel 5 and obtained by communication between the data transmission
devices 40 and 80. Thus, the guidance calculation unit 34 functions as a second
relative-position acquisition unit that calculates the relative position (X_{GPS} ,
 Y_{GPS}) between the vertical take-off and landing aircraft 1 and the target landing
40 point 2 based on position coordinates of the vertical take-off and landing
aircraft 1 obtained by the GPS and position coordinates of the marine vessel 5

5 provided with the target landing point 2 that are acquired by the data transmission device 40.

[0027]

Furthermore, the guidance calculation unit 34 calculates a relative velocity between the vertical take-off and landing aircraft 1 and the target landing point 2. Thus, the guidance calculation unit 34 functions as a relative-velocity acquisition unit that acquires the relative velocity between the vertical take-off and landing aircraft 1 and the target landing point 2. More specifically, the guidance calculation unit 34 calculates the relative velocity based on, for example, a difference between the aircraft velocity of the vertical take-off and landing aircraft 1 and a hull velocity of the marine vessel 5, which are obtained by the navigation systems 20 and 70, respectively. In addition, the guidance calculation unit 34 may calculate the relative velocity based on a pseudo differential of the relative position (X, Y). In other words, the guidance calculation unit 34 functions as a relative-velocity acquisition unit that acquires the relative velocity. Furthermore, the guidance calculation unit 34 calculates a relative heading between the aircraft heading of the vertical take-off and landing aircraft 1 and the ship heading of the marine vessel 5.

[0028]

The guidance calculation unit 34 calculates the relative altitude Δh to the target landing point 20 based on an altitude of the vertical take-off and landing aircraft 1 detected by the altitude sensor 25. Thus, the altitude sensor 25 and the guidance calculation unit 34 function as a relative-altitude acquisition unit that acquires the relative altitude Δh between the vertical take-off and landing aircraft 1 and the target landing point 2. Note that when the image processing unit 32 calculates the relative altitude Δh between the vertical take-off and landing aircraft 1 and the marine vessel 5 by performing image processing on an image including the marker 7 captured by the camera 10, the image processing unit 32 serves as the relative-altitude acquisition unit.

[0029]

35 Then, the guidance calculation unit 34 calculates the control amounts by feedback control (PID control, for example) based on the relative position (X, Y), the relative velocity, the relative heading, and the aircraft acceleration. In the first embodiment, the guidance calculation unit 34 calculates the control amounts of the vertical take-off and landing aircraft 1 by feedback control such that the relative position (X, Y) and the relative heading become zero.

Furthermore, the guidance calculation unit 34 may calculate the control amounts of the vertical take-off and landing aircraft 1 by feedback control such

5 that the relative velocity is within a predetermined velocity and such that the aircraft acceleration is within a predetermined acceleration. The range within the predetermined velocity and within the predetermined acceleration is a range that satisfies a condition that the vertical take-off and landing aircraft 1 is considered to be in a state of stably flying at a predetermined relative altitude
 10 Δh . For example, the predetermined velocity is zero, and the predetermined acceleration is zero. The guidance calculation unit 34 outputs the calculated control amounts to the flight control unit 36. In the calculation of such control amounts, the guidance calculation unit 34 controls the vertical take-off and landing aircraft 1 in a plurality of control modes to guide and land the vertical
 15 take-off and landing aircraft 1 to the target landing point. The plurality of control modes include an approach mode, a hovering mode including a high altitude hovering mode and a low altitude hovering mode, and a landing mode. Details of each control mode will be described later.

[0030]

20 Flight Control Unit

The flight control unit 36 controls each constituent element of the vertical take-off and landing aircraft 1 and causes the vertical take-off and landing aircraft 1 to fly in accordance with the control amounts calculated by the guidance calculation unit 34 to be described below. The flight control unit
 25 36 controls a blade pitch angle, a rotational speed, and the like of individual rotary blades in accordance with the control amounts, and adjusts the aircraft velocity, attitude angles, attitude rates, and the like of the vertical take-off and landing aircraft 1. Thus, the vertical take-off and landing aircraft 1 is guided to the target landing point 2. Note that in the present embodiment, the image
 30 processing unit 32 and the guidance calculation unit 34 are described as functional units separate from the flight control unit 36, but the flight control unit 36, the image processing unit 32, and the guidance calculation unit 34 may be an integrated functional unit. In other words, processing of the image processing unit 32 and the guidance calculation unit 34 may be performed in the
 35 flight control unit 36.

[0031]

Landing Control Method for Vertical Take-off and Landing Aircraft

Next, as a landing control method for a vertical take-off and landing aircraft according to the first embodiment, a procedure for guiding and landing
 40 the vertical take-off and landing aircraft 1 to the target landing point 2 by using the control unit 30 will be described. FIG. 4 is a flowchart illustrating an example of a processing procedure of the landing control method for the

5 vertical take-off and landing aircraft according to the first embodiment. FIG. 5 is an explanatory diagram illustrating a landing operation of the vertical take-off and landing aircraft according to the first embodiment. FIG. 6 is a flowchart illustrating an example of a processing procedure in the approach mode. FIG. 7 is a flowchart illustrating an example of a processing procedure in the high altitude hovering mode. FIG. 8 is a flowchart illustrating an example of a processing procedure in the low altitude hovering mode. FIG. 9 is a flowchart illustrating an example of a processing procedure in the landing mode. FIG. 10 is a flowchart illustrating an example of relative position calculation processing. The processing illustrated in FIG. 4 to FIG. 10 is executed by the guidance calculation unit 34.

[0032]

First, a landing operation of the vertical take-off and landing aircraft 1 will be described with reference to FIG. 4 and FIG. 5. The vertical take-off and landing aircraft 1 executes a plurality of control modes in a series of landing operations when landing on (boarding) the marine vessel 5 from a flying state. Specifically, the vertical take-off and landing aircraft 1 performs the series of landing operations by performing a step S1 in which the approach mode is executed, a step S2 in which the high altitude hovering mode is executed, a step S3 in which the low altitude hovering mode is executed, and a step S4 in which the landing mode is executed in this order. The vertical take-off and landing aircraft 1 also performs a step (a step S17 that will be described below) of executing an emergency mode in which execution of the high altitude hovering mode and the low altitude hovering mode is interrupted and the landing operation is interrupted.

[0033]

As illustrated in FIG. 5, the approach mode is a mode in which the vertical take-off and landing aircraft 1 is caused to advance above the deck of the marine vessel 5 and the vertical take-off and landing aircraft 1 is caused to hover over the marker 7 serving as the target landing point 2, based on an instruction from the marine vessel 5. The high altitude hovering mode is a mode in which the vertical take-off and landing aircraft 1 hovers such that the marker 7 on the deck is captured by the camera 10, and the target landing point 2 that is the center of the marker 7 is at the center of the coverage area (angle of view) B of the camera 10. The low altitude hovering mode is a mode in which the vertical take-off and landing aircraft 1 descends and hovers at a lower altitude than that in the high altitude hovering mode. The landing mode is a mode in which the vertical take-off and landing aircraft 1 lands on the target landing

5 point 2. The emergency mode is a mode in which the landing operation of the vertical take-off and landing aircraft 1 on the marine vessel 5 is interrupted and the vertical take-off and landing aircraft 1 ascends.

[0034]

The vertical take-off and landing aircraft 1 performs the landing
10 operation on the marine vessel 5 by executing these control modes. Next, each control mode will be described in detail with reference to FIG. 6 to FIG. 10.

[0035]

Approach Mode

The guidance calculation unit 34 executes the approach mode as step S1.
15 The approach mode will be described in detail with reference to FIG. 6. As a step S31, the guidance calculation unit 34 calculates (generates) the relative position (X_{GPS} , Y_{GPS}) from position coordinates obtained by the navigation systems 20 and 70, that is, the GPSs.

[0036]

20 Next, the guidance calculation unit 34 determines whether an approach mode button is turned on as a step S32. The approach mode button is a button provided on the operation display unit 90 of the marine vessel 5 for inputting a transition instruction of the control mode, and is turned on and off by an operator aboard the marine vessel 5. The operator turns on the approach mode
25 button once the vertical take-off and landing aircraft 1 is ready for landing on the marine vessel 5. When the control unit 30 determines that the approach mode button is not turned on (NO in step S2), the control unit 30 continues the processing in step S1. On the other hand, when the control unit 30 determines that the approach mode button is turned on (YES in step S2), the control unit 30
30 proceeds to the processing in a step S33.

[0037]

As step S33, the guidance calculation unit 34 executes feedback control such that the relative position (X_{GPS} , Y_{GPS}) generated in step S31 becomes zero. In this way, the guidance calculation unit 34 causes the vertical take-off and
35 landing aircraft 1 to fly in the horizontal direction toward the target landing point 2. Furthermore, the guidance calculation unit 34 executes the feedback control such that the calculated relative heading between the aircraft heading of the vertical take-off and landing aircraft 1 and the ship heading of the marine vessel 5 becomes zero, as an example. As a result, the guidance calculation unit
40 34 causes the vertical take-off and landing aircraft 1 to fly such that the aircraft heading of the vertical take-off and landing aircraft 1 matches the ship heading of the marine vessel 5 in the horizontal direction. Note that, as an example, the

5 guidance calculation unit 34 performs the feedback control such that the relative heading becomes zero, but the present invention is not particularly limited thereto, and the relative heading does not need to be zero. Furthermore, the guidance calculation unit 34 executes the feedback control such that the relative altitude Δh measured by the altitude sensor 25 becomes a first relative
 10 altitude Δh_1 . As a result, the guidance calculation unit 34 causes the vertical take-off and landing aircraft 1 to descend from an initial altitude to the first relative altitude Δh_1 (see FIG. 2) in the vertical direction, and causes the vertical take-off and landing aircraft 1 to maintain the first relative altitude Δh_1 . The first relative altitude Δh_1 is, for example, 8 m. Thus, in the approach mode,
 15 flight of the vertical take-off and landing aircraft 1 is controlled such that the vertical take-off and landing aircraft 1 is within a predetermined range of the target landing point 2 by performing control such that the relative position (X_{GPS} , Y_{GPS}) becomes zero.

[0038]

20 The guidance calculation unit 34 executes relative position calculation processing with an image as a step S34, and calculates the relative position (X, Y) as a distance in the horizontal direction between the vertical take-off and landing aircraft 1 and the target landing point 2. Details of the relative position calculation processing with an image will be described later.

25 [0039]

The guidance calculation unit 34 determines, as a step S35, whether the relative position (X, Y) as the distance in the horizontal direction, which has been calculated in step S34, between the vertical take-off and landing aircraft 1 and the target landing point 2 is within a first threshold value. The first
 30 threshold value is set as a value at which there is sufficient distance for the camera 10 to continue to capture the target landing point 2. When the guidance calculation unit 34 determines that the relative position (X, Y) is not within the first threshold value (NO in step S35), the guidance calculation unit 34 executes the processing of step S31 and subsequent steps again. That is, the vertical
 35 take-off and landing aircraft 1 performs the processing of step S33 and subsequent steps again due to the determination that the camera 10 cannot capture the target landing point 2, that is, the vertical take-off and landing aircraft 1 is not sufficiently close to the target landing point 2. Then, the guidance calculation unit 34 iterates the processing of step S33 and subsequent
 40 steps until the vertical take-off and landing aircraft 1 is at a distance sufficient to allow the camera 10 to continue to capture the target landing point 2. When the guidance calculation unit 34 determines that the relative position (X, Y) is

5 within the first threshold value (YES in step S35), the guidance calculation unit
34 ends the approach mode and shifts the control mode to the next control mode
due to the determination that the vertical take-off and landing aircraft 1 is at a
distance sufficient to allow the camera 10 to continue to capture the target
10 landing point 2, that is, the vertical take-off and landing aircraft 1 is sufficiently
close to the target landing point 2.

[0040]

High Altitude Hovering Mode

Description will be made returning to FIG. 4. When the approach mode
has ended, the guidance calculation unit 34 executes the high altitude hovering
15 mode as step S2. The high altitude hovering mode will be described in detail
with reference to FIG. 7. In the high altitude hovering mode, the guidance
calculation unit 34 executes the feedback control such that the relative position
(X, Y) calculated in the relative position calculation processing with an image
becomes zero, as illustrated in step S41 in FIG. 7. Additionally, the guidance
20 calculation unit 34 executes the feedback control such that the calculated
relative heading between the aircraft heading of the vertical take-off and
landing aircraft 1 and the ship heading of the marine vessel 5 becomes zero, as
an example. Furthermore, the guidance calculation unit 34 executes the
feedback control such that the relative altitude Δh measured by the altitude
25 sensor 25 becomes the first relative altitude Δh_1 . In this way, the guidance
calculation unit 34 causes the vertical take-off and landing aircraft 1 to maintain
the first relative altitude Δh_1 while causing the vertical take-off and landing
aircraft 1 to hover directly above the target landing point 2 in the vertical
direction. Then, the guidance calculation unit 34 executes the relative position
30 calculation processing with an image again as a step S42.

[0041]

As a step S43, the guidance calculation unit 34 determines whether the
relative position (X, Y) calculated in step S42 is within a second threshold
value, and whether a low altitude hovering mode button is turned on. The
35 second threshold value is set as a value that is equal to or less than the first
threshold value in the approach mode. The low altitude hovering mode button is
a button provided on the operation display unit 90 of the marine vessel 5 for
inputting a transition instruction of the control mode, and is turned on and off
by an operator aboard the marine vessel 5. The operator visually checks whether
40 the vertical take-off and landing aircraft 1 can stably fly at the first relative
altitude Δh_1 , and turns on the low altitude hovering button when the vertical
take-off and landing aircraft 1 can stably fly. Step S43 is for determining

5 whether a first condition for transition from the high altitude hovering mode to the low altitude hovering mode is satisfied. That is, in the first embodiment, the first condition includes, in addition to the condition that the relative position (X, Y) is within the second threshold value, a condition that the operator has instructed a mode transition to the low altitude hovering mode.

10 [0042]

When the guidance calculation unit 34 determines that the relative position (X, Y) is not within the second threshold value (NO in step S43), the guidance calculation unit 34 executes the processing of step S41 and subsequent steps again. In addition, when the guidance calculation unit 34 determines that the low altitude hovering mode button is not turned on (NO in step S43), the guidance calculation unit 34 also executes the processing of step S41 and subsequent steps again. Then, the guidance calculation unit 34 iterates the processing of step S41 and subsequent steps until the relative position (X, Y) of the vertical take-off and landing aircraft 1 with respect to the target landing point 2 falls within the second threshold value. When the guidance calculation unit 34 determines that the relative position (X, Y) is within the second threshold value and that the low altitude hovering mode button is turned on (YES in step S43), the guidance calculation unit 34 ends the high altitude hovering mode and shifts to the next control mode.

25 [0043]

Low Altitude Hovering Mode

Description will be made returning to FIG. 4. When the guidance calculation unit 34 ends the high altitude hovering mode, the guidance calculation unit 34 executes the low altitude hovering mode as the step S3. The low altitude hovering mode will be described in details with reference to FIG. 8. In the low altitude hovering mode, the guidance calculation unit 34 executes the feedback control such that the relative position (X, Y) calculated in the relative position calculation processing with an image becomes zero, as illustrated in a step S51 in FIG. 8. Additionally, the guidance calculation unit 34 executes the feedback control such that the calculated relative heading between the aircraft heading of the vertical take-off and landing aircraft 1 and the ship heading of the marine vessel 5 becomes zero, as an example. Furthermore, the guidance calculation unit 34 performs the feedback control such that the relative altitude Δh measured by the altitude sensor 25 becomes a second relative altitude Δh_2 that is lower than the first relative altitude Δh_1 . Due to this, the guidance calculation unit 34 causes the altitude of the vertical take-off and landing aircraft 1 to descend to the second relative altitude Δh_2 (see FIG. 2) while

5 causing the vertical take-off and landing aircraft 1 to perform hovering directly above the target landing point 2. The second relative altitude Δh_2 is, for example, 3 m. At this time, the guidance calculation unit 34 causes a descent rate of the vertical take-off and landing aircraft 1 to be a first descent rate. The first descent rate is, for example, 0.6 m/s. Then, the guidance calculation unit
 10 34 executes the relative position calculation processing with an image again as a step S52.
 [0044]

As a step S53, the guidance calculation unit 34 determines whether the relative position (X, Y) calculated in the step S52 is within a third threshold
 15 value (predetermined threshold value) or not and whether a landing mode button is turned on or not. The third threshold value is set as a value that is less than or equal to the second threshold value in the high altitude hovering. Additionally, the landing mode button is a button provided on the operation display unit 90 of the marine vessel 5 for inputting a transition instruction of the
 20 control mode, and is turned on and off by an operator being aboard the marine vessel 5. The operator visually checks whether the vertical take-off and landing aircraft 1 can stably fly at the second relative altitude Δh_2 , and turns on the landing mode button when the vertical take-off and landing aircraft 1 can stably fly. In the step S53, whether a second condition (predetermined condition) for
 25 the transition from the low altitude hovering mode to the landing mode is satisfied or not is determined. That is, in the first embodiment, the second condition includes, in addition to the condition that the relative position (X, Y) is within the third threshold value, a condition that the operator has instructed a mode transition to the landing mode. Note that the operator may turn on the
 30 landing mode button even when the vertical take-off and landing aircraft 1 is not stable.
 [0045]

When the guidance calculation unit 34 determines that the relative position (X, Y) is not within the third threshold value (NO in the step S53), the
 35 guidance calculation unit 34 executes the processing of the step S51 and the subsequent steps again. Also, in a case where the guidance calculation unit 34 determines that the landing mode button is not turned on (NO in the step S53), the guidance calculation unit 34 executes the processing of the step S51 and the subsequent steps again. Then, the guidance calculation unit 34 repeatedly
 40 performs the processing of the step S51 and the subsequent steps such that the vertical take-off and landing aircraft 1 is at a position where the relative position (X, Y) with respect to the target landing point 2 is within the third

5 threshold value and descends to the second relative altitude Δh_2 . When the guidance calculation unit 34 determines that the relative position (X, Y) is within the third threshold value and that the landing mode button is turned on (YES in the step S53), the guidance calculation unit 34 ends the low altitude hovering mode and shifts to the next control mode.

10 [0046]

Landing Mode

Description will be made returning to FIG. 4. When the guidance calculation unit 34 ends the low altitude hovering mode, the guidance calculation unit 34 performs the landing mode as step S4. The landing mode will be described in detail with reference to FIG. 9. In the landing mode, as illustrated in step S61 in FIG. 9, the guidance calculation unit 34 executes feedback control such that the relative position (X, Y) calculated in the relative position calculation processing with an image becomes zero. Additionally, the guidance calculation unit 34 executes the feedback control such that the calculated relative heading between the aircraft heading of the vertical take-off and landing aircraft 1 and the ship heading of the marine vessel 5 becomes zero, as an example. Furthermore, the guidance calculation unit 34 performs vertical velocity control in which a descent rate is made to be constant until the relative altitude Δh measured by the altitude sensor 25 reaches a third relative altitude Δh_3 . The descent rate is the degree of altitude descending per unit time. In the vertical velocity control, the guidance calculation unit 34 causes a descent rate of the vertical take-off and landing aircraft 1 to be a second descent rate. As a result, the guidance calculation unit 34 lowers the relative altitude Δh of the vertical take-off and landing aircraft 1 to the third relative altitude Δh_3 (see FIG. 2). The third relative altitude Δh_3 is, for example, 10 cm. In addition, the second descent rate is, for example, 1.0 m/s. Note that in the present embodiment, although the second descent rate is set to be larger than the first descent rate in order to quickly land the vertical take-off and landing aircraft 1 on the target landing point 2 in the landing mode, any of the first descent rate and the second descent rate may be set to be larger, or the first descent rate and the second descent rate may have the same value. Furthermore, when the altitude of the vertical take-off and landing aircraft 1 reaches the third relative altitude Δh_3 , the guidance calculation unit 34 causes the vertical take-off and landing aircraft 1 to further descend while holding the control amounts related to the attitude angles of the vertical take-off and landing aircraft 1 when the altitude of the vertical take-off and landing aircraft 1 reaches the third relative altitude Δh_3 .

5 [0047]

The guidance calculation unit 34 determines whether the target landing point 2 can be captured by the camera 10 as a step S62. Whether the target landing point 2 can be captured by the camera 10 can be calculated by processing similar to that in the relative position calculation processing with an image in a step S12 that will be described below. When the guidance calculation unit 34 determines that the target landing point 2 can be captured by the camera 10 (YES in step S62), the guidance calculation unit 34 calculates the relative position (X, Y) by the image processing as a step S63. The relative position (X, Y) can be calculated by processing similar to that in a step S14 of the relative position calculation processing with an image that will be described later. On the other hand, when the guidance calculation unit 34 determines that the target landing point 2 cannot be captured by the camera 10 (NO in step S62), the guidance calculation unit 34 omits the processing of step S63 and proceeds to a step S64. In the present embodiment, in the landing mode, the landing mode is continuously performed due to the fact that the vertical take-off and landing aircraft 1 is in a state of being sufficiently close to the target landing point 2 and, even when the vertical take-off and landing aircraft 1 temporarily cannot capture the target landing point 2 by the camera 10, the vertical take-off and landing aircraft 1 can land near the target landing point 2. Note that, when the vertical take-off and landing aircraft 1 is a manned aircraft, the execution of the landing mode may be interrupted based on the determination of a pilot.

[0048]

The flight control unit 36 determines, as step S64, whether the vertical take-off and landing aircraft 1 has landed on the target landing point 2. Whether the vertical take-off and landing aircraft 1 has landed on the target landing point 2 can be determined, for example, by providing a contact-type sensor on landing gear (not illustrated) of the vertical take-off and landing aircraft 1. When the flight control unit 36 determines that the vertical take-off and landing aircraft 1 has not landed on the target landing point 2 (NO in step S64), the flight control unit 36 executes the processing of step S61 and subsequent steps again. This controls the vertical take-off and landing aircraft 1 to descend in accordance with the procedure of step S61 until the vertical take-off and landing aircraft 1 lands on the target landing point 2. When the flight control unit 36 determines that the vertical take-off and landing aircraft 1 has landed on the target landing point 2 (YES in step S64), the guidance calculation unit 34 ends the landing mode. This also ends the processing routine illustrated in FIG. 4.

5 [0049]

Relative Position Calculation processing with Image

Next, the relative position calculation processing with an image will be described with reference to FIG. 10. In the relative position calculation processing with an image, the guidance calculation unit 34 determines whether
 10 an emergency mode button is off, as a step S11. The emergency mode button is provided on the operation display unit 90 of the marine vessel 5, and is turned on and off by an operator aboard the marine vessel 5. The operator turns on the emergency mode button when the operator determines that the vertical take-off and landing aircraft 1 should stop landing on the marine vessel 5. Specifically,
 15 the operator turns on the emergency mode button after visually checking the fact that the flying state of the vertical take-off and landing aircraft 1 is unstable, for example, due to influence of wind, occurrence of some kind of failure, or the like.

[0050]

20 When the guidance calculation unit 34 determines in step S11 that the emergency mode button is on (NO in step S11), the guidance calculation unit 34 shifts to execution of the emergency mode as a step S17. In the emergency mode, the guidance calculation unit 34 causes the vertical take-off and landing aircraft 1 to ascend once to a predetermined altitude (for example, 20 m) being
 25 sufficiently away from the marine vessel 5 and to maintain the current relative position (X, Y). When shifting to the emergency mode, the guidance calculation unit 34 can perform the emergency mode during execution of step S2 in which the high altitude hovering mode illustrated in FIG. 4 is performed and step S3 in which the low altitude hovering mode is executed. Once the guidance
 30 calculation unit 34 causes the vertical take-off and landing aircraft 1 to ascend to an altitude that is sufficiently away from the marine vessel 5 by performing the emergency mode, the guidance calculation unit 34 restarts the processing illustrated in FIG. 4 again from step S1.

[0051]

35 On the other hand, when the guidance calculation unit 34 determines that the emergency mode button is off (YES in step S11), the guidance calculation unit 34 determines whether the target landing point 2 can be captured by the camera 10, as step S12. Whether the target landing point 2 can be captured by the camera 10 can be determined by whether information that can be used to
 40 calculate the center (Cx, Cy) of the marker 7 can be obtained in an image captured by the camera 10.

[0052]

5 When the guidance calculation unit 34 determines that the target landing point 2 can be captured by using the camera 10 (YES in step S12), the guidance calculation unit 34 sets a target non-capture counter to a value of 0, as a step S13. Then, as step S14, the guidance calculation unit 34 calculates the relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2 based on the center (Cx, Cy) of the marker 7, an azimuth of the camera 10 (i.e., the aircraft heading of the vertical take-off and landing aircraft 1 having the same azimuth), and the altitude of the vertical take-off and landing aircraft 1 (the relative altitude Δh with respect to the target landing point 2). As described above, the relative position (X, Y) is calculated by

10 converting the center (Cx, Cy) of the marker 7 in the camera-fixed coordinate system calculated by the image processing unit 32 into the relative position between the vertical take-off and landing aircraft 1 and the target landing point 2 in the ship inertial reference frame, and further converting the converted relative position into the relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2 in the aircraft inertial reference frame.

[0053]

 On the other hand, in step S12, when the guidance calculation unit 34 determines that the target landing point 2 cannot be captured by using the camera 10 (NO in step S12), the guidance calculation unit 34 adds a value of 1 to the target non-capture counter as a step S15, and determines whether the target non-capture counter is within a predetermined value as a step S16. When the guidance calculation unit 34 determines that the target non-capture counter is within a predetermined value (YES in step S16), the guidance calculation unit

25 34 executes the processing of step S11 and subsequent steps again. When the guidance calculation unit 34 determines that the target non-capture counter is not within the predetermined value (NO in step S16), the guidance calculation unit 34 proceeds to a step S17 and shifts to execution of the emergency mode. In other words, the guidance calculation unit 34 determines that, when the target non-capture counter exceeds the predetermined value, a time period for which the target landing point 2 cannot be captured by the camera 10 continues longer than or equal to a predetermined time period, and executes the emergency mode.

[0054]

40 Operational Effects of First Embodiment

 As described above, the automatic landing system 100 for a vertical take-off and landing aircraft according to the first embodiment includes the

5 camera 10 (an imaging device) mounted on the vertical take-off and landing aircraft 1, the image processing unit 32 and the guidance calculation unit 34 (a relative-position acquisition unit) configured to perform image processing on an image, of the marker 7 provided at the target landing point 2, captured by the camera 10 and to acquire a relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2, the guidance calculation unit 34 (a relative-velocity acquisition unit) configured to acquire a relative velocity between the vertical take-off and landing aircraft 1 and the target landing point 2, the altitude sensor 25 and the guidance calculation unit 34 (a relative-altitude acquisition unit) configured to acquire a relative altitude Δh between the vertical take-off and landing aircraft 1 and the target landing point 2, and the control unit 30 configured to control the vertical take-off and landing aircraft 1 in a plurality of control modes such that the relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2 becomes zero, wherein the plurality of control modes include the hovering mode and the landing mode, and in the hovering mode, when the relative position (X, Y) is within the first threshold value, the relative altitude Δh of the vertical take-off and landing aircraft 1 is lowered to the second relative altitude Δh_2 (a predetermined relative altitude) and when the second condition (a predetermined condition) including a condition that the relative position (X, Y) is within the third threshold value (a predetermined threshold value) is satisfied, the control mode is shifted to the landing mode, and in the landing mode, the relative altitude Δh of the vertical take-off and landing aircraft 1 is further lowered and, when the relative altitude Δh is lower than or equal to the third relative altitude Δh_3 (a predetermined value), the vertical take-off and landing aircraft 1 is caused to descend and land on the target landing point 2 while a command for the control amounts related to the attitude angles of the vertical take-off and landing aircraft 1 is being held.

[0055]

35 With this configuration, the target landing point 2 can be captured by using the camera 10, and when the relative position (X, Y) is within the first threshold value, the vertical take-off and landing aircraft 1 can be controlled in the order of the hovering mode and the landing mode and be caused to land on the target landing point 2. In the hovering mode, the condition that the vertical take-off and landing aircraft 1 is caused to descend to the second relative altitude Δh_2 and the relative position (X, Y) is within the third threshold value (a predetermined threshold value) is regarded as a condition for shifting to the landing mode. Thus, the vertical take-off and landing aircraft 1 is moved closer

5 to the target landing point 2, and then, the control mode can be shifted to the
 landing mode. Additionally, in the landing mode, when the relative altitude Δh
 reaches the third relative altitude Δh_3 , the vertical take-off and landing aircraft
 1 is caused to descend and land on the target landing point 2 while holding the
 control amounts related to the attitude angles of the vertical take-off and
 10 landing aircraft 1 when the relative altitude Δh reaches the third relative altitude
 Δh_3 . Thus, when the vertical take-off and landing aircraft 1 is positioned
 directly in front of the target landing point 2, the vertical take-off and landing
 aircraft 1 can be caused to land on the target landing point 2, while unstable
 behavior of the vertical take-off and landing aircraft 1 is suppressed by
 15 controlling the attitude angles of the vertical take-off and landing aircraft 1.
 Note that, although the automatic landing system 100 performs control such that
 the relative position becomes zero, in practice, after landing the vertical
 take-off and landing aircraft 1 on the marine vessel 5, the relative position does
 not necessarily become zero including errors, and the position of the vertical
 20 take-off and landing aircraft 1 and the position of the target landing point 2 do
 not perfectly coincide.

[0056]

Further, in the first embodiment, when the target landing point 2 can be
 captured by at least the camera 10, the relative position (X, Y) can be calculated
 25 based on the marker 7 captured by the camera 10. In other words, when the
 relative position (X, Y) is calculated, data communication with the marine
 vessel 5 side is not required. Thus, when the vertical take-off and landing
 aircraft 1 is controlled based on the relative position (X, Y), positioning
 accuracy can be improved and degradation in the responsiveness of the flight
 30 control caused by performing communication can be suppressed because
 influence due to errors or the like caused by the navigation systems 20 and 70
 can be avoided.

[0057]

Thus, according to the first embodiment, the vertical take-off and
 35 landing aircraft 1 can be more accurately landed on the target landing point 2.
 Further, by accurately controlling the position of the vertical take-off and
 landing aircraft 1 with respect to the target landing point 2, interference
 between the vertical take-off and landing aircraft 1 and facilities or structures
 provided near the target landing point 2 can be suppressed.

40 [0058]

Additionally, the hovering mode includes the high altitude hovering
 mode and the low altitude hovering mode, wherein, in the high altitude

5 hovering mode, when the relative position (X, Y) is within the first threshold value, the relative altitude Δh of the vertical take-off and landing aircraft 1 is maintained at the first relative altitude Δh_1 that is higher than the second relative altitude Δh_2 (a predetermined relative altitude), and when the first condition including the condition that the relative position (X, Y) is within the
 10 second threshold value is satisfied, the control mode is shifted to the low altitude hovering mode, and in the low altitude hovering mode, the relative altitude Δh of the vertical take-off and landing aircraft 1 is lowered to the second relative altitude Δh_2 (a predetermined relative altitude), and when the second condition including the condition that the relative position (X, Y) is
 15 within the third threshold value is satisfied as a predetermined condition, the control mode is shifted to the landing mode. Note that, as described above, the second threshold value may include the first threshold value, or may be a value that is less than or equal to the first threshold value. Similarly, the third threshold value may include the second threshold value, or may be a value less
 20 than or equal to the second threshold value.
 [0059]

This configuration allows the control mode to be shifted to the landing mode through the high altitude hovering mode and the low altitude hovering mode. In the high altitude hovering mode, the relative altitude Δh of the vertical
 25 take-off and landing aircraft 1 is maintained at the first relative altitude Δh_1 that is higher than the second relative altitude Δh_2 (a predetermined relative altitude), and when the relative position (X, Y) is within the second threshold value, the control mode is shifted to the low altitude hovering mode. Thus, the control mode can be shifted to the low altitude hovering mode in a state where
 30 the vertical take-off and landing aircraft 1 is caused to hover directly above the target landing point 2 while being temporarily maintained at the first relative altitude Δh_1 . Then, in the low altitude hovering mode, the vertical take-off and landing aircraft 1 is caused to descend to the second relative altitude Δh_2 , and when the relative position (X, Y) is within the third threshold value (a
 35 predetermined threshold value), the control mode is shifted to the landing mode. Thus, the vertical take-off and landing aircraft 1 can be shifted to the landing mode in a state where the vertical take-off and landing aircraft 1 is caused to hover directly above the target landing point 2. In this way, in the state where the vertical take-off and landing aircraft 1 is caused to hover directly above the
 40 target landing point 2, the vertical take-off and landing aircraft 1 can be stably landed by gradually changing the relative altitude Δh of the vertical take-off and landing aircraft 1 to be zero.

5 [0060]

Additionally, the first condition and the second condition include a condition that mode transition has been instructed by an operator. That is, the first condition includes a condition that the operator has turned on the low altitude hovering mode button. Further, the second condition includes a
 10 condition that the operator has turned on the landing mode button. This configuration allows the operator to visually check whether the flight of the vertical take-off and landing aircraft 1 is stable, and then, allows the transition from the high altitude hovering mode to the low altitude hovering mode and the transition from the low altitude hovering mode to the landing mode to be
 15 performed.

[0061]

The automatic landing system 100 also includes the navigation system
 20 configured to acquire position coordinates of the vertical take-off and landing aircraft 1, the data transmission device 40 configured to exchange data between the vertical take-off and landing aircraft 1 and the marine vessel 5 (a
 20 facility) provided with the target landing point 2, and the guidance calculation unit 34 (a second relative-position acquisition unit) configured to calculate a relative position (X_{GPS} , Y_{GPS}) between the vertical take-off and landing aircraft 1 and the target landing point 2 based on the position coordinates of the vertical
 25 take-off and landing aircraft 1 acquired by the navigation system 20 and position coordinates of the marine vessel 5 provided with the target landing point 2 that are acquired by the data transmission device 40, wherein the plurality of control modes include the approach mode, and in the approach mode, the relative position (X_{GPS} , Y_{GPS}) acquired by the guidance calculation
 30 unit 34 is controlled to become zero, the relative altitude Δh of the vertical take-off and landing aircraft 1 is maintained so as to descend to the first relative altitude $\Delta h1$ that is higher than the second relative altitude $\Delta h2$ (a predetermined relative altitude), and when the relative position (X , Y) acquired by the image processing unit 32 and the guidance calculation unit 34 (a
 35 relative-position acquisition unit) is within the first threshold value, the control mode is shifted to the high altitude hovering mode.

[0062]

With this configuration, the vertical take-off and landing aircraft 1 can be guided toward the target landing point 2 by using the relative position (X_{GPS} ,
 40 Y_{GPS}) based on position coordinates obtained by using the GPS when the vertical take-off and landing aircraft 1 and the target landing point 2 are separated to the extent that the target landing point 2 cannot be captured by the

5 camera 10. Additionally, when the target landing point 2 can be captured by the camera 10, the control mode can be shifted to the high altitude hovering mode under the condition that the relative position (X, Y) calculated by the image processing is within the first threshold value.

[0063]

10 Furthermore, when a time period for which the marker 7 cannot be continuously captured by the camera 10 is longer than or equal to a predetermined time period during execution of each control mode, the control unit 30 (the guidance calculation unit 34) shifts the control mode to the emergency mode in which the altitude of the vertical take-off and landing
15 aircraft 1 is raised to a predetermined altitude. This configuration allows the vertical take-off and landing aircraft 1 to be separated from the marine vessel 5 once due to the emergency mode in a case where the time period for which the marker 7 cannot be captured by the camera 10 continues for a long period and it is determined that the vertical take-off and landing aircraft 1 cannot be
20 controlled based on the relative position (X, Y) obtained by the image processing.

[0064]

Note that in the first embodiment, the approach mode button, the high altitude hovering mode button, the low altitude hovering mode button, the
25 landing mode button, and the emergency mode button are provided on the operation display unit 90 of the marine vessel 5, and are operated by the operator of the marine vessel 5, but in a case where the vertical take-off and landing aircraft 1 is a manned aircraft, these various mode buttons may be provided in the vertical take-off and landing aircraft 1 and may be operated by a
30 pilot.

[0065]

Also in the first embodiment, the flight of the vertical take-off and landing aircraft 1 to the target landing point 2 is performed by the approach mode, but step S1 illustrated in FIG. 4 may be omitted and the vertical take-off
35 and landing aircraft 1 may be caused to fly toward the target landing point 2 by a manual operation.

[0066]

Second Embodiment

Next, an automatic landing system 200 and a landing control method for
40 a vertical take-off and landing aircraft 1 according to a second embodiment will be described. FIG. 10 is a schematic configuration diagram illustrating an example of an automatic landing system for a vertical take-off and landing

5 aircraft 1 according to the second embodiment. The automatic landing system 200 according to the second embodiment is a configuration in which the data transmission device 40 is omitted from the automatic landing system 100, as illustrated in FIG. 10. In addition, the automatic landing system 200 includes a guidance calculation unit 34A in place of the guidance calculation unit 34.

10 Other configurations of the automatic landing system 200 are similar to those of the automatic landing system 100, and thus descriptions are omitted and the same constituent elements are denoted by the same reference signs. In addition, except for that described below, the guidance calculation unit 34A has functions similar to those of the guidance calculation unit 34, and thus, descriptions of

15 such similar functions are omitted.

[0067]

Additionally, in the second embodiment, the marine vessel 5 need not include the data transmission device 80 and the operation display unit 90. Note that in FIG. 10, the navigation system 70 is omitted because exchange of data

20 acquired by the navigation system 70 is not required between the vertical take-off and landing aircraft 1 and the marine vessel 5.

[0068]

In the second embodiment, the automatic landing system 200 does not perform data communication with the marine vessel 5 side. Thus, in calculating

25 the relative velocity, it is not possible to acquire a hull velocity from the marine vessel 5. Thus, in the second embodiment, the guidance calculation unit 34 calculates the relative velocity based on a relative position (X, Y) between the vertical take-off and landing aircraft 1 and the target landing point 2. Specifically, the guidance calculation unit 34A calculates the relative velocity

30 by a pseudo differential of the relative position (X, Y).

[0069]

Next, details of the landing control method of the second embodiment will be described. In the second embodiment, the guidance calculation unit 34A does not perform the processing of step S1 in the flowchart illustrated in FIG. 4,

35 and causes the vertical take-off and landing aircraft 1 to approach the marine vessel 5, that is, the target landing point 2 to the extent that the marker 7 is captured in the coverage area B of the camera 10 by another method. Examples of the other method include a method in which a laser irradiation device is mounted on the vertical take-off and landing aircraft 1, laser light is emitted

40 toward the marine vessel 5 and a reflection wave of the laser light is received on the vertical take-off and landing aircraft 1 side, whereby the relative position between the vertical take-off and landing aircraft 1 and the marine vessel 5 is

5 acquired and the vertical take-off and landing aircraft 1 is guided to the marine vessel 5 (target landing point 2) based on the relative position.
[0070]

When the vertical take-off and landing aircraft 1 is sufficiently close to the marine vessel 5, that is, the target landing point 2 to the extent that the
10 marker 7 is captured in the coverage area B of the camera 10, the guidance calculation unit 34A calculates a relative position (X, Y) by processing similar to that in step S14 in the relative position calculation processing with an image illustrated in FIG. 10 and, when the calculated relative position (X, Y) is within the first threshold value, performs the processing illustrated in FIG. 12 and FIG.
15 13 instead of the processing in step S2 (FIG. 7) and step S3 (FIG. 8) in FIG. 4. FIG. 12 is a flowchart illustrating an example of a processing procedure in a high altitude hovering mode according to the second embodiment. FIG. 13 is a flowchart illustrating an example of a processing procedure in a low altitude hovering mode according to the second embodiment.
20 [0071]

The high altitude hovering mode in the second embodiment will be described with reference to FIG. 12. In step S41A and step S42A in FIG. 11, processing is similar to that in step S41 and step S42 in FIG. 7, and thus, description thereof is omitted. Note that in the second embodiment, the relative
25 position calculation processing with an image is similar to that illustrated in FIG. 10.
[0072]

As a step S43A, the guidance calculation unit 34A determines whether the relative position (X, Y) calculated in step S42A, attitude rates (in a pitch
30 direction and a roll direction) of the vertical take-off and landing aircraft 1, and the relative velocity are within corresponding first determination threshold values. The corresponding first determination threshold value of the relative position (X, Y) is the second threshold value in the first embodiment. In addition, the corresponding first determination threshold values of the attitude
35 rates and the relative velocity are individually set for each parameter. The first determination threshold values that correspond to the attitude rates and the relative velocity are provided in place of the condition that the operator turns on the low altitude hovering mode button in the first embodiment. Thus, the first determination threshold values that correspond to the attitude rates and the
40 relative velocity are set to satisfy that the vertical take-off and landing aircraft 1 is considered to stably fly at the first relative altitude Δh_1 .
[0073]

5 When the guidance calculation unit 34A determines that the relative position (X, Y) is not within the corresponding first determination threshold value, that is, a second threshold value (NO in step S43A), the guidance calculation unit 34A performs the processing of step S41A and subsequent steps again. Furthermore, also in a case where the guidance calculation unit 34A
10 determines that the attitude rates and the relative velocity are not within the corresponding first determination threshold values (NO in step S43A), the guidance calculation unit 34A performs the processing of step S41A and subsequent steps again.

[0074]

15 On the other hand, in a case where the relative position (X, Y) is within the second threshold value, and the attitude rates and the relative velocity are within the corresponding first determination threshold values (YES in step S43A), the guidance calculation unit 34A ends the high altitude hovering mode and shifts the control mode to the low altitude hovering mode. Step S43A is for
20 determining whether a first condition for transition from the high altitude hovering mode to the low altitude hovering mode is satisfied. That is, in the second embodiment, the first condition includes, in addition to the condition that the relative position (X, Y) is within the second threshold value, a condition that the attitude rates and the relative velocity are within the
25 corresponding first determination threshold values.

[0075]

 The low altitude hovering mode in the second embodiment will be described with reference to FIG. 13. Processing in step S51A and step S52A in FIG. 13 is similar to the processing in step S51 and step S52 in FIG. 8 in the
30 first embodiment, and thus, description thereof is omitted.

[0076]

 The guidance calculation unit 34A determines, as a step S53A, whether the relative position (X, Y) calculated in step S52A, the attitude rates (in the pitch direction and the roll direction) of the vertical take-off and landing
35 aircraft 1, a relative heading, a relative velocity, the attitude angles (in the pitch direction and the roll direction), angles (in the pitch direction and the roll direction) in a horizontal direction of the target landing point 2, and the relative altitude Δh are within corresponding second determination threshold values. The corresponding second determination threshold value of the relative position
40 (X, Y) is the third threshold value in the first embodiment. Additionally, the second determination threshold value of the relative altitude Δh is the second relative altitude Δh_2 . The second determination threshold value of the relative

5 altitude Δh is provided in order to automatically determine that the vertical take-off and landing aircraft 1 has descended to the second relative altitude Δh_2 and is stable in the low altitude hovering mode.

[0077]

Moreover, the corresponding second determination threshold values of
 10 the attitude rates of the vertical take-off and landing aircraft 1, the relative heading, the relative velocity, the attitude angles, and the angles in the horizontal direction of the target landing point 2 are individually set for each parameter. Note that the angles in the horizontal direction of the target landing point 2 are angles in the horizontal direction of the surface on which the target
 15 landing point 2 of the marine vessel 5 is provided, and can be calculated by performing image processing on an image of the marker 7 captured by the camera 10 in the image processing unit 32. The second determination threshold values corresponding to the attitude rates, the relative heading, the relative velocity, the attitude angles, and the angles in the horizontal direction of the
 20 target landing point 2 are provided instead of the condition that an operator turns on the landing mode button in the first embodiment. Thus, the second determination threshold values corresponding to the attitude rates, the relative heading, the relative velocity, the attitude angles, and the angles in the horizontal direction of the target landing point 2 are set to satisfy that the
 25 vertical take-off and landing aircraft 1 is regarded as being able to stably fly at the second relative altitude Δh_2 . Note that the second determination threshold values of the attitude rates and the relative velocity may be values smaller than the first determination threshold values, or may be the same values as the first determination threshold values.

30 [0078]

When the guidance calculation unit 34A determines that the relative position (X, Y) is not within the corresponding second determination threshold value, that is, the third threshold value (NO in step S53A), the guidance calculation unit 34A executes the processing of step S51A and subsequent steps
 35 again. Additionally, when the guidance calculation unit 34A determines that the relative altitude Δh is not within the corresponding first determination threshold value, that is, the second relative altitude Δh_2 (NO in step S53A), the guidance calculation unit 34A executes the processing of step S51A and subsequent steps again. Furthermore, also in a case where the guidance calculation unit 34A
 40 determines that the attitude rates, the relative heading, the relative velocity, the attitude angles, and the angles in the horizontal direction of the target landing point 2 are not within the corresponding second determination threshold values

5 (NO in step S53A), the guidance calculation unit 34A executes the processing of step S51A and subsequent steps again.

[0079]

On the other hand, when the guidance calculation unit 34A determines that the relative position (X, Y) is within the second determination threshold value, that is, the third threshold value, the relative altitude Δh is within the second relative altitude Δh_2 , and the attitude rates, the relative heading, the relative velocity, the attitude angles, and the angles in the horizontal direction of the target landing point 2 are within the corresponding second determination threshold values (YES in step S53A), the guidance calculation unit 34A ends the low altitude hovering mode and shifts the control mode to the landing mode. Step S53A is for determining whether a second condition (a predetermined condition) for shifting from the low altitude hovering mode to the landing mode is satisfied. That is, in the second embodiment, the second condition includes, in addition to the condition that the relative position (X, Y) is within the third threshold value, a condition that the attitude rates, the relative heading, the relative velocity, the attitude angles, the angles in the horizontal direction of the target landing point 2, and the relative altitude Δh are within the corresponding second determination threshold values.

[0080]

25 Operational Effects of Second Embodiment

As described above, the automatic landing system 200 for a vertical take-off and landing aircraft according to the second embodiment can calculate the relative position (X, Y) based on the marker 7 captured by the camera 10, and can calculate the relative velocity based on the relative position (X, Y). Thus, in calculating the relative position (X, Y) and the relative velocity, data communication with the marine vessel 5 side is not required. Thereby, when the vertical take-off and landing aircraft 1 is controlled based on the relative position (X, Y) and the relative velocity, the system can be simplified because data communication is not required.

35 [0081]

Also, in the second embodiment, the first condition includes a condition that the attitude rates of the vertical take-off and landing aircraft 1 and the relative velocity are within the corresponding first determination threshold values. With this configuration, a transition instruction from an operator is not required, and the control mode can be automatically shifted from the high altitude hovering mode to the low altitude hovering mode while the vertical take-off and landing aircraft 1 is caused to stably fly. Thus, there is no need to

5 exchange data with the marine vessel 5 when the control mode is shifted from the high altitude hovering mode to the low altitude hovering mode.
[0082]

The second condition includes a condition that the attitude angles of the vertical take-off and landing aircraft 1, the attitude rates, the relative heading,
10 the relative velocity, the angles in the horizontal direction of the target landing point 2, and the relative altitude Δh are within the corresponding second determination threshold values. With this configuration, a transition instruction from an operator is not required, and the control mode can be automatically shifted from the low altitude hovering mode to the landing mode while the
15 vertical take-off and landing aircraft 1 is caused to stably fly. Thus, when the control mode is shifted from the low altitude hovering mode to the landing mode, there is no need to exchange data with the marine vessel 5.
[0083]

Third Embodiment

20 Next, an automatic landing system 300 and a landing control method for the vertical take-off and landing aircraft 1 according to a third embodiment will be described. FIG. 14 is a schematic configuration diagram illustrating an automatic landing system according to the third embodiment. As illustrated in FIG. 14, the automatic landing system 300 according to the third embodiment
25 includes an image processing unit 32B and a guidance calculation unit 34B instead of the image processing unit 32 and the guidance calculation unit 34A of the automatic landing system 200 according to the second embodiment, respectively. Other configurations of the automatic landing system 300 are similar to those of the automatic landing system 200, and thus descriptions are
30 omitted and the same constituent elements are denoted by the same reference signs. In addition, the image processing unit 32B and the guidance calculation unit 34B have functions similar to those of the image processing unit 32 and the guidance calculation unit 34, except for portions that will be described below, and thus, descriptions of the similar functions are omitted.
35 [0084]

Further, in the third embodiment, the marine vessel 5 need not include the data transmission device 80 and the operation display unit 90, similarly to the second embodiment. Note that in FIG. 14, the navigation system 70 is omitted because exchange of data acquired by the navigation system 70 is not
40 required between the vertical take-off and landing aircraft 1 and the marine vessel 5. Further, in the third embodiment, the marine vessel 5 includes an operation display unit 95 connected to the marker 7. Furthermore, in the third

5 embodiment, the marker 7 is displayed on a display device (not illustrated) such as a liquid crystal display, and the shape of the marker is variable. The marker 7 includes at least a shape for instructing transition from the high altitude hovering mode to the low altitude hovering mode, and a shape for instructing transition from the low altitude hovering mode to the landing mode.

10 [0085]

The image processing unit 32B performs image processing on an image captured by the camera 10 to identify the shape of the marker 7 in the image, and outputs an instruction based on the identified shape to the guidance calculation unit 34B. Specifically, in a case where the image processing unit 15 32B identifies that the marker 7 is shaped to instruct transition from the high altitude hovering mode to the low altitude hovering mode, the image processing unit 32B outputs a transition instruction to transition from the high altitude hovering mode to the low altitude hovering mode to the guidance calculation unit 34B. Additionally, in a case where the image processing unit 32B identifies 20 that the marker 7 is shaped to instruct transition from the low altitude hovering mode to the landing mode, the image processing unit 32B outputs a transition instruction to transition from the low altitude hovering mode to the landing mode to the guidance calculation unit 34B.

[0086]

25 The guidance calculation unit 34B calculates relative velocity in a manner similar to that of the guidance calculation unit 34A according to the second embodiment. As a result, as in the second embodiment, the relative velocity can be acquired without acquiring a hull velocity from the marine vessel 5.

30 [0087]

Next, a landing control method according to the third embodiment will be described. In the third embodiment, as in the second embodiment, the guidance calculation unit 34B does not perform the processing from step S1 to step S3 of the flowchart illustrated in FIG. 4, and causes the vertical take-off and landing aircraft 1 to approach the marine vessel 5, that is, the target landing 35 point 2 to the extent that the marker 7 is captured in the coverage area B of the camera 10 by another method. Then, when the vertical take-off and landing aircraft 1 is sufficiently close to the marine vessel 5, that is, the target landing point 2 to the extent that the marker 7 is captured in the coverage area B of the camera 10, the guidance calculation unit 34B calculates a relative position (X, Y) by processing similar to that in step S14 in the relative position calculation processing with an image illustrated in FIG. 10, and when the calculated 40

5 relative position (X, Y) is within a first threshold value, the guidance
 calculation unit 34B executes the processing illustrated in FIG. 15 and FIG. 16
 instead of the processing in step S2 (FIG. 7) and step S3 (FIG. 8) in FIG. 4. FIG.
 15 is a flowchart illustrating an example of a processing procedure in the high
 altitude hovering mode according to the third embodiment. FIG. 16 is a
 10 flowchart illustrating an example of a processing procedure in the low altitude
 hovering mode according to the third embodiment.
 [0088]

The high altitude hovering mode according to the third embodiment will
 be described with reference to FIG. 15. Processing in step S41B and step S42B
 15 in FIG. 15 is similar to that in step S41 and step S42 in FIG. 8, and thus,
 description thereof is omitted. Note that, in the third embodiment, the relative
 position calculation processing with an image is similar to the processing
 illustrated in FIG. 10.
 [0089]

20 As a step S43B, the guidance calculation unit 34B determines whether
 the relative position (X, Y) calculated in step S42B is within the second
 threshold value and whether the marker 7 is shaped to indicate transition to the
 low altitude hovering mode. The determination of whether the marker 7 is
 shaped to indicate transition to the low altitude hovering mode is provided
 25 instead of the condition that the operator turns on the low altitude hovering
 mode button in the first embodiment. The operator visually checks whether the
 vertical take-off and landing aircraft 1 can stably fly at the first relative altitude
 $\Delta h1$, and changes the marker 7 to have a shape indicating transition to the low
 altitude hovering mode by using the operation display unit 95 in the case where
 30 the vertical take-off and landing aircraft 1 can stably fly.
 [0090]

When the guidance calculation unit 34B determines that the relative
 position (X, Y) is not within the corresponding second threshold value (NO in
 step S43B), the guidance calculation unit 34B performs the processing of step
 35 S41B and subsequent steps again. In addition, also in a case where the guidance
 calculation unit 34B determines that the marker 7 does not have the shape
 indicating transition to the low altitude hovering mode (NO in step S43B), the
 guidance calculation unit 34B performs the processing of step S41B and
 subsequent steps again. This controls the flight of the vertical take-off and
 40 landing aircraft 1 by feedback control, as in the first embodiment, such that the
 relative position (X, Y) with respect to the target landing point 2 is within the
 second threshold value, and the first relative altitude $\Delta h1$ is maintained.

5 [0091]

When the guidance calculation unit 34B determines that the relative position (X, Y) is within the second threshold value and the marker 7 has the shape indicating transition to the low altitude hovering mode (YES in step S43B), the guidance calculation unit 34B ends the high altitude hovering mode
10 and shifts the control mode to the low altitude hovering mode. In the third embodiment, in step S43B, whether a first condition for the transition from the high altitude hovering mode to the low altitude hovering mode is satisfied is determined. That is, in the third embodiment, the first condition includes, in addition to the condition that the relative position (X, Y) is within the second
15 threshold value, a condition that the marker 7 is shaped to indicate transition to the low altitude hovering mode.

[0092]

The low altitude hovering mode in the third embodiment will be described with reference to FIG. 16. Processing in step S51B and step S52B in
20 FIG. 16 is similar to the processing in step S51 and step S52 in FIG. 8 in the first embodiment, and thus, description thereof is omitted.

[0093]

As a step S53B, the guidance calculation unit 34B determines whether the relative position (X, Y) calculated in the step S52B is within the third
25 threshold value and whether the marker 7 is shaped to indicate transition to the landing mode. The determination of whether the marker 7 is shaped to indicate transition to the landing mode is provided instead of the condition that the operator turns on the landing mode button in the first embodiment. An operator visually checks whether the vertical take-off and landing aircraft 1 can stably
30 fly at the second relative altitude Δh_2 , and changes the marker 7 to a shape indicating transition to the landing mode by using the operation display unit 95 in a case where the vertical take-off and landing aircraft 1 can stably fly.

[0094]

When the guidance calculation unit 34B determines that the relative
35 position (X, Y) is not within the corresponding second threshold value (NO in step S53B), the guidance calculation unit 34B performs the processing of step S51B and subsequent steps again. In addition, also in a case where the guidance calculation unit 34B determines that the marker 7 is not shaped to indicate transition to the landing mode (NO in step S53B), the guidance calculation unit
40 34B performs the processing of step S51B and subsequent steps again. This controls the flight of the vertical take-off and landing aircraft 1 by feedback control, as in the first embodiment, such that the relative position (X, Y) with

5 respect to the target landing point 2 is within the third threshold value, and the second relative altitude Δh_2 is maintained.

[0095]

When the guidance calculation unit 34B determines that the relative position (X, Y) is within the third threshold value and the marker 7 is shaped to
10 indicate transition to the landing mode (YES in step S53B), the guidance calculation unit 34B ends the low altitude hovering mode and shifts the control mode to the landing mode. In the third embodiment, in the step S53B, whether a second condition (a predetermined condition) for transitioning from the low altitude hovering mode to the landing mode is satisfied is determined. That is,
15 in the third embodiment, the second condition includes, in addition to the condition that the relative position (X, Y) is within the third threshold value, a condition that the marker 7 is shaped to indicate transition to the landing mode.

[0096]

Operational Effects of Third Embodiment

20 As described above, the automatic landing system 300 of the vertical take-off and landing aircraft according to the third embodiment does not need to perform data communication with the marine vessel 5 side in calculating the relative position (X, Y) and the relative velocity. Thereby, when the vertical take-off and landing aircraft 1 is controlled based on the relative position (X, Y)
25 and the relative velocity, the system can be simplified because data communication is not required.

[0097]

In addition, in the third embodiment, the marker 7 has a variable marker shape, and the first condition and the second condition include a condition that
30 the marker shape is a shape indicating a mode transition. This configuration allows the transition from the high altitude hovering mode to the low altitude hovering mode, and the transition from the low altitude hovering mode to the landing mode to be performed based on a change in the marker shape without receiving an instruction of the mode transition from the operator through data
35 communication. Thus, when the transition from the high altitude hovering mode to the low altitude hovering mode, and the transition from the low altitude hovering mode to the landing mode are performed, data communication with the marine vessel 5 is not required, the mode transition can be instructed without communication, and the mode transition can be instructed even under an
40 environment where a radio wave is shielded, for example.

[0098]

[0099]

- | | | |
|----|---------------|--|
| | 1 | Vertical take-off and landing aircraft |
| | 2 | Target landing point |
| | 5 | Marine vessel |
| 20 | 7 | Marker |
| | 10 | Camera |
| | 20, 70 | Navigation system |
| | 25 | Altitude sensor |
| | 30 | Control unit |
| 25 | 32, 32B | Image processing unit |
| | 34, 34A, 34B | Guidance calculation unit |
| | 36 | Flight control unit |
| | 40, 80 | Data transmission device |
| | 90, 95 | Operation display unit |
| 30 | 100, 200, 300 | Automatic landing system |

5 Claims

[Claim 1]

An automatic landing system for a vertical take-off and landing aircraft,
the automatic landing system comprising:

10 an imaging device mounted on the vertical take-off and landing aircraft;
a relative-position acquisition unit configured to perform image

processing on an image, of a marker provided on a target landing point,
captured by the imaging device, and configured to acquire a relative position
between the vertical take-off and landing aircraft and the target landing point;

15 a relative-altitude acquisition unit configured to acquire a relative
altitude between the vertical take-off and landing aircraft and the target landing
point; and

a control unit configured to control the vertical take-off and landing
aircraft in a plurality of control modes such that the relative position becomes
20 zero, wherein

the plurality of control modes include a hovering mode and a landing
mode,

the hovering mode is executed within a first threshold value at which the
relative position is within a range of the target landing point, the relative
25 altitude of the vertical take-off and landing aircraft is lowered to a
predetermined relative altitude, and when a predetermined condition including a
condition that the relative position is within a predetermined threshold value
that is less than the first threshold value is satisfied, the control mode is shifted
to the landing mode, and

30 in the landing mode, the relative altitude of the vertical take-off and
landing aircraft is further lowered to land the vertical take-off and landing
aircraft on the target landing point.

[Claim 2]

35 The automatic landing system for a vertical take-off and landing aircraft
according to claim 1, further comprising:

a relative-velocity acquisition unit configured to acquire a relative
velocity between the vertical take-off and landing aircraft and the target landing
point, wherein

40 the control unit controls the vertical take-off and landing aircraft in a
plurality of control modes such that the relative velocity is within a
predetermined velocity.

5

[Claim 3]

The automatic landing system for a vertical take-off and landing aircraft according to claim 1 or 2, wherein

10 in the landing mode, when the relative altitude is less than or equal to a predetermined value, the vertical take-off and landing aircraft is caused to descend without changing an attitude angle of the vertical take-off and landing aircraft.

[Claim 4]

15 The automatic landing system for a vertical take-off and landing aircraft according to any one of claims 1 to 3, wherein

the hovering mode includes a high altitude hovering mode and a low altitude hovering mode,

20 in the high altitude hovering mode, the relative altitude of the vertical take-off and landing aircraft is maintained at a first relative altitude that is higher than the predetermined relative altitude, and when a first condition including a condition that the relative position is within a second threshold value is satisfied, the control mode is shifted to the low altitude hovering mode, and

25 in the low altitude hovering mode, the relative altitude of the vertical take-off and landing aircraft is lowered to the predetermined relative altitude, and when a second condition as the predetermined condition including a condition that the relative position is within the predetermined threshold value is satisfied, the control mode is shifted to the landing mode.

30

[Claim 5]

The automatic landing system for a vertical take-off and landing aircraft according to claim 4, wherein

35 the first condition and the second condition include a condition that a mode transition is instructed by an operator.

[Claim 6]

The automatic landing system for a vertical take-off and landing aircraft according to claim 4, wherein

40 the first condition includes a condition that an attitude rate of the vertical take-off and landing aircraft and a relative velocity between the vertical take-off

5 and landing aircraft and the target landing point are within corresponding first determination threshold values.

[Claim 7]

10 The automatic landing system for a vertical take-off and landing aircraft according to claim 4 or 6, wherein

the second condition includes a condition that an attitude angle of the vertical take-off and landing aircraft, an attitude rate, a relative velocity between the vertical take-off and landing aircraft and the target landing point, an angle in a horizontal direction of the target landing point, and the relative
15 altitude are within corresponding second determination threshold values.

[Claim 8]

The automatic landing system for a vertical take-off and landing aircraft according to claim 4, wherein

20 the marker has a marker shape being variable, and

the first condition and the second condition include a condition that the marker shape is a shape indicating a mode transition.

[Claim 9]

25 The automatic landing system for a vertical take-off and landing aircraft according to any one of claims 1 to 8, further comprising:

a position measuring unit configured to acquire position coordinates of the vertical take-off and landing aircraft;

a data transmission device configured to exchange data between the
30 vertical take-off and landing aircraft and a facility provided with the target landing point; and

a second relative-position acquisition unit configured to calculate a relative position between a position of the vertical take-off and landing aircraft acquired by the position measuring unit and a position of the target landing
35 point based on the position coordinates of the vertical take-off and landing aircraft acquired by the position measuring unit and position coordinates of the facility provided with the target landing point acquired by the data transmission device, wherein

the plurality of control modes include an approach mode, and

40 in the approach mode, the vertical take-off and landing aircraft is caused to fly toward the target landing point based on the relative position acquired by the second relative-position acquisition unit and, when the relative position

5 acquired by the relative-position acquisition unit is within the first threshold value, the control mode is shifted to the hovering mode.

[Claim 10]

10 The automatic landing system for a vertical take-off and landing aircraft according to any one of claims 1 to 9, wherein
 when a time period for which the marker cannot be captured by the imaging device continues longer than or equal to a predetermined time period during execution of the hovering mode, the control unit shifts the control mode to an emergency mode in which an altitude of the vertical take-off and landing
15 aircraft is raised to a predetermined altitude.

[Claim 11]

 A vertical take-off and landing aircraft comprising:
 the automatic landing system for a vertical take-off and landing aircraft
20 according to any one of claims 1 to 10.

[Claim 12]

 A landing control method for a vertical take-off and landing aircraft, the method comprising:
25 performing image processing on an image, of a marker provided to a target landing point, captured by an imaging device mounted on the vertical take-off and landing aircraft, and acquiring a relative position between the vertical take-off and landing aircraft and the target landing point;
 acquiring a relative altitude between the vertical take-off and landing
30 aircraft and the target landing point; and
 controlling the vertical take-off and landing aircraft in a plurality of control modes such that the relative position becomes zero, wherein
 the plurality of control modes include a hovering mode and a landing mode,
35 the hovering mode is executed within a first threshold value at which the relative position is within a range of the target landing point, the relative altitude of the vertical take-off and landing aircraft is lowered to a predetermined relative altitude, and when a predetermined condition including a condition that the relative position is within a predetermined threshold value
40 that is less than the first threshold value is satisfied, the control mode is shifted to the landing mode, and

- 5 in the landing mode, the relative altitude of the vertical take-off and landing aircraft is further lowered to land the vertical take-off and landing aircraft on the target landing point.