(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number
WO 2004/004194 A3

(51) International Patent Classification[7]: H04L 1/00

(21) International Application Number:
PCT/IB2003/002784

(22) International Filing Date: 17 June 2003 (17.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02014411.9 28 June 2002 (28.06.2002) EP

(71) Applicant *(for all designated States except US)*: **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NY 10504 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **JELITTO, Jens** [DE/CH]; Saeumerstrasse 11, CH-8803 Rueschlikon (CH). **NOLL BARRETO, Andre** [BR/BR]; R. Gustavo Sampaio 194 ap. 303, CEP-22010-010 Rio de Janeiro, RJ (BR). **TRUONG, Hong, Linh** [DE/CH]; Rifertstrasse 30b, CH-8134 Adliswil (CH).


(74) Agents: **KLETT, Peter, M.** et al.; International Business Machines Corporation, Saeumerstrasse 4 / Postfach, CH-8803 Rueschlikon (CH).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: LINK ADAPTATION



(57) Abstract: The present invention discloses an apparatus and method for adapting a transmission parameter in a transmitting node of a data communication system to the current link quality of a data communication channel. The adapted transmission parameter is selected by the transmitting node from a set of transmission parameters in dependence on a number of successful transmissions. The number of successful transmissions is compared in the transmitting node against one of a first threshold value corresponding to a first state of the transmitting node and a second threshold value corresponding to a second state of the transmitting node. The method comprises in the transmitting node the steps of (a) counting the number of successful transmissions; (b) selecting the adapted transmission parameter (bl) in response to the number of successful transmissions equaling or exceeding the first threshold value when the transmitting node is in the first state, and (b2) in response to the number of successful transmissions equaling or exceeding the second threshold value when the transmitting node is in the second state; and in dependence of the result of a following transmission, operating the transmitting node in one of the first state and the second state.

WO 2004/004194 A3

Published:
— *with international search report*

(88) Date of publication of the international search report:
4 March 2004

(48) Date of publication of this corrected version:
8 April 2004

(15) Information about Correction:
see PCT Gazette No. 15/2004 of 8 April 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.