

PATENT SPECIFICATION

(11) 1 240 531

DRAWINGS ATTACHED

- (21) Application No. 35635/68 (22) Filed 25 July 1968
(3) Convention Application No. 655 850 (32) Filed 25 July 1967 in
(33) United States of America (US)
(45) Complete Specification published 28 July 1971
(51) International Classification G 03 b 17/17
(52) Index at acceptance
G2A 2A4 2AX1 D20G2



(54) IMPROVEMENTS RELATING TO PHOTOGRAPHIC APPARATUS

(71) We, INTERNATIONAL POLAROID CORPORATION, a corporation organised and existing under the laws of the State of New Jersey, United States of America, of 1 Exchange Place, Jersey City, New Jersey, United States of America, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention is concerned with a photographic camera of the self-developing type and with an arrangement of parts in such a camera which enables the camera to be of compact construction. A camera of the self-developing type includes means for at least initiating the processing of a suitable film unit which has been exposed within the camera. As an example, such a camera may include means for holding a number of photographic film units, successively positioning the film units for exposure, exposing each film unit and processing an exposed film unit to form a visible image by advancing it between a pair of pressure-applying members to distribute a liquid processing combination within the film unit.

According to the present invention, the camera comprises a housing within which are means for positioning a photosensitive element at a focal plane of the camera, processing means mounted adjacent a first end of the focal plane, a mirror orientated at an angle of less than 45° to the focal plane and positioned so as to diverge from the focal plane in the direction from the other end of that plane towards the first end, a photographic objective lens positioned near the first end of the focal plane and orientated so that its optical axis is inclined at an angle of less than 45° to the focal plane and diverges from the latter in the direction from the first end of the focal plane to the other end, the lens directing

image light incident upon it on to the focal plane by reflection from the mirror, and means for moving the photosensitive element into engagement with the processing means.

This construction permits the location of the lens fairly close to the film plane; in the conventional arrangement of a camera employing a mirror, the mirror is arranged at 45° with respect to the lens axis and film plane and the lens is located equidistant from the mirror and film plane. The arrangement embodying the invention leads to a more compact camera and is particularly well adapted to a folding camera, that is to say one which folds from an operative or extended position to a collapsed or transport position.

The preferred form of camera embodying the invention is a folding camera including at least three and preferably four relatively movable housing sections, the positioning means for the photosensitive element being located in one housing section and the lens and mirror being located in two different housing sections. In this form of camera, the thickness dimension of the camera, when collapsed to its transport condition, is governed by one of the major dimensions of the objective lens, for example the front-to rear thickness of the lens. The camera may fold to a condition in which the lens axis is perpendicular to the focal plane, the housing sections for the photosensitive element and lens being in line with one another and the housing section for the mirror being so positioned that the mirror lies parallel with the photosensitive element. The width dimension of the collapsed camera may be only slightly greater than the width of a film unit containing the photosensitive element and the length dimension may be the length of the film unit plus a small amount for a compact shutter mechanism.

For a fuller understanding of the nature

[Price 25p]

and objects of the invention, reference should be had to the following detailed description taken in connection with the accompanying drawings wherein:

5 Figure 1 is a perspective view of a camera embodying the invention in an operative or extended condition;

Fig. 2 is a perspective view of the camera illustrated in a folded or transport condition;

10 Fig. 3 is a sectional view of the camera, the section being taken between the sides of the camera and the camera being illustrated with a film pack in operative position in the camera;

Fig. 4 is an enlarged sectional view similar to Fig. 3 showing a portion of the camera;

Fig. 5 is a perspective view of components of the camera and a film pack;

20 Fig. 6 is an enlarged perspective view of components of the camera; and

Fig. 7 is a circuit diagram showing an electrical circuit for controlling the operation of the camera.

25 In Figs. 1 to 4 there is shown a camera, generally designated 10, comprising a housing including a first section 12, a second section 14, a third section 16, and a fourth section 18. The first housing section 12 may be characterized as the rear housing section and includes means for holding an assemblage or pack of film units with one of the film units located in position for exposure. The first housing section is pivotally connected at one end to one end of second housing section 14 at a hinge 20 and near its opposite end to third housing section 16 at pivots 22, the location of which will be described more fully hereafter. Housing sections 14 and 16 are coupled at hinges 24 and 26 respectively to fourth housing section 18 so that the four housing sections form, in effect, a four-bar linkage which is movable between an extended or operative position (see Figure 1) in which the housing sections are spaced apart to provide four sides of a chamber, and a folded or transport position (shown in Fig. 2) in which the first and third housing sections are located beside one another substantially in a line and the second and fourth housing sections are located in line with one another and in face-to-face adjacency with the first and third housing sections.

55 The first housing section 12 essentially comprises a generally rectangular rear wall 28 (Figure 3), the dimensions of which are slightly greater than the dimensions of the film pack adapted to be employed in the camera, dependent side walls 30 and 32 and a door 34 provided about hinge 20 which is supported at its ends on side walls 30 and 32. Door 34, which forms a part of rear wall 28 and an end wall for the rear housing section, is retained in the closed position

by a latch 36 and may be opened to permit loading of a film pack into the camera housing.

The camera is adapted to be employed with film assemblage or film pack 40 (Figures 4 and 5) including a plurality of film unit 42 preferably of the type shown and described in detail in British Patents Nos. 1,224,371 and 1,224,372. Film units of this type each incorporates all of the materials necessary to produce a positive photographic print including a photosensitive element 44, a second or image-receiving element 46 which is transparent and is secured in face-to-face relation with the photosensitive element, and a rupturable container 48 of processing liquid secured to one end of the photosensitive and second elements for dispensing its liquid contents therebetween in response to the application of compressive pressure to the container. Each film unit is adapted to be processed by advancing the film unit, container foremost, between a pair of pressure-applying members which dispense the liquid contents of the container therefrom between the photosensitive and second elements and spread the liquid between and in contact with the two elements toward the trailing end thereof. The image-forming process is well-known in the art and involves the formation of transferable image-forming substances in the exposed photosensitive element and diffusion of the image-forming substances to another layer within the film unit where they are deposited to form a visible, positive image. In the particular example shown herein and described in the aforementioned applications, the processing liquid includes an opacifying agent which is spread in a layer between the photosensitive element, which is preferably opaque to actinic light, and the transparent image-receiving element 46 for providing a background for the positive transfer image which serves to mask any image formed in the photosensitive element.

Camera size can be reduced and a higher degree of compactness achieved by eliminating the necessity for a processing or imbibition chamber in the camera in which the film unit is advanced and retained in a light-free environment during image formation. Accordingly, the film unit is designed to be advanced from the camera into the light immediately as the processing liquid is distributed within the film unit which means that spreading of the processing liquid must be effective to prevent further exposure of the photosensitive elements almost immediately as it (liquid spreading) occurs. The opacifying agent in the processing liquid functions to prevent exposure of the photosensitive element to light transmitted by the transparent second element 46.

A number of film units 42 are provided in stacked relation in an opaque container 50 having a forward wall 52 provided with an exposure aperture 54 substantially co-extensive in size and shape with the image to be formed and an end wall 56 formed with a slot 58 through which the film units may be moved one at a time. A spring 60 and pressure plate 62 are provided in film pack containing 50 behind the film units for supporting the forwardmost film unit in position for exposure against forward wall 52 and in alignment with exit slot 58. Openings 64 (Figure 5) are provided in forward wall 52 adjacent the side thereof and in the region of the containers 48 to enable engagement between the forwardmost film unit and a component of the camera for advancing the leading end of the forwardmost film unit from container 50 through slot 58 following the exposure of the film unit. The film pack is initially supplied with a dark slide (not shown) located between forward wall 52 and the forwardmost film unit 42 so as to cover exposure aperture 54 and prevent the exposure of the film units. The dark slide may be initially the same size as a film unit and can be withdrawn from the film pack through slot 58 in the same manner as the film unit.

As previously indicated, rear housing section 12 includes holding means for positioning film pack 40 in the camera with the forwardmost film unit 42 supported in position for exposure. In the form shown, these holding means comprise a plate 66 (Figure 4) formed with a rectangular exposure aperture 68 mounted near its end opposite door 34 for pivotal movement about a pin 70 and biased in a clockwise direction by a torsion spring 71 engaged around pin 70 which urges the end of plate 66 closest door 34, toward rear wall 28 against a stop (not shown) which locates the rear surface of plate 66 slightly forwardly of the focal surface of the camera lens so as to locate the photosensitive element of the forwardmost unit at the focal surface of the lens. Film pack 40 is thicker at the end enclosing containers 48 than it is at the opposite end and the pivotal mounting of plate 66 is provided to enable the introduction of a film pack into the camera through door 34 into the position shown in Fig. 3. The first section 12 of the camera housing also includes means for processing each film unit following exposure and in the form shown, these means comprise a pair of rolls 72 and 74 mounted in juxtaposition for rotation about axes located substantially in a plane perpendicular to rear wall 28, with the bite of the rolls located closely adjacent and in substantial alignment with slot 58 in film pack container 50. Means are provided for mounting the rolls in juxtaposition

and biasing the rolls toward one another so as to apply compressive pressure to a film unit during movement of the film unit between the rolls. In the form shown, these mounting means comprise a frame 75 shown in detail in Fig. 6 and including a transverse member 76 having two forwardly extended arms 78 at its ends in which shafts on the ends of rolls 74 are journaled. A pair of arms 80 extend from the ends of transverse member 76 toward the opposite end of the rear section of the camera housing and include forwardly extended arms 82 on which a pair of levers 84 are pivotally mounted at their ends. Roll 72 is mounted for rotation on the opposite ends of levers 84 and is biased toward roll 74 by a pair of torsion springs 85 each engaged at one end in one of arms 80 and engaged at its opposite end in a portion of one of levers 84.

A drive motor and transmission to be described more fully hereafter are provided for rotating either or both rolls 72 and 74 to advance a film unit between the rolls while applying compressive pressure to the film unit. Means are provided in the rear housing section for feeding the leading edge, (i.e., edge of container 48) of the forwardmost film unit, following the exposure thereof, through slot 58 into the bite of rolls 72 and 74 so that the latter may engage, advance, and process a film unit. These last-mentioned feeding means are illustrated as comprising a pair of friction rolls 86 (Figures 3 and 5) each mounted on one end on a lever 88 in position to engage the forwardmost film unit through openings 64 in forward wall 52 of a film pack container 50. Levers 88 are pivotally mounted on frame 75 to pivot about the same centres as arms 80, the location of these centres being indicated by the holes at the ends of the perpendicular extensions of arms 82 (Figure 6), and are biased by torsion springs 90 so as to urge friction rolls 86 rearwardly into engagement with a film unit. Rolls 86 are designed to be rotated in engagement with the forwardmost film unit to advance it into the bite of rolls 72 and 74 and for this purpose, are driven from roll 72 by an endless flexible drive coupling such as an O-ring 92. Rolls 86 are rotated during the rotation of rolls 72 and 74 and provision is made for disengaging rolls 86 from the film unit as soon as the leading edge portion of the film unit becomes engaged between rolls 72 and 74 and thereby prevent the movement of the next succeeding film unit into the bite of the pressure rolls during processing of the preceding film unit. These last-mentioned means include a pair of levers 94 each pivotally mounted intermediate its ends with one end engaged with a shaft on the end of roll 72 and the other end engaged with the end

of lever 88 opposite roll 86 for pivoting lever 88 in a clockwise direction to disengage roll 86 from the forwardmost film unit as roll 72 is displaced forwardly relative to roll 74 and frame 75 as a film unit enters the bite of rolls 72 and 74. The pivotal mounting shown multiplies the motion of rolls 86 to provide for a relatively large displacement of rolls 86 in response to a relatively small displacement of roll 72.

Rolls 72 and 74 are preferably driven by an electrically operated motor housed within one of the sections of the camera housing, coupled with roller 74 through a suitable transmission which will be described more fully hereafter, and powered by a battery (not shown) also housed within one of the sections of the camera housing, for example, mounted on door 34 so as to be located between the door and the end of film pack 40. The circuit for controlling the operation of the motor is illustrated in Fig. 7 as including the motor 96, a battery 98, and first and second switches 100 and 102 connected in parallel with one another and in series with the motor and battery. First switch 100 is manually actuated to energize motor 96 which drives rollers 72 and 74 and friction rolls 86. Switch 100 is preferably of the type which closes only momentarily, preferably for a time sufficient to feed the leading end of a film unit into the bite of rolls 72 and 74 which, in turn, advance the film unit beyond the friction rolls into the engagement with the operating lever 104 of a second switch 102 thereby closing the second switch which keeps motor 96 energized as long as a film unit is engaged with the operating lever to ensure operation of the motor and advancement of a film unit completely between rolls 72 and 74. After the trailing edge of the film unit has been advanced completely between the pressure rolls past the operating lever 104 of switch 102, the latter will open disconnecting the motor from battery 98 and terminating the processing cycle. Switch 100 may be incorporated in the shutter mechanism of the camera and coupled with a manually operable shutter-actuating element such as a shutter release button 162 (Figure 5) so as to initiate a processing cycle immediately following exposure of a film unit. It is anticipated that the processing cycle for each film unit may require a period of the order of 1/3 of a second thus making the operation of the camera semi-automatic and enabling the operator to make exposures and process the exposed film units at the relatively rapid rate of three per second and because the friction feed rolls 86 are displaced from engagement with a film unit during movement of a film unit between the processing rolls it is impossible to advance in process two film units at a time.

Third housing section 16 is generally parallelepiped shaped, is engaged between side walls 30 and 32 of first housing section 12 and is pivotable with respect to the first housing section about the axis of processing roll 74. The third housing section includes an outer wall 106 which, in the folded position of the camera housing, is disposed in essentially the same plane as rear wall 28 and in the operative position of the camera housing, functions as the forward wall of the camera; and an outer wall 108 which in the folded position of the camera constitutes an end wall of the camera and in the operative position of the camera housing sections functions as one of the upper walls of the camera housing. The third housing section also includes side walls 109 engaged between side walls 30 and 32 of the rear housing section. A conventional photographic objective lens 110 is mounted within third housing section 16 with the lens axis disposed perpendicularly to outer or forward wall 106 so that light transmitted through the lens along the lens axis is directed, in the operative position of the camera housing, away from and at an acute angle with respect to the forwardmost film unit; and in the folded position of the camera housing, the axis of lens 110 extends approximately perpendicularly to rear wall 28 and the film units. It will be noted that when the camera is folded, the minimum controlling thickness of the camera is the front-to-rear thickness of lens 110.

Second housing section 14 comprises an outer wall 120 pivotally connected at one end via hinge 20 to rear housing section 12, and dependent side walls 122 engaged between side walls 30 and 32 of the rear housing section. A substantially planar and preferably front surface, mirror 116 is mounted on the inside of wall 120 for reflecting light from lens 110 toward a film unit positioned for exposure in the rear housing section. The angle at which the axis of lens 110 intersects mirror 116 in the operative position of the camera housing is greater than 45° thus making it possible to locate lens 110 relatively closer to the focal plane of the lens, i.e., plane of the photosensitive element of the foremost film unit, than to the mirror and asymmetrically with respect to the focal plane thus providing for a smaller structure when the camera housing is extended in its operating position and the relatively thin compact structure previously described when the camera is folded and the housing sections are in a transport condition.

The camera includes a conventional view finder, generally designated 117, mounted within the second housing section adjacent one side of mirror 116 and including entrance and exit apertures provided with

mirrors 118 at opposite ends of the second housing section.

Third housing section 16 incorporates a shutter mechanism (not shown) which may include a photocell 160 and a button 162 for releasing the shutter to make an exposure and closing switch 100 to initiate a processing cycle. Drive motor 96 (Figure 5) for processing rolls 72 and 74 is also incorporated in the third housing section and is coupled with processing roll 74 via a speed-reducing transmission including gears 164, 166, 168, 170 and 172. The drive motor is preferably of a low torque, very high speed type requiring the reduction gears to provide the torque at rolls 72 and 74 necessary to advance each film unit between the rolls at the proper speed.

Fourth housing section 18 comprises an outer wall 112 pivotally connected at one side to outer wall 120 of second housing section 14 at hinge 24 and along its opposite side to wall 108 of third housing section 16 at hinge 26, and dependent side walls 114 engaged between side walls 122 of the second housing section and outside of the ends of third housing section 16 so that in the folded position of the camera housing, the second and fourth housing sections are located between side walls 30 and 32 of the first housing section and the side walls of the fourth housing section are located between the side walls of the second housing section. Wall 112 includes an opening 124 for receiving the forward end of the view finder 117 when the camera housing is folded, in which position wall 112 appears as an extension of wall 120 of the second housing section.

The fourth housing section functions essentially as a connection between the second and third housing sections, and as one side of a chamber providing a light path between lens 110 and a film unit positioned for exposure. The two remaining sides of this chamber in addition to those provided by the housing sections are each formed by fan-like bellows 126. Each of these bellows comprises a plurality of interlocking blades 128 all pivoted about a single axis and covered at their ends and along the sides of the two outermost blades by side walls 30, 109, 114, and 122. Blades 128 have generally U-shaped cross sections, are adapted to telescope into one another. The camera also includes means for retaining the camera housing in an operative or erect position and in the form shown, these means include a rigid link 129 (Figure 3) pivoted at one end on second housing section 14 engaged for pivoting and sliding movement at its other end on first housing section 12. A detent (not shown) coupled with a manually operable button is provided on the first housing section for engaging the end of link

129 to retain the latter against movement and thereby secure the housing sections in the erect position shown in Fig. 3.

The third housing section provides the forward wall of the camera (i.e., the wall facing the subject), when the latter is in an operative condition, and for preventing light from being admitted into the camera housing in the region of processing rolls 72 and 74. Film units, as they are processed, are advanced directly from the camera into the light and accordingly, outer wall 106 of the third housing section is formed with an opening 130 for passing the film units. A pair of flexible convergent lips 132 are mounted on the inside of wall 106 between the latter and the processing rolls to provide a light-tight passage through which successive film units may be advanced from the camera and prevent the emission of light into the camera. Lips 132 may also function to grip and hold the trailing end of each film unit and prevent it from falling until the operator can grasp the film unit.

A baffle 134 is pivotally mounted within and on rear housing section 12 and is pivotally biased in a clockwise direction against a stop into the operative position shown in Fig. 3 in which the baffle prevents exposure of the photosensitive element by off-axis light transmitted by the lens. When the camera housing is folded, the baffle is engaged by means on the second housing section for pivoting it in a clockwise direction to enable the housing to be completely folded.

It will be appreciated from the foregoing description a camera constructed in accordance with the invention, namely a folding camera including a lens and mirror in which the lens axis intersects the mirror at an acute angle less than 45° , is characterized by a small size compactness and small overall volume in relation to image size that is impossible with structures in which the mirror and lens axis intersects at a 45° angle at a point symmetrical with respect to the mirror and/or focal plane. This particular disposition of the lens axis relative to the mirror enables the lens to be located much more closely to the film plane than would otherwise be possible in the operative position of the camera and asymmetrically with respect thereto while contributing to a more compact structure in the folding condition. The specification has disclosed a self-developing camera having four relatively movable housing sections which is so compact that the minimum limiting thickness is the front-to-rear dimension of the lens rather than space required by the many components needed to house a film pack and successively expose and process the plurality of film units comprising the film pack.

Our copending Application No. 45623/70

(Serial No. 1 240 538) divided from the present application, is concerned with a folding camera.

Another copending application No. 5 5839/71 (Serial No. 1 240 540) also divided from the present application, is directed to a folded camera comprising four body sections, relatively movable between folded and extended positions, each having one primary exterior planar surface forming a part of the exterior of the body of the camera in both the folded and the extended positions; these sections are pivotally coupled near their ends to form a closed loop to permit their relative movement between a folded position in which the said planar surfaces of the sections are substantially parallel to each other and an extended position in which each of the planar surfaces forms an angle with those of the adjacent sections; extensible light sealing means form a light-tight enclosure with the body sections, one of which includes a photographic objective lens and another film supporting means for positioning a photosensitive element for exposure.

Our copending Application No. 35636/68 (Serial No. 1 240 532) is directed to the combination of a pair of pressure rollers, film-feeding means for engaging a film unit and moving it into the bite of the pressure rollers, drive means for driving the film-feeding means to feed a film unit into the bite of the pressure rollers and rotating at least one of the pressure rollers, and disabling means arranged to sense the presence of a film unit engaged between the pressure rollers and coupled with the film feeding means so that when a film unit is engaged between the pressure rollers, the film feeding means is rendered incapable of moving another of the film units toward the bite of the pressure rollers.

WHAT WE CLAIM IS:—

1. A photographic camera of the self-developing type, comprising: a housing; means within the housing for positioning a photosensitive element at a focal plane of the camera; processing means mounted adjacent a first end of the focal plane; a mirror orientated at an angle of less than 45° to the said focal plane and positioned so as to diverge from the focal plane in the direction from the other end thereof towards the said first end; a photographic objective lens positioned near the said first end of the focal plane and orientated so that the optical axis of the lens is inclined at an angle of less than 45° to the focal plane and diverges from the latter in the direction from the first end thereof to the said other end, the said objective lens directing image light incident upon it on to the said focal plane by reflection from the

mirror; and means for moving the photosensitive element into engagement with the processing means.

2. A camera in accordance with Claim 1, in which the housing includes a first housing section for supporting the positioning means for the photosensitive element, a second housing section for positioning the mirror and a third housing section for positioning the lens, the first housing section being pivoted to each of the second and third housing sections to permit relative movement of the housing sections between a folded inoperative position and an extended operative position.

3. A camera as defined in Claim 2, further comprising a fourth housing section pivotally coupled between the second and third housing sections, the housing sections co-operating to define walls of a chamber providing a light path between the lens and the said focal plane.

4. A camera as defined in Claim 2 or 3, wherein the third housing section is pivotal to an inoperative position in which the lens is disposed with its optical axis substantially perpendicular to the said focal plane.

5. A camera as defined in Claim 4, in which the housing sections are so arranged that in their inoperative position the first and third housing sections are disposed end to end and the second housing section is located with the mirror in face-to-face adjacency with the said positioning means for the photosensitive element.

6. A camera as defined in any one of Claims 2-5, in which the housing sections in the operative position are so located that the axis of the lens intersects the mirror at an angle greater than 45° .

7. A camera as defined in any one of Claims 1-6, in which the processing means includes a pair of rolls mounted for rotation in juxtaposition and means for rotating at least one of the rolls to advance a film unit, including a photosensitive element positioned for exposure, from the said positioning means through the rolls to distribute a processing liquid in contact with the photosensitive element, and in which the housing includes means defining a passage located in alignment with the rolls for enabling the movement of the film unit from between the rolls through the said passage and from the camera.

8. A camera in accordance with Claim 1, substantially as herein described with reference to the accompanying drawings.

For the Applicants:
GILL, JENNINGS & EVERY,
Chartered Patent Agents,
51/52 Chancery Lane,
London, W.C.2. WC2A 1HN.



(Serial No. 1 240 538) divided from the present application, is concerned with a folding camera.

Another copending application No. 5 5839/71 (Serial No. 1 240 540) also divided from the present application, is directed to a folded camera comprising four body sections, relatively movable between folded and extended positions, each having one primary exterior planar surface forming a part of the exterior of the body of the camera in both the folded and the extended positions; these sections are pivotally coupled near their ends to form a closed loop to permit their relative movement between a folded position in which the said planar surfaces of the sections are substantially parallel to each other and an extended position in which each of the planar surfaces forms an angle with those of the adjacent sections; extensible light sealing means form a light-tight enclosure with the body sections, one of which includes a photographic objective lens and another film supporting means for positioning a photosensitive element for exposure.

Our copending Application No. 35636/68 (Serial No. 1 240 532) is directed to the combination of a pair of pressure rollers, film-feeding means for engaging a film unit and moving it into the bite of the pressure rollers, drive means for driving the film-feeding means to feed a film unit into the bite of the pressure rollers and rotating at least one of the pressure rollers, and disabling means arranged to sense the presence of a film unit engaged between the pressure rollers and coupled with the film feeding means so that when a film unit is engaged between the pressure rollers, the film feeding means is rendered incapable of moving another of the film units toward the bite of the pressure rollers.

WHAT WE CLAIM IS:—

1. A photographic camera of the self-developing type, comprising: a housing; means within the housing for positioning a photosensitive element at a focal plane of the camera; processing means mounted adjacent a first end of the focal plane; a mirror orientated at an angle of less than 45° to the said focal plane and positioned so as to diverge from the focal plane in the direction from the other end thereof towards the said first end; a photographic objective lens positioned near the said first end of the focal plane and orientated so that the optical axis of the lens is inclined at an angle of less than 45° to the focal plane and diverges from the latter in the direction from the first end thereof to the said other end, the said objective lens directing image light incident upon it on to the said focal plane by reflection from the

mirror; and means for moving the photosensitive element into engagement with the processing means.

2. A camera in accordance with Claim 1, in which the housing includes a first housing section for supporting the positioning means for the photosensitive element, a second housing section for positioning the mirror and a third housing section for positioning the lens, the first housing section being pivoted to each of the second and third housing sections to permit relative movement of the housing sections between a folded inoperative position and an extended operative position.

3. A camera as defined in Claim 2, further comprising a fourth housing section pivotally coupled between the second and third housing sections, the housing sections co-operating to define walls of a chamber providing a light path between the lens and the said focal plane.

4. A camera as defined in Claim 2 or 3, wherein the third housing section is pivotal to an inoperative position in which the lens is disposed with its optical axis substantially perpendicular to the said focal plane.

5. A camera as defined in Claim 4, in which the housing sections are so arranged that in their inoperative position the first and third housing sections are disposed end to end and the second housing section is located with the mirror in face-to-face adjacency with the said positioning means for the photosensitive element.

6. A camera as defined in any one of Claims 2-5, in which the housing sections in the operative position are so located that the axis of the lens intersects the mirror at an angle greater than 45° .

7. A camera as defined in any one of Claims 1-6, in which the processing means includes a pair of rolls mounted for rotation in juxtaposition and means for rotating at least one of the rolls to advance a film unit, including a photosensitive element positioned for exposure, from the said positioning means through the rolls to distribute a processing liquid in contact with the photosensitive element, and in which the housing includes means defining a passage located in alignment with the rolls for enabling the movement of the film unit from between the rolls through the said passage and from the camera.

8. A camera in accordance with Claim 1, substantially as herein described with reference to the accompanying drawings.

For the Applicants:
GILL, JENNINGS & EVERY,
Chartered Patent Agents,
51/52 Chancery Lane,
London, W.C.2. WC2A 1HN.