

SPECIFICATION

ESCALATOR APPARATUS

BACKGROUND OF THE INVENTION

Technical Field

The present invention relates to an escalator apparatus which can be safely utilized not only by ordinary passengers but also by special passengers who use vehicles such as wheelchairs, baby carriages and shopping carts.

Background Art

Conventional escalators have been designed to transport ordinary passengers and hence the depth dimension of the steps is about 400 mm. Therefore, it has been difficult to transport wheelchairs or baby carriages safely while maintaining their horizontal state.

Therefore, various suggestions have been made including;

(1) a first arrangement in which, as in the case of Japanese Patent Publication No. 41555/1981, one or more large-sized steps having a sufficient depth dimension to transport a wheelchair or the like are incorporated in advance and man conveyor start and stop switches for exclusive use by physically handicapped persons are installed, the arrangement being such that operating such stop switch causes the large-sized step to stop at the entrance area without fail and pushing the exclusive start

switch subsequent to wheelchair passengers stepping on causes the escalator to start, the large-sized step being stopped again at the exit area in the desired story after the lapse of a given time, and

(2) a second arrangement in which, as in the case of Japanese Patent Publication No. 2153/1983, all steps are connected by pivotally connecting the main and auxiliary treads to construct an escalator having a substantially great depth dimension capable of carrying vehicles.

In the former escalator apparatus, however, the presence of the large-sized steps, though small in number, each having a sufficient depth dimension to carry a wheelchair or the like thereon, makes it necessary to increase the radii of the sprocket wheels for return drive at the entrance and exit areas, necessarily increasing the size of the escalator and limiting the installation space.

Further, since large-sized steps are combined at random with normal-sized steps, the time for a large-sized step arrives at an entrance area or exit area cannot be known, so that when a person using a wheelchair or the like wants to step on the escalator, a large-sized step has to be detected and stopped at the entrance area; thus the traffic will be shut off each time a wheelchair passenger utilizes the escalator.

On the other hand, in the latter escalator apparatus, though there is no need to increase the radii of the sprocket wheels for return drive at the entrance and exit

areas, the step height becomes too great if it is desired to construct a large-sized step having a sufficient depth dimension to receive a large-sized wheelchair and to set the maximum inclination angle at 30° as in the conventional escalator. Therefore, there is a danger of a passenger tripping over when he is moving on the step. If the step height is decreased to about 200 mm approximate to the value for the conventional escalator, the maximum inclination angle is decreased to about 10° ; after all, to obtain a required lift, the overall length of the escalator is necessarily increased, requiring an increased installation space.

Thus, the present applicant has already suggested, as described in Japanese Patent Application No. 160448/1988, an escalator apparatus having suitable degrees of step height and inclination angle, without no possibility of suffering from an increase in size, and capable of transporting vehicles simultaneously with ordinary passengers.

In the suggested arrangement, a plurality of specific steps having a predetermined depth are continuously disposed to form a large-sized step having an increased depth, and a predetermined number of ordinary passenger steps having a predetermined depth are continuously disposed between said large-sized steps, said large-sized and ordinary passenger steps forming a unit step, such unit steps being endlessly connected, wherein the maximum

inclination angle of the escalator can be optionally changed by changing the number of ordinary passenger steps.

Such latest escalator apparatus will now be described with reference to the drawings.

Fig. 2 is a side view showing an example of the lower story of this escalator apparatus; Fig. 3 is a detailed view showing an example of the arrangement of the steps shown in Fig. 2; and Fig. 4 is an explanatory view for explaining the basic technical concept of this escalator apparatus. In these figures, the numeral 1 denotes an escalator body; 2 denotes a balustrade; 3 and 4 denote steps having risers 3a and 4a for ordinary passengers; and 10 denotes a large-sized step for conveying a vehicle such as a wheelchair in such a manner that three specific steps 11, 12 and 13 to be later described in more detail maintain the same horizontal state in the transport region, said large-sized step 10 cooperating with the ordinary passenger steps 3 and 4 (only the step 3 or 4 or numbers of steps 3 and 4 may be involved) to form a single unit step 100.

The ordinary passenger steps 3 and 4, like conventional steps, have front wheels 31, 41 and rear wheels 32, 42 rotatably mounted in the lower areas of their front and rear ends, so that in the region of maximum inclination, the front wheels 31, 41 and rear wheels 32, 42 are supported and guided by guide rails 33, 43, 34, 44 having a predetermined angle of inclination θ .

The specific step 11 is exactly the same in

construction as the ordinary passenger steps 3 and 4, provided with a riser 11a, and have front and rear wheels 111 and 112 rotatably mounted in the lower areas of its front and rear ends, so that in the region of maximum inclination, the front and rear wheels 111 and 112 are supported and guided by guide rails 113 and 114 having a predetermined angle of inclination θ .

On the other hand, the specific steps 12 and 13 are the same in construction as the ordinary passenger steps except that they do not have riser portions (they may be ordinary passenger steps having riser portions) and have front wheels 121, 131 and rear wheels 122, 132 rotatably mounted on the lower areas of their front and rear ends, so that in the region of maximum inclination, the front wheels 121, 131 and rear wheels 122, 132 are supported and guided by guide rails 123, 133, 124, 134 having a predetermined angle of inclination θ ; however, the guide rails 133 preferably have a U-shaped cross section to prevent the specific step 13 from deviating upward.

And a driving chain 20 for driving the steps, as shown in Fig. 3, is attached to the shafts 31a, 41a of the front wheels 31, 41 of the ordinary passenger steps 3, 4 and the shafts 111a, 121a, 131a of the front wheels 111, 121, 131 of the specific steps 11, 12 and 13 and connected in endless form.

In this connection, the riser of a step of the escalator, as shown in Fig. 5, has a curve having a radius

R with the center located at the front end A5 of the tread 5 of the step, that is, a curve having the depth dimension L of the tread 5. Thus, the maximum angle of inclination θ of an escalator having large-sized steps and ordinary steps regularly combined therewith to form unit steps 100 as shown in Fig. 3 is expressed by the formula 1 below.

$$\theta = \tan^{-1} \frac{H (n + 1)}{L (N - 1) + L (n+1) \cos \theta_1} \dots\dots\dots(1)$$

where, as in Fig. 4, n is the number of ordinary passenger steps included in each unit step; H is the common step height; L is the depth dimension of ordinary passenger steps; θ_1 is the angle of inclination of ordinary passenger steps; and N is the magnification of the depth dimension of the large-sized steps with respect to ordinary passenger steps.

In Fig. 3, if the depth dimension L of the ordinary passenger steps 3 and 4 is 400 mm, the step height H is 200 mm, the magnification N of the depth dimension of the large-sized steps 10 is 3, and the angle of inclination θ_1 of the ordinary passenger steps 3 and 4 is 30° , then the maximum angle of inclination θ of the escalator in Fig. 3 is expressed by the formula 2, which is a function of the number n of ordinary steps 3 and 4 included in each unit step 100, it being seen that as the number n increases, a greater value of θ in the formula 2 can be taken (it being noted that θ_1 is not more than 30°). For example, for $n = 2$, $\theta \div 18^\circ$, for $n = 3$, $\theta \div 20^\circ$, for $n = 4$, $\theta \div 22^\circ$... for

$n = 22, \theta \div 28^\circ.$

$$\theta = \tan^{-1} \frac{200 (n + 1)}{400 (3-1) + 400 (n+1) \cos 30^\circ} \dots\dots(2)$$

Therefore, the arrangement shown in Fig. 3 provides an escalator which is theoretically short in overall length since in order to obtain a rise required by the escalator, the maximum angle of inclination can be made as great as possible without increasing the step height irrespective of the presence of large-sized steps on which wheelchairs and the like can be carried.

In this connection, in the arrangement of Fig. 3, the number of guide rails for guiding the front and rear wheels of steps increases, but to prevent it, arrangements shown in Figs. 6 and 7 may be employed.

First, in Fig. 6 in which the parts having the same reference characters as in Fig. 3 indicate the same parts, the numeral 50 denotes a large-sized step connected as by hinges 54 and 55 so that it can be bent backward at the opposed end surfaces of specific steps 51, 52 and 53 but that it is prevented from being bent forward and that it is held in the same horizontal state in the transport region, said large-sized step 50 cooperating with the ordinary passenger steps 3 and 4 (in this case also, only the step 3 or 4 or numbers of steps 3 and 4 may be involved) to form a single unit step 200 as in the case of Fig. 3.

The specific step 51 has a riser 51a like those of the ordinary passenger steps 3 and 4 and has a rear wheel 512

rotatably mounted in the rear lower area (with no front wheel at the front end), each rear wheel 512 being supported and guided by a guide rail 514 having a predetermined angle of inclination θ in the region of maximum inclination of the escalator

The specific step 52 has only a tread 52b and the specific step 53 has no riser but a front wheel 531 rotatably mounted in the front lower area (with no rear wheel at the rear end), each front wheel 531 being supported and guided by a guide rail 533 of U-shaped cross section having a predetermined angle of inclination θ in the region of maximum inclination of the escalator.

Therefore, in the arrangement shown in Fig. 6, the number of rails is 4 less on either side than that of guide rails used in the arrangement shown in Fig. 3. And a driving chain 21 for driving the steps is attached to the shafts 31a and 41a of the front wheels 31 and 41 of the ordinary passenger steps 3 and 4 and the shaft 531a of the front wheel 531 of the specific step 53 and is connected in endless form. In addition, the riser 51a of the specific step 51 differs from the riser 11a of the specific step 11 shown in Fig. 3 in the following points.

Thus, the ordinary passenger step 3 opposed to the riser 51a of the specific step 51 shown in Fig. 6 is designed to rise and lower in its horizontal state while maintaining unchanged the distance R_1 between the shaft 531a of the front wheel 531 of the specific step 53 and the

shaft 31a of the front wheel 31 of the ordinary passenger step 3, and this design makes it necessary to arrange the riser 51a of the specific step 51 such that it has a curved surface with a radius equal to the distance R_1 .

In contrast, in the case of the specific step 11 of Fig. 3, the riser 11a of this specific step 11 has a curved surface with its radius equal to the distance R between the shaft 111a of the front wheel 111 of the specific step 11 and the shaft 31a of the front wheel 31 of the ordinary passenger step 3, that is, the same curved surface as those of the risers 3a and 4a of the ordinary passenger steps 3 and 4.

Now, in the unit step 200 in Fig. 6, if the front end A3 and front wheel shaft 31a of the ordinary passenger step 3 and the front end A53 and front wheel shaft 531a of the specific step 53 are arranged to form a parallelogram, then the riser 51a of the specific step 51 has to be formed with a curved surface having a radius equal to the depth dimension R_2 of the large-sized step 50 with the center located at the front end A53 of the specific step 53. And usually the dimension R_1 equals this dimension R_2 .

An embodiment which makes it possible to further reduce the number of rails by two more on each side will now be described with reference to Fig. 7. In Fig. 7, the numeral 60 denotes a large-sized step connected as by hinges 64 and 65 so that it can be bent backward at the opposed end surfaces of the specific steps 61, 62 and 63 and in the

transport region for persons or vehicles these steps are maintained in the same horizontal state. The numeral 612 denotes a rear wheel rotatably mounted in the lower area of the rear end of the specific step 61 having a riser 61a, said rear wheel 612 being supported and guided by a guide rail 614 having a predetermined angle of inclination θ in the region of maximum inclination of the escalator.

The numeral 631 denotes a front wheel rotatably mounted in the lower area of the front end of the specific step 63 through a shaft 631a, said front wheel 631 being supported and guided by a guide rail 633 having a predetermined angle of inclination θ in the region of maximum inclination of the escalator.

The numeral 66 denotes a support link rotatably connected to the lower areas of the front ends of the specific steps 61 and 62 by pins 66a and 66b and also to the front wheel shaft 631a of the specific step 63, with means, e.g., hinges 66c and 66d, disposed between the pins 66a and 66b and between the pin 66b and the shaft 631a to allow said link to be bent only toward the tread side of said large-sized step 60.

The numerals 7 and 8 denote ordinary passenger steps having risers 7a and 8a, and 72 denotes a rear wheel rotatably mounted in the lower area of the rear end of the ordinary passenger step 7, said rear wheel 72 being supported and guided by a guide rail 74 having a predetermined angle of inclination θ in the region of

maximum inclination of the escalator. The numeral 82 denotes a rear wheel rotatably mounted in the lower area of the rear end of the ordinary passenger step 8, said rear wheel 82 being supported and guided by a guide rail 84 having a predetermined angle of inclination θ in the region of maximum inclination of the escalator.

The numeral 67 denotes a support link connected to the lower areas of the front ends of the ordinary passenger steps 7 and 8 by pins 67a and 67b and to the lower area of the front end of the specific step 61 above the ordinary passenger step 7 and to the support link 66 by said pin 66a and slidably connected to the shaft 631'a of the front wheel 631' of the specific step 63' constituting a large-sized step below the ordinary passenger step 8 through an elongated opening 67c, the link elements being connected by means, e.g., hinges 67d, 67e and 67f disposed between the pins 67a and 67b, between the pins 67a and 66a and between the pins 67b and shaft 631'a to allow them to be bent only toward the tread side.

And this large-sized step 60 cooperates with the ordinary passenger steps 7 and 8 (only the ordinary step 7 or 8 or numbers of ordinary passenger steps 7 and 8 may be involved) to form a unit step 300. A driving chain 22 for driving said unit step 300 is attached only to the shafts 631a and 631'a of the front wheels 631 and 631' of the specific steps 63 and 63' and connected in endless form.

Now, let the depth dimensions of the treads of the

specific steps 61, 62, 63 and 63' and ordinary passenger steps 7 and 8 be the same as L and let the distance between the pins 66a and 66b of the support link 66, the distance between the pin 66b of the support link 66 and the shaft 631a, the distance between the pins 67a and 67b of the support link 67, and the distance between the pins 66a and 67a of the support link 67 be also the same as L. And let the front end A7 and pin 67a of the ordinary passenger step 7 and the front end A61 and pin 66a of the specific step 61 define a parallelogram, the front end A8 and pin 67b of the ordinary passenger step 8 and the front end A7 and pin 67a of the ordinary passenger step 7 define a parallelogram and the front end A63' and shaft 631'a of the specific step 63' and the front end A8 and pin 67b of the ordinary passenger step 8 define a parallelogram. Then it follows that the ordinary passenger steps 7 and 8 describe arcs having a radius L with the respective centers located at the pins 66a and 67a of the support link 67 with respect to the respective upper steps. Therefore, the riser 61a of the specific step 61 and the riser 7a of the ordinary passenger step 7 have curved surfaces having a radius L with their respective centers located at the front ends A61 and A7.

As to the specific step 63', however, since it moves in such a manner as to maintain a fixed distance between the shaft 631a of the specific step 63 thereabove and the shaft 631'a of the specific step 63' therebelow, the distance between the pin 67b of the ordinary passenger step 8 and

the shaft 631'a of the specific step 63' equals the depth dimension L of the step in the horizontal travel region for the escalator and in the region having a predetermined angle of inclination it gradually increases beyond L as the shaft 631'a slides in the elongated opening 67c of the support link 67. Thus, the curved surface of the riser 8a of the ordinary passenger step 8 has to be formed such that its radius with the center located at the front end A8 gradually changes.

In the escalator of such construction, only the specific steps 63 and 63' of the unit step 300 are directly driven by the drive chain 22, while the specific steps 61 and 62 are driven through the support link 66 and the ordinary passenger step is driven through the support links 66 and 67, driving the unit step 300 in its entirety.

And the support link 66 serves to increase the rigidity of the large-sized step 60 and the support link 67 serves to maintain the horizontal state of the ordinary passenger steps 7 and 8. At the reversal points for the steps in the top and bottom regions of an escalator, they are bent at the hinges 66c, 66d and 67d, 67e, 67f, so that there is no possibility of the links propping to interfere with the movement of the escalator when the drive chain 22 is driven.

In such escalators, there have been shown regular combinations comprising a large-sized step with a depth dimension greater than that of ordinary passenger steps and

ordinary passenger steps having a predetermined depth dimension (each of the three embodiments described above shows an example in which three specific steps are used to form a large-sized step; the reason is that a large-sized wheelchair, such as a motor-powered wheelchair, is envisaged, but there are other cases in which two specific steps are sufficient to provide a sufficiently wide space for a baby carriage, a shopping cart, a child's wheelchair or the like) to provide a unit step, such unit steps being connected in endless form; thus, any desired maximum angle of inclination of the escalator can be easily selected, without changing the step height, by simply changing the number of ordinary passenger steps to be connected .

In such escalator apparatus, various means have been made to decrease the number of guide rails. Each of the examples shown in Figs. 3, 6 and 7 is destined to increase the number of guide rails to one degree or another if the number of ordinary passenger steps included in the unit step is increased. Even if the number of ordinary passenger steps is increased to make the maximum angle of inclination of the escalator to approach 30° so as to decrease the overall length of the escalator, the number of guide rails which guide the steps increases in proportion thereto, resulting in a new problem that the width of the escalator has to be increased. Further, an increase in the number of guide rails leads to an increase in the weight of

the trusses supporting the rails; thus, the problem is not limited to one of installation space.

The present invention has been accomplished with the above in mind and has for its object the provision of an vehicle transporting, space-saving escalator apparatus which minimizes the number of rails which guide the steps and capable of maintaining a suitable degree of maximum angle of inclination.

SUMMARY OF THE INVENTION

According to the present invention, an escalator includes a plurality of adjacent steps to form a large-sized step having a greater depth than that of ordinary passenger steps, said large-sized step being guided with its horizontal state maintained in the horizontal, transient and inclined regions of the escalator, said escalator being characterized in that the escalator includes a plurality of special steps which are guided by first and second guide rails in the horizontal and inclined regions, respectively, said first and second rails being different from each other, said special steps being disposed to form part of said large-sized step and continue to the lower part of said large-sized step.

With the arrangement made as described above, since the large-sized step is periodically circulated, even if such a vehicle as a wheelchair can smoothly step on and off while the escalator is running.

EFFECTS OF THE INVENTION

According to the present invention, since the number of guide rails for guiding the steps can be reduced to a necessary minimum, a space-saving escalator can be obtained in which the width of the escalator is the same as in the conventional escalator and the angle of inclination of the escalator is approximate to the maximum inclination angle of the conventional escalator.

Further, the reduced number of guide rails required eliminates the problem of beam strength for the building structure which would be otherwise caused by the increased weight of the entire truss.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1 is a schematic view showing the overall arrangement of an escalator according to the present invention;

Fig. 2 is a side view showing an example of the lower story of a tiltable escalator;

Fig. 3 is a detailed view showing an example of the arrangement of the steps of the tiltable escalator shown in Fig. 2;

Fig. 4 is an explanatory view for explaining the basic technical concept of the tiltable escalator;

Fig. 5 is a view showing the shape of an ordinary step riser;

Fig. 6 is a detailed view showing another example of

- 17 -

the arrangement of the steps of the tiltable escalator shown in Fig. 2;

Fig. 7 is a detailed view showing another example of the arrangement of the steps of the tiltable escalator shown in Fig. 2;

Fig. 8 is an enlarged view of an area A in Fig. 1;

Fig. 9 is an enlarged view of a large-sized step 90 in Fig. 8;

Fig. 10 is an enlarged view of special steps for ordinary passengers in Fig. 8;

Fig. 11 is a plan view of Fig. 8;

Fig. 12 is an enlarged front view of a special step for ordinary passengers in Fig. 8;

Fig. 13 is a view showing the path of travel of special steps for ordinary passengers;

Fig. 14 is an explanatory view for explaining the positional relation of special steps for ordinary passengers in an inclined region;

Fig. 15 is a view showing the relation between special steps S1 through S9 and a step chain 23 according to the present invention;

Fig. 16 is a view showing an embodiment for connecting and driving special steps S1 through S9 according to the present invention;

Fig. 17 is a view showing the disposition of connecting links 24 and step chains 23 for driving the large-sized step 90 and special steps S2 through S9 for ordinary

- 18 -

passengers according to the present invention;

Fig. 18 is a view showing the shape of the riser surface for special steps S1 through S9;

Fig. 19 is a complete view showing an embodiment of a wheel stopping device;

Fig. 20 is a view showing the shape of grooves 923a through 923d in a plate 923 in Fig. 19;

Fig. 21 is an explanatory view for explaining the operation of a wheel stop 921;

Fig. 22 is an explanatory view for explaining the operation of a wheel stopping device 920; and

Fig. 23 is an explanatory view for explaining the operation of the wheel stop 921.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the present invention will now be described. Fig. 1 is a schematic view showing the overall arrangement of an escalator according to the present invention; Fig. 8 is an enlarged view of an area A in Fig. 1; Fig. 9 is an enlarged view of a large-sized step 90 in Fig. 8.; Fig. 10 is an enlarged view of special steps for ordinary passengers in Fig. 8; Fig. 11 is a plan view of Fig. 8; Fig. 12 is enlarged front and side views of a special step in Fig. 8. In these figures, the same reference characters as used in Figs. 2 through 7 denote the same parts, and the numeral 90 denotes a large-sized step according to the present invention, said large-sized

- 19 -

step 90 comprising two specific steps 91 and 92 and one special step S1 which are rotatably connected together so they travel always in the same horizontal state in a transport region.

The specific step 91, like an ordinary passenger step ST, is a step which has front and rear wheels 911 and 912 rotatably mounted thereon and supported and guided by guide rails ST₁ and ST₂ having a predetermined angle of inclination θ but which may not have a riser portion. The specific step 92 is a step which requires neither front and rear wheels nor a riser portion; it is only necessary for it to have a tread.

The special step S1 has two types of front wheels S1a and S1b and two types of rear wheels S1c and S1d rotatably mounted thereon and also has a riser S1r having a curved surface different from the conventional one. The front wheel S1a, as shown in Fig. 13, is supported and guided by a guide rail 93 installed inside the escalator body 1 at a predetermined angle of inclination, for example, about 25°, while the front wheel S1b is supported and guided by a guide rail 94 installed inside the escalator body 1 to extend from the transient portion of the escalator to the horizontal portion. In the inclined portion the front wheel S1a is supported and guided by the guide rail 93 (the front wheel S1b is separated from the guide rail 94). From the transient portion the front wheel S1b is supported and guided by the guide rail 94 and in the horizontal portion

- 20 -

the front wheel S1a is completely separated from the guide rail 93.

On the other hand, the rear wheel S1c, as shown in Fig. 13, is supported and guided by a guide rail 95 installed inside the escalator body 1 at a predetermined angle of inclination, for example, about 25° , while the rear wheel S1d is supported and guided by a guide rail 96 installed inside the escalator body 1 to extend from the transient portion of the escalator to the horizontal portion. After all, in the inclined portion the rear wheel S1c is supported and guided by the guide rail 95 (the rear wheel S1d is separated from the guide rail 96). From the transient portion the rear wheel S1d is supported and guided by the guide rail 96 and in the horizontal portion the rear wheel S1c is completely separated from the guide rail 95.

Therefore, the special step S1 travels together with the specific steps 91, 92 with the front wheels S1a, S1b and the rear wheels S1c, S1d being guided by the guide rails 93, 95 and 94, 96 and ST₁, ST₂.

S2 through S9 are special steps for ordinary passengers, constructed in substantially the same manner as said special step S1, having front wheels S2a, S2b through S9a, S9b, rear wheels S2c, S2d through S9c, S9d and risers S2r through S9r; however, in the inclined portion, the front wheels S2a through S9a and rear wheels S2c through S9c guided by the guide rails 93 and 95 are vertically

- 21 -

slightly displaced from each other.

That is, to move the group SS composed of the special steps S1 through S9 in a direction, for example, inclined at 25° , the guide rails 93 and 95 which guide the steps must also be inclined at 25° ; however, since the special steps group SS_o for ordinary passengers is disposed at an angle of inclination of 30° as shown in Fig. 14, the distances X1 through X9 between the step surfaces and the guide rails 93, 95 differ from each other, a fact which means that the levels of the front wheels S1a through S9a and rear wheels S1c through S9c guided by the guide rails 93 and 95 must be changed for each step.

However, if the path extends to the horizontal portion, the individual step surfaces will no longer align with each other; therefore, in the horizontal portion, other front wheels Sb₂ through S9₂ and rear wheels S2d through S9d (the distances from the guide rails 94 and 96 are equal to each other) are guided by other guide rails 94 and 96, thereby solving the above problem and greatly reducing the number of guide rails and minimizing the escalator width.

The numeral 23 denotes a step chain connecting the shaft STRa of the front wheel STa of each ordinary passenger step ST and the shaft 911a of the front wheel 911 of the specific step 91 and the pins 23Ra of the chain wheels 23R in endless form throughout the periphery of the escalator, said chain wheels 23R being rotatably mounted on the step chain 23 through the pins 23Ra₁ - 23Ra₉ at

- 22 -

locations corresponding to the special steps S1 through S9, said chain wheels 23R (23R₁ through 23R₉) being supported and guided by the guide rail ST₁ in the transport region of the escalator. On the side associated with the special steps S1 through S9, as shown in Fig. 15, the horizontal portion and reversal point of the escalator are formed with recesses S1e through S9e adapted to receive the shafts 23Ra₁ through 23Ra₉ therein to allow smooth reversing of the special steps S1 through S9, as in the case of the usual escalator.

The numeral 24 denotes connecting links according to the present invention for connecting the special steps S1 through S9 in such a manner as to cause no problem in strength even if the rise of the escalator is increased. As shown in Fig. 16, they are connected in the joint portions of the special steps S1 through S9 to form stepped portions and are bendable intermediate between the stepped portions.

In the case of the escalator apparatus of such construction, the step chain 23 and the connecting links 24 have to be adjusted such that the dimensions L1, L2 and L3 shown in Fig. 17 satisfy the relation $L1 + L2 > L3$ in the inclined region and the relation $L1 + L2 = L3$ in the horizontal region. However, since the connecting links 24 are connected to form stepped portions, the state of Fig. 16 (a) is established in the horizontal region, while the length is increased in the inclined region as shown in Fig.

- 23 -

16 (b); therefore, the above arithmetic relations can be satisfied. Further, at the reversal point, as shown in Fig. 15 (c), since each connecting link 24 is inwardly bent at the intermediate portion, the straight length L_4 of the connecting links 24 becomes equal to the length L_5 of the step chain 23, enabling smooth reversing of the special steps S_1 through S_9 .

As for the step chain 23, the above arithmetic relations are also satisfied by shaping the riser surface of each of the special steps S_1 through S_9 such that the center of the riser arc is displaced from the usual center O to a point P therebelow, as shown in Fig. 18.

The character PS_1 denotes a vehicle operating button. When a passenger using a wheelchair or the like wants to use the escalator, he pushes this button PS_1 , whereby the large-sized step 90, when approaching the entrance area, is decelerated to make it easier for the person using the vehicle to step on. The character PS_2 denotes a stepping-on confirmation button which, when pushed, gradually accelerates the escalator until the rated speed is reached. The character PS_3 denotes a stepping-off confirmation button which, when pushed, restores a wheel stopping device to be later described.

In addition, such system using push buttons may be replaced by a different system in which wheelchair passengers carry transmitters with them to emit signals to decelerate or accelerate the escalator. As for such

- 24 -

communications means utilized by wheelchair passengers, mention may be made of a wireless transmitter-receiver having an induction communications function for detection in a limited range.

If the escalator is operated with a vehicle mounted on this large-sized step 90, an accident of the vehicle falling off the large-sized step 90 will naturally be anticipated. To solve this problem, it is recommended to employ a wheel stopping device which is designed so that even when the escalator is moving, it can be automatically and smoothly projected or retracted and when a wheelchair or the like is not carried on the escalator, it is housed so as not to project above the tread of the step.

Fig. 19 is an enlarged view showing the mechanism of a wheel stopping device 920 installed in a special step S1 having a riser S1r among large-sized steps 90. In the figure, the numeral 921 denotes a wheel stop installed in the special step S1 so that it is turnable around a point Q, and 922 denotes a rod having a roller 922a at its lower end and a plate 923 at its upper end and adapted to be movable upward. And the plate 923 has grooves 923a, 923b, 923c and 923d cut therein in loop form as shown in Fig. 19 and having depth dimensions to be later described.

The numeral 924 denotes a rod installed for upward movement in a bracket SB on the special step S1, said rod being contacted at its upper end with part of the vehicle stop 921 to support the weight of the wheel stop 921, said

- 25 -

rod having a washer 924a attached to its lower end. The numeral 925 denotes a lever rotatably supported at its upper end by the bracket SB on the special step S1 and guided at its lower end by the grooves 923a, 923b, 923c and 923d of said plate 923 in loop form in the order mentioned. More particularly, the grooves 923a, 923b, 923c and 923d of the plate 923 are machined such that as shown in Fig. 20, each groove is deepest at its initial end, becoming gradually shallower until it reaches the deepest portion of the next groove, the arrangement being such that the lower end of the lever 925 is turned clockwise, but never reversed.

The numeral 926 denotes a spring interposed between the plate 923 and the washer 924a, and 927 denotes a spring interposed between the plate 923 and the bracket SB.

The operation of the present wheel stopping device 920 will now be described first with reference to the upward movement of the escalator. During the upward movement, a passenger in a wheelchair or someone else pushes the vehicle operating button PS1 (a portable transmitter may be employed) to rotate the motor M on an escalator body 1 shown in Fig. 21 to move a cam Ma upward.

On the other hand, the vehicle operating button PB1 is operated to cause the large-sized step 90 to approach the floor plate 1a at the entrance area, whereupon the escalator is decelerated and the large-sized step 90 passes under the floor plate 1a while the roller 922a contacts the

- 26 -

cam Ma, which pushes up the roller 922a.

Then, since the rod 922 is pushed up together with the plate 923 against the force of the spring 927, the lower end of the lever 925 lowers along the groove 923a (actually, the plate 923 rises) to enter the groove 923b. And when the roller 922a leaves the cam Ma in response to the movement of the special step S1, the force of the spring 927 somewhat moves the rod 922 backward or downward but the lower end of the lever 925 is guided by the groove 923b to enter the groove 923c where it is locked (assuming the state of being unable to move back). Therefore, even if the special step S1 continues to move, there occurs no change in the position of the rod 922 and plate 923 relative to the special step S1.

On the other hand, concerning the wheel stop 921, when the rod 922 and plate 923 are pushed up, the force of the spring 926 also pushes up the rod 924 and hence the upper end of the rod 924 pushes up the wheel stop 921, with the result that the wheel stop 921 projects beyond the tread surface of the special step S1 as shown in Fig. 22.

When the wheel stop 921 is projected in this manner, a passenger using a vehicle such as a wheelchair steps on the special step S in the direction of arrow; however, if a force is applied to the wheel stop 921 in the direction of arrow, the spring 926 flexes so that the wheel stop 921 can be easily drawn into the tread. Therefore, there is no obstacle to this stepping on, and once the passenger steps

- 27 -

on, the wheel stop 921 projects again to perform the function of vehicle slip-off prevention (even if a reverse force acts on the wheel stop 921, the latter will not move).

When the large-sized step 90 approaches the exit area, the roller 922a comes into contact with the cam M'a already moved upward by the motor M' shown in Fig. 23 (the time to drive the motor M' may be when the vehicle operating button PS1 or the stepping-on confirmation button PS2 is operated) and is thereby pushed up. This time also, the force of the spring 927 pushes up the rod 922 together with the plate 923 against the force of the spring 927, whereby the lower end of the lever 925 lowers along the groove 923c (actually, the plate 923 rises) to enter the groove 923d. And as the special step S1 moves, the roller 922a leaves the cam M'a, whereupon the rod 922 returns to its lower position under the force of the spring 927, so that the lever 925 is moved with its lower end guided by the groove 923d, returning to the groove 923a to restore its original state where it is locked.

On the other hand, since the rod 922 and plate 923 are lowered, the wheel stop 921 also lowers together with the rod 922 under its weight, restoring the state of the ordinary step in which it is completely received in the tread of the special step S1, as shown in Fig. 19.

In the lifting operation of the escalator, a passenger using such a vehicle as a wheelchair can step off the

- 28 -

escalator at the exit area regardless of the state of the wheel stop 921; therefore, there is no need to take the trouble of decelerating the escalator at the exit area.

After the passenger has stepped off, he pushes the stepping-off confirmation button PB3 to rotate the motors M and M' in the opposite direction to pull down the cams Ma and M'a so as to prevent interference between the roller 922a of the special step S1 and the cams Ma and M'a. Thus, during the lowering operation of the escalator there is no possibility of the wheel stop 921 projecting to form an obstacle which is liable to trip a passenger.

In addition, the lowering operation is almost the same as the lifting operation, and a detailed description of it is therefore omitted. The operation of the wheel stopping device 920 has much to do with the safety of the stepping-on and stepping-off of a vehicle. That is, during stepping-on if the wheel stop 921 fails to be projected, the vehicle is liable to fall by inertia, or if the wheel stop 921 fails to be retracted, the vehicle cannot step off; thus, it is desirable to run the escalator at low speed.



* C L M S *

- 29 -

THIS SHEET HAS BEEN
REPLACED

THIS SHEET HAS BEEN
REPLACED

CLAIMS:

1. An escalator apparatus including a plurality of adjacent steps to form a large-sized step having a greater depth than that of ordinary passenger steps, said large-sized step being guided with its horizontal state maintained in the horizontal, transient and inclined regions of the escalator, said escalator apparatus being characterized in that the escalator includes a plurality of special steps which are guided by first and second guide rails in the horizontal and inclined regions, respectively, said first and second rails being different from each other, said special steps being disposed to form part of said large-sized step and continue to the lower part of said large-sized step.

2. An escalator apparatus as set forth in Claim 1, characterized in that said special step is separately provided with front and rear wheels adapted to be guided by a guide rail in the horizontal region and front and rear wheels adapted to be guided by a guide rail in the inclined region.

3. An escalator apparatus as set forth in Claim 1, characterized in that said plurality of special steps are connected by stepped links.

4. An escalator apparatus as set forth in Claim 1, characterized in that said large-sized step is provided with a wheel stop having a mechanism which causes the wheel stop to project when the said large-sized step comes

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 30 -


out of the floor plate and to retract before it enters the floor plate.

5. An escalator apparatus substantially as hereinbefore described with reference to Figures 1 and 8 to 23 of the accompanying drawings.

This Sheet Has Been Replaced




Fig.1



2/21

Fig. 2




This Sheet Has Been Replaced



4/21

Fig. 4



This Sheet Has Been Replaced



5/21




Fig. 5

Fig. 6





Fig. 7




This Sheet Has Been Replaced



8/21


Fig. 8



This Sheet Has Been Replaced



உ.ர.



This Sheet Has Been Replaced






Fig. 10

This Sheet Has Been Replaced





12/21

Fig.12




Fig.12





Fig.13



14/21

Fig.14




Fig.15





Fig.15



(b)

Fig.15






Fig.16



(a)

Fig.16



(b)






Fig. 17

This Sheet Has Been Replaced



Fig.18

18/21





Fig.19




19/21

Fig.20




Fig.21



This Sheet Has Been Replaced




Fig.22



This Sheet Has Been Replaced



Fig.23



ABSTRACT

ESCALATOR APPARATUS

The invention provides an escalator constructed such that even persons using large-sized wheelchairs can utilize it with a sense of security together with healthy persons.

A group of special steps consisting of a large-sized step and special steps are disposed between ordinary passenger steps and the special steps are guided by guide rails different from those for the ordinary passenger steps.

(FIGURE 13)

This Sheet Has Been Replaced



Fig.1





Fig.2



3/21

Fig. 3





Fig.4



5/21

Substitute sheet - 9.4.96





Fig.5

Date: 10 APR 1996

Substitute sheet - 9.4.96

Fig.6




Date: 10 APR 1996

Substitute sheet - 9.4.96

7/21

Fig. 7



8/21






Fig. 8

Fig. 9.






Substitute sheet - 9.4.96

11/21

Fig.11



12/21

Substitute sheet - 9.4.96

Fig.12




Fig.12





Fig.13



14/21

Fig.14





Fig.15



Substitute sheet - 9.4.96

Fig.15




Fig.15






Fig.16




a

Fig.16



b

Fig. 17



18/21

Substitute sheet - 9.4.96

Fig.18




Fig.19




Fig.20



Fig.21




Fig. 22.





Fig.23



8-8881030

AS APPLIED TO THE INVENTION

1991 97A 81



16 APR 1997

Date :

- 29 -

Substitute Sheet(15 April 1997)CLAIMS

1. An escalator apparatus including a plurality of adjacent steps to form a large-sized step having a greater depth than that of ordinary passenger steps, said large-sized step being guided horizontally through the horizontal, transient and inclined regions of the escalator, said escalator apparatus being characterized in that a plurality of special steps each provided with at least a pair of wheels for the horizontal region and at least a pair of wheels for the inclined region respectively are disposed successively so as to extend up to the lower part of said large-size step, said pair of wheels for the horizontal region being guided by first guide rails for the horizontal region and said pair of wheels for the inclined regions being guided by second guide rails for the inclined region.

2. An escalator apparatus as set forth in claim 1, characterized in that said at least a pair of wheels for the horizontal region consist of a pair of front wheels and a pair of rear wheels and said at least a pair of wheels for the inclined region consist of a pair of front wheels and a pair of rear wheels respectively.

3. An escalator apparatus as set forth in claim 1 or claim 2, characterized in that said apparatus is so arranged that each said special step takes two situations, in one of which situations said at least a pair of wheels for the horizontal region are guided by said first guide rails for the horizontal region when the special step is in the horizontal region and in another of which situations said at least a pair of wheels for the inclined region are guided by said second guide rails for the



REPLACEMENT SHEET

Date: 16 APR 1997

- 30 -

Substitute Sheet(15 April 1997)

inclined region when the special step is in the inclined region, said two situations being interchangeable when the special step is in the transient region.

4. An escalator apparatus as set forth in any of claims 1 to 3, characterized in that said at least a pair of wheels for the inclined region of one of said special steps are positioned further away from the top face of the special step than the corresponding said at least a pair of wheels for the inclined region of another one of said special steps, disposed adjacent to and lower than said one of said special steps, are positioned away from the top face of said another one of said special steps.

5. An escalator apparatus as set forth in any preceding claim, characterized in that said at least a pair of wheels for the horizontal region of one of said special steps are positioned at the same distance away from the top face of the special step as said at least a pair of wheels of another one of said special steps are positioned away from the top face of said another one of said special steps.

6. An escalator apparatus as set forth in any preceding claim, characterized in that said large-sized step is provided with a wheel stop having a mechanism which causes the wheel stop to project when the said large-sized step comes out of the floor plate and to retract before it enters the floor plate.

7. An escalator apparatus substantially as hereinbefore described with reference to Figures 1 and 8 to 23 of the accompanying drawings.