

SPECIFICATION

Passenger conveyor balustrade

5 This invention relates to a balustrade for use with passenger conveyors such as escalators and, electrically operated passageways and, more particularly, to a balustrade which is formed of stainless steel sheets.

10 Passenger conveyors have become widely known as fixtures which are indispensable to a building as a means for conveying persons from one point to another within the building. In recent years, a variety of demands have been put forward for industrial designs of balustrades. As is well known, the balustrade constitutes a major part of a designed body in a passenger conveyor, and it is generally recognized by the parties concerned that whether the balustrade has an attractive industrial design or not is a major selling point in respect of making a discrimination among room designs.

As described in U.S. Patents Nos. 3,321,059 and 3,353,650, the balustrade includes stationary members except for an endless series of steps adapted to convey passengers thereon, and moving parts such as handrails. As described above, each balustrade includes, as main components thereof, a main deck member upon which handrail is mounted, a lower deck member and a glass panel, all of which constitute an object of industrial design. It is conventional to form the main and lower deck members by extruded material of aluminum alloy, of which surfaces have been subjected to alumite treatment.

Aluminum alloy material has been widely used for the main and lower deck members of a balustrade since it is advantageous in its formability into substantially complex shapes. However, the use of this material has a disadvantage in that the manufacturing cost thereof continues to increase due to high electric power consumption and the raw material therefor tends to be reduced. However, what is more significant than the high manufacturing cost is the fact the aluminum alloy material is relatively soft (as compared to such metallic materials as steel) so as to be readily marred. This presents a serious problem in which the respective members of a balustrade present scratches and impressions on the inner sides thereof facing the steps after the members have been contacted by a large number of passengers during several years of operation. Thus such passenger conveyors present an unsightly appearance. Additionally, in the case of passenger conveyors installed in underground markets, corrosion of the material of the balustrades caused by water adds to deterioration of the appearance of the balustrades.

Therefore, stainless steel sheets have begun to be used in place of aluminum alloy material, which sheets are superior to the latter in price stabilization, hardness and anticorrosive resistance. However, the use of stainless steel for balustrades raises the technical problems of the material being deformed during bending, as described hereinafter. Since these problems have not been solved satisfactorily, the practice of using a stainless steel sheet has not

yet become popular.

It is an object of the present invention to provide a balustrade for passenger conveyors which is easily manufactured and obviates the aforementioned problem of deformation during bending.

According to the present invention there is provided a balustrade for use with passenger conveyors, including a first deck member provided with a guide for guiding a handrail which is adapted to be moved in synchronism with an endless series of steps, a second deck member formed of sheet material connected to the first deck member, the second deck member having a substantially U-shaped cross-section with its opening facing in a direction opposite the handrail, each of the first and second deck members having a first arcuate shaped portion at landings of the passenger conveyor and second arcuate-shaped portions provided adjacent opposite ends of the first arcuate-shaped portion, the second arcuate-shaped portions having larger radii of curvature than that of the first arcuate-shaped portion, and flange means provided on the second deck member adjacent the opening in the region of the arcuate-shaped portions at said landings for preventing deformation of the second deck member.

Embodiments of the present invention will now be described by way of example with reference to the accompanying drawings, in which:

Figure 1 is a side elevational view of a portion of a passenger conveyor adjacent an upper landing;

Figure 2 is a sectional view taken along the line II-II in *Figure 1*, showing a conventional balustrade having deck members made of stainless steel material;

Figure 3 is a perspective view showing a deck member being subject to bending;

Figure 4 is a side view of a deck member;

Figure 5 is a partial, perspective view showing the manner in which the deck member is deformed;

Figure 6 is a sectional view taken along the line VI-VI in *Figure 5*;

Figure 7 is a graph showing elongation of various sections of a deck member;

Figure 8 is a side view showing a deck member according to an embodiment of the present invention;

Figure 9 is a partial enlarged view showing the essential part of the deck member shown in *Figure 8*;

Figure 10 is a sectional view similar to *Figure 2*, but showing a balustrade according to the present invention;

Figure 11 is a sectional view showing the essential part of the balustrade shown in *Figure 10*;

Figure 12 is a graph showing elongation of the bent portion of the balustrade according to the embodiment of *Figures 8* to *11*;

Figure 13 shows part of another embodiment according to the present invention;

Figure 14 shows a portion of a modified balustrade according to the invention;

As shown in *Figures 1* and *2*, a passenger conveyor comprises known balustrades each including stationary members disposed above steps except for an endless series of steps 1 for conveying passen-

gers thereon, and a handrail 2. The stationary members comprise mainly a main deck member 3 for supporting the handrail 2, a guide deck member 4, a lower deck member 5 and a balustrade glass panel 6, all of which are objects of industrial design, together with auxiliary parts such as fasteners 7 and guide rollers 8. A material for balustrades is, first of all, required to have a good bending workability since the contour of a balustrade consists of many curves of various shapes.

Problems encountered when a balustrade deck member made of stainless steel material is subjected to bending to define the terminal ends of the balustrade will be described hereinbelow by referring to the main deck member 3 at the semi-circular terminal end of the balustrade by way of example.

As shown in Figures 3 to 6, a main deck member 3 is generally of U-shape with its opening facing inwardly in a direction opposite the handrail, and includes straight portion A, B and a semi-circular curved portion C, of which outer peripheral surface g_1 has radius of curvature R_1 and of which inner peripheral surface g_2 has radius of curvature R_2 . As shown in Figure 3, bending of the main deck member 3 is generally performed by uniformly exerting forces Z on the inner peripheral portion thereof and by pulling the opposite ends a, b thereof in the directions of arrows X, Y. In this case, tensile forces in the directions X, Y cause the outer peripheral surface g_1 to be elongated in the direction of an arrow G and the inner peripheral surface to be contracted in the direction of an arrow E. This phenomenon of elongation and contraction is ordinarily explained by the manner in which the main deck member is contracted at its portion inwardly of a neutral axis L and elongated at its portion outwardly of the axis L owing to the cross-sectional configuration of the main deck member and to the bending form as shown in Figure 4. The aforementioned contraction naturally results in wrinkles S as shown in Figures 5 and 6. Therefore, the flange portions of the main deck member 3 with a width of W therebetween are displaced inwardly (S_1) or outwardly (S_2), which becomes a problem in the design and assembly of the glass panel 6 and lower deck member 5.

As described above, the production of the wrinkles S in the main deck member due to the contraction thereof is common knowledge to a person skilled in the art. However, the phenomenon of deformation upon bending discussed further below.

More specifically, the main deck member 3 adjacent the terminal portion consists of the semi-circular curved portion C and the straight portions A and B. It has been found that the wrinkles S were produced largely in the boundaries between the semi-circular curved portion C and the straight portions A, B.

The drawbacks of the prior art method will be explained by referring to Figure 7 in which the outer peripheral portion g_1 of the main deck member 3 in the region of the terminal portion is marked with uniformly spaced points and the elongation of the member 3 between each point is easily measured.

Figure 7 shows values of elongation obtained with the main deck member 3, which is formed of

stainless sheet material SUS 304 (Japanese standard notation for stainless steel plate having predetermined quantities of Ni and Cr) having a thickness of 1.5 mm and is shaped as having a radius R_1 of 300 mm as shown in Figure 4. It will be seen that the elongation of the deck member 3 is about 10% in the curved portion C and is about 2% in the straight portions A and B. In other words, the main deck member 3 is forced to undergo a sudden change in elongation at the curved portion which change amounts to five times as large as that of the straight portions. It will readily be understood that, as the result of this sudden change in elongation, bending deformation such as wrinkles S occurs mainly in the boundaries between the curved portion C and the straight portions A, B. It is to be noted that this inequality in elongation also occurs in cases where R_1 is greater than 300 mm. This is a major cause for the fact that balustrades formed of stainless steel have not been widely accepted up to the present time. It is also natural, of course, that the production of wrinkles S is greatly related to the position of the neutral axis L from the viewpoint of the strength of materials. As shown in Figure 6, the neutral axis L is spaced a short distance n from the outer peripheral surface g_1 and a radius of curvature R_2 at the neutral axis L is close to the radius of curvature R_1 of the outer peripheral surface g_1 . Accordingly, the amount of contraction near the inner peripheral surface g_2 becomes great and naturally manifests itself as wrinkles S.

In the case of balustrades formed of aluminum, it is possible to assimilate wrinkles by increasing the thickness of portions where wrinkles tend to be produced. However, such a measure can not be applied to balustrades formed of thin stainless steel plate.

In order to remove objectionable wrinkles, there is no other way available than the use of such an inefficient measure as heating the member to elevated temperatures and subjecting the same to manual hammering. This manual operation results in a less attractive balustrade which is more expensive to manufacture.

As aforesaid, wrinkles produced in balustrades formed of stainless steel is directly caused by the following factors:

1. A sudden change in elongation particularly in the boundaries between the straight portions and the curved portion;
2. The positioning of the neutral axis of the balustrade member remote from the inner peripheral surface in which wrinkles are likely to be produced.

Figures 8 to 12 show an embodiment of the present invention. In the drawings, a handrail 2 and a balustrade glass panel 6 are similar in construction to those of the prior balustrade described herein with reference to Figures 1 to 7.

According to the present invention, the balustrade includes a major curved portion and curved portions disposed on the opposite ends of the major curved portion and having a larger radius of curvature than that of the major curved portion, and there are provided flanges 9a which assist in preventing deformation, each of which extends a distance M_1

inwardly along an inner peripheral surface g_3 (corresponding to g_2 of the hereinbefore described prior deck member) of a main deck member 9 (corresponding to the main deck member 3 of the prior art balustrade).

It is to be noted that the main deck member 9 comprises a principal curved portion having the same radii of curvature R_1 (at its outer periphery) and R_2 (at its inner periphery) as those of the corresponding prior art deck member, and curved portions each extending over the area D and having a radius of curvature R_4 ($R_4 > R_1$). The magnitude of R_4 is preferable about twice to five times as large as that of R_1 , and when $R_1 = 300$ mm, R_4 is desirably in the range between 600 and 1500 mm.

The flanges 9a preferably extend a distance which amounts to one and half or more, or preferably to about three times as large as the plate thickness. The flanges 9a increase the flexural rigidity of the inner peripheral surface g_3 (as seen from Figure 11, the cross sectional area of the inner peripheral surface portion g_3 becomes larger than that of the inner peripheral surface portion g_2 of the prior art main deck member 3), and the neutral axis ℓ of the main deck member is substantially displaced toward the inner peripheral surface g_3 to be positioned a distance N from the outer peripheral surface g_1 where N is larger than n ($N > n$), and the radius of curvature is R_5 at the central portion of the main deck member 9. Thus, the provision of the flanges 9a are effective to substantially reduce the amount of contraction in the main deck member 9, thereby avoiding the production of wrinkles S.

Figure 12 diagrammatically shows the elongation of the main deck member 9, in which $R_1 = 300$ mm and $R_4 = 1000$ mm, in the same manner as in the prior art shown in Figure 7. As can be seen from Figure 12, excellent results can be obtained in a manner as presently to be discussed.

In Figure 12, it will be seen that a change in elongation at the areas D where $R_4 = 1000$ mm is represented by a much more gentle curve than that as shown in Figure 7 and as shown in dotted lines in Figure 12. That is, the elongation increase over a gentle slope from 2% in the straight portions A and B to about 10%. As a result, any objectionable wrinkles (deformation corresponding to the wrinkles S in the prior art) are scarcely produced in the boundaries between the straight portions A and B and the curved portion C which is in the form of an arc. The radius of curvature R_4 at the areas on both sides of the major arcuate-shaped portion having a radius of curvature R_1 can be suitably selected depending on the quality of material of the stainless steel plate and the stock thickness.

From the results of test shown and described hereinabove, it will be apparent that any bending deformation such as objectionable wrinkles can be prevented from being produced on a balustrade deck member of stainless steel plate which is formed on the inner peripheral surface thereof with flanges and which is shaped such that on both sides of a major curved portion having a radius of curvature R_1 are provided curved portions having a larger radius of curvature R_4 than R_1 .

From the foregoing description, it will be appreciated that the present invention facilitates bending a balustrade deck member formed of stainless steel, thereby greatly increasing productivity. An additional advantage of the present invention is that there is provided a passenger conveyor having a superior durability and free from the problem relating to surface damages and erosion associated with prior balustrade deck members formed of aluminum.

The present invention is not limited to terminal portions of a balustrade deck member as shown and described hereinabove, but is also applicable to any convex-shaped and concave-shaped portions thereof. Also, according to the present invention, the same results can be attained in a balustrade deck member, of which terminal portion includes, as shown in Figure 13, an arcuate-shaped portion ℓ_1 having a radius of curvature R_{10} , an arcuate-shaped portion ℓ_2 having a radius of curvature R_{11} ($R_{11} > R_{10}$) and disposed on one side of the arcuate-shaped portion ℓ_1 , and an arcuate-shaped portion ℓ_3 having a radius of curvature R_{12} ($R_{12} > R_{11} > R_{10}$) and disposed on the other side of the arcuate-shaped portion ℓ_1 . It should be understood that the present invention is not limited to the specific form of flanges 9a shown and described hereinabove and that a folded flange portion 10 shown in Figure 14, for example, can achieve the same results. The technical concept of the present invention can also be applied to balustrade deck members formed of steel materials and steel plates as well as stainless steel.

CLAIMS

1. A balustrade for use with passenger conveyors, including a first deck member provided with a guide for guiding a handrail which is adapted to be moved in synchronism with an endless series of steps, a second deck member formed of sheet material connected to the first deck member, the second deck member having a substantially U-shaped cross-section with its opening facing in a direction opposite the handrail, each of the first and second deck members having a first arcuate shaped portion at landings of the passenger conveyor and second arcuate-shaped portions provided adjacent opposite ends of the first arcuate-shaped portion, the second arcuate-shaped portions having larger radii of curvature than that of the first arcuate-shaped portion, and flange means provided on the second deck member adjacent the opening in the region of the arcuate-shaped portions at said landings for preventing deformation of the second deck member.

2. A balustrade as claimed in claim 1, wherein the flange means are formed so as to project from the second deck member for a distance which is in excess of 1.5 times the thickness of the sheet material of the second deck member.

3. A balustrade as claimed in claim 1, wherein the first and second deck members are formed of stainless steel material.

4. A balustrade as claimed in claim 1, wherein the second arcuate-shaped portions have radii of



18

inwardly along an inner peripheral surface g_3 (corresponding to g_2 of the hereinbefore described prior deck member) of a main deck member 9 (corresponding to the main deck member 3 of the prior art balustrade).

It is to be noted that the main deck member 9 comprises a principal curved portion having the same radii of curvature R_1 (at its outer periphery) and R_2 (at its inner periphery) as those of the corresponding prior art deck member, and curved portions each extending over the area D and having a radius of curvature R_4 ($R_4 > R_1$). The magnitude of R_4 is preferable about twice to five times as large as that of R_1 , and when $R_1 = 300$ mm, R_4 is desirably in the range between 600 and 1500 mm.

The flanges 9a preferably extend a distance which amounts to one and half or more, or preferably to about three times as large as the plate thickness. The flanges 9a increase the flexural rigidity of the inner peripheral surface g_3 (as seen from Figure 11, the cross sectional area of the inner peripheral surface portion g_3 becomes larger than that of the inner peripheral surface portion g_2 of the prior art main deck member 3), and the neutral axis ℓ of the main deck member is substantially displaced toward the inner peripheral surface g_3 to be positioned a distance N from the outer peripheral surface g_1 , where N is larger than n ($N > n$), and the radius of curvature is R_5 at the central portion of the main deck member 9. Thus, the provision of the flanges 9a are effective to substantially reduce the amount of contraction in the main deck member 9, thereby avoiding the production of wrinkles S.

Figure 12 diagrammatically shows the elongation of the main deck member 9, in which $R_1 = 300$ mm and $R_4 = 1000$ mm, in the same manner as in the prior art shown in Figure 7. As can be seen from Figure 12, excellent results can be obtained in a manner as presently to be discussed.

In Figure 12, it will be seen that a change in elongation at the areas D where $R_4 = 1000$ mm is represented by a much more gentle curve than that as shown in Figure 7 and as shown in dotted lines in Figure 12. That is, the elongation increase over a gentle slope from 2% in the straight portions A and B to about 10%. As a result, any objectionable wrinkles (deformation corresponding to the wrinkles S in the prior art) are scarcely produced in the boundaries between the straight portions A and B and the curved portion C which is in the form of an arc. The radius of curvature R_4 at the areas on both sides of the major arcuate-shaped portion having a radius of curvature R_1 can be suitably selected depending on the quality of material of the stainless steel plate and the stock thickness.

From the results of test shown and described hereinabove, it will be apparent that any bending deformation such as objectionable wrinkles can be prevented from being produced on a balustrade deck member of stainless steel plate which is formed on the inner peripheral surface thereof with flanges and which is shaped such that on both sides of a major curved portion having a radius of curvature R_1 , are provided curved portions having a larger radius of curvature R_4 than R_1 .

From the foregoing description, it will be appreciated that the present invention facilitates bending a balustrade deck member formed of stainless steel, thereby greatly increasing productivity. An additional advantage of the present invention is that there is provided a passenger conveyor having a superior durability and free from the problem relating to surface damages and erosion associated with prior balustrade deck members formed of aluminum.

The present invention is not limited to terminal portions of a balustrade deck member as shown and described hereinabove, but is also applicable to any convex-shaped and concave-shaped portions thereof. Also, according to the present invention, the same results can be attained in a balustrade deck member, of which terminal portion includes, as shown in Figure 13, an arcuate-shaped portion ℓ_1 having a radius of curvature R_{10} , an arcuate-shaped portion ℓ_2 having a radius of curvature R_{11} ($R_{11} > R_{10}$) and disposed on one side of the arcuate-shaped portion ℓ_1 , and an arcuate-shaped portion ℓ_3 having a radius of curvature R_{12} ($R_{12} > R_{11} > R_{10}$) and disposed on the other side of the arcuate-shaped portion ℓ_1 . It should be understood that the present invention is not limited to the specific form of flanges 9a shown and described hereinabove and that a folded flange portion 10 shown in Figure 14, for example, can achieve the same results. The technical concept of the present invention can also be applied to balustrade deck members formed of steel materials and steel plates as well as stainless steel.

CLAIMS

1. A balustrade for use with passenger conveyors, including a first deck member provided with a guide for guiding a handrail which is adapted to be moved in synchronism with an endless series of steps, a second deck member formed of sheet material connected to the first deck member, the second deck member having a substantially U-shaped cross-section with its opening facing in a direction opposite the handrail, each of the first and second deck members having a first arcuate shaped portion at landings of the passenger conveyor and second arcuate-shaped portions provided adjacent opposite ends of the first arcuate-shaped portion, the second arcuate-shaped portions having larger radii of curvature than that of the first arcuate-shaped portion, and flange means provided on the second deck member adjacent the opening in the region of the arcuate-shaped portions at said landings for preventing deformation of the second deck member.

2. A balustrade as claimed in claim 1, wherein the flange means are formed so as to project from the second deck member for a distance which is in excess of 1.5 times the thickness of the sheet material of the second deck member.

3. A balustrade as claimed in claim 1, wherein the first and second deck members are formed of stainless steel material.

4. A balustrade as claimed in claim 1, wherein the second arcuate-shaped portions have radii of



4 GB 2 006 706 B 4

curvature equal to two to five times as large as that of the first arcuate-shaped portion.

5. A balustrade substantially as hereinbefore described with reference to Figures 8 to 12, Figure 5 13, or these figures as modified by Figure 14 of the accompanying drawings.

Printed for Her Majesty's Stationery Office, by Croydon Printing Company Limited, Croydon, Surrey, 1982.
Published by The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.