SYSTEM AND METHOD FOR SYRINGE PLUNGER ENGAGEMENT WITH AN INJECTOR

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to United States Patent Application No. 14/925,722, filed on October 28, 2015 and entitled "System and Method for Syringe Plunger Engagement with an Injector", the disclosure of which is incorporated herein in its entirety.

BACKGROUND OF THE DISCLOSURE

Field of the Disclosure

[0002] The present disclosure relates generally to a system including a front-loading or front-installing syringe for use with a fluid injector and, further, to a connection interface for securing a syringe plunger to a piston of the fluid injector and to a method for engaging and disengaging the syringe plunger to and from the piston of the fluid injector.

Description of Related Art

[0003] In many medical diagnostic and therapeutic procedures, a medical practitioner, such as a physician, injects a patient with one or more medical fluids. In recent years, a number of injector-actuated syringes and fluid injectors for pressurized injection of fluids, such as a contrast solution (often referred to simply as "contrast"), a flushing agent, such as saline, and other medical fluids have been developed for use in procedures such as angiography, computed tomography (CT), ultrasound, magnetic resonance imaging (MRI), nuclear medicine, positron emission tomography (PET), and other imaging procedures. In general, these fluid injectors are designed to deliver a preset amount of fluid at a preset flow rate.

[0004] Various connection interfaces have been developed to facilitate the engagement of a syringe plunger to and from a piston of the fluid injector. In some aspects, the syringe having a retention feature is inserted into a syringe port on the fluid injector by aligning the syringe with a corresponding locking feature provided on the fluid injector. Such alignment also aligns the plunger in the syringe with the piston on the fluid injector such that the piston can engage the plunger and drive the plunger through the syringe barrel to draw fluid into the syringe barrel or deliver fluid from the syringe barrel. In other aspects, upon initial engagement with the plunger, the piston may be rotated, in a clockwise or counter-clockwise direction, until the piston engages a catch on the plunger. In further aspects, the piston has one or more radially-extendable pins that engage a lip on the plunger.

[0005] Many of the existing connection interfaces have construction that requires a complex piston head with various sensor elements and active engagement structures. There is a need in the art for an improved connection interface that allows for a simpler and easier

engagement and disengagement of the syringe plunger to and from the piston of the fluid injector. There is a further need in the art for reducing or eliminating the need for the operator to rotationally align the syringe with the fluid injector to allow for a proper engagement of the syringe plunger with the piston of the fluid injector. There is a further need in the art for reducing the angle of rotation through which the operator rotates the syringe to release the syringe plunger from the piston for removal of the syringe. While various syringe plunger connection interfaces and methods are known in the medical field, improved connection interfaces between the syringe plunger and the piston of the fluid injector and methods for engaging and disengaging the syringe plunger to and from the piston of the fluid injector continue to be in demand.

SUMMARY OF DISCLOSURE

[0006] In view of the disadvantages of the existing connection interfaces between a syringe plunger and a piston of a fluid injector, there is a need in the art for an improved connection interface between a syringe plunger and a piston of a fluid injector that overcomes the deficiencies of the prior art. There is an additional need for improved methods for engaging and disengaging a syringe plunger to and from a piston of a fluid injector to allow easy loading or removal of a syringe to and from a fluid injector.

[0007] In accordance with some aspects, plunger for use with a syringe may have a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis. The plunger may have at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second segment protruding toward the distal end of the plunger body and deflectable relative to the first segment, and at least one actuation member associated with the at least one resiliently deflectable retaining member. The at least one actuation member may interact with a piston used to engage the plunger to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston.

[0008] In accordance with other aspects, at least one alignment member may be associated with the plunger body or the at least one resiliently deflectable retaining member. The at least one alignment member may have an alignment surface for guiding the piston into self-orienting alignment with the plunger. The at least one alignment member may have a plurality of alignment members spaced apart around the plunger longitudinal axis. The plurality of alignment members may be spaced apart at equal radial intervals around the plunger longitudinal axis. The second segment of the at least one resiliently deflectable retaining member may be deflectable radially relative to the first segment away from the

plunger longitudinal axis. The at least one resiliently deflectable retaining member may be linearly or curvilinearly contiguous between the first segment and the second segment. The second segment of the at least one resiliently deflectable retaining member may be angled toward the plunger longitudinal axis.

[0009] In accordance with other aspects, the at least one actuation member may be provided on a surface of the at least one resiliently deflectable retaining member. The at least one actuation member may be at the second segment of the at least one resiliently deflectable retaining member. The at least one actuation member may be angled relative to a plane defined by a body of the at least one resiliently deflectable retaining member. The at least one resiliently deflectable retaining member may have a plurality of resiliently deflectable retaining members spaced apart around the plunger longitudinal axis. The plurality of resiliently deflectable retaining members may be spaced apart at equal radial intervals around the plunger longitudinal axis. A terminal surface of the second segment of the at least one resiliently deflectable retaining member may engage a surface of the piston to releasably lock the plunger with the piston. The terminal surface may be linear. The terminal surface may be perpendicular or angled relative to a direction of the plunger longitudinal axis.

[0010] In accordance with other aspects, the plunger body may define an interior cavity with a conical-shaped portion at the distal end of the plunger body and a cylindrical-shaped portion at the proximal end of the plunger body. The first segment of the at least one resiliently deflectable member may be attached to an inner surface of the plunger body. The at least one resiliently deflectable retaining member may protrude from the inner surface of the plunger body into the interior cavity. A plunger cover may be disposed over at least a portion of an outer surface of the plunger body. The plunger cover may have a resilient seal disposed around at least a portion of a circumferential sidewall of the plunger cover. The resilient seal may have an inner surface at least partially seated in a groove in the circumferential sidewall of the plunger body and an outer surface adapted to slidably engage with a barrel of a syringe. The actuating member may be a cam member.

[0011] In accordance with other aspects, a plunger for use with a syringe may have a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis. The plunger may have at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second end protruding toward the distal end of the plunger body and deflectable relative to the first segment and at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member. The at least

one alignment member may guide a piston into self-orienting alignment with the plunger during engagement of the plunger with the piston. The plunger may have at least one actuation member associated with the at least one resiliently deflectable retaining member. The at least one actuation member may interact with the piston to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston. A terminal surface of the second segment of the at least one resiliently deflectable retaining member may engage a surface of the piston to releasably lock the plunger with the piston. The at least one actuation member may be at the second segment of the at least one resiliently deflectable retaining member. The second segment of the at least one resiliently deflectable retaining member may be deflectable radially relative to the first segment away from the plunger longitudinal axis.

[0012] In accordance with other aspects, a plunger for use with a syringe may have a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis. The plunger may have at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second segment deflectable relative to the first segment, at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member, and at least one actuation member associated with the at least one resiliently deflectable retaining member. The at least one alignment member may guide a piston into self-orienting alignment with the plunger during engagement of the plunger with the piston. The at least one actuation member may interact with the piston to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston. The second segment of the at least one resiliently deflectable retaining member may protrude towards the distal end of the plunger body and wherein the second end of the at least one resiliently deflectable retaining member is deflectable radially relative to the first end away from the plunger longitudinal axis. The second end of the at least one resiliently deflectable retaining member may protrude in a direction circumferentially around the longitudinal axis of the plunger body and wherein the second end of the at least one resiliently deflectable retaining member is deflectable circumferentially relative to the first end.

[0013] In accordance with other aspects, a syringe may have a barrel having a barrel proximal end, a barrel distal end having a discharge nozzle, and a barrel sidewall extending between the barrel proximal end and the barrel distal end. The syringe may have a plunger slidably disposed within the barrel and reciprocally movable between the barrel proximal end

and the barrel distal end. The plunger may have a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis, at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second segment protruding toward the distal end of the plunger body and deflectable relative to the first segment, and at least one actuation member associated with the at least one resiliently deflectable retaining member. The at least one actuation member may interact with a piston used to engage the plunger to radially deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston.

[0014] Various aspects of the present disclosure may be further characterized by one or more of the following clauses:

[0015] Clause 1. A plunger for use with a syringe, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second segment protruding toward the distal end of the plunger body and deflectable relative to the first segment; and

at least one actuation member associated with the at least one resiliently deflectable retaining member,

wherein the at least one actuation member interacts with a piston used to engage the plunger to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston.

[0016] Clause 2. The plunger according to clause 1, further comprising at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member, the at least one alignment member having an alignment surface for guiding the piston into self-orienting alignment with the plunger.

[0017] Clause 3. The plunger according to clause 2, wherein the at least one alignment member comprises a plurality of alignment members spaced apart around the plunger longitudinal axis.

[0018] Clause 4. The plunger according to clause 3, wherein the plurality of alignment members is spaced apart at equal radial intervals around the plunger longitudinal axis

[0019] Clause 5. The plunger according to any of clauses 1-4, wherein the second segment of the at least one resiliently deflectable retaining member is deflectable radially relative to the first segment away from the plunger longitudinal axis.

[0020] Clause 6. The plunger according to any of clauses 1-5, wherein the at least one resiliently deflectable retaining member is linearly or curvilinearly contiguous between the first segment and the second segment.

[0021] Clause 7. The plunger according to any of clauses 1-6, wherein the second segment of the at least one resiliently deflectable retaining member is angled toward the plunger longitudinal axis.

[0022] Clause 8. The plunger according to any of clauses 1-7, wherein the at least one actuation member is provided on a surface of the at least one resiliently deflectable retaining member.

[0023] Clause 9. The plunger according to clause 8, wherein the at least one actuation member is at the second segment of the at least one resiliently deflectable retaining member.

[0024] Clause 10. The plunger according to any of clauses 1-9, wherein the at least one actuation member is angled relative to a plane defined by a body of the at least one resiliently deflectable retaining member.

[0025] Clause 11. The plunger according to any of clauses 1-10, wherein the at least one resiliently deflectable retaining member comprises a plurality of resiliently deflectable retaining members spaced apart around the plunger longitudinal axis.

[0026] Clause 12. The plunger according to clause 11, wherein the plurality of resiliently deflectable retaining members is spaced apart at equal radial intervals around the plunger longitudinal axis.

[0027] Clause 13. The plunger according to any of clauses 1-12, wherein a terminal surface of the second segment of the at least one resiliently deflectable retaining member engages a surface of the piston to releasably lock the plunger with the piston.

[0028] Clause 14. The plunger according to clause 13, wherein the terminal surface is linear.

[0029] Clause 15. The plunger according to clause 13 or clause 14, wherein the terminal surface is perpendicular or angled relative to a direction of the plunger longitudinal axis.

[0030] Clause 16. The plunger according to any of clauses 1-15, wherein the plunger body defines an interior cavity with a conical-shaped portion at the distal end of the plunger body and a cylindrical-shaped portion at the proximal end of the plunger body.

[0031] Clause 17. The plunger according to clause 16, wherein the first segment of the at least one resiliently deflectable member is attached to an inner surface of the plunger body.

[0032] Clause 18. The plunger according to clause 17, wherein the at least one resiliently deflectable retaining member protrudes from the inner surface of the plunger body into the interior cavity.

[0033] Clause 19. The plunger according to any of clauses 1-18, further comprising a plunger cover disposed over at least a portion of an outer surface of the plunger body, the plunger cover comprising a resilient seal disposed around at least a portion of a circumferential sidewall of the plunger cover.

[0034] Clause 20. The plunger according to clause 19, wherein the resilient seal comprises an inner surface at least partially seated in a groove in the circumferential sidewall of the plunger body and an outer surface adapted to slidably engage with a barrel of a syringe.

[0035] Clause 21. The plunger according to any of clauses 1-20, wherein the actuating member is a cam member.

[0036] Clause 22. A plunger for use with a syringe, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second end protruding toward the distal end of the plunger body and deflectable relative to the first segment; and

at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member,

wherein the at least one alignment member guides a piston into self-orienting alignment with the plunger during engagement of the plunger with the piston.

[0037] Clause 23. The plunger according to clause 22, further comprising at least one actuation member associated with the at least one resiliently deflectable retaining member, wherein the at least one actuation member interacts with the piston to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston.

[0038] Clause 24. The plunger according to clause 23, wherein a terminal surface of the second segment of the at least one resiliently deflectable retaining member engages a surface of the piston to releasably lock the plunger with the piston.

[0039] Clause 25. The plunger according to clause 23 or clause 24, wherein the at least one actuation member is at the second segment of the at least one resiliently deflectable retaining member.

[0040] Clause 26. The plunger according to any of clauses 23-25, wherein the second segment of the at least one resiliently deflectable retaining member is deflectable radially relative to the first segment away from the plunger longitudinal axis.

[0041] Clause 27. A plunger for use with a syringe, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second segment deflectable relative to the first segment;

at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member; and

at least one actuation member associated with the at least one resiliently deflectable retaining member,

wherein the at least one alignment member guides a piston into self-orienting alignment with the plunger during engagement of the plunger with the piston, and

wherein the at least one actuation member interacts with the piston to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston.

[0042] Clause 28. The plunger according to clause 27, wherein the second segment of the at least one resiliently deflectable retaining member protrudes towards the distal end of the plunger body and wherein the second end of the at least one resiliently deflectable retaining member is deflectable radially relative to the first end away from the plunger longitudinal axis.

[0043] Clause 29. The plunger according to clause 27 or clause 28, wherein the second end of the at least one resiliently deflectable retaining member protrudes in a direction circumferentially around the longitudinal axis of the plunger body and wherein the second end of the at least one resiliently deflectable retaining member is deflectable circumferentially relative to the first end.

[0044] Clause 30. A syringe comprising:

a barrel having a barrel proximal end, a barrel distal end having a discharge nozzle, and a barrel sidewall extending between the barrel proximal end and the barrel distal end; and

a plunger slidably disposed within the barrel and reciprocally movable between the barrel proximal end and the barrel distal end, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to the plunger body and a second segment protruding toward the distal end of the plunger body and deflectable relative to the first segment; and

at least one actuation member associated with the at least one resiliently deflectable retaining member,

wherein the at least one actuation member interacts with a piston used to engage the plunger to radially deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston.

[0045] These and other features and characteristics of syringes, syringe plungers, and systems having syringes and/or syringe plungers, as well as the methods of operation and functions of the related elements of structures and the combination of parts and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only. As used in the specification and the claims, the singular form of "a", "an", and "the" include plural referents unless the context clearly dictates otherwise.

BRIEF DESCRIPTION OF THE DRAWINGS

[0046] **FIG. 1** is a top perspective view of a system including a fluid injector and at least one syringe according to an aspect of the present disclosure;

[0047] **FIG. 2** is a side cross-sectional view of a syringe according to one aspect of the present disclosure;

[0048] **FIG. 3A** is a top perspective view of a plunger according to one aspect of the present disclosure;

[0049] **FIG. 3B** is a bottom perspective view of the plunger shown in **FIG. 3A**;

[0050] **FIG. 3C** is a bottom view of the plunger shown in **FIG. 3A**;

[0051] **FIG. 3D** is a side view of the plunger shown in **FIG. 3A**;

[0052] **FIG. 3E** is a side cross-sectional view of the plunger shown in **FIG. 3A**;

[0053] **FIG. 4A** is a top perspective view of a piston according to one aspect of the present disclosure;

[0054] **FIG. 4B** is an exploded perspective view of the piston shown in **FIG. 4A**;

[0055] **FIG. 4C** is a side view of the piston shown in **FIG. 4A**;

[0056] **FIG. 5A** is a side view of a plunger and a piston in an assembled state;

[0057] **FIG. 5B** is a side cross-sectional view of the plunger and the piston during initial engagement of the piston with the plunger;

[0058] **FIG. 5C** is a side cross-sectional view of the plunger and the piston prior to full engagement of the piston with the plunger;

[0059] **FIG. 5D** is a side cross-sectional view of the plunger and the piston during full engagement of the piston with the plunger;

[0060] **FIG. 6A** is a top perspective view of a plunger according to another aspect of the present disclosure;

[0061] **FIG. 6B** is a bottom perspective view of the plunger shown in **FIG. 6A**;

[0062] **FIG. 7A** is a perspective cross-sectional view of the plunger shown in **FIGS. 6A-6B** and a piston prior to initial engagement of the piston with the plunger;

[0063] **FIG. 7B** is a side cross-sectional view of the plunger and piston shown in **FIG. 7A**;

[0064] **FIG. 8A** is a perspective cross-sectional view of the plunger and the piston during initial engagement of the piston with the plunger;

[0065] **FIG. 8B** is a side partial cross-sectional view of the plunger and the piston shown in **FIG. 8A**;

[0066] **FIG. 9A** is a perspective cross-sectional view of the plunger and the piston prior to full engagement of the piston with the plunger;

[0067] **FIG. 9B** is a side cross-sectional view of the plunger and piston shown in **FIG. 9A**;

[0068] **FIG. 10A** is a perspective cross-sectional view of the plunger and the piston during full engagement of the piston with the plunger;

[0069] **FIG. 10B** is a side cross-sectional view of the plunger and piston shown in **FIG. 10A**;

[0070] **FIG. 11A** is a perspective cross-sectional view of the plunger and the piston during initial disengagement as the plunger is rotated relative to the piston;

[0071] **FIG. 11B** is a side cross-sectional view of the plunger and piston shown in **FIG. 11A**;

[0072] **FIG. 12A** is a perspective cross-sectional view of the plunger and the piston during disengagement with a locking ring of the piston in a forward position;

[0073] **FIG. 12B** is a side cross-sectional view of the plunger and piston shown in **FIG. 12A**;

[0074] **FIG. 13** is a side cross-sectional view of a first adapter configured for connecting a non-compatible plunger with a piston in accordance with one aspect of the present disclosure;

[0075] **FIG. 14** is a side cross-sectional view of a second adapter configured for connecting a plunger with a non-compatible piston in accordance with one aspect of the present disclosure;

[0076] **FIG. 15A** is a front perspective view of a piston in accordance with another aspect;

[0077] **FIG. 15B** is a side view of the piston head shown in **FIG. 15A**;

[0078] **FIG. 15C** is a front perspective view of the piston shown in **FIG. 15A** and a plunger removed from the piston;

[0079] **FIG. 15D** is a front perspective of the piston and plunger shown in **FIG. 15C** with the plunger assembled on the piston;

[0080] **FIG. 15E** is a side cross-sectional view of the plunger and piston shown in **FIG. 15D**;

[0081] **FIG. 15F** is an exploded perspective view of the piston shown in **FIG. 15A**;

[0082] **FIG. 15G** is a bottom perspective view of a plunger in accordance with another aspect of the present disclosure;

[0083] **FIG. 16** is a cylindrical plan projection view of the piston and the plunger shown in **FIG. 15C**;

[0084] **FIG. 17** is a cylindrical plan projection view of a piston and a plunger in accordance with another aspect of the present disclosure;

[0085] **FIG. 18** is a cylindrical plan projection view of a piston and a plunger in accordance with another aspect of the present disclosure;

[0086] **FIG. 19** is a cylindrical plan projection view of a piston and a plunger in accordance with another aspect of the present disclosure;

[0087] **FIG. 20A** is a top perspective view of a piston in accordance with another aspect;

[0088] **FIG. 20B** is a top perspective view of the piston shown in **FIG. 20A** and a plunger in accordance with one aspect of the present disclosure;

[0089] **FIG. 20C** is a bottom perspective view of the plunger shown in **FIG. 20B**;

[0090] **FIG. 20D** is a side cross-sectional view of the plunger shown in **FIG. 20C**;

[0091] **FIG. 21A** is a front perspective view of a piston and a plunger in accordance with another aspect of the present disclosure;

[0092] **FIG. 21B** is a detailed cross-sectional side view of **FIG. 21A** showing the engagement between the piston and the plunger;

[0093] **FIG. 21C** is a cross-sectional top view of **FIG. 21A** showing the engagement between the piston and the plunger;

[0094] **FIG. 22A** is a top perspective view of a plunger in accordance with another aspect of the present disclosure;

[0095] **FIG. 22B** is a bottom perspective view of the plunger shown in **FIG. 22A**;

[0096] **FIG. 22C** is a cross-sectional side view of the plunger illustrated in **FIG. 22A** showing the engagement between a piston and the plunger;

[0097] **FIG. 22D** is a cross-sectional top view of the plunger illustrated in **FIG. 22A** showing the engagement between a piston and the plunger;

[0098] **FIG. 23A** is a top perspective view of a plunger in accordance with another aspect of the present disclosure;

[0099] **FIG. 23B** is a first cross-sectional side view of the plunger illustrated in **FIG. 23A** showing the engagement between a piston and the plunger;

[00100] **FIG. 23C** is a second cross-sectional side view of the plunger illustrated in **FIG. 23A** showing the engagement between the piston and the plunger;

[00101] **FIG. 23D** is a cross-sectional top view of the plunger illustrated in **FIG. 23A** showing the engagement between a piston and the plunger;

[00102] **FIG. 24A** is a top perspective view of a piston and a plunger in accordance with another aspect of the present disclosure;

[00103] **FIG. 24B** is a side cross-sectional view of the piston and the plunger of **FIG. 24A** shown in an assembled state; and

[00104] **FIG. 24C** is a top cross-sectional view of the piston and the plunger shown in **FIG. 24B**.

DETAILED DESCRIPTION

[00105] For purposes of the description hereinafter, the terms “upper”, “lower”, “right”, “left”, “vertical”, “horizontal”, “top”, “bottom”, “lateral”, “longitudinal”, and derivatives thereof shall relate to the components as they are oriented in the drawing figures. When used in relation to a syringe and/or a plunger, the term “proximal” refers to a portion of a syringe and/or a plunger nearest a fluid injector when a syringe and/or a plunger is oriented for connecting to a fluid injector. The term “distal” refers to a portion of a syringe and/or a plunger farthest away from a fluid injector when a syringe and/or a plunger is oriented for connecting to a fluid injector. The term “radial” refers to a direction in a cross-sectional plane normal to a longitudinal axis of a syringe, a plunger, and/or a piston extending between proximal and distal ends. The term “circumferential” refers to a direction around an inner or outer surface of a sidewall of a syringe, a plunger, and/or a piston. The term “axial” refers to a direction along a longitudinal axis of a syringe, a piston, and/or a piston extending between

the proximal and distal ends. The term "self-orienting" means that a piston head or a plunger orients itself to a correct orientation relative to a plunger or piston head, respectively, without a rotational effort by a technician or a fluid injector. The term "curvilinear" refers to a shape of a surface that has one or more curved lines, one or more straight lines with one or more curved lines, and/or one or more straight line segments arranged non-linearly. It is to be understood, however, that the disclosure may assume alternative variations and step sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification, are simply exemplary aspects of the disclosure. Hence, specific dimensions and other physical characteristics related to the aspects disclosed herein are not to be considered as limiting.

[00106] Referring to the drawings in which like reference characters refer to like parts throughout the several views thereof, the present disclosure is generally directed to a syringe plunger and a connection interface for connecting the syringe plunger to a piston of a fluid injector. Various aspects are directed to syringe plungers that may be connected to and disconnected from the piston. In various aspects, such plungers may be manually, hydraulically, or electrically activated. Furthermore, the present disclosure provides a quick and easy solution for engaging and disengaging the syringe plunger to and from the piston without a specific rotational orientation of the plunger about the plunger longitudinal axis relative to a longitudinal axis of the piston. For example, the piston may be advanced forward until it engages with the plunger, regardless of rotational orientation of the piston relative to the plunger about a longitudinal axis of the syringe, as described herein. In addition, a simple angular rotation of the plunger relative to the piston about a longitudinal axis of the syringe may allow for detachment of the two elements. In certain aspects, the syringe and the plunger may be engaged with a syringe port and piston extending from the syringe port, respectively. Concomitant disengagement of the syringe from the syringe port and the plunger from the piston may require the operator or technician to manually rotate the syringe. According to various aspects, rotation of the syringe may first result in disengagement of the plunger from the piston, as described herein, followed by disengagement of the syringe from the syringe port, for example as described in U.S. Patent Application Serial Nos. 14/526,294 and 14/526,395, both of which were filed on October 28, 2014, U.S. Patent No. 6,652,489, issued November 25, 2003, and U.S. Patent No. 7,540,856, issued June 2, 2009, the disclosures of each of which are incorporated by reference herein. In specific aspects, since rotation of the syringe also results in rotation of the plunger, due to frictional fit of plunger within the

syringe, to affect disengagement of the plunger from the piston prior to disengagement of the syringe from the injector port, the rotational distance that the plunger must turn relative to the piston to cause disengagement of the plunger from the piston must be less than the rotational distance that the syringe must turn relative to the injector port to cause disengagement of the syringe from the port. Various aspects of the present disclosure provide a piston/plunger interface mechanism with features that provide this sequential disengagement requirement.

[00107] With reference to **FIG. 1**, a fluid injector **10** (hereinafter referred to as "injector **10**"), such as an automated or powered fluid injector, is adapted to interface with and actuate at least one syringe **12**, each of which may be independently filled with a medical fluid **F**, such as contrast media, saline solution, or any desired medical fluid. The injector **10** may be used during a medical procedure to inject the medical fluid into the body of a patient by driving a plunger **26** of the at least one syringe **12** with at least one piston. The injector **10** may be a multi-syringe injector, wherein several syringes **12** may be oriented in a side-by-side or other arrangement and include plungers **26** separately actuated by respective pistons associated with the injector **10**. In aspects with two syringes arranged in a side-by-side relationship and filled with two different medical fluids, the injector **10** may deliver fluid from one or both of the syringes **12**.

[00108] The injector **10** may be enclosed within a housing **14** formed from a suitable structural material, such as plastic or metal. The housing **14** may have various shapes and sizes depending on a desired application. For example, the injector **10** may be a free-standing structure configured to be placed on the floor with a stationary or movable platform. Alternatively, the injector **10** may be configured for placement on a suitable table or support frame. The injector **10** includes at least one syringe port **16** for connecting the at least one syringe **12** to respective piston elements. In some aspects, the at least one syringe **12** includes at least one syringe retaining member for retaining the syringe **12** within the syringe port **16** of the injector **10**. The at least one syringe retaining member operatively engages a locking mechanism provided on or in the syringe port **16** of the injector **10** to facilitate loading and/or removal of the syringe **12** to and from the injector **10**, as described herein. The syringe retaining member and the locking mechanism together define a connection interface for connecting the syringe **12** to the injector **10**.

[00109] At least one fluid path set **17** may be fluidly connected with the at least one syringe **12** for delivering medical fluid **F** from the at least one syringe **12** to a catheter, needle, or other fluid delivery device (not shown) inserted into a patient at a vascular access site. Fluid flow from the at least one syringe **12** may be regulated by a fluid control module

(not shown). The fluid control module may operate various pistons, valves, and/or flow regulating structures to regulate the delivery of the medical fluid, such as saline solution and contrast, to the patient based on user selected injection parameters, such as injection flow rate, duration, total injection volume, and/or ratio of contrast media and saline. One example of a suitable front-loading fluid injector **10** that may be modified for use with the above-described system including at least one syringe **12** and at least one syringe interface for self-oriented loading and releasable retaining of the at least one syringe **12** with the fluid injector **10** described herein with reference to **FIG. 1** are disclosed in United States Patent No. 5,383,858 to Reilly et al. and U.S. Patent Application Serial Nos. 14/526,294 and 14/526,395, both of which were filed on October 28, 2014 which are incorporated by reference in their entirety. Another example of relevant multi-fluid delivery systems that may be modified for use with the present system are found in United States Patent No. 7,553,294 to Lazzaro et al.; United States Patent No. 7,666,169 to Cowan et al.; International Patent Publication No. WO 2012/155035; and United States Patent Application Publication No. 2014/0027009 to Riley et al.; the disclosures of which are incorporated herein by reference. Other aspects may include new fluid injector systems designed to include various aspects of the piston plunger interfaces described herein.

[00110] Having described the general structure and function of the injector **10**, the at least one syringe **12** will now be discussed in greater detail. With reference to **FIG. 2**, the syringe **12** generally has a cylindrical syringe barrel **18** formed from glass, metal, or a suitable medical-grade plastic. The barrel **18** has a proximal end **20** and a distal end **24**, with a sidewall **19** extending therebetween along a syringe longitudinal axis **15** extending through a center of the barrel **18**. The barrel **18** may be made from a transparent or translucent material, and may include at least one fluid verification member **11** (shown in **FIG. 1**) for verifying a presence of the fluid **F** within the syringe barrel **18**. A nozzle **22** extends from the distal end **24** of the barrel **18**. The barrel **18** has an outer surface **21** and an inner surface or wall **23** that defines an interior volume **25** for receiving the fluid therein. The proximal end **20** of the barrel **18** may be sealed with the plunger **26** that is slidable through the barrel **18**. The plunger **26** may have a plunger cover **58** that forms a liquid-tight seal against the inner surface **23** of sidewall **19** of the barrel **18** as the plunger **26** is advanced therethrough. Details of various aspects of the plunger body and plunger cover are set forth herein.

[00111] A drip flange **35** may extend radially outwardly from the outer surface **21** of the syringe barrel **18** relative to the longitudinal axis **15**. The drip flange **35** may extend around at least a portion of the outer circumference of the barrel **18**. The drip flange **35** may prevent

fluid that drips from the nozzle **22** from entering the syringe port **16** on the injector **10**. In this manner, the drip flange **35** helps reduce the amount of fluid that may enter the syringe port **16** and jam or otherwise interfere with the connection interface and/or the interior mechanics and electronics of the injector **10**. In some aspects, the drip flange **35** defines a stop surface that delimits the depth at which an insertion section **30** of the syringe **12** may be inserted into the syringe port **16** (shown in **FIG. 1**). The drip flange **35** may be formed integrally with the barrel **18** or it may be affixed or otherwise secured to the outer surface **21** of the barrel **18** using, for example, a frictional fit and/or an adhesive, welding, or by molding. In other aspects, the drip flange **35** may be formed on the outer surface **21** of the barrel **18** by etching, laser cutting, or machining.

[00112] With continued reference to **FIG. 2**, the proximal end **20** of the syringe **12** is sized and adapted for being removably inserted in the syringe port **16** of the injector **10** (shown in **FIG. 1**). In some aspects, the proximal end **20** of the syringe **12** defines the insertion section **30** that is removably inserteable into the syringe port **16** of the injector **10** while the remaining portion of the syringe **12** remains outside of the syringe port **16**. In certain aspects, the proximal end **20** of the syringe **12** includes one or more syringe retaining members (not shown) adapted to form a locking engagement with a corresponding locking mechanism in the syringe port **16** of the injector **10** for releasably retaining the syringe **12** in the syringe port **16**. Various retaining members for releasably locking the syringe **12** with the injector **10** are described in, for example, U.S. Patent Application No. 14/526,294, filed on October 28, 2014 and entitled "Self-Orienting Syringe and Syringe Interface", and U.S. Patent Application No. 14/526,395, filed on October 28, 2014 and entitled "Self-Orienting Syringe and Syringe Interface", the disclosures are incorporated herein by reference in their entirety.

[00113] Exemplary syringes suitable for use with the injector **10** depicted in **FIG. 1** and which can be adopted for use with a fluid verification system are described in United States Patent No. 5,383,858 to Reilly et al., which is assigned to the assignee of the present application, the disclosure of which is incorporated by reference in its entirety. Additional exemplary syringes are disclosed in, for example, United States Patent No. 6,322,535 to Hitchins et al. and United States Patent No. 6,652,489 to Trocki et al., both of which are assigned to the assignee of the present application, and the disclosures of which are both incorporated by reference in their entireties.

[00114] With reference to **FIGS. 3A-3B**, the plunger **26** is shown in accordance with one aspect of the present disclosure. The barrel **18** of the syringe **12** is omitted from **FIGS. 3A-3B** for clarity. The plunger **26** includes a plunger body **32** defining a plunger longitudinal axis **34**

(shown in **FIG. 3A**) and having a proximal end **36**, a distal end **38**, and a circumferential sidewall **39** connecting the proximal end **36** and the distal end **38**. The sidewall **39** may have a uniform or non-uniform thickness between the proximal end **36** and the distal end **38**. The sidewall **39** may have a continuous outer surface. In some aspects, the sidewall **39** may have a discontinuous outer surface having one or more portions of sidewall **39** separated by one or more voids or openings. The plunger body **32** may be formed from glass, metal, plastic, or other suitable material, including medical grade versions.

[00115] With continued reference to **FIGS. 3A-3B**, the plunger body **32** has an interior cavity **40** defined by a conical-shaped portion **42** at the distal end **38** of the plunger body **32** and a cylindrical-shaped portion **44** at the proximal end **36** of the plunger body **32**. The conical-shaped portion **42** may be monolithically formed with the cylindrical-shaped portion **44**. In some aspects, the conical-shaped portion **42** may be affixed or otherwise secured to the cylindrical-shaped portion **44** of the plunger body **32** using, for example, a frictional fit and/or an adhesive, welding, or by molding. The conical-shaped portion **42** may have a truncated end **46** that has a central opening **48**. In some aspects, the distal end **38** of the plunger body **32** may be partially or fully enclosed such that the plunger **26** does not have a central opening **48**. In other aspects, the distal end **38** of the plunger body **32** may have one or more radial openings, such as the openings **49** shown in **FIG. 20B**.

[00116] With reference to **FIG. 3E**, the plunger **26** may have a plunger cover **58** with a resilient seal **59** that covers at least a portion of an outer surface **60** of the plunger body **32**. The seal **59** may be a resilient and flexible seal that engages the inner surface **23** of the syringe barrel **18** (shown in **FIG. 2**) such that the seal **59** seals the interior volume **25** of the syringe barrel **18** in a liquid-tight manner. The plunger cover **58** may be provided separately from the plunger body **32**, or it may be integrally formed with the plunger body **32**, such as by co-molding. In some aspects, the outer surface **60** of the plunger body **32** may have a circumferential groove **62**. At least a portion of the plunger cover **58** may be retained within the circumferential groove **62**. The exterior surface **64** of the seal **59** may have one or more lips, projections, or other sealing elements **66** that engage the inner surface **23** of the syringe barrel **18**. In some aspects, the one or more sealing elements **66** of the seal **59** may be made from an elastomeric material that resiliently engages the inner surface **23** of the syringe barrel **18** (shown in **FIG. 2**). The at least one extension **56** on the plunger body **32** may prevent the seal **59** from coming out of axial engagement with the syringe **12** as the plunger **26** is moved through the syringe barrel **18**.

[00117] Referring again to **FIGS. 3A-3B**, the plunger **26** may have at least one resiliently deflectable retaining member **68** (hereinafter "retaining member **68**") protruding from the plunger body **32**. In some aspects, the at least one retaining member **68** may protrude in a direction from the proximal end **36** toward the distal end **38** of the plunger body **32**. In some aspects, the at least one retaining member **68** may protrude distally and radially inward from an inner surface **52** of the plunger body **32** into the interior cavity **40**. In various aspects, the at least one retaining member **68** may be formed as a cantilever spring element, a coil spring element, or an elastomeric portion of the plunger body **32**.

[00118] With reference to **FIG. 3E**, the at least one retaining member **68** has a first segment or a first end **70** connected to the plunger body **32** and a second segment or a second end **72** protruding distally from the first end **70**. The second end **72** may deflect or twist relative to the first end **70**. As described herein, the second end **72** may be radially deflectable relative to the first end **70** when the at least one retaining member **68** engages a piston of the fluid injector **10**. In some aspects, the retaining member **68** may be radially deflected outwards, away from the longitudinal axis **34** when deflected by a portion of a piston during the engagement process. The resiliently deflectable retaining member **68** may then move radially inwards under the restoring force of the retaining member **68** to engage a portion of the piston to releasably lock the plunger body **26** with the piston. In some aspects where the retaining member **68** is circumferential with the plunger body **32** (described herein), the second end **72** may be circumferentially deflectable relative to the first end **70**. The first end **70** and the second end **72** may be spaced apart in a direction that extends substantially along a direction of the plunger longitudinal axis **34** of the plunger **26**. The at least one retaining member **68** may be linearly, stepwise, or curvilinearly contiguous between the first end **70** and the second end **72**. In some aspects, one or more retaining members **68** may generally extend in a direction parallel to a direction of the plunger longitudinal axis **34**. In other aspects, one or more retaining members **68** may extend in a direction that is angled relative to the direction of the plunger longitudinal axis **34**. For example, one or more retaining members **68** may be angled at an angle **A** toward or away from the plunger longitudinal axis **34** from the inner surface **52** of the plunger body **32**. The inner surface **52** of the plunger body **32** may have one or more pockets **69** that are recessed in a radially outward direction into the sidewall **39** to allow for an increased deflection of the second end **72** relative to the first end **70** of the at least one retaining member **68**.

[00119] With reference to **FIG. 3A**, the at least one retaining member **68** may include a plurality of retaining members **68** spaced apart radially relative to the plunger longitudinal

axis **34** along a circumference of the inner surface **52** of the interior cavity **40**. The retaining members **68** may be separated from each other by portions of the inner surface **52** of the interior cavity **40**. In aspects where two or more retaining members **68** are provided, the retaining members **68** may be evenly spaced apart from each other. In one exemplary and non-limiting aspect with three retaining members **68** having equal angular center-to-center separation therebetween, such as shown in **FIG. 3C**, each retaining member **68** is separated by 120 degrees from the retaining members **68** adjacent on either side. In another exemplary and non-limiting aspect with six retaining members **68** having equal angular separation therebetween, each retaining member **68** is separated by 60 degrees from the retaining members **68** adjacent on either side. In some aspects, the retaining members **68** may have unequal angular extension and/or unequal angular spacing between the retaining members **68** about the inner surface **52** of the interior cavity **40**. The radial spacing of the at least one retaining member **68** relative to the plunger longitudinal axis **34** is selected to correspond to or operably interact with an outer shape of the piston, as described herein. In another exemplary and non-limiting aspect with two or more retaining members **68**, each retaining member **68** has a center to center separation from the retaining members **68** adjacent on either side of an integer number of 60 degrees and furthermore each retaining member **68** has an angular extent less than 60 degrees, for example 15 to 45 degrees. This enables the release of the plunger **26** from the piston **88** with a relative rotation of 15 to 45 degrees. Optionally the relative rotation is less than 30 degrees.

[00120] With reference to **FIG. 3E**, the second end **72** of the retaining member **68** has at least one catch **74**. The at least one catch **74** may be a terminal surface of the second end **72** of the retaining member **68**. As described herein, the at least one catch **74** is shaped to be received within at least a portion of a recess, lip, or ledge on the piston to releasably lock the at least one retaining member **68**, along with the plunger **26**, to the piston with respect to motion in at least one direction. In some aspects, the at least one catch **74** may be linear or curvilinear to fit within a recess, lip, or ledge on the piston to releasably lock the at least one retaining member **68** and resist disconnecting from the piston **88** during reciprocal movement of the plunger **26** through the barrel **18** of the syringe **12** (shown in **FIG. 2**). In some aspects, the at least one catch **74** may be oriented in a direction substantially perpendicular to a direction of the plunger longitudinal axis **34**. In other aspects, the at least one catch **74** may be angled relative to a direction of the plunger longitudinal axis **34**. The at least one catch **74** may be continuous or discontinuous. In some aspects, the at least one catch **74** may protrude radially inward or outward relative to a body of the retaining member **68**. The at least one

catch **74** may be formed integrally with the second end **72** of the at least one retaining member **68** or it may be comolded, affixed, or otherwise secured to the second end **72** of the at least one retaining member **68** using, for example, a frictional fit and/or an adhesive, welding, or by molding. In other aspects, the at least one catch **74** may be formed on the second end **72** of the at least one retaining member **68** by etching, laser cutting, or machining.

[00121] At least one retaining member **68** may have at least one actuation member associated therewith. In various aspects, the at least one actuation member on the retaining member **68** of the plunger **26** is configured to interact with a corresponding actuation surface, such as an actuation surface on the piston **88** (shown in **FIG. 4A**), when the plunger **26** is connected to the piston **88**. The at least one actuation member may interact with the corresponding actuation surface on the piston **88** to cause the at least one retaining member **68** to be released from the piston **88**, such as when it is desired to disconnect the plunger **26** from the piston **88**. Relative rotation between the piston **88** and the plunger **26** about the plunger longitudinal axis **34** causes at least a portion of the actuation member to engage at least a portion of the piston **88**, such as the corresponding actuation surface on the piston **88**. For example, the piston may be substantially fixed against rotation in the direction of the plunger **26**, while the plunger **26** is rotated about the plunger longitudinal axis **34**, by frictional contact with an inner wall of a syringe during rotation of the syringe, to cause the actuation member on the plunger **26** to engage, through rotational contact, the corresponding actuation surface on the piston **88**. Alternatively, the plunger **26** may be fixed, while the piston **88** is rotated about the piston longitudinal axis **115** (shown in **FIG. 4A**) to cause the actuation surface on the plunger **26** to engage, through rotational contact, the corresponding actuation surface on the piston **88**. As a further alternative, the piston **88** and the plunger **26** may be rotated in opposite directions relative to one another about their respective longitudinal axes, or the piston **88** and the plunger **26** may be rotated in a same direction, such as clockwise or counter-clockwise direction, about their respective longitudinal axes at different rotation rates. The engagement between the actuation member on the plunger **26** and the corresponding actuation surface on the piston may be through sliding contact occurring when the rotational position of the actuation member on the plunger **26** is rotationally aligned with the rotational position of the corresponding actuation surface on the piston **88**. In some aspects, a sliding contact between the actuation member on the plunger **26** and the corresponding actuation surface on the piston **88** during relative rotational movement between the piston **88** and the plunger **26** causes a movement of the at least one retaining member **68** to a disengaged position to release the plunger **26** from the piston **88**.

[00122] With reference to **FIGS. 3A-3B**, the plunger **26** may have at least one actuation member, such as at least one first cam member **78**. In some aspects, the first cam member **78** may be provided directly on the retaining member **68**, or it may be provided on a portion of the plunger body **32** or an extension therefrom such that movement of the cam member **78** causes a corresponding disengagement of the retaining member **68**. In some aspects, the at least one first cam member **78** may be provided between the first end **70** and the second end **72** of the retaining member **68**. The at least one first cam member **78** interacts with a piston of the fluid injector **10** (shown in **FIG. 1**) to radially deflect the at least one retaining member **68** upon rotation of the plunger **26** relative to the piston, as described herein. In some aspects, the position of the at least one first cam member **78** may be selected to allow for an increased radial deflection of the at least one first cam member **78** upon relative rotation between the plunger **26** and the piston. In such aspects, the at least one first cam member **78** may be provided closer to the second end **72** of the retaining member **68**.

[00123] In some aspects, the at least one retaining member **68** may have the catch **74** formed thereon, while the actuation member, such as the cam member **78**, may be formed as a separate component that interacts with the at least one retaining member **68**. The actuation member, for example, the cam member **78** used to disengage the at least one retaining member **68**, may be a second, separate member attached to the plunger body **32**. Alternatively, the actuation member may be formed on a second separate member which is attached to the plunger body **26** and interacts with the piston **88** and the at least one retaining member **68** to transmit force, motion, or displacement from the piston **88** to the at least one retaining member **68** to deflect it for disengagement from the plunger **26**.

[00124] In some aspects, the at least one first cam member **78** may protrude at an angle relative to a plane defined by a body of the retaining member **68**. With reference to **FIG. 3C**, the at least one first cam member **78** may be angled at an angle **B** relative to the plane defined by the body of the retaining member **68**. In various aspects, the at least one first cam member **78** may be formed as a sidewall, lip, extension, or protrusion that is associated with the body of the retaining member **68**. The at least one first cam member **78** may be planar, curved, or a combination thereof. The at least one first cam member **78** may be formed as a continuous surface or a discontinuous surface formed from two or more separate surfaces that together form the at least one first cam member **78**. The at least one first cam member **78** may have an angled engagement surface **83** that interacts with the piston to disengage the plunger **26** from the piston, as described herein. The position of the at least one first cam member **78** between the first end **70** and the second end **72** of the retaining member **68** minimizes the radial

protrusion of the at least one first cam member **78** while still allowing a full radial deflection of the at least one retaining member **68** upon rotation of the plunger **26** relative to the piston **88** to allow disengagement of the plunger **26** from the piston **88**, as described herein. In some aspects, the at least one first cam member **78** may be provided on at least a portion of the at least one catch **74**. A plurality of first cam members **78** may be axially spaced apart along a length of the retaining member **68** between the first end **70** and the second end **72**. The at least one first cam member **78** may be formed integrally with the at least one retaining member **68** or it may be affixed or otherwise secured to the at least one retaining member **68** using, for example, a frictional fit and/or an adhesive, welding, or by molding. In other aspects, the at least one first cam member **78** may be formed on the at least one retaining member **68** by etching, laser cutting, or machining.

[00125] With reference to **FIG. 3A**, according to certain aspects, the plunger **26** may have at least one first alignment member **71** protruding radially inward from the plunger body **32**. In some aspects, the at least one first alignment member **71** may protrude in a direction from the distal end **38** toward the proximal end **36** of the plunger body **32**. In some aspects, the at least one first alignment member **71** may protrude proximally from the inner surface **52** of the interior cavity **40** of the plunger body **32**.

[00126] With reference to **FIG. 3E**, the at least one first alignment member **71** has a first end **73** connected to the plunger body **32** and a second end **75** protruding radially inward from the first end **73**. The at least one first alignment member **71** is shaped and/or configured for facilitating self-orienting alignment of the piston **88** with the plunger **26**. In some aspects, at least a portion of the at least one first alignment member **71** may extend in a direction that is angled relative to the direction of the plunger longitudinal axis **34**. For example, at least one first alignment member **71** may have a proximal alignment surface **77a** that is angled at an angle **C** relative to the longitudinal axis **34** to facilitate positioning of the retaining member **68** during connection of the plunger **26** to a piston. The at least one first alignment member **71** may have a distal alignment surface **77b** that is angled in a direction opposite to the proximal alignment surface **77a** to facilitate positioning of the retaining member **68** when the plunger **26** is being disconnected from the piston. The proximal alignment surface **77a** helps guide the piston **88** into self-orienting alignment with the plunger **26**, as described herein, for example by rotation of a portion of the piston **88** relative to the plunger **26** utilizing a one-way clutch associated with the piston **88**.

[00127] With reference to **FIG. 3C**, a plurality of first alignment members **71** may be spaced apart radially relative to the plunger longitudinal axis **34** along a circumference of the

inner surface **52** of the interior cavity **40**. In some aspects, the number of first alignment members **71** may be equal or unequal to the number of retaining members **68**. When equal in number, the first alignment members **71** may be disposed between the retaining members **68** such that each first alignment member **71** has a retaining member **68** on either side of the first alignment member **71**. The first alignment members **71** may be separated from each other by portions of the inner surface **52** of the interior cavity **40**. In aspects where two or more first alignment members **71** are provided, the first alignment members **71** may be evenly spaced apart from each other. In one exemplary and non-limiting aspect with three first alignment members **71** having equal angular separation therebetween, such as shown in **FIG. 3C**, each first alignment member **71** is separated by 120 degrees from the first alignment members **71** adjacent on either side. In another exemplary and non-limiting aspect with six first alignment members **71** having approximately equal angular center-to-center separation therebetween, each first alignment member **71** is separated by 60 degrees from the first alignment members **71** adjacent on either side. In some aspects, the first alignment members **71** may have unequal angular extension and/or unequal angular spacing between adjacent first alignment members **71** about the inner surface **52** of the interior cavity **40**. The radial spacing of the at least one first alignment member **71** relative to the plunger longitudinal axis **34** is selected to correspond to or operably interact with an outer shape of the piston **88** to allow for alignment of the plunger **26** with the piston **88**, as described herein. The at least one first alignment member **71** may be constituted from or composed of multiple members, optionally separately attached to the inner surface **52** of the plunger body **32**, whose alignment surfaces, both real and virtual, interact to perform the alignment function. Similarly, an at least one retaining member **68** may be constituted from or composed of multiple members, optionally separately attached to the inner surface **52** of the plunger body **32**, whose catches **74**, interact to perform the engagement, connection, attachment, or retention functions. Similarly, an at least one actuation member may be constituted from or composed of multiple members, optionally separately attached to the inner surface **52** of the plunger body **32**, which interact to provide the activation of the at least one retaining member **68** to perform the disengagement, disconnect, separation, or release function. Optionally, the at least one alignment member **71**, the at least one retaining member **68**, and/or the at least one actuation member may be attached to each other and interact or transmit force directly from one to another, or optionally may be separate and interact with each other through surfaces between them that transmit force, motion, or deflection from one to another, directly or indirectly, or through their action on the plunger body **32**. Similarly, the force, motion, or deflection for activation

to accomplish release of a retaining member **68** may occur through the movement or force transmitted from a second retaining member **68** or intermediate linkage or mechanism.

[00128] Referring to **FIG. 4A**, a piston **88** (shown in **FIG.4A** as only the distal portion of piston **88**) is configured to interact with the plunger **26** (shown in **FIG. 3A**) to releasably lock the plunger **26** such that the plunger **26** can be driven reciprocally within the barrel of the syringe **12** (shown in **FIG. 2**). The piston **88** is extendible and retractable from the housing **14** of the fluid injector **10** (shown in **FIG. 1**) via a powered means (not shown) preferably contained within housing **14**. The powered means may include, for example, an electric motor, a hydraulic system, or a pneumatic system, including appropriate gearing (not shown). As known in the art, the fluid injector **10** also may include a controller (not shown) for controlling operation of the powered means and thereby controlling operation of piston **88**.

[00129] With continued reference to **FIG. 4A**, the piston **88** includes a stem **90** connected to the proximal portion of the piston **88** within the injector **10** (shown in **FIG. 10A**) and a piston head **92** formed on a distal end of the stem **90**. At least a portion of the piston head **92** extends distally from the stem **90**. The piston **88** is constructed from a rigid material, such as metal or plastic that resists deformation. The stem **90** may have a cavity **91** for collecting any fluid that may drip from the syringe. The piston head **92** has a substantially cylindrical structure with a pointed distal end **94** with a cap **95** that is shaped to be received inside at least a portion of the interior cavity **40** (shown in **FIG. 3A**) of the plunger **26**. In some aspects, a sensing member **79**, such as a pin connected to a sensor, may be provided. The sensing member **79** may extend along a longitudinal axis of the piston **88** and may protrude through at least a portion of the piston head **92**, such as through at least a portion of the cap **95**. The sensing member **79** may be operative for sensing contact with a surface, such as a surface of the plunger **26** and/or the plunger cover **58**, and control a movement of the piston **88** based on the sensed condition. For example, an initial contact between the sensing member **79** and the plunger **26** and/or the plunger cover **58** may cause the pin to be moved in a proximal direction such that it makes contact with the sensor. The sensing member **79** may be biased in an extended position by a resilient element **81** (shown in **FIG. 4B**), such as a spring. The sensor may be connected to the controller of the injector such that, upon activation of the sensor by the pin, the controller controls the movement of the drive mechanism. For example, the drive mechanism may be stopped or slowed from a first rate to a second, slower rate.

[00130] The piston head **92** may be rotatable relative to the stem **90**. In some aspects, the piston head **92** may be rotatable in one direction only, such as a clockwise or a counter-

clockwise direction, relative to the stem **90**. A one-way rotation mechanism **99** (shown in **FIG. 4B**), such as a one-way clutch mechanism, may be provided to allow the rotation of the piston head **92** in a first direction only, such as the clockwise or the counter-clockwise direction. The one-way rotation mechanism **99** may be rotatable around a central shaft **101** having a seal **102**, such as an O-ring seal. In some aspects, the one-way rotation mechanism **99** may have a stop that prevents rotation of the piston head **92** in a second direction opposite the first direction, such as the counter-clockwise or the clockwise direction, respectively. In other aspects, the one-way rotation mechanism **99** may be provided on at least a portion of the plunger **26**.

[00131] With reference to **FIG. 4C**, the piston head **92** has a proximal portion **103** connected to a distal portion **105**. Terminal ends of the proximal and distal portions **103**, **105** may have a radiused or chamfered edge **107**. At least a portion of the proximal portion **103** has a smaller outer diameter compared to an outer diameter of the distal portion **105** such that a radial lip **109** is formed at a transition between the proximal portion **103** and the distal portion **105**. The radial lip **109** may be continuous or discontinuous around a circumference of the piston head **92**. In some aspects, the radial lip **109** defines a locking ledge **111** for engaging the catch **74** (shown in **FIG. 5D**) of the at least one retaining member **68** when the plunger **26** is fully seated on the piston head **92**. At least a portion of the retaining member **68** shown in **FIG. 5D** is shown as being hidden behind the piston head **92** due to the rotational position of the plunger **26** relative to the piston head **92** about the piston longitudinal axis **115**.

[00132] With continued reference to **FIG. 4C**, the piston head **92** may have at least one second alignment member **113** protruding radially outward from an outer surface of the piston head **92**. The at least one second alignment member **113** may be shaped and/or configured for interacting with the first alignment member **71** (shown in **FIG. 5B**) of the plunger **26** for facilitating alignment of the piston **88** with the plunger **26** in order to allow for a releasable locking connection of the plunger **26** with the piston **88**. In some aspects, at least a portion of the at least one second alignment member **113** may extend in a direction that is angled relative to the direction of a piston longitudinal axis **115**. For example, at least one second alignment member **113** may have a guiding surface **117** that is angled at an angle **D** relative to the piston longitudinal axis **115**. The guiding surface **117** is desirably angled such that the piston head **92** may rotate around the piston stem **90**, for example around the axis of the one-way rotation mechanism **99**, when the proximal alignment surface **77a** of the first alignment member **71** contacts the guiding surface **117** of the second alignment member **113**.

[00133] In some aspects, a plurality of second alignment members **113** may be spaced apart radially relative to the piston longitudinal axis **115** along an outer circumference of the piston head **92**. In some aspects, the number of second alignment members **113** may be equal to a total number of retaining members **68** and first alignment members **71** on the plunger **26**. The second alignment members **113** are spaced apart circumferentially such that a retaining member **68** or a first alignment member **71** may be received between adjacent second alignment members **113**. The second alignment members **113** may be separated from each other by portions of an outer surface of the proximal portion **103** and/or the distal portion **105** of the piston head **92**. In aspects where two or more second alignment members **113** are provided, the second alignment members **113** may be evenly spaced apart from each other. In one exemplary and non-limiting aspect with six second alignment members **113** having equal angular separation therebetween, such as shown in **FIG. 4A**, each second alignment member **113** is separated by 60 degrees from the second alignment members **113** adjacent on either side. In some aspects, the second alignment members **113** may have unequal angular extension and/or unequal angular spacing between the second alignment members **113** about the outer surface of the proximal portion **103** and/or the distal portion **105** of the piston head **92**. The radial spacing of the second alignment members **113** relative to the piston longitudinal axis **115** is selected to correspond to or operably interact with an inner shape of the plunger **26** to allow the one or more retaining members **68** to be received into the locking ledge **111**. Locking ledge **111** may be radially perpendicular to the longitudinal axis **115** or in certain aspects locking ledge **111** may be radially angled relative to the longitudinal axis **115**. In certain aspects, locking ledge **111** may be angled with an angle complementary to an angle of the catch **74**, such as the angle of the catch **74** shown in **FIG. 3E**.

[00134] With reference to **FIG. 4C**, each of the guiding surfaces **117** of the second alignment members **113** define a travel path for guiding the movement of the proximal alignment surface **77a** of the first alignment member **71** in and out of a recess **119** defined between adjacent second alignment members **113**. The guiding surfaces **117** may be inclined or angled radially and axially relative to the piston longitudinal axis **115** to guide the movement of the proximal alignment surfaces **77a**. The guiding surfaces **117** aid in self-orienting the piston head **92** as the plunger **26** is brought into contact with the piston **88** by guiding the one or more proximal alignment surfaces **77a** on the plunger **26** into the corresponding recess **119** on the piston head **92**. In this manner, a piston **88** whose piston longitudinal axis **115** is rotationally misaligned with the plunger longitudinal axis **34** and the one or more first alignment members **71** which are initially misaligned relative to the

corresponding one or more second alignment members **77a** is rotated in a rotational direction of the one-way rotation mechanism **99** and brought in alignment axially and rotationally such that the one or more first alignment members **71** are received within the recess **119** between adjacent second alignment members **113**. In this manner, the one or more retaining members **68** are brought into rotational alignment with the recess **119** having the locking ledge **111** adjacent the recess **119**.

[00135] The one or more second alignment members **113** may have a bottom surface **121** that is angled relative to the direction of a piston longitudinal axis **115**. For example, the bottom surface **121** may be angled at an angle **E** relative to the piston longitudinal axis **115**. Angle **E** may be the same or different than angle **D** of the guiding surface **117**. In another aspect, bottom surface **121** may be rounded or angled to merge with the proximal wall or proximal end **103**.

[00136] The piston head **92** further has an actuation surface that interacts with the actuation member on the plunger **26**, such as the first cam member **78**. In some aspects, the actuation surface on the piston head **92** may be a second cam member **98** or a cam following surface. In some aspects, the actuation surface or second cam member **98** cooperates with the first cam member **78** on the at least one retaining member **68** of the plunger **26**, as described herein. The actuation surface or second cam member **98** desirably has a shape that, upon relative rotation between the piston **88** and the plunger **26**, the actuation surface or second cam member **98** engages the first cam member **78** to cause the at least one retaining member **68** to be deflected from the piston head **92** to disengage catch **74** of retaining member **68** from the locking ledge **111** such that the plunger **26** disengages and can be removed from the piston **88**. In some aspects, the actuation surface or second cam member **98** may be formed on the second alignment member **113** on the piston head **92**. The actuation surface or second cam member **98** may be a surface that is aligned with a direction of the piston longitudinal axis **115**. In certain aspects, the actuation surface or second cam member **98** may have a chamfered portion **98a** to facilitate the initial movement and/or the passing of the first cam member **78** after the retaining member **68** is deflected sufficiently to allow the retaining member to be released. In other aspects, the actuation surface **98** may be radially aligned and parallel to longitudinal axis **115**.

[00137] The piston **88** is configured to interact with the plunger **26** to releasably lock with plunger **26**, such as shown in **FIG. 3A**. By locking the piston **88** to the plunger **26**, the plunger **26** can be driven reciprocally within the barrel of the syringe **12** (shown in **FIG. 2**). The actuation surface or second cam member **98** on the piston **88** cooperates with the first

cam member **78** on the at least one retaining member **68** of the plunger **26**, to releasably lock the plunger **26** to the piston **88**. Further, due to the distal arrangement and in certain aspects, the radially inwardly angled nature, of the at least one retaining member **68**, the locking force between the locking ledge **111** of piston **88** and the catch **74** of the retaining member **68** is increased due to the compressive force as the piston **88** withdraws the plunger **26** in the proximal direction during a syringe filling process. The locking or engagement of the plunger **26** to the piston **88**, and the unlocking or disengagement of the plunger **26** from the piston **88** will be described herein with reference to **FIGS. 5A-5C**. The syringe **12**, shown initially in phantom in **FIG. 5A** is omitted from the remainder of **FIGS. 5B-5D** for clarity.

[00138] To engage the plunger **26** with the piston **88**, the syringe **12** is first inserted into the syringe port **16** of the fluid injector **10** (shown in **FIG. 1**). Once or while the syringe **12** is inserted into the syringe port **16**, various locking mechanisms (not shown) may be used to retain the syringe **12** within the syringe port **16** to prevent detachment of the syringe **12** from the syringe port **16**. Initially, the plunger **26** may be positioned at the proximal end **20** of the syringe barrel **18**. In some aspects, the plunger **26** is positioned at any axial location between the proximal end **20** and the distal end **24** of the syringe barrel **18**. The piston **88** may then be advanced distally toward the plunger **26** for engagement of the piston head **92** with the plunger **26**. In some aspects, the piston **88** may be advanced distally toward the plunger **26** by way of the powered means operated by a controller. In other aspects, the piston **88** may be advanced distally toward the plunger **26** by manual operation.

[00139] With reference to **FIG. 5B**, the piston **88** is advanced axially in a distal direction shown by the arrow **A**. If the piston **88** is rotationally misaligned relative to the plunger **26** about the longitudinal axis **115** such that the first alignment members **71** on the plunger **26** are not in rotational alignment to be received within the recesses **119** (shown in **FIG. 4C**) on the plunger head **92**, the proximal alignment surface **77a** of the first alignment member **71** on the plunger **26** contacts the guiding surface **117** of the second alignment member **113** on the piston head **92**. The proximal alignment surface **77a** and the guiding surface **117** are angled in a same direction relative to the longitudinal axes **34**, **115** such that continued movement of the piston **88** in a distal direction causes the proximal alignment surface **77a** to engage the guiding surface **117**. Engagement of the proximal alignment surface **77a** with the guiding surface **117** causes the piston head **92** to automatically rotate in a free rotation direction of the one-way rotation mechanism **99**. Such rotation of the piston head **92** aligns the first alignment members **71** and the retaining members **68** to be received within the recesses **119** between adjacent second alignment members **113**. In this manner, the piston **88** self-orients itself

relative to the plunger **26** such that the plunger **26** may be releasably locked with the piston **88**. If the piston **88** is rotationally aligned relative to the plunger **26** such that the first alignment members **71** on the plunger **26** are in rotational alignment with the second alignment members **113** on the piston head **92**, the first alignment members **71** and the retaining members **68** on the plunger **26** can be received within the recesses **119** between adjacent second alignment members **113** without rotation of the piston head **92**.

[00140] With reference to **FIG. 5C**, after aligning the first alignment members **71** and the retaining members **68** to be received within the recesses **119** between adjacent second alignment members **113**, the piston **88** is advanced further in the distal direction. Such movement of the piston **88** in the distal direction, causes the retaining members **68** to initially engage an outer sidewall of the distal portion **105** of the piston head **92**. Continued distal movement of the piston **92** causes the retaining members **68** to deflect radially outward relative to the plunger longitudinal axis **34** from a first, undeflected position, to a second, radially deflected position. The piston **88** is advanced distally until the terminal portion of the second end **72** of each retaining member **68** clears the radial lip **109**. The retaining members **68** then deflect radially inward toward or to their initial undeflected position, for example due to the restoring force built up in the retaining members **68** during radial deflection. As shown in **FIG. 5D**, the catch **74** of at least one retaining member **68** is retained within the locking ledge **111** to prevent disengagement of the plunger **26** from the piston head **92**. Distal movement of the piston **88** may be stopped when the sensing member **79** engages at least a portion of the plunger **26**, such as the plunger cover **58** (shown in **FIG. 3E**). The plunger **26** resists being disconnected from the piston **88** upon movement of piston **88** in a distal and proximal direction relative to the syringe barrel **18**. In one aspect, the retaining members **68** may be designed such that the compressive forces exerted upon the catch **74** upon movement of piston head **92** in the proximal direction substantially prevent radially outward deflection (or bending) of the retaining members **68**. For example, once the retaining members **68** are locked to the piston head **92**, axial movement of the piston **88** does not introduce a bending moment sufficient to deflect the retaining members **68** radially to cause the plunger **26** to be disconnected from the piston **88**. Proximal movement of the piston **88** causes the at least one retaining member **68** to be loaded in compression between the first end **70** and the second end **72** such that the retaining member **68** may be urged in a radially inward direction, thereby increasing the locking force between the plunger **26** and the piston **88**.

[00141] To unlock the syringe **12** from the syringe port **16** (shown in **FIG. 1**) and disengage the plunger **26** from the piston **88**, the syringe **12** is rotated clockwise or counter-

clockwise about the syringe longitudinal axis, in a clockwise or counter-clockwise direction, relative to the syringe port **16**. Because the plunger **26** is substantially free from rotation within the syringe barrel **18** due to a frictional force of the seal **59** with the inner surface **23** of the syringe sidewall **19** (shown in **FIG. 2**), the rotation of the syringe **12** also causes the plunger **26** to rotate relative to the piston **88**. The free-rotation direction of the one-way rotation mechanism **99** is desirably opposite to the rotation direction of the syringe **12** during the release of the syringe **12** from the syringe port **16**. Rotation of the syringe **12**, and thereby the plunger **26**, about the plunger longitudinal axis **34** engages the first cam member **78** on the plunger **26** with the actuation surface or second cam member **98** on the piston head **92**. Such movement causes a radial deflection of the at least one retaining member **68** away from the piston head **92**.

[00142] As the at least one retaining member **68** is deflected radially outward relative to the plunger longitudinal axis **34**, the catch **74** is moved out of engagement with the locking ledge **111**. In this position, the at least one retaining member **68** is in a deflected state that allows the plunger **26** to be moved axially relative to the piston **88**. Such axial movement of the plunger **26** can be effected by withdrawing the syringe **12** from the syringe port **16** in a distal direction along the syringe longitudinal axis **15**, by withdrawing the piston **88** in a proximal direction away from the plunger **26**, or both. The plunger **26**, together with the syringe **12**, can then be completely disengaged from the piston **88** and the injector **10**. In some aspects, the piston **88** can be released from the plunger **26** by rotating the piston **88** about its longitudinal axis and retracting the piston **88** in a proximal direction to disengage the at least one retaining member **68** in a manner described herein.

[00143] With reference to **FIGS. 6A-6B**, a plunger **26** and a piston **88** are shown in accordance with another aspect of the present disclosure. The components of the plunger **26** shown in **FIGS. 6A-6B** are substantially similar to the components of the plunger **26** described herein with reference to **FIGS. 3A-3C**. As the previous discussion regarding the plunger **26** generally shown in **FIGS. 3A-3C** is applicable to the aspect of the present disclosure shown in **FIGS. 6A-6B**, only the relative differences between the plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** and the plunger **26** and piston **88** shown in **FIGS. 6A-6B** are discussed hereinafter.

[00144] In one exemplary and non-limiting aspect with 6 locking ledges **111** having equal angular separation therebetween, to mate with the plunger as shown in **FIG. 3C**, each locking ledge **111** is separated by 60 degrees center to center from the locking ledge **111** adjacent on either side. In some aspects, the locking ledge **111** may have unequal angular extension

and/or unequal angular spacing between the locking ledge **111** about the outer surface of the piston **88**. In another exemplary and non-limiting aspect with two or more locking ledges **111**, each retaining locking ledge **111** has a center to center separation from the locking ledge **111** adjacent on either side of an integer number of 60 degrees and furthermore each locking ledge **111** has an angular extent less than 60 degrees, for example 15 to 45 degrees. This enables the release of the plunger **26** from the piston **88** with a relative rotation of 15 to 45 degrees. Optionally the relative rotation is less than 30 degrees. The radial spacing of the at least one locking ledge **111** relative to the plunger longitudinal axis **34** is selected to correspond to or operably interact with radial spacing of the at least one plunger retaining member **68**, as described herein.

[00145] With reference to **FIGS. 6A-6B**, a plunger **260** is shown in accordance with another aspect of the present disclosure. The barrel **18** of the syringe **12** is omitted from **FIGS. 6A-6B** for clarity. The plunger **260** includes a plunger body **320** defining a plunger longitudinal axis **340** and having a proximal end **360**, a distal end **380**, and a circumferential sidewall **390** connecting the proximal end **360** and the distal end **380**. The sidewall **390** may have a uniform or non-uniform thickness between the proximal end **360** and the distal end **380**. Plunger body **320** may be formed from glass, metal, or suitable medical-grade plastic.

[00146] With continued reference to **FIGS. 6A-6B**, the plunger body **320** has an interior cavity **400** with a conical-shaped portion **420** at the distal end **380** of the plunger body **320** and a cylindrical-shaped portion **440** at the proximal end **360** of the plunger body **320**. The conical-shaped portion **420** may be monolithically formed with the cylindrical-shaped portion **440**. In some aspects, the conical-shaped portion **420** may be affixed or otherwise secured to the cylindrical-shaped portion **440** of the plunger body **320** using, for example, a frictional fit and/or an adhesive, welding, or by molding. The conical-shaped portion **420** may have a truncated end **460** that has a central opening **480**. In some aspects, the distal end **380** of the plunger body **320** may be enclosed. In some aspects, the plunger **260** may have a plunger cover, such as the plunger cover **58** shown in **FIG. 2**, configured for covering at least a portion of an outer surface of the plunger body **320**.

[00147] With continued reference to **FIGS. 6A-6B**, the plunger **260** may have at least one resiliently deflectable retaining member **680** (hereinafter "retaining member **680**") protruding from the plunger body **320** in a distal direction. In some aspects, the at least one retaining member **680** may protrude distally and radially inward from an inner surface **520** of the interior cavity **400** of the plunger body **320**. The at least one retaining member **680** has a first segment or a first end **700** connected to the plunger body **320** and a second segment or a

second end **720** radially deflectable relative to the first end **700**. As described herein, the second end **720** may be radially deflectable relative to the first end **700** when the at least one retaining member **680** engages a piston of the fluid injector **10** (shown in **FIG. 1**). The first end **700** and the second end **720** may be spaced apart in a direction that extends substantially along a direction of the plunger longitudinal axis **340** of the plunger **260**. The at least one retaining member **680** may be linearly or curvilinearly contiguous between the first end **700** and the second end **720**.

[00148] In some aspects, a plurality of retaining members **680** are spaced apart radially from the plunger longitudinal axis **340** along a circumference of the inner surface **520** of the interior cavity **400**. In such aspects, the retaining members **680** are separated from each other by portions of the inner surface **520** of the interior cavity **400**. In aspects where more than one retaining member **680** is provided, the retaining members **680** may be evenly spaced apart from each other. In one exemplary and non-limiting aspect with three retaining members **680** having equal angular separation therebetween, a center of each retaining member **680** is separated by 120 degrees from a center of the retaining members **680** adjacent on either side. In another exemplary and non-limiting aspect with six retaining members **680** having equal angular separation therebetween, a center of each retaining member **680** is separated by 60 degrees from a center of the retaining members **680** adjacent on either side. In some aspects, the retaining members **680** may have unequal angular extension and/or unequal angular spacing between the retaining members **680** about the inner surface **520** of the interior cavity **400**. The radial spacing of the at least one retaining member **680** relative to the plunger longitudinal axis **340** is selected to correspond to features on an outer circumference of the piston, as described herein.

[00149] In some aspects, one or more retaining members **680** may be parallel with the longitudinal axis **340**. In other aspects, one or more retaining members **680** may be angled relative to the longitudinal axis **340**. For example, one or more retaining members **680** may be angled inward toward the longitudinal axis **340** in a direction from the first end **700** toward the second end **720**.

[00150] With continued reference to **FIGS. 6A-6B**, the second end **720** of the retaining member **680** has at least one catch **740**. The at least one catch **740** may be a terminal surface of the second end **720** of the retaining member **680**. In some aspects, the at least one catch **740** may protrude radially from the retaining member **680**. For example, the at least one catch **740** may protrude radially inward toward the plunger longitudinal axis **340** of the plunger body **320**, or radially outward away from the plunger longitudinal axis **340**. As described

herein, the at least one catch **740** is shaped to engage at least a portion of a recess on the piston to releasably lock the at least one retaining member **680** relative to the piston. The at least one catch **740** may be formed integrally with the second end **720** of the at least one retaining member **680** or it may be affixed or otherwise secured to the second end **720** of the at least one retaining member **680** using, for example, a frictional fit and/or an adhesive, welding, or by molding. In other aspects, the at least one catch **740** may be formed on the second end **720** of the at least one retaining member **680** by etching, laser cutting, or machining.

[00151] With continued reference to **FIGS. 6A-6B**, the plunger **260** may have at least one first cam member **780** disposed between the first end **700** and the second end **720** of the retaining member **680**. The at least one first cam member **780** is configured to interact with a piston of the fluid injector **10** (shown in **FIG. 1**) to radially deflect the at least one retaining member **680** upon rotation of the plunger **260** relative to the piston, as described herein. The position of the at least one first cam member **780** between the first end **700** and the second end **720** of the retaining member **680** allows for a greater radial deflection of the at least one first cam member **780** upon relative rotation between the plunger **260** and the piston **880** (shown in **FIGS. 7A-7B**) compared to providing the at least one first cam member **780** at the second end **720**. The at least one first cam member **780** may be parallel with a surface of the retaining member **680**. In some aspects, the at least one cam member **780** may be angled relative to a surface of the retaining member **680**.

[00152] In some aspects, the at least one first cam member **780** protrudes radially inward toward the plunger longitudinal axis **340** of the plunger body **320**. In other aspects, the at least one first cam member **780** protrudes radially outward relative to the plunger longitudinal axis **340** of the plunger body **320**. The position of the at least one first cam member **780** between the first end **700** and the second end **720** of the retaining member **680** may minimize the radial protrusion of the at least one first cam member **720** while still allowing a full radial deflection of the at least one retaining member **680** upon rotation of the plunger **260** relative to the piston **880**, as described herein. In some aspects, the at least one first cam member **780** may be provided on at least a portion of the at least one catch **740**. A plurality of first cam members **780** may be axially spaced apart along a length of the retaining member **680** between the first end **700** and the second end **720**. The at least one first cam member **780** may be formed integrally with the at least one retaining member **680** or it may be affixed or otherwise secured to the at least one retaining member **680** using, for example, a frictional fit and/or an adhesive, welding, or by molding. In other aspects, the at least one first cam

member **780** may be formed on the at least one retaining member **680** by etching, laser cutting, or machining.

[00153] With reference to **FIG. 6A**, the at least one first cam member **780** may have at least one tooth **800** configured to engage a corresponding groove on the piston. The at least one tooth **800** on the at least one first cam member **780** is desirably shaped to generally correspond to the corresponding groove on the piston. Each tooth **800** may have a peak **820** leading to a groove **840** for example along a gear surface **860**. The at least one tooth **800** on the at least one first cam member **780** may be the shape of a gear tooth having a spur gear profile or a helical gear profile. While **FIGS. 6A-6B** illustrate one non-limiting aspect of the at least one first cam member **780**, various other shapes are also contemplated. For example, the at least one first cam member **780** of the at least one retaining member **680** may have a generally circular, triangular, square, rectangular, or any suitable polygonal shape or cross-section. In each aspect, the at least first cam member **780** is configured for engaging at least a portion of the piston to cause the at least one retaining member **680** to be deflected from the piston upon rotation of the plunger **260** relative to the piston. In general, the at least one first cam member **780** may have at least one corrugated, rippled, or multilevel surface, either in singular or regularly or irregularly repeating form, that is configured for engaging with the corresponding cam member on the piston of the fluid injector.

[00154] With continued reference to **FIGS. 6A-6B**, the plunger **260** may have at least one first alignment member **825** disposed between the first end **700** and the second end **720** of the retaining member **680**. The first alignment member **825** has a proximal edge or tip **826**, a distal edge **827**, and a proximal alignment surface **828**. The first alignment member **825** cooperates with a second alignment member **1010** (shown in **FIG. 7A**) on the piston head **920** to rotationally guide, self-align, move, or drive the plunger **260** and piston **880** into the proper rotational alignment for attachment or engagement and for subsequent detachment. The proximal alignment surface **828** may be a continuous surface or may be multiple discrete surfaces which act to provide continuous alignment activation when cooperating with the second alignment member **925** of the piston head **920** during plunger to piston engagement. A first alignment member **825** may optionally be on the retaining member **680**, may be part of the first cam member **780**, and/or may be rigidly associated with another aspect of the plunger **260**.

[00155] Referring to **FIG. 7A**, a piston **880** is extendible and retractable from the housing **14** of the fluid injector **10** (shown in **FIG. 1**) via a powered means (not shown) preferably contained within housing **14**. The powered means may include, for example, an electric

motor, a hydraulic system, or a pneumatic system, including appropriate gearing (not shown). As known in the art, the fluid injector **10** also may include a controller for controlling operation of the powered means and thereby controlling operation of the piston **880**.

[00156] With continued reference to **FIG. 7A**, the piston **880** includes a stem **900** and a piston head **920** formed on a distal end of the stem **900**. The piston **880** is construed from a relatively rigid material, such as metal or plastic that resists deformation due to repeated engagement with and disengagement from the plunger **260**. The piston head **920** has a substantially cylindrical structure with a pointed or conical distal end **940** that is configured to be received inside at least a portion of the interior cavity **400** of the plunger **260**. In some aspects, a sensing member **1500**, such as a spring-loaded pin connected to a sensor, may be provided. The sensing member **1500** may extend along a longitudinal axis of the piston **880** and may protrude through at least a portion of the piston head **920**. The sensing member **1500** may be operative for sensing contact with a surface, such as a surface of the plunger **260** and/or the plunger cover **58** (shown in **FIG. 3E**), and control a movement of the piston **880** based on the sensed condition. For example, an initial contact between the sensing member **1500** and the plunger **260** and/or the plunger cover **58** may cause the pin to be retracted in a proximal direction such that it makes contact with the sensor. The sensor may be connected to the drive mechanism of the piston **880** such that, upon activation of the sensor by the pin, the sensor controls the movement of the drive mechanism. For example, the drive mechanism may be stopped or slowed from a first rate to a second, slower rate.

[00157] The proximal end **960** of the piston head **920** has an actuation member that interacts with the actuation member on the plunger **260**, such as the first cam member **780**. In some aspects, the actuation member on the piston head **920** may be a second cam member **980**. In some aspects, the second cam member **980** is a tooth of a gear **990** that extends around at least a portion of an outer circumference of the piston head **920**. The second cam member **980** is configured for cooperation with the first cam member **780** on the at least one retaining member **680** of the plunger **260**, as described herein. The second cam member **980** desirably has a shape that, upon self-aligning, relative rotation between the piston **880** and the plunger **260**, engages the first cam member **780** to cause the at least one retaining member **680** to be deflected from the piston head **920** such that the plunger **260** can be removed from the piston **880**.

[00158] In some aspects, the second cam member **980** may be parallel with the longitudinal axis **340**. In other aspects, the second cam member **980** may be angled relative to the longitudinal axis **340**. For example, the second cam member **980** may be angled toward

the longitudinal axis **340** at an angle corresponding to an angle of inclination of the at least one retaining member **680**. In various aspects, regardless of the angular orientation of the at least one retaining member **680**, the first cam member **780** is desirably parallel with the second cam member **980**.

[00159] With continued reference to **FIGS. 7A-7B**, the piston head **920** may have a second alignment member **1010** to interact with the first alignment member **825** (shown in **FIG. 6B**) on the plunger **260**. The alignment member **1010** has a first edge **927** and a second edge **926**, and a surface **928** between the first edge **927** and the second edge **926**. The longitudinal, radial, and circumferential locations of the first edge **927** and the second edge **926** and contour and extent of surface **928** of the second alignment member **1010** are chosen to interact with the edges and surfaces of the first alignment member **825** to provide a rotational force and motion as the piston **880** and plunger **260** are axially moved together. The piston head **920**, and optionally the collar **1100**, may be connected to the piston stem **900** via a one-way rotation mechanism, such as the one-way rotation mechanism **99** discussed herein with reference to **FIG. 4B**, so that the piston **880** and the plunger **260** can rotate into alignment in response to the interaction of the first and second alignment surfaces. Alternatively, if the amount of rotation is small enough, the elasticity or slip of the plunger cover (shown in **FIG. 3E**) with respect to the syringe barrel may be sufficient to allow the plunger **260** to rotate into alignment with the piston head **920**.

[00160] With continued reference to **FIGS. 7A-7B**, the piston **880** may have a collar **950** surrounding at least a portion of the stem **900** and/or the piston head **920**. The collar **950** may protrude radially outward relative to an outer radial surface of the stem **900** and the piston head **920** such that an annular space **970** is defined between the piston **880** and the collar **950**. The collar **950** may have an open top end and a closed bottom end that is defined by a bottom sidewall **1000** that connects the collar **950** to the stem **900** and/or the piston head **920**. The bottom sidewall **1000** defines a seat **1020** for a first end **1040** of a resiliently elastic member, such as a spring **1060**, that surrounds the stem **900**. In other aspects, the seat **1020** may be provided as a radial flange that protrudes from an outer surface of the stem **900**. The second end **1080** of the spring **1060** engages a proximal end of a movable capture ring **1100**. The capture ring **1100** has a substantially annular shape and surrounds at least a portion of an outer circumference of the stem **900**. In some aspects, at least a portion of an outer diameter of the capture ring **1100** may have a same or larger outer diameter than an outer diameter of the piston head **920**. The spring **1060** biases the capture ring **1100** toward a first radial lip **1120** of the piston head **920**. The capture ring **1100** is movable axially between a first

position, where the capture ring **1100** engages the first radial lip **1120** of the piston head **920**, and a second position, where the spring **1060** is compressed and the capture ring **1100** is deflected by at least a portion of the at least one retaining member **680** toward the bottom sidewall **1000** of the collar **950**. In some aspects, the capture ring **1100** may be movable between the first position and the second position when urged by contact with, for example, the first end **700** of the at least one retaining member **680**. A stop member (not shown) may be provided to limit the movement of the capture ring **1100** to the second position. During disengagement of the plunger **260** from the piston **880**, the capture ring **1100** urges the at least one retaining member **680** in a distal direction due to a restoring force of the spring **1060**. In some aspects, the capture ring **1100** may have a grooved radial edge **1530** configured to engage the first cam member **780** of the at least one retaining member **680**.

[00161] With continued reference to **FIGS. 7A-7B**, the piston head **920** further defines a second radial lip **1510** at a distal end of the at least one second cam member **980**. When the plunger **260** is engaged with the piston **880**, the second radial lip **1510** acts as a retention surface for the at least one catch **740** of the at least one retaining member **680**. The piston head **920** may further have guiding grooves **1520** provided distally from the second radial lip **1510**. In some aspects, the guiding grooves **1520** may have a shape that corresponds to the shape of the first cam member **780**. In this manner, the tooth **800** of the first cam member **780** may be guided into the guiding groove **1520** as the plunger **260** and the piston head **920** are moved toward each other.

[00162] Having described the structure of the plunger **260** and the piston **880** in accordance with one non-limiting aspect of the present disclosure, the engagement and disengagement of the plunger **260** with and from the piston **880** will now be described with reference to **FIGS. 7A-12B**. The syringe **12**, shown initially in phantom in **FIG. 7A** is omitted from the remainder of **FIGS. 7B-12B** for clarity.

[00163] To engage the plunger **260** with the piston **880**, the syringe **12** is first inserted into the syringe port **16** of the fluid injector **10**, as described herein. Once the syringe **12** is inserted into the syringe port **16**, various locking mechanisms (not shown) may be used to releasably retain the syringe **12** within the syringe port **16** to prevent detachment of the syringe **12** from the syringe port **16**. Initially, the plunger **260** may be positioned at the proximal end **20** of the syringe barrel **18**. In some aspects, the plunger **260** is positioned at any axial location between the proximal end **20** and the distal end **24** of the syringe barrel **18**. The piston **880** may then be advanced distally toward the plunger **260** for engagement of the piston head **920** with the plunger **260**. In some aspects, the piston **880** may be advanced

distally toward the plunger **260** by way of the powered means operated by a controller. In other aspects, the piston **880** may be advanced distally toward the plunger **260** by manual operation.

[00164] With reference to **FIGS. 8A-8B**, the piston **880** is advanced axially in a distal direction such that at least a portion of the pointed or conical distal end **940** of the piston head **920** contacts the at least one retaining member **680** of the plunger **260**. Initially, at least a portion of the piston head **920**, such as the guiding grooves **1520**, contacts the first alignment member **825** (shown in **FIG. 6B**), for example, on the at least one retaining member **680**. The piston head **920** may be connected to the piston stem **900** via a one-way rotation mechanism, such as the one-way rotation mechanism **99** discussed herein with reference to **FIG. 4B**, so that the piston **880** and the plunger **260** can rotate into self-alignment in response to the interaction of the first and second alignment surfaces. Alternatively, if the amount of rotation is small enough, the elasticity or slip of the plunger cover (shown in **FIG. 3E**) with respect to the syringe barrel may be sufficient to allow the plunger **260** to rotate into alignment with the piston head **920**.

[00165] Due to an angled orientation of the at least one retaining member **680** relative to the longitudinal axis, continued axial movement of the piston head **920** relative to the plunger **260** causes the at least one retaining member **680** to be deflected radially outward due to the contact between the at least one retaining member **680** and the outer surface of the piston head **920**. In an aspect having a plurality of retaining members **680**, each of the retaining members **680** may be deflected radially outward relative to the piston head **920**.

[00166] With reference to **FIGS. 9A-9B**, during continued axial movement of the piston **880** in a distal direction, at least a portion of the retaining member **680** engages the distal end of the capture ring **1100**. For example, the first end **720** and/or the first cam member **780** of the retaining member **680** may engage the distal end of the capture ring **1100**. The contact between at least a portion of the retaining member **680** and the distal end of the capture ring **1100** urges the capture ring **1100** against the restoring force of the spring **1060** and away from the first radial lip **1120** of the piston head **920**.

[00167] With reference to **FIGS. 10A-10B**, at least a portion of the retaining member **680**, such as the first end **720** and/or the first cam member **780** of the retaining member **680**, urges the capture ring **1100** proximally against the restoring force of the spring **1060**. The body of the at least one retaining member **680** has an inherent restoring force built up in the material of the at least one retaining member **680** when the at least one retaining member **680** is deflected from its natural, undeflected state to a radially deflected state. Due to this inherent

restoring force created within the body of the at least one retaining member **680** during a radial deflection of the at least one retaining member **680**, the second end **720** and/or the catch **740** is snapped radially into the second radial lip **1510**. Such radial movement of the second end **720** and/or the catch **740** also or further engages the first cam member **780** on the plunger **260** with the second cam member **980** on the piston head **920**. Specifically, the peaks **820** of the first cam member **780** are received in the groove **103** of the second cam member **980**, and the groove **840** of the first cam member **780** receives the peaks **101** of the second cam member **980** (shown in **FIGS. 6A** and **7A**). In this manner, the gear surface **860** of the first cam member **780** is engaged with the gear surface **105** of the second cam member **980**. The capture ring **1100** maintains contact with at least portion of the retaining member **680** to urge the second end **720** and/or the catch **740** into contact with the second radial lip **1510**. After retention of the plunger **260** on the piston head **920** by the engagement of the second end **720** and/or the catch **740** in the second radial lip **1510** of the piston head **920**, the plunger **260** resists being disconnected from the piston **880** upon movement of piston **880** in a distal and proximal direction relative to the syringe barrel **18**. In one aspect, the second end **720** and/or the catch **740** may be designed such that the compressive forces exerted upon the second end **720** and/or the catch **740** upon movement of piston **920** in the proximal direction substantially prevents radially outward deflection (or bending) of the catch **740**. For example, once the catch **740** is engaged, axial movement of the piston **880** does not introduce a bending moment which may deflect the catch **740** radially to cause the plunger **260** to be disconnected from the piston **880**.

[00168] To unlock the syringe **12** from the syringe port **16** (shown in **FIG. 1**) and disengage the plunger **260** from the piston **880**, the syringe **12** is rotated clockwise or counter-clockwise about the syringe longitudinal axis, in a clockwise or counter-clockwise direction, relative to the syringe port **16**. Because the plunger **260** is substantially free from rotation within the syringe barrel **18** due to a frictional force between plunger seal **59** and the inner surface **23** of the syringe sidewall **19**, the rotation of the syringe **12** also causes the plunger **260** to rotate relative to the piston **880**. With reference to **FIGS. 11A-11B**, rotation of the plunger **260** about its longitudinal axis **340** engages the first cam member **780** on the plunger **260** with the second cam member **980** on the piston head **920**. In particular, rotational movement of the plunger **260** causes the gear surface **860** of the first cam member **780** to move along the gear surface **105** of the second cam member **980** such that the peaks **820** of the first cam member **780** are moved out of the grooves **101** of the second cam member **980** and toward the peaks **101** of the second cam member **980**. Such movement causes a radial

deflection of the at least one retaining member **680** away from the piston head **920**. The at least one retaining member **680** is at its maximum radial deflection when the peaks **820** of the first cam member **780** on the plunger **260** are positioned over or aligned with the peaks **101** of the second cam member **980** on the piston head **920**.

[00169] As the at least one retaining member **680** is deflected radially outward relative to the plunger longitudinal axis **340**, the second end **720** and/or the catch **740** is moved from the second radial lip **1510** of the piston head **920**. As the catch **740** moves out of its engaged position, the capture ring **1100** is advanced in the distal direction under the restoring force of the spring **1060**. As shown in **FIGS. 12A-12B**, the distal movement of the capture ring **1100** causes the capture ring **1100** to maintain the position of the at least one retaining member **680** in the radially outward deflected position, for example by moving under at least a segment of the at least one first cam member **780** or another part of the at least one retaining member **680**. In this position, the at least one retaining member **680** is held in a deflected state that allows the plunger **260** to be moved axially relative to the piston **880**. Such axial movement of the plunger **260** can be effected by withdrawing the syringe **12** from the syringe port **16** in a distal direction along the syringe longitudinal axis **15** or by withdrawing the piston **880** in a proximal direction away from the plunger **260**. The plunger **260**, together with the syringe **12**, can then be completely disengaged from the piston **880** and the injector **10**. In some aspects, the piston **880** can be released from the plunger **260** by rotating the piston **880** about its longitudinal axis and retracting the piston **880** in a proximal direction to disengage the at least one retaining member **680** in a manner described herein.

[00170] With reference to **FIG. 13**, a first adapter **114** may connect with a non-compatible plunger **P** without the at least one retaining member **68** described herein for removably engaging with the piston **88** of an injector having the piston head **92** with the second cam member **98** in accordance with one of the aspects described herein. In various aspects, the first adapter **114** may be connected to the plunger **P** for subsequent engagement with the piston **88**. For example, the first adapter **114** may be connected to the non-compatible plunger **P** releasably or permanently. Such a first adapter **114** may have a connection interface having at least one retaining member **68** with the first cam member **78** in accordance with various aspects described herein. According to another aspect, first adapter **114** may releasably connect with an injector having the piston **88** described herein. The first adapter **114** and the plunger **P** may be connected prior to connecting to the piston **88**, or the first adapter **114** may be connected to the piston **88** before the plunger **P** is connected to the first adapter **114**. The first adapter **114** and plunger **P** may be removed from the piston **88** after use, with the first

adapter **114** being disposed of with the plunger **P**, or being removed from the used plunger **P** and saved for subsequent use with a different plunger **P**. Alternatively, the first adapter **114** may be reversibly or non-reversibly connected to piston **88** for use with multiple syringes.

[00171] In one aspect, a first portion **116** of the first adapter **114** may permanently or releasably receive the plunger **P**, which is not compatible for use with the piston **88** described herein. The first adapter **114** allows a connection mechanism **118** of the non-compatible plunger **P** to engage a corresponding attachment mechanism **215** on the first adapter **114** such that the plunger **P** can be retained on the first adapter **114**. In some aspects, the first adapter **114** may have a separate mechanism for engaging and disengaging the plunger **P** while the first adapter **114** remains connected to the piston **88**. A second portion **120** of the first adapter **114** may have at least one retaining member **68** in accordance with any of the aspects described herein. In some aspects, the first adapter **114** may have at least one retaining member **68** may have an actuation member, such as a first cam member **78** described herein with reference to **FIGS. 3A-3B**; the first cam member **780** described herein with reference to **FIGS. 6A-12B**; the first cam member **78** shown in **FIGS. 15A-G**; the first cam member **78** shown in **FIGS. 20A-D**; the first cam member **78** shown in **FIGS. 21A-C**; the first cam member **78** shown in **FIGS. 22A-D**; the first cam member **78** shown in **FIGS. 23A-D**; and/or the first cam member **78** shown in **FIGS. 24A-C**. The second portion **120** of the first adapter **114** may releasably connect to an injector having the piston **88** with the piston head **92** according to any of the aspects described herein. In this manner, various non-compatible plungers **P** may be used. First adapter **114** may non-permanently, permanently, or semi-permanently connect to an injector having piston **88** with the piston head **92** described herein, allowing plungers **P** with alternate connection mechanisms to be used with the injector.

[00172] With reference to **FIG. 14**, a second adapter **122** may connect the plunger **26** with an injector that does not have the piston **88** with the piston head **92** according to any of the aspects described herein. In various aspects, the second adapter **122** may connect to the plunger **26** having at least one retaining member **68** in accordance with any of the aspects described herein for subsequent engagement with a non-compatible piston **P'**. For example, the second adapter **122** may be connected to the plunger **26** releasably or permanently. Such a second adapter **122** may have a connection interface having features of the piston head **92** in accordance with various aspects described herein. The second adapter **122** and the plunger **26** may be connected prior to connecting to the piston **P'**, or the second adapter **122** may be connected to the piston **P'** before the plunger **26** is connected to the second adapter **122**. The second adapter **122** and plunger **26** may be removed from the piston **P'** after use, with the

second adapter **122** being disposed of with the plunger **26**, or being removed from the used plunger **26** and saved for subsequent use with a different plunger **26**.

[00173] In one aspect, a first portion **124** of the second adapter **122** may be configured for permanently or releasably engaging the plunger **26** which is not compatible for use with the piston **P'**. The second adapter **122** allows a connection mechanism **126** of the non-compatible piston **P'** to engage a corresponding connection mechanism **125** on the second adapter **122**. A second portion **128** of the second adapter **122** may have features of the piston head **92** in accordance with aspects described herein. In some aspects, the second portion **128** may have the second cam member **98** described herein with reference to **FIG. 4A, 15A, 20A** and/or **24A** and/or the second cam member **980** described herein with reference to **FIG. 7A**. The second portion **128** of the second adapter **122** may releasably connect to the plunger **26** described herein. In this manner, the plunger **26** may be connected to various non-compatible injectors using the second adapter **122**.

[00174] Referring to **FIGS. 15A-15G**, a piston **88** and a plunger **26** are shown in accordance with another aspect. The piston **88** is configured to interact with the plunger **26** (shown in **FIG. 15C**) to releasably lock the plunger **26** such that the plunger **26** can be driven reciprocally within the barrel of the syringe **12** (shown in **FIG. 2**).

[00175] With continued reference to **FIG. 15A**, the piston **88** includes a stem **90** and a piston head **92** formed on a distal end of the stem **90**. The piston head **92** is construed from a rigid material, such as metal or plastic that resists deformation. The stem **90** may have a cavity **91** for collecting any fluid that may drip from the syringe and an annular collar **93** that surrounds the cavity **91**. One or more buttresses **97** connect the annular collar **93** to the stem **90**. The piston head **92** has a substantially cylindrical structure with a pointed or conical distal end **94** with a cap **95** that is shaped to be received inside at least a portion of the interior cavity **40** (shown in **FIG. 3A**) of the plunger **26**. In some aspects, a sensing member **79**, such as a pin connected to a sensor, may be provided. The sensing member **79** may extend along a longitudinal axis of the piston **88** and may protrude through at least a portion of the piston head **92**, such as through at least a portion of the cap **95**. The sensing member **79** may be operative for sensing contact with a surface, such as a surface of the plunger **26** and/or the plunger cover **58** (shown in **FIG. 3E**), and control a movement of the piston **88** based on the sensed condition. For example, an initial contact between the sensing member **79** and the plunger **26** and/or the plunger cover **58** may cause the pin to be retracted in a proximal direction such that it makes contact with the sensor. The sensing member **79** may be biased in an extended position by a resilient element **81** (shown in **FIG. 15E**), such as a spring. The

sensor may be connected to the control mechanism which controls the drive mechanism of the piston **88** such that, upon activation of the sensor by the pin, the controller controls the movement of the drive mechanism. For example, the drive mechanism may be stopped or slowed from a first rate to a second, slower rate.

[00176] With reference to **FIG. 15B**, the piston head **92** has a proximal portion **103** connected to a distal portion **105**. Terminal ends of the proximal and distal portions **103**, **105** may have a radiused edge **107**. At least a portion of the proximal portion **103** has a smaller outer diameter compared to an outer diameter of the distal portion **105** such that a radial lip **109** is formed at a transition between the proximal portion **103** and the distal portion **105**. The radial lip **109** may be continuous or discontinuous around a circumference of the piston head **92**. In some aspects, the radial lip **109** defines a locking ledge **111** for engaging the catch **74** of the at least one retaining member **68** when the plunger **26** is fully seated on the piston head **92**.

[00177] With continued reference to **FIG. 15B**, the piston head **92** may have at least one second alignment member **113** protruding radially outward from an outer surface of the piston head **92**. The at least second alignment member **113** is shaped and/or configured for interacting with the first alignment member **71** of the plunger **26** for facilitating alignment of the piston **88** with the plunger **26** in order to allow for a releasable locking connection of the plunger **26** with the piston **88**. In some aspects, at least a portion of the at least second alignment member **113** may extend in a direction that is angled relative to the direction of a piston longitudinal axis **115**. For example, at least second alignment member **113** may have a guiding surface **117** that is angled at an angle **D** relative to the piston longitudinal axis **115**. The guiding surface **117** is desirably angled such that the piston head **92** may rotate around the piston stem **90,** for example around an axis of the one-way rotation mechanism **99**, when the proximal alignment surface **77a** of the first alignment member **71** contacts the guiding surface **117** of the second alignment member **113**.

[00178] In some aspects, a plurality of second alignment members **113** may be spaced apart radially relative to the piston longitudinal axis **115** along an outer circumference of the piston head **92**. In some aspects, the number of second alignment members **113** may be equal to a total number of retaining members **68** and first alignment members **71** on the plunger **26**. The second alignment members **113** are spaced apart circumferentially such that a retaining member **68** or a first alignment member **71** may be received between adjacent second alignment members **113**. The second alignment members **113** may be separated from each

other by portions of an outer surface of the proximal portion **103** and/or the distal portion **105** of the piston head **92**.

[00179] With continued reference to **FIG. 15B**, each guiding surface **117** of the second alignment members **113** defines a travel path for guiding the movement of the proximal alignment surface **77a** of the first alignment member **71** in and out of a recess **119** defined between adjacent second alignment members **113** (see **FIG. 15G**). The guiding surfaces **117** may be inclined or angled radially and axially relative to the piston longitudinal axis **115** to guide the movement of the proximal alignment surfaces **77a**. The guiding surfaces **117** aid in self-orienting the piston head **92** as the plunger **26** (see **FIG. 15G**) is brought into contact with the piston **88** by guiding the one or more proximal alignment surfaces **77a** on the plunger **26** into the corresponding recess **119** on the piston head **92**. In this manner, a piston **88** whose piston longitudinal axis **115** is rotationally misaligned with the plunger longitudinal axis **34** and the one or more first alignment member **71** which are initially misaligned relative to the corresponding one or more second alignment members **113** in a rotational direction are brought in alignment axially and rotationally such that the one or more first alignment members **71** are received within the recess **119** between adjacent second alignment members **113**. The one or more second alignment members **113** may have a bottom surface **121** that is angled relative to the direction of a piston longitudinal axis **115**.

[00180] The piston head **92** further has an actuation surface that interacts with the actuation member on the plunger **26**, such as the first cam member **78**. In some aspects, the actuation surface on the piston head **92** may be a second cam member **98**. In some aspects, the second cam member **98** cooperates with the first cam member **78** on the at least one retaining member **68** of the plunger **26**, as described herein. The second cam member **98** desirably has a shape that, upon relative rotation between the piston **88** and the plunger **26**, engages the first cam member **78** to cause the at least one retaining member **68** to be deflected from the piston head **92** such that the plunger **26** can be removed from the piston **88**. In some aspects, the second cam member **98** may be formed on or intersect with the second alignment member **113** on the piston head **92**. In certain aspects, the second cam member **98** may have a cam surface **98a** extending radially outward and parallel to the longitudinal axis **115**. The cam surface **98a** may be aligned with a direction of the piston longitudinal axis **115**. The second cam member **98** may have a chamfered portion, not shown, to facilitate passing of the first cam member **78** after the retaining member **68** is deflected sufficiently to allow the retaining member to be released.

[00181] With reference to **FIG. 15C**, the piston **88** is configured to interact with the plunger **26** to releasably lock with plunger **26**, such as shown in **FIG. 15D**. By locking the piston **88** to the plunger **26**, the plunger **26** can be driven reciprocally within the barrel of the syringe **12** (shown in **FIG. 2**). The second cam member **98** on the piston **88** cooperates with the first cam member **78** on the at least one retaining member **68** of the plunger **26**, to releasably lock the plunger **26** to the piston **88**.

[00182] With reference to **FIG. 15F**, the piston head **92** may be rotatable relative to the stem **90**. In some aspects, the piston head **92** may be rotatable in one direction only, such as a clockwise or a counter-clockwise direction, relative to the stem **90**. A one-way rotation mechanism **99**, such as a one-way clutch mechanism shown in **FIG. 15F**, may be provided to allow the rotation of the piston head **92** in a first direction only, such as the clockwise or the counter-clockwise direction. The one-way rotation mechanism **99** may be rotatable around a central shaft **101** having a seal **102**, such as an O-ring seal. In some aspects, the one-way rotation mechanism **99** may have a stop that prevents rotation of the piston head **92** in a second direction opposite the first direction, such as the counter-clockwise or the clockwise direction, respectively. In other aspects, the one-way rotation mechanism **99** may be provided on at least a portion of the plunger **26**.

[00183] With reference to **FIG. 15G**, the at least one first alignment member **71** may be provided directly on one or more of the retaining members **68**. In such aspects, at least one retaining member **68** may have a proximal alignment surface **77a** provided directly on the body of the at least one retaining member **68**. The first cam member **78** may be also provided directly on the retaining member **68** such that engagement of the cam member **78** causes a corresponding movement of the retaining member **68**, as described herein. Cam member **78** may be provided on a side surface of retaining member **68** or may be provided on an edge of the at least one first alignment member **71** may be provided directly on one or more of the retaining members **68**.

[00184] With reference to **FIG. 16**, a cylindrical plan projection view of one aspect of the piston **88** and the plunger **26** is shown. If the piston **88** is rotationally misaligned relative to the plunger **26** such that the first alignment members **71** directly on the retaining members **68** on the plunger **26** are not in rotational alignment to be received within the recesses **119** on the plunger head **92**, the proximal alignment surface **77a** (shown as a dotted line) of the first alignment member **71** on the plunger **26** contacts the guiding surface **117** of the second alignment member **113** on the piston head **92**. Engagement of the proximal alignment surface **77a** with the guiding surface **117** causes the piston head **92** to automatically rotate in a free

rotation direction of the one-way rotation mechanism **99**. Such rotation of the piston head **92** aligns the first alignment members **71** and the retaining members **68** to be received within the recesses **119** between adjacent second alignment members **113**. In this manner, the piston **88** self-orients itself relative to the plunger **26** such that the plunger **26** may be releasably locked with the piston **88**. If the piston **88** is rotationally aligned relative to the plunger **26**, such as shown in **FIG. 16**, the first alignment members **71** and the retaining members **68** on the plunger **26** can be received within the recesses **119** between adjacent second alignment members **113** without rotation of the piston head **92**.

[00185] In some aspects, such as shown in **FIG. 17**, the plunger **26** may have one or more first alignment members **71** positioned adjacent to the one or more retaining members **68**. In some aspects, the width of the second alignment member **113** on the piston head **92** in a circumferential direction may be reduced such that the first alignment member **71** and the retaining member **68** may be received in a same space defined between adjacent second alignment members **113** on the piston head **92**. The one or more first alignment members **71** may have a first end **71a** connected to the body **32** of the plunger and a second end **71b** that protrudes in a proximal direction which is opposite to the protrusion direction of the second end **72** of the one or more retaining members **68**. The second end **71b** of the first alignment member **71** may be deflectable in a radial direction relative to the first end **71a**. The first alignment members **71** may further have an angled guide surface, for example defined by an outer surface of the second end **71b**, that cooperates with the second alignment members **113** of the piston head **92** to align the plunger **26** relative to the piston **88**. During the engagement/disengagement process, the second end **71b** of the first alignment members **71** may be deflected radially outward as it passes over the region defined by the recesses **119** and the second alignment members **113**, and is deflected back in a radially inward direction once the second end **71b** clears the recesses **119**. The one or more first alignment members **71** may have a latching member (not shown) to lock with at least a portion of the piston head **92**, such as the radial lip **109**.

[00186] In another aspect, such as shown in **FIGS. 18**, the one or more first alignment members **71** may be spaced apart from the one or more retaining members **68** such that each first alignment member **71** and the retaining member **68** is received in a separate space defined between adjacent second alignment members **113** on the piston head **92**. With reference to **FIG. 19**, the at least one first alignment member **71** may be bifurcated and formed from two separate portions. Each portion may be separately attached to the plunger body **32**. In some aspects, the two portions may be joined together at the second end **71b**,

such as shown in **FIG. 19**. In various aspects, interaction of the at least one first alignment member **71** on the plunger **26** with the one or more second alignment members **113** on the piston **88** causes self-orientation of the piston **88** such that at least one retaining member **68** is received in the recess **119** on the piston head **92**.

[00187] With reference to **FIG. 20A**, according to certain aspects, at least a portion of the second alignment members **113**, such as a lower or proximal end of the second alignment members **113** may be connected by a continuous lip **123** that extends continuously around an outer circumference of the piston head **92** at a radial position that may be flush with, radially recessed, or radially protruding relative to an outer surface of the second alignment members **113**. In aspects where two or more second alignment members **113** are provided, the second alignment members **113** may be evenly spaced apart from each other. In one exemplary and non-limiting aspect with six second alignment members **113** having equal angular separation therebetween, each second alignment member **113** is separated by 60 degrees from the second alignment members **113** adjacent on either side. In some aspects, the second alignment members **113** may have unequal angular extension and/or unequal angular spacing between the second alignment members **113** about the outer surface of the proximal portion **103** and/or the distal portion **105** of the piston head **92**. The radial spacing of the at least one second alignment members **113** relative to the piston longitudinal axis **115** is selected to correspond to an inner shape of the plunger **26** (shown in **FIG. 20B-20D**) to allow the retaining members **68** and the first alignment members **71** to be received between adjacent second alignment members **113**.

[00188] With reference to **FIGS. 20C-20D**, the at least one first alignment member **71** may be provided directly on one or more of the retaining members **68**. In such aspects, at least one retaining member **68** may have a proximal alignment surface **77a** and a distal alignment surface **77b** provided directly on the body of the at least one retaining member **68**. The proximal alignment surface **77a** may be angled relative to the plunger longitudinal axis **34**. In some aspects, the proximal alignment surface **77a** may be aligned with the guiding surface **117** on the piston **88** (shown in **FIG. 20A**) such that the proximal alignment surface **77a** is guided into the recess **119** on the piston head **92** (shown in **FIG. 20A**). The first cam member **78** may be also provided directly on the retaining member **68** such that engagement of the cam member **78** causes a corresponding movement of the retaining member **68**, for example during rotation of the plunger **26** relative to the piston head **92** as described herein. The retaining members **68** may have at least one catch **74** that it formed on the second end **72** of the retaining member **68**. The at least one catch **74** may be shaped to be received within

locking ledge **111** on the piston **88** (shown in **FIG. 20A**) to lock the plunger **26** axially relative to the piston **88**. In some aspects, the at least one catch **74** may be linear or curvilinear. In some aspects, the at least one catch **74** may be oriented in a direction substantially perpendicular to a direction of the plunger longitudinal axis **34**. In other aspects, the at least one catch **74** may be angled relative to a direction of the plunger longitudinal axis **34**. The at least one catch **74** may be continuous or discontinuous. In some aspects, the at least one catch **74** may protrude radially inward toward the plunger longitudinal axis **34**. With reference to **FIG. 20B**, the distal end **38** of the plunger body **32** may have one or more openings **49** extending through the plunger body **32**. The one or more openings **49** may be spaced apart radially relative to the plunger longitudinal axis **34**. The openings **49** may have equal or unequal angular extension and/or equal or unequal angular spacing between each other. In some aspects, the one or more openings **49** may be formed to facilitate molding of the plunger body **32**. For example, the one or more openings **49** define a path for a molding tool to follow during the molding process of the plunger **26**.

[00189] With reference to **FIGS. 21A-21C**, a plunger **26** and a piston **88** are shown in accordance with another aspect of the present disclosure. The components of the plunger **26** shown in **FIGS. 21A-21C** are substantially similar to the components of the plunger **26** described herein with reference to **FIGS. 3A-3C**. Similarly, the components of the piston **88** shown in **FIGS. 21A-21C** are substantially similar to the components of the piston **88** described herein with reference to **FIGS. 4A-4C**. Reference numerals in **FIGS. 21A-21C** are used to illustrate identical components of the corresponding reference numerals in **FIGS. 3A-4C**. As the previous discussion regarding plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** is applicable to the aspect of the present disclosure shown in **FIGS. 21A-21C**, only the relative differences between plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** and plunger **26** and piston **88** generally shown in **FIGS. 21A-21C** are discussed hereinafter.

[00190] With reference to **FIG. 21A**, the plunger **26** may have at least one resiliently deflectable retaining member **68** (hereinafter "retaining member **68**") protruding from the plunger body **32**. In some aspects, the at least one retaining member **68** may protrude in a circumferential direction extending around an inner circumference of the inner surface **52** of the interior cavity **40**. In some aspects, the at least one retaining member **68** may extend substantially perpendicularly to a longitudinal axis **34** of the plunger body **32**. In other aspects, the at least one retaining member **68** may be angled in a distal or proximal direction relative a plane extending perpendicularly to the longitudinal axis **34** of the plunger body **32**. Features such as the at least one alignment members **71** are omitted for clarity.

[00191] With continued reference to **FIG. 21A**, the at least one retaining member **68** has a first segment or a first end **70** connected to the plunger body **32** and a second segment or a second end **72** extending circumferentially around at least a portion an inner circumference of the plunger body **32** relative to the first end **70**. The second end **72** may deflect and/or twist relative to the first end **70**. As described herein, the second end **72** may be circumferentially and/or radially deflectable toward or away from the inner surface of the plunger body **32** relative to the first end **70**. The first end **70** and the second end **72** may be spaced apart in a direction that extends substantially circumferentially around an inner surface of the plunger body **32**. The at least one retaining member **68** may be linearly, stepwise, or curvilinearly contiguous between the first end **70** and the second end **72**. In some aspects, a plurality of retaining members **68** may be spaced apart radially relative to the plunger longitudinal axis **34** along a circumference of the inner surface **52** of the interior cavity **40**. The retaining members **68** may be separated from each other, such as by even or uneven spacing, by portions of the inner surface **52** of the interior cavity **40**. The radial spacing of the at least one retaining member **68** relative to the plunger longitudinal axis **34** is selected to correspond to or operably interact with an outer shape of the piston, as described herein.

[00192] With reference to **FIG. 21B**, the second end **72** of the retaining member **68** has at least one catch **74** that is shaped to engage at least a portion of a recess, lip, or ledge on the piston to lock the at least one retaining member **68**, along with the plunger **26**, relative to the piston. In some aspects, the at least one catch **74** may protrude radially inward or outward relative to a body of the retaining member **68**. The at least one catch **74** may be formed integrally with the second end **72** of the at least one retaining member **68** or it may be affixed or otherwise secured to the second end **72** of the at least one retaining member **68** using, for example, a frictional fit and/or an adhesive, welding, or by molding.

[00193] With reference to **FIG. 21C**, the plunger **26** may have at least one actuation member, such as a first cam member **78** that interacts with a piston of the fluid injector **10** (shown in **FIG. 1**) to radially deflect the at least one retaining member **68** upon rotation of the plunger **26** relative to the piston, as described herein. The at least one first cam member **78** may be provided at the second end **72** of the retaining member **68**. The at least one first cam member **78** may be angled relative to the body of the retaining member **68**. In some aspects, the at least one cam member **78** may be on at least one surface of a pocket **170** formed on the second end **72** of the at least one retaining member **68**.

[00194] The plunger **26** may have at least one alignment member, such as the first alignment member **71** shown in **FIG. 3A** protruding from the plunger body **32**. As described

herein, the at least one first alignment member **71** is shaped and/or configured for facilitating self-orienting alignment of the plunger **26** with the piston **88**.

[00195] To engage the plunger **26** with the piston **88**, the syringe **12** is first inserted into the syringe port **16** of the fluid injector **10** (shown in **FIG. 1**), as described herein. If the piston **88** is rotationally misaligned relative to the plunger **26** such that the one or more alignment members on the plunger **26** are not in rotational alignment to be received within the recesses **119** on the plunger head **92**, the one or more alignment members on the plunger **26** contact the guiding surface **117** of the second alignment member **113** on the piston head **92** to rotate the piston head **92** into alignment for connecting to the plunger **26**. In this manner, the piston **88** self-orients itself relative to the plunger **26** such that the plunger **26** may be releasably locked with the piston **88**. Distal movement of the piston **92** causes the retaining members **68** to circumferentially deflect outward relative to the plunger longitudinal axis **34** from a first, undeflected position, to a second deflected position. The piston **88** is advanced distally until the terminal portion of the second end **72** clears the retaining members **68**, thereby allowing them to deflect circumferentially inward toward or to their initial undeflected position. The catch **74** of at least one retaining member **68** is retained within the locking ledge **111** of the recess **119** or under a locking ledge **111a** formed on a proximal end of the a least one second alignment member **113** on the piston head **92** to prevent disengagement of the plunger **26** from the piston head **92**, for example by a frictional fit against a second portion of the inner wall of the plunger **26**. In some aspects, such as shown in **FIG. 21B**, at least a portion of the piston **88**, such as the at least one second alignment member **113**, may have a locking ledge **111a** that engages the catch **74** when the plunger **26** is connected to piston **88** to prevent plunger **26** from disconnecting from the piston **88** when the plunger **26** is moved in a proximal direction within syringe barrel **18** (shown in **FIG. 2**).

[00196] To unlock the syringe **12** from the syringe port **16** (shown in **FIG. 1**) and disengage the plunger **26** from the piston **88**, the syringe **12** is rotated clockwise or counter-clockwise about the syringe longitudinal axis, in a clockwise or counter-clockwise direction, relative to the syringe port **16**. Rotation of the syringe **12**, and thereby the plunger **26,** about the plunger longitudinal axis **34** engages the first cam member **78** on the plunger **26** with the second cam member **98** on the piston head **92.** Such movement causes a circumferential deflection of the at least one retaining member **68** away from the piston head **92** to unlock the plunger **26** from the piston head **92** and allow the removal of the syringe **12**.

[00197] With reference to **FIGS. 22A-22D**, a plunger **26** and a piston **88** are shown in accordance with another aspect of the present disclosure. The components of the plunger **26**

shown in **FIGS. 22A-22D** are substantially similar to the components of the plunger **26** described herein with reference to **FIGS. 3A-3C**. Similarly, the components of the piston **88** shown in **FIGS. 22A-22D** are substantially similar to the components of the piston **88** described herein with reference to **FIGS. 4A-4C**. Reference numerals in **FIGS. 22A-22D** are used to illustrate identical components of the corresponding reference numerals in **FIGS. 3A-4C**. As the previous discussion regarding plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** is applicable to the aspect of the present disclosure shown in **FIGS. 22A-22D**, only the relative differences between plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** and plunger **26** and piston **88** generally shown in **FIGS. 22A-22D** are discussed herein.

[00198] With reference to **FIG. 22A**, the plunger **26** may have at least one resiliently deflectable retaining member **68** (hereinafter "retaining member **68**") protruding from the plunger body **32**. In some aspects, the at least one retaining member **68** may be U-shaped, with a first portion **130** having a first end **132** connected to the plunger body **32** and a second end **134** extending in a direction toward the proximal end of the plunger body **32**. The at least one retaining member **68** may further have a transition portion **136** connected to the second end **134** of the first portion **130**. A first end **138** of a second portion **140** may be connected to the transition portion **136** at an end opposite to the connection of the second end **134** of the first portion **130**. The transition portion **136** extends in a radial direction relative to the longitudinal axis **34** of the plunger body **32** and connects the first portion **130** to the second portion **140**. A second end **142** of the second portion **140** extends toward the distal end of the plunger body **32**. The first portion **130**, the second portion **140**, or both may deflect or twist relative to the plunger body **32**. For example, the second end **134** of the first portion **130** may be deflectable in a radial or circumferential direction relative to the first end **132** and the plunger body **132**. Alternatively, or in addition, the second end **142** of the second portion **140** may be deflectable in a radial or circumferential direction relative to the first end **138**, and therefore, relative to the first portion **130** and the plunger body **32**. In some aspects, a plurality of retaining members **68** may be spaced apart radially relative to the plunger longitudinal axis **34** along a circumference of the inner surface **52** of interior cavity **40**. The retaining members **68** may be separated from each other, such as by even or uneven spacing, by portions of the inner surface **52** of the interior cavity **40**. The radial spacing of the at least one retaining member **68** relative to plunger longitudinal axis **34** is selected to correspond to or operably interact with an outer shape of the piston, as described herein.

[00199] With reference to **FIG. 22A**, the second end **142** of the second portion **140** of the retaining member **68** has at least one catch **74** that is shaped to engage at least a portion of a

recess, lip, or ledge on the piston to lock the at least one retaining member **68**, along with the plunger **26**, relative to the piston. In some aspects, the at least one catch **74** may protrude radially inward or outward relative to a body of the retaining member **68**. The at least one catch **74** may be formed integrally with the second end **142** of the second portion **140** of the at least one retaining member **68** or it may be affixed or otherwise secured to the second end **72** of the at least one retaining member **68** using, for example, a frictional fit and/or an adhesive, welding, or by molding.

[00200] With reference to **FIG. 22C**, the plunger **26** may have at least one first cam member **78** that interacts with a piston of the fluid injector **10** (shown in **FIG. 1**) to radially deflect the at least one retaining member **68** upon rotation of the plunger **26** relative to the piston, as described herein. The at least one first cam member **78** may be provided on the second portion **140** of the at least one retaining member **68**. The at least one first cam member **78** may be angled at an angle **B** relative to the body of the retaining member **68**.

[00201] With reference to **FIG. 22A**, the plunger **26** may have at least one first alignment member **71** defined on at least a portion of the at least one retaining member **68**, such as the transition portion **136**. The at least one first alignment member **71** is shaped and/or configured for facilitating self-orienting alignment of the plunger **26** with the piston **88**. In some aspects, at least a portion of the at least one first alignment member **71** may extend in a direction that is angled relative to the direction of the plunger longitudinal axis **34**. For example, at least one first alignment member **71** may have a proximal alignment surface **77a** that is angled at an angle **C** relative to the longitudinal axis **34** to facilitate positioning of the retaining member **68** during connection of the plunger **26** to a piston. The proximal alignment surface **77a** helps guide the plunger **26** into self-orienting alignment with the piston, as described herein.

[00202] To engage the plunger **26** with the piston **88**, the syringe **12** is first inserted into the syringe port **16** of the fluid injector **10** (shown in **FIG. 1**), as described herein. If the piston **88** is rotationally misaligned relative to the plunger **26** such that the one or more alignment members on the plunger **26** are not in rotational alignment to be received within the recesses **119** on the plunger head **92**, the one or more alignment members on the plunger **26** contact the guiding surface **117** of the second alignment member **113** on the piston head **92** to rotate the piston head **92** into alignment for connecting to the plunger **26**. In this manner, the piston **88** self-orients itself relative to the plunger **26** such that the plunger **26** may be releasably locked with the piston **88**. Distal movement of the piston **92** causes the retaining members **68** to deflect outward relative to the plunger longitudinal axis **34** from a

first, undeflected position, to a second, radially deflected position. The piston **88** is advanced distally until the terminal portion of the second end **72** clears the retaining members **68**, thereby allowing them to deflect radially inward toward or to their initial undeflected position. The catch **74** of at least one retaining member **68** is retained within the locking ledge **111** to prevent disengagement of the plunger **26** from the piston head **92**.

[00203] To unlock the syringe **12** from the syringe port **16** (shown in **FIG. 1**) and disengage the plunger **26** from the piston **88**, the syringe **12** is rotated clockwise or counter-clockwise about the syringe longitudinal axis, in a clockwise or counter-clockwise direction, relative to the syringe port **16**. Rotation of the syringe **12**, and thereby the plunger **26,** about the plunger longitudinal axis **34** engages the first cam member **78** on the plunger **26** with the second cam member **98** on the piston head **92.** Such movement causes a deflection of the at least one retaining member **68** away from the piston head **92** to unlock the plunger **26** from the piston head **92** and allow the removal of the syringe **12**.

[00204] With reference to **FIGS. 23A-23D**, a plunger **26** and a piston **88** are shown in accordance with another aspect of the present disclosure. The components of the plunger **26** shown in **FIGS. 23A-23D** are substantially similar to the components of the plunger **26** described herein with reference to **FIGS. 3A-3C** and other aspects described herein. Similarly, some of the components of the piston **88** shown in **FIGS. 23A-23D** are substantially similar to some of the components of the piston **88** described herein with reference to **FIGS. 4A-4C**. Reference numerals in **FIGS. 23A-23D** are used to illustrate identical components of the corresponding reference numerals in **FIGS. 3A-4C**. As the previous discussion regarding the plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** is applicable to the aspect of the present disclosure shown in **FIGS. 23A-23D**, only the relative differences between the plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** and plunger **26** and piston **88** generally shown in **FIGS. 23A-23D** are discussed hereinafter.

[00205] With reference to **FIG. 23A**, the plunger **26** may have at least one resiliently deflectable retaining member **68** (hereinafter "retaining member **68**") protruding from the plunger body **32**. In some aspects, the at least one retaining member **68** may protrude in a proximal direction toward the proximal end of the plunger body **32**. In some aspects, the at least one retaining member **68** may extend substantially parallel to a longitudinal axis **34** of the plunger body **32**. In other aspects, the at least one retaining member **68** may be angled relative to the longitudinal axis **34** of the plunger body **32**.

[00206] With continued reference to **FIG. 23A**, the at least one retaining member **68** has a first segment or a first end **70** connected to the plunger body **32** and a second segment or a

second end **72** extending in a proximal direction relative to the first end **70**. The second end **72** may deflect or twist relative to the first end **70**. As described herein, the second end **72** may be radially deflectable toward or away from the inner surface of the plunger body **32** relative to the first end **70**. The at least one retaining member **68** may be linearly, stepwise, or curvilinearly contiguous between the first end **70** and the second end **72**. In some aspects, a plurality of retaining members **68** may be spaced apart radially relative to the plunger longitudinal axis **34** along a circumference of the inner surface **52** of the interior cavity **40**. The retaining members **68** may be separated from each other, such as by even or uneven spacing, by portions of the inner surface **52** of the interior cavity **40**. The radial spacing of the at least one retaining member **68** relative to the plunger longitudinal axis **34** is selected to correspond to or operably interact with an outer shape of the piston, as described herein.

[00207] With reference to **FIG. 23B**, the second end **72** of the retaining member **68** has at least one catch **74** that is shaped to engage at least a portion of a recess, lip, or ledge on the piston to lock the at least one retaining member **68**, along with the plunger **26**, relative to the piston. In some aspects, the at least one catch **74** may protrude radially inward or outward relative to a body of the retaining member **68**. The at least one catch **74** may be formed integrally with the second end **72** of the at least one retaining member **68** or it may be affixed or otherwise secured to the second end **72** of the at least one retaining member **68** using, for example, a frictional fit and/or an adhesive, welding, or by molding.

[00208] With reference to **FIG. 23C**, the plunger **26** may have at least one first cam member **78** that interacts with a piston of the fluid injector **10** (shown in **FIG. 1**) to radially deflect the at least one retaining member **68** upon rotation of the plunger **26** relative to the piston, as described herein. The at least one first cam member **78** may be provided at the second end **72** of the retaining member **68**. The at least one first cam member **78** may be angled at an angle **B** relative to the body of the retaining member **68**.

[00209] The plunger **26** may have at least one alignment member, such as the at least one first alignment member **71** protruding from the plunger body **32**. As described herein, the at least one first alignment member **71** is shaped and/or configured for facilitating self-orienting alignment of the plunger **26** with the piston **88**. The at least one first alignment member **71** may be provided adjacent to the at least one retaining member **68**.

[00210] To engage the plunger **26** with the piston **88**, the syringe **12** is first inserted into the syringe port **16** of the fluid injector **10** (shown in **FIG. 1**), as described herein. If the piston **88** is rotationally misaligned relative to the plunger **26** such that the one or more alignment members **71** on the plunger **26** are not in rotational alignment to be received within

the recesses **119** on the plunger head **92**, the one or more alignment members **71** on the plunger **26** contact the guiding surface **117** of the second alignment member **113** on the piston head **92** to rotate the piston head **92** into alignment for connecting to the plunger **26**. In this manner, the piston **88** self-orients itself relative to the plunger **26** such that the plunger **26** may be releasably locked with the piston **88**. Distal movement of the piston **88** causes the retaining members **68** to deflect outward relative to the plunger longitudinal axis **34** from a first, undeflected position, to a second, radially deflected position. The piston **88** is advanced distally until the terminal portion of the second end **72** clears the retaining members **68**, thereby allowing them to deflect radially inward toward or to their initial undeflected position. The catch **74** of at least one retaining member **68** is retained within the locking ledge **111** of the recess **119** or under a locking ledge **111a** formed on a proximal end of the a least one second alignment member **113** on the piston head **92** (shown in **FIG. 23B**) to prevent disengagement of the plunger **26** from the piston head **92**.

[00211] To unlock the syringe **12** from the syringe port **16** (shown in **FIG. 1**) and disengage the plunger **26** from the piston **88**, the syringe **12** is rotated clockwise or counter-clockwise about the syringe longitudinal axis, in a clockwise or counter-clockwise direction, relative to the syringe port **16**. Rotation of the syringe **12**, and thereby the plunger **26,** about the plunger longitudinal axis **34** engages the first cam member **78** on the plunger **26** with the second cam member **98** on the piston head **92.** Such movement causes a deflection of the at least one retaining member **68** away from piston head **92** to unlock plunger **26** from the piston head **92** and allow removal of the syringe **12** from the injector **10** (shown in **FIG. 1**).

[00212] With reference to **FIGS. 24A-24C**, a plunger **26** and a piston **88** are shown in accordance with another aspect of the present disclosure. Some aspects of some of the components of the plunger **26** shown in **FIGS. 24A-24C** are substantially similar to the components of the plunger **26** described herein with reference to **FIGS. 3A-4C**. Other aspects of the components of the plunger **26** shown in **FIGS. 24A-24C** are substantially similar to the components of the plunger **26** described herein with reference to **FIGS. 21A-21C**. Similarly, the components of the piston **88** shown in **FIGS. 24A-24C** are substantially similar to the components of the piston **88** described herein with reference to **FIGS. 21A-21C**. Reference numerals in **FIGS. 24A-24C** are used to illustrate identical components of the corresponding reference numerals in **FIGS. 4A-4C** or **FIGS. 21A-21C**. As the previous discussion regarding the plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** is applicable to the aspect of the present disclosure shown in **FIGS. 24A-24C**, only the relative differences

between the plunger **26** and piston **88** generally shown in **FIGS. 3A-4C** and the plunger **26** and piston **88** generally shown in **FIGS. 24A-24C** are discussed hereinafter.

[00213] With reference to **FIG. 24A**, the plunger **26** may have at least one resiliently deflectable retaining member **68** (hereinafter "retaining member **68**") associated with the plunger body **32**. In some aspects, the at least one retaining member **68** may protrude in a radial direction from the inner surface **52** of the interior cavity **40**. With continued reference to **FIG. 24A**, the at least one retaining member **68** has a first segment or a first end **70** extending through, towards, or into the outside to the plunger body **32**. For example, the first end **70** of the at least one retaining member **68** may extend through an opening **73** extending through the sidewall **39** of the plunger body **32**. The at least one retaining member **68** may have a second segment or a second end **72** extending radially inward to the interior cavity **40** relative to the first end **70**. Features such as the at least one alignment members **71** are omitted for clarity.

[00214] The first end **70** of the at least one retaining member **68** may contact or abut, either directly or indirectly, a resilient member, for example the resilient inside surface of the plunger cover, such as the plunger cover **58** shown in **FIG. 3E**. Alternatively, or in addition, the first end **70** of the at least one retaining member **68** may contact or abut, either directly or indirectly, an elastic element, such as a metal or plastic spring, or other resilient material which urges the at least one retaining member **68** radially inward. With reference to **FIG. 24B**, the first end **70** of the at least one retaining member **68** may have at least one stop member **171** which limits the radially inward and/or outward travel of the at least one retaining member **68** so that it does not fall out of the plunger body **32**. The stop member **171** may be the elastic element associated the at least one retaining member **68**. The at least one retaining member **68** may be manufactured as a separate piece and inserted into the plunger body **32** before the plunger cover **58** is installed, co-molded with the plunger body **32** using a co-molding process, or may be molded as part of the plunger body **32** with a thin section (not shown) which deflects or breaks upon assembly or deflection of the at least one retaining member **68** in a radially inward or outward direction to allow the desired motion of the at least one retaining member **68**. Optionally, the at least one resilient member **68** can have the stop member **171** or the thin section (not shown) which attaches the at least one retaining member **68** to the plunger body **32**. In some aspects, a plurality of retaining members **68** may be spaced apart radially relative to the plunger longitudinal axis **34** along a circumference of the inner surface **52** of the interior cavity **40**. The retaining members **68** may be separated from each other, such as by even or uneven spacing, by portions of the inner surface **52** of the

interior cavity **40**. The radial spacing of the at least one retaining member **68** relative to the plunger longitudinal axis **34** is selected to correspond to or operably interact with an outer shape of the piston, as described herein.

[00215] With reference to **FIG. 24B**, the second end **72** of the retaining member **68** has at least one catch **74** that is shaped to engage at least a portion of a recess, lip, or ledge on the piston to lock the at least one retaining member **68**, along with the plunger **26**, relative to the piston. In some aspects, the at least one catch **74** may protrude radially inward or outward relative to a body of the retaining member **68**. The at least one catch **74** may be formed integrally with the second end **72** of the at least one retaining member **68** or it may be affixed or otherwise secured to the second end **72** of the at least one retaining member **68** using, for example, a frictional fit and/or an adhesive, welding, or by molding.

[00216] With reference to **FIG. 24C**, the plunger **26** may have at least one first cam member **78** that interacts with a piston of the fluid injector **10** (shown in **FIG. 1**) to radially deflect the at least one retaining member **68** upon rotation of the plunger **26** relative to the piston, as described herein. The at least one first cam member **78** may be provided at the second end **72** of the retaining member **68**. The at least one first cam member **78** may be angled relative to the body of the retaining member **68**.

[00217] The plunger **26** may have at least one alignment member, such as the first alignment member **71** shown in **FIG. 3A** or **FIG. 23** protruding from the plunger body **32**. As described herein, the at least one first alignment member **71** is shaped and/or configured for facilitating self-orienting alignment of the plunger **26** with the piston **88**.

[00218] To engage the plunger **26** with the piston **88**, the syringe **12** is first inserted into the syringe port **16** of the fluid injector **10** (shown in **FIG. 1**), as described herein. If the piston **88** is rotationally misaligned relative to the plunger **26** such that the one or more alignment members on the plunger **26** are not in rotational alignment to be received within the recesses **119** on the plunger head **92**, the one or more alignment members on the plunger **26** contact the guiding surface **117** of the second alignment member **113** on the piston head **92** to rotate the piston head **92** into alignment for connecting to the plunger **26**. In this manner, the piston **88** self-orients itself relative to the plunger **26** such that the plunger **26** may be releasably locked with the piston **88**. Distal movement of the piston **92** causes the retaining members **68** to deflect outward relative to the plunger longitudinal axis **34** from a first, undeflected position, to a deflected position. The piston **88** is advanced distally until the terminal portion of the second end **72** clears the retaining members **68**, thereby allowing them to deflect radially inward toward or to their initial undeflected position. The catch **74** of at

least one retaining member **68** is retained within the locking ledge **111** of the recess **119** or the locking ledge **111a** on a proximal surface of the second alignment members **113** to prevent disengagement of the plunger **26** from the piston head **92**.

[00219] To unlock the syringe **12** from the syringe port **16** and disengage the plunger **26** from the piston **88**, the syringe **12** is rotated clockwise or counter-clockwise about the syringe longitudinal axis, in a clockwise or counter-clockwise direction, relative to the syringe port **16**. Rotation of the syringe **12**, and thereby the plunger **26,** about the plunger longitudinal axis **34** engages the first cam member **78** on the plunger **26** with the second cam member **98** on the piston head **92**. Such movement causes a deflection of the at least one retaining member **68** radially away from the piston head **92** to unlock the plunger **26** from the piston head **92** and allow the removal of the syringe **12** from the injector **10** (shown in **FIG. 1**). In an alternative aspect, the catch **74a** (shown in **FIG. 24A**) may be on the distal surface of the at least one retaining member **68** to engage within the locking ledge **111** shown in **FIG. 24A** to prevent disengagement of the plunger **26** from the piston head **92**. The first cam member **78a** may positioned as indicated in **FIG 24A** to enable the catch **74a** to be released upon relative rotation of the plunger **26** and the piston **88**.

[00220] In accordance with various alternative aspects of the disclosure, the structural details of the connection interface between the plunger **26** and the piston **88** described herein could be reversed. That is, connection interfaces of any plunger **26** could comprise, for example, the locking mechanism and corresponding features described herein with reference to any piston **88**, while the connection interface on the piston **88** could comprise, for example, the elements described herein as being part of the plunger **26**.

[00221] Although the disclosure has been described in detail for the purpose of illustration based on what are currently considered to be the most practical and preferred aspects, it is to be understood that such detail is solely for that purpose and that the disclosure is not limited to the disclosed aspects, but, on the contrary, is intended to cover modifications and equivalent arrangements. For example, it is to be understood that the present disclosure contemplates that, to the extent possible, one or more features of any aspect can be combined with one or more features of any other aspect.

WE CLAIM:

1. A plunger for use with a syringe, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to an inner surface at the proximal end of the plunger body and a second segment protruding from the first segment toward the distal end of the plunger body and deflectable relative to the first segment along the longitudinal axis; and

at least one actuation member associated with the at least one resiliently deflectable retaining member, wherein the at least one actuation member comprises at least one cam member provided on a surface of the at least one resiliently deflectable retaining member,

wherein the at least one cam member of the at least one actuation member interacts with a piston used to engage the plunger to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston.

2. The plunger according to claim 1, further comprising at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member, the at least one alignment member having an alignment surface for guiding the piston into self-orienting alignment with the plunger during engagement of the plunger with the piston.

3. The plunger according to claim 2, wherein the at least one alignment member comprises a plurality of alignment members spaced apart around the plunger longitudinal axis.

4. The plunger according to claim 3, wherein the plurality of alignment members are spaced apart at equal radial intervals around the plunger longitudinal axis.

5. The plunger according to claim 1, wherein the second segment of the at least one resiliently deflectable retaining member is deflectable radially relative to the first segment away from the plunger longitudinal axis.

6. The plunger according to claim 1, wherein the at least one resiliently deflectable retaining member is linearly or curvilinearly contiguous between the first segment and the second segment.

7. The plunger according to claim 1, wherein the second segment of the at least one resiliently deflectable retaining member is angled toward the plunger longitudinal axis.

8. The plunger according to claim 1, wherein the at least one actuation member is at the second segment of the at least one resiliently deflectable retaining member.

9. The plunger according to claim 1, wherein the at least one actuation member is angled relative to a plane defined by a body of the at least one resiliently deflectable retaining member.

10. The plunger according to claim 1, wherein the at least one resiliently deflectable retaining member comprises a plurality of resiliently deflectable retaining members spaced apart around the plunger longitudinal axis.

11. The plunger according to claim 10, wherein the plurality of resiliently deflectable retaining members is spaced apart at equal radial intervals around the plunger longitudinal axis.

12. The plunger according to claim 1, wherein a terminal surface of the second segment of the at least one resiliently deflectable retaining member engages a surface of the piston to releasably lock the plunger with the piston.

13. The plunger according to claim 12, wherein the terminal surface is linear.

14. The plunger according to claim 12, wherein the terminal surface is perpendicular or angled relative to a direction of the plunger longitudinal axis.

15. The plunger according to claim 1, wherein the plunger body defines an interior cavity with a conical-shaped portion at the distal end of the plunger body and a cylindrical-shaped portion at the proximal end of the plunger body.

16. The plunger according to claim 1, wherein the at least one resiliently deflectable retaining member protrudes from the inner surface of the plunger body into the interior cavity.

17. The plunger according to claim 1, further comprising a plunger cover disposed over at least a portion of an outer surface of the plunger body, the plunger cover comprising a resilient seal disposed around at least a portion of a circumferential sidewall of the plunger cover.

18. The plunger according to claim 17, wherein the resilient seal comprises an inner surface at least partially seated in a groove in the circumferential sidewall of the plunger body and an outer surface adapted to slidably engage with a barrel of a syringe.

19. A plunger for use with a syringe, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to an inner surface at the proximal end of the plunger body and a second end protruding from the first segment toward the distal end of the plunger body and deflectable relative to the first segment along the longitudinal axis;

at least one actuation member comprising at least one cam member provided on a surface of the at least one resiliently deflectable retaining member, and

at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member,

wherein the at least one alignment member guides a piston into self-orienting alignment with the plunger during engagement of the plunger with the piston.

20. The plunger according to claim 19, further comprising at least one actuation member associated with the at least one resiliently deflectable retaining member, wherein the at least

one actuation member interacts with the piston to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston.

21. The plunger according to claim 20, wherein a terminal surface of the second segment of the at least one resiliently deflectable retaining member engages a surface of the piston to releasably lock the plunger with the piston.

22. The plunger according to claim 20, wherein the at least one actuation member is at the second segment of the at least one resiliently deflectable retaining member.

23. The plunger according to claim 20, wherein the second segment of the at least one resiliently deflectable retaining member is deflectable radially relative to the first segment away from the plunger longitudinal axis.

24. A plunger for use with a syringe, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to an inner surface at the proximal end of the plunger body and a second segment protruding from the first segment toward the distal end of the plunger body and deflectable relative to the first segment along the longitudinal axis;

at least one alignment member associated with the plunger body or the at least one resiliently deflectable retaining member; and

at least one actuation member associated with the at least one resiliently deflectable retaining member, wherein the at least one actuation member comprises at least one cam member provided on a surface of the at least one resiliently deflectable retaining member,

wherein the at least one alignment member guides a piston into self-orienting alignment with the plunger during engagement of the plunger with the piston, and

wherein the at least one cam member of the at least one actuation member interacts with the piston to deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston.

25. The plunger according to claim 24, wherein the second segment of the at least one resiliently deflectable retaining member protrudes towards the distal end of the plunger body and wherein the second end of the at least one resiliently deflectable retaining member is deflectable radially relative to the first segment away from the plunger longitudinal axis.

26. The plunger according to claim 24, wherein the second segment of the at least one resiliently deflectable retaining member protrudes in a direction circumferentially around the longitudinal axis of the plunger body and wherein the second end of the at least one resiliently deflectable retaining member is deflectable circumferentially relative to the first segment.

27. A syringe comprising:

a barrel having a barrel proximal end, a barrel distal end having a discharge nozzle, and a barrel sidewall extending between the barrel proximal end and the barrel distal end; and

a plunger slidably disposed within the barrel and reciprocally movable between the barrel proximal end and the barrel distal end, the plunger comprising:

a plunger body having a proximal end, a distal end, and a circumferential sidewall extending between the proximal end and the distal end along a plunger longitudinal axis;

at least one resiliently deflectable retaining member having a first segment attached to an inner surface at the proximal end of the plunger body and a second segment protruding from the first segment toward the distal end of the plunger body and deflectable relative to the first segment along the longitudinal axis; and

at least one actuation member associated with the at least one resiliently deflectable retaining member, wherein the at least one actuation member comprises at least one cam member provided on a surface of the at least one resiliently deflectable retaining member,

wherein the at least one cam member of the at least one actuation member interacts with a piston used to engage the plunger to radially deflect the at least one resiliently deflectable retaining member upon rotation of the plunger relative to the piston during disengagement of the plunger from the piston.