

CONTROL DEVICE FOR MOTOR-DRIVEN INJECTION MOLDING
MACHINE CAPABLE OF GENERATING LARGER CLAMPING FORCE

Background of the Invention:

The present invention relates to a mold clamping system of a motor-driven injection molding machine. More particularly, the present invention relates to a control device for a mold clamping system used for carrying out a clamping process with a toggle mechanism that is driven by a servo-motor.

A mold clamping system in an injection molding machine comprises a servo-motor, a ball screw, and a toggle mechanism. The servo-motor has a predetermined rated torque. The ball screw has a screw shaft and a nut to convert rotation of the servo-motor into rectilinear motion. The rotation of the servo-motor is transmitted to the screw shaft. In response to this, the screw shaft rotates and the nut moves forward, allowing the toggle mechanism to achieve clamping.

Molding of resins typically involves in a plurality of processes, i.e., dispensing of resin, filling, dwelling, and cooling. Besides these processes, the mold clamping system carries out a clamping process. In the mold clamping system, a torque of the servo-motor is controlled during the clamping process in order to

provide a clamping force of which a profile exhibits a predetermined pattern or patterns.

The time required for the clamping process may vary depending on the product to be molded. For example, it may take an hour for the clamping process to mold a lens. Under such circumstances, a conventional mold clamping system determines a rated torque for the servo-motor based on a maximum clamping force required for the molded product. This means that the servo-motor used for the mold clamping system is the one that is capable of generating the maximum clamping force within the ratings. However, such a situation that requires the maximum clamping force does not last for a long time in typical mold clamping systems, except for those designed for a special purpose as described above. In other words, the time during which the maximum clamping force is required accounts for a small proportion of the time for the entire clamping process.

Summary of the Invention:

Accordingly, an object of the present invention is to provide a control device for a motor-driven injection molding machine in which a clamping force above the ratings can be obtained with a mold clamping system driven by a servo-motor having smaller ratings.

The present invention is applicable to a control device for a motor-driven injection molding machine that comprises a mold clamping system having a servo-motor and a ball screw mechanism in which the ball screw mechanism

comprises a screw shaft and a nut for use in converting rotation of the servo-motor into rectilinear motion.

According to an aspect of the present invention, the control device comprises a pattern generator for generating a set pattern for the clamping force. The mold clamping system generates a clamping force according to the set pattern. A maximum clamping force with the set pattern is determined to be larger than the clamping force that is generated by the servo-motor within predetermined ratings.

Brief Description of the Drawings:

Fig. 1 is a view illustrating a structure of the essentials of a mold clamping system to which the present invention is applied;

Fig. 2 is a block diagram illustrating a structure of a control device for a mold clamping system according to the present invention;

Fig. 3 is a view showing an example of a set pattern generated by a set pattern generator illustrated in Fig. 2; and

Fig. 4 is a view illustrating an example of a table that is prepared in a memory to calculate the clamping force according to the set pattern illustrated in Fig. 3.

Description of the Preferred Embodiment:

Referring to Fig. 1, a mold clamping system of a motor-driven injection molding machine is described, to which the present invention is applied. In Fig. 1, a

mold clamping system 10 comprises a fixed platen 11, four tie bars 12, a movable platen 13, two arms 14, a toggle support 15, a servo-motor 16, a screw shaft 17, a cross head 18, a first toggle lever 19-1, and a second toggle lever 19-2. Only two tie bars 12 are illustrated in Fig. 2. A toggle mechanism is formed of the two arms 14, the toggle support 15, the cross head 18, and the first and the second toggle levers 19-1 and 19-2. While not illustrated, the fixed and the movable platens 11 and 13 are attached to fixed and movable molds, respectively, such that they are opposed to each other. The fixed platen 11 is securely fixed to a base plate 20. The movable platen 13 slides on the four tie bars 12 depending on the position of the two arms 14.

Rotation of the servo-motor 16 is transmitted to the screw shaft 17. A nut 21 is thread-engaged with the screw shaft 17. Rotation of the screw shaft 17 results in forward movement of the nut 21, which causes the toggle mechanism to achieve the clamping operation.

Referring to Fig. 2, it is described a control device for a mold clamping system according to a preferred embodiment of the present invention. The control device comprises a pattern generator 31. In response to a set clamping force F_0 , the pattern generator 31 generates a set pattern P_r as illustrated in Fig. 3 according to the set clamping force F_0 . The set clamping force F_0 is supplied from a main control unit (not shown) for the motor-driven injection molding

machine. The pattern generator 31 produces a command signal indicative of a command value in accordance with the set pattern P_r generated. The control device further comprises a sensor 32 for use in sensing the clamping force generated by the mold clamping system. The sensor 32 produces a sensed clamping force signal indicative of the sensed clamping force. A subtracter 33 calculates a difference between the command signal supplied from the pattern generator 31 and the sensed clamping force signal obtained by the sensor 32. The subtracter 33 then supplies a calculated difference signal indicative of the difference to an amplifier 34. The amplifier 34 has functions including PID compensation. The amplifier 34 amplifies the calculated difference signal and produces a torque instruction signal indicative of an instructed torque value for the servo-motor 16. A motor drive 35 drives the servo-motor 16 in accordance with the instructed torque value provided by the amplifier 34.

The mold clamping system to which the present invention is applied is the same type as the one illustrated in Fig. 1. However, the present invention makes it possible to use a conventional mold clamping system with the servo-motor for generating the maximum clamping force of, for example, 50 tons as the one that is capable of providing the maximum clamping force of larger than 50 tons. Reasons for it are described below.

As apparent from Fig. 3, the clamping force is typically applied after a certain time from the beginning

of the injection process and is increased rapidly. The clamping force then reaches a peak, set clamping force F_0 immediately after switching from the injection process to the dwelling process. From that point the clamping force is gradually decreased. A time interval T_p during which the maximum clamping force is present accounts for a significantly small proportion of the time for the entire clamping process.

It is assumed that the servo-motor 16 for the mold clamping system 10 has the ratings of the maximum clamping force of 50 tons. With the mold clamping system 10 comprising such servo-motor 16, no problems are in the generation of the maximum clamping force of approximately 70 tons by the servo-motor 16 when the time interval T_p during which the maximum clamping force is present accounts for a significantly small proportion of the time for the entire clamping process as shown in Fig. 3.

Based on this, the present invention makes it possible to provide the maximum clamping force above the ratings even in the mold clamping system with a servo-motor having smaller ratings.

The pattern generator 31 has a memory (not shown). The memory stores the set pattern P_r shown in Fig. 3 in the form of a table as illustrated in Fig. 4. In Fig. 4, a symbol x indicates the number of table entries of 0, ..., K , ..., and n . Each table entry indicates the time elapsed after the beginning of the injection process. K and n are each a natural number and

a numerical value between 100 and 1000 is typically given for n . In other words, the table number is set for each $T_w/1000$ seconds when n is equal to 1000 and the time interval is T_w seconds from the beginning of the injection process to the point when the clamping process completes and the clamping force becomes zero. A symbol y is a profile value that is given by a numerical value between 0 and 1. The profile value is obtained by means of converting the clamping force corresponding to each table number x , with the assumption that the set clamping force F_0 is a reference value 1 to define the maximum clamping force.

It is assumed that the injection process time is T_i and that the elapsed time from the beginning of the injection process is t . The table number x for use in looking up the profile value y on the table in Fig. 4 is then given by the equation: $x = K * t/T_i$, where K is the table number when $t = T_i$. The table number x obtained with the above equation may be a value having one decimal range. In such a case, the decimal range should be interpolated. The set clamping force F_r obtained at any point from the beginning of the injection is given by the following equation:

$$F_r = \{[y(X) - y(X - 1)] * (x - X) + y(X - 1)\} * F_0,$$

where X is obtained by truncating the figures of x below 1.

The pattern generator 31 reads, one by one, the clamping force defined by the set pattern out of the

memory. The pattern generator 31 produces the read clamping force as a command value. The motor drive 35 controls the torque of the servo-motor in accordance with the command value. This results in the control of the clamping force. The servo-motor 16 generates the maximum clamping force above its ratings for the short time interval of T_p . Such overloading for the short time interval of T_p is considered into design, so that no problem arises. Therefore, according to the mold clamping system of the present invention, it is possible to provide the maximum clamping force that is 1.5 to 2.0 times larger than the clamping force determined depending on the ratings of the servo-motor 16.

The above embodiment has thus been described in conjunction with the case where the memory has a single set pattern stored therein. However, several kinds of the set patterns are stored in practice in the memory for the various set clamping force. The set pattern corresponding to a set clamping force is looked up in response to the given set clamping force F_0 . In addition, the profile value y in the table is calculated with the time interval T_i for the injection process and the set clamping force F_0 in the above-mentioned embodiment. However, any time interval other than the time interval T_i for the injection process may be used. Furthermore, the set clamping force F_0 does not need to use the maximum clamping force. Moreover, the clamping force may be obtained by using a functional value rather

than the table as illustrated in Fig. 4.

As described above, the mold clamping system according to the present invention can provide the maximum clamping force above the clamping force determined depending on the ratings of the servo-motor. This makes it possible to mold a larger molded product as compared with the conventional mold clamping system having the same ratings.



WHAT IS CLAIMED IS:

1. A control device for a motor-driven injection molding machine that comprises a mold clamping system having a servo-motor and a ball screw mechanism in which the ball screw mechanism comprises a screw shaft and a nut for use in converting rotation of the servo-motor into rectilinear motion, wherein the control device comprises a pattern generator for generating a set pattern for the clamping force, the mold clamping system generating a clamping force according to the set pattern, and a maximum clamping force with the set pattern being determined to be larger than the clamping force that is generated by the servo-motor within predetermined ratings.

2. A control device for a motor-driven injection molding machine as claimed in claim 1, wherein said pattern generator comprises a memory, the memory storing the set pattern in the form of a table in which a time interval elapsed after the beginning of an injection process is in a one-to-one relationship with a value between 0 and 1, the value being determined depending on a desired clamping force with the maximum clamping force begin used as a reference value 1.