

SPECIFICATION  
REPRODUCER FOR DISC-SHAPE STORAGE MEDIUM

5    Technical Field of the Invention

        The present invention relates to a device for reproducing data from a CD-ROM or like storage medium.

        Background of the Technology

10          As is disclosed in Japanese Laid-Open Patent No. Hei 10-83615, for example, data is generally read out by first measuring vibration value by rotating a disc at a maximum speed prior to reproducing data and, when the vibration value is beyond a predetermined threshold level, by rotating the disc at a speed lower than the maximum speed.

15          A CD-ROM is a CD (compact disc) used as a ROM (read-only memory) and is used in computer systems just like a semiconductor ROM. As high speed processing is required in computer systems, rotational speed of a CD-ROM is generally set at a speed several to several tens of times higher than the rotational speed (200rpm) of audio CD's.

20          When a CD-ROM is scanned by a disc reproducer at such a high speed as 40 times the standard scanning speed, for example, an error of a tracking control system for correcting eccentricity of track due to disc vibration increases thus resulting in an error in reading-out data on the disc and requiring a retrial thereby lowering  
25          performance of reproduction. Also, when a low-quality disc having a large mass eccentricity is rotated, not only the disc but also the entire disc reproducer vibrates, and the vibration affects a hard disc drive (HDD) installed in a housing of a computer system together with the disc reproducer. There is thus a possibility of causing  
30          read/write error in the HDD, which lowers reliability of the entire computer system. Also, even if an error may not be generated in reading/writing of the HDD, vibration of the disc reproducer gives an unpleasant feeling to a user. The above problem can be solved by either reducing mass eccentricity of the CD-ROM or lowering the

rotational speed. However, in practice, there is a large dispersion in the quality of CD-ROM's and some discs are inappropriate for reproduction at a high speed.

In order to solve this problem, vibration value of a disc reproducer is detected and, when the detected value is beyond a preset threshold level, the reproducer is operated at a reduced disc rotational speed. However, as the detected vibration value varies due to manufacturing dispersion of individual disc reproducers, in a conventional fixed threshold level design, there has been a problem of inability to precisely switching the disc rotational speed.

#### Disclosure of the Invention:

It is an object of the present invention to provide a disc reproduction method and device that can stably reproduce data at as high speed as possible for both a high-quality storage medium disc and low-quality storage medium disc. Also, the present invention employs a method of detecting the maximum data reproducible speed by performing vibration detection from the side of a lower disc speed in order not to give an unpleasant feeling to a user by generating large vibration even during a vibration detecting mode.

In order to achieve the above object, the data reproducer in accordance with the present invention comprises the following: namely, disc rotating means structured in a manner such that a storage medium disc having data recorded on a spiral or concentric track and a center hole can be detachably fit to a spindle of the reproducer, a signal converter for reading out the data from the disc, and moving means for moving the signal converter in the radial direction of the disc.

Next, an allowable-limit vibration value is set in an adjusting process of individual data reproducer manufacture, and a plurality of allowable-limit mass eccentricity discs (hereinafter referred to as "standard vibrating discs") with a known mass eccentricity is prepared of which the vibration values at the maximum data reproduction speed and lower data reproduction speeds are equivalent to the allowable-limit vibration value. Each of the discs is then

mounted and the difference (P-P value) between the peak value in the positive direction of a tracking servo error signal (TE signal) and the peak value in the negative direction as obtained by rotating at a predetermined reproduction speed is detected as the vibration value of the disc reproducer in question, and the vibration value is set as the threshold level for the combination of the data reproduction speed and the vibration-limit disc as described later. When a disc with an unknown mass eccentricity is mounted, vibration value is detected at a data reproduction speed on the lower speed side that is lower than the maximum reproduction speed (hereinafter simply referred to as "the low speed side", the opposite side being referred to as "the high speed side"), followed by a first step of measuring a voltage (hereinafter referred to as "vibration value") proportional to the disc vibration that is occurring and a second step of judging whether or not the vibration value is below the threshold level. When it is judged in the second step that the vibration value is below the threshold level, the disc is rotated at the above-mentioned reproduction speed by the disc rotating means, and the signal converter reads out the data from the disc. When it is judged that the mass eccentricity is not within the allowable range, the disc is rotated by the disc rotating means at a data reproduction speed lower than the vibration detecting speed so that the afore-mentioned data can be read out from the disc with the signal converter.

In other words, a plurality of vibration detecting speeds (which may be the same as the data reproduction speed) is set at the maximum data reproduction speed and at speeds lower than that, and an allowable-limit mass eccentricity disc (standard vibrating disc) is prepared for each of the detecting speeds. The first threshold level for the first vibration detecting speed is set at the vibration value as detected on an allowable-limit mass eccentricity disc Da at a first vibration detecting speed. When a disc D with an unknown mass eccentricity is mounted, if the detected vibration data at the first vibration detecting speed is within the range of the first threshold level, vibration detection is carried out at a second

vibration detecting speed that is higher than the first vibration detecting speed.

The second threshold level for the second detection speed is set at the vibration data as detected on an allowable-limit vibrating disc Db at a second speed. When the detected vibration data at the  
5 second vibration detecting speed of the disc D with an unknown mass eccentricity is within the range of the second threshold level, vibration detection at a third vibration detecting speed is carried out. In this way, vibration detection is carried out in sequence  
10 from the low-speed side toward the high-speed side. At the stage a detected vibration data is found to be outside of respective threshold level range, the data is read out with a vibration detecting speed lower than the vibration detecting speed at which the detected vibration value was outside of respective threshold level range as  
15 the maximum speed. A data reproducer having such data reading means is hereby proposed.

According to a reproducer having the above structure, an allowable mass eccentricity of a disc is precisely set as a threshold level (allowable range) for each individual disc reproducer at the  
20 time the disc is reproduced at the maximum rotational speed at which data is reproducible. Consequently, by changing the maximum speed at which data can be reproduced depending on the mass eccentricity, it becomes possible to carry out high-speed reproduction of a disc that has a small mass eccentricity at the maximum speed available  
25 with the data reproducer, and to carry out reproduction of a disc having a large mass eccentricity under a condition in which a problem associated with mass eccentricity will not occur.

Also, according to the present invention, as high-speed rotation of a low-quality disc can be prevented, vibration value of  
30 a disc or data reproducer is limited. As a result, ripple effect of vibration on a separate device (HDD, for example) contained in the same housing as that of a data reproducer according to the present invention can be limited, thus enabling normal operation of the separate device (HDD, for example). Also, as vibration of the disc

or data reproducer is limited, unpleasant feeling to a user will be reduced.

Furthermore, in the present invention, as the maximum reproduction speed that is available within the allowable limit of the vibration value is determined by carrying out vibration detection two or more times from the low speed side of the disc rotation toward the high speed side, unpleasant feeling to the user can be prevented in the vibration detecting mode, too.

10    **Brief Description of the Drawings:**

Fig. 1 is a block diagram of a disc-shape storage medium (e.g., CD-ROM) drive in an exemplary embodiment of the present invention.

Fig. 2 is a block diagram showing disc, optical pickup, tracking servo circuit, focus servo circuit, and read-out output circuit in Fig. 1.

Fig. 3 is a flow chart for vibration detection.

Fig. 4 is an equivalent block diagram that illustrates mass eccentricity measurement and disc speed setting means in system control block 11 in Fig. 1.

20    Fig. 5 is a flow chart for vibration data read-out process.

Fig. 6 is a flow chart for vibration threshold level changing process.

Fig. 7 is an external view of a reproducer in which EEPROM is incorporated in an IC card.

25    Fig. 8 is a graph showing relationship between disc rotational speed and vibration value.

Fig. 9 is a graph showing relationship between vibration detecting speed and allowable-limit vibration value.

30    **Description of the Preferred Embodiments:**

A description of a disc reproducer will be given in reference to Figs. 1 to 7 as an exemplary embodiment of the present invention. Fig. 1 shows host computer 1 and disc reproducer 2. Disc reproducer 2 functions as a source of data supply to host computer 1, and they

are connected with bus 3.

Disc reproducer 2 comprises optical storage medium disc (CD-ROM) 4 comprising a CD, disc-rotating spindle motor 5M and spindle drive 5D of the spindle motor both being part of disc rotating means, optical pickup 6 as a signal converter, pickup drive 7 having a function as means for positioning or moving optical pickup 6, waveform-shaping circuit 8 for amplifying and shaping signal picked up by optical pickup 6, servo processor 9 for moving and focusing pickup 6 and for controlling synchronous rotation of motor 5M, signal processor block 10, system control block 11, and EEPROM 51 for storing threshold level.

Servo processor 9 comprises spindle servo block 12 as rotation control means for disc 4, servo block 13 of drive block 7 of tracking servo, focus servo, and pickup 6, synchronization detection and demodulating circuit 14, and interface 15 for a microprocessor for interfacing with system control block 11. Signal processing block 10 comprises error detection and correction circuit 16 and interface circuit 17.

System control block 11 comprises microprocessor 18M, program ROM 18P for storing executive instruction and the like for microprocessor 18M, work RAM 18R for microprocessor 18M, and clock generator 18C.

Disc (CD-ROM) 4 has center hole 20 to which spindle 19 coupled with motor 5M is to be inserted, and has spiral track 41 that runs from the inner side of the disc toward the outer side with center hole 20 at the center as illustrated in Fig. 2. Data is recorded on track 41 as optical pits of a number of data blocks in the known format, where 2352 bytes constitute 1 unit or 1 data block, 1 byte being 8 bits. One data block is reproduced in 1/75 second when reproduced at a standard speed that is the same as the scanning speed (1.2 to 1.4 m/sec) of an audio CD. As is well known, CD-ROM data is reproduced at a constant angular velocity (CAV).

As schematically shown in Fig. 2, optical pickup 6 is a known unit comprising, for example, laser source 61 comprising a laser diode,

diffraction grating 62, beam splitter 64, collimator lens 66 for obtaining a parallel light beam, quarter-wavelength plate 67, objective lens 68L, cylindrical lens (a lens looking like a part of a cylinder) disposed on the optical path of a reflected light beam, optical detector 69 (consisting of 69F and 69B), actuator 68T for tracking control, and actuator 68F for focus control.

In optical pickup 6, focus actuator 68F is driven by a control signal from focus servo block (focus error detecting circuit 32, phase compensation and drive circuit 33) that constitutes pickup servo block 13, and a light beam emitted by light source 61 is focused with objective lens 68 and projected to the main surface of disc 4, and the data stored on disc 4 in the form of optical pits is read out. As the optical pits are disposed on track 41 in a manner corresponding to the data, when a non-modulated light beam is projected onto disc 4 as a reproducing beam, the reproducing beam is modulated by the pits (data) and reflected light beam 64 incident on optical detector 69 becomes a modulated beam. Optical detectors 69F, 69B are optical detecting means for converting light into electric signals.

The tracking servo circuit and focus servo circuit that constitute pickup servo block 13 are publicly known as disclosed in Japanese Laid-Open Patent Application No. Hei-83615, for example.

The vibration of a disc reproducer due to mass eccentricity of disc 4 as referred to in the present invention takes place in principle in the radial direction of the disc, where the magnitude is proportional to the product of the amount of mass eccentricity and square of rotational speed of the disc, and its main component is one that is periodically produced in each rotation of the disc.

In Fig. 2, tracking servo circuit 13T that constitutes pickup servo block 13 detects radial displacement (in a direction crossing the track) of light beam spot 42 on track 41 as a TE signal with tracking-error detecting circuit 31. Subsequently, negative feedback control is carried out with phase compensation and drive circuit 30 to drive objective lens 68L in the radial direction of the disc (direction crossing the track) by means of tracking actuator

68T, namely, in the direction of arrow 68L, thus enabling tracing of the track.

Consequently, the TE signal contains vibration information even in the vibration data read-out mode.

5 Also, waveform-shaping circuit 8 demodulates EFM (Eight-to-Fourteen Modulation) signals into NRZ digital signals, for example, by using a sync signal obtained by connecting to sync detection and demodulation circuit 14, and supplies them to servo processor 9.

Well-known error detection and correction circuit 16 connected  
10 to sync detection and demodulation circuit 14 detects error in the demodulated data (reproduced data) and makes correction when error is detected and is correctable. Error detection and correction circuit 16 is connected to interface circuit 17 and system control block 11. In the event an uncorrectable data reproduction error has  
15 occurred, retrieval is carried out in a well-known manner. In the meantime, waveform-shaping circuit 8, sync detection and demodulation circuit 14, and error detection and correction circuit 16 can be collectively called reproduction signal processing means.

Also, interface circuit 17 is connected between error  
20 detection and correction circuit 16 and host computer 1 as well as between host computer 1 and system control block 11.

Though not shown in Fig. 1, a frequency signal generator (hereinafter FG) is coupled to motor 5M and generates pulses at a frequency corresponding to the rotation of motor 5M. FG is connected  
25 to system control block 11 and to spindle servo block 8 that executes CAV control. The output pulses of FG are not only used for CAV control but also for setting time required for detection of vibration value of disc 4. Consequently, FG can be regarded as part of the vibration value detecting means. System control block 11 as reproduction  
30 control means comprises microprocessor 18M, program ROM 18P, and work RAM 18R, and operates according to an operation control program stored in program ROM 18P.

Fig. 4 is a block diagram illustrating a part of system control block 11 and servo processor 9 in Fig. 1 in an equivalent or functional

manner. As is clear from Fig. 4, system control block 11 and servo processor 9 include mode switching signal generating means 96 and vibration value detecting and judging means 90 that further includes frequency divider 93, comparing means 94, A/D converter 91, maximum value detecting means 92, threshold-level generating means 95 and  
 5 comparing means 94, and speed command data generating means 97 for commanding the rotational speed of motor 5M.

Mode switching signal generating means 96 generates vibration value detecting mode signal, normal reproduction mode signal, and  
 10 threshold-level setting mode signal.

A/D converter 91 in Fig. 4 converts a TE signal voltage in pickup servo block 13 into a digital signal when in vibration detecting mode. Maximum value detecting means 92 detects maximum amplitude value (Peak-to-Peak value) of the TE signal within the time of one rotation  
 15 of disc 4 based on signal 5S that indicates one rotational period of disc 4 as obtained by frequency division of FG pulse 5F with frequency divider 93 and TE signal 36D as obtained from A/D converter 91. Here, the vibration value of disc 4 can be known from the difference between the positive peak and negative peak of the TE  
 20 signal, namely, the interval between the positive peak and negative peak. In other words, if there is no vibration of disc 4, it is not necessary to adjust tracking of light spot 42 based on vibration, and the voltage of the TE signal is in the vicinity of zero volt under normal servo condition. On the other hand, when there is vibration  
 25 due to mass eccentricity of a disc, the position of the objective lens in the radial direction of disc 4 changes greatly, and the voltage of the TE signal changes toward positive or negative direction in order to make correction. Accordingly, it becomes possible to measure vibration as eccentricity of a track in terms of the TE signal.  
 30 In this exemplary embodiment, vibration is detected based on the sum of the maximum value of the positive peak and the maximum value of the negative peak of the TE signal voltage during one rotation of disc 4, namely, the amount of amplitude change from the maximum value of the positive peak to the maximum value of the negative peak.

Threshold-level generating means 95 sends out to first judging means, namely, comparing means 94 a signal, namely, threshold level  $V_r$  that indicates allowable limit of vibration when disc 4 is rotated at the maximum speed. The threshold level  $V_r$  is a criterion value pre-  
 5 stored in EEPROM 51, which is read out from EEPROM 51 by writing/reading (hereinafter R/W) control means 52, and is sent to comparing means 94 through threshold-level generating means 95. Comparing means 94 makes judgment as to whether or not the maximum value of the TE signal that indicates vibration value is below the  
 10 criterion value, and sends the result to speed command data generating means 97. When the vibration value exceeds threshold level  $V_r$ , a low-quality disc flag is set and the disc rotational speed is lowered.

In Fig. 4, speed command data generating means 97 puts out at least two speed command data to line 98, namely, a maximum speed and  
 15 a second speed lower than the maximum speed. When a maximum speed command is put out from speed command data generating means 97, spindle servo block 12 drives disc 4, and the focus servo circuit and tracking servo circuit are brought into operation. Under a state of data reproduction, signal 36D obtained by digitalizing TE signal  
 20 36 is put to maximum value detecting means 92. By obtaining periodic signal 5S for one rotation of a disc by frequency division of FG signal 5F, maximum amplitude value  $V_{te}$  during one rotation of the disc is obtained, comparison is made by comparing means 94 to determine whether or not  $V_{te}$  is within the allowable range, namely, less than  
 25 the threshold level  $V_{tr}$ . When a "No" signal is obtained indicating that  $V_{te} > V_{tr}$ , an assumption is made that the disc is of low quality, rotational speed of disc 4 is lowered from the maximum speed to the second speed, and data reproduction is carried out.

When a "Yes" signal is obtained indicating that  $V_{te} < V_{tr}$ , an  
 30 assumption is made that the disc is within the allowable range, and it is rotated at the maximum speed as it is, and data reproduction is carried out. As a result, the time required for data reproduction can be shortened.

In the above, a conceptual description is given on two cases

of speed, namely, the maximum speed and a second speed lower than the maximum speed. It is an object of the present invention to minimize as much as possible the vibration that is unpleasant to a user even during the vibration detecting mode.

5           In other words, it is an object to find out a maximum speed for a disc with an unknown mass eccentricity at which secure data reproduction is possible at or below an allowable vibration value. That is, for a disc having a large vibration value, to detect the maximum speed at which data is reproducible on the low speed side  
10 where the vibration value is less than the allowable-limit vibration value of the reproducer, and, for a disc having a small vibration value, to detect the maximum speed at which data is reproducible on the high speed side.

          This approach makes it possible to avoid reduction in  
15 performance of the reproducer due to a situation in which reproduction speed is set on the low speed side for a disc having a small vibration value.

          A description of operation of an exemplary embodiment of the present invention will now be given in reference to Fig. 8. The  
20 abscissa of the graph of Fig. 8 represents disc rotational speed of a reproducer, which can be set in a manner such that data reproduction at  $x10$  (10 times),  $x12$ ,  $x20$ , and  $x24$  the standard speed can be made. The speeds of  $x12$ ,  $x20$ , and  $x24$  are also set as vibration detecting speeds. The ordinate represents vibration value and the values  $Aa$ ,  
25  $Ba$ ,  $Ca$  on the ordinate axis represent respective vibration values of allowable-limit discs  $Da$ ,  $Db$ ,  $Dc$  at  $x12$ ,  $x20$ , and  $x24$  speeds. As shown in Fig. 8, the vibration value increases in the order of  $Da$ ,  $Db$ ,  $Dc$ . These values are used as threshold levels at each respective speed. Curves A, B, C show speed vs. vibration value characteristic  
30 of discs  $Da$ ,  $Db$ ,  $Dc$ .

          Next, a description will be given below on the method of finding the maximum speed for data reproduction by detecting vibration value of a disc with an unknown mass eccentricity. First, vibration value is detected at the moment the disc rotational speed has reached  $x12$

speed from a low speed. Supposing that the vibration value is detected to be  $V_{12}$ , if  $V_{12} > A_a$ , the disc is judged to be outside of the allowable limit. As a result, a minimum data reproduction speed (x10 speed in this case) can be set at which most of the vibration of disc reproducers will fall below the allowable limit when dispersion of mass eccentricity of discs on the market is taken into account. In the case of the figure, as x10 speed is set as the minimum speed, the x10 speed is set as the maximum speed at which data is reproducible.

10        If  $V_{12} < A_a$ , data reproduction at x12 speed is judged to be possible. Additionally, a command is issued to increase the disc rotational speed to x20 speed and the vibration value at the moment the disc rotational speed has reached x20 speed is detected as  $V_{20}$  in the same manner as before.

15        If  $V_{20} > B_a$ , the disc is judged to be outside of the allowable limit and a speed change command is issued to lower the disc rotational speed to x12 speed, thus making the x12 speed the maximum speed at which data is reproducible.

20        Furthermore, if  $V_{20} < B_a$ , judgment is made that data reproduction is possible at a further higher speed, and a command to increase the disc rotational speed to x24 speed is issued. At the moment the disc rotational speed has reached x24 speed, vibration detection is carried out and detected value  $V_{24}$  is obtained as the vibration value in the same manner as above.

25        If  $V_{24} > C_a$ , the disc is judged to be outside of the allowable limit, a rotational speed change command is issued to lower the disc rotational speed to x20 speed, and the x20 speed is set as the maximum speed at which the disc is reproducible.

30        If  $V_{24} < C_a$ , judgment is made that data reproduction at x24 speed is possible and the x24 speed is set as the maximum speed. By setting maximum speed of data reproduction in the manner described above, it becomes possible to set the maximum speed at which data is reproducible without allowing vibration that exceeds the allowable vibration limit to take place on the high-speed side independently

of the magnitude of disc vibration values.

In other words, data reproduction on the high-speed side is enabled as surely as possible even for a disc with a small mass eccentricity, and previously mentioned functional reduction can be prevented.

Also, instead of making judgment by successively increasing the vibration detecting speed from the low-speed side as described above, vibration value  $A_{a1}$  in Fig. 8 of an allowable-limit disc is chosen as a threshold level at  $12x$  speed. If a vibration value  $V_{12}$  of a disc with a known vibration value as obtained by reproducing at  $x_{12}$  speed satisfies  $V_{12} < A_{a1}$ , it can be assumed that the vibration value is below the allowable limit at a maximum speed of  $x_{24}$ , and the  $x_{24}$  speed is judged to be the maximum reproduction speed. If  $A_{a1} < V_{12} < A_s$  is satisfied,  $x_{20}$  speed is judged to be the maximum reproduction speed while, when  $V_{12} < A_s$  is satisfied,  $x_{10}$  speed is judged to be the maximum speed. If the sensitivity of vibration detection is high enough, one-time vibration detection will suffice indicating that it is simpler than a method of making judgment by successively increasing vibration detecting speed from the low speed side.

By setting threshold levels and making vibration value detection on the low speed side as has been described above, the present invention has advantages of not giving an unpleasant feeling to a user during vibration value detection and also avoiding the risk of possible damage of a computer system due to abnormal vibration that might be generated when carrying out vibration value detection on the high speed side from the beginning using a disc having a large vibration value.

In recent data reproducers, data reproduction speed has increased such as  $x_8$ ,  $x_{10}$ ,  $x_{20}$ ,  $x_{30}$ ,  $x_{40}$  speeds, and there are many cases where data reproduction is carried out at respective speeds. In comparison to these data reproducers, the present invention provides a method in which a maximum reproduction speed applicable for a disc with an unknown vibration value can be determined in a

stable and efficient manner.

A description of the above vibration detection operation will be given in reference to the flow chart of Fig. 3. In the flow chart of Fig. 3, vibration detection starts when a disc with an unknown vibration value has been mounted, namely, when disc 4 has started to rotate and optical pickup 6 has detected a signal. A command for x12 speed at which the disc rotational speed is higher than the lowest data reproduction speed set in the disc reproducer is sent to speed command data generating means 97. At the moment x12 speed is reached, vibration value data V12, namely TE signal (2-byte numeral), is input to microprocessor 18M of system control block 11 as an output of maximum value detecting means 92 as described earlier. Vibration value data V12 is then compared with a threshold level Aa (stored in EEPROM 51) to determine whether vibration value data V12 is greater or smaller. When vibration value data V12 is greater than the threshold level Aa, x10 speed is judged to be the speed at which data is reproducible. If the vibration value data is smaller than the threshold level Aa, judgment is made that reproduction at a higher speed is possible, and a signal is sent to speed command data generating means 97 so as to increase the reproduction speed. In this case the command is for x20 speed. In the same manner as above, vibration value data V20 at x20 speed is compared with threshold level Ba. If vibration value data V20 is greater than the threshold level Ba, x12 speed is judged to be the maximum speed at which data is reproducible. If vibration value data V20 is smaller than the threshold level Ba, judgment is made that reproduction at a still higher speed (in this case the maximum speed is assumed to be x24 speed) is possible. Similarly, a command signal to increase the speed is sent to speed command data generating means 97, and vibration value data V24 obtained at the moment the disc has reached x24 speed is compared with threshold level Ca. If vibration value data V24 is greater than threshold level Ca, judgment is made that the disc is a vibrating disc, and a signal to lower the reproduction speed is sent to speed command data generating means 97, and x20 speed is judged

to be the maximum speed at which data is reproducible. Also, while data reproduction at a further higher speed is possible if vibration value data V24 is smaller than threshold level Ca, vibration value detection is completed by judging that x24 speed is the maximum speed  
5 at which data is reproducible because x24 speed is the maximum speed in this case.

Next, a description will be given on vibration data read-out process in reference to Fig. 5. Upon start of vibration detection as described above, vibration data read-out routine will start in  
10 the first place, and initialization of peak data is carried out. This is done by storing positive or negative peak voltage of the TE voltage that appears during one rotation of a disc. Data capture during one rotation is done by successively sampling data from the first positive or negative peak voltage to the next positive or negative peak voltage  
15 at appropriate intervals, and sending the result from maximum value detecting means 94 in Fig. 4 to microprocessor 18M. Microprocessor 18M temporarily stores the TE signal voltage in work RAM 18R. After data of one rotation is stored in work RAM 18R, positive and negative peak voltages are read out and the values are stored as vibration  
20 data at a separate address within work RAM 18R.

A description on threshold level change, being a key part of the present invention, will now be given below in reference to Fig. 6. In the present invention, it is common that allowable vibration value of a disc-shape storage medium (CD-ROM and the like) reproducer  
25 differs depending on the product system to which the disc-shape storage medium (CD-ROM and the like) reproducer is applied, such as a portable personal computer in which a key board, HDD unit, display and the like are encased as an integral unit, or a desktop personal computer in which individually encased separate units are connected  
30 with cables. Consequently, in the manufacturing process of a disc storage media (CD-ROM and the like), the allowable vibration value, namely, threshold level differs for each individual product system such as Specification A, Specification B, etc.

Therefore, a standard threshold level for each different

specification is burnt into EEPROM 51 (Figs. 1 and 4) in advance as a voltage value in the form of a 2-byte long numeral.

For example, supposing that the exemplary embodiment described above is Specification A, as parameters for Specification A as in  
 5 the description in reference to Fig. 8, maximum values of the tracking error signal amplitude that correspond to the allowable-limit vibration value (0.5 gram-cm, for example) of a disc-shape storage medium (CD-ROM and the like) reproducer are burned in for an allowable-limit vibrating disc, for example, Aa for the lowest  
 10 rotational speed of x12 speed of the reproducer, Ba for medium x20 speed, and Ca for the highest speed of x24 speed. As parameters for Specification B, maximum values of tracking error signal amplitude that correspond to separate allowable-limit vibration values are burned in with 2-byte numerals Ab, Bb, Cc in the same manner as above.

15 On the other hand, as individual disc reproducers have performance dispersion in the manufacturing process, the maximum value of tracking error that corresponds to each of the standard threshold level parameters at respective rotational speed varies and is measured in a reproducer of Specification A, for example, to be  
 20 Aa', Ba', Ca'; or Ab', Bb', Cb' in the case of Specification B. Table 1 shows an example. In order that a disc reproducer can surely detect a vibrating disc and detect the allowable maximum reproduction speed of the disc reproducer, in the event the maximum value of TE signal voltage that corresponds to the standard threshold level parameter  
 25 is different, rewriting of the EEPROM data is carried out using the maximum value of the TE signal voltage as the threshold level.

By way of concrete examples, in Table 1, suppose that the designed central TE signal voltage, Ca, of a disc-shape storage medium reproducer based on Specification A at x24 speed is Ca = 1.50 volt.  
 30 If the TE signal voltage obtained by mounting an allowable-limit disc Dc on a reproducer being manufactured is 1.60 volt, rewriting of the threshold level is not necessary.

Table 1.

| Disc<br>rotational<br>speed | Spec A reproducer                      |                               | Spec B reproducer                      |                               |
|-----------------------------|----------------------------------------|-------------------------------|----------------------------------------|-------------------------------|
|                             | Std<br>threshold<br>level<br>parameter | Measured<br>tracking<br>error | Std<br>threshold<br>level<br>parameter | Measured<br>tracking<br>error |
| X12 speed                   | Aa                                     | Aa'                           | Ab                                     | Ab'                           |
| X20 speed                   | Ba                                     | Ba'                           | Bb                                     | Bb'                           |
| X24 speed                   | Ca                                     | Ca'                           | Cb                                     | Cb'                           |

The reason is because, as the TE signal voltage is greater than the threshold level, a disc having a vibration value greater than that of the allowable-limit disc will be reproduced at a lowered speed thus vibration will not increase.

However, when the TE voltage is 1.45 volt, there may occur a case where the TE signal voltage is 1.50 volt or smaller even when a disc with a larger vibration value than the allowable-limit disc is mounted and reproduced. In such a case, unless the threshold level is rewritten, vibration will increase. By rewriting the threshold level, reproduction at the maximum speed is enabled as close to the allowable vibration limit as possible, and data read-out at a high speed is enabled. When the threshold level is set at 1.20 volt, for example, TE signal voltage of majority of discs will be 1.20 volt or greater, and there will be little possibility of being able to read out data at the maximum speed.

Next, when the vibration value data of an allowable-limit disc Dc at x20 speed is Ba', judgment is made on the standard threshold level Ba in the same manner.

By correcting dispersions of individual disc reproducers in the manner described above, an accurate discrimination as to whether or not vibration value of a disc in general with an unknown mass eccentricity is within the allowable limit is enabled.

When the change mode is "Yes" under this condition, microprocessor 18M captures the vibration value that is measured to be the maximum value of the TE signal, and changes standard value data Ca burned in EEPROM 51 to threshold level Ca' that is peculiar

to the reproducer in question thus accomplishing vibration detection threshold level changing process. Subsequently, when the vibration value data of the allowable limit disc Dc at x20 speed is Ba' and the change mode is "Yes", a process is carried out to change the standard data Ba to peculiar threshold level Ba' in the same way. Subsequently, if the vibration value data of an allowable-limit disc Db at x12 speed is Aa' and the change mode is "Yes", a process is carried out in the same way to change the standard data Aa to threshold level Aa' that is peculiar to the reproducer in question.

Further examples of above method of increasing detection accuracy by increasing the number of vibration detection and judgment will be described below.

When data reproduction speeds of a data reproducer are x10 speed, x20 speed, x30 speed, and x40 speed, by setting vibration detecting speeds as shown in Table 2 and increasing the number of vibration judgment, the maximum reproduction speed of a disc with further smaller vibration value (0.3 gram-cm, for example) can be judged with high accuracy. Furthermore, by providing two threshold levels Ac1, Ac2 for vibration detection, it becomes possible to prevent possibility of a disc with a large vibration value (1 gram-cm, for example) to vibrate to an extent discernible by a user even at x20 speed, and to prevent abandoning of a situation in which little vibration occurs at x20 speed with a disc having a small vibration value (0.3 gram-cm, for example), namely, abandoning of possibility of reproduction at a higher speed.

Table 2.

|           | Specification A |                | Specification C |                |                                  |
|-----------|-----------------|----------------|-----------------|----------------|----------------------------------|
|           | Threshold level | Measured value | Threshold level | Measured value | Estimated threshold level change |
| X12 speed | Aa              | As'            | Ac1             | Ac'            | Ac'                              |
|           |                 |                | Ac2             |                | Ac'+ $\alpha$ 1                  |
| X20 speed | Ba              | Ba'            | Bc1             | Bc'            | Bc'                              |
|           |                 |                | Bc2             |                | Bc'+ $\alpha$ 2                  |
| X24 speed | Ca              | Ca'            | Cc1             | Cc'            | Cc'                              |
|           |                 |                | Cc2             |                | Cc'+ $\alpha$ 3                  |

In summary, reduction in system functionality due to reproduction of a disc with a small vibration value at a low speed can be lessened by reproducing a disc with a large vibration value  
 5 (Ac' > Ac2) at a low speed, and reproducing a disc with a small vibration value (Ac1 < Ac' < Ac2) at a medium speed.

Here, the estimated threshold level change is a change of the value that is judged to be needed when the measured value is for a standard disc, and  $\alpha_1$ ,  $\alpha_2$ ,  $\alpha_3$  are values for correction equal to the  
 10 distance between two threshold levels.

A further detailed description will now be given below in reference to Fig. 9. Fig. 9 shows relationship between speed of vibration detection and vibration value produced. Curves A, B, C, D, E represent speed vs. vibration value characteristic for each of  
 15 standard discs that generates allowable-limit vibration value at the speed of vibration detection. As shown in the figure, threshold levels can be set as threshold levels Ac1/Ac2 for x12 speed, threshold levels Bc1/Bc2 for x20 speed, threshold levels Cc1/Cc2 for x24 speed, ..., and threshold levels Ec1/Ec2 for x40 speed.

20 These cases include cases where the data reproduction speed and vibration detecting speed are different. For example, when vibration detection of a disc with an unknown vibration value is started, vibration is detected at x12 speed that is the lowest of the vibration detecting speeds. If vibration value Ac' satisfies  
 25 Ac' > Ac2, the disc is judged to be a vibrating disc, and the data reproduction speed is determined to be x10 speed. If Ac1 < Ac' < Ac2, x10 speed is determined to be the data reproduction speed as this speed is not a data reproduction speed.

If Ac' < Ac1, judgment is made that data reproduction at a higher  
 30 speed is possible, and vibration measurement is carried out by increasing the reproduction speed to x20 speed which is the next vibration detecting speed. The relationship between threshold levels Bc1, Bc2 at this speed and the obtained vibration value Bc' is then judged. This case being data reproduction speed, the maximum

data reproduction speed will be x10 speed if  $Bc' > Bc2$  and x20 speed if  $Bc1 < Bc' < Bc2$ . Also, if  $Bc' < Bc1$ , judgment is made that maximum data reproduction speed for data reproduction exists on even higher speed side, vibration detection is carried out by increasing the reproduction speed to x24 speed, and the relationship with threshold levels  $Cc1, Cc2$  is judged. When maximum speed of x40 speed is reached by successively repeating this process, detected vibration value  $Ec'$  (of a disc with a small vibration value) is compared with threshold level  $Ec1$  ( $\sim Ec2$ ) and judged in the same manner as above.

As x40 speed is the maximum speed for data reproduction in this case, if  $Ec' < Ec1$ , then  $Ec1 < Ec1' < Ec2$ , and x40 speed is judged to be the maximum data reproduction speed. If  $Ec' > Ec2$ , then x30 speed is judged to be the maximum data reproduction speed and vibration detection is completed.

Next, EEPROM 51 for storing threshold levels will be discussed. One possible embodiment is to incorporate EEPROM 51 in the so-called IC card 151 so that IC card 151 can be inserted into slot 150 provided on a housing of a disc reproducer 2 as illustrated in Fig. 7. In this case, as a different threshold level is stored in EEPROM 51 for each different specification, it gives convenience in manufacturing mixed models on a single production line. The same advantage may be obtained by providing slot 152 for the IC card on a housing of host computer 1. In this case, needless to say, threshold level and vibration value are compared after reproducer 2 has been inserted into reproducer slot 122 of host computer 1, threshold level is set based on the measured result, and reproducer 2 is kept inserted in host computer 1 once setting has been made. In Fig. 7, numeral 121 is a slot for a floppy disc and numeral 123 is a display of host computer 1.

As has been described above, the present exemplary embodiment has the following advantages.

- (1) As the amount of eccentricity is measured and rotational speed of disc 4 is determined prior to data reproduction, occurrence of a data

read-out error due to a tracking error that occurs after start of data reproduction can be avoided, and overall reduction in data reproduction speed can be avoided. Even if reproduction is made at the maximum speed (first speed) from the beginning, if an error occurs, the time required for reproduction will become long in the end due to retrials and the like. Conversely, in this exemplary embodiment, the maximum speed at which stable data reproduction is possible can always be determined at below the vibration value that is acceptable by a reproducer by carrying out detection of vibration value on the low speed side using a plurality of threshold levels that have been set. As a result, data reproduction is enabled without giving unpleasant feeling to a user, occurrence of error is reduced, and required reproduction time is made shorter than when an error is occurring.

(2) In this exemplary embodiment, a description is made on detection of vibration of a reproducer due to a disc with mass eccentricity as the amount of eccentricity of a track in terms of a tracking servo error signal. However, similar concept can be applied to a system in which vibration is detected in the form of a signal that crosses the track obtained by making the tracking servo system open. It is also applicable to a system in which vibration of a reproducer is detected with an acceleration sensor.

(3) The advantages of (1) and (2) above also apply to a recording device of a recordable disc-shape storage medium in which allowable vibration of the device is severer, and further enhanced advantage will be exhibited.

(4) In the case of a low quality disc, as rotational speed is not made high, vibration of disc 4 and a disc reproducer as a whole is suppressed, and influence of vibration on other devices (such as HDD) is lessened. Also, as vibration is reduced, unpleasant feeling to a user is reduced.

**Industrial Applicability:**

- By setting an amount of allowable vibration of a disc-shape storage medium reproducer-recorder by using a disc having a known
- 5 mass eccentricity, data reproduction is enabled by rotating a disc at the maximum speed that can be set while keeping the vibration value produced within an allowable limit when discs with different mass eccentricity are reproduced or recorded.



### Claims

1. A disc-shape storage medium reproducer comprising:

disc rotating means for rotating a storage medium disc having data recorded on a spiral or concentric tracks and having a center  
5 hole, said disc rotating means including a spindle to be inserted into said center hole, and being formed in a manner such that said disc can be detachably inserted and that the rotational speed can be varied;

a signal converter for reading out said data from said disc;  
10 moving means for moving said signal converter in radial direction of said disc; wherein

values relating to vibration values that are measured with vibration value measuring means by mounting a disc (allowable-limit disc) with a known mass eccentricity into said reproducer and rotating  
15 said allowable-limit disc are stored in storage means inside said reproducer as a threshold level that indicates the allowable limit.

2. A disc-shape storage medium reproducer comprising comparing means for  
comparing a value related to vibration value as obtained by rotating  
20 an allowable-limit disc and a threshold level stored in advance in a reproducer and judging means for judging whether or not said obtained vibration value is within an allowable range, wherein, when a result of judgment is obtained that the value relating to said vibration value is not within the allowable range, numerical data  
25 that indicates the allowable range as stored in a memory device for storing said allowable range is revised.

3. The disc-shape storage medium reproducer of claim 1, wherein stored  
content of said storage medium disc is rewritable.

30 4. The disc-shape storage medium reproducer of claim 1, wherein reading out and rewriting of the content of said storage medium disc are possible.

5. The disc-shape storage medium reproducer of claim 1, wherein a storage medium disc is mounted on a disc-shape storage medium



reproducer comprising rotation control means which is settable to n kinds of data reproducing speeds and at least n kinds of vibration detecting speeds including said reproducing speeds, the vibration value of said disc is measured by rotating said disc at a vibration  
5 detecting speed lower than the maximum reproducing speed, and the maximum reproducing speed at which data is reproducible is determined based on judgment on at least n pieces of threshold levels that have been set based on the allowable-limit vibration value that is preset in said reproducer.

10 6. The disc-shape storage medium reproducer of claim 1, wherein a plurality of threshold levels corresponding to a plurality of allowable-limit discs is stored in a nonvolatile memory.

7. The disc-shape storage medium reproducer of claim 1, wherein a nonvolatile memory storing threshold levels is incorporated in an  
15 IC card (memory card) and said memory card is detachable from outside said reproducer.

8. The disc-shape storage medium reproducer of claim 2, wherein the stored content of said storage medium disc is rewritable.

9. The disc-shape storage medium reproducer of claim 2, wherein  
20 reading out and rewriting of the stored content of said storage medium disc are possible.

10. The disc-shape storage medium reproducer of claim 2, wherein a storage medium disc is mounted on a disc-shape storage medium reproducer comprising rotation control means which is settable  
25 to n kinds of data reproducing speeds and at least n kinds of vibration detecting speeds including said reproducing speeds, the vibration value of said disc is measured by rotating said disc at a vibration detecting speed lower than the maximum reproducing speed, and the maximum reproducing speed at which data is reproducible is determined  
30 based on judgment on at least n pieces of threshold levels that have been set based on the allowable-limit vibration value preset in said reproducer.

11. The disc-shape storage medium reproducer of claim 2, wherein a plurality of threshold levels corresponding to a plurality



of allowable-limit discs is stored in a nonvolatile memory.

12. The disc-shape storage medium reproducer of claim 2, wherein a nonvolatile memory for storing threshold levels is incorporated in an IC card (memory card) and said memory card is detachable from outside said reproducer.

13. The disc-shape storage medium reproducer of claim 3, wherein a storage medium disc is mounted on a disc-shape storage medium reproducer comprising rotation control means which is settable to n kinds of data reproducing speeds and at least n kinds of vibration detecting speeds including said reproducing speeds, the vibration value of said disc is measured by rotating said disc at a vibration detecting speed lower than the maximum reproducing speed, and the maximum reproducing speed at which data is reproducible is determined based on judgment on at least n pieces of threshold levels that have been set based on the allowable-limit vibration value that is preset in said reproducer.

14. The disc-shape storage medium reproducer of claim 3, wherein a plurality of threshold levels corresponding to a plurality of allowable-limit discs is stored in a nonvolatile memory.

15. The disc-shape storage medium reproducer of claim 3, wherein a nonvolatile memory for storing threshold levels is incorporated in an IC card (memory card) and said memory card is detachable from outside said reproducer.

16. The disc-shape storage medium reproducer of claim 4, wherein a storage medium disc is mounted on a disc-shape storage medium reproducer comprising rotation control means which is settable to n kinds of data reproducing speeds and at least n kinds of vibration detecting speeds including said reproducing speeds, the vibration value of said disc is measured by rotating said disc at a vibration detecting speed lower than the maximum reproducing speed, and the maximum reproducing speed at which data is reproducible is determined based on judgment on at least n pieces of threshold levels that have been set based on the allowable-limit vibration value that is preset in said reproducer.



17. The disc-shape storage medium reproducer of claim 4, wherein a plurality of threshold levels corresponding to a plurality of allowable-limit discs is stored in a nonvolatile memory.

5 18. The disc-shape storage medium reproducer of claim 4, wherein a nonvolatile memory for storing threshold levels is incorporated in an IC card (memory card) and said memory card is detachable from outside said reproducer.

10 19. The disc-shape storage medium reproducer of claim 5, wherein a plurality of threshold levels corresponding to a plurality of allowable-limit discs is stored in a nonvolatile memory.

20. The disc-shape storage medium reproducer of claim 5, wherein a nonvolatile memory for storing threshold levels is incorporated in an IC card (memory card) and said memory card is detachable from outside said reproducer.

15 21. The disc-shape storage medium reproducer of claim 5, wherein a plurality of threshold levels corresponding to a plurality of allowable-limit discs is stored in a nonvolatile memory.