

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 .June 2006 (29.06.2006)

(10) International Publication Number
WO 2006/067919 A3

(51) International Patent Classification:
H01M 2/10 (2006.01) *H01M 2/02* (2006.01)

(74) **Agent:** NAKAMURA, Tomoyuki; c/o Miyoshi International Patent Office, Toranomom Kotohira Tower, 2-8, Toranomom 1-chome, Minato-ku, Tokyo, 1050001 (JP).

(21) International Application Number:
PCT/JP2005/020683

(22) International Filing Date: 4 November 2005 (04.11.2005)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) Priority Data:
2004-367325 20 December 2004 (20.12.2004) JP

(71) **Applicant** (for all designated States except US): **SONY CORPORATION** [JP/JP]; 7-35, Kitashinagawa 6-chome, Shinagawa-ku, Tokyo, 1410001 (JP).

(72) Inventors; and


(75) **Inventors/Applicants (for US only):** TAKAHASHI, Atsushi. TAKESHITA, Toshio. KAMIYA, Hideki. MIYAJIMA, Yoichi.

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: BATTERY CASE



(57) Abstract: The present invention provides a battery including a case and a battery cell accommodated in the case. The case is divided in a thicknesswise direction of the battery cell into an upper case (12) and a lower case (14). The cases have joint portions (1201, 1401) formed along peripheries thereof for jointing with each other. The joint portion of the lower case (14) has a joining thin wall formed to extend along a periphery thereof and project in the thicknesswise direction. The joint portion of the upper case (12) has a joining recess formed to extend along a periphery thereof for receiving the joining thin wall inserted therein. The joining thin wall and the joining recess in which the joining thin wall is inserted are joined together by welding. The upper case (12) has a projecting wall (1002) formed at a location of an outer face thereof positioned on the outer side of the joining recess in such a manner as to extend along the joining recess.



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
15 February 2007

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.