CLAIMS:

1. An elevator equipped with an electronic safety system, comprising:

a safety controller (40) having a first processing device(50) and a second processing device (60) to check for an abnormal condition based on input information from sensors monitoring an operation state of an elevator car (1) and to produce a command signal to bring the elevator car to a safe state;

wherein each of the first processing device (50) and the second processing device (60) includes:

an elevator-at-rest check unit (86A, 86B) to decide if the elevator car (1) is at rest;

a diagnostic input information storage unit (87A, 87B) to store in advance a diagnostic input information to simulate an output of the sensors in an operation status in which the elevator car should be stopped;

an input selection unit (85A, 85B) to output the sensor input information when the elevator car is operating normally and, when the elevator-at-rest check units (86A, 86B) decide that the elevator car is at rest, output the diagnostic input information;

a processing unit (81A, 81B) to check an anomaly of the elevator car based on the output information from the input selection units (85A, 85B) and to output a stop signal which stops the elevator; and

a comparison unit (84A, 84B) to compare an output from the first processing device (50) with an output from the second processing device (60);

wherein when the elevator-at-rest check units (86A, 86B) decide that the elevator car is at rest each of the processing devices (50, 60) outputs the stop signal by calculation using the diagnostic input information, if the comparison units (84A, 84B) decide that outputs from the first processing device (50) and the second processing device (60) disagree as a stop signal the elevator car (1) is stopped and if the outputs agree as a stop signal it is diagnosed that the safety controller (40) is working normally.

2. An elevator equipped with an electronic safety system according to claim 1, wherein the sensors include an encoder (21) for detecting a speed and a position of the elevator car (1) and an elevator car door switch (25) mounted on the elevator car (1) for detecting an open/close state of the door;

wherein, when a state in which the elevator car door (1) is closed and the speed of the elevator car (1) is zero persists for a predetermined time, it is decided that the elevator car is at rest.

3. An elevator equipped with an electronic safety system according to claim 1, wherein the sensors are a car interior monitoring camera (26) for checking the presence or absence of passengers inside the car or a car weight sensor (27);

wherein, when a state in which there are no passengers in the elevator car (1) persists for a predetermined time, it is decided that the elevator car is at rest.

CLAIMS:

1. An elevator equipped with an electronic safety system, comprising:

a safety controller (40) having a first processing device(50) and a second processing device (60) to check for an abnormal condition based on input information from sensors monitoring an operation state of an elevator car (1) and to produce a command signal to bring the elevator car to a safe state;

wherein each of the first processing device (50) and the second processing device (60) includes:

an elevator-at-rest check unit (86A, 86B) to decide if the elevator car (1) is at rest;

a diagnostic input information storage unit (87A, 87B) to store in advance a diagnostic input information to simulate an output of the sensors in an operation status in which the elevator car should be stopped;

an input selection unit (85A, 85B) to output the sensor input information when the elevator car is operating normally and, when the elevator-at-rest check units (86A, 86B) decide that the elevator car is at rest, output the diagnostic input information;

a processing unit (81A, 81B) to check an anomaly of the elevator car based on the output information from the input selection units (85A, 85B) and to output a stop signal which stops the elevator; and

a comparison unit (84A, 84B) to compare an output from the first processing device (50) with an output from the second processing device (60);

wherein when the elevator-at-rest check units (86A, 86B) decide that the elevator car is at rest each of the processing devices (50, 60) outputs the stop signal by calculation using the diagnostic input information, if the comparison units (84A,84B) decide that outputs from the first processing device (50) and the second processing device (60) disagree as a stop signal the elevator car (1) is stopped and if the outputs agree as a stop signal it is diagnosed that the safety controller (40) is working normally.

2. An elevator equipped with an electronic safety system according to claim 1, wherein the sensors include an encoder (21) for detecting a speed and a position of the elevator car (1) and an elevator car door switch (25) mounted on the elevator car (1) for detecting an open/close state of the door;

wherein, when a state in which the elevator car door is closed and the speed of the elevator car (1) is zero persists for a predetermined time, it is decided that the elevator car is at rest.

3. An elevator equipped with an electronic safety system according to claim 1, wherein the sensors are a car interior monitoring camera (26) for checking the presence or absence of passengers inside the car or a car weight sensor (27);

wherein, when a state in which there are no passengers in the elevator car (1) persists for a predetermined time, it is decided that the elevator car is at rest.