

12/11/04
This Sheet Has Been Replaced



HP Docket 190504

1 -

REPLACED SHEETS SG

☒ Description : paged/ to paged¹⁵
☒ Claim(s) : paged/ to paged⁹
☒ Drawing(s) : paged/ to paged⁸
☐ Abstract : paged to paged

METHOD AND APPARATUS FOR SOLVING MULTIPLE EQUATIONS

BACKGROUND OF THE INVENTION

This invention generally relates to method and apparatus for assisting a user in the process of solving multiple equations sharing common variables. More particularly, this invention relates to a method for representing to a user the state of variables in multiple equations to be solved.

The ability to solve an equation for an unknown is a powerful tool of newer computing devices such as calculators and computers. When such a tool is applied to an actual problem, the problem is often best represented as a set of multiple equations. For simple problems with few equations and variables, a user chooses one equation, puts in values that he knows and solves for an unknown. He then use the result of the first equation to solve for an unknown in a second equation and so forth. Ultimately this solution process leads to a value for a particular variable of interest.

For more complex problems, however, the number of equations and variables to be determined is large and the solution process becomes tedious. The user must keep track in each step for each variable whether it is known, unknown, or calculated. It also becomes difficult to select the proper equation in sequence to lead to a value for the desired variable. And once the solution is complete, it is difficult to identify which variables have related values and which do not.

Prior attempts to solve the difficulties of equation selection, variable tracking and variable identification have largely been manual in nature. Some have employed numerical root finders for the actual solving operation for each equation. Others have employed calculator or computer-based methods that automate the select-and-solve portion. But none of these prior attempts has provided a user with a visual indication of the state of a variable and its relationship to the other

2-403103



variables in the set of equations after solution of the equation.

SUMMARY OF THE INVENTION

5 An object of the invention, therefore, is to provide a method and apparatus for solving multiple equations which overcome the drawbacks of prior approaches.

10 A second object of the invention is to create a user interface that allows a user to easily enter known variables and solve for unknown variables.

 A third object of the invention is to provide a visual indication to a user of the relationship among variables in multiple equations.

15 In accordance with these objects, a method of representing to a user the state of variables in multiple equations is disclosed. In the method, each of the multiple equations is scanned to find the variables in the equations. Each variable is then assigned a data entry
20 point such as a key on a keyboard. A label for each variable is then displayed, and indicated on the label is the state of its variable. In the present embodiment, the state of a variable represented by a label is indicated by the color and pattern of the label.

25 In accordance with the invention, the order in which the variables are found and in which the equations are solved is determined. This information allows the user to review the solution path followed in solving the multiple equations.

30

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a pictorial view of a calculator as one embodiment of apparatus programmed according to the invention.

35 FIG. 2 is a block diagram of the architecture of the calculator of FIG. 1.

 FIG. 3 is a series of screen displays illustrating a user interface according to the invention.

FIGS. 4A-B are portions of a flowchart illustrating the overall method of solving for variables in multiple equations in accordance with the invention.

FIG. 5 is a flowchart of a method for determining
5 if an equation within the multiple equations at a given point may be solved.

FIG. 6 is a flowchart of a method for solving an equation within the multiple equations.

FIG. 7 is a flowchart of a method for displaying
10 to a user the state of each variable within the multiple equations.

FIGS. 8A-D illustrate how variables and equations are stored in memory according to the invention.

15 BRIEF DESCRIPTION OF A PREFERRED EMBODIMENT

The Apparatus

FIG. 1 shows a calculator 20 which is programmed to solve multiple equations according to the invention. The hardware and architecture of the calculator 20 (shown
20 in FIG. 2) may be of conventional design. The calculator includes an entry means such as a keyboard 22 and a display means such as an LCD display 24. On the face of the keyboard are a plurality of keys that each have a number of functions. Relevant to the present invention
25 are several of the keys that have unique functions. A LIBRARY key 26 is used for activating a multiple equation solver menu interface in a shifted operation. The shift is accomplished by first pressing the left shift key 28. Other keys of note include a right shift key 30, a NXT key
30 32, and a row of menu keys 34. In response to activating the solver menu, the menu keys are assigned to labels 36 that appear at the bottom of display 24, as will be further described hereafter.

The architecture of calculator 20 includes a
35 central processing unit (CPU) 38 to which are connected via various buses the keyboard 22, the display 24 and memory in the form of ROM 42 and RAM 44. The instructions for operating the CPU are written and stored in the ROM 42



in a conventional manner. The RAM 44 is available for storing data entered via the keyboard 22 and generated by the CPU 38 in the process of solving multiple equations according to the invention.

5 Of course, any equivalent calculating device may be used, such as a general purpose computer. Equivalent to the keyboard would be any data entry device such as a mouse. Equivalent to the LCD display would be any type of display device such as a CRT, hard copy device, etc.

10

The Multiple Equation Solver

The method of the present invention solves multiple equations for one or more variables and indicates to the user the state of the variables in the equations
15 after each solution. These states are four: user-supplied values (U); machine-supplied values (C); related values (R); and non-related values (N). Related values are values that were used or found together in the latest solution of an equation. To assist a user in identifying
20 the states of different values, a user interface as shown in FIG. 3 is provided.

FIG. 3 is a series of screen displays illustrating the user interface as it appears on the display 24. The top screen display shows a list of two
25 equations to be solved, VCONE and LCONE. The equations on the list may either come from a library of standard equations or be entered by the user separately. The next screen display shows the entry of two user supplied values, five for the variable R and twelve for the
30 variable L. These variables are considered "known." At the bottom of the display 24, a row of labels 36 then appears, one label for each variable in the multiple equations. If more variables existed than could be shown in a single row, additional rows are created and can be
35 brought into display by pressing the NXT key 32. The labels are assigned to menu keys 34 for selecting which variables are to be found in solving the equations. The background color of the label indicates the source (state)

of the value of the associated variable. A black background, as for labels L and R, indicates that the value is user-supplied. A white background, as for labels V and H, indicates that the value is or will be machine
5 (calculator) supplied. These variables are considered "unknown" until a value is calculated for each. The last label in the row is ALL and is selected for finding all the unknown variables. Thus in this example the user has the option of finding the values of H or V individually by
10 pressing the assigned menu key or as a group by pressing the key 34 assigned to ALL.

The third screen display shows additional indicators on the labels 36 for indicating whether the values of the variables are related through the solving of
15 the equations. That is, the indicators, which appear as black or white boxes within each label, indicate whether the variable was involved in the latest solution of the equations. Black boxes in a white label indicate the variable was calculated. White boxes in a black label
20 indicate the variable was used. If a variable label does not have a black box in the third screen display, then the variable's value was not recently calculated or played no role in solving the equations. For example, if it is desirable to find only the value of the variable H, this
25 can be done by employing only the equation LCONE. The variable V is not involved, and its label would not include a box after the computation. This tells the user that the value of V is not related to the values of the other variables.

30 The last screen display shows the values found for each variable. L and R were user supplied and thus are considered known. V and H were solved for using the supplied values for L and R and the two equations LCONE and VCONE. Table I, below, summarizes the key action,
35 label appearance and effect on variable state for the interface:





Variable State/ Key Definition	Appearance/Action	State Abbrev.
User-supplied values	Black key label	U
Calculator-supplied values	White (outline) key label	C
Related values	Block in menukey label	R
Non-related values	No block in menukey label	N
menukey action	Store value in var	
left-shift menukey action	Solve for var	
right-shift menukey action	Recall var	
Blank memkeys	White (outline) keys	
ALL key	Sets all keys to CN	
left ALL	Starts entire solution	
right ALL	Shows review of solution	

Table I

The method of the present invention of representing to a user the state of a variable in multiple equations to be solved in particularly described in the pseudocode that appears in Appendix I. A more general description of the method is illustrated in the flowcharts of FIGS. 4-7, which will now be described. Each step of the method as it appears in a flowchart is indicated herein by an identifying numeral in parentheses.

FIGS. 4A-B are portions of a flowchart illustrating the overall method for solving for variables in multiple equations. The beginning of the flowchart corresponds to the second screen display of FIG. 3, wherein the user supplied variables have been entered (50). The user first decides whether a specific variable or all of the variables is to be found (52). If only a specific variable (such as V in FIG. 3) is the object, then that variable is deleted from the found_name_list (if it were on it), because its value is to be found regardless of whether the user supplied a value (54). The equations are then checked to see if there are any known variables (56), and if not, an error signaling that there are too many unknown variables is displayed (58). Following is a check to see if there are any unknown variables (60), and if not, another error signaling that there are no unknown variables to be found is displayed



(64). Assuming no error signal, the method checks again if it is solving for all unknown variables (66).

For the case where only a specific variable is to be found, the method scans the list of multiple equations
5 for an equation containing only the desired unknown, such as V (68). If such an equation is found to exist (70), the equation is solved (72). The result for the variable is then stored and displayed (74) and the menu of FIG. 3 indicating the state of each variable in the multiple
10 equations is displayed (76). The process for solving an equation is illustrated in FIG. 6 and the process of displaying the menu is illustrated in FIG. 7, both of which are described hereafter.

If no equation is found that contains only the
15 desired unknown (68), then the method proceeds as though all variables are to be found, as shown at the bottom of FIG. 4A, which continues onto FIG. 4B. A counter i is then initialized for solving each of the equations on the list (78). The first equation is retrieved (80) and
20 examined to determine if it is solvable (82). FIG. 5 illustrates the process for determining if the ith equation is presently solvable and is described hereafter. If the equation is solvable, then it is solved (84). With the equation solved, the method checks if all unknown
25 variables are to be solved for (86). If not, it is then determined if the variables to be found have all been found (88). If so, then the variables are stored and displayed (90) and the menu indicating the state of each variable is also displayed (92). If there are other
30 variable to be found at step (88), then the found variable is added to list of variables than need not be found (94), the i counter is incremented (96) and the next equation is retrieved from the equation list (80).

Returning to step (86), if all unknown variables
35 are to be solved for, the method checks if the present variable is the last unknown (98). If so, then the solutions are complete and the menu is displayed (92). If there are other unknown variables still present, however,



then the method checks if the i th equation is the last equation on the list (100). If not, then the variable is added to the list of variables that have been found (94). If, on the other hand, this is the last equation on the

5 list, then the method inquires whether any variables were found on this pass through the i loop (102). If yes, then the i counter is reinitialized and the process repeats (78). If no variables are found on this pass, then the method determines if it is solving for a single variable

10 or if no variables were found at all when solving for all variables (104). If so, then there are still too many unknown variables (106), and the error is signaled to the user. If not, then all variables have been found that can be found, and the menu indicating the state of each

15 variable is displayed (108).

Referring now to FIG. 5, determining whether the i th equation is solvable begins by initializing a counter j for the variables in the equation (110). The variable is then examined to determine if it needs to be found,

20 i.e., if it is an unknown (112). If it is, the i th equation is examined to determine if there are other unknown variables present in the equation (114). If that is the case, then the i th equation presently is not solvable (116), answering the question in the negative

25 posed in step (82). If the i th equation has only the one unknown (114) to this point, then it must be determined if the j th variable in the i th equation is the last to be examined (118). If so, then the i th equation is deemed solvable (120), answering the question in the affirmative

30 posed in step (82). If the variable is not the last in the i th equation, then the counter j is incremented (122) to the next variable and step (112) is again undertaken. If the j th variable need not be found, because it may have been user-supplied or not requested, then the method

35 branches to step (118) and proceeds as described above.

The step of solving an equation which appears in FIG. 4A as step (72) and in FIG. 4B as step (84) is shown in detail in FIG. 6. Any preexisting relationship among



the variables in the equation being solved is first cleared (130,132). Such a relationship may have existed from an earlier solution where the value of one variable was determined from values of one or more others. A root
5 finder algorithm is then utilized to find a value for the unknown variable (134). Such algorithms are well known in the art, such as described in U.S. Pat. No. 4,845,652, which is hereby incorporated by reference. The state of the unknown variable is then set to "calculator supplied"
10 and "solved for" (CR) in the present equation (136). The states of the other variables in the equation are then set to "used in the solution" (UR) (138). This completes the equation solving step, and the overall method proceeds therefrom.

15 The step of displaying the variable menu, which appears in FIGS. 4A and 4B, is shown in detail in FIG. 7. The variable counter k is first initialized (140) and the state of the first variable is examined to determine if it is "user-supplied" (142). If so, then the kth variable is
20 examined to determine if it was used in the solution of the equation(s) (144). If the variable was used in the solution, then a black label with a white block (indicating that state) is displayed above the menu key 34 assigned to the label (146). If it was not used in the
25 solution but was user-supplied, a black label (indicating that state) is displayed above the menu key 34 assigned to the variable represented by the label (148). In either case, the process then checks if there are other variables in the equations to be displayed (150) and, if so,
30 increments the variable counter k (152).

Returning to step (142), if the variable is not "user-supplied," then it is examined to determine if it was "solved for" in the solution to the equation (154). If not, then the variable was not involved in the solution
35 process. This may occur where the user has sought to find only specific variables rather than all of those present in the list of equations. In this case, a white label (indicating that state) is displayed above the menu key 34



assigned to the variable represented by the label (156).
If, on the other hand, the variable was "solved for," then
a white label with a black block (indicating that state)
is displayed above the menu key 34 assigned to the
5 variable represented by the label (158).

FIGS. 8A-D illustrate functionally how the
variables and equations are stored within the calculating
device. In FIG. 8A, each variable is stored with its
value, name, and state, with the variables shown in FIG. 3
10 entered for example. These states, as mentioned above,
are four: user-supplied values (U); calculator-supplied
values (C); related values (R); and non-related values
(N). The first column under "user-supplied" is for
indicating whether the variable was user supplied. The
15 second column is for indicating whether the user-supplied
variable was used in the last solution to the equations.
The first column under "calculator supplied" is for
indicating if the value was calculator or machine
supplied. The second column is for indicating whether the
20 calculator supplied variable was solved for in the last
solution to the equations. The actual representation of
this information in memory, of course, may be quite
different from the illustration.

FIGS. 8B and 8D illustrate how the orders of
25 solution of the variables and equations are saved in
memory for later examination by a user. The values found
for unknown variables may differ, depending on the order
in which the root finder solves equations. As part of the
method for solving the multiple equations herein, the
30 orders in which the variables are found and equations
solved are saved and may be recalled by the user through
appropriate commands to the calculating device. The order
shown is chronological, though other orders may be used as
well. This information on orders of solution allows a
35 user to determine the path taken by the multiple equation
solver in solving the equations.

FIG. 8C illustrates a register within the
calculating device for tracking the i th equation and j th

variable as part of the method herein. Each equation and variable is stored in its order of solution, as shown in FIGS. 8B and 8D.

5 Having illustrated and described the principles of the invention in a preferred embodiment, it should be apparent to those skilled in the art that the invention can be modified in arrangement and detail without departing from such principles. We claim all
10 modifications coming within the spirit and scope of the following claims.

This Sheet Has Been Replaced



APPENDIX I

*Solution Procedure

*Nomenclature:

var_list is the list of all variable names for the eqn system
 user-supplied_list is the list of variable names with U status
 var_to_find is the var to be found by a single-var solution
 found_name_list is the list of variable names that have been found by the MES
 unknown-var is the name of the single unknown in a solvable eqn
 newly_found_value is the result of calculating unknown_var
 number_of_eqns is number of eqns
 number_of_eqn_vars is the number of vars in the eqn being examined for solvability
 total_newly_found is the total number of variables calculated in the eqn system
 newly_found_this_pass is the number of values calculated during this pass of the solution
 solution indicates a single-var solution or an all-vars solution
 R->N_done indicates if all the R states were made into N states

```

if left-shift ALL pressed
then solution = all
else solution = single
endif
if solution = all
then found_name_list = user-supplied_list
else found_name_list = user-supplied_list - var_to_find
endif
number_found = length(found_name_list)
if number_found = 0
then
  display "Too Many Unknowns"
  display_menu and quit
endif
number_vars = length(var_list)
if number_found = number_vars
then
  display "All Variables Known"
  display_menu and quit
endif

if solution = single
then
  number_found = 0
  for i=1 to number_of_eqns
    get eqn(i)
  
```

This Sheet Has Been Replaced



```

    if eqn(i) solvable          (determines unknown_var)
    then
        if unknown_var = var_to_find
        then
            solve_eqn(eqn(i), unknown_var)
            store and display newly_found_value
            number_found = 1
            display_menu and quit
        endif
    endif
next i
if number_found = 1
then display_menu and quit
endif
endif

number_found = length(found_name_list)
newly_found_this_pass = 1
total_newly_found = 0

while newly_found_this_pass > 0
    newly_found_this_pass = 0
    for i=1 to number_of_eqns
        get eqn(i)
        if eqn(i) solvable          (determines unknown_var)
        then
            solve_eqn(eqn(i), unknown_var)
            if solution = single and unknown_var = var_to_find
            then
                store and display newly_found_value
                display_menu and quit
            endif
            number_found = number_found + 1
            if number_found = number_vars
            then display_menu and quit
            endif
            found_name_list = found_name_list + unknown_var
            total_newly_found = total_newly_found + 1
            newly_found_this_pass = newly_found_this_pass + 1
        endif
    next i
endwhile

if solution = single or total_newly_found = 0
then
    display "Too Many Unknowns"
    display_menu and quit
endif

```

*Additional Details

```
if eqn(i) solvable
```

*This determines if the equation is solvable (has only one
*unknown)

This Sheet Has Been Replaced



```

solvable = TRUE
number_of_unknowns = 0
for j=1 to number_of_eqn_vars
  if pos(found_name_list, var(j)) = 0
  then      (var(j) is unknown)
    number_of_unknowns = number_of_unknowns + 1
  else
    if var(j) does not exist  (var(j) is known but
erased)
    then
      number_of_unknowns = number_of_unknowns + 1
    endif
  endif
  if number_of_unknowns > 1
  then
    solvable = FALSE
  done
  endif
  unknown_var = var(j)
next j

```

```

solve_eqn(eqn(i), unknown_var)

```

*This handles prompting and state changes while solving an
 *equation for a specific variable.

```

if R->N_done = FALSE
then
  set all R -> N
  R->N_done = TRUE
endif
display "Solving for unknown_var"2
newly_found_value = solve(eqn(i), unknown_var)
set unknown_var to CR
set UN vars in eqn(i) to UR

```

```

newly_found_value = solve(eqn(i), unknown_var)

```

*This routine feeds the root finder the equation being
 solved, *and the name of the unknown variable
 (unknown_var).

*If unknown_var exists, its value should be supplied as a
 guess.

*This may be a real or unit object, or a list of 1 or 2
 reals or *unit objects.

*If unknown_var does not exist, 0 should be used as a
 guess to *the root finder.

```

display_menu

```

This Sheet Has Been Replaced



*This routine determines the appearance of the menu key labels *based on the states of the variables.

```
for k = 1 to number_vars
  get state(1)
  if state(k) = user-supplied
    then      (U means user-supplied)
      if state(k) = used in solution  (R means relationship
exists)
        then
          key label is black with white block
        else      (N means no relationship exists)
          key label is black with no block
        endif
      else      (C means calculator supplied)
        if state(k) = solved for  (R means relationship
exists)
          then
            key label is white with black block
          else      (N means no relationship exists)
            key label is white with no block
          endif
        endif
      endif
    endif
  next k
```

This Sheet Has Been Replaced





We claim:

1. In a calculating device including a display and data entry means, a method of representing to a user the state of variables in multiple equations to be solved,
5 comprising:

scanning each of the multiple equations to find variables within the equations;

assigning to each variable a data entry point for the data entry means;

- 10 displaying a label for each variable; and
indicating with each label the state of its variable.

2. The method of claim 1 wherein the indicated state of a variable includes whether the value of the
15 variable is supplied by the user.

3. The method of claim 1 wherein the indicated state of a variable includes whether the value of the variable is supplied by the calculating device.

4. The method of claim 1 wherein the indicated
20 state of a variable includes whether the value of the variable was involved in the last solution to the multiple equations.

5. The method of claim 1 wherein the indicated state of a variable includes whether the value of the
25 variable was not involved in the last solution to the multiple equations.

6. The method of claim 1 wherein the indicated state of a variable includes whether the value of a user-supplied variable was used in the last solution to the
30 multiple equations.

7. The method of claim 1 wherein the indicated state of a variable includes whether the value of a user-supplied variable was not used in the last solution to the multiple equations.

- 35 8. The method of claim 1 wherein the indicated state of a variable includes whether the value of a calculating device-supplied variable was solved for in the last solution to the multiple equations.



9. The method of claim 1 wherein the indicated state of a variable includes whether the value of a calculating device-supplied variable was not solved for in the last solution to the multiple equations.

5 10. The method of claim 1 including defining a value for a variable by selecting a value and then selecting the data entry point to which the variable is assigned, the label for the variable indicating in response that the variable value is user supplied.

10 11. The method of claim 1 wherein the data entry means comprises a keyboard and a data entry point comprises a key on the keyboard.

12. A calculating device comprising:
a display;

15 a data entry means for entering multiple equations that include variables and for entering values for the variables into the device;

means for scanning each of the entered multiple equations to find the variables within the equations;

20 means for assigning a data entry point to each variable;

means for displaying a label for each variable;

and

25 means for indicating with each label the state of its variable.

13. The calculating device of claim 12 wherein the assigning means comprises a processing means within the device programmed to assign a data entry point to each variable extracted from the multiple equations.

30 14. The calculating device of claim 12 wherein the scanning means comprises processing means within the device programmed to read the multiple equations entered into the device.

35 15. The calculating device of claim 12 wherein the displaying means comprises processing means within the device programmed to cause the display to display a row of labels adjacent to a row of data entry points to identify the variable assigned to each key.



16. The calculating device of claim 12 wherein the indicating means comprises means for indicating with each label whether the value of its variable is defined by the user.

5 17. The calculating device of claim 12 wherein the indicating means comprises means for indicating with each label whether the value of its variable was used in the last solution to the multiple equations.

10 18. The calculating device of claim 12 wherein the indicating means comprises including means for indicating with each label whether the value of its variable was solved for in the last solution to the multiple equations.

15 19. A calculating device comprising:
 (a) a display;
 (b) memory;
 (c) a plurality of keys for entering multiple equations that include variables and for entering values for the variables into the memory; and
20 (d) a processing unit for:
 scanning each of the entered multiple equations to find the variables within the equations;
 assigning a key to each variable;
 displaying a label on the display for each
25 variable in the multiple equations in proximity to the key to which the variable is assigned; and
 indicating on each label the state of is variable;

 20. In a calculating device, a method for
30 solving multiple equations having unknown variables, comprising:
 examining each of the multiple equations in the process of solving the equations for the unknown variables;
35 storing an order in which the variables are solved for; and
 storing an order in which the equations are solved;

21. The method of claim 20 including displaying at least one of the orders.

22. The method of claim 20 wherein the order of variables in the chronological order in which the values
5 for the variables are found.



This Sheet Has Been Replaced



A barcode with vertical black bars of varying widths, located below the text 'This Sheet Has Been Replaced'.

FIG. 1





FIG. 2




This Sheet Has Been Replaced



FIG. 3

CALCULATE A FRACTION FROM REAL NUMBERS






FIG. 4B





FIG. 5






FIG. 7




FIG. 8A

VALUE	NAME	USER SUPPLIED		CALCULATOR SUPPLIED	
		USED IN SOLUTION	NOT USED IN SOLUTION	SOLVED FOR	NOT SOLVED FOR
5	R	✓	✓		
12	L	✓	✓		
285.58..	V			✓	✓
10.90..	H			✓	✓

FIG. 8B

	VAR. BEING SOLVED FOR	EQUATION USING VAR
1	V	1
2	H	2
⋮		
⋮		
⋮		
j		

FIG. 8C

j

CURRENT
VARIABLE
WITHIN
EQUATION

i

CURRENT
EQUATION

FIG. 8D

EQUATIONS

1	
2	
3	
⋮	
⋮	
⋮	
i	

This Sheet Has Been Replaced



METHOD AND APPARATUS FOR SOLVING MULTIPLE EQUATIONS
ABSTRACT OF THE DISCLOSURE

In a calculating device, a method and apparatus for representing to a user the state of variables in multiple equations to be solved. The representation in the present embodiment is through a user interface. The interface displays labels assigned to the variables within the multiple equations and indicates to the user on the label the state of each variable. These states are four: user-supplied values (U); calculator-supplied values (C); related values (R); and non-related values (N). Related values (R) are values that were used or solved for together in the latest solution of the equations. Through menu keys assigned to the variables represented by the labels, a user can supply or clear values for the variables for the next solution. The method also includes saving the order in which the variables are found and the order in which the equations are solved. This information allows the user to review the solution path followed by the calculating device in solving the multiple equations.

(Fig. 1)

REPLACEMENT SHEETS	SG
☒ Description : paged .../to paged ...	
☐ Claim(s) : paged ... to paged ...	
☒ Drawing(s) : paged .../to paged ...	
☐ Abstract : paged ... to paged ...	
DATE OF RECEIPT - 7 MAY 1997	

REPLACED SHEETS	SG
☐ Description : paged ... to paged ...	
Substitute sheet 7 May 1997	
☒ Drawing(s) : paged .../to paged ...	
☐ Abstract : paged ... to paged ...	

- 1 -

METHOD AND APPARATUS FOR SOLVING MULTIPLE EQUATIONS

BACKGROUND OF THE INVENTION

This invention generally relates to method and apparatus for assisting a user in the process of solving multiple equations sharing common variables. More particularly, this invention relates to a method for representing to a user the state of variables in multiple equations to be solved.

The ability to solve an equation for an unknown is a powerful tool of newer computing devices such as calculators and computers. When such a tool is applied to an actual problem, the problem is often best represented as a set of multiple equations. For simple problems with few equations and variables, a user chooses one equation, puts in values that he knows and solves for an unknown. He then use the result of the first equation to solve for an unknown in a second equation and so forth. Ultimately this solution process leads to a value for a particular variable of interest.

For more complex problems, however, the number of equations and variables to be determined is large and the solution process becomes tedious. The user must keep track in each step for each variable whether it is known, unknown, or calculated. It also becomes difficult to select the proper equation in sequence to lead to a value for the desired variable. And once the solution is complete, it is difficult to identify which variables have related values and which do not.

Prior attempts to solve the difficulties of equation selection, variable tracking and variable identification have largely been manual in nature. Some have employed numerical root finders for the actual solving operation for each equation. Others have employed calculator or computer-based methods that automate the select-and-solve portion. But none of these prior attempts has provided a user with a visual indication of the state of a variable and its relationship to the other

variables in the set of equations after solution of the equation.

SUMMARY OF THE INVENTION

An object of the invention, therefore, is to provide a method and apparatus for solving multiple equations which overcome the drawbacks of prior approaches.

A second object of the invention is to create a user interface that allows a user to easily enter known variables and solve for unknown variables.

A third object of the invention is to provide a visual indication to a user of the relationship among variables in multiple equations.

In accordance with these objects, a method of representing to a user the state of variables in multiple equations is disclosed. In the method, each of the multiple equations is scanned to find the variables in the equations. Each variable is then assigned a data entry point such as a key on a keyboard. A label for each variable is then displayed, and indicated on the label is the state of its variable. In the present embodiment, the state of a variable represented by a label is indicated by the color and pattern of the label.

In accordance with the invention, the order in which the variables are found and in which the equations are solved is determined. This information allows the user to review the solution path followed in solving the multiple equations.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a pictorial view of a calculator as one embodiment of apparatus programmed according to the invention.

FIG. 2 is a block diagram of the architecture of the calculator of FIG. 1.

FIG. 3 is a series of screen displays illustrating a user interface according to the invention.

FIGS. 4A-B are portions of a flowchart illustrating the overall method of solving for variables in multiple equations in accordance with the invention.

FIG. 5 is a flowchart of a method for determining if an equation within the multiple equations at a given point may be solved.

FIG. 6 is a flowchart of a method for solving an equation within the multiple equations.

FIG. 7 is a flowchart of a method for displaying to a user the state of each variable within the multiple equations.

FIGS. 8A-D illustrate how variables and equations are stored in memory according to the invention.

BRIEF DESCRIPTION OF A PREFERRED EMBODIMENT

The Apparatus

FIG. 1 shows a calculator 20 which is programmed to solve multiple equations according to the invention. The hardware and architecture of the calculator 20 (shown in FIG. 2) may be of conventional design. The calculator includes an entry means such as a keyboard 22 and a display means such as an LCD display 24. On the face of the keyboard are a plurality of keys that each have a number of functions. Relevant to the present invention are several of the keys that have unique functions. A LIBRARY key 26 is used for activating a multiple equation solver menu interface in a shifted operation. The shift is accomplished by first pressing the left shift key 28. Other keys of note include a right shift key 30, a NXT key 32, and a row of menu keys 34. In response to activating the solver menu, the menu keys are assigned to labels 36 that appear at the bottom of display 24, as will be further described hereafter.

The architecture of calculator 20 includes a central processing unit (CPU) 38 to which are connected via various buses the keyboard 22, the display 24 and memory in the form of ROM 42 and RAM 44. The instructions for operating the CPU are written and stored in the ROM 42

in a conventional manner. The RAM 44 is available for storing data entered via the keyboard 22 and generated by the CPU 38 in the process of solving multiple equations according to the invention.

Of course, any equivalent calculating device may be used, such as a general purpose computer. Equivalent to the keyboard would be any data entry device such as a mouse. Equivalent to the LCD display would be any type of display device such as a CRT, hard copy device, etc.

The Multiple Equation Solver

The method of the present invention solves multiple equations for one or more variables and indicates to the user the state of the variables in the equations after each solution. These states are four: user-supplied values (U); machine-supplied values (C); related values (R); and non-related values (N). Related values are values that were used or found together in the latest solution of an equation. To assist a user in identifying the states of different values, a user interface as shown in FIG. 3 is provided.

FIG. 3 is a series of screen displays illustrating the user interface as it appears on the display 24. The top screen display shows a list of two equations to be solved, VCONE and LCONE. The equations on the list may either come from a library of standard equations or be entered by the user separately. The next screen display shows the entry of two user supplied values, five for the variable R and twelve for the variable L. These variables are considered "known." At the bottom of the display 24, a row of labels 36 then appears, one label for each variable in the multiple equations. If more variables existed than could be shown in a single row, additional rows are created and can be brought into display by pressing the NXT key 32. The labels are assigned to menu keys 34 for selecting which variables are to be found in solving the equations. The background color of the label indicates the source (state)

of the value of the associated variable. A black background, as for labels L and R, indicates that the value is user-supplied. A white background, as for labels V and H, indicates that the value is or will be machine (calculator) supplied. These variables are considered "unknown" until a value is calculated for each. The last label in the row is ALL and is selected for finding all the unknown variables. Thus in this example the user has the option of finding the values of H or V individually by pressing the assigned menu key or as a group by pressing the key 34 assigned to ALL.

The third screen display shows additional indicators on the labels 36 for indicating whether the values of the variables are related through the solving of the equations. That is, the indicators, which appear as black or white boxes within each label, indicate whether the variable was involved in the latest solution of the equations. Black boxes in a white label indicate the variable was calculated. White boxes in a black label indicate the variable was used. If a variable label does not have a black box in the third screen display, then the variable's value was not recently calculated or played no role in solving the equations. For example, if it is desirable to find only the value of the variable H, this can be done by employing only the equation LCONE. The variable V is not involved, and its label would not include a box after the computation. This tells the user that the value of V is not related to the values of the other variables.

The last screen display shows the values found for each variable. L and R were user supplied and thus are considered known. V and H were solved for using the supplied values for L and R and the two equations LCONE and VCONE. Table I, below, summarizes the key action, label appearance and effect on variable state for the interface:

Variable State/ Key Definition	Appearance/Action	State Abbrev
User-supplied values	Black key label	U
Calculator-supplied values	White (outline) key label	C
Related values	Block in menukey label	R
Non-related values	No block in menukey label	N
menukey action	Store value in var	
left-shift menukey action	Solve for var	
right-shift menukey action	Recall var	
Blank memkeys	White (outline) keys	
ALL key	Sets all keys to CN	
left ALL	Starts entire solution	
right ALL	Shows review of solution	

Table I

The method of the present invention of representing to a user the state of a variable in multiple equations to be solved in particularly described in the pseudocode that appears in Appendix I. A more general description of the method is illustrated in the flowcharts of FIGS. 4-7, which will now be described. Each step of the method as it appears in a flowchart is indicated herein by an identifying numeral in parentheses.

FIGS. 4A-B are portions of a flowchart illustrating the overall method for solving for variables in multiple equations. The beginning of the flowchart corresponds to the second screen display of FIG. 3, wherein the user supplied variables have been entered (50). The user first decides whether a specific variable or all of the variables is to be found (52). If only a specific variable (such as V in FIG. 3) is the object, then that variable is deleted from the found_name_list (if it were on it), because its value is to be found regardless of whether the user supplied a value (54). The equations are then checked to see if there are any known variables (56), and if not, an error signaling that there are too many unknown variables is displayed (58). Following is a check to see if there are any unknown variables (60), and if not, another error signaling that there are no unknown variables to be found is displayed

(64). Assuming no error signal, the method checks again if it is solving for all unknown variables (66).

For the case where only a specific variable is to be found, the method scans the list of multiple equations for an equation containing only the desired unknown, such as V (68). If such an equation is found to exist (70), the equation is solved (72). The result for the variable is then stored and displayed (74) and the menu of FIG. 3 indicating the state of each variable in the multiple equations is displayed (76). The process for solving an equation is illustrated in FIG. 6 and the process of displaying the menu is illustrated in FIG. 7, both of which are described hereafter.

If no equation is found that contains only the desired unknown (68), then the method proceeds as though all variables are to be found, as shown at the bottom of FIG. 4A, which continues onto FIG. 4B. A counter *i* is then initialized for solving each of the equations on the list (78). The first equation is retrieved (80) and examined to determine if it is solvable (82). FIG. 5 illustrates the process for determining if the *i*th equation is presently solvable and is described hereafter. If the equation is solvable, then it is solved (84). With the equation solved, the method checks if all unknown variables are to be solved for (86). If not, it is then determined if the variables to be found have all been found (88). If so, then the variables are stored and displayed (90) and the menu indicating the state of each variable is also displayed (92). If there are other variable to be found at step (88), then the found variable is added to list of variables than need not be found (94), the *i* counter is incremented (96) and the next equation is retrieved from the equation list (80).

Returning to step (86), if all unknown variables are to be solved for, the method checks if the present variable is the last unknown (98). If so, then the solutions are complete and the menu is displayed (92). If there are other unknown variables still present, however,

then the method checks if the i th equation is the last equation on the list (100). If not, then the variable is added to the list of variables that have been found (94). If, on the other hand, this is the last equation on the list, then the method inquires whether any variables were found on this pass through the i loop (102). If yes, then the i counter is reinitialized and the process repeats (78). If no variables are found on this pass, then the method determines if it is solving for a single variable or if no variables were found at all when solving for all variables (104). If so, then there are still too many unknown variables (106), and the error is signaled to the user. If not, then all variables have been found that can be found, and the menu indicating the state of each variable is displayed (108).

Referring now to FIG. 5, determining whether the i th equation is solvable begins by initializing a counter j for the variables in the equation (110). The variable is then examined to determine if it needs to be found, i.e., if it is an unknown (112). If it is, the i th equation is examined to determine if there are other unknown variables present in the equation (114). If that is the case, then the i th equation presently is not solvable (116), answering the question in the negative posed in step (82). If the i th equation has only the one unknown (114) to this point, then it must be determined if the j th variable in the i th equation is the last to be examined (118). If so, then the i th equation is deemed solvable (120), answering the question in the affirmative posed in step (82). If the variable is not the last in the i th equation, then the counter j is incremented (122) to the next variable and step (112) is again undertaken. If the j th variable need not be found, because it may have been user-supplied or not requested, then the method branches to step (118) and proceeds as described above.

The step of solving an equation which appears in FIG. 4A as step (72) and in FIG. 4B as step (84) is shown in detail in FIG. 6. Any preexisting relationship among

the variables in the equation being solved is first cleared (130,132). Such a relationship may have existed from an earlier solution where the value of one variable was determined from values of one or more others. A root finder algorithm is then utilized to find a value for the unknown variable (134). Such algorithms are well known in the art, such as described in U.S. Pat. No. 4,845,652, which is hereby incorporated by reference. The state of the unknown variable is then set to "calculator supplied" and "solved for" (CR) in the present equation (136). The states of the other variables in the equation are then set to "used in the solution" (UR) (138). This completes the equation solving step, and the overall method proceeds therefrom.

The step of displaying the variable menu, which appears in FIGS. 4A and 4B, is shown in detail in FIG. 7. The variable counter k is first initialized (140) and the state of the first variable is examined to determine if it is "user-supplied" (142). If so, then the kth variable is examined to determine if it was used in the solution of the equation(s) (144). If the variable was used in the solution, then a black label with a white block (indicating that state) is displayed above the menu key 34 assigned to the label (146). If it was not used in the solution but was user-supplied, a black label (indicating that state) is displayed above the menu key 34 assigned to the variable represented by the label (148). In either case, the process then checks if there are other variables in the equations to be displayed (150) and, if so, increments the variable counter k (152).

Returning to step (142), if the variable is not "user-supplied," then it is examined to determine if it was "solved for" in the solution to the equation (154). If not, then the variable was not involved in the solution process. This may occur where the user has sought to find only specific variables rather than all of those present in the list of equations. In this case, a white label (indicating that state) is displayed above the menu key 34

assigned to the variable represented by the label (156). If, on the other hand, the variable was "solved for," then a white label with a black block (indicating that state) is displayed above the menu key 34 assigned to the variable represented by the label (158).

FIGS. 8A-D illustrate functionally how the variables and equations are stored within the calculating device. In FIG. 8A, each variable is stored with its value, name, and state, with the variables shown in FIG. 3 entered for example. These states, as mentioned above, are four: user-supplied values (U); calculator-supplied values (C); related values (R); and non-related values (N). The first column under "user-supplied" is for indicating whether the variable was user supplied. The second column is for indicating whether the user-supplied variable was used in the last solution to the equations. The first column under "calculator supplied" is for indicating if the value was calculator or machine supplied. The second column is for indicating whether the calculator supplied variable was solved for in the last solution to the equations. The actual representation of this information in memory, of course, may be quite different from the illustration.

FIGS. 8B and 8D illustrate how the orders of solution of the variables and equations are saved in memory for later examination by a user. The values found for unknown variables may differ, depending on the order in which the root finder solves equations. As part of the method for solving the multiple equations herein, the orders in which the variables are found and equations solved are saved and may be recalled by the user through appropriate commands to the calculating device. The order shown is chronological, though other orders may be used as well. This information on orders of solution allows a user to determine the path taken by the multiple equation solver in solving the equations.

FIG. 8C illustrates a register within the calculating device for tracking the *i*th equation and *j*th

variable as part of the method herein. Each equation and variable is stored in its order of solution, as shown in FIGS. 8B and 8D.

Having illustrated and described the principles of the invention in a preferred embodiment, it should be apparent to those skilled in the art that the invention can be modified in arrangement and detail without departing from such principles. We claim all modifications coming within the spirit and scope of the following claims.

APPENDIX I

*Solution Procedure

*Nomenclature:

var_list is the list of all variable names for the eqn system
user-supplied_list is the list of variable names with U status
var_to_find is the var to be found by a single-var solution
found_name_list is the list of variable names that have been found by the MES
unknown-var is the name of the single unknown in a solvable eqn
newly_found_value is the result of calculating unknown_var
number_of_eqns is number of eqns
number_of_eqn_vars is the number of vars in the eqn being examined for solvability
total newly found is the total number of variables calculated in the eqn system
newly_found_this_pass is the number of values calculated during this pass of the solution
solution indicates a single-var solution or an all-vars solution
R->N_done indicates if all the R states were made into N states

```
if left-shift ALL pressed
then solution = all
else solution = single
endif
if solution = all
then found_name_list = user-supplied_list
else found_name_list = user-supplied_list - var_to_find
endif
number_found = length(found_name_list)
if number_found = 0
then
    display "Too Many Unknowns"
    display_menu and quit
endif
number_vars = length(var_list)
if number_found = number_vars
then
    display "All Variables Known"
    display_menu and quit
endif

if solution = single
then
    number_found = 0
    for i=1 to number_of_eqns
        get eqn(i)
```

```

    if eqn(i) solvable          (determines unknown_var)
    then
        if unknown_var = var_to_find
        then
            solve_eqn(eqn(i), unknown_var)
            store and display newly_found_value
            number_found = 1
            display_menu and quit
        endif
    endif
next i
if number_found = 1
then display_menu and quit
endif
endif

number_found = length(found_name_list)
newly_found_this_pass = 1
total_newly_found = 0

while newly_found_this_pass > 0
    newly_found_this_pass = 0
    for i=1 to number_of_eqns
        get eqn(i)
        if eqn(i) solvable          (determines unknown_var)
        then
            solve_eqn(eqn(i), unknown_var)
            if solution = single and unknown_var = var_to_find
            then
                store and display newly_found_value
                display_menu and quit
            endif
            number_found = number_found + 1
            if number_found = number_vars
            then display_menu and quit
            endif
            found_name_list = found_name_list + unknown_var
            total_newly_found = total_newly_found + 1
            newly_found_this_pass = newly_found_this_pass + 1
        endif
    next i
endwhile

if solution = single or total_newly_found = 0
then
    display "Too Many Unknowns"
    display_menu and quit
endif

```

*Additional Details

```
if eqn(i) solvable
```

*This determines if the equation is solvable (has only one
*unknown)

```

solvable = TRUE
number_of_unknowns = 0
for j=1 to number_of_eqn_vars
  if pos(found_name_list, var(j)) = 0
    then      (var(j) is unknown)
      number_of_unknowns = number_of_unknowns + 1
    else
      if var(j) does not exist  (var(j) is known but
erased)
      then
        number_of_unknowns = number_of_unknowns + 1
      endif
    endif
  if number_of_unknowns > 1
  then
    solvable = FALSE
  done
  endif
  unknown_var = var(j)
next j

```

```

solve_eqn(eqn(i), unknown_var)

```

*This handles prompting and state changes while solving an
 *equation for a specific variable.

```

if R->N_done = FALSE
then
  set all R -> N
  R->N_done = TRUE
endif
display "Solving for unknown_var"2
newly_found_value = solve(eqn(i), unknown_var)
set unknown_var to CR
set UN vars in eqn(i) to UR

```

```

newly_found_value = solve(eqn(i), unknown_var)

```

*This routine feeds the root finder the equation being
 solved, *and the name of the unknown variable
 (unknown_var).

*If unknown_var exists, its value should be supplied as a
 guess.

*This may be a real or unit object, or a list of 1 or 2
 reals or *unit objects.

*If unknown_var does not exist, 0 should be used as a
 guess to *the root finder.

```

display_menu

```

*This routine determines the appearance of the menu key labels *based on the states of the variables.

```
for k = 1 to number_vars
  get state(1)
  if state(k) = user-supplied
    then (U means user-supplied)
      if state(k) = used in solution (R means relationship
exists)
        then
          key label is black with white block
        else (N means no relationship exists)
          key label is black with no block
        endif
      else (C means calculator supplied)
        if state(k) = solved for (R means relationship
exists)
          then
            key label is white with black block
          else (N means no relationship exists)
            key label is white with no block
          endif
        endif
      endif
    next k
```

FIG. 1

20





FIG. 2



This Sheet Has Been Replaced



FIG. 3

CALCULATE A FRACTION FROM REAL NUMBERS




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8A

VALUE	NAME	USER SUPPLIED		CALCULATOR SUPPLIED	
		USED IN SOLUTION	NOT USED IN SOLUTION	SOLVED FOR	NOT SOLVED FOR
5	R	✓	✓		
12	L	✓	✓		
285.58..	V			✓	✓
10.90..	H			✓	✓

FIG. 8B

	VAR. BEING SOLVED FOR	EQUATION USING VAR
1	V	1
2	H	2
⋮		
⋮		
⋮		
j		

FIG. 8C




FIG. 8D

	EQUATIONS
1	
2	
3	
⋮	
⋮	
⋮	
i	

We claim:

1. In a calculating device including a display and data entry means, a method of representing to a user the state of variables in multiple equations to be solved, comprising:

scanning each of the multiple equations to find variables within the equations;

assigning to each variable a data entry point for the data entry means;

displaying a label for each variable; and

indicating with each label the state of its variable

wherein the indicated state of a variable includes whether the value of the variable is supplied by the user.

2. In a calculating device including a display and data entry means, a method of representing to a user the state of variables in multiple equations to be solved, comprising:

scanning each of the multiple equations to find variables within the equations;

assigning to each variable a data entry point for the data entry means;

displaying a label for each variable; and

indicating with each label the state of its variable

wherein the indicated state of a variable includes whether the value of the variable is supplied by the calculating device.

3. In a calculating device including a display and data entry means, a method of representing to a user the state of variables in multiple equations to be solved, comprising:

scanning each of the multiple equations to find variables within the equations;

assigning to each variable a data entry point for the data entry means;

This is the replacement sheet

Date: - 9 JUN 1998



REPLACEMENT SHEETS		SG
☐ Description	: paged to paged	
☒ Claim(s)	: paged 16 to paged 19.	
☒ Drawing(s)	: paged 1. to paged 2.	
☐ Abstract	: paged to paged	
		- 9 JUN 1998
DATE OF RECEIPT		

displaying a label for each variable; and
indicating with each label the state of its variable
wherein the indicated state of a variable includes whether the value of the variable was involved in the last solution to the multiple equations.

4. In a calculating device including a display and data entry means, a method of representing to a user the state of variables in multiple equations to be solved, comprising:

scanning each of the multiple equations to find variables within the equations;

assigning to each variable a data entry point for the data entry means;

displaying a label for each variable; and

indicating with each label the state of its variable

wherein the indicated state of a variable includes whether the value of the variable was not involved in the last solution to the multiple equations.

5. The method of claim 1 wherein the indicated state of a variable includes whether the value of a user-supplied variable was used in the last solution to the multiple equations.

6. The method of claim 1 wherein the indicated state of a variable includes whether the value of a user-supplied variable was not used in the last solution to the multiple equations.

7. The method of claim 2 wherein the indicated state of a variable includes whether the value of a calculating device-supplied variable was solved for in the last solution to the multiple equations.



This is the replacement sheet

Date: - 9 JUN 1998

8. The method of claim 2 wherein the indicated state of a variable includes whether the value of a calculating device-supplied variable was not solved for in the last solution to the multiple equations.

9. A calculating device comprising:

a display;

a data entry means for entering multiple equations that include variables and for entering values for the variables into the device;

means for scanning each of the entered multiple equations to find the variables within the equations;

means for assigning a data entry point to each variable;

means for displaying a label for each variable; and

means for indicating with each label the state of its variable

wherein the indicating means comprises means for indicating with each label whether the value of its variable is defined by the user.

10. A calculating device comprising:

a display;

a data entry means for entering multiple equations that include variables and for entering values for the variables into the device;

means for scanning each of the entered multiple equations to find the variables within the equations;

means for assigning a data entry point to each variable;

means for displaying a label for each variable; and

means for indicating with each label the state of its variable

wherein the indicating means comprises means for indicating with each label whether the value of its variable was used in the last solution to the multiple equations.

This is the replacement sheet



Date: 9 JUN 1998

11. A calculating device comprising:

a display;

a data entry means for entering multiple equations that include variables and for entering values for the variables into the device;

means for scanning each of the entered multiple equations to find the variables within the equations;

means for assigning a data entry point to each variable;

means for displaying a label for each variable; and

means for indicating with each label the state of its variable

wherein the indicating means comprises means for indicating with each label whether the value of its variable was solved for in the last solution to the multiple equations.

This is the replacement sheet



Date: - 9 JUN 1998

FIG. 1





FIG. 2



This is the replacement sheet

Date: - 9 JUN 1998

FIG. 3

(▼ AS NEEDED)

EQ+

{ VCONE LCONE }					
VCONE: ' V= π *R^2*H/3 '					
EQ: ' VCONE '					
▶LCONE: ' L= $\sqrt{R^2+H^2}$ '					
PLOTR	SOLVR	EQ+	EDIT	→STK	VIEW

MSOL

5 R 12 L

L: 12					
4:					
3:					
2:					
1:					
V	L	R	H		ALL

← ALL

1:					
V	L	R	H		ALL

EQ					
V: 285.589415328					
L: 12					
R: 5					
H: 10.9087121146					
V	L	R	H		ALL

This is the replacement sheet

Date: 9 JUN 1998