

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International patent classification⁶: H01H 85/32	A1	(11) International publication number: WO 99/35658 (43) International publication date: 15 July 1999 (15.07.99)
(21) International application number: PCT/EP99/00052 (22) International filing date: 7 January 1999 (07.01.99) (30) Data relating to the priority: 198 00 779.5 12 January 1998 (12.01.98) DE (71)(72) Applicant and Inventor: BRUCHMANN, Klaus [DE/DE]; Am Ölberg 7a, D-96450 Coburg (DE). (74) Attorney: GROENING, Hans, W.; Boehmert & Boehmert, Franz-Joseph-Strasse 38, D-80801 Munich (DE).		(81) Designated states: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO Patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI Patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With the International Search Report. Before expiry of the period provided for amending the claims, will be republished if such amendments are received.

As printed

(54) Title: FUSE HOLDER HAVING AN INTEGRATED CONNECTING LINE FOR STATUS INDICATORS**(54) Bezeichnung:** SICHERUNGSHALTER MIT INTEGRIERTER ANSCHLUSSLEITUNG FÜR ZUSTANDSMELDER**(57) Abstract**

The invention relates to a fuse holder (10) for a fuse-link (20) in which a fuse status indicator having a printed circuit board (25) and a glow lamp (26) is fitted. The necessary connecting lines (16, 17) are made of conductive plastic from the top and base contacts (22, 23) of the fuse-link (20) to the printed circuit board (25) of the status indicator. The conductive plastic is injected in channels which are provided therefor and are situated in the housing of the fuse holder (10).

(57) Zusammenfassung

In den beschriebenen Sicherungshalter (10) für einen Sicherungseinsatz (20) ist ein Sicherungs-Zustandsmelder mit einer Platine (25) und einer Glühlampe (26) eingebaut. Die erforderlichen Anschlußleitungen (16, 17) vom Kopf- und Fußkontakt (22, 23) des Sicherungseinsatzes (20) zur Platine (25) des Zustandsmelders sind aus leitendem Kunststoff, der in dafür vorgesehene Kanäle im Gehäuse des Sicherungshalters (10) eingespritzt ist.

