

COVER

TECHNOLOGICAL FIELD

The presently disclosed subject matter relates to seeker heads in general.

PRIOR ART

5 References considered to be relevant as background to the presently disclosed subject matter are listed below:

- US 5,973,649
- US 5,167,386
- US 4,348,677
- 10 - US 4,085,910
- US 2013/0214093
- US 6,057,915
- US 5,796,474
- US 5,134,409
- 15 - US 6,484,619
- US 6,262,800
- WO 2010/001402

Acknowledgement of the above references herein is not to be inferred as
20 meaning that these are in any way relevant to the patentability of the presently disclosed subject matter.

BACKGROUND

Instrument packages having a number of sensor devices and energy emitting
25 devices are well known tools, used for example in aircraft or missiles for detecting, tracking and/or homing onto a target. Such devices often include electro-optical sensors, radar and the like, accommodated in a seeker head, for example.

There are many known applications where different types of sensors are used with airborne platforms, and the sensors are commonly configured for simultaneous operation through a common aperture. In some such systems having a plurality of electro-optical sensors, some including laser radar or other optical elements, a system of
5 mirrors or other optical components may be used for enabling each of the sensors to look through the common aperture at the same time, or at alternating periods via a movable mirror arrangement, for example. Applications are also known having separate dedicated sensors, including a radar system and an electro-optical sensor for example, in which a different part of the available aperture is assigned to each of the sensors. In yet
10 other applications, each sensor may be configured and mounted to an aircraft, for example, as a separate and independent sensor system.

Such electro-optical sensors are often fitted with a transparent cover.

GENERAL DESCRIPTION

15 According to an aspect of the presently disclosed subject matter there is provided a cover assembly (also interchangeably referred to herein as a cover or as a cover system) for use with an instrument package having a common aperture, comprising:

an inner cover member, substantially transparent to electromagnetic
20 (EM) radiation of at least a first wavelength range;

an outer radome member configured for selectively and reversibly covering the inner cover member and transparent to EM radiation of at least a second wavelength range different from said first wavelength range, the second wavelength range including a radio frequency (RF) wavelength range (thus, EM
25 communication in said second wavelength range between the common aperture and an outside of the outer radome member is via at least the outer radome member (and in some examples also via the inner cover member)); the outer radome member being configured for being mounted in overlying relationship with respect to the common aperture of the instrument package;

30 the outer radome member being configured for being initially in overlying relationship with respect to the inner cover member and for being

selectively removed from said overlying relationship with respect to the inner cover member at least during flight conditions.

For example, there is a lack of overlap between said first wavelength range and said second wavelength range.

5 For example, the inner cover member is also configured for being mounted in overlying relationship with respect to the common aperture of the instrument package (thus, EM communication in said first wavelength range between the common aperture and an outside of the inner cover member is via the inner cover member).

For example, said first wavelength range includes wavelengths corresponding to
10 at least one of: the visible spectrum; infra red (IR) spectrum; ultraviolet (UV) spectrum.

Additionally or alternatively, for example, said second wavelength range includes RF wavelengths corresponding to at least one of: L-band, S-band, C-band, X-band, K-band, V-band, W-band, Multi-band, Y-band.

Additionally or alternatively, for example, said inner cover member is further
15 substantially transparent to EM radiation of said second wavelength range.

Additionally or alternatively, for example, the inner cover member is made from a material transparent to said radiation of at least said first wavelength range.

Additionally or alternatively, for example, the inner cover radome cover is made from any one of: Silicon, Silicon oxide (SiO), or other Silicon-based materials; Copper
20 oxide (CuO); Manganese Oxide (MnO); Germanium; Sapphire; Magnesium aluminate spinel (MgAl₂O₄); Yttria; AlON (Al₂₃O₂₇N₅); Alumina; YAG, Nd:YAG; plastic; glass; composite materials; transparent spinel.

Additionally or alternatively, for example, the outer radome cover is made from a material transparent to said radiation of said second wavelength range.

25 Additionally or alternatively, for example, the outer radome cover is made from any one of: Slip Cast Fused Silica; ceramic materials; composite materials such as for example quartz-based composite materials; Teflon; some plastics; Ultem; fiberglass; PTFE-coated fabrics; boron carbide, alumina, glass, silicon carbide.

Additionally or alternatively, for example, the inner member is formed as a transparent dome, or any other suitable aerodynamic shape having a flat or rounded nose section that allows the EM radiation of the first wavelength range to pass through with zero distortion or with a minimum distortion, and that optionally allows the EM radiation of the second wavelength range to pass through with zero distortion or with a minimum distortion.

Additionally or alternatively, for example, the outer member has an ogive form, or any other suitable aerodynamic shape, for example a cone.

Additionally or alternatively, for example, said outer radome member is reversibly engageable with respect to the inner cover member. Thus, for example, when the outer radome member is initially in said overlying relationship with respect to the inner cover member the outer radome member is engaged with respect to the inner cover member; conversely, when the outer radome member is removed from said overlying relationship with respect to the inner cover member, said outer radome member is automatically disengaged with respect to the inner cover member.

Additionally or alternatively, for example, the outer radome member is formed from a plurality of radome segments, wherein in said overlying relationship with respect to the inner cover member said radome segments are mutually engaged together, and wherein said outer radome member is selectively removable from said inner cover member by mutually disengaging said radome segments.

Additionally or alternatively, for example, said radome segments are reversibly connected to one another along longitudinal edges thereof when mutually engaged together.

Additionally or alternatively, for example, said radome segments are held together via explosive bolts, which are configured for being selectively activated to separate the radome segments from one another.

Additionally or alternatively, for example, said radome segments comprise reactive material, wherein upon activation of the reactive material, a mechanical connection between said radome segments is weakened or destroyed, enabling said radome segments to become separated from one another.

Additionally or alternatively, for example, the cover assembly is configured for use with a seeker head accommodating the instrument package, and wherein at least the inner cover member is configured for being affixed to the seeker head.

5 Additionally or alternatively, for example, the cover assembly is configured for use with a sensor including the instrument package, and wherein at least the inner cover member is configured for being affixed to the sensor.

Additionally or alternatively, for example, the cover assembly further comprises a radome cover for selectively and reversibly covering the outer radome member.

10 Additionally or alternatively, for example, the outer radome member is configured for being concurrently in overlying relationship with respect to the common aperture when initially in said overlying relationship with respect to the inner cover member.

According to the above aspect of the presently disclosed subject matter there is also provided a seeker head for an air vehicle comprising:

15 a cover assembly and instrument package having a common aperture, as defined in the above aspect of the presently disclosed subject matter;

the instrument package comprising:

- at least one first sensing/emitting unit configured for operating in said first wavelength range via emission/reception of EM radiation in said first wavelength range through at least said inner cover member;
- 20 - at least one second sensing/emitting unit configured for operating in said first wavelength range, via emission/reception of EM radiation in said second wavelength range through at least said outer radome
- each said sensing/emitting unit adapted for at least one of sensing and emitting energy along a respective sensing/emitting unit line of sight aligned with respect to the common aperture of said instrumentation package.
- 25

For example, said at least one first sensing/emitting unit includes any one of : an imaging camera, CCD, CMOS, configured for video imaging and/or still picture imaging, in any one or more of the visible spectrum, the infra red spectrum (IR), or in the ultraviolet spectrum (UV); a visual unit, an IR sensor, a thermal sensor (e.g. FLIR

30

sensor), a NIR (near infra-red) sensor; laser-based module including for example LADAR or LIDAR; bolometric sensor.

Additionally or alternatively, for example, said at least one first sensing/emitting unit includes any one of: a passive RF seeker; an active or semi active RADAR seeker; 5 an RF range sensor; a Doppler radar; a synthetic aperture radar (SAR); passive phased array / passive electronically scanned array (PESA) seeker; active phased array / active electronically steered array / active electronically scanned array (AESA) seeker / DBF (digital beam forming) seeker / proximity sensor; an anti-radiation RF sensor.

Additionally or alternatively, for example, the seeker head further comprises a 10 controller for selectively causing the outer radome member to be removed from said overlying relationship with the inner cover member according to preset criteria. For example, said controller is further configured for concurrently operating said at least one first sensing/emitting unit and said at least one second sensing/emitting unit for at least a predetermined time interval after said outer radome member is removed to 15 thereby synchronize operation of said at least one first sensing/emitting unit with said at least one second sensing/emitting unit. For example, the instrument package can be further configured for selectively switching operation from the at least one first sensing/emitting unit to the at least one second sensing/emitting unit via a handshake procedure. Such switching can be controlled by said controller, for example an airborne 20 computer. For example, the switching operation can be initiated according to said preset criteria. For example, such criteria can include one or more of the following: after the passage of a certain time period after launch of the vehicle on which the instrument package is mounted; when the vehicle reaches a certain distance from an intended target; when the vehicle reaches a certain geographical location (in which case for 25 example the vehicle can also be configured for determining its geographical location); and so on. The criteria can also include that vehicle on which the instrument package is mounted is in flight or otherwise in a trajectory in the atmosphere.

According to the above aspect of the presently disclosed subject matter there is provided an air vehicle comprising a seeker head as defined according to the above 30 aspect of the presently disclosed subject matter. For example, the air vehicle is any one of an air-to-air missile, an air-to-surface missile, a surface-to-air missile, a surface-to-

surface missile, a cruise missile, an anti-missile interceptor, munitions, a gliding bomb, a guided bomb, a rocket, a MK bomb including a homing kit, a UAV.

According to the above aspect of the presently disclosed subject matter there is provided a method for operating a seeker head, comprising

- 5 - providing a seeker head as defined according to the above aspect of the presently disclosed subject matter;
- operating the seeker head to selectively remove the outer radome member from said overlying relationship with the inner cover member according to preset criteria.

10 For example, such criteria can include one or more of the following: after the passage of a certain time period after launch of the vehicle on which the instrument package is mounted; when the vehicle reaches a certain distance from an intended target; when the vehicle reaches a certain geographical location (in which case for example the vehicle can also be configured for determining its geographical location);
15 and so on. The criteria can also include that vehicle on which the instrument package is mounted is in flight or otherwise in a trajectory in the atmosphere.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to better understand the subject matter that is disclosed herein and to
20 exemplify how it may be carried out in practice, examples will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 is an isometric view of a cover assembly according to a first example of the presently disclosed subject matter installed on a forward end of an air vehicle, in
25 which the cover assembly is in the covered configuration.

Fig. 2 is an isometric view of the example of Fig. 1, in which the respective outer radome member is in the process of being removed.

Fig. 3 is a partially fragmented isometric view of the example of Fig. 1, in which the respective outer radome member is fully removed and the cover assembly is in the
30 uncovered configuration.

Fig. 4 is a side cross-sectional view of the example of Fig. 1.

Fig. 5 is a partially fragmented side cross-sectional view of an alternative variation of the example of Fig. 1.

Fig. 6 is a schematic illustration of an example of a trajectory for the example of
5 Fig. 1.

DETAILED DESCRIPTION

Referring to Figs. 1 to 4, a cover assembly (also referred to interchangeably herein as a cover or as a cover system) according to a first example of the presently disclosed subject matter, generally designated **100**, comprises an inner cover member **200** and an
10 outer radome member **300**.

The cover assembly **100** is configured for being mounted to the forward end **2** of a vehicle **1**, in particular an air vehicle. In this example, the air vehicle **1** is a missile, for example any one of: an air-to-air missile, an air-to-surface missile, a surface-to-air missile, a surface-to-surface missile, and cruise missile. In alternative variations of this
15 example, the air vehicle can be any one of: anti-missile interceptor, munitions, gliding bomb, guided bomb, rocket, MK bomb including a homing kit, some types of UAV's.

Referring in particular to Fig. 3, the forward end **2** comprises the seeker head of the air vehicle **1**, and comprises an external casing **3**, accommodating an on-board instrument package **400** having a sensor/emitting face **410** and defining a common
20 instrument aperture **405** facing in a general forward direction along the longitudinal axis **LA** of the air vehicle **1**.

Referring also to Fig. 6, in this example, the air vehicle **1** is configured for homing onto a target **T** using an on-board instrument package **400** operatively connected to a controller in the form of an airborne computer **480**, which is configured
25 for steering the air vehicle **1** in response to homing data and/or homing signals received from the instrument package **400** responsive to EM energy transmitted and/or received via common aperture **405**. The instrument package **400** comprises at least one first sensing/emitting unit in the form of electro-optic (EO) unit **420**, and at least one second sensing/emitting unit in the form of radio frequency (RF) unit **440**. Furthermore, in at

least this example, the respective apertures of each of the EO unit **420** and the RF unit **440** are at common aperture **405**, centered on the longitudinal axis **LA**.

The cover assembly **100** is configured for selectively protecting operation of the instrument package **400** (in particular for selectively protecting proper operation of the units **420**, **440**) during the various operations phases thereof, particularly during flight of the air vehicle **1**, while concurrently allowing operation of the units **420**, **440**, as will become clearer herein.

The EO unit **420** is configured for operating with respect to a particular range of operating wavelengths λ_{EO} , i.e., for sensing and/or emitting electromagnetic (EM) energy having wavelengths within this operating range, with respect to a field of view (FOV) and along a line of sight (LOS) generally forward of the sensor/emitting face **410**. For example, the EO units **420** can include one or more of: an imaging camera, CCD, CMOS, and so on, for imaging (video and/or still pictures) in the visible spectrum, and/or in the infra red spectrum (IR) and/or in the ultraviolet spectrum (UV), for example including a visual unit, an IR sensor, a thermal sensor (e.g. FLIR sensor), a NIR (near infra-red) sensor; laser-based module including for example LADAR or LIDAR, or other laser sensor; bolometric sensor; other heat seekers.

The RF unit **440** is configured for operating with respect to a particular range of operating wavelengths λ_{RF} , i.e., for sensing and/or emitting electromagnetic (EM) energy having wavelengths within this operating range, also with respect to the field of view (FOV) generally forward of the sensor/emitting face **410**. For example, the RF unit **440** comprises a RADAR sensor/emitter system, capable of operating in one or more of L-band, S-band, C-band, X-band, K-band, V-band, W-band, Multi-band, Y-band. For example, the RF units **420** can include one or more of: a passive RF seeker; an active or semi active RADAR seeker; an RF range sensor; a Doppler radar; a synthetic aperture radar (SAR); passive phased array / passive electronically scanned array (PESA) seeker; active phased array / active electronically steered array / active electronically scanned array (AESA) seeker / DBF (digital beam forming) seeker / proximity sensor; an anti-radiation RF sensor.

In the illustrated example of Figs. 1 to 4, the range of operating wavelengths λ_{EO} for the EO unit **420** is totally different from the range of operating wavelengths λ_{RF} of

the RF unit **440**, i.e., there is no overlap between the range of operating wavelengths λ_{EO} and the range of operating wavelengths λ_{RF} . In alternative variations of this example, there can be some overlap between the range of operating wavelengths λ_{EO} and the range of operating wavelengths λ_{RF} , while the range of operating wavelengths λ_{EO} and the range of operating wavelengths λ_{RF} are not identical and thus different from one another.

In this example, the RF unit **440** is fixedly located with respect to the EO unit **420** and with respect to the longitudinal axis **LA**. The EO unit **420** has its aperture, and optical axis at the aperture, aligned with the longitudinal axis **LA**. Alternatively, EO unit **420** has its aperture, and optical axis at the aperture, aligned with an axis parallel to or at an angle with the longitudinal axis **LA**. Optionally, the EO unit **420** has an element, for example a field lens or window, on the sensor/emitting face **410**. In alternative variations of this example, a plurality of EO units **420** are provided, each having its aperture, and its respective optical axis at the aperture, aligned with or offset from the longitudinal axis **LA** or at angle thereto. In these cases, the apertures of each of the EO units **420** are included within the system's common aperture **405**.

The RF unit **440** is concurrently concentric with respect to the EO unit **420**, and also has its aperture aligned with the longitudinal axis **LA**. Alternatively, RF unit **440** has its aperture, and optical axis at the aperture, aligned with an axis parallel to or at an angle with the longitudinal axis **LA**.

The RF unit **440** in this example is configured as an SAR array, and comprises a plurality of radiating elements **442**, for example radiating tiles, radially and circumferentially distributed over an annular ring **444** over the sensor/emitting face **410**. For example, each radiating element **442** comprises a plurality of RF down-conversion units, a plurality of digital beam forming units and a plurality of Gigabits X-links, mounted on a mechanical frame. For example, the SAR array can be configured for operating in any suitable band, for example from the X-Band to the L-Band.

In this example, the sensor/emitting face **410** is fixed in orientation with respect to longitudinal axis **LA**. However, in alternative variations of this example, the sensor/emitting face **410**, or alternatively the sensing package **400**, can be mounted to the air vehicle **1**, in particular to the forward end **2**, via a suitable tilt and pan mechanism, for

example via gimbals, to allow the azimuth and/or elevation of the field of view (FOV) of one or both of the unit **420**, **440** to be pivoted in pitch and/or way with respect to the longitudinal axis **LA** of the vehicle **1**.

In this example, the instrument package **400** is further configured for selectively
5 switching operation from the RF unit **440** to the EO unit **420** via a handshake procedure (also interchangeably referred to herein as a handover procedure). For example, the EO unit **420** begins to operate as soon as the RF unit **440** ceases its operation. Alternatively, the EO unit **420** begins to operate before the RF unit **440** ceases its operation so that
10 both the EO unit **420** and the RF unit **440** operate concurrently for an overlapping period of time, and thereafter the EO unit **420** operates on its own. During the overlapping period of time in which both EO unit **420** and the RF unit **440** operate concurrently, the operation of the RF unit **440** is phased out while the EO unit **420** is brought into full operation.

Such switching can be controlled by a suitable controller, for example airborne
15 computer **480**. For example, the switching operation can be initiated according to preset criteria, such as for example one or more of the following: after the passage of a certain time period after launch of the vehicle **1**; when the vehicle **1** reaches a certain distance from an intended target; when the vehicle **1** reaches a certain geographical location (in which case for example the vehicle **1** is configured for determining its geographical
20 location); when the RF unit **440** cannot identify the target or cannot provide target data; when the RF unit **440** becomes inoperative or its operation is faulty; and so on.

Alternatively or additionally, the instrument package **400** is configured for hybrid operation (also referred to herein as data fusion operation) in which the RF unit **440** and the EO unit **420** are concurrently operated, and operation of the two units is not
25 terminated.

The inner cover member **200** is transparent to EM radiation of a first wavelength range λ_1 , corresponding to the range of operating wavelengths λ_{EO} of the EO unit **420**. Thus, first wavelength range λ_1 can be identical to the operating wavelengths range λ_{EO} , or, the first wavelength range λ_1 can be broader than, and thus include, the range of
30 operating wavelengths range λ_{EO} . Thus, in the particular example where the EO unit

420 operates in the visible spectrum, the inner cover member **200** is also transparent at least to visible light.

For example, the inner cover member **200** can be made from one or more of the following materials, generally depending on the particular values desired or required for the first wavelength range λ_1 : Silicon, Silicon oxide (SiO), or other Silicon-based materials; Copper oxide (CuO); Manganese Oxide (MnO); Germanium; Sapphire; Magnesium aluminate spinel (MgAl₂O₄); Yttria; ALON (Al₂₃O₂₇N₅); Alumina; YAG, Nd:YAG; plastic; glass; composite materials; transparent spinel.

In this example, the EO unit **420** has its optical axis in fixed spatial relationship with the longitudinal axis LA, and a particular **FOV**. Thus, in this example it is only necessary for part of the inner cover member **200** (that is intersected by the **FOV**) needs to be transparent to the first wavelength range λ_1 , while the remainder of the inner cover member **200** need not be so.

The outer radome member **300** is transparent to EM radiation of a second wavelength range λ_2 corresponding to the range of operating wavelengths λ_{RF} of the RF unit **440**. Thus, second wavelength range λ_2 can be identical to the operating wavelengths range λ_{RF} , or, the second wavelength range λ_2 can be broader than, and thus include, the operating wavelengths range λ_{RF} . Thus, in the particular example where the RF unit **440** is a SAR operating in the X-Band and the K-Band or the X-Band to the L-Band, the outer radome member **300** is also transparent at least to EM energy in the X-Band and the K-Band or the X-Band to the L-Band, respectively.

For example, the outer radome member **300** can be made from one or more of the following materials, depending on the particular values of the second wavelength range λ_2 : Slip Cast Fused Silica; ceramic materials; composite materials such as for example quartz-based composite materials; Teflon; some plastics; Ultem; fiberglass; PTFE-coated fabrics, boron carbide, alumina, glass, silicon carbide.

Thus, in at least some examples, some composite materials can be used only for one or the other but not for both of outer radome member **300** and the inner cover member **200**. In at least some other examples, plastic materials can be used for both of outer radome member **300** and the inner cover member **200**. In at least some other

examples, glass can be used for both of outer radome member **300** and the inner cover member **200**. In this example, the inner cover member **200** is also transparent to EM radiation of the second wavelength range λ_2 , or at least to the range of operating wavelengths λ_{RF} of the RF unit **440**, and thus the RF unit **440** can operate via the inner
5 cover member **420** and the outer cover member **440**.

In this example, the EO unit **420** has its optical axis (at or within the common aperture **405**) in fixed spatial relationship with the longitudinal axis **LA**, and the EO unit **420** also has a particular **FOV**. Thus, in this example it is only necessary for part of the inner cover member **200** (that is intersected by the **FOV**) to be transparent to the first
10 wavelength range λ_1 , while the remainder of the inner cover member **200** need not be so.

In this example, the first wavelength range λ_1 is totally different from the second wavelength range λ_2 , i.e., there is no overlap between the wavelength range λ_1 and the second wavelength range λ_2 . In alternative variations of this example, there can be
15 some overlap between the wavelength range λ_1 and the second wavelength range λ_2 , while the first wavelength range λ_1 and the second wavelength range λ_2 are not identical and thus different from one another.

In the covered configuration illustrated in Fig. 1, the outer radome member **300** covers the inner cover member **200** (both radially and axially with respect to the longitudinal axis **LA**), and both are in overlying relationship with respect to the
20 common aperture **405** of the instrument package **400**. Thus, the outer radome member **300** is configured for being initially in overlying relationship with respect to the inner cover member **200**; the outer radome member is further configured for being concurrently in overlying relationship with respect to the common aperture **405** when
25 initially in the aforesaid overlying relationship with respect to the inner cover member **200**. Furthermore, and as will become clearer herein, the outer radome member **300** is also configured for being selectively removed from the inner cover member **200** at least during flight conditions, to thereby expose the inner cover member **200** to the airflow – referred to herein as the uncovered configuration.

30 In this example, and in other examples, the inner cover member **200** has a geometrical form that is at least partially aerodynamic, for example generally rounded,

such that when the inner cover member **200** is exposed to an external airflow, such as in the uncovered configuration of Fig. 3 for example, it minimizes drag or at least provides low drag to the vehicle **1**.

In this example, and referring in particular to Fig. 4, the inner cover member **200** is in the form of a dome, comprising a convex dome outer surface **210** separated from a concave dome inner surface **220** via the dome thickness **t1**. In this example the longitudinal axis **LA** intersects the dome at its apex **215**, and the dome is axisymmetric about longitudinal axis **LA**. In this example the dome is hemispherical, having uniform curvature throughout, and the dome outer surface **210** having a height **H1** along the longitudinal axis **LA** about half the base diameter **D** of the dome outer surface **210**. However, in alternative variations of this example, the dome can be non-axisymmetric, and/or can have variable curvature and/or can have a height **H1** that is greater than or that is less than the half the base diameter **D**, for example.

In this example, the outer surface base diameter **D** is less than the outer diameter **DO** of the forward end **2**, providing an annular shoulder **5** between the base **225** of the dome and the outer skin of external casing **3**.

In at least this example, the inner cover member **200** is configured for remaining fixed in position on the forward end, throughout most or all of the flight or trajectory of the air vehicle **1**.

In this example the inner cover member **200** has rounded cross-sections in planes transverse to the longitudinal axis **LA** – for example circular cross-sections, or elliptical cross-sections, or super elliptical cross-sections. However, in alternative variations of this example and in other examples, the inner cover member **200** has non-rounded cross-sections in planes transverse to the longitudinal axis **LA** – for example polygonal, providing a faceted configuration for the inner cover member **200**.

In this example, and in other examples, the outer radome member **300** has a geometrical form that is at least partially aerodynamic, for example at least partially rounded or pointed, such that when the outer radome member **300** is mounted on the vehicle **1** and covering the inner member **200** (and thus the outer radome member **300** is exposed to an external airflow when the air vehicle is in flight in the atmosphere), such

as in the covered configuration of Fig. 1 for example, it minimizes drag or at least provides low drag to the vehicle **1**.

In this example, the outer radome member **300** is axisymmetric about an axis **A**, which is parallel and co-axial with longitudinal axis **LA** when in the covered
5 configuration.

In this example, the outer radome member **300** is in the form of an ogive, comprising a pointed nose **311**, and an ogive outer surface **310** separated from an ogive inner surface **320** via the thickness **t2** of the outer radome member **300**, and annular base edge **330**. In this example the longitudinal axis **LA** intersects the ogive via the nose
10 **311**, i.e., at its apex **315**, and the ogive is axisymmetric about axis **A**. In this example the inner surface **320** has a height **H2** along the longitudinal axis **LA** greater than the height **H1** of the dome outer surface **210**, providing a spacing **S** between the inner member **200** and the outer radome member **300** in the covered configuration.

However, in alternative variations of this example, the ogive can be non-
15 axisymmetric, and/or can have uniform curvature, and/or can be replaced with a conical form, and/or can have an inner surface having a form that is complementary to that of the dome outer surface **210**, and/or have a rounder nose, for example.

In this example the outer radome member **300** has rounded cross-sections in planes transverse to the longitudinal axis **LA** – for example circular cross-sections, or
20 elliptical cross-sections, or super elliptical cross-sections. However, in alternative variations of this example and in other examples, the outer radome member **300** has non-rounded cross-sections in planes transverse to the longitudinal axis **LA** – for example polygonal, providing a faceted configuration for the outer radome member **300**.

25 The outer radome member **300** is removably mounted to the air vehicle **1** by engagement of the base edge **330** with the shoulder **5**.

In at least this example, the outer radome member **300** is configured for being removed from the overlying relationship with the inner cover member **200** at a certain point in the trajectory of the vehicle **1**, to thereby expose the inner cover member **200** to
30 the airflow, and allow the EO unit **420** to operate.

To facilitate in-flight removal of the outer radome member **300**, the outer radome member **300** is formed from a number of radome segments, in the illustrated example two radome segments **350**. As best seen on Fig. 2, the two radome segments **350** are mirror images of one another, and are connected to one another along longitudinal edges **355** in the covered configuration, and detached from one another via the edges **355** in the uncovered configuration. In alternative variations of this example, the outer radome member is formed from a plurality of, for example three, four, or more than four, radome segments, *mutatis mutandis*.

In this example, the outer radome member **300** is directly and reversibly secured to the forward end **2**, via reversible engagement between the base edge **330** and shoulder **5**, for example via explosive bolts. In such cases, the radome segments **350** have to be separated from one another and concurrently from the forward end **5**, for example simultaneously or with a small time interval between the two actions.

In alternative variations of this example and in other examples, the outer radome member **300** is not directly secured (i.e., is not independently engaged) to the forward end **2**, but rather is indirectly secured to the forward end **2** via engagement of the radome segments **350** to one-another. For example, referring to Fig. 5, projections **330A** are provided on the radome segments **350** at or near the base edge **330**; the projections **330A** face radially towards the longitudinal axis **LA** and radially engage in slots or a groove **330B** provided in the casing **3** or the inner dome member **420**. When projections **330A** are engaged in the groove **330B** and the radome segments **350** are connected to one another, the outer radome member **300** is automatically locked onto, and thus prevented from moving with respect to, the forward end **2**; when the radome segments **350** are disengaged from one another, the projections **330A** can move out of the groove **330B** allowing the radome segments **350** to be fully detached from the air vehicle.

In this example, the radome segments **350** are held together via explosive bolts, which can be activated when desired to separate the radome segments **350** from one another. Alternatively the radome segments **350** comprise reactive material, for example pyrotechnic or explosive material at the longitudinal edges **355**, so that upon activation of the reactive material, the mechanical connection between the radome segments is weakened or destroyed, enabling the radome segments **350** to become separated from

one another. For example, the reactive material can be activated by heating or passing an electric current through the reactive material, to thereby detonate the reactive material.

In one example of operation of the instrument package **400** for homing onto a target when the air vehicle **1** is in flight along a particular trajectory **F**, and referring to Fig. 6, the RF unit **440** first operates to provide homing data to the airborne computer **480** for steering the air vehicle **1** during a first homing phase **HM1** of the flight, while the air vehicle **1** is within a first range **R1** of the target **T**, but greater than a second range **R2**. Once the air vehicle **1** is within the second range **R2** from the target **T**, at point **FO** in the trajectory **F**, the instrument package **400** further operates to switch to the electro-optic unit **420**, which operates to provide homing data to the airborne computer for steering the air vehicle **1** during the second homing phase **HM2** of the flight, while the air vehicle **1** is within the second range **R1** from the target, for example until the air vehicle **1** impacts or otherwise destroys the target.

For example, the location of point **FO** in the trajectory **F** can be chosen according to preset criteria, such as for example one or more of the following: after the passage of a certain time period after launch of the vehicle **1**; when the vehicle **1** reaches a certain distance from an intended target, and this defines ranges **R1** and **R2**, for example when the vehicle **1** is at range **R2**; when the vehicle **1** reaches a certain geographical location (in which case for example the vehicle **1** is configured for determining its geographical location); when the RF unit **440** cannot identify the target or cannot provide target data; when the RF unit **440** becomes inoperative or its operation is faulty; and so on.

Thus, during the first homing phase **HM1** of the trajectory **F** and until point **FO**, the cover assembly **100** is in the covered configuration, with the outer radome member **300** exposed to the atmosphere and concurrently in overlying relationship with respect to the inner cover member **200**. In this phase of the trajectory, the RF unit **440** is able to operate by transmitting and/or receiving EM energy in the operating wavelengths λ_{RF} , via the outer radome member **300** and the inner cover member **200**, both being transparent to at least these operating wavelengths λ_{RF} . At the same time, the inner

cover member **200** is not in direct contact with the airflow, and is protected from the atmospheric environment.

The air vehicle 1 is configured to execute the following two actions at point **FO**:

5 (a) removal of the outer radome member **300** from the cover assembly **100** to provide the uncovered configuration, to thereby allow unhampered operation of the inner cover member **200**.

10 (b) switching operation from the RF unit **440** to the EO unit **420** (or at least commence operation of the EO unit **420**, while the RF unit **440** continues to operate), executing a handshake procedure or handover procedure, or a data fusion procedure, to ensure continuity of homing operations of the instrument package **400**.

15 In this homing example, action (a) precedes action (b). Thus when the outer radome member **300** is removed, both the RF unit **440** and the EO unit **420** are able to operate concurrently (for example via data fusion operation or hybrid operation). As such, both units can provide homing data concurrently, and thus enable the airborne computer to ensure smooth transition of operation of the instrument package **400** to the EO unit **420**, and cease operation of the RF unit **440**, to allow homing in the second homing phase **HM2** of the flight to be via the EO unit **420**. However, it is to be noted that, optionally, both the EO unit **420** and the RF unit **440** can continue to operate in the
20 second homing phase **HM2** of the flight.

It is thus evident to the skilled practitioner that the outer radome member **300** protects the inner cover member **200** during initial portions of the flight or trajectory of the air vehicle 1 during which the EO unit **420** is not required to operate, while at the same time allowing the RF unit **420** to operate to transmit and/or receive EM energy in
25 the operating wavelengths λ_{RF} . Thereby, the inner cover member **200** is protected from the elements, in particular the weather and/or airborne contaminants (for example sand, ice, etc), while the EO unit **420** is not being operated, thereby preventing scratches, contaminant deposits and so on from forming on the inner cover member **200**, and thus protecting the quality of the optical transparency of the inner cover member **200**.
30 Furthermore, the inner cover member **200** is also protected from the airflow by the outer

radome member **300** during the initial stages of the flight or trajectory, and thus the inner cover member **200** does not need to be structured to withstand high aerodynamic loads that may be present only in the initial stages of the flight or trajectory, but not present in later stages of the flight or trajectory when the EO unit **420** is required to be
5 operated.

Optionally, an additional protective cover (not shown) can be provided for the outer radome cover **300**, to protect the cover assembly **100**, and in particular the outer radome member **300**, during transportation and handling, and until the air vehicle **1** to be launched, for example. Thus, the protective cover can be selectively discarded, for
10 example on the ground (e.g. by ground crew), prior to the air vehicle being launched or fitted to a carrier vehicle such as for example an aircraft. The protective cover does not require to be transparent to any of the first wavelength range $\lambda 1$ or second wavelength range $\lambda 2$.

In some alternative variations of the above examples, the inner cover member
15 **200** is not permanently fixed on the forward end **2** covering the sensor/emitting face **410**. For example, the inner cover member can be configured for being in overlying relationship with the common aperture only once the outer radome member has been removed, and prior to this the inner cover member is retracted away from the common aperture; for example, the inner cover member can be made from two or more parts that
20 are movable (for example hinged), so that in the retracted configuration they can be moved out of alignment with the common aperture, and when the radome is removed, or about to be removed, the parts are moved into engagement to form a contiguous inner cover member in alignment with the common aperture. In another example, the inner cover member is in one piece and is movable from a retracted position in which the
25 inner cover member is out of alignment with the common aperture, to an overlying position in which the inner cover member in alignment with the common aperture.

In some alternative variations of the above examples, the inner cover member **200** is in overlying relationship only with respect to the aperture of the optical unit(s). in such examples, the inner cover member is thus substantially transparent to
30 electromagnetic (EM) radiation of at least a first wavelength range, and configured for

being mounted in overlying relationship with respect to the aperture(s) of the components of the instrument package that operate within said first wavelength range.

In such cases, the inner cover member **200** does not need to be transparent to the operating wavelengths λ_{RF} of the RF unit **440**.

- 5 In general the inner cover member **200** needs to be transparent to the operating wavelengths λ_{RF} of the RF unit **440**, when the inner cover member **200** is in overlying relationship with the common aperture or at least with the aperture of the RF unit **440** and where it is desired to operate the RF unit **440** and the EO unit **420** concurrently.

10 In the method claims that follow, alphanumeric characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any particular order of performing the steps.

Finally, it should be noted that the word “comprising” as used throughout the appended claims is to be interpreted to mean “including but not limited to”.

15 While there has been shown and disclosed examples in accordance with the presently disclosed subject matter, it will be appreciated that many changes may be made therein without departing from the spirit of the presently disclosed subject matter.

CLAIMS:

1. A seeker head for an air vehicle comprising a cover assembly and an instrument package,

the cover assembly comprising an inner cover member and an outer radome member, said inner cover member and said outer radome member being associated with a common aperture, and wherein:

said inner cover member is substantially transparent to electromagnetic (EM) radiation of at least a first wavelength range;

said outer radome member is configured for selectively and reversibly covering the inner cover member and transparent to EM radiation of at least a second wavelength range different from said first wavelength range, the second wavelength range including a radio frequency (RF) wavelength range;

said outer radome member being configured for being initially in overlying relationship with respect to said inner cover member and for being selectively removed from said overlying relationship with respect to said inner cover member at least during flight conditions;

said outer radome member being in overlying relationship with respect to said common aperture when said outer radome member is mounted in overlying relationship with respect to said instrument package;

the instrument package comprising:

- at least one first sensing/emitting unit configured for operating in said first wavelength range via emission/reception of EM radiation in said first wavelength range through at least said inner cover member via said common aperture;
- at least one second sensing/emitting unit configured for operating in said second wavelength range, via emission/reception of EM radiation in said second wavelength range through at least said outer radome via said common aperture.

2. The seeker head according to claim 1, wherein there is a lack of overlap between said first wavelength range and said second wavelength range.
3. The seeker head according to any one of claims 1 to 2, wherein said first wavelength range includes wavelengths corresponding to at least one of: the visible spectrum; infra red (IR) spectrum; ultraviolet (UV) spectrum.
4. The seeker head according to any one of claims 1 to 3, wherein said second wavelength range includes RF wavelengths corresponding to at least one of: L-band, S-band, C-band, X-band, K-band, V-band, W-band, Multi-band, Y-band.
5. The seeker head according to any one of claims 1 to 4, wherein said inner cover member is further substantially transparent to EM radiation of said second wavelength range.
6. The seeker head according to any one of claims 1 to 5, wherein the inner cover member is made from a material transparent to said radiation of at least said first wavelength range.
7. The seeker head according to any one of claims 1 to 6, wherein the inner cover radome cover is made from any one of: Silicon, Silicon oxide (SiO), or other Silicon-based materials; Copper oxide (CuO); Manganese Oxide (MnO); Germanium; Sapphire; Magnesium aluminate spinel (MgAl_2O_4); Yttria; AlON ($\text{Al}_{23}\text{O}_{27}\text{N}_5$); Alumina; YAG, Nd:YAG; plastic; glass; composite materials; transparent spinel.
8. The seeker head according to any one of claims 1 to 7, wherein the outer radome cover is made from a material transparent to said radiation of said second wavelength range.
9. The seeker head according to any one of claims 1 to 8, wherein the outer radome cover is made from any one of: Slip Cast Fused Silica; ceramic materials; composite materials such as for example quartz-based composite materials; Teflon; some plastics; Ultem; fiberglass; PTFE-coated fabrics; boron carbide, alumina, glass, silicon carbide.

10. The seeker head according to any one of claims 1 to 9, wherein the inner member is formed as a transparent dome.

11. The seeker head according to any one of claims 1 to 10, wherein the outer member has an ogive form.

12. The seeker head according to any one of claims 1 to 11, wherein said outer radome member is reversibly engageable with respect to the inner cover member.

13. The seeker head according to any one of claims 1 to 12, wherein the outer radome member is formed from a plurality of radome segments, wherein in said overlying relationship with respect to the inner cover member said radome segments are mutually engaged together, and wherein said outer radome member is selectively removable from said inner cover member by mutually disengaging said radome segments.

14. The seeker head according to any one of claims 1 to 13, wherein said radome segments are reversibly connected to one another along longitudinal edges thereof when mutually engaged together.

15. The seeker head according to any one of claims 1 to 14, wherein said radome segments are held together via explosive bolts, which are configured for being selectively activated to separate the radome segments from one another.

16. The seeker head according to any one of claims 1 to 15, wherein said radome segments comprise reactive material, wherein upon activation of the reactive material, a mechanical connection between said radome segments is weakened or destroyed, enabling said radome segments to become separated from one another.

17. The seeker head according to any one of claims 1 to 16, wherein the cover assembly is configured for use with a seeker head accommodating the instrument package, and wherein at least the inner cover member is configured for being affixed to the seeker head.

18. The seeker head according to any one of claims 1 to 17, further comprising a radome cover for selectively and reversibly covering the outer radome member.

19. The seeker head according to any one of claims 1 to 18, wherein the outer radome member is configured for being concurrently in overlying relationship with respect to the common aperture when initially in said overlying relationship with respect to the inner cover member.

20. The seeker head according to any one of claims 1 to 19,
- wherein each said sensing/emitting unit is adapted for at least one of sensing and emitting energy along a respective sensing/emitting unit line of sight aligned with respect to said common aperture.

21. The seeker head according to any one of claims 1 to 20, wherein said at least one first sensing/emitting unit includes any one of: an imaging camera, CCD, CMOS, configured for video imaging and/or still picture imaging, in any one or more of the visible spectrum, the infra red spectrum (IR), or in the ultraviolet spectrum (UV); a visual unit, an IR sensor, a thermal sensor, a NIR sensor; laser-based module optionally including LADAR or LIDAR; bolometric sensor.

22. The seeker head according to any one of claims 1 to 21, wherein said at least one second sensing/emitting unit includes any one of: a passive RF seeker; an active or semi active RADAR seeker; an RF range sensor; a Doppler radar; a synthetic aperture radar (SAR); passive phased array / passive electronically scanned array (PESA) seeker; active phased array / active electronically steered array / active electronically scanned array (AESA) seeker / DBF (digital beam forming) seeker / proximity sensor; an anti-radiation RF sensor.

23. The seeker head according to any one of claims 1 to 22, further comprising a controller for selectively causing the outer radome member to be removed from said overlying relationship with the inner cover member according to preset criteria.

24. The seeker head according to claim 23, wherein said controller is further configured for concurrently operating said at least one first sensing/emitting unit and said at least one second sensing/emitting unit for at least a predetermined time interval after said outer radome member is removed to thereby synchronize operation of said at least one first sensing/emitting unit with said at least one second sensing/emitting unit.

- 25.** An air vehicle comprising a seeker head as defined in any one of claims 1 to 24.
- 26.** The air vehicle according to claim 25, the air vehicle being any one of an air-to-air missile, an air-to-surface missile, a surface-to-air missile, a surface-to-surface missile, a cruise missile, an anti-missile interceptor, munitions, a gliding bomb, a guided bomb, a rocket, a MK bomb including a homing kit, a UAV.
- 27.** A method for operating a seeker head, comprising
- a) providing a seeker head as defined in any one of claims 1 to 24;
 - b) operating the seeker head to selectively remove the outer radome member from said overlying relationship with the inner cover member according to preset criteria.