

METHOD AND SYSTEM FOR FILLING THERMALLY INSULATED CONTAINERS WITH LIQUID CARBON DIOXIDE

Field of the invention

5 The present invention relates to a method, as well as a system, for filling a container with an amount of liquid carbon dioxide (CO₂) which is partially converted into an amount of solid CO₂ into said container, for the purpose of maintaining one or more products, loaded into said container, at a defined temperature, below a defined temperature, or within a defined
10 temperature range, which temperature or temperature range is below environmental temperature. The invention further relates to a method and a system for providing identification and traceability data determining the container and its loaded one or more products, and for enabling the identification of said container during transport to a particular destination.

15

Background

 In the field of maintaining goods at a defined temperature which is below environmental temperature, in particular for maintaining goods cold or frozen, especially during transport, several different solutions have been
20 proposed in the prior art. Some of these comprise the use of vehicles with integrated freezers or refrigerators. Other solutions are based on the use of thermally insulated containers, supplied with solid CO₂, as is the case in the present invention.

 EP1326046 B1 (Yara International ASA) discloses a multi-coupling
25 system for filling containers, in particular thermally insulated containers, to be supplied with a cryogenic medium such as solid CO₂ (commonly known as dry ice), with liquid CO₂, injected from a liquid source, and which is converted into solid CO₂ upon injection. Typically, a specifically dedicated inner part of such thermally insulated containers comprises a compartment
30 or cell that is dedicated to containing the cryogenic medium, e.g. solid CO₂, by separating it from the product transported inside the thermally insulated container.

The amount of solid CO₂ to be supplied to a container is typically calculated based on the required residence time of the loaded one or more products to maintain at a defined temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature. Consequently, the residence time is the time the one or more loaded products are to be maintained in the container at a defined temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature, e.g. during transport of the container.

Typical residence times are 12 hours up to 3 days (i.e. over a weekend, from a Friday morning till a Monday morning), or even longer.

When performing the filling of the container with CO₂, in the prior art is mentioned that the amount of solid CO₂ to be generated is based on the duration of the injection of the liquid CO₂. This is a fairly inaccurate method. When the liquid CO₂, which is stored in a refrigerated form, expands into the cold cell located in the container, this cold cell being specially developed for this purpose, approximately 50 - 60 % of the injected quantity becomes dry ice and approximately 40 - 50 % becomes gaseous CO₂, depending on the pressure within this cold cell. The gaseous CO₂ produced on injection, i.e. 40 - 50 % of the total injected quantity, is extracted via suitable devices in order to prevent an impermissible concentration of the CO₂ in the atmosphere of the working premises.

Therefore, the prior art method of determining the amount of solid CO₂ that is actually supplied to a container upon injection of liquid CO₂ will give rise to large uncertainties due to, for example, pressure and temperature variations during the filling operation.

As soon as the desired quantity of liquid CO₂ is injected into the cooling container, the CO₂ filling process is automatically stopped by a timer in control thereof.

Furthermore, the prior art method will not provide identification and traceability of relevant data for a container filled with CO₂.

Consequently, there exists the need to provide a more accurate way of supplying an amount of solid CO₂ to a thermally insulated container.

Short description of the invention

An example of the present disclosure relates to a method for filling a compartment in an inner part of a container with an amount of liquid CO₂ which is partially converted into an amount of solid CO₂ upon injection of the liquid CO₂ into said compartment, said container being designed to contain one or more products loaded into it, wherein said products are to be maintained at a defined temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature, using said solid CO₂, wherein said container is subjected to a weighing operation using weighing means resulting into a weight of said container, wherein said weight of said container, is determined by said weighing means at least before and after said container has been supplied with said amount of converted solid CO₂.

A first aspect of the present disclosure relates to a method for estimating a remaining residence time of solid CO₂ in a container, comprising: receiving the container with the solid CO₂, wherein the container is configured to contain one or more products; and wherein the products are to be maintained using the solid CO₂ at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature; scanning a machine-readable optical label or connecting to a radiofrequency (RF) transmitter, said machine-readable optical label or said RF transmitter affixed to or included with the container or accompanying packaging; launching application software; accessing unique identification information for the container from the machine-readable optical label or the RF transmitter, said unique identification information residing locally on the machine-readable optical label or the RF transmitter; or residing locally or remotely in a database or a combination thereof, said unique identification information including a tare weight of the container and a standard sublimation rate associated with the container; determining a real-time weight of the solid CO₂ in the container by subjecting the container to a weighing operation using a scale resulting in the real-time weight of the container; calculating the residence time remaining, that the one or more products can be maintained at the defined temperature, below the defined temperature, or within the defined temperature range; said residence time

remaining based, at least in part, on the real time weight of the solid CO₂ in the container and the standard sublimation rate.

A second aspect of the present disclosure relates to a method of preparing a container with solid CO₂ introduced inside the container, wherein the container is adapted to provide an estimate of residence time of the solid CO₂ in the container on a real-time basis, comprising: determining a standard sublimation rate of the container; determining a tare weight of the container; filling an inner part of the container with the solid CO₂ until a fill weight of the solid CO₂ is generated inside the container; wherein the container is configured to contain one or more products; and wherein the products are to be maintained using the solid CO₂ at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature; affixing to or including within the container or associated packaging a machine-readable optical label or RF transmitter; inputting into a database or into the machine-readable optical label or RF transmitter or a combination thereof unique identifier information of the container, said unique identifier information of the container comprising the standard sublimation rate, the tare weight of the container, and the fill weight of the container; wherein the standard sublimation rate, the tare weight, and the fill weight can be accessed by application software upon scanning the machine-readable optical label or connecting to the RF transmitter; said application software configured to calculate the (i) residence time of the solid CO₂ in the container based on the tare weight, the fill weight, and the standard sublimation rate, or the (ii) remaining residence time based on the tare weight, the standard sublimation rate and the weight of the solid CO₂ remaining in the container measured subsequent to the fill weight.

A third aspect of the present disclosure relates to a method for estimating a remaining residence time of a refrigerant in a container, comprising: receiving the container with the refrigerant, wherein the container is configured to contain one or more products; and wherein the products are to be maintained using the refrigerant at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature; scanning a machine-readable optical label or connecting to a RF transmitter, said machine-readable optical label or said RF transmitter affixed to or included with the container or associated

packaging; launching application software; accessing unique identification information for the container from the machine-readable optical label or the RF transmitter, said unique identification information residing locally on the machine-readable optical label or the RF transmitter, or residing locally or remotely in a database or a combination thereof, said unique identification information including a tare weight of the container and a standard refrigerant evaporation rate associated with the container; determining a real-time weight of the refrigerant in the container by subjecting the container to a weighing operation using a scale resulting in the real-time weight of the container; calculating the residence time remaining, that the one or more products can be maintained at the defined temperature, below the defined temperature, or within the defined temperature range; said residence time remaining based, at least in part, on the real time weight of the refrigerant in the container and the standard refrigeration evaporation rate.

A fourth aspect of the present disclosure relates to a method of preparing a container with refrigerant inside the container, wherein the container is adapted to provide an estimate of residence time of the refrigerant in the container on a real-time basis, comprising: determining a standard refrigerant evaporation rate associated with the container; determining a tare weight of the container; filling an inner part of the container with the refrigerant until a fill weight of the refrigerant is generated inside the container; wherein the container is configured to contain one or more products; and wherein the products are to be maintained using the refrigerant at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature; affixing to or including within the container or associated packaging a machine-readable optical label or RF transmitter; inputting into a database, into the machine-readable optical label or RF transmitter, or into a combination thereof, unique identifier information of the container, said unique identifier information of the container comprising the standard refrigerant evaporation rate, the tare weight of the container, and the fill weight of the container; wherein the standard refrigerant evaporation rate, the tare weight, and the fill weight can be accessed by application software upon scanning the machine-readable optical label or connecting to the RF transmitter; said application software configured to calculate the (i) residence time of the refrigerant in the container based on the

tare weight, the fill weight, and the standard refrigerant evaporation rate, or the (ii) remaining residence time based on the tare weight, the standard refrigerant evaporation rate and the weight of the refrigerant remaining in the container measured subsequent to the fill weight.

5

Further, in another example there is provided a method for filling a container with an amount of liquid CO₂ which is partially converted into an amount of solid CO₂ in said container, for the purpose of maintaining one or more products, loaded into said container, at a defined temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature, wherein said container, optionally loaded with one or more products, is subjected to a weighing operation using weighing means resulting into a weight of said container, wherein said weight of said container, optionally loaded with one or more products, is determined by said weighing means at least before and after said container has been supplied with said amount of converted solid CO₂.

The inventive method according to the disclosure will contribute to increased accuracy of the determination of the amount of solid CO₂ supplied to the container, compared to prior art methods and systems. This leads to less CO₂ consumption, and hence to a lower carbon dioxide footprint.

Furthermore, because of a weighing operation, in case of an emergency situation like a power failure, the filling process does not need to

be restarted as is the case in prior art systems, as the data on the amount of liquid CO₂ already filled before the power failure, is not lost.

According to one embodiment, the method comprises the following steps:

- 5 (a) determining the weight of said container, using weighing means;
- (b) generating barcode data by scanning a barcode, provided with the container;
- (c) calculating the weight of the amount of converted solid CO₂ to be supplied to said compartment in the inner part of said container,
- 10 based on said barcode data, generated in step (b);
- (d) filling said container with an amount of liquid CO₂, thereby monitoring the weight of the container, until the weight of the container is equal to the weight of the container, as determined in step (a), increased by the weight of the amount of converted solid CO₂, as calculated in step
- 15 (c);
- (e) storing in a database, the barcode data, obtained in step (b); and
- (f) storing in said database, data on the weight of the amount of converted solid CO₂, supplied to said container, as determined in step (c).

20 Particularly, the invention relates to a method for filling a container with an amount of liquid CO₂ which is partially converted into an amount of solid CO₂ in said container, for the purpose of maintaining one or more products, loaded into said container, at a defined temperature, below a defined temperature, or within a defined temperature range, which

25 temperature or temperature range is below environmental temperature, comprising the following steps :

- (a) determining the weight of a container, optionally loaded with one or more products, using weighing means, in particular by placing the container, optionally loaded with one or more products, on a weighbridge;
- 30 (b) generating barcode data by scanning a barcode, provided with the container, said barcode data describing, for example, the type of said container, the type of said loaded one or more products, the required

residence time of the one or more products in said container and the destination of said container;

- (c) calculating the weight of the amount of solid CO₂ to be supplied to the container, based on said barcode data, generated in step (b), in particular
5 based on the required temperature of said container, the nature of said loaded one or more products and the required residence time of said loaded one or more products;
- (d) filling said container with an amount of liquid CO₂, thereby monitoring the weight of the container, until the weight of the container is equal to the
10 weight of the container, as determined in step (a), increased by the weight of the amount of solid CO₂, as calculated in step (c);
- (e) storing in said database, said barcode data, obtained in step (b); and
- (f) storing in said database, data on the weight of the amount of solid CO₂ supplied to said container, as obtained in step (d).

15 This method will also provide identification and traceability data determining the container and its loaded one or more products that will enable the identification of said container during transport to a particular destination and that will enable reviewing its history and building statistical data for later review.

20 According to one embodiment, the container is a thermally insulated container.

According to one embodiment, the container may be empty or may already be loaded with one or more products, when subjecting the container to the method according to the invention.

25 According to one embodiment, data on the weight of the amount of solid CO₂, supplied to said container, comprise the weight of the amount of liquid CO₂, injected into said container, the weight of the amount of solid CO₂, and the date and time of the filling operation.

Furthermore, it should be noted that the order of the method
30 steps, as recited above, may be executed in any order, as long as step (c) follows after step (b), step (d) follows after step (a) and step (c), step (e) follows after step (b) and step (f) follows after step (d). With the wording

"follows after" it is meant that a step A is executed after a step B, either immediately after, or with one or more intervening step.

5 The invention is also related to a system for performing the inventive method as described above.

 The invention concerns a system for filling a compartment in an inner part of a container with an amount of liquid CO₂, which is partially converted into an amount of solid CO₂ upon injection of the liquid CO₂ into
10 said compartment, said container being designed to contain one or more products loaded into it, wherein said products are to be maintained at a defined temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature, using said solid CO₂, wherein said system
15 comprises weighing means for subjecting said container to a weighing operation resulting into a weight of said container at least before and after said inner part of said container has been supplied with said amount of converted solid CO₂.

20 In one embodiment, the system comprises:

- weighing means, capable of determining the weight of said container;
- a barcode scanner, capable of scanning a barcode, provided with said container for generating barcode data;
- 25 - calculating means, capable of calculating the weight of the amount of converted solid CO₂ to be supplied to said compartment in the inner part of the container, based on said barcode data; and
- filling means, capable of filling said compartment in the inner part of said container with an amount of liquid CO₂ which is at least partially
30 converted into solid CO₂ upon injection of the liquid CO₂ into said compartment, thereby monitoring the weight of the container, until the weight of the container is equal to the weight of the container as previously determined, increased by the weight of the calculated amount of converted solid CO₂; and

- a database, capable of storing said barcode data, and data on the weight of the amount of converted solid CO₂, supplied to said compartment in the inner part of said container.

5 **Brief description of the drawings**

Figure 1 shows an example of a setup used for performing the method according to the invention;

Figure 2 shows an overview of the different components comprised in the system according to the invention for enabling registration of traceable data;
10 and

Figure 3 shows an example of a control panel used for controlling the filling process according to the invention.

Detailed description of the invention

15 The invention will now be described in detail with reference to the drawings. The detailed description contemplates the features, aspects and embodiments in various permutations and combinations, as being within the scope of the disclosure. The disclosure may therefore be specified as comprising, consisting of or consisting essentially of, any of such
20 combinations and permutations of these specific features, aspects, and embodiments, or a selected one or ones thereof.

A particular purpose of the present invention is maintaining goods cold or frozen for a specific period of time. Goods to be kept cold or frozen can be different types of products like for instance food, pharmaceutical
25 products and biological products. Such products will typically have an expiration date and must be kept at a specific low temperature prior to said expiration date. In order to comply with this requirement during loading from a facility, as well as shipping and transport to a destination, the products are stored in a compartment of a thermally insulated container **100**, supplied
30 with a specific amount of solid CO₂. According to the invention, the injected amount of liquid CO₂ is weighted in order to increase the accuracy of the determination of the amount of solid CO₂ and to avoid the disadvantages in the filling process, known from prior art systems. It should be understood

that container 100 can mean any storage, filling, delivery or transportable vessel capable of receiving solid CO₂ or CO₂ fluid and capable of receiving one or more products, including but not limited to cylinders, dewars, bottles, tanks, barrels, bulk tanks and microbulk tanks.

5 Another purpose of the invention is enabling identification and traceability of a container **100** during transport to a destination, together with the amount of CO₂ filled.

Figure 1 shows an embodiment of a setup, used for performing the inventive method for filling a compartment **101** of a thermally insulated
10 container **100** with a specific amount of CO₂ for the purpose of maintaining its content frozen or cold.

For performing the method, the system comprises a thermally insulated container **100** with an inner compartment **101** (in Figure 1, several containers **100** are shown), a weighing scale **200** generating weighing data,
15 weight display means **250** displaying said weighing data, a barcode scanner **300** for scanning a barcode **150** related to one or more containers **100** and generating barcode data, control means **450** comprising a database **451** for storing said barcode data and weighing data, as well as calculation means **452** for calculating the weight of the amount of solid CO₂ to be supplied, and
20 a filling gun **400**, connected to a supply of liquid CO₂ **350** for filling liquid CO₂ into each container **100**. It should be understood that as used herein and throughout, a barcode is intended to include any type of barcode, including linear barcodes and two-dimensional barcodes, such as a QR code.

The weighing scale **200** is connected to the weight display means
25 **250** which in turn is connected to the database **451**. The connection can be wired or wireless by known means and protocols, e.g. Ethernet, WiFi, HTTPS, RS232, GSM, FTP etc.

When filling a container with liquid CO₂, a filling gun **400**,
connected to a supply of liquid CO₂, is attached to the container **100**. The
30 filling gun **400** is connected to the control means **450** for controlling the amount of liquid CO₂ to be filled, based on calculated and measured weight of solid CO₂. The control means **450** is a computer controlling opening and closing of a valve in the filling gun **400**. The amount of liquid CO₂ to be filled

in each container **100** is thus based on the calculated weight of solid CO₂ to be supplied to the respective container **100** and measured weight of the container **100** that is being filled with liquid CO₂ that at least partially converts into solid CO₂ when in this container **100**.

5 The functions and operations of the different devices comprised in the system will now be further described with reference to the inventive method.

 The inventive method comprises several steps to be performed. The method is typically performed when an order is received regarding
10 products to be transported from a storage or production facility to a specific destination, e.g. a store or a shop.

 The first step in the method is embodied by placing a container **100** on a weighing scale **200**. The number of containers **100** placed on the weighing scale **200** can range from 1 to 4, and will typically be 3 to 4
15 containers **100**. Prior to placing a container **100** on the weighing scale **200**, they may be loaded with goods or products.

 In one embodiment, the type of weighing means **200** used is a weighbridge, as shown in Figure 1. In another embodiment, the weighing means **200** is a wheel weight (not shown in the figures). In yet another
20 embodiment, the weighing means is a suspended spring weight (not shown in the figures). The type of weighing means **200** used will depend on the specific requirement or setup at the loading facility.

 Each container **100** to be shipped is provided with a barcode **150** describing at least the type of container **100**, the type of loaded one or more
25 products, the required residence time of the one or more products in said container, and the destination of the container **100**.

 The next step in the method is scanning each barcode **150** of the at least one thermally insulated container **100** by means of a barcode scanner **300** and thereby generating barcode data.

30 The generated barcode data is transferred and stored in a database **451**. The barcode data is transferred to the database **451** via known means, i.e. via cable or wireless. In one embodiment of the invention,

the database **451** is accessible through a dedicated secured interface, e.g. a secured Internet website.

The scanning of a barcode of a container **100** can be performed in the loading process of loading a container **100** onto the weighing scale **200** or after a container **100** has been loaded on the weighing scale **200** and the weight of the container **100** has been determined. Hence the steps of (a) determining the weight of a container **100**, optionally loaded with one or more products, using weighing means **200**; and (b) generating barcode data by scanning a barcode **150**, provided with the container **100**, are interchangeable and/or are interchanged.

The next step in the inventive method is calculating the amount of CO₂ to be filled in the container **100** based on the barcode data, for example, on the temperature to be maintained in each container **100** during the time of transportation to its destination, i.e. the loading time of the products. The total amount of the liquid CO₂ to be filled is based on the total weight of solid CO₂ to be supplied to a container **100** for maintaining its content at a defined temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature during the whole transportation period.

In addition to the transportation time, another input parameter in the calculation of the amount of CO₂ is the environmental temperature of the surroundings where the container will be located during transport.

The thermodynamic principle used will now be explained, wherein:

formula	$Q =$	$k * S * \Delta T * t * \alpha$	$=$	$m * L$
heat quantity		Q	J	
heat exchange overall coefficient		k	W/m ² .K	
surface		S	m ²	
temperature difference		$\Delta T = \theta_{ext} - \theta_{int}$	K	
transport duration		t	s	
insulation thickness		e	m	
insulation thermal conductivity		λ	W/m.K	
CO ₂ values				
snow potential energy	L		640 kJ/kg	
Safety coefficient	α		1	
		to establish during test period		

The amount of energy Q, defined as heat quantity, is calculated in order to determine the amount of CO₂, necessary to compensate for this amount of energy Q, lost through the walls of a given thermally insulated container **100** during a given time, and for a given temperature difference. The amount of CO₂ allows a container **100** to maintain its internal temperature at a defined temperature, below a defined temperature, or within a defined temperature range.

Heat exchange overall coefficient k is a technical data given by the manufacturer of the container **100**. It depends on the insulation product used (e.g. polystyrene, polyurethane, etc.). Heat exchange overall coefficient k is linked to insulation thickness and component thermal conductivity.

Surface S is the total internal surface of the thermally insulated container (m²), exposed to the environmental temperature.

ΔT is the difference between the environmental temperature θ_{ext} and the internal temperature θ_{int} . The internal temperature θ_{int} is determined by the products to be transported. Most of these product storage temperatures are determined according to established European or local directives, regulations or best practices. The environmental temperature θ_{ext}

is determined by an operator each day or can be determined by a weather station, located at the site of the operator, e.g. NETATMO weather station. Hence, according to one embodiment, the environmental temperature can be based on a temperature measurement or can be any temperature value,
5 determined by an operator. It is worth noting that solid CO₂ (dry ice) has a temperature of -109.3 °F (-78.5 °C) at 1 atmosphere. Hence, the internal temperature can never be set lower than said temperature.

The environmental temperature can be modified by an operator with an "adjustment factor" representing a percentage between early
10 morning and afternoon seasonal average variation. Usually, containers **100** for holding goods are prepared early in the morning and are transported within the following day, depending on the distance between the preparation area and the delivery point. The environmental temperature will typically be higher in the middle of the afternoon. Said "adjustment factor" will thus add a
15 standard percentage to the early morning environmental temperature. For instance, if the environmental temperature early in the morning is 22 °C, an adjustment factor of +30 % means that the maximal environmental temperature of the day will be around 28.6 °C. Using the system of Figure 3, an operator can also use + or – signs (see Figure 3) to increase or decrease
20 the adjustment factor with his weather knowledge.

Hence, in one embodiment of the method according to the invention, the environmental temperature is based on a temperature measurement, adjusted with an adjustment factor.

In yet another embodiment, the environmental temperature used
25 for calculation is manually set, for example, by an operator. A scenario where this is relevant is when the difference between the selected environmental temperature and the measured environmental temperature is too high, i.e. greater than a set level. The set level may, for instance, be 5 °C. If this is the case, an alarm will be triggered, or notification will be given
30 via the control screen (see Figure 3). An operator can then manually change the value of the temperature to be used in the calculation of the amount of CO₂.

Time t is determined by a guarantee of a total transport time (for instance 48 hours) or a guarantee until an arrival time (for example, the products are prepared on day A and, for instance, delivery is planned to be made on day B at 13:00).

5 Usually, a safety coefficient α is further added to adjust the thermodynamic formula to take into account, for instance, the aging of the thermally insulated containers. This safety coefficient is adapted on a container- by-container basis, for instance based on the operators' knowledge and/or the results of a quality campaign.

10 When the temperature to be used in the calculation is determined, the calculation of the amount of CO₂ based on the weight of the container **100**, optionally loaded with one or more products, will be done. The calculation itself is based on a well-known thermodynamic calculation and further details will not be described here.

15 After the amount of the solid CO₂, to be supplied to a container **100**, has been calculated, the next step in the method is filling said container **100** with an amount of liquid CO₂, thereby monitoring the weight of the container, optionally loaded with one or more products, until the weight of the container **100** is equal to the weight of the container **100**, as determined
20 by weighing using said weighing means **200**, increased by the weight of the calculated amount of solid CO₂. Filling will start once the filling gun **400** has been connected to a container **100** and will stop once the calculated weight of the CO₂ for that container **100** has been reached.

 If the filling fails due to, for instance, an emergency stop, e.g. a
25 filling gun **400** off hook signal or a too high level of CO₂ in the area, the system will remember the last weight value and an operator can restart the filling process to reach the calculated amount of solid CO₂, starting from said last weight value. This is a big advantage compared to filling methods known from the prior art in which filling will be halted.

30 Prior to filling each container **100**, the weight can be reset. Hence, the weight of the container **100**, optionally loaded with one or more products, is monitored until the weight of the container **100** is equal to the weight of

the container, as determined by weighing (but reset to zero), increased by the weight of the calculated amount of solid CO₂.

The weight of the amount of solid CO₂ supplied to a container **100**, as well as the date and time of filling/weighing is registered into said database **451** together with its barcode data. The weight of each container **100** will then be traceable together with the other barcode data for each container **100**.

Figure 2 shows an overview of the different components that may be comprised in the system for providing identification and traceability data, determining the container **100** and its loaded one or more products, and for enabling the identification of said container **100** during transport to a particular destination.

Figure 2 illustrates the principle enabling full traceability for both the supplier and the customer of the loaded products. The main component in this set-up is the dosing system **305** where all relevant data regarding registered/scanned containers **100** are stored in a database **451**.

The main inputs to the system comprising the database **451** are barcode data, generated by the barcode reader **300**, and weight data, measured by the weighing scale **200**. In one embodiment, the generated barcode data is transmitted from a barcode scanner **300** with a built-in wireless transmitter **301**. In another embodiment, scanned data is sent from the barcode scanner **300** with wired means and interface **302**, e.g. RS232.

All data **303** identifying a container **100**, are traceable from an external server **304**. Customers may log on to the database **451** for tracing relevant parameters for their containers **100** with ordered products.

Figure 3 shows an example of a control panel **500** used for controlling the system and the filling process. The panel is located at the loading facility of the thermally insulated containers **100**.

As mentioned above, the system can be operated automatically, based on direct environmental temperature data (shown on display **506**), or an operator can manually override the environmental temperature, used in the calculation of the amount of solid CO₂ to be supplied to each cabinet.

The type of container **100** used, the type of product transported, the desired temperature **505** inside the container **100**, and the time period for maintaining a product frozen or cold, can be selected from different default programs **507**. By inputting a code on a number pad **501**, an operator
5 can select such a specific program. The control panel can also be used for making tailor-made programs for specific needs.

By pressing the sun sign (**502**, right upper area), the temperature used in the calculations will increase, and by pressing the cloud sign (**503**, right upper area), the temperature will decrease. Relevant selected
10 information will be displayed on a display panel **504**.

The following describes an example of a typical user scenario when using the system and method according to the present invention. An operator of the system receives an order for a product and loads one or more containers **100** with the ordered product. This may, for instance, be
15 frozen fish to be transported to a food shop at a distance with a travel time of 6 hours (the residence time is at least equal to the travel time). The specific food shop may or may not already be registered in the system, for example, after having placed a previous order. If it is already registered, returned containers **100** used in a previous shipment, are already provided
20 with barcodes **150** identifying the products and the customer. If it is not registered, new barcodes **150** will be generated with relevant information. According to one embodiment, the barcode data comprises at least data such as the type of container **100**, the type of loaded one or more products, the required residence time of the one or more products in said container
25 **100**, and the destination of the container **100**. Furthermore, it may contain data identifying the customer.

The type of container **100** used, the time to maintaining a product frozen (residence time of the one or more products), and the environmental temperature will directly influence the amount of solid CO₂ to be supplied to
30 the container **100** and hence, the amount of liquid CO₂ to be injected into the container **100**.

Each container **100** with the frozen fish is subsequently loaded onto a weighbridge **200**. This operation is typically performed by means of

an order picker forklift placing 3 to 4 containers **100** on the weighbridge **200**. The frozen fish may also be loaded into the containers **100** after the containers **100** have been loaded onto the weighbridge **200**.

5 The barcodes **150** on the containers **100** are scanned and the barcode data is registered in the database **451** providing online access for the customer. Based on the barcode data and the selected environmental temperature (either determined by measurement or manually set), the amount of solid CO₂ to be supplied to each container **100** is calculated. The weighbridge **200** may be reset before filling each container **100** such that
10 only the weight of the solid CO₂ is shown.

An operator or a robot will then connect the filling gun **400** to the container **100** to be filled, and filling is performed while the amount of solid CO₂ is measured. When the calculated amount of CO₂ has been reached, as determined from the weighing operation, the control means **450** controlling
15 the filling gun **400** will stop the filling and the actual weight of solid CO₂ will be registered in the database **451** together with the date and the time of filling and the relevant barcode data for the filled container **100**. The same injection operation will be performed on the next container **100** until all containers **100** on the weighbridge **200** are filled.

20 The invention further relates to the system for performing the method as disclosed above. Furthermore, the invention relates to a system for filling a container **100** with an amount of CO₂, which is partially converted into an amount of solid CO₂ in said container, for the purpose of maintaining one or more products, loaded into said container **100**, at a defined
25 temperature, below a defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature, said system comprising weighing means for subjecting said container **100** to a weighing operation resulting into a weight of said container.

30 Moreover, the invention relates to a system for filling a container **100** with an amount of CO₂, which is partially converted into an amount of solid CO₂ in said container **100**, for the purpose of maintaining one or more products, loaded into said container **100**, at a defined temperature, below a

defined temperature, or within a defined temperature range, which temperature or temperature range is below environmental temperature, said system comprising:

- weighing means **200**, capable of determining the weight of said container **100**;
- a barcode scanner, capable of scanning a barcode **150**, provided with said container **100** for generating barcode data;
- calculating means, capable of calculating the weight of the amount of solid CO₂ to be supplied to the container **100**, based on said barcode data; and
- filling means **400**, capable of filling said container **100** with an amount of liquid CO₂ that at least partially converts into solid CO₂ into said container **100**, thereby monitoring the weight of the container **100**, until the weight of the container **100** is equal to the weight of the container previously determined, increased by the weight of the calculated amount of solid CO₂; and
- a database **100**, capable of storing said barcode data, and data on the weight of the amount of solid CO₂, supplied to said container **100**.

The invention further relates to a method of estimating a residence time remaining of solid CO₂ in a container **100**. A user or recipient (e.g., final recipient such as a customer or intermediate recipient such as a distributor) of the container **100** can receive the container **100** with the solid CO₂ contained therein. The container **100** is designed to be capable of receiving and storing one or more products. The products are to be maintained using the solid CO₂ at a defined temperature, below a defined temperature, or within a defined temperature range. As used herein and throughout, “defined temperature” or “defined temperature range” is a suitable temperature or temperature range of a container **100** that has a temperature or temperature range below an environmental temperature, in which the defined temperature or defined temperature range is sufficient to maintain preservation for a certain duration of one or more products loaded or to be loaded into the container **100**.

A machine-readable optical label such as a barcode **150** or QR code that is included with the container **100** or associated packaging is scanned by a scanner. The machine-readable optical label can be read by a

smartphone or another dedicated reader to determine unique identification information of the container **100**. The machine-readable optical label is included with the container **100** such that the machine-readable optical label can be located anywhere on the outside or inside of the container **100** or
5 associated packaging.

Alternatively, the container **100** may include a radiofrequency (as used herein, "RF") transmitter, such as a RF tag (e.g., RFID tag), Bluetooth tag or near-field communication (NFC) tag. In one example, the RF transmitter is a NFC tag, which requires close proximity to the NFC reader.
10 In another example, the RF transmitter is a RF tag, which can operate over longer ranges than NFC tags. The exact type of RF tag to use can depend on the specific operational ranges required. The RF transmitter can be read by a RF reader, such as a smartphone, other cloud connected device or a purpose-built, cloud connected RF device to identify the unique identification
15 information of the container **100**. "Cloud connected device" such as a "cloud connected RF device" means any digital device that can be used to read data related to the container and then transmit the data to a cloud database, where the data can be stored. Examples include cameras, RF gateways, scales and smartphones. "Cloud database" as used herein is intended to
20 mean a digital repository of information for individual containers that contains specific attributes of the individual containers, in which the digital repository of information can be appended or modified as information related to the individual containers is collected over time. The RF transmitter can relay a RF transmission that is received by the RF reader.

25 The machine-readable optical label or RF transmitter can be attached to the container **100** or accompanying packaging. Either the scanning of the machine-readable optical label or connecting to the RF transmitter allows the container **100** to be recognized and specifically identified, such that certain application software can be launched upon the
30 scanner or RF reader, respectively, linking to the application software. The application software accesses unique identification information for container **100**, preferably through a dedicated secured internet website. The unique identification information of container **100** includes, but is not limited to, a

tare weight of the container **100** and a standard sublimation rate associated with the container **100**. Generally speaking, the standard sublimation rate defines the expected rate at which the solid CO₂ in the container **100** is converting or sublimating into vapor. The standard sublimation rate in one
5 example is determined by a supplier of the container **100** prior to transport of the container **100** filled with solid CO₂ to the user or recipient.

The unique identification information can be stored on the machine-optical label or the RF transmitter and/or locally or remotely in a database. The database can be, by way of example, maintained and stored
10 in a cloud database. For example, a serial identification number or model number for container **100** may be locally accessed by application software while other unique identification information of container **100** is remotely accessed by application software from a database. The container **100** is placed on the scale after the scale has been tared. A real-time weight of the
15 solid CO₂ in the container **100** is determined by subjecting the container **100** to a weighing operation using a scale (e.g., weighing scale 200) resulting in the real-time weight of the container **100**.

After identifying the unique container **100**, which can be based on unique information retrieved through the machine-readable optical label or
20 RF transmitter, and having subject the container **100** to the weighing operation, the application software determines the remaining residence time for the solid CO₂ in the container **100** as follows:

$$D = (W(t) - W_{tare})/R_s$$

where, D (days) is the remaining residence time of the solid CO₂ in the
25 container **100**, W(t) (lbs) is the real-time weight of the solid CO₂ in the container **100** that is being measured at time t by subjecting the container **100** to the weighing operation using the scale, W_{tare} (lbs) is the weight of the container **100** itself and R_s (lbs/day) is the standard sublimation rate of the solid CO₂ in the container **100**. W_{tare} and R_s, both of which form, at least a
30 portion of a particular container's **100** unique identification information, have been previously inputted (i) locally into the machine-optical label, or the RF transmitter or (ii) locally or remotely into a database. In one example, W_{tare} and R_s are inputted by a supplier of the container **100**, where the supplier

initially introduces solid CO₂ into the container **100** until a fill weight, W_{fill} , is created therein. It should be noted that W_{fill} has been previously added into a database. The application software can access such unique identification information at (i) or (ii).

5 It should be understood that the method of the present invention can be utilized by any recipient or user having a need to periodically monitor the remaining residence time of the solid CO₂ in the container **100**. The monitoring can occur prior to or during transport or upon arrival of the container **100** to a specific destination. The supplier of the container **100**
10 may receive notification when a user or recipient of container **100** has performed a real-time weight measurement.

 The real-time weight determination may also occur with one or more products inside of container **100**. Alternatively, or in addition thereto, the step of determining the real-time weight of the solid CO₂ in the container **100** ($W(t)$) may
15 include subjecting the container **100** to the weighing operation in a presence of accompanying packaging or accessories using the scale and resulting in the real-time weight of the container **100**, products therein, and the accompanying packaging or the accessories. Examples of accessories can include various components of container **100**, such as, by way of example, a cap, a temperature
20 monitor or temperature device probe affixed to the container **100** or a sample holder within container **100**. Additionally, accessories can include return labelling or other instructions of use provided with container **100**. Accompanying packaging can include, but is not limited to, the shipping box (e.g., cardboard box) into which the container **100** is placed during transport. As used herein and
25 throughout, it should be understood that when products or accompanying packaging or accessories are included in the measurement of the real-time weight W_t , the tare weight W_{tare} includes those same products or accompanying packaging such that the difference $W_t - W_{tare}$ yields the weight of the solid CO₂ dry ice in the container at time t . Preferably, the supplier of the container **100**
30 receives notification when a user or recipient of container **100** has performed a real-time weight measurement with one or more products loaded into container **100**.

Any suitable device may be utilized for hosting the application software such as by way of example, a smart phone, smart scale, dedicated scanner, RF reader (examples of which have been provided hereinbefore) or computer terminal. The device is in a wired or wireless communication with a network and a server. Alternatively, the application software can be located on the scale that is used to perform the real-time weight measurement of the solid CO₂ in the container **100** that is being measured at time t.

The inventive method in another aspect includes an automatic notification system that is configured to send one or more notification alerts to one or more users or recipients when certain conditions are triggered. For example, an alert can be transmitted when the measured real-time weight of the solid CO₂ is greater than the fill weight of the solid CO₂. Such a notification alert that the real-time weight is greater than the fill weight can indicate a potential operational or system error has occurred (e.g., the weight measurement has been performed incorrectly). The notification alert can be transmitted to one or more recipients of container **100** to repeat the weight measurement to eliminate the potential of an operational error where, by way of example, the weight measurement has been performed incorrectly. The term 'fill weight' of the solid CO₂ as used herein is defined as the weight of the solid CO₂ after the most recent filling of the container **100** with an initial amount of the solid CO₂. Preferably, the fill weight is a value that is previously determined by a provider of the container **100** (e.g., by a supplier of the container **100** that has preferably also filled the container **100** with the solid CO₂) and stored in a local or remote database accessible by the application software.

Another type of notification alert can be generated when the calculated remaining residence time of the solid CO₂ is less than a specified critical limit. For example, a notification alert can be transmitted to a user or recipient of the container **100** when the remaining residence time of the solid CO₂ in the container **100** is less than one (1) day. In such an instance, the notification alert is a message that instructs the user or recipient of container **100** to return the container **100** to the supplier as a result of the remaining residence time determined to be insufficient for further use (e.g., insufficient for the preservation of one or more products loaded or to be loaded into container **100** at or below a

certain defined temperature or within a defined temperature range).

Alternatively, or in addition thereto, the conditions under which return of the container **100** should occur can be provided as instructions of use, which may be included with the container **100** and associated packaging.

- 5 A notification alert can also be generated when the actual sublimation rate, R_a , is outside a specified tolerance of the standard sublimation rate, R_s , where R_a can be determined as follows:

$$R_a = (W_{\text{fill}} - W(t)) / (T(t) - T_{\text{fill}})$$

- where, R_a is the actual sublimation rate (lbs/day); W_{fill} is the weight of the container **100** after the most recent filling of the container **100** with an initial amount of the solid CO_2 occurring at an initial time T_{fill} ; and $W(t)$ is the real-time weight of the container **100** that is being measured at time $T(t)$ by subjecting the container **100** to the weighing operation using the scale. W_{fill} and T_{fill} are preferably values stored in a database that is accessible locally or remotely by the application software. It should be understood, that the same weight of product and/or accompanying packaging or accessories should be included in W_{fill} and $W(t)$ such that the difference $W_{\text{fill}} - W(t)$ yields an accurate measurement of the amount of solid CO_2 that has sublimated over the time interval $T(t) - T_{\text{fill}}$. A value of R_a greater than a value of R_s can indicate a container **100** that has structurally degraded and the expected solid CO_2 residence time might not be achieved.

- In yet another embodiment of the present invention, a method of preparing a container **100** with solid CO_2 introduced inside the container **100** is provided. The container **100** is configured to contain one or more products; and the products are to be maintained using the solid CO_2 at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature, in which the defined temperature or the defined temperature range is sufficient to maintain preservation for a certain duration of one or more products loaded or to be loaded into container **100**. The method is capable of providing an estimate of residence time of the solid CO_2 remaining in the container **100** on a real-time basis. A standard sublimation rate, R_s , (lbs/day) of a container **100** and a tare weight, W_{tare} (lbs), is determined. Next, solid CO_2 is

filled into an inner part of the container **100** until a fill weight of the solid CO₂ is generated inside the container **100**. It should be understood that solid CO₂ may be filled into the container **100** in any manner, including by transferring solid CO₂ in the form of pellets, nuggets, flakes or slab of dry ice, as well as charging liquid CO₂ from a liquid CO₂ source into the container **100** such that at least a portion of the liquid CO₂ is converted into solid CO₂.

A machine-readable optical label or RF transmitter can be affixed to or included with the container **100** or associated packaging. For example, a machine-readable optical label or RF transmitter can be included with the container **100** such that the machine-readable optical label or RF transmitter can be located anywhere on the outside or inside of the container **100** or associated packaging. Unique identifier information of the container **100** is inputted into a database or into the machine-readable optical label or into a RF transmitter. The unique identifier information of the container **100** comprises, but is not limited to, a standard sublimation rate of the solid CO₂ in the container **100**, a tare weight of the container **100** and a fill weight of the container **100**, all of which can be accessed by application software upon scanning the machine-readable optical label or connecting to the RF transmitter. Other types of unique identifier information may be included, such as by way of example, the manufacturing date of the container **100** and a model number of the container **100**. The application software is configured to calculate the residence time of the solid CO₂ in the container **100** based on the tare weight, the fill weight and the standard sublimation rate. The application software is also configured to calculate the remaining residence time based on the tare weight, the standard sublimation rate and the weight of the solid CO₂ remaining in the container **100** that is measured subsequent to the fill weight. It should be understood that the step of measuring the weight of the solid CO₂ filled into the container **100** or solid CO₂ remaining in the container **100** can be performed in the presence of accompanying packaging or accessories as previously described herein.

Having prepared the container **100** with solid CO₂ introduced (e.g., loaded or charged) inside the container **100**, certain arrangements can made for delivering the container **100** to an intermediate and/or final destination site. In one example, the container **100** with solid CO₂ filled therein is transported by a

commercial carrier such as United Parcel Service (UPS) or Federal Express (FedEx) to the intermediate or final destination site for access or use by a corresponding intermediate recipient or final recipient. Additionally, instructions for use and instructions for handling of the container **100** can also accompany the container **100** during transport.

The step of preparing the container **100** can include assigning an alphanumeric identification (ID) number for the container **100**. The ID number can be stored and maintained on a machine-readable optical label or RF transmitter and/or locally or remotely in a database that is accessible by the application software. The ID is one of the pieces of information that is considered part of the unique identifier information of a container **100**. In one example, the ID is a serial number. The database contains historical information of the container **100**, including weight measurements of the container **100** and the time, location and dates when such weight measurements were performed, along with identification of the type of weight measurement. The type of weight measurement can be a (i) tare weight of container **100**, (ii) a fill weight of container **100**, or (iii) a real-time weight of the container **100** that is being measured subsequent to the fill weight at time t by subjecting the container **100** to a weighing operation using a scale. The historical information of the container **100** can include measurements performed by suppliers, users and recipients of the container **100**. The historical information is preferably accessible by the supplier of the container **100**, but also may be accessible by the recipients and users of the container **100**.

As part of the preparation of container **100**, an actual sublimation rate of the container **100**, R_a (lbs/day) can be determined as previously described herein. The actual sublimation rate can be compared with a standard sublimation rate, R_s , as previously described herein, with certain notification alerts generated should the R_a exceed a specified tolerance of the R_s .

Other methods for identification of the unique identification information of the container **100** by the application software are contemplated. For example, digital image processing techniques can be employed to carry out the present invention. In one example of a digital image processing technique, a dedicated cloud connected device, such as a smartphone camera, can be utilized to

identify the unique identification information. The identification is based on algorithms typically used in applications such as facial recognition, whereby the algorithms recognize and read certain text, numbers and various types of graphics. In particular, the camera-based technique which can be used in the present invention reads a unique alphanumeric or pictographic label on the container **100** or accompanying packaging as the means for identifying the unique identification information.

The present invention contemplates various ways for identifying a container. For instance, the identification process can be performed manually. An example of a manual identification process of a container involves a user using a smartphone to read a barcode. A cellular connection links unique identification information of the container to a cloud database. The identification process can also be done by an automatic process without user intervention. An example of an automated process involves a cloud connected RF scanning device identifying a container that is in close proximity through a RF transmitter on the container. Upon identifying the container, a cloud database is linked to by the RF scanning device or information relating to the container is uploaded into the cloud database by the RF scanning device.

It should be understood that the principles of the present invention are applicable for estimating a residence time remaining of other refrigerants in a container. For example, a recipient (e.g., intermediate or final) can receive the container with refrigerant. The container is configured to contain one or more products; and the products are to be maintained using the refrigerant at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature, in which the defined temperature or defined temperature range is sufficient to maintain preservation for a certain duration of the one or more products loaded or to be loaded into container. A machine-readable optical label is scanned or a RF transmission from a RF transmitter included with the container is received to enable launching of application software as a result of the application software linking to the unique identifier information of the container **100**. The machine-readable optical label and RF transmitter as included with the container can be located anywhere on

the outside or inside of the container and associated packaging. The application software accesses unique identification information for the container from the machine-readable optical label or the RF transmitter. The unique identification information resides locally on the machine-readable optical label or the RF transmitter or remotely on a database. The unique identifier information includes a tare weight of the container and a standard refrigerant evaporation rate associated with the container. A real-time weight of the container is determined by subjecting the container to a weighing operation using a scale, resulting in the real-time weight of the container. The residence time remaining is determined such that the one or more products can be maintained at the defined temperature, below the defined temperature, or within the defined temperature range.

In another embodiment, a method of preparing the container with refrigerant introduced inside the container is provided. The container is adapted to provide an estimate of a residence time of the refrigerant remaining in the container on a real-time basis. A standard refrigerant evaporation rate associated with the container is determined. A tare weight of the container is also determined.

An inner part of the container is filled with the refrigerant until a desired fill weight of the refrigerant is generated inside the container. A machine-readable optical label or RF transmitter is affixed to or included within the container, such that the machine-readable optical label or RF transmitter can be located anywhere along the outside or inside of the container and associated packaging. Unique identifier information of the container is inputted into a database, the machine-readable optical label or the RF transmitter or a combination thereof. The unique identifier information of the container includes, but is not limited to, the standard evaporation rate, the tare weight of the container and the fill weight of the container, all of which can be accessed by application software upon scanning the machine-readable optical label or connecting to the RF transmitter. The application software is configured to calculate the residence time of the refrigerant in the container based on the tare weight, the fill weight, and the standard refrigerant evaporation rate. The application software is also configured to calculate the remaining residence time

based on the tare weight, the standard refrigerant evaporation rate and the weight of the refrigerant remaining in the container that is measured subsequent to the fill weight. It should be understood that the step of measuring the weight of the refrigerant filled into container or refrigerant remaining in the container can
5 be performed in the presence of accompanying packaging or accessories as previously described herein.

In one example, the refrigerant is liquid nitrogen absorbed onto an absorbent. In another example, the refrigerant is helium.

The methods of the present invention allow for real-time assessment of
10 the functional performance of the container. By (i) estimating R_a or an actual evaporation rate, (ii) comparing the R_a or actual evaporation rate of refrigerant with the R_s or standard evaporation rate of refrigerant, and then (iii) determining the R_a or the actual evaporation rate of the refrigerant to be unacceptably higher than the R_s or standard evaporation rate of the refrigerant, the present invention
15 allows for detection of containers that may have structurally degraded and as a result should be removed from operational service; such real-time detection and notification is a benefit not previously provided by containers filled with solid CO_2 or other refrigerants. Additionally, the ability of the present invention to assess on a real time basis the estimated remaining residence time of the solid CO_2 or
20 other refrigerant in the container allows for a more efficient use and management of a fleet of the containers filled with solid CO_2 or other refrigerant, whereby decisions on where to transport the containers can be made by anyone in the supply chain from supplier to final user or recipient, as a result of timely notification alerts provided based on real-time weight measurements of the
25 container being performed. In one example, when the refrigerant is solid CO_2 , and the R_a is determined to fall within an acceptable tolerance of the R_s , containers with less than one (1) day of residence time remaining of the solid CO_2 in the container are recommended by the application software to be returned to the supplier, whereas containers with greater than one (1) day of
30 residence time remaining of the solid CO_2 in the container are deemed functionable (i.e., configured to contain one or more products, wherein the products are to be maintained using the solid CO_2 at a defined temperature, below a defined temperature, or within a defined temperature range, the defined

temperature or the defined temperature range being below an environmental temperature, in which the defined temperature or defined temperature range is sufficient to maintain preservation for a certain duration of the one or more products loaded or to be loaded into a container).

5

CLAIMS

1. A method for estimating a remaining residence time of solid CO₂ in a container, comprising:

receiving the container with the solid CO₂, wherein the container is configured to contain one or more products; and wherein the products are to be maintained using the solid CO₂ at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature;

scanning a machine-readable optical label or connecting to a radiofrequency (RF) transmitter, said machine-readable optical label or said RF transmitter affixed to or included with the container or accompanying packaging;

launching application software;

accessing unique identification information for the container from the machine-readable optical label or the RF transmitter, said unique identification information residing locally on the machine-readable optical label or the RF transmitter; or residing locally or remotely in a database or a combination thereof, said unique identification information including a tare weight of the container and a standard sublimation rate associated with the container;

determining a real-time weight of the solid CO₂ in the container by subjecting the container to a weighing operation using a scale resulting in the real-time weight of the container;

calculating the residence time remaining, that the one or more products can be maintained at the defined temperature, below the defined temperature, or within the defined temperature range;

said residence time remaining based, at least in part, on the real time weight of the solid CO₂ in the container and the standard sublimation rate.

2. The method according to claim 1, wherein the step of determining the real-time weight of the solid CO₂ in the container includes subjecting the container to the weighing operation in a presence of the accompanying packaging or accessories using the scale and resulting in the real-time weight of the container and the accompanying packaging or the accessories.

3. The method according to claim 1, further comprising the steps of confirming (i) the scale is tared and (ii) the container is placed on the scale.

5 4. The method of claim 1, comprising the step of sending an alert when the real-time weight of the container is greater than a fill weight of the container, said fill weight defined as the weight of the container after a most recent filling of the container with an initial amount of the solid CO₂, said fill weight previously obtained and stored in a database of the application software.

10 5. The method according to claim 1, wherein the container is loaded with the one or more products.

15 6. The method according to claim 1, wherein the step of launching the application software further comprises a device hosting the application software.

7. The method according to claim 6, wherein the device is in a wired or wireless communication with a network and a server.

20 8. The method according to claim 1, a notification alert being generated when the calculated residence time remaining is less than a specified critical limit, said notification alert instructing return of the container to a supplier of the container.

25 9. The method according to claim 1, wherein an actual sublimation rate is determined based on a fill weight, the real-time weight, the weight of the one or more products that may be loaded into the container, and a time transpired between the fill weight and the real-time weight, said fill weight defined as the weight of the container after a most recent filling of the container with an initial
30 amount of the solid CO₂, said fill weight previously obtained and stored in a database of the application software.

35 10. The method according to claim 9, wherein a notification alert is generated when the actual sublimation rate is outside a specified tolerance of the standard sublimation rate.

11. The method according to claim 1, wherein data for the real-time weight of the solid CO₂ in the container is stored in a database of the application software.

12. A method of preparing a container with solid CO₂ introduced inside the container, wherein the container is adapted to provide an estimate of residence time of the solid CO₂ in the container on a real-time basis, comprising:

- determining a standard sublimation rate of the container;
- determining a tare weight of the container;
- filling an inner part of the container with the solid CO₂ until a fill weight of the solid CO₂ is generated inside the container;
- wherein the container is configured to contain one or more products; and wherein the products are to be maintained using the solid CO₂ at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature;
- affixing to or including within the container or associated packaging a machine-readable optical label or RF transmitter.
- inputting into a database or into the machine-readable optical label or RF transmitter or a combination thereof unique identifier information of the container, said unique identifier information of the container comprising the standard sublimation rate, the tare weight of the container, and the fill weight of the container;
- wherein the standard sublimation rate, the tare weight, and the fill weight can be accessed by application software upon scanning the machine-readable optical label or connecting to the RF transmitter;
- said application software configured to calculate the (i) residence time of the solid CO₂ in the container based on the tare weight, the fill weight, and the standard sublimation rate, or the (ii) remaining residence time based on the tare weight, the standard sublimation rate and the weight of the solid CO₂ remaining in the container measured subsequent to the fill weight.

13. The method of claim 12, further comprising arranging for delivering of the container to a destination site via a commercial carrier.

14. The method of claim 12, wherein the step of measuring the weight of the solid CO₂ remaining in the container is performed in the presence of accompanying packaging or accessories.

5

15. The method of claim 12, wherein the step of preparing the container further comprises assigning an identification (ID) number for the container into a database of the application software, said ID number forming part of the unique identifier information of the container.

10

16. The method of claim 12, further comprising retrieving historical information of the container, said historical information located in a database.

15

17. The method of claim 12, further comprising receiving notification when the container has been subject to a weighing operation using a scale resulting in a real-time weight of the container and accompanying packaging.

20

18. The method of claim 12, further comprising performing a weight measurement after confirming (i) a weighing scale is tared; and (ii) the container is placed on the weighing scale.

25

19. The method of claim 12, further comprising:
determining an actual sublimation rate;
comparing the actual sublimation rate with the standard sublimation rate; and
sending an alert to inspect the container when the actual sublimation rate is outside a specified tolerance of the standard sublimation rate.

30

20. The method of claim 12, further comprising accessing the database through a dedicated secured Internet website.

35

21. A method for estimating a remaining residence time of a refrigerant in a container, comprising:
receiving the container with the refrigerant, wherein the container is configured to contain one or more products; and wherein the products are to

be maintained using the refrigerant at a defined temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature;

5 scanning a machine-readable optical label or connecting to a RF transmitter, said machine-readable optical label or said RF transmitter affixed to or included with the container or associated packaging;

 launching application software;

 accessing unique identification information for the container from the
10 machine-readable optical label or the RF transmitter, said unique identification information residing locally on the machine-readable optical label or the RF transmitter, or residing locally or remotely in a database or a combination thereof, said unique identification information including a tare weight of the container and a standard refrigerant evaporation rate
15 associated with the container;

 determining a real-time weight of the refrigerant in the container by subjecting the container to a weighing operation using a scale resulting in the real-time weight of the container;

 calculating the residence time remaining, that the one or more
20 products can be maintained at the defined temperature, below the defined temperature, or within the defined temperature range;

 said residence time remaining based, at least in part, on the real time weight of the refrigerant in the container and the standard refrigeration evaporation rate.

25

22. A method of preparing a container with refrigerant inside the container, wherein the container is adapted to provide an estimate of residence time of the refrigerant in the container on a real-time basis, comprising:

 determining a standard refrigerant evaporation rate associated with the
30 container;

 determining a tare weight of the container;

 filling an inner part of the container with the refrigerant until a fill weight of the refrigerant is generated inside the container;

 wherein the container is configured to contain one or more products; and

35 wherein the products are to be maintained using the refrigerant at a defined

temperature, below a defined temperature, or within a defined temperature range, the defined temperature or the defined temperature range being below an environmental temperature;

5 affixing to or including within the container or associated packaging a machine-readable optical label or RF transmitter;

10 inputting into a database, into the machine-readable optical label or RF transmitter, or into a combination thereof, unique identifier information of the container, said unique identifier information of the container comprising the standard refrigerant evaporation rate, the tare weight of the container, and the fill weight of the container;

wherein the standard refrigerant evaporation rate, the tare weight, and the fill weight can be accessed by application software upon scanning the machine-readable optical label or connecting to the RF transmitter;

15 said application software configured to calculate the (i) residence time of the refrigerant in the container based on the tare weight, the fill weight, and the standard refrigerant evaporation rate, or the (ii) remaining residence time based on the tare weight, the standard refrigerant evaporation rate and the weight of the refrigerant remaining in the container measured subsequent to the fill weight.

20