

## Description

The invention relates to punch assemblies used in punch presses.

### BACKGROUND OF THE INVENTION

Repeated use of a punch assembly in a punch press operation results in the natural dulling and wear of the punch tip. Once the tip has become dull, the effectiveness of the punch assembly is reduced and the punch tip must be sharpened. Sharpening may be accomplished by grinding the end of the punch tip, and this results in shortening the length of the punch. The length of the punch then must be adjusted to compensate for the ground-off portion. US-A-3958476 discloses a punching device in which an assembly of a punch, a guide and stripping sleeve is removable from a fixed frame as a unit. The sleeve has a circumferential groove in which there is a radial aperture. A retainer member is disposed in the groove and has a portion that projects radially through the radial aperture into an elongated recess in the punch body. By these means the assembly may be retained together. JP-A-63036934 discloses a punch which includes a detaining means freely installable between a setting means and an engaging part. To obstruct rotation of an adjusting nut against a punch and to improve the reliability of the punch mechanism a side face part of the detaining means engages an engaging part.

Punch assemblies that allow for length corrections are exemplified in U.S. Patent No. Re 29,958. This reference compensates for the lost punch length by adding washers or other similar objects to the punch. The problem with this method is that the added washers or the like are usually weak and cannot withstand the constant cyclical forces placed upon a punch. Also, the length of the punch tip can only be adjusted within certain limits before it becomes too short for effective operation, thereby limiting the number of times the punch tip can be sharpened.

Most known methods that allow for the adjustment of the length of the punch tip require dismantling of the entire punch in order to access the punch tip for adjustment; this obviously can be a rather time-consuming process. Additionally, once the punch has been reassembled further effort is frequently expended in determining how much the sharpening and adjusting steps have affected the position of the tip. A need exists, therefore, for an accurate means of adjusting the length of the punch in a manner that is not overly time consuming or difficult.

### SUMMARY OF THE INVENTION

The present invention provides a readily adjustable punch assembly for use in a punch press. The assembly includes a punch comprising a pair of elongated rods having mating respective male and female threaded

ends, such that the overall length of the punch may be altered by rotating one rod with respect to the other, one of the threaded rods having at its other end a punch tip. The punch is axially slidably received within a bore provided in a punch guide. The punch assembly includes releasable lock means for locking the threaded ends against relative rotation. The lock means is movable between a locked position, in which the threaded rod ends are locked against relative rotation, and an unlocked position, wherein relative rotation of the threaded ends is permitted for adjusting the length of the punch. Position maintaining means are carried by the punch guide and serve to maintain the lock means in its locked position when the punch is operatively positioned in the punch guide.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is an axial cross-sectional view of a punch assembly of the invention before sharpening; FIGURE 2 is an axial cross-sectional view of the punch assembly of Figure 1 with a force imparted on its head; FIGURE 3 is an axial cross-sectional view of the punch assembly of Figures 1 and 2 after sharpening; FIGURE 4 is a cross-sectional view of a lock means of the invention taken along line 4-4 of Fig. 1; and FIGURE 5 is a cross-sectional view of the lock means shown in Figure 4 in its unlocked position.

### DETAILED DESCRIPTION OF THE INVENTION

The principles of this invention relate to the workings of a punch and stripper assembly. Accordingly, the invention is appropriate for the numerous applications concerning punch presses, including, but not limited to, single station and turret presses.

A punch assembly of the present invention is exemplified in Figures 1-3 as comprising a punch (5) having a punch holder (10) and a punch body (20); a locking means (30); and a punch guide (40). In operation, a ram (not shown) strikes downwardly on the head (12) of the punch holder, compressing the compression spring (11) and urging the punch downwardly until the punch tip (22) protrudes below the lower face (48) of the punch guide (40), as shown in Figure 2. The protruding punch tip (22) passes through a workpiece (not shown) of a sheet material and into a die casting (not shown) to punch an item out of the workpiece having the desired shape. The punch assembly is adaptable to a variety of punch tip shapes depending upon the shape desired to be removed from the workpiece. The ram is then retracted, releasing the compressive force on the spring (11). The spring then acts against the head (12), which it abuts, to draw the punch upward. When the punch tip (22) is retracted upwardly through the aperture (44) in the punch guide, the lower face (48) of the guide acts as a "stripper plate," i.e., it engages the workpiece, which

often sticks to the retreating punch, and separates it from the punch tip.

As can be seen in Figs. 1-3, the punch assembly is comprised of individual units joined together. The punch holder (10) consists of an axially elongated shaft terminating in a female threaded end (14). At the opposite end is a head (12) of increased diameter that is axially adjustable in relation to the punch holder (10). The external circumferential surface of the head (12) is textured to facilitate the frictional resistance force required when the head needs to be loosened from the assembly. A set screw (13) is embedded in the head (12) perpendicular to the axis of the punch holder (10). The set screw (13) acts to removably affix the head (12) in place about the punch holder after it has been axially positioned along the punch holder to achieve the desired compressive force on the spring (11). The spring (11) is wrapped around the shaft of the punch holder (10) in a helical fashion.

The punch body (20) consists of an elongated shaft tapering to a lower sharpened tip (22) which is configured in the shape of the item to be punched out of the workpiece. The punch body (20) is retained and axially slidable within the bore (50) of the punch guide (40). The punch tip (22) is capable of extending through an axially aligned aperture (44) located in the base of the punch guide (40). A male threaded end (24) is located at the end opposite the punch tip (22) and extends axially upwardly into the female threaded end (14) defining the lower portion of the punch holder (10).

The male threaded portion is sized to be matingly received within the female threaded end (14), and the threads on the male and female portions are adapted to matingly engage one another. As the punch holder (10) is rotated with respect to the punch body (20), the punch body will move axially with respect to the punch holder. If the pitch of the mating threads is known, the relationship between the degree of relative rotation of these members and the resultant axial movement can be readily determined. Thus, the overall length of the punch can be precisely adjusted by axially rotating the punch holder (10) with respect to the punch body (20) through a known angle.

If so desired, a central shaft (23) can extend from the top of the head (12) axially through the punch holder (10) and most of the punch body (20). The shaft may be linked to connecting holes and can be used as an aid in lubricating the assembly. The shaft can be of any suitable dimension for this purpose; a 5/32 inch diameter hole has been found to work well.

The punch assembly further comprises a generally tubular punch guide (40). The punch body (20) and a lower portion of the punch holder (10), including the threaded female portion (14) are slidably received within the guide. An upper portion (41) of the guide desirably extends radially outwardly of the punch (5) to define a generally upwardly facing annular shoulder (42). This shoulder (42) generally faces the head (12) and abuts the end of the compression spring (11) opposite the head

so that the spring (11) is retained in compression between the opposed surfaces of the head (12) and the annular shoulder (42) of the punch guide.

On the outer surface of the punch guide is a generally U-shaped positioning groove (46) that permits the guide to be accurately positioned in a punch turret (not shown) when the punch assembly is mounted thereon. In a preferred embodiment, the groove extends generally parallel to the axis of the substantially cylindrical punch guide and includes a generally flat face (52). A bolt or a mating projection provided on the punch turret may be received within the groove and engage the flat face to limit rotational displacement of the guide with respect to the turret.

A vent (56) is situated on the lower portion of the flat face (52) of the positioning groove (46) near the end closest to the punch tip (22). In the preferred embodiment, the vent is desirably of a generally circular slope and extends perpendicular to the axis of the punch guide (40) entirely through the punch guide (40). The punch tip (22) acts as a seal with the punch guide aperture (44) and the vent (56) allows any gasses that build up during the operation of the punch assembly to be discharged to the surrounding air.

If so desired, a protective sheath (not shown) that is slidably receivable about the guide may be used to protect the guide during transportation. Although the sheath can be constructed of any appropriate shape and material, it is desirably made of a plastic wire mesh and extends past the guide pore. Such a construction protects the punch guide and tip from possible abrasion impacts during shipping, as well as protecting handlers from possible cuts from the sharp tip (22) or positioning groove (46).

The guide (40) is desirably removably attached to the punch (5) in a manner which permits the punch to move axially within the guide during operation. In a preferred embodiment, a compressible O-ring (16), which may be formed of neoprene or the like, is utilized. The O-ring may be maintained in a position disposed above the female threaded end (14) of the punch holder by an annular O-ring slot (15). The O-ring slot is adapted to be slidably received about the punch holder (10) and about the top of the female threaded end (14) and an inner shoulder (54) of the punch guide when the punch is in its rest position (shown in Figure 1).

The O-ring slot (15) is held in an abutting relationship with the female end (14) and the shoulder (54) by the force of the compression spring (11). When the punch is depressed during operation, as shown in Figure 2, movement of the slot (15) will continue to be limited by the inner shoulder of the punch guide; when the punch guide is removed from the punch (5) as outlined below, the female end (14) of the punch holder will limit movement of the holder.

An O-ring seat (36) is provided on the inner wall (38) of the upper portion (41) of the guide and is adapted to receive the O-ring (16) when the O-ring slot (15) abuts the inner shoulder (54) of the guide. The portion of the

inner wall disposed above the O-ring seat (36) desirably has an inner diameter slightly less than the outer diameter of the O-ring. As noted above, the O-ring is formed of a compressible material such as neoprene. This permits the O-ring to yield inwardly as the guide is slid upwardly about the punch during assembly of the invention. When the O-ring reaches the seat (36) on the guide, it will expand into and engage the seat to restrict movement of the punch guide with respect to the O-ring slot (15), and hence the punch (5). If one desires to remove the punch guide (40) from the punch assembly, one may pull downwardly on the guide while holding the punch stationary. If sufficient force is applied, the O-ring will yield in compression and permit the guide to be retracted from its position about the punch.

As noted above, the overall punch length can be adjusted by rotating the punch holder (10) and punch body (20) members with respect to one another. In order to maintain the punch at a constant length during use, therefore, locking means are provided to restrict relative rotation between the punch holder and punch body. Any of a wide variety of locking means may be employed, but a preferred embodiment utilizes an arcuate wire clip (30). Referring to Figures 4 and 5, the clip desirably comprises a generally C-shaped, semicircular body (36) and a generally radially inwardly extending cam pin (39). For reasons explained below, the body (36) of the clip preferably extends through an arc of more than 180°. The clip is desirably integrally formed of a springy, resilient material, such as stainless steel or the like.

The female threaded end (14) of the punch holder includes an annular groove (31) within which the body (36) of the clip may be fully received so that it does not extend significantly beyond the outer perimeter of the rest of the generally cylindrical female end (14). An aperture (33) extends generally radially inwardly through the female end from a position within the groove (31) to its threaded interior. This aperture is sized to slidably receive the cam pin (39) of the clip, which is long enough to extend inwardly from the groove to a position wherein it may lockingly engage the male threaded end (24) as explained below. The body (36) of the clip desirably has an inner diameter at rest that is less than the outer diameter of the threaded female end (14) adjacent to the annular groove (31) so that the clip, with the tip received in the aperture (33), fits into the groove (31). As noted above, the body (36) of the clip desirably extends more than half way around the circumference of the groove (31). This ensures that the clip will remain in place within the groove; if the clip were shorter, it could simply fall out of the groove because the distance between the two ends of the body would be greater than the diameter of the female end (14) within the groove.

The male threaded end (24) of the punch body is provided with at least one notch, recess or detent (32). In a preferred embodiment, the male end (24) includes a plurality of these detents in a predetermined spacing about the periphery of the male end. In the embodiment shown, four such detents are spaced equiangularly

about the male end's circumference. Each of the detents (32) is adapted to receive a portion of the cam pin (39) therein. Each detent is desirably generally V-shaped in cross section and extends along substantially the entire length of the male end (24) generally parallel to the male end's axis. Aligning the aperture (33) with the detent also aligns the punch assembly. When the cam pin (39) is positioned within a detent, it restricts rotation of the male end with respect to the female end. This serves to lock the threaded rod ends (14, 24) against relative rotation and defines a locked position of the locking means.

The inner end of the cam pin (39) can be of any appropriate shape that will be firmly received within the V-shaped detents (32). A particularly preferred configuration includes a generally V-shaped end sized to be received within the detents. The angled walls of each detent may serve as an inclined plane or ramp along which the angled end of the cam pin may ride. By applying sufficient torque, the cam pin may be urged along a wall of a detent until it disengages from the detent. As the cam pin follows the wall, it is urged radially outwardly through the aperture (33) in the female threaded end into the position shown in Figure 5. The clip (30) is desirably formed of a springy metal, as noted above, so that it may be resiliently deformed to permit the cam pin to so move.

In the locked position the spring clip (30) extends inwardly through the aperture (33). The inner circumference of the punch guide is of a dimension such that the guide (40) holds the spring clip (33) in position within the aperture (33) so that the clip (30) is in the locked position when the guide (40) is positioned over the punch members (10, 20). The punch guide (40), therefore, acts as a further locking mechanism to lock the punch assembly into a desired length. The thread diameter and pitch and the number of grooves determine the amount of length added to the punch tip (22) by turning the threaded portions of the assembly with respect to each other.

In practice, the punch assembly is used to punch items having a desired shape from a larger workpiece in a manner well known in the art. After the punch tip has worn and become dull due to repeatedly striking a workpiece, the punch assembly is removed from its turret or machine for sharpening. The punch assembly is disassembled by axially sliding the punch guide (40) away from the shaft of the punch body (20), as explained in detail above. With the punch guide removed, the punch tip (22) can then be sharpened. After sharpening, the length of the punch is shortened by whatever length was ground off. To compensate for this lost length, the punch holder (10) and punch body (20) are axially rotated in opposite directions. The rotating process causes the cam pin (39) of the wire clip to exit the detent (32) and slide along the groove until it enters the next detent. The motion of the clip entering a detent produces a "click" sound which alerts the user that the clip has entered a detent. As the thread diameter and pitch, as well as the location and number of grooves, will all be known before the assembly is used, the length the punch is increased by rotating the two threaded members of the punch will

be predetermined. Thus, the user can adjust the length of the punch as needed simply by counting the number of "clicks". This process is repeated until the punch reaches the desired length. The punch assembly will be aligned and ready for use when the aperture is aligned with a detent. The punch assembly is then reassembled by sliding the guide back onto the shaft of the punch body and the punch assembly can be employed once again (Fig. 3).

While a preferred embodiment of the present invention has been described, it should be understood that various changes, adaptation and modifications may be made therein without departing from the scope of the appended claims.

#### Claims

1. A punch assembly for use in a punch press, the assembly including a punch (5) comprising a pair of elongated rods (10,20) having mating respective male (24) and female (14) threaded ends co-acting to enable the length of the punch to be altered by rotating one rod with respect to the other, one of the rods having at its other end a punch tip (22), and a punch guide (40) having a bore (50) axially slidably receiving the punch (5), the punch assembly including releasable lock means for locking the threaded ends against relative rotation and including means (39) movable between a locked position in which said threaded rod ends are locked against relative rotation and an unlocked position permitting said relative rotation for adjusting the length of the punch, and position maintaining means carried by the punch guide (40) for maintaining the lock means (39) in its locked position when the punch is operatively positioned in the punch guide.
2. The punch assembly of claim 1 wherein said female threaded end (14) comprises an internally threaded circumferential wall having an aperture (33) therethrough, and wherein said male end (24) includes a recess (32) alignable during rotation thereof with said aperture, the lock means comprising a cam pin (39) having a portion insertable generally radially through the aperture and into locking contact with the recess of the male end to lock the threaded ends against relative rotation.
3. The punch assembly of claim 2 wherein said position maintaining means comprises an interior surface carried by the punch guide (40) and positioned to engage and prevent the locking pin (39) from moving into its second position when the punch is operatively positioned in the guide.
4. The punch assembly of claim 2 or claim 3 wherein said threaded female rod end (14) includes an exterior annular groove (31) formed therein and within which is located said aperture (33), and wherein the

locking pin includes a generally "C" shaped wire clip (30) bearing said cam pin (39) at one end, said clip being shaped to be retained within said groove.

5. The punch assembly of claim 4 wherein said clip (30) is of springy metal and extends more than half way around the circumference of the groove (31), the clip having an inner diameter at rest that is less than the outer diameter of the threaded rod end adjacent the groove, whereby said clip (30), with the tip (39) received in said aperture (33), snaps into said groove (31).
6. The punch assembly of any one of claims 1 to 5 wherein the punch guide (40) includes a bore bearing said interior surface, the bore being sized to closely receive the female end (14) of the punch (5) and to prevent the cam pin (39) from withdrawing from the recess carried by said threaded male rod end.
7. The punch assembly of claim 5 or claim 6 when dependent on claim 5 wherein said male end (24) comprises a plurality of recesses (32) equally spaced about its circumference and sized to consecutively receive and release the pin (39) as the male threaded end is rotated with respect to the female end (14), whereby the length of the punch (5) is adjusted a finite, predetermined amount as the pin (39) moves from one recess (32) to the next.
8. The punch assembly of claim 7 wherein the spring metal clip (30) is sized to urge the pin (39) to snap into the consecutive recesses (32) with an audible clicking sound as the male threaded end (24) is rotated with respect to the female end (14), thereby signaling to an operator, by the number of clicks, the change in length of the punch.
9. The punch assembly of claim 7 wherein the clip (30) may be urged out of a recess (32) by applying sufficient torque to the male threaded end (24) with respect to the female end (14).
10. A punch assembly for use in a punch press, the assembly including a punch (5) comprising a pair of elongated rods (10,20), the first of which has an exteriorly threaded male end (24) and a second of which has a female end (14) including an exterior annular groove (31) formed therein and having an internally threaded circumferential wall that is threadingly receptive of the threaded male end (24) of the first rod such that the length of the punch (5) formed by the two rods threaded together may be altered by rotating one rod with respect to the other, one of the rods having at its other end a punch tip (22), the punch including means for releasably locking the rods together against rotation of one with respect to the other, said means comprising an aperture (33)

be predetermined. Thus, the user can adjust the length of the punch as needed simply by counting the number of "clicks". This process is repeated until the punch reaches the desired length. The punch assembly will be aligned and ready for use when the aperture is aligned with a detent. The punch assembly is then reassembled by sliding the guide back onto the shaft of the punch body and the punch assembly can be employed once again (Fig. 3).

While a preferred embodiment of the present invention has been described, it should be understood that various changes, adaptation and modifications may be made therein without departing from the scope of the appended claims.

#### Claims

1. A punch assembly for use in a punch press, the assembly including a punch (5) comprising a pair of elongated rods (10,20) having mating respective male (24) and female (14) threaded ends co-acting to enable the length of the punch to be altered by rotating one rod with respect to the other, one of the rods having at its other end a punch tip (22), and a punch guide (40) having a bore (50) axially slidingly receiving the punch (5), the punch assembly including releasable lock means for locking the threaded ends against relative rotation and including means (39) movable between a locked position in which said threaded rod ends are locked against relative rotation and an unlocked position permitting said relative rotation for adjusting the length of the punch, and position maintaining means carried by the punch guide (40) for maintaining the lock means (39) in its locked position when the punch is operatively positioned in the punch guide.
2. The punch assembly of claim 1 wherein said female threaded end (14) comprises an internally threaded circumferential wall having an aperture (33) therethrough, and wherein said male end (24) includes a recess (32) alignable during rotation thereof with said aperture, the lock means comprising a cam pin (39) having a portion insertable generally radially through the aperture and into locking contact with the recess of the male end to lock the threaded ends against relative rotation.
3. The punch assembly of claim 2 wherein said position maintaining means comprises an interior surface carried by the punch guide (40) and positioned to engage and prevent the locking pin (39) from moving into its second position when the punch is operatively positioned in the guide.
4. The punch assembly of claim 2 or claim 3 wherein said threaded female rod end (14) includes an exterior annular groove (31) formed therein and within which is located said aperture (33), and wherein the locking pin includes a generally "C" shaped wire clip (30) bearing said cam pin (39) at one end, said clip being shaped to be retained within said groove.
5. The punch assembly of claim 4 wherein said clip (30) is of springy metal and extends more than half way around the circumference of the groove (31), the clip having an inner diameter at rest that is less than the outer diameter of the threaded rod end adjacent the groove, whereby said clip (30), with the tip (39) received in said aperture (33), snaps into said groove (31).
6. The punch assembly of any one of claims 1 to 5 wherein the punch guide (40) includes a bore bearing said interior surface, the bore being sized to closely receive the female end (14) of the punch (5) and to prevent the cam pin (39) from withdrawing from the recess carried by said threaded male rod end.
7. The punch assembly of claim 5 or claim 6 when dependent on claim 5 wherein said male end (24) comprises a plurality of recesses (32) equally spaced about its circumference and sized to consecutively receive and release the pin (39) as the male threaded end is rotated with respect to the female end (14), whereby the length of the punch (5) is adjusted a finite, predetermined amount as the pin (39) moves from one recess (32) to the next.
8. The punch assembly of claim 7 wherein the spring metal clip (30) is sized to urge the pin (39) to snap into the consecutive recesses (32) with an audible clicking sound as the male threaded end (24) is rotated with respect to the female end (14), thereby signaling to an operator, by the number of clicks, the change in length of the punch.
9. The punch assembly of claim 7 wherein the clip (30) may be urged out of a recess (32) by applying sufficient torque to the male threaded end (24) with respect to the female end (14).
10. A punch assembly for use in a punch press, the assembly including a punch (5) comprising a pair of elongated rods (10,20), the first of which has an exteriorly threaded male end (24) and a second of which has a female end (14) including an exterior annular groove (31) formed therein and having an internally threaded circumferential wall that is threadingly receptive of the threaded male end (24) of the first rod such that the length of the punch (5) formed by the two rods threaded together may be altered by rotating one rod with respect to the other, one of the rods having at its other end a punch tip (22), the punch including means for releasably locking the rods together against rotation of one with respect to the other, said means comprising an aperture (33)



formed through said circumferential wall, and a recess (32) formed in the threaded male end and alignable during rotation thereof with the aperture and the female rod end, a locking pin (39) having a portion insertable through the aperture and into locking contact with the recess of the male end, and means for resiliently retaining the locking pin in said aperture comprising a generally "C" shaped wire clip (30) bearing said pin at one end, said clip being of springy metal and extending more than half way around the circumference of the groove (31) and being shaped to be retained within said groove, and having an inner diameter at rest that is less than the outer diameter of the threaded rod end adjacent to the groove, whereby said clip (30), with the tip (39) received in said aperture, snaps into said groove (31), the assembly including stripper means to strip a metal workpiece away from the punch tip during a return stroke of the punch tip in a punching operation, the stripper means comprising a tubular sheath within which is received the rod (20) bearing the punch tip (22), the stripper means including a stripper plate at its end having an orifice through where the punch tip protrudes in a punching operation, wherein adjustment of the length of the punch (5) by rotating one of the punch rods with respect to the other (10,20) adjusts the distance by which the punch tip (22) protrudes from the punch plate in a punching operation.

#### Patentansprüche

1. Stanzstempelbaueinheit zur Verwendung in einer Stanzpresse, mit einem Stanzstempel (5), der zwei langgestreckte Stangen (10, 20) umfaßt, die ein dazu passendes Außengewindeende (24) bzw. Innengewindeende (14) besitzen, die zusammenwirken, um ein Einstellen der Länge des Stanzstempels durch Drehen einer Stange gegenüber der anderen zu ermöglichen, wobei eine der Stangen an ihrem anderen Ende eine Stanzstempelspitze (22) besitzt, und mit einer Stanzstempelführung (40) mit einer Bohrung (50), die den Stanzstempel (5) axial gleitend aufnimmt, wobei die Stanzstempelbaueinheit eine lösbare Verriegelungsvorrichtung zum Verriegeln der Gewindeenden gegen eine relative Drehung, welche eine Vorrichtung (39) enthält, die zwischen einer verriegelten Position, in der die Gewindestangenenden gegen eine relative Drehung verriegelt sind, und einer unverriegelten Position, die eine relative Drehung zum Einstellen der Länge des Stanzstempels erlaubt, bewegt werden kann, sowie eine von der Stanzstempelführung (40) getragene Positionshaltevorrichtung zum Halten der Verriegelungsvorrichtung (39) in deren verriegelter Position umfaßt, wenn sich der Stanzstempel in der Stanzstempelführung in Arbeitsstellung befindet.

2. Stanzstempelbaueinheit nach Anspruch 1, bei der das Innengewindeende (14) eine Innengewindeumfangswand mit einer Öffnung (33) besitzt, die durch diese hindurchführt, und bei der das Außengewindeende (24) einen Einzug (32) besitzt, der während der Drehung desselben auf die Öffnung ausgerichtet werden kann, wobei die Verriegelungsvorrichtung einen Nockenstift (39) umfaßt, der einen Abschnitt besitzt, der im allgemeinen radial durch die Öffnung eingesetzt und in Verriegelungskontakt mit dem Einzug des Außengewindeendes gebracht werden kann, um die Gewindeenden gegen eine relative Drehung zu verriegeln.
3. Stanzstempelbaueinheit nach Anspruch 2, bei der die Positionshaltevorrichtung eine Innenfläche umfaßt, die von der Stanzstempelführung (40) getragen wird und so angeordnet ist, daß sie mit dem Verriegelungsstift (39) in Eingriff ist und verhindert, daß dieser in seine zweite Position bewegt wird, wenn sich der Stanzstempel in der Führung in Arbeitsstellung befindet.
4. Stanzstempelbaueinheit nach Anspruch 2 oder Anspruch 3, bei der das Innengewindestangenende (14) eine daran ausgebildete äußere ringförmige Rille (31) umfaßt, in der eine Öffnung (33) angebracht ist, wobei der Verriegelungsstift eine im allgemeinen "C"-förmige Drahtklammer (30) ist, die an einem Ende den Nockenstift (39) trägt, wobei die Klammer so geformt ist, daß sie von der Rille aufgenommen wird.
5. Stanzstempelbaueinheit nach Anspruch 4, bei der die Klammer (30) aus einem federnden Metall besteht und sich über mehr als den halben Umfang der Rille (31) erstreckt, wobei die Klammer im entspannten Zustand einen Innendurchmesser besitzt, der kleiner ist als der Außendurchmesser des Gewindestangenendes nahe der Rille, und wobei die Klammer (30), deren Spitze (39) in der Öffnung (33) aufgenommen ist, in die Rille (31) einschnappt.
6. Stanzstempelbaueinheit nach einem der Ansprüche 1 bis 5, bei der die Stanzstempelführung (40) eine Bohrung enthält, die die Innenfläche trägt, wobei die Bohrung so bemessen ist, daß sie das Innengewindeende (14) des Stanzstempels (5) eng aufnimmt und verhindert, daß der Nockenstift (39) aus dem vom Außengewindestangenende getragenen Einzug zurückgezogen wird.
7. Stanzstempelbaueinheit nach Anspruch 5 oder nach Anspruch 6, wenn dieser von Anspruch 5 abhängt, bei der das Außengewindeende (24) mehrere Einzüge (32) umfaßt, die am Umfang in gleichen Abständen angeordnet sind und so bemessen sind, daß sie aufeinanderfolgend den Stift (39) aufnehmen und freigeben, wenn das Außengewinde-



ende gegenüber dem Innengewindeende (14) gedreht wird, wobei die Länge des Stanzstempels (5) um ein endliches, vorgegebenes Maß verstellt wird, wenn sich der Stift (39) von einem Einzug (32) zum nächsten bewegt.

8. Stanzstempelbaueinheit nach Anspruch 7, bei der die Federmetallklammer (30) so bemessen ist, daß sie den Stift (39) dazu zwingt, in die aufeinanderfolgenden Einzüge (32) mit einem hörbaren Klickgeräusch einzurasten, wenn das Außengewindeende (24) gegenüber dem Innengewindeende (14) gedreht wird, und somit einer Bedienungsperson durch die Anzahl der Klickgeräusche die Längenänderung des Stanzstempels signalisiert.
9. Stanzstempelbaueinheit nach Anspruch 7, bei der die Klammer (30) aus dem Einzug (32) gedrückt werden kann, indem auf das Außengewindeende (24) ein ausreichendes Drehmoment bezüglich des Innengewindeendes (14) ausgeübt wird.
10. Stanzstempelbaueinheit zur Verwendung in einer Stanzpresse, mit einem Stanzstempel (5), der zwei langgestreckte Stangen (10, 20) umfaßt, von denen die erste ein Außengewindeende (24) besitzt, während die zweite ein Innengewindeende (14), eine daran ausgebildete äußere ringförmige Rille (31) und eine Innengewindeumfangswand besitzt, in die das Außengewindeende (24) der ersten Stange eingeschraubt werden kann, so daß die Länge des von den beiden zusammengeschraubten Stangen gebildeten Stanzstempels (5) durch Drehen einer Stange gegenüber der anderen verändert werden kann, wobei eine der Stangen an ihrem anderen Ende eine Stanzstempelspitze (22) besitzt und der Stanzstempel eine Vorrichtung zum lösbaren Verriegeln der Stangen gegen eine Drehung der einen gegenüber der anderen, wobei diese Vorrichtung eine in der Umfangswand ausgebildete Öffnung (33) sowie einen im Außengewindeende ausgebildeten Einzug (32) umfaßt, der während der Drehung desselben auf die Öffnung des Innengewindestangenendes ausgerichtet wird, einen Verriegelungsstift (39), der einen Abschnitt besitzt, der durch die Öffnung eingesetzt und in Verriegelungskontakt mit dem Einzug des Außengewindeendes gebracht werden kann, sowie eine Vorrichtung zum elastischen Halten des Verriegelungsstiftes in dieser Öffnung mit einer im allgemeinen "C"-förmigen Drahtklammer (30) umfaßt, die an einem Ende einen Stift trägt, wobei die Klammer aus federndem Metall besteht, sich über mehr als den halben Umfang der Rille (31) erstreckt und so geformt ist, daß sie in der Rille aufgenommen wird und im entspannten Zustand einen Innendurchmesser besitzt, der kleiner ist als der Außendurchmesser des Gewindestangenendes neben der Rille, wobei die Klammer (30) deren Spitze (39) in der Öffnung aufgenommen ist, in die

Rille (31) einschnappt, wobei die Baueinheit eine Abstreifvorrichtung zum Abstreifen eines Metallwerkstücks von der Stanzstempelspitze während eines Rückkehrhubes der Stanzstempelspitze bei einem Stanzvorgang umfaßt, wobei die Abstreifvorrichtung eine rohrförmige Hülse umfaßt, in der die Stange (20), die die Stanzstempelspitze (22) trägt, aufgenommen ist, und die Abstreifvorrichtung an ihrem Ende eine Abstreifplatte mit einer Mündung besitzt, durch die die Stanzstempelspitze bei einem Stanzvorgang hervortritt, wobei das Einstellen der Länge des Stanzstempels (5) durch Drehen einer der Stanzstempelstangen gegenüber der anderen (10, 20) den Abstand einstellt, um den die Stanzstempelspitze (22) bei einem Stanzvorgang aus der Stanzplatte hervorsticht.

#### Revendications

1. Ensemble de poinçon utilisable dans une presse mécanique, l'ensemble comprenant un poinçon (5) comprenant une paire de tiges allongées (10, 20) ayant des extrémités filetées mâle (24) et femelle (14) respectives appariées co-opérant pour permettre la modification de la longueur du poinçon, en tournant une tige par rapport à l'autre, l'une des tiges possédant, à son autre extrémité, une extrémité de poinçon (22), et un guide de poinçon (40) ayant un alésage (50) qui reçoit axialement de manière coulissante le poinçon (5), l'ensemble de poinçon comprenant un moyen de verrouillage débloable pour verrouiller les extrémités filetées contre la rotation relative et comprenant un moyen (39) mobile entre une position bloquée, dans laquelle lesdites extrémités des tiges filetées sont verrouillées contre la rotation relative, et une position débloquée, permettant ladite rotation relative pour ajuster la longueur du poinçon, et des moyens de maintien de position supportés par le guide de poinçon (40) pour maintenir le moyen de verrouillage (39) dans sa position verrouillée lorsque le poinçon est positionné en fonctionnement dans le guide de poinçon.
2. Ensemble de poinçon selon la revendication 1, dans lequel ladite extrémité femelle (14) comprend une paroi circonférentielle filetée intérieurement ayant une ouverture (33) à travers, et dans lequel ladite extrémité mâle (24) comprend un évidement (32) alignable pendant la rotation avec ladite ouverture, le moyen de verrouillage comprenant un axe de came (39) ayant une partie insérable généralement radialement par l'ouverture et en contact de verrouillage avec l'évidement de l'extrémité mâle pour verrouiller les extrémités filetées contre la rotation relative.
3. Ensemble de poinçon selon la revendication 2, dans lequel lesdits moyens de maintien de position comprennent une surface intérieure supportée par le guide de poinçon (40) et positionnée pour s'engager



et empêcher l'axe de verrouillage (39) de se déplacer dans sa deuxième position lorsque le poinçon est positionné en fonctionnement dans le guide.

4. Ensemble de poinçon selon la revendication 2 ou la revendication 3, dans lequel ladite extrémité de tige femelle filetée (14) comprend une rainure annulaire extérieure (31) formée à l'intérieur et dans laquelle est située ladite ouverture (33), et dans lequel l'axe de verrouillage comprend un collier métallique (30) généralement en forme de "C", portant ledit axe de came (39) à une extrémité, ledit collier étant formé pour être retenu à l'intérieur de ladite rainure. 5 10
5. Ensemble de poinçon selon la revendication 4, dans lequel ledit collier (30) est en métal souple et s'étend sur plus de la moitié de la circonférence de la rainure (31), le collier ayant un diamètre intérieur au repos qui est inférieur au diamètre extérieur de l'extrémité de la tige filetée adjacente à la rainure, ce qui permet l'encliquetage dans ladite rainure (31) dudit collier (30), avec l'extrémité (39) reçue dans ladite ouverture (33). 15 20
6. Ensemble de poinçon selon l'une quelconque des revendications 1 à 5, dans lequel le guide de poinçon (40) comprend un alésage portant ladite surface intérieure, l'alésage étant dimensionné pour recevoir étroitement l'extrémité femelle (14) du poinçon (5) et pour empêcher l'axe de came (39) de sortir de l'évidement supporté par ladite extrémité de tige mâle filetée. 25 30
7. Ensemble de poinçon selon la revendication 5 ou la revendication 6, lorsqu'elle dépend de la revendication 5, dans lequel ladite extrémité mâle (24) comprend une pluralité d'évidements (32) équidistants autour de sa circonférence et dimensionnés pour recevoir et libérer consécutivement l'axe (39) lorsque l'extrémité filetée mâle est tournée par rapport à l'extrémité femelle (14), ce qui permet de régler la longueur du poinçon (5) sur une valeur prédéterminée, finie, lorsque l'axe (39) se déplace d'un évidement (32) à l'autre. 35 40 45
8. Ensemble de poinçon selon la revendication 7, dans lequel le collier métallique à ressort (30) est dimensionné pour pousser l'axe (39) et l'encliqueter dans les évidements consécutifs (32) avec un déclic audible lorsque l'extrémité filetée mâle (24) est tournée par rapport à l'extrémité femelle (14), signalant ainsi à un opérateur, par le nombre de clics, le changement de longueur du poinçon. 50
9. Ensemble de poinçon selon la revendication 7, dans lequel le collier (30) peut être poussé hors d'un évidement (32), en appliquant un couple suffisant à l'extrémité filetée mâle (24) par rapport à l'extrémité femelle (14). 55

10. Ensemble de poinçon utilisable dans une presse mécanique, l'ensemble comprenant un poinçon (5) comportant une paire de tiges allongées (10, 20), dont la première a une extrémité mâle (24) filetée extérieurement et dont la deuxième a une extrémité femelle (14) comprenant une rainure annulaire extérieure (31) formée à l'intérieur et ayant une paroi circonférentielle filetée intérieurement qui reçoit par filetage l'extrémité mâle filetée (24) de la première tige, de manière que la longueur du poinçon (5) formé par les deux tiges filetées ensemble puisse être modifiée en tournant une tige par rapport à l'autre, l'une des tiges ayant à son autre extrémité une extrémité de poinçon (22), le poinçon comprenant un moyen pour verrouiller de manière déblocable les tiges ensemble contre la rotation de l'une par rapport à l'autre, ledit moyen comprenant une ouverture (33) formée par ladite paroi circonférentielle, et un évidement (32) formé dans l'extrémité mâle filetée et alignable pendant la rotation avec l'ouverture et l'extrémité de la tige femelle, un axe de verrouillage (39) ayant une partie insérable à travers l'ouverture et en contact de verrouillage avec l'évidement de l'extrémité mâle, et un moyen pour retenir de manière résiliente l'axe de verrouillage dans ladite ouverture comprenant un collier métallique généralement en forme de "C" (30) portant ledit axe à une extrémité, ledit collier étant en métal souple et s'étendant sur plus de la moitié de la circonférence de la rainure (31) et étant formé pour être retenu dans ladite rainure, et ayant un diamètre intérieur au repos qui est inférieur au diamètre extérieur de l'extrémité de la tige filetée adjacente à la rainure, ce qui permet l'encliquetage dans ladite rainure (31) dudit collier (30) avec l'extrémité (39) reçue dans ladite ouverture, l'ensemble comprenant un moyen éjecteur pour éjecter une pièce en métal de l'extrémité du poinçon pendant une course de retour de l'extrémité du poinçon dans une opération de poinçonnage, le moyen éjecteur comprenant une gaine tubulaire à l'intérieur de laquelle est reçue la tige (30) portant l'extrémité du poinçon (22), le moyen éjecteur comprenant une plaque d'éjecteur à son extrémité ayant un orifice par lequel fait saillie l'extrémité du poinçon dans une opération de poinçonnage, dans laquelle le réglage de la longueur du poinçon (5) en tournant l'une des tiges du poinçon par rapport à l'autre (10, 20) permet de régler la distance de saillie de l'extrémité du poinçon (22) par rapport à la plaque de poinçon dans une opération de poinçonnage.

