[DESCRIPTION]

[Title of Invention]

TABLE GAME SYSTEM

[Technical Field]

[0001]

The present invention relates to a table game system with a security function in a card game such as baccarat using shuffled playing cards (hereinafter simply referred to as "cards") and also relates to a method for administrating operations of operator "a dealer" of games using cards and game tables in casino.

[Background Art]

[0002]

In poker, baccarat, bridge, blackjack, and other card games, a dealer sets a package of cards comprising several decks of playing cards in a card shoe or the like, and deals cards on the table by drawing them one by one.

In so doing, to ensure the fairness of the games, the cards need to be dealt at random. Therefore, a game host must sufficiently shuffle the playing cards randomly to ensure a random order of arrangement of the playing cards before they are set in the card shoe.

[0003]

A conventional card shuffling device for shuffling cards is disclosed in, for example, Patent Literature 1. Each package of shuffled playing cards is provided after being shuffled with a shuffling apparatus to be arranged in a unique order with a uniquely identifiable shuffled card ID affixed on its packing box or the like as a barcode.

[Citation List]

[Patent Literature]

[0004]

[PTL 1] WO 2009/069708

[Summary of Invention]

[Technical Problem]

[0005]

A cut card is used to prevent any player from counting the ranks of th e cards dealt during a game to predict the ranks of the cards when the number of cards not yet dealt becomes small. Usually, the cut card is inserted into the shuffled playing cards before the beginning of the first game, and the cards are dealt onto the game table one by one by the dealer or the like. When the cut c ard is drawn from the card shoe apparatus, the card set that is currently being used is no longer used immediate after the game of few games later and will be replaced by the dealer or the operator to a new set of shuffled playing cards. T his makes it impossible to identify the shuffled playing card currently being use d at each game table since the replacement of the shuffled playing cards with a new one manually. For this reason, in case of any problem with the card shoe apparatus or the shuffled playing cards, it is difficult to identify the shuffled pla ying cards in use at the timing when the problem happened thereof, which is a problem because the casino is not able to investigate the cause of the problems.

[0006]

The present invention has been made in view of the above problem, an d aims to provide a table game system that is capable of identifying the shuffle d playing card set that is currently being used at a game table, and also capabl e of, if any problem occurs with a card shoe apparatus or with cards is found, i dentifying the shuffled playing card set that has been used at the time of the oc currence thereof, thereby enabling an investigation of the cause whether or not t here is a human (a dealer etc.) error or cards error thereof etc.

[Solution to Problem]

[0007]

To solve the above conventional problems, the present invention provide s a table game system including:

shuffled playing cards composed of playing cards made up of a plurality of number of decks shuffled to have a unique arrangement order and a cut car d, and

a card shoe apparatus that houses the shuffled playing cards and the cut card such that the housed shuffled playing cards and the cut card are manually dealt one by one onto a game table,

the card shoe apparatus comprising:

a card housing unit for housing the shuffled playing cards;

an opening for drawing cards from the card housing unit one by one;

a card reading unit that reads from a card and from the cut card information contained in the said card;

a control unit that stores rules of a card game and includes a winner/loser determination unit that determines the winner/loser of the card game based on the information on the ranks of the cards read by the card reading unit; and

a display unit that outputs a result of the winner/loser determined by the winner/loser determination unit,

the control unit has a function of identifying specified events that occur during the use of the identified shuffled playing cards at a game table, and of reporting these occurrences of the specified event,

the control unit has further function of identifying an exposition of the cut card and of sending information of the exposition of the cut card,

the information of the exposition of the cut card is at least used for identifying an end of the current games and the end the use of the shuffled playing cards currently set in the card shoe apparatus,

and

the specified events include at least one of the following:

(1) a reading error in the card reading unit of a card,

(2) an attempt to draw a card when no card should be drawn according to the rules of the card game;

(3) the winner/loser of each card game during the use of the shuffled playing cards currently set in the card shoe apparatus, and,

(4) an improper shuffling of a set of shuffled playing cards set in the card shoe apparatus comprising the relative arrangement of

predetermined number of cards; and

wherein,

the information of the exposition of the cut card is used for administrating at least one of the followings;

(1) an average time for one game during the use of the shuffled playing cards currently set in the card shoe apparatus,

(2) an average error occurrences during the use of the shuffled playing cards currently set in the card shoe apparatus,

(3) monitoring of tendencies of the results of games during the use of the shuffled, and

(4) restart or reset of a monitor for displaying results of games during the use of the playing cards currently set in the card shoe apparatus.

[Advantageous Effects of Invention]

[0008]

With the present invention, it is possible to provide a table game system that is capable of, if any problem occurs with a card shoe apparatus or cards, identifying the shuffled playing cards that is being used at the time of the occurrence thereof, and thereby enables the investigation of the cause thereof or the taking of countermeasures therefor by identifying the shuffled playing cards being used or operators etc. of the games at the time of occurrence thereof.

[Brief Description of Drawings]

[0009]

[Fig. 1]

Fig. 1 is a perspective view schematically showing the entirety of a table game system according to an embodiment of the present invention.

[Fig. 2]

Fig. 2 is a perspective view of shuffled playing cards to be used in the table game system according to the embodiment of the present invention.

[Fig. 3]

Fig. 3 is a diagram showing a general configuration of the card shoe apparatus.

[Fig. 4]

Fig. 4 (a) is a plan view of a card according to the embodiment of the present invention, Fig. 4 (b) is a plan view of a cut card according to the embodiment of the present invention.

[Fig. 5]

Fig. 5 is an enlarged plan view showing a main portion of a card guide of the card shoe apparatus, in which the card guide is partially broken.

[Fig. 6]

Fig. 6 is a diagram showing the relation between the output waves from sensors and marks in the card shoe apparatus.

[Fig. 7]

Fig. 7 shows a cut card being inserted into a package of shuffled playing cards according to an exemplary embodiment of the present invention.

[Fig. 8]

Figs. 8(a) and 8(b) show cards that have been improperly shuffled according to exemplary embodiments of the present invention.

[Description of Embodiments]

[0010]

An embodiment of a table game system of the present invention will be described below. Fig. 1 is a perspective view schematically showing the entirety of a table game system according to an embodiment of the present invention. Fig. 2 is a perspective view of a package of shuffled playing cards to be used in the table game system according to the embodiment of the present invention. The shuffled playing cards used in various card games such as poker, baccarat, bridge or blackjack will ordinarily include 8 to 10 (eight to ten) decks of cards. Although a shuffled playing card set 1s is packed in the table game system of the present embodiment, when the shuffled playing card set 1s is to be used in the game, it is housed in a card shoe apparatus 2 after the packing is undone to enable the cards 1 of the shuffled playing card set 1s to be dealt one by one. During the game, the dealer deals the cards 1 from the card shoe apparatus 2

onto the game table. The cards 1 of each shuffled playing card set 1s, which ma de up of a predetermined number of decks (normally, 6, 8, 9 or 10 decks), are s huffled to be arranged in a unique and random arrangement order, and packed with a uniquely identifiable shuffled card ID attached to a packing box 4 as a b arcode 3 (RFID or RF-tag can be used instead) as an ID code.

[0011]

In an assembled state, a packing box 4 of the shuffled playing card set 1s has the shape of a rectangular parallelepiped, encasing the shuffled playing card set 1s as shown in Fig. 2. The packing box 4 has zippers 5 provided in tw o locations (may at least one) a predetermined interval, each of which has zipp er-shaped cut lines arranged in parallel to a longitudinal direction of the rectang ular parallelepiped shape, and has a central band 6 in the central portion define d by the zippers 5 provided in the two locations. A configuration is achieved in which by removing the two zippers 5 (or at least one) along the cut lines, the left and right side faces of the packing box 4 are removed such that the side f aces of the shuffled playing card set 1s would be exposed (Fig. 7). Circled numb ers 1 to 3 indicating the procedural order for removing the zippers 5 are printed on each of the zippers 5, as shown in Fig. 2.

[0012]

In accordance with this order, the portion on the left of a zipper 5 is r emoved first to remove the left side face of the packing box 4, thereby exposing one side edge of each of the shuffled playing cards 1 within the packing box 2 (a first side edge exposure step). This first side edge exposure step may further i nclude a card cut step of inserting a cut card 1c, which is used at a casino in o rder to stop the use of the shuffled playing cards set 1s in the middle of games after that game as appropriate, into the shuffled playing cards set 1s. The card cut step of inserting a cut card 1c into the shuffled playing cards set 1s allows for: 1) dividing of the shuffled playing cards set 1s into two parts by the cut ca rd 1c (the first half and second half) and then 2) exchanging positions of the tw o halves (the first half should be the backward position to the cut card and the

second half should be in front position). This step is so called normally the "cut" in a card game. After the first "cut", the cut card 1c may again be inserted into the shuffled playing cards set 1s at casinos (see Fig. 7) in order to stop the use of the shuffled playing cards set 1s going forward or after a few games after the cut card 1c appears during dealings of the cards.

[0013]

The cut card 1c is inserted in the shuffled playing card set 1s before it is set in the card shoe apparatus 2. The cut card 1c is inserted at any place within the latter half portion of the shuffled playing card set 1s when used in a game (in the last quarter or one-fifth of the shuffled playing card set 1s). The cut card 1c is used to end a game at the game table leaving about 20 to 40 cards 1 in the card shoe apparatus 2 to prevent any player counting the ranks of the cards 1 dealt during a game to predict the ranks of the cards when the number of cards not yet dealt becomes small. Normally, when the cut card 1s is drawn during games, use of the shuffled playing card set 1s currently in use is stopped after that game or a few games thereafter, and the game ends. The shuffled playing card set 1s in the card shoe apparatus 2 is replaced with a new set, and a new game begins.

[0014]

As shown in Fig. 4, an RFID (or a RF-tag) may be attached as the ID code to the cut card 1c instead of attaching an RFID (or a RF-tag) to the packing box 4. In this case, the cut card 1c may be inserted into the shuffled playing cards set 1s when they are packaged in a factory. This is advantageous in that it obviates the need for casinos to prepare the cut card 1c for the "cut". The cut card 1c is inserted at the left side or right side of the shuffled playing cards set 1s in the packing box 4, and the player (customer) or dealer of the casino may easily find and pick the cut card 1c in the packing box 4. In this case the RFID (or a RF-tag) may not be attached to the packing box 4, but the ID code may still be easily read from the RFID of the cut card 1c and the ID code uniquely identifies each set 1s of shuffled playing cards.

[0015]

In Fig. 1, the table game system of the present embodiment includes t he shuffled playing card set 1s composed of cards 1 made up of a predetermined number of decks shuffled to have a unique arrangement order, and which has a uniquely identifiable shuffled card ID attached as a barcode 3, or the RFID of the cut card 1c and a card shoe apparatus 2 for housing the shuffled playing c ard set 1s therein to allow the manual dealing of the housed cards 1 one by on e onto the game table, and which has a barcode reader 100, an input means 20 0 or RFID reading device 300 capable of identifying the shuffled card ID for eac h shuffled playing card set 1s when it is used on the game table.

[0016]

In Fig. 3, the card shoe apparatus 2 of the table game system of the p resent embodiment is provided with a lid 2f that enables the insertion and remo val of the shuffled playing card set 1s. A sensor S for detecting the opening/closi ng of the lid 2f is provided under the lid 2f, and which detects the opening/closi ng of the lid 2f, thereby detecting the replacement of the shuffled playing card s et 1s. The card shoe apparatus 2 has a card guide unit 7 that guides cards 1 t hat are manually drawn one by one from a card housing unit 2C onto a game t able, a code reading unit 8 that reads, when a card 1 is manually drawn from t he card housing unit 2C by a dealer or the like of a casino, the code C that ind icates a figure (number, rank) of that card 1, a winner/loser determination unit 10 that determines the winner/loser of the card game based on the numbers (ra nks) of the cards 1 sequentially read by the code reading unit 8, and an output means 11 that outputs the result of the determination made by the winner/lose r determination unit 10.

[0017]

Fig. 4 shows the cards 1 that form the shuffled playing card set 1s. A figure (number, rank) is encoded and printed on each card 1 that is used in a t able game such as baccarat as marks M in UV ink or the like, which is invisibl e under normal conditions. Codes C, each of which is configured with marks M,

are provided in the upper and lower sides of the card 1 in a point-symmetric manner. The cut card 1c has also code C, each of which is configured with mark(s) M to be identified that it is the cut card itself). Preferably, the code C is printed in a position where it does not overlap with the indications of the card types 101 or indexes 102 with a paint material that becomes visible when irradiated with a UV ray.

[0018]

Next, the code reading unit 8, which reads from a card 1 the code C that indicates the figure (number, rank) of the card 1 when the card 1 is manually drawn from the card housing unit 2C, will be described in detail with reference to Fig. 5. Fig. 5 is a plan view of a main portion of the card shoe apparatus 2. In Fig. 5, the code reading unit 8 is provided in the card guide unit 7 that guides the cards 1 manually drawn one by one from an opening 13 of the card housing unit 2C onto the game table, with the opening 13 provided in a front portion of the card housing unit 2C. The card guide unit 7 is an inclined surface, and a card guide cover 14 is attached to a portion of the edge of each of both sides thereof, with the card guide cover 14 also serving as a sensor cover. Also, each of the two card guide covers 14 is configured to be attachable/detachable with screws or the like (not shown). When a card guide cover 14 is removed, a sensor group 15 of the code reading portion 8 is exposed. The sensor group 15 is composed of four sensors, including two ultraviolet reactive sensors (UV sensors) 20 and 21, and object detection sensors 22 and 23.

[0019]

The object detection sensors 22 and 23 are optical fiber sensors that each can detect the presence of a card 1 and movement thereof. The object detection sensor 22 is placed in the upstream side of the card guide unit 7 in the direction of the flow (arrow F) of the card 1, and the object detection sensor 23 is placed in the downstream side of the card guide unit 7 in the direction of the flow of the card 1. As shown in Fig. 5, the object detection sensors 22 and 23 are provided in the upstream and downstream sides of the UV sensors 20 and 21, r

espectively. Each of the UV sensors 20 and 21 includes an LED (UV LED) that emits an ultraviolet ray and a detector. The marks M are printed on the card 1 in UV luminescent ink that emits color when UV ray is applied. The card 1 is irradiated with the UV ray (black light), and the detector detects the light reflected by the marks M of the code C of the card 1. The UV sensors 20 and 21 are connected to a control unit 12 of the code reading unit 8 via a cable. In the code reading unit 8, the arrangement patterns of the marks M are determined based on the output signals of the detectors of the UV sensors 20 and 21, and the number (rank) corresponding to the code C is also determined.

The cut card 1c has also code C and is determined to be the cut card by the code reading unit 8.

[0020]

In the code reading unit 8, the start and end of the reading performed by the UV sensors 20 and 21 are controlled by the control unit 12 based on the detection signals from the object detection sensors 22 and 23. Also, the control unit 12 determines whether a card 1 has properly passed through the card guide unit 7 based on the detection signals from the object detection sensors 22 and 23. As shown in Fig. 4, the rectangular marks M are arranged within a framework of two rows with four columns on each of the upper and bottom edges of the card 1, and the arrangement of such marks M indicates the rank (number) and the suit (Heart, Spade or the like) of the card 1. If the UV sensor(s) 20 and/or 21 detect(s) a mark M, such UV sensor(s) will give out an on signal. The code reading unit 8 determines the relative relation between the signals received from the two UV sensors 20 and 21. This enables the code reading unit 8 to identify the code based on the relative difference or the like between the two marks M detected by the two UV sensors 20 and 21, thereby identifying the number (rank) and the type (suit) of the corresponding card 1and the cut card 1c as well.

[0021]

The relation between the code C and the output of the on signals of th

e two UV sensors 20 and 21 are shown in Fig. 6. It is possible to identify a pre determined arrangement pattern of the marks M based on a comparison of the results of the relative changes in the output of the on signals of the UV sensors 20 and 21. As a result, in two rows (the upper and lower rows), four types of arrangement patterns of the mark M are possible, and since patterns are printe d in four columns, it is possible to form 256 types of codes (4 x 4 x 4 x 4). Fift y two (52) different playing cards are each assigned to one of the 256 codes, and the associations of such assignments are stored in a memory or by a program as an association table. The card reading unit 8 can, by identifying the code C, i dentify the number (rank) and the type (suit) of the card 1 based on that prede termined association table (not shown). Also, 52 cards can be freely associated wi th 52 codes out of the 256 codes to be stored in the association table, and thus, there will be a variety of associations between them. Therefore, it is possible to change the associations among the 256 codes C and the suits and ranks of the 52 cards depending on the time or place. Preferably, the code C is printed in a position where it does not overlap with the indications of the card types or ind exes with a paint material that becomes visible when irradiated with a UV ray.

[0022]

Next, the control unit 12 will be described in further detail. The control unit 12 is achieved by a computer apparatus, and includes the winner/loser det ermination unit 10 that automatically determines the winner/loser of a game, an d the like. This process function (in the control unit 12) is achieved by installing in a computer a program for determining the winner/loser, which is executed b y a computer processor. Also, the control unit 12 reads from the barcode 3 read by the barcode reader 100 or the input means 200 or RFID reading device 300, the shuffled card ID, which uniquely identifies the shuffled playing card set 1s, and stores the shuffled card ID in a reading memory 12M.

[0023]

The control unit 12 has further a function of identifying an exposition o f the cut card by the card reading unit 8 and memorizing this information as th

at the shuffled playing card set 1s now being used is will be or have changed t o the new one. The information of the exposition of the cut card is at least used for identifying an end of the current game using the shuffled playing cards set 1s currently set in the card shoe apparatus 2. The control unit 12 has also a fu nction of identifying specified events that occur during the use of the set of the shuffled playing cards 1s at a game table during the two expositions of the cut cards that is to say the shuffled playing card set 1s is being used and has chan ged to the new one at the event of identifying an exposition of the cut card 1c. The control unit 12 has a function of memorizing these the memory 12M and re porting these occurrences of the specified event to a database and main compute r 400 in a administration section of the casino.

[0024]

The specified events include at least one of the following:

(1) a reading error in the card reading unit of a card,

(2) an attempt to draw a card when no card should be drawn accordin g to the rules of the card game,

(3) the winner/loser of each card game during the use of the shuffled pl aying cards currently set in the card shoe apparatus, and,

(4) an improper shuffling of a set of shuffled playing cards set in the c ard shoe apparatus comprising the relative arrangement of predetermined numb er of cards.

[0025]

The information of the exposition of the cut card 1c and/or a new shuff led card ID reported by the control unit 12 to a database and main computer 4 00, and the occurrences of the specified event to a database 400 will be used for administrating at least one of the followings;

(1) an average time for one game during the use of the shuffled playin g cards currently set in the card shoe apparatus 2,

(2) an average error occurrences during the use of the shuffled playing cards set 1s currently set in the card shoe apparatus 2,

(3) monitoring of tendencies of the results of games during the use of t he shuffled playing cards set 1s, and

(4) the restart or reset of a monitor 500 for displaying results of games during each use of playing cards set 1s currently set in the card shoe apparatu s 2. The displaying of the results by the monitor 500 is reset every end of the u se of playing cards set 1s in casino as usual.

[0026]

When it comes to identifying the shuffled card ID the control unit 12 i dentifies and stores the uniquely identifiable shuffled card ID, then the control u nit 12 identifies that this ID is the ID of the shuffled playing card set 1s that i s currently being used in the game and the current time, and stores them in co nnection with the shuffled card ID. The control unit 12 identify each of the follo wing specified events that occur while the shuffled playing card set 1s identified by the shuffle card ID is being used at the game table to be stored in the me mory 12M in connection with the time of occurrence thereof. Also, the ordinal n umber of the card subject of the occurrence of the relevant event within the shu ffled playing card set 1s currently set in the card shoe apparatus, or the ordinal number of the game subject of the occurrence of the relevant event among the individual games played with such shuffled playing cards (the winner (the player or the banker) is determined for each individual game, and after betting chips are settled, the next individual game starts) is stored.

[0027]

The items of specified events to be stored the memory 12M in connecti on with the shuffled card ID include at least one of the following:

(1) a reading error in the cord reading unit 8 of a card in the identifie d shuffled playing card set;

(2) an end of a game due to an operation of an end button 53 to end t he use of the shuffled playing card set 1s currently set in the card shoe apparat us 2, or the drawing of the cut card 1c from the shuffled playing card set 1s cu rrently set in the card shoe apparatus 2;

(3) an attempt to draw a card when no card should be drawn accordin g to the rules of the card game;

(4) an attempt to move or insert a card in a direction opposite to a dra wing direction of the opening 13; and

(5) an occurrence of a preset irregular operation to be determined to be irregular by the card shoe apparatus 2.

[0028]

Note that the reading error in item (1) above refers to a failure by the cord reading unit 8 that reads two marks M of the card 1 to identify the card based on the association table due to the code that is read not being a predeter mined code, or a failure to identify the number (rank) and the type (suit) of the card 1 that correspond to the code read. With respect to item (2) above, the en d button 53 is pressed to end the use of the shuffled playing card set 1s current ly set in the card shoe apparatus 2. Upon this action, the end of a game is regi stered in the card shoe apparatus 2. Also, if the cut card 1c is drawn from the shuffled playing card set 1s currently housed in the card shoe apparatus 2, the game ends at the next game or after a few games, and the remaining cards of the shuffled playing card set 1s will not be used anymore. An attempt to draw any card when no card should be drawn according to the rules of the card gam e as described in item (3) above will be described later. Any attempt to insert a ny card in the opposite direction at the opening 13 as described in item (4) abov e refers to a case where the object detection sensors 22 and 23 detect a fraudule nt act such as the insertion of any card in the direction opposite to the direction of the movement of a card 1 (arrow F) under the relevant conditions, and assu mes a case where the object detection sensors 22 and 23 detect movement of a card 1 in the direction opposite to the arrow F. Any preset irregular situation th at will be determined by the card shoe apparatus 2 as irregular as described in item (5) above refers to, for example, a situation where the card 1 stays above t he object detection sensors 22 and 23 for a period longer than the predetermine d period, and such irregular situation has been input and stored in advance in t

he memory 12M as a program.

[0029]

The memory 12M stores the occurrence of any security item in connecti on with the relevant shuffled card ID read by the barcode 3, and when it stores a security item, it stores the time of occurrence of that security item as well. F or this purpose, the memory 12M includes a clock 12t. It also includes an exter nal transmission apparatus 300 for externally transmitting the occurrence of a s ecurity item with the shuffled card ID. Notice of the occurrence of a security ite m and the time of its occurrence is given to the management division or the pit of the casino via the external transmission apparatus 300 in connection with th e relevant shuffled card ID. The management division of the casino stores and r egisters such transmitted items in connection with the relevant shuffled card IDs in a database 400. The dealer or the like is also informed about the occurrence of a security item by the display made by lamps 51 and a liquid crystal displa y unit 52.

[0030]

Next, a variation in which an input means 200 is provided instead of t he barcode reader 100 that is capable of identifying the shuffled card ID will be described. Instead of reading the barcode 3 with the barcode reader 100 to iden tify the shuffled card ID of the card set currently being used, a configuration is possible in which a barcode reader is provided in a separate device installed on the game table (for example, an apparatus for the disposal of a card 1 or a devi ce that confirms the card 1 disposed), and the shuffled card ID [of the card set] to be used is obtained by such a barcode reader, and the shuffled card ID is inp ut to the card shoe apparatus 2 through communication 201 or another compute r with such a device. In this case, the separate device with the barcode reader s erves as an input apparatus capable of identifying the shuffled card ID.

[0031]

According to an exemplary embodiment of the present invention, the c ard shoe apparatus 2 may detect an irregularity in the manner in which the ca

rds are shuffled and in some cases generate an alert based on the detected irregularity. In this regard, the information collected by the card reading unit 8 as the cards are drawn from the card shoe apparatus 2 may be used to determine whether the cards have been shuffled improperly. An irregularity in the arrangement order of the cards will be described with reference to Fig. 8(a) and Fig. 8(b. Fig. 8(a) shows an example where the cards 1 drawn from the card housing unit have the same suit (Clubs) with sequential figures (number, rank) beginning from Ace. Fig. 8(b) shows an example where the cards 1 drawn from the card housing unit 2c consist of 9 cards with the same rank (3). Generally, the cards 1 are shuffled by a random number generator or the like so as to be arranged in a random order. The arrangement of the cards 301 shown in Figs. 8(a) and 8(b) is substantially non-random, thus indicating an irregular shuffling of the playing cards 1. Other examples of card arrangements which may indicate a shuffling irregularity include:

[0032]

(a) a case in which a predetermined number of cards within a set of cards exhibit a pattern in which the rank of a card is larger (or smaller) by one as compared to compared to the rank of the preceding card (for example, 1, 2, 3, 4, ---, K) (as shown in Fig. 8(a));

(b) a case where a predetermined number of cards in sequence have the same rank (for example, A, A, A, A, ---) (as shown in Fig. 8(b));

(c) a case where the same sequence is repeated throughout a predetermined number of cards (for example, A, Q, 10, A, Q, 10, ---);

(d) a case where a predetermined number of cards in sequence have the same suit (for example, 13 consecutive cards with Hearts);

(e) a case in which a predetermined number of cards in each of two or more sets of cards have the same sequence of suit and rank (A,5,Q,J,2,8,9,K,---). In particular, for each card game, a different set of cards may be housed in the card shoe apparatus 2.

[0033]

A shuffling irregularity may be detected if a predetermined number of cards in a later-used set match the same predetermined number of cards in an earlier-used set in terms of suit and/or rank sequence; and

(f) a case where the order of a predetermined number of cards matches an order registered in advance (for example, where the order of the cards matches the order of cards used in a separate card manufacturing process). Irregular shuffling patterns (such as examples (a) - (d)) as well as the sequence of suit and rank (e.g., A,5,Q,J,2,8,9,K,---) of card sets previously housed in the card shoe apparatus 304 may be stored in the memory 12M , and the control unit 12 may use this stored information to determine whether irregular shuffling has occurred. For example, irregular shuffling may be determined if the order of a predetermined number of cards 1 within a set matches at least a portion of the stored patterns. In another example, irregular shuffling may be determined if a number of card sets each used in one of a predetermined number of games include a predetermined number of cards that match the stored patterns.

[0034]

As another example, a shuffling irregularity may be determined when each deck of cards within a set of cards is detected to be shuffled in the same or substantially similar way. For example, a shuffling irregularity may be detected when, for a plurality of cards, the suit and rank of each card drawn are the same as those of the card preceding it by 52 cards. In such a case, shuffling of a plurality of decks has failed for some reason, and instead each of the 52 cards is arranged in the same order.

In general, a shuffling irregularity may be detected when a stored pattern continues throughout a predetermined number of cards. In this regard, a preliminary alarm of irregularity may be generated at some point prior to the stored pattern being detected in all of the predetermined number of cards. For example, a preliminary alarm may be generated upon the drawing of a card that is several cards before the end of a predetermined number of cards. The preliminary alarm may be in a form different from the final alarm, for example, by ch

aracters, in a certain color, or with a different lamp. In an exemplary embodiment, if a state does not continue to be irregular throughout a predetermined number of cards and returns to a random state, then the preliminary alarm may be cancelled.

[0035]

For each shuffled card ID of the shuffled playing card set 1s, when an event falling under any of the specified events (security items) occurs thereto, the management division or the pit of the casino is informed via an external transmission apparatus 600 of the fact and the time of said occurrence in connection with the relevant shuffled card ID, and such information is forwarded to the database 400 and stored therein. Furthermore, the dealer or the like is informed of the occurrence of a security item by the display made by the lamps 51 and the liquid crystal display unit 52. Such transmitted items are registered in the database 400 of the management division of the casino so that an item that falls under at least one of the following is registered in connection with the shuffled card ID identified with respect to the card set currently used in the game, thereby providing overall control of the operations of the casino or an efficient operation thereof.

[0036]

For the overall control of the operations of the casino or the efficient operation thereof, the management division of the casino register in the database and use, for example, the data items described below.

(1) the game table used;

(2) the dealer (person who draws the cards) in charge of the game table used;

(3) the start time of the use of the identified shuffled playing card set;

(4) the end time of the use of the identified shuffled playing card set;

(5) the time period when the card(s) of the identified shuffled playing card set were present on the game table;

(6) information concerning the pit or the card room where the identified sh

uffled playing card set is managed before it is delivered to the relevant game ta ble;

(7) information concerning the process of disposal of the identified shuffled playing card set after its use at the game table;

(8) information on whether all of the cards of the identified shuffled playin g card set have reached the disposal apparatus;

(9) information concerning the pit or the card room where the shuffled pla ying card set identified in advance is managed before it is delivered to the relev ant game table;

(10) information concerning the win and the lose at the game table where t he identified shuffled playing card set is used;

(11) the time period after the end of the game played using the identified s huffled playing card set and until the start of the next game with the new shuff led playing card set;

(12) the time period from the start to the end of the game played using the identified shuffled playing card set;

(13) information on the purchase or procurement of the identified shuffled pl aying card set;

(14) an average time for one game during the use of the shuffled playing card s currently set in the card shoe apparatus 2;

(15) an average error occurrences during the use of the shuffled playing cards set 1s currently set in the card shoe apparatus ;,

(16) monitoring of tendencies of the results of games during the use of the sh uffled playing cards set 1s, and

(17) the restart or reset of a monitor 500 for displaying results of games during each use of playing cards set 1s currently set in the card shoe apparatus 2. The displaying of the results by the monitor 500 is reset every end of the use of pl aying cards set 1s in casino as usual.

[0037]

An embodiment of the present invention has been described above, the

scope of the present invention also covers the following annexes.

[Annex 1]

[0038]

A table game system comprising:

shuffled playing cards composed of playing cards made up of a plurality of number of decks shuffled to have a unique arrangement order and a cut card, a uniquely identifiable shuffled card ID being attached to the shuffled playing cards and/or the cut card as an ID code; and

a card shoe apparatus that includes ID code identifying means and/or an input means capable of identifying the shuffled card ID, and houses the shuffled playing cards and the cut card,

the card shoe apparatus comprising:

a card housing unit for housing the shuffled playing cards;

an opening for drawing cards from the card housing unit one by one;

a card reading unit that reads from a card and the cut card information contained in the said card;

a control unit that stores rules of a card game and includes a winner/loser determination unit that determines the winner/loser of the card game based on the information on the ranks of the cards read by the card reading unit; and

a display unit that outputs a result of the winner/loser determined by the winner/loser determination unit,

the control unit has a function of identifying specified events that occur during the use of set of the shuffled playing cards at a game table, and of reporting these occurrences of the specified event,

and the control unit has further a function of identifying an exposition of the cut card and of sending information of the exposition of the cut card,

the information of the exposition of the cut card is at least used for identifying an end of the current game using the shuffled playing cards currently set in the card shoe apparatus, and

the specified events include at least one of the following:

(1) a reading error in the card reading unit of a card,

(2) an attempt to draw a card when no card should be drawn accordin g to the rules of the card game;

(3) the winner/loser of each card game during the use of the shuffled pl aying cards currently set in the card shoe apparatus, and,

(4) an improper shuffling of a set of shuffled playing cards set in the c ard shoe apparatus comprising the relative arrangement of predetermined numb er of cards; and

wherein the information of the exposition of the cut card is used for ad ministrating at least one of the followings;

(1) an average time for one game during the use of the shuffled playin g cards currently set in the card shoe apparatus,

(2) an average error occurrences during the use of the shuffled playing cards currently set in the card shoe apparatus,

(3) monitoring of tendencies of the results of games during the use of t he shuffled playing cards, and

(4) restart or reset of a monitor for displaying results of games during t he use of playing cards currently set in the card shoe apparatus.

[Annex 2]

[0039]

Table game system according to annex 1, wherein at least one of the fo llowing items is stored and forwarded to a database in connection with the shuff led card ID identified in relation to the card set in the card shoe apparatus:

(1) the game table used;

(2) the dealer (person who draws cards) in charge of the game table used;

(3) the start time of the use of the identified shuffled playing cards;

(4) the end time of the use of the identified shuffled playing cards;

(5) the time period when the identified shuffled playing cards were present on the game table;

(6) information concerning the pit or the card room where the identified sh

uffled playing cards are managed before it is delivered to the relevant game tabl e;

(7) information concerning the pit or the card room where the shuffled pla ying cards identified in advance is managed before it is delivered to the relevant game table;

(8) the time period after the end of the game played using the identified shuffled playing cards and until the start of the next game with the new shuffle d playing cards;

(9) the time period from the start to the end of the game played using the identified shuffled playing cards; and

(10) information on the purchase or procurement of the identified shuffled pl aying cards.

[Annex 3]

[0040]

A table game system according to annex 1 or 2, wherein the input mea ns of information capable of identifying the shuffled card ID is configured to obt ain shuffled card ID by a communication means or, wherein the improper shuffli ng for determining relative arrangement comprises determining at least one of r ank or suit of each of the predetermined number of cards drawn in sequence fro m the card shoe apparatus card shoe apparatus.

[Annex 4]

[0041]

A table game system according to annexes 1 to 3, wherein the improper shuffling for determining relative arrangement comprising whether the ranks o f cards increase or decrease in order, and/or wherein the improper shuffling for determining relative arrangement comprising whether each of the predetermined number of cards have the same rank and or wherein the improper shuffling for determining relative arrangement comprising whether each of the predetermine d number of cards are of the same suit and/or wherein the improper shuffling fo r determining relative arrangement comprising whether a repeating sequence of

rank or suit is present within the predetermined number of cards and/or wherei n the improper shuffling for determining relative arrangement comprising wheth er the determined relative arrangement matches a pre-stored relative arrangeme nt.

[Reference Signs List]

[0042]

1	card
1s	shuffled playing card set
2	card shoe apparatus
2C	card housing unit
3	barcode
8	code reading unit
10	winner/loser determination unit
12	control unit
13	opening

CLAIMS

1. A system for managing a card game, the system comprising:

a plurality of decks of playing cards shuffled in a unique order, the decks having a cut card;

a card shoe apparatus comprising:

a card housing part for housing the shuffled playing cards and the cut card;

an opening enabling drawing the playing cards from the card housing part one by one; and

a card reader for reading card information from each of the playing cards,

a display on which a result of a card game is displayed; and

a controller for identifying the cut card so as to determine an end of a use of the shuffled playing cards housed in the card shoe apparatus, wherein

the controller determines, based on the identified cut card, a relationship between a number of a plurality of games in which the shuffled playing cards currently housed in the card shoe apparatus are used and a time.

2. The system according to claim 1 further comprising a database communicably connected to the controller, wherein

the controller send information to the database for storing, the information relating at least one of:

an identification of a game table used in the game;

an identification of a dealer of the game table;

a use start time of the shuffled playing cards to the card game;

a use end time of the shuffled playing cards to the card game;

a time period during which the shuffled playing cards existed on the game table;

a pit or a card room in which the shuffled playing card are stored before transferred to the game table;

a time period until a new game in which a new shuffled playing cards starts after the game which was played using the shuffled playing cards ends;

a time period from a start to an end of the game which was

played using the shuffled playing cards; and

a purchase or obtaining of the shuffled playing cards.

3. The system according to claim 1, wherein the controller is configured to identify a specific event which occurred during using the shuffling playing cards, the specific event includes at least one of:

a reading error in the card reader;

a drawing error when a card is trying to be drawn when no cards are allowed to be drawn by a rule of the card game;

a determination of a winner/loser of each card game in which the shuffled playing cards are used; and

an improper shuffling of the playing cards housed in the card shoe apparatus.

4. The system according to claim 3, wherein an occurrence information of the specific event is sent to a remote terminal.

5. The system according to claim 1, wherein

the shuffling playing cards and/or the cut card has a card ID uniquely identifiable as ID code, and

the card shoe apparatus identifies the ID code.

6. The system according to claim 5, wherein

the controller performs, as an operation coupled to the ID code of the card housed in the card shoe apparatus based on the identification of the cut card, at least one of:

determining an average time of a game in which the shuffled playing cards currently housed in the card shoe apparatus is being used;

determining a number of average error occurrence during the shuffled playing cards currently housed in the card shoe apparatus is being used; and

monitoring a tendency of a game result in which the shuffled playing cards is being used;

7. The system according to claim 5 further comprising a database communicably connected to the controller, wherein

the controller send information to the database for storing, the

information relating at least one of:

an identification of a game table used in the game;

an identification of a dealer of the game table;

a use start time of the shuffled playing cards to the card game designated by the ID code;

a use end time of the shuffled playing cards to the card game designated by the ID code;

a time period during which the shuffled playing cards existed on the game table;

a pit or a card room in which the shuffled playing card are stored before transferred to the game table;

a time period until a new game in which a new shuffled playing cards starts after the game which was played using the shuffled playing cards ends;

a time period from a start to an end of the game which was played using the shuffled playing cards; and

a purchase or obtaining of the shuffled playing cards.

8. The system according to claim 5 further comprising a transmitting apparatus, wherein the specific event includes at least one of:

a reading error in the card reader;

a drawing error when a card is trying to be drawn when no cards are allowed to be drawn by a rule of the card game;

a determination of a winner/loser of each card game in which the shuffled playing cards are used; and

an improper shuffling of the playing cards housed in the card shoe apparatus.

9. The system according to one of claims 5 to 8, wherein the ID code is obtained by a communication means.