

SYSTEM AND METHOD FOR APPLYING ACCURATE THREE-DIMENSIONAL VOLUME TEXTURES TO ARBITRARY TRIANGULATED SURFACES

FIELD OF THE INVENTION

5 The invention relates to systems and methods for displaying graphical data, and more particularly to techniques for applying accurate three-dimensional volume textures to arbitrary triangulated surfaces.

BACKGROUND OF THE INVENTION

10 In some fields, it is useful to model real or computer-generated objects in three dimensions. Modeling such objects proves useful in a variety of applications. For example, modeling the subsurface structure of a portion of the earth's crust is useful for finding oil deposits, locating fault lines, and in other geological applications. Similarly, modeling human body parts is useful for medical training exercises, diagnoses, performing remote surgery, or for other
15 medical applications. Modeling computer-generated objects is useful in creating computer games, designing flight simulations, and other applications. Other applications for three-dimensional modeling of real and computer-generated objects exist.

20 Some three-dimensional models represent an object as a three-dimensional matrix of volume data points. Such a matrix, known as a data volume, includes a plurality of data points, known as volume data points. Each volume data point may be referred to as a volume pixel, also known as a voxel. A voxel is the smallest distinguishable box-shaped part of a three-dimensional image. A voxel is similar to a pixel, but represents a three-dimensional volume
25 rather than a two-dimensional area. Each voxel represents a discrete sampling of a three-dimensional portion of the object being modeled.

 Each voxel in the data volume contains a unique set of coordinates (x, y, z) and one or more data values that represent a specific property being examined. These data values may be illustrated on a scale (0-256) which

corresponds to a specific Red, Green, Blue color value (RGB) and opacity variable (A) that are derived from a measurement or value of the property being examined. The measurement or value of the property corresponds to the portion of the object that the voxel represents. This allows for a graphical representation
5 of the property being examined.

For example, in seismic or geological applications, seismic data is obtained by artificially creating sound waves and recording the arrival of these sound waves after they are reflected from interfaces of subsurface rock formations with different physical properties. A data volume representing the
10 subsurface structure is then created from the reflected sound waves, or seismic data. In such an example, each voxel contains a data value representing a transmission wave (*i.e.*, amplitude) from the reflected sound wave. Geological structure may be inferred from the displayed image of this data value. For example, the highest seismic amplitude data values may be represented by the
15 color red, slightly lower amplitude data values may be represented by the color orange, and other amplitude data values may be represented by other colors. Other color schemes are possible. This allows for a graphical representation of the seismic data.

Once a data volume has been created, its contents can be displayed to
20 users. A user may specify a three-dimensional surface contained within the volume, and a display system displays the voxels on this surface on a screen or other display medium. This enables a user to view voxels that are contained in the interior of the data volume.

One system for displaying the voxels on an arbitrary three-dimensional
25 surface is known as three-dimensional texture mapping. This technique is implemented in the raster processing unit of a computer graphics hardware accelerator. This technique uses a specific specialized memory, known as texture cache or texture memory, that is set aside on the integrated circuit.

In this technique, the texture cache is used as a buffer for the information
30 contained in the data volume. A block or portion of the data volume is read into

the texture cache, and information in this block is used by the raster processing unit. Subsequently, a second block of the data volume is read into the texture cache, and information in the second block is used by the raster-processing unit. This process continues until the entire data volume has been made available to the raster processing unit, one block at a time, through the texture cache. In this way, the texture cache is used as a buffer for the data volume.

Such a technique has certain inherent properties that render it inefficient for particular situations. For example, for data volumes that are large compared to the size of the available texture cache, the data volume must be broken up into blocks and each block must be swapped into the texture cache. This is inefficient because of the relatively large overhead required in determining the size of each block and reading it into the texture cache.

Furthermore, even though only the voxels that lie on the three-dimensional surface may be needed by the raster processing unit in such a technique, every voxel in the data volume is read into and stored in the texture cache. Thus, memory in the texture cache is not used efficiently because a relatively large amount of unneeded data may be stored in the texture cache. This problem is exacerbated when the three-dimensional surface is small compared to the data volume.

In addition, because a relatively large amount of texture cache is used in this operation, the amount of texture cache available to other graphics operations is limited. This limits the performance of the rendering of the object and limits the performance of other graphics operations.

There is a need among other things for a technique for displaying the contents of a data volume on an arbitrary three-dimensional surface contained within the volume, that uses a reduced amount of texture cache.

SUMMARY OF THE INVENTION

In one aspect, an embodiment of the invention overcoming these and other problems in the art relates to a method for applying a three-dimensional

volume texture to a polygon. The method includes the steps of providing a data volume comprising a plurality of volume data points, providing a polygonal surface partially or wholly contained within the data volume, the polygonal surface comprising at least one polygon, creating a set of texture atlases, each texture atlas comprising a two-dimensional layout of at least one polygon in the polygonal surface, and allocating a segment of memory for each texture atlas. The method also includes the steps of scan-converting each polygon based on the volume data points in the data volume and writing the results of the scan conversion of each polygon into the segment of memory allocated to the texture atlas containing a layout including the polygon.

In a further aspect, the invention includes a texture tile having tile dimensions describing a tile size and a representation of a polygon, the polygon being wholly or partially contained in a three-dimensional data volume.

In yet a further aspect, a texture atlas includes atlas dimensions describing an atlas size and a representation of a polygon, the polygon being wholly or partially contained in a three-dimensional data volume.

In yet an additional aspect, a segment of memory includes a plurality of texels (base units of textured graphics), the plurality of texels including one or more predetermined polygon texels and one or more predetermined non-polygon texels, wherein each polygon texel in the plurality of texels contains a value computed based on a volume data point in a data volume, and each other texel is invalid.

In a still further aspect, the invention includes a system for applying a three-dimensional volume texture to a polygonal surface. The system includes a texture cache configured to contain a plurality of texels, and a memory configured to contain a polygonal surface and a data volume, the polygon surface comprising one or more polygons and the data volume comprising one or more volume data points. The system also includes a control module configured to create a set of texture atlases, each texture atlas comprising a two-dimensional layout of at least one polygon in the polygonal surface, to allocate a segment of

the texture cache for each texture atlas, to scan-convert the at least one polygon, thereby creating one or more texels, and to write the one or more texels resulting from the scan conversion of each polygon into the segment of the texture cache allocated to the texture atlas containing a layout including the polygon.

5 BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described with reference to the accompanying drawings, in which like elements are referenced with like reference numerals, and in which:

Fig. 1 illustrates a data volume and a three-dimensional surface in
10 accordance with an embodiment of the invention.

Fig. 2 is a flow chart depicting a method for applying volume data to a surface in accordance with an embodiment of the invention.

Fig. 3 illustrates a set of texture tiles in accordance with an embodiment of the invention.

15 Fig. 4 illustrates a set of texture atlases in accordance with an embodiment of the invention.

Fig. 5 illustrates a segment of texture memory in accordance with an embodiment of the invention.

20 Fig. 6 illustrates a polygon before and after scan-conversion in accordance with an embodiment of the invention.

Fig. 7 is a block diagram of a system for applying a three-dimensional volume texture to a polygonal surface in accordance with an embodiment of the invention.

25 Fig. 8 is a flow chart depicting a method for polygon subdivision and texture tile creation in accordance with an embodiment of the invention.

Fig. 9 is a flow chart depicting a method for texture atlas generation in accordance with an embodiment of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Fig. 1 illustrates a data volume and a three-dimensional surface in accordance with an embodiment of the invention. A data volume **100** may be or include a three-dimensional model of a real or computer-generated object. The data volume **100** may be or include a three-dimensional matrix of volume data points **102a-d**.

Each of the volume data points **102a-d** may contain one or more values that describe a particular portion of the data volume **100**. For example, each of the volume data points **102a-d** may contain x, y, z coordinates that specify the location of a portion of the data volume **100**. Each of the volume data points **102a-d** may further contain one or more data values corresponding to one or more specific properties. For example, each of the volume data points **102a-d** may contain a data value corresponding to a seismic property, a density, or some other property.

In one implementation, each of the volume data points **102a-d** may be or include a voxel. Each voxel may be displayed as a combined color value and opacity variable (RGBA) that are derived from a measurement or value of a specific property.

The data volume **100** may be defined in any coordinate system, for example, in a Cartesian coordinate system with an origin **104**.

A polygonal surface **106** may be wholly or partially contained in the data volume **100**. The polygonal surface **106** may be a two- or three-dimensional surface that is chosen or specified by a user or by a computer. The polygonal surface **106** may be chosen to enable a user to examine the volume data points **102a-d** that intersect the polygonal surface **106**. The polygonal surface **106** may, in some applications, be chosen in order to exactly or approximately model a

naturally occurring surface. For example, the polygonal surface **106** may be chosen in order to model an interface between layers of the earth's crust.

The polygonal surface **106** may be defined by one or more polygons **108a-d**. Various methods for describing each polygon are possible. For example, each polygon may be defined by a set of vertices and edges. In one implementation, the polygons **108a-d** are triangles, and each of the polygons **108a-d** is defined by the Cartesian coordinates of its vertices.

Fig. 2 is a flow chart depicting a method for applying volume data to a surface in accordance with an embodiment of the invention. The method begins in step 200, wherein a data volume **100** may be provided. The data volume **100** may be generated from measured data such as seismic data, or may be otherwise generated.

In step 202, a polygonal surface **106** may be provided. The polygonal surface **106** may be user- or computer-specified. The polygonal surface **106** may be chosen in order to examine the volume data points **102a-d** that intersect the polygonal surface **106**. The polygonal surface **106** may be chosen to exactly or approximately model a naturally occurring surface or may be otherwise chosen.

In step 204, compressed indexing of the polygons **108a-d** may be removed. In some implementations, the polygons **108a-d** may be represented using a form of compressed indexing also referred to as vertex indexing or triangle stripping. For example, **110a-d** each represent a vertex shared by two or more polygons. In order to remove this form of compressed indexing and assign a set of vertices unique to each polygon for separate identification, each vertex **110a-d** is assigned a vertex number V_n and a polygon number P_n . In this manner, each polygon can be separately indexed according to its own set of vertices. For example, the polygon bound by **110a-c** would be represented by $V_n=0,1,2$ and $P_n=0$; the polygon bound by **110b-d** would be represented by $V_n=0,1,2$ and $P_n=1$; and the polygon bound by **110c-e** would be represented by $V_n=0,1,2$ and $P_n=2$. Other methods of removing this and other forms of compressed indexing may be well known in the art and therefore, are not repeated here.

In step 206, polygons **108a-d** may be subdivided. This step may ensure that each polygon **108a-d** may fit onto a texture tile in step 208. In one implementation, a maximum texture tile size is specified. In this implementation, some polygons may not fit onto the largest permissible texture tile. In this case, these polygons may be subdivided into smaller polygons that fit onto texture tiles of permissible size.

In step 208, a texture tile may be created for each polygon **108a-d**. The texture tiles created in this step are described with reference to Fig. 3. Each texture tile **300a-d** may include or represent a two-dimensional array or other portion of electronic memory that is sized to fit a particular polygon **108a-d**. If a particular polygon **108a-d** is smaller than the predetermined size of the tile, then, in one implementation, each texture tile **300a-d** includes the smallest two-dimensional array that contains a particular polygon **108a-d**. In another implementation where a particular polygon **108a-d** is smaller than the predetermined size of the tile, each texture tile **300a-d** includes the dimensions of an array that is large enough to contain a particular polygon **108a-d**, but does not contain the physical array itself.

Each texture tile **300a-d** may contain information describing the particular corresponding polygon **108a-d**. For example, each texture tile may comprise coordinates (x, y, z) of the vertices for each corresponding polygon **108a-d**, and a number (Pn) which identifies the polygon.

Each texture tile **300a-d** may also contain a number (Tn) that identifies the tile, a number (An) that identifies the texture atlas created in step 210 that is associated with the tile, coordinates (s',t') that identify the location of the tile on the texture atlas, coordinates (s, t) that identify the position of the tile in the displayed image, and coordinates (x', y') that identify an origin for the polygonal surface **106**.

In step 210, the texture tiles **300a-d** may be combined to form one or more texture atlases. The texture atlases created in this step are described with reference to Fig. 4. Each texture atlas **400a-c** may be or include a two-

dimensional layout of texture tiles **300a-d**. Each texture tile **300a-d** may be placed into one texture atlas **400a-c**. If there is no space in any existing texture atlas **400a-c**, a new texture atlas **400a-c** may be created. In some implementations, a user may specify a target or maximum size for each texture
5 atlas **400a-c**.

In another implementation, each texture atlas **400a-c** may be or include a two-dimensional array or other type of electronic memory that is configured to contain one or more texture tiles **300a-d**. In yet another implementation, each texture atlas **400a-c** may contain information about how the texture tiles **300a-d**
10 could be optimally arranged in a two-dimensional layout, including where each texture atlas **400a-c** is located in the memory segment **500** discussed in reference to step 212. In this implementation, it may be unnecessary for the texture atlases to contain enough physical memory to contain each texture tile **300a-d**.

As thus described, the creation of the texture tiles **300a-d** in steps 206 and
15 208 and the creation of the texture atlases **400a-c** in step 210 may be performed in an optimized fashion. This will reduce or minimize empty or unused space in the texture tiles **300a-d**, the texture atlases **400a-c**, or both. In this manner, the available texture memory space is optimized using the foregoing techniques. Other well-known optimization techniques, such as those described in the paper
20 *Fast Line Integral Convolution for Arbitrary Surfaces in 3D* by Battke, Stalling and Hege published in the 1997 edition of *Visualization and Mathematics*, may also be applied.

In step 212, a memory segment may be allocated for each texture atlas **400a-c**. The memory segments allocated in this step are described with reference
25 to Fig. 5. The dimensions of the memory segment **500** allocated for a particular texture atlas **400a** may equal to or may be proportional to the dimensions of the texture atlas **400a**. The memory segment **500** may be or include one or more segments of texture memory or texture cache. The memory segments **500** may include a plurality of texels **502a-d**. A texel is the base unit of a textured graphic,
30 a graphic that defines the surface of a three-dimensional object. The texels **502a-d** may be indivisible units of texture present in the memory segment **500**.

One or more texels **502a** and **502b** may correspond to a portion of the texture atlas **400a** that is wholly or partially contained within a polygon **108d**. These texels **502a** and **502b** may be referred to as polygon texels. One or more texels **502c** may correspond to a portion of the texture atlas **400a** that is contained
5 within a texture tile **300d**, but is not contained within any polygon **108a-d**. These texels may be referred to as tile texels. One or more texels **502d** that are neither polygon texels nor tile texels may be included in the memory segment **500**. Because the information contained in the texture atlas and the texture tiles may be used to determine which of the texels in the memory segment are polygon texels,
10 the polygon texels in the memory segment **500** may be considered to be predetermined.

In step 214, each polygon **108a-d** may be scan-converted. The step of scan converting a polygon is described with reference to Fig. 6. Scan conversion is the process by which data values contained in the data volume **100** are mapped
15 into texels. One or more of the volume data points **102a-d** in the data-volume **100** may intersect the particular polygon **108d**. From the information contained in these intersecting volume data points **102a-d**, texels **600a-d** are created that correspond to the volume data points **102a-d**. If the volume data points **102a-d** include voxels, the voxels may be mapped into corresponding texels **600a-d**
20 using a well-known mathematical technique referred to as tri-linear interpolation. Using this technique, each texel is determined by a linear weighting of the eight (8) voxels that are nearest the texel in the data-volume **100**. The texels **600a-d** that are created in the scan-conversion may correspond to the polygon texels **502a-b** that are contained in the memory segment **500**. The arrangement of the
25 texture tiles within each texture atlas, and the location of each texture atlas within the memory segment, is not set until this step.

In step 216, results of the scan-conversion may be written to the memory segment **500**. This may include writing the texels **600a-d** into the polygon texels **502a-b** in the memory segment **500**. In one implementation, each texel **600a-d**
30 maybe written to a corresponding polygon texel **502a-b** as it is created. In another implementation, texels **600a-d** corresponding to a particular polygon **108a-d** may be created, and all the texels **600a-d** for the polygon **108a-d** may be

written to the memory segment **500**. In other implementations, texels **600a-d** corresponding to a particular texture atlas **400a-c** may be created and written as a group, or all texels corresponding to all polygons **108a-d** may be created and written as a group.

5 The memory segment **500** may contain one or more texels **502c-d** that are not polygon texels. These texels may not contain information that is useful in the rendering of the surface **106**. Therefore, these texels may be considered invalid. In one implementation, the invalid texels **502c-d** may be blank texels, texels containing only initial values, or texels that are otherwise specifically marked
10 invalid. In another implementation, invalid texels **502c-d** may contain texel data, for example texel data from a previous surface rendering or another operation.

 After all the polygon texels **502a-b** for all polygons in the polygonal surface **106** have been written to the memory segments **500**, the memory segments **500** may contain the required information to display the information
15 contained in the data volume **100** on the surface **106**.

 In step 218, the results may be displayed to a user. The contents of the memory segments **500** may be displayed via a cathode ray tube or other screen, may be printed, or may be otherwise displayed.

 The method may be performed in conjunction with other systems and
20 methods for graphically displaying volume data. For example, the method can be used in conjunction with a system for analyzing and imaging three-dimensional volume data sets described in the commonly-owned U.S. Patent Application "System and Method for Analyzing and Imaging Three-Dimensional Volume Data Sets," serial number 09/119,635, which is incorporated herein by reference.
25 When practicing the present invention in conjunction with such a device, a number of sampling probes, or user-specified surfaces, can be created, shaped, sized, and moved interactively by the user within the whole 3D volume data set. The intersection of the sampling probe with the whole 3D volume data set is texture mapped onto the surfaces of the sampling probe, or volume rendered with
30 varying degrees of transparency within the sampling probe. For example, as the

user moves the sampling probe, such as by “clicking and dragging” with a “mouse,” the user perceives the texture on the surfaces of the sampling probe changing in “real-time” with movement of the sampling probe. In this manner, the user can interactively move the sampling probes through the whole 3D volume, and more easily and effectively visualize and interpret the features and physical parameters that are present within the geographic space represented by the whole 3D volume data set.

Referring now to Fig. 7, a block diagram of a system for applying a three-dimensional volume texture to a polygonal surface is shown in accordance with an embodiment of the invention. A system **700** may include a texture cache **702** containing a plurality of texels **704**. The system **700** also includes a memory **706** which may contain a polygonal surface **106** and a data volume **100**. The polygonal surface **106** may be represented in the memory **706** by a plurality of vertex coordinates describing a plurality of polygons **108a-d** or by some other method. The data volume **100** may be represented in the memory **706** by a plurality of volume data points **102a-d**. Each of the volume data points **102a-d** may be or include a voxel.

The system **700** also contains a control module **708**. The control module **708** may be capable of executing computer-executable instructions. The control module **708** may include or reference computer-executable instructions **710**. The computer-executable instructions **710** may be stored in the control module **708**, in the memory **706**, or in another location. The control module **708** may execute the computer-executable instructions **710** in order to perform various functions.

The control module **708** may be configured to perform various functions by executing the computer-executable instructions **710**. The control module **710** may be configured to remove compressive indexing from the polygonal surface **106**, for example, by distinctly representing each vertex of each polygon **108a-d** in the polygonal surface **106**. The control module **708** may also be configured to subdivide those polygons **108a-d** in the polygonal surface **106** that are larger than a maximum permissible tile size.

The control module **708** may also be configured to create a texture tile **300a-d** for each polygon **108a-d** contained in the polygonal surface **106**. The control module **708** may store the texture tiles **300a-d** in the memory **706** or elsewhere. The control module **708** may further be configured to combine the
5 texture tiles **300a-d** in one or more texture atlases **400a-c**. The control module **708** may store the texture atlases **400a-c** in the memory **706** or elsewhere.

The control module **708** may further be configured to allocate a segment **710a-c** of the texture cache **702** for each of the texture atlases **400a-c**. The control module **708** may also be configured to scan-convert each polygon **108a-d**
10 in the polygonal surface **106** based on the volume data points **102a-d** contained in the data volume **100**. The results of the scan conversion may be one or more texels, which may be written to the texels **704** of the texture cache **702**. The texels **704** that are written as the result of a scan-conversion of a particular polygon **108a** may be texels **704** that are contained in the segment **710a** that is
15 allocated to the texture atlas **400a** that contains a layout including the polygon **108a**.

The control module **708** may also be configured to display the results of the scan-conversion to a user via a cathode ray tube, other screen, printer, or other display device.

20 Fig. 8 is a flow chart depicting one implementation of a method for polygon subdivision and texture tile creation in accordance with an embodiment of the invention. This method may be one implementation of steps 206 and 208 in Fig. 2.

The method begins in step 800, wherein a polygon set may be created.
25 The polygon set may be a representation of the polygons **108a-d** that make up a polygonal surface **106**. In one implementation, the step 800 of creating a polygon set may include removing compressive indexing in the representation of the polygons **108a-d**. In another implementation, the polygons may already be represented without compressive indexing.

In step 802, a texture tile set may be created. The texture tile set may be configured to hold one or more texture tiles **300a-d**. The texture tile set may contain a maximum texture tile size, which may be represented by a width and a height. The texture tile set may not contain any texture tiles **300a-d** when it is
5 created.

In step 804, the polygon set is examined to determine whether any unprocessed polygons **108a-d** remain in the polygon set. If the polygon set does not contain one or more unprocessed polygons, the method is complete, and the method ends in step 806.

10 If the polygon set contains one or more unprocessed polygons **108a-d**, one of the unprocessed polygons **108a-d** is selected in step 808. In step 810, the polygon **108a-d** is examined in order to determine whether the polygon **108a-d** will fit in a texture tile **300a-d** of the maximum permissible size. If the polygon **108a-d** will not fit in a texture tile **300a-d** of the maximum permissible size, the
15 polygon **108a-d** may be subdivided in step 812. Subdivision may be any process by which several smaller polygons **108a-d** are created, the union of which is the original polygon **108a-d**. In one implementation, the polygon **108a-d** is subdivided bisecting the longest edge of the polygon **108a-d**, and by creating a new edge at the bisection point of a vertex of the polygon **108a-d**. In another
20 implementation, the polygon **108a-d** may be subdivided by centroid degeneration. This may include finding the centroid of the polygon **108a-d**, and creating a new edge from each vertex of the polygon **108a-d** to the centroid.

In step 814, the polygons **108a-d** resulting from the subdivision may be placed in the polygon set. This may ensure that each of these polygons **108a-d** is
25 subdivided if necessary, and that a texture tile **300a-d** is created for each.

In step 816, the original polygon **108a-d** may be marked as processed. This may include, for example, setting a Boolean variable or otherwise denoting that the polygon **108a-d** has been examined. A texture tile **300a-d** need not be created for the original polygon **108a-d** since texture tiles **300a-d** for the
30 polygons **108a-d** resulting from the subdivision will be created.

If it is determined in step 810 that the polygon **108a-d** being examined will fit into a texture tile **300a-d** of maximum permissible size, a new texture tile **300a-d** may be created in step 818. The texture tile **300a-d** that is created may include the polygon **108a-d** or may contain information describing the polygon

5 **108a-d**. In one implementation, the dimensions of the texture tile **300a-d** may be chosen to reduce the size of the texture tile **300a-d** while ensuring that the texture tile **300a-d** contains the polygon **108a-d**. For example, in one implementation, the texture tile **300a-d** may be the smallest rectangular texture tile **300a-d** that contains the polygon **108a-d**.

10 In step 820, the texture tile **300a-d** may be added to the texture tile set. The method then continues in step 816, wherein the polygon **108a-d** is marked as processed. The method returns to step 804, wherein it is determined if there are any unprocessed polygons **108a-d** remaining in the polygon set.

Fig. 9 is a flow chart depicting one implementation of a method for

15 texture atlas generation in accordance with step 210 in Fig. 2. The method begins in step 900, wherein a texture atlas set may be created. The texture atlas set may be configured to hold one or more texture atlases **400a-c**. The texture atlas set may contain a maximum texture atlas size, which may be represented by a width and a height. The texture atlas set may not contain any texture atlases **400a-c**

20 when it is created.

In step 902, a texture tile set may be examined to determine whether any unprocessed texture tiles **300a-d** remain in the texture tile set. The texture tile set examined may be the texture tile set created in the method of Fig. 8. If the texture tile set does not contain one or more unprocessed texture tiles **300a-d**, the

25 method is complete, and the method ends in step 904.

If the polygon set contains one or more unprocessed texture tiles **300a-d**, one of the unprocessed texture tiles **300a-d** is selected in step 906. In step 908, the texture tile **300a-d** and the atlas set are examined in order to determine whether the texture tile **300a-d** will fit into any texture atlas **400a-c** contained in

30 the texture atlas set. If the texture tile **300a-d** will not fit into any texture atlas

400a-c, a new texture atlas **400a-c** may be created in step 910. The new texture atlas **400a-c** may be placed in the texture atlas set. In one implementation, empty space in the texture atlas **400a-c** is represented by empty texture tiles **300a-d** in the texture atlas **300a-c**. These may be texture tiles **300a-d** that are specifically marked as empty. In this implementation, a single empty texture tile **300a-d**, of the dimensions of the texture atlas **400a-c**, may be added to the texture atlas **400a-c**.

In step 912, the texture tile **300a-d** selected in step 906 may be added to a texture atlas **400a-c** in the texture atlas set. In one implementation, the placement of the texture tile **300a-d** may be performed in an optimized fashion or in another fashion to reduce the empty space in the texture atlases **400a-c**.

In one implementation, empty space in each texture atlas **400a-c** is represented by empty texture tiles **300a-d**. In this implementation, the texture tile **300a-d** being added to the texture atlas set may be placed in the location of the empty texture tile **300a-d** that has the smallest area difference with the texture tile **300a-d** being added. Once the texture tile **300a-d** has been added, new empty texture tiles **300a-d** may be created. These new empty texture tiles **300a-d** may cover the area of the texture atlas **400a-c** that was previously covered by the empty texture tile **300a-d**, but is not covered by the texture tile **300a-d** that was added. These new empty texture tiles **300a-d** may be placed in the location of the area difference between the added texture tile **300a-d** and the empty texture tile **300a-d**.

In step 914, the texture tile **300a-d** may be marked as processed. This may include, for example, setting a Boolean variable or otherwise denoting that the texture tile **300a-d** has been placed in the texture atlas set. The method returns to step 902, wherein it is determined if there are any unprocessed texture tiles **300a-d** remaining in the texture tile set.

The foregoing description of the invention is illustrative, and modifications in configuration and implementation will occur to persons skilled in the art. For instance, steps can be combined or may be performed in any order.

While texture tiles and texture atlases have been described as physical segments of electronic memory capable of containing one or more polygons, they need not physically contain this memory. Rather, the texture tiles or texture atlases may include data specifying the dimensions of a sufficient segment of memory.

- 5 Hardware, software or other resources described as singular may in embodiments be distributed, and similarly in embodiments resources described as distributed may be combined. The scope of the invention is accordingly intended to be limited only by the following claims.

CLAIMS

1. A method for displaying graphical data, the graphical data comprising at least one volume-data point within a data volume, the method comprising the steps of:
 - 5 creating a texture atlas, the texture atlas comprising a two-dimensional layout of at least one polygon in a polygonal surface;
allocating a memory segment for the texture atlas and the data volume;
scan-converting the at least one polygon to form a corresponding texel;
writing the texel into the memory segment; and
 - 10 determining an intersection of the texel and the polygonal surface.
2. The method of claim 1, wherein the at least one polygon is a triangle.
3. The method of claim 1, wherein the data volume is a seismic data volume comprising at least one attribute from amplitude, phase, frequency,
15 semblance and coherency.
4. The method of claim 1, further comprising the step of creating a texture tile.
5. The method of claim 4, further comprising the steps of:
 - 20 determining whether the at least one polygon fits within a predetermined maximum texture tile size;
subdividing the at least one polygon into a plurality of component polygons if it does not fit within the maximum texture tile size;
and
 - 25 marking the at least one polygon and each of the plurality of component polygons that fit within the maximum texture tile size.

6. The method of claim 5, further comprising the step of creating a texture tile set, the texture tile set comprising a plurality of texture tiles, the plurality of texture tiles including the texture tile, each of the plurality of texture tiles containing at least one of the at least one polygon and the plurality of
5 component polygons.

7. The method of claim 5 wherein the at least one polygon that does not fit within the maximum tile size comprises a longest edge, a midpoint on the longest edge and a vertex.

8. The method of claim 7, further comprising the steps of:
10 creating an edge between the midpoint and the vertex; and
performing a centroid degeneration.

9. The method of claim 6, further comprising the steps of:
determining whether each of the plurality of texture tiles fit within a predetermined maximum texture atlas size;
15 assigning each of the plurality of texture tiles that fit within the maximum texture atlas size to the texture atlas;
assigning each of the plurality of texture tiles that do not fit within the maximum texture atlas size to a new texture atlas; and
marking each of the plurality of texture tiles that are assigned to the
20 texture atlas and the new texture atlas.

10. The method of claim 9, further comprising the step of comparing a tile size for each of the plurality of texture tiles with the maximum texture atlas size, each of the plurality of texture tiles assigned to the texture atlas and the new texture atlas being assigned to minimize a difference between a collective tile size
25 for the plurality of texture tiles assigned to the texture atlas and the maximum texture atlas size and to minimize a difference between a collective tile size for the plurality of texture tiles assigned to the new texture atlas and the maximum texture atlas size.

11. The method of claim 1, wherein the memory segment comprises texture cache.
12. The method of claim 1, wherein the texel is based on a corresponding volume-data point.
- 5 13. The method of claim 1, further comprising the step of processing a representation of the at least one polygon to remove any compressive indexing.
14. The method of claim 13, wherein processing the representation of the at least one polygon comprises representing at least one vertex for the polygon.
- 10 15. The method of claim 1, further comprising the step of displaying at least a portion of the intersection of the texel and the polygonal surface to a user.
16. A texture atlas comprising:
- a texture tile;
- 15 a number that identifies the texture tile;
- a number that identifies the texture tile location on the texture atlas;
- a texture atlas dimension;
- a texture atlas aspect ratio; and
- coordinates that identify the position of the texture atlas in a memory
- 20 segment designated for the texture atlas.
17. The texture atlas of claim 16, wherein the texture tile comprises:
- a representation of a polygon, the representation of the polygon comprising vertices, the vertices being at least partially contained in a three-dimensional data volume;
- 25 coordinates that identify an origin of the polygon;

a number that identifies the polygon;

a tile dimension;

a number that identifies the tile;

a number that identifies the texture atlas that contains the tile;

- 5 coordinates that identify the location of the tile on the texture atlas; and
coordinates that identify the position of the tile in a displayed image.

18. The texture atlas of claim 17, wherein the data volume comprises seismic data, the seismic data comprising at least one attribute from amplitude, phase, frequency, semblance and coherency.

- 10 19. The texture atlas of claim 17, wherein the polygon is a triangle.

20. The texture atlas of claim 17, wherein the representation of the polygon comprises distinct coordinates for each of its vertices.

21. The texture atlas according to claim 16, wherein the memory segment comprises texture cache.

- 15 22. A system comprising a program storage device readable by a machine, the program storage device embodying a program of instructions executable by the machine for displaying graphical data, the graphical data comprising at least one volume data point within a data volume, the instructions comprising the steps of:

20 creating a texture atlas, the texture atlas comprising a two-dimensional layout of at least one polygon in a polygonal surface;

allocating a memory segment for the texture atlas and the data volume;

scan-converting the at least one polygon to form a corresponding texel;

writing the texel into the memory segment; and

- 25 determining an intersection of the texel and the polygonal surface.

23. The system of claim 22, wherein the at least one polygon is a triangle.

24. The system of claim 22, wherein the data volume is a seismic data volume comprising at least one attribute from amplitude, phase, frequency,
5 semblance and coherency.

25. The system of claim 22, wherein the texture atlas comprises a texture tile.

26. The system of claim 25, further comprising the step of creating a texture tile set, the texture tile set comprising the texture tile and another texture
10 tile.

27. The system of claim 26, wherein the texture atlas comprises at least one of the texture tile and the another texture tile.

28. The system of claim 27, further comprising the step of creating a texture atlas set, the texture atlas set comprising the texture atlas and another
15 texture atlas, the another texture atlas comprising at least one of the texture tile and the another texture tile.

29. The system of claim 25 wherein the texture tile contains the polygon.

30. The system of claim 22, wherein the memory segment comprises
20 texture cache.

31. The system of claim 22, wherein the texel is based on a corresponding volume data point.

32. The system of claim 22, further comprising the step of processing a representation of the at least one polygon to remove any compressing indexing.

25 33. The system of claim 32, wherein the processed representation of the at least one polygon comprises at least one vertex for the polygon.