

9805725-0



IPOS

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 35/22		A1	(11) International Publication Number: WO 97/46463
			(43) International Publication Date: 11 December 1997 (11.12.97)
(21) International Application Number: PCT/US97/08623 (22) International Filing Date: 21 May 1997 (21.05.97) (30) Priority Data: 08/659,734 6 June 1996 (06.06.96) US 08/758,986 2 December 1996 (02.12.96) US (71) Applicant: COLGATE-PALMOLIVE COMPANY [US/US]; 300 Park Avenue, New York, NY 10022 (US). (72) Inventors: CONNAN, Patrick, A.; 19 Chrystal Drive, Lebanon, NJ 08833 (US). MACK, Robert; 1 Grandview Circle, Flemington, NJ 08822 (US). MUSTAFA, Ramon, Afmando, Mejia, 33 Baker Circle, Hillsborough, NJ 08876 (US). MASTERS, James, G.; 9 Londonderry Drive, Flemington, NJ 08822 (US). SULLIVAN, Richard, J.; 1015 Blueberry Court, Edison, NJ 08817 (US). PRENCIPE, Michael; 39 Spruce Street, West Windsor, NJ 08550 (US). (74) Agent: McGREAL, Michael, J.; Colgate-Palmolive Company, 909 River Road, Piscataway, NJ 08855-1343 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG , SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(54) Title: UNIFORM DISPENSING MULTICHAMBER TUBULAR CONTAINERS			
(57) Abstract			
A multichamber container must have certain characteristics in order to uniformly dispense the contents of each chamber from the container. The outer wall of the container and the inner divider web walls must have certain characteristics. The inner divider web walls must be highly flexible while the outer container wall must be less flexible. The Deflective Force for the outer wall must be greater than the Deflective Force for the web walls. In addition, to alleviate the problem of suckback of air into the container chambers, the outer wall should exhibit a specific Retention Index. This is a measure of the outer wall to remain deflected after the removal of the deflecting force. The inner divider web wall will have a lower Retention Index than the outer wall. By the proper selection of outer wall and web walls, there can be uniform dispensing from the dispenser.			