A single-axis electrically-steered panel is much simpler and less expensive than a full two-dimensional scanning phased array, but has a narrow azimuthal beamwidth, which maintains the high requirements on pointing accuracy and response time on the mechanical actuators.

Phased arrays of electrically-reconfigurable RF lens modules, as in U.S. Patent No. 10,116,051 to Scarborough et al., offer a number of advantages in power consumption and component count over conventional phased arrays for SATCOM, radar, and other purposes.

SUMMARY

The disclosure pertains generally to a radio-frequency lens array that employs tilted elements, tilted sub-arrays, and/or a degree of azimuthal mechanical scan to all or a subset of the lens elements. The addition of mechanical rotation allows for a reduction to the required scanning range, and therefore feed count, of each lens element. The azimuthal scan that the mechanical rotation provides also enables various configurations of tilted elements and tilted arrays. Tilting the individual lens elements and/or tilting the arrays provides improved gain performance at scan compared to a standard planar-phased array, while maintaining a low profile compared to gimbaled antennas.

According to an aspect, there is an antenna system comprising a substantially planar phased array of radio-frequency lens modules, and a mechanical actuator, said lens modules mounted to said mechanical actuator, wherein each of said lens modules is configured to electronically scan in a first azimuth; the planar array has the same scan profile for every azimuth angle; and said mechanical actuator is configured to mechanically rotate said lens modules to scan in a second azimuth.

In an example according to the present disclosure, there is an antenna system comprising a primary phased array of radio-frequency lens modules, each of said lens modules being configured to electronically scan in a first azimuth, and a secondary phased array of radio-frequency lens modules where each lens module is tilted in elevation at a fixed angle with respect to the primary phased array toward the first azimuth.

In a further example according to the present disclosure, there is an antenna assembly comprising: a platform having a primary portion and a secondary portion, said secondary portion angled to be offset with respect to said primary portion; a primary phased lens array mounted to the primary portion of said platform, said primary lens array having a plurality of primary antenna lens assemblies; and a secondary phased lens array mounted to the secondary portion of said platform, said secondary lens array having a plurality of secondary antenna lens assemblies, whereby said secondary lens array is angled to be offset with respect to said primary lens array.

In an embodiment, a planar array of a plurality of lens modules is mechanically rotated. This configuration allows for a significant reduction in the scan range, and therefore feed count, required of each lens element. The elements themselves primarily provide elevation scan with limited range of azimuth scan. The main azimuth scan is provided by the mechanical rotation. Unlike a standard phased array that has been configured for single-axis scanning, the lens array maintains a degree of two-dimensional scanning capability within the beamwidth of the lens element pattern (typically 5-15 deg). In this way, the antenna can electrically scan (for example) within any +/- 5 deg cone of all points on the line between 0 and 65 deg parallel with the Azimuth=0 deg axis relative to the panel itself.

In order to increase scanned gain performance from the above configuration, the array can be tilted towards the horizon in a specified azimuth angle. The provides a larger projected area of the array facing the scan direction, thereby increasing the scanned gain.

CLAIMS:

1. An antenna system comprising:
    a. a substantially planar phased array of radio-frequency lens modules; and
    b. a mechanical actuator, said lens modules mounted to said mechanical actuator;
    wherein each of said lens modules is configured to electronically scan in a first azimuth;
    the planar array has the same scan profile for every azimuth angle; and
    said mechanical actuator is configured to mechanically rotate said lens modules to scan in a second azimuth.

2. The antenna system of Claim 1 where the second azimuth overlaps with or is different than the first azimuth to scan over a combined 360 degrees.

3. The antenna system of Claim 1 or 2 where each lens module is individually tilted in elevation with respect to the actuator towards the first azimuth.

4. The antenna system of any of Claims 1-3 further comprising a rotation platform connected to said actuator where said array is mounted to said rotation platform and said rotation platform is tilted with respect to the actuator toward the first azimuth.

5. The antenna system of Claim 4 where each lens module is individually tilted in elevation with respect to the rotation platform towards the first azimuth.

6. The antenna system of any of Claims 1-5 wherein the lens modules are configured to electronically scan in an elevation plane.