

DESCRIPTION

BASE STATION DEVICE, MOBILE STATION, RADIO
COMMUNICATION SYSTEM, AND COMMUNICATION CONTROL
5 METHOD

TECHNICAL FIELD

The present invention relates to a LTE
(Long Term Evolution) system and specifically
10 relates to a base station apparatus, a mobile
station, and a communication control method.

BACKGROUND ART

A communication system as a successor of W-
15 CDMA and HSDPA, namely, a Long Term Evolution (LTE)
system has been considered by a W-CDMA
standardization organization 3GPP. As a radio access
scheme, Orthogonal Frequency Division Multiplexing
(OFDM) is under consideration for downlink, and
20 Single-Carrier Frequency Division Multiple Access
(SC-FDMA) is under consideration for uplink (see 3GPP
TR 25.814 (V7.0.0), "Physical Layer Aspects for
Evolved UTRA", June 2006, for example).

In OFDM, a frequency band is divided into
25 plural narrow frequency bands (sub-carriers), and
data are placed on the respective divided frequency
bands to carry out transmission. The sub-carriers
are densely arranged in a frequency direction,
allowing the sub-carriers to be partly overlapped
30 without causing interference, thereby realizing high
speed transmission and improving frequency usage
efficiency.

In SC-FDMA, a frequency band is divided
into plural narrow bands, and different narrow bands
35 are used by different mobile stations, so that
interference between the mobile stations can be
reduced. According to SC-FDMA, which is

characterized in that variations in the transmission power are reduced, a large coverage area and low energy consumption can be realized.

5 In LTE, one or more physical channels for both uplink and downlink are shared by plural mobile stations. The channel which is shared by plural mobile stations is typically called a shared channel. In LTE, a Physical Uplink Shared Channel (PUSCH) is used in uplink and a Physical Downlink Shared
10 Channel (PDSCH) is used in downlink.

In uplink, a control channel (PUCCH: Physical Uplink Control Channel) and a random access channel (PRACH: Physical Random Access Channel) are used in addition to the shared channel. Furthermore,
15 Demodulation Reference Signals (Demodulation RSs), Sounding Reference Signals (Sounding RSs), and so on are transmitted as pilot signals.

The PUCCH includes two types, i.e., a channel to be time-multiplexed with the PUSCH and a
20 channel to be frequency-multiplexed with the PUSCH.

In the communication system which uses the shared channel, scheduling is needed to determine to which mobile station the shared channel is assigned for each subframe. Scheduling is performed based on
25 information such as communication quality derived from the Sounding RSs.

In LTE uplink, the Sounding RSs are transmitted to mobile stations with various bandwidths in the whole system band. The Sounding
30 RSs are time-multiplexed with the PUSCH.

DISCLOSURE OF INVENTION

[PROBLEM(S) TO BE SOLVED BY THE INVENTION]

However, the above-mentioned technology
35 has the following problem.

Specifically, in LTE uplink, the Sounding RS is transmitted in the same time slot as the PRACH

and the PUCCH. As a result, interference occurs when the transmission band for the Sounding RS overlaps with the transmission bands for the PUCCH and the PRACH.

5 In order to solve this problem, it is a general object of the present invention to provide a base station apparatus, a mobile station, a radio communication system, and a communication control method to appropriately control transmission of the
10 Sounding RS when the transmission band for the Sounding RS overlaps with the transmission bands for the PUCCH and the PRACH.

[MEANS FOR SOLVING THE PROBLEM(S)]

15 In one aspect of the present invention, there is provided a radio communication system including a mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA (Single-Carrier Frequency
20 Division Multiple Access) scheme in uplink, the mobile station including:

 a transmitting unit configured to transmit at least one of a first signal and a second signal; and

 a Sounding RS transmitting unit configured
25 to determine a transmission band for a Sounding Reference Signal (Sounding RS) based on mapping information of at least one of the first signal and the second signal.

 The radio communication system can
30 appropriately control transmission of the Sounding RS when the transmission band for the Sounding RS overlaps with the transmission bands for the PUCCH and the PRACH.

 In another aspect of the present invention,
35 there is provided a radio communication system including a mobile station and a base station apparatus for communicating with the mobile station

according to a SC-FDMA scheme in uplink, including:
a substituting unit configured to use a
SIR (Signal-to-Interference ratio) for an adjacent
RB (Resource Block) or an immediately preceding RB
5 in which the Sounding RS is transmitted in place of
a SIR for a RB in which the sounding RS is not
transmitted.

The radio communication system can
appropriately control transmission of the Sounding
10 RS when the transmission band for the Sounding RS
overlaps with the transmission bands for the PUCCH
and the PRACH.

In another aspect of the present invention,
there is provided a radio communication system
15 including a mobile station and a base station
apparatus for communicating with the mobile station
according to a SC-FDMA scheme in uplink, wherein:
a Sounding RS is not transmitted, when all
or part of a transmission band for the Sounding RS
20 overlaps all or part of a transmission band for a
first signal or a second signal.

In another aspect of the present invention,
there is provided a base station apparatus in a
radio communication system including a mobile
25 station and the base station apparatus for
communicating with the mobile station according to a
SC-FDMA scheme in uplink, including:

a receiving unit configured to receive a
first signal and a second signal;
30 a Sounding RS receiving unit configured to
receive a Sounding RS whose transmission band is
determined based on mapping information of the first
signal and the second signal.

In another aspect of the present invention,
35 there is provided a base station apparatus in a
radio communication system including a mobile
station and the base station apparatus for

communicating with the mobile station according to a SC-FDMA scheme in uplink, including:

5 a receiving unit configured to receive either a first signal or a third signal when reception opportunities for the first signal and the third signal are provided in a same subframe.

10 In another aspect of the present invention, there is provided a base station apparatus in a radio communication system including a mobile station and the base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, comprising:

15 a receiving unit configured to receive part of a first signal and a third signal when reception opportunities for the first signal and the third signal are provided in a same subframe.

20 In another aspect of the present invention, there is provided a mobile station in a radio communication system including the mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, including:

25 a transmitting unit configured to transmit a first signal and a second signal; and a Sounding RS transmitting unit configured to transmit a Sounding RS whose transmission band is determined based on mapping information of the first signal and the second signal.

30 In another aspect of the present invention, there is provided a mobile station in a radio communication system including the mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, including:

35 a transmitting unit configured to transmit either a first signal or a third signal when transmission opportunities for the first signal and

the third signal are provided in a same subframe.

In another aspect of the present invention, there is provided a mobile station in a radio communication system including the mobile station
5 and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, including:

a transmitting unit configured to transmit part of a first signal and a third signal when
10 transmission opportunities for the first signal and the third signal are provided in a same subframe.

In another aspect of the present invention, there is provided a communication control method in a radio communication system including a mobile
15 station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, including the steps of:

determining, by the mobile station, a frequency band for a Sounding RS based on mapping
20 information of a first signal and a second signal; and

transmitting, by the mobile station, at least one of the first signal, the second signal, and the Sounding RS.

25 [ADVANTAGEOUS EFFECT OF THE INVENTION]

According to an embodiment of the present invention, a base station apparatus, a mobile station, a radio communication system, and a communication control method are achieved, in which
30 transmission of the Sounding RS is appropriately controlled when the transmission band for the Sounding RS overlaps with the transmission bands for the PUCCH and the PRACH.

35 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a schematic diagram illustrating a configuration of a radio

communication system according to an embodiment of the present invention.

Fig. 2 shows a configuration of a subframe and slots according to an embodiment of the present invention.

Fig. 3 shows a transmission band for a Sounding RS according to an embodiment of the present invention.

Fig. 4 shows uplink mapping according to an embodiment of the present invention.

Fig. 5 shows a transmission band for a Sounding RS when a PUCCH is mapped to both ends of the system band according to an embodiment of the present invention.

Fig. 6 shows a transmission band for a Sounding RS when a PRACH is mapped to the transmission band for the Sounding RS according to an embodiment of the present invention.

Fig. 7 shows a first diagram illustrating a transmission scheme for a PUCCH and a Sounding RS according to an embodiment of the present invention.

Fig. 8 shows a second diagram illustrating a transmission scheme for a PUCCH and a Sounding RS according to an embodiment of the present invention.

Fig. 9 shows a partial block diagram illustrating a base station apparatus according to an embodiment of the present invention.

Fig. 10 shows a partial block diagram illustrating a mobile station according to an embodiment of the present invention.

Fig. 11 shows a flowchart illustrating a communication control method according to an embodiment of the present invention.

Fig. 12 shows a flowchart illustrating a communication control method according to an embodiment of the present invention.

Fig. 13 shows a flowchart illustrating a

communication control method according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 [DESCRIPTION OF NOTATIONS]

50 cell
100₁, 100₂, 100₃, 100_n mobile station
102 transceiving antenna
104 amplification unit
10 106 transceiving unit
108 baseband signal processing unit
110 call processing unit
112 application unit
200 base station apparatus
15 202 transceiving antenna
204 amplification unit
206 transceiving unit
208 baseband signal processing unit
210 call processing unit
20 212 transmission path interface
300 access gateway apparatus
400 core network
1000 radio communication system

[BEST MODE OF CARRYING OUT THE INVENTION]

25 With reference to the accompanying drawings, preferred embodiments of the present invention are described below.

Throughout the drawings, corresponding elements are referenced by the same reference numerals and repetitive explanations are omitted.

30 Referring to Fig. 1, a radio communication system is explained below in which a base station apparatus according to an embodiment of the present invention is applied.

35 A radio communication system 1000, to which Evolved UTRA and UTRAN (also known as: Long Term Evolution (LTE) or Super 3G) is applied,

includes a base station apparatus (eNB: eNodeB) 200 and plural mobile stations (UE: User Equipment) 100_n (100₁, 100₂, 100₃, ..., 100_n, n: an integer more than zero). The base station apparatus 200 is connected
5 to an upper layer station, for example, an access gateway apparatus 300, and the access gateway apparatus 300 is connected to a core network 400. The mobile stations 100_n communicate with the base station apparatus 200 in a cell 50 under Evolved
10 UTRA and UTRAN.

In the following, the mobile stations 100₁, 100₂, 100₃, ..., 100_n are referred to as the mobile station 100_n, unless otherwise noted, because they have the same configuration, function, and condition.

15 The radio communication system 1000 employs Orthogonal Frequency Division Multiple Access (OFDMA) for downlink and Single-Carrier Frequency Division Multiple Access (SC-OFDMA) for uplink as radio access schemes. As stated above, in
20 OFDM, a frequency band is divided into plural narrow frequency bands (sub-carriers), and data are placed on the respective divided frequency bands to carry out transmission. In SC-FDMA, a frequency band is divided, and different frequency bands are used by
25 different mobile stations to carry out transmission, so that interference between the mobile stations can be reduced.

Communication channels in LTE are explained below.

30 In downlink, a Physical Downlink Shared Channel (PDSCH) shared by the mobile stations 100_n and a downlink control channel (PDCCH: Physical Downlink Control Channel) are used. In downlink, transport format information and user identification
35 of the user to which PDSCH is transmitted, transport format information and user identification of the user to which Physical Uplink Shared Channel (PUSCH)

is transmitted, acknowledgement information (HARQ
ACK information) of the PUSCH, and so on are
provided on the downlink control channel, and user
data are transmitted on the PDSCH. The channel on
5 which the acknowledgement information is transmitted
is called a Physical Hybrid-ARQ Indicator Channel
(PHICH).

In uplink, the PUSCH shared by the mobile
stations 100_n and an uplink control channel (PUCCH:
10 Physical Uplink Control Channel) are used.

In uplink, PDSCH scheduling, downlink
quality information (CQI: Channel Quality Indicator)
to be used for Adaptive Modulation and Coding (AMC)
and Transmission Power Control (TPC), and
15 acknowledge information of the PDSCH are transmitted
on the uplink control channel. In addition, user
data are transmitted on the PUSCH.

In uplink transmission, seven long blocks
(LBs) are used for each slot. Because one subframe
20 includes two slots, one subframe includes fourteen
long blocks as shown in Fig. 2. Reference signals
for data demodulation (i.e., Demodulation Reference
Signals) are mapped to two long blocks of the
fourteen long blocks. A reference signal for
25 sounding (i.e., Sounding Reference Signal), which is
to be used for determining a transmission format of
the PUSCH for uplink AMC, TPC, and scheduling is
transmitted through one long block of the fourteen
long blocks except for the long blocks to which the
30 Demodulation Reference Signals are mapped. The
Sounding Reference Signal may not be mapped to every
subframe. In the long block in which the Sounding
Reference Signal is transmitted, the Sounding
Reference Signals from plural mobile stations are
35 multiplexed according to Code Division Multiplexing
(CDM). The Demodulation Reference Signals are
mapped to the fourth long block and the eleventh

long block in the subframe, for example. The Sounding Reference Signal is mapped to the first long block in the subframe, for example. The long blocks may be called SC-FDMA symbols.

5 In uplink, each mobile station 100_n transmits signals in terms of resource blocks (RBs) in the frequency direction and in terms of subframes in the time direction. In LTE, the frequency band for one resource block is equal to 180 kHz. The
10 number of RBs is equal to 25 for the system bandwidth of 5 MHz, is equal to 50 for the system bandwidth of 10 MHz, and is equal to 100 for the system bandwidth of 20 MHz.

 Each mobile station 100_n transmits the
15 Sounding RS with one or more RBs. As shown in Fig. 3, the transmission band for the Sounding RS is uniquely determined by a transmission bandwidth, a transmission period, a frequency hopping period, a frequency hopping spacing, and so on, for example.
20 It should be noted that the transmission bandwidth, the transmission period, the frequency hopping period, and the frequency hopping spacing for each mobile station are managed by the base station apparatus 200, for example, and they are transmitted
25 from the base station apparatus 200 to the mobile station 100_n by means of an RRC message at the beginning of communication.

 For the pattern 1 in Fig. 3, the mobile station transmits Sounding RSs several times in the
30 time direction based on the frequency hopping period. Then the mobile station changes the transmission band to the adjacent frequency band, and again transmits Sounding RSs several times in the time direction based on the frequency hopping period.
35 The distance between the original transmission band to the adjacent frequency band corresponds to the frequency hopping spacing.

As shown in Fig. 4, the PUCCH which is frequency-multiplexed with the PUSCH is mapped to RBs at both ends of the system band. Although Fig. 4 shows the case where one RB is allocated to each end of the system band, two or more RBs may be allocated to each end of the system band. Information about resources on the PUCCH, such as resource IDs, transmission periods, and transmission timings for the PUCCH, to be used by the respective mobile stations 100_n to transmit CQI may be managed by the base station apparatus 200, for example, and the information may be transmitted from the base station apparatus 200 to the mobile station 100_n by means of an RRC message or broadcast information.

As shown in Fig. 4, six RBs as a frequency resource are allocated to the PRACH. In addition, one subframe of ten subframes as a time resource is allocated to the PRACH. For example, the frequency band for the PRACH is defined in the first subframe within one radio frame (10 ms) including ten subframes.

Two or more PRACHs, each of which uses six RBs, may be defined in one subframe. Specifically, when two PRACHs are defined in one subframe, twelve RBs in total are allocated to the PRACHs.

Mapping information of the PUCCH and the PRACH are typically determined by the base station apparatus 200. Alternatively, the mapping information may be defined in advance as a predetermined parameter in the radio communication system 1000. In either case, information about which subframes and which RBs the PUCCH and the PRACH use for transmission is provided to the mobile station 100_n on the broadcast channel or the like, for example. Namely, the mobile station 100_n knows information about which subframes and which RBs the PUCCH and the PRACH use for transmission.

The Sounding RS is transmitted with the frequency band which does not include the frequency band for the PUCCH (the Sounding RS is transmitted with the frequency band to which the PUCCH is not mapped or allocated). It should be noted that the transmission band for the Sounding RS may be divided into one or more transmission bands.

When the transmission band for the Sounding RS is divided into plural transmission bands, the frequency band except for the frequency bands for the PUCCH may be divided into plural transmission bands, without imposing a limit on the bandwidth for the Sounding RS (allowing for the use of various bandwidths for the Sounding RS). For example, the transmission bands for the Sounding RS may be determined as shown in Fig. 5(A).

Alternatively, the frequency band except for the frequency bands for the PUCCH may be equally divided into plural transmission bands to a maximum extent, with the use of the limited number of bandwidths for the Sounding RS. For example, the transmission bands for the Sounding RS may be determined as shown in Fig. 5(B).

Alternatively, the frequency band except for the frequency bands for the PUCCH may be filled with the fixed bandwidths of the Sounding RS, starting from the low frequency. The remaining frequency band may not be used to transmit the Sounding RS. For example, the transmission bands for the Sounding RS may be determined as shown in Fig. 5(C). In this example, six resource blocks are not used to transmit the Sounding RS.

Alternatively, the transmission bands for the Sounding RS may be overlapped in part so as to avoid the remaining frequency band. For example, the transmission bands for the Sounding RS may be determined as shown in Fig. 5(D). In this example,

the transmission bands overlap at boundaries between #1 and #2, #2 and #3, #3 and #4, and #4 and #5.

Alternatively, the frequency band including the frequency bands for the PUCCH, i.e.,
5 the system band may be equally divided into plural transmission bands to a maximum extent and portions which overlap with the frequency bands for the PUCCH may not be used to transmit the Sounding RS. For example, the transmission bands for the Sounding RS
10 may be determined as shown in Fig. 5(E). In this example, eight RBs in transmission bands #1 and #5 are used to transmit the Sounding RS, since part of the transmission bands overlaps with the frequency bands for the PUCCH. On the other hand, ten RBs in
15 transmission bands #2, #3, and #4 are used to transmit the Sounding RS, since the transmission bands do not overlap with the frequency bands for the PUCCH.

The SIR (Signal-to-Interference ratio) for
20 an adjacent RB or an immediately preceding RB in which the Sounding RS is transmitted is used in place of the SIR for the RB in which the Sounding RS is not transmitted.

In addition, the Sounding RS is
25 transmitted with the frequency band which does not include the frequency band for the PRACH (the Sounding RS is transmitted with the frequency band to which the PRACH is not mapped or allocated).

As shown in Fig. 6(A), when the frequency
30 band for the PRACH is included in the predetermined frequency band for the Sounding RS, a larger frequency band selected from two frequency bands except for the frequency band for the PRACH may be used as the transmission band for the Sounding RS,
35 for example. When two frequency bands except for the frequency band for the PRACH are identical, a lower frequency band may be used as the transmission

band for the Sounding RS.

Alternatively, as shown in Fig. 6(B), when the frequency band for the PRACH is partly included in the predetermined frequency band for the Sounding RS, the frequency band except for the frequency band for the PRACH may be used as the transmission band for the Sounding RS.

Alternatively, as shown in Fig. 6(C), when the frequency band for the PRACH is wholly included in the predetermined frequency band for the Sounding RS, the Sounding RS may not be transmitted.

Alternatively, when at least part of the frequency band for the PRACH is included in the predetermined frequency band for the Sounding RS, the Sounding RS may not be transmitted.

As shown in Fig. 7(A), when both a control signal to be transmitted on the PUCCH and the Sounding RS have transmission opportunities in the same subframe, the mobile station (UE) may transmit only the control signal without transmitting the Sounding RS. Namely, the mobile station (UE) prioritizes transmission of the control signal. In other words, in a subframe in which both transmission timing for the control signal on the PUCCH and transmission timing for the Sounding RS are provided, the mobile station (UE) may transmit only the control signal without transmitting the Sounding RS, as shown in Fig. 7(A). For example, the control signal to be transmitted on the PUCCH includes CQI, HARQ ACK information, Scheduling Request, or the like. Alternatively, the control signal may include both CQI and HARQ ACK information.

Alternatively, as shown in Fig. 7(B), when both a control signal to be transmitted on the PUCCH and the Sounding RS have transmission opportunities in the same subframe, the mobile station (UE) may transmit only the Sounding RS without transmitting

the control signal. Namely, the mobile station (UE) prioritizes transmission of the Sounding RS. In other words, in a subframe in which both transmission timing for the control signal on the PUCCH and transmission timing for the Sounding RS are provided, the mobile station (UE) may transmit only the Sounding RS without transmitting the control signal, as shown in Fig. 7(B). For example, the control signal to be transmitted on the PUCCH includes CQI, HARQ ACK information, Scheduling Request, or the like. Alternatively, the control signal may include both CQI and HARQ ACK information.

Alternatively, as shown in Fig. 8 ((A) and (B)), when both a control signal to be transmitted on the PUCCH and the Sounding RS have transmission opportunities in the same subframe, the mobile station (UE) may transmit the Sounding RS without transmitting the control signal in the LB in which the Sounding RS is transmitted. The mobile station (UE) may transmit the control signal in LBs in which the Sounding RS is not transmitted. In other words, in a subframe in which both transmission timing for the control signal on the PUCCH and transmission timing for the Sounding RS are provided, the mobile station (UE) may transmit only the Sounding RS without transmitting the control signal in the LB in which the Sounding RS is transmitted and transmit the control signal in LBs in which the Sounding RS is not transmitted.

Although the LB in which the Sounding RS is transmitted is LB #1 in Fig. 8 ((A) and (B)), the Sounding RS may be transmitted in LBs other than the LB #1.

Referring to Fig. 8(A), operations in the mobile station are explained below in detail. In Fig. 8(A), the control signal to be transmitted on the PUCCH is HARQ ACK information. In this example,

the signal for HARQ ACK information is not transmitted in the LB #1 (undergoes DTX (discontinuous transmission)).

Referring to Fig. 8(B), operations in the mobile station are explained below in detail. In Fig. 8(B), the control signal to be transmitted on the PUCCH is CQI. In this example, the signal for CQI to be mapped to the LB #1 may be the least significant bit for the CQI. The least significant bit is a bit in a lowest position among five bits for CQI, for example. Mapping the least significant bit for CQI to the LB in which the Sounding RS is transmitted in this manner can reduce property degradation of CQI, even though the least significant bit is not transmitted.

Next, the base station apparatus 200 according to an embodiment of the present invention is explained below with reference to Fig. 9.

The base station apparatus 200 according to this embodiment includes a transceiving antenna 202, an amplification unit 204, a transceiving unit 206, a baseband signal processing unit 208, a call processing unit 210, and a transmission path interface 212.

Packet data to be transmitted from the base station apparatus 200 to the mobile station 100_n through downlink are input to the baseband signal processing unit 208 from the upper layer station, for example, the access gateway apparatus 300 associated with the base station apparatus 200 via the transmission path interface 212.

In the baseband signal processing unit 208, the packet data undergoes segmentation/concatenation, Radio Link Control (RLC) layer transmission processing such as RLC retransmission control, MAC retransmission control, for example, transmission processing of Hybrid Automatic Repeat request (HARQ),

scheduling, transmission format selection, channel coding, and Inverse Fast Fourier Transform (IFFT) processing, and then is forwarded to the transceiving unit 206.

5 In the transceiving unit 206, the baseband signal output from the baseband signal processing unit 208 undergoes frequency conversion processing for converting the baseband signal to a radio frequency signal, which is then amplified by the
10 amplification unit 204 and transmitted from the transceiving antenna 202.

 On the other hand, regarding data transmitted from the mobile station 100_n to the base station apparatus 200 in uplink, the radio frequency
15 signal received by the transceiving antenna 202 is amplified by the amplification unit 204, frequency-converted into a baseband signal by the transceiving unit 206, and input to the baseband signal processing unit 208.

20 In the baseband signal processing unit 208, the input baseband signal undergoes FFT (Fast Fourier Transform) processing, error correction decoding, reception processing for the MAC retransmission control, RLC layer reception
25 processing, and is forwarded to the access gateway apparatus 300 via the transmission path interface 212.

 In the baseband signal processing unit 208, the control signal received on the PUCCH, which is
30 included in the input baseband signal, also undergoes demodulation and decoding. In a subframe in which both reception timing for the control signal on the PUCCH and reception timing for the Sounding RS are provided, the baseband signal
35 processing unit 208 in the base station apparatus 200 receives the control signal and/or the Sounding RS, conforming to the transmission scheme of the

control signal and/or the Sounding RS in the radio communication system 1000 as described with reference to Figs. 7 and 8. For example, the control signal received on the PUCCH includes CQI,
5 HARQ ACK information, Scheduling Request, or the like. Alternatively, the control signal may include both CQI and HARQ ACK information.

Also, the baseband signal processing unit 208 in the base station apparatus 200 receives the
10 Sounding RS based on mapping information of the PUCCH and the PRACH. Specifically, the baseband signal processing unit 208 receives the Sounding RS in the transmission band for the sounding RS for the mobile station 100_n, which is determined based on
15 the mapping information of the PUCCH and the PRACH. The transmission band for the Sounding RS and the scheme for receiving the Sounding RS conform to the transmission band and the transmission scheme in the radio system 1000 as described with reference to
20 Figs. 5, 6, 7, and 8. The baseband signal processing unit 208 receives information about the frequency bands for the PUCCH and the PRACH from the call processing unit 210.

The call processing unit 210 performs
25 status management of the base station apparatus 200 and management of radio resources.

The call processing unit 210 determines the frequency bands for the PUCCH and the PRACH. The call processing unit 210 also provides
30 information about the frequency bands for the PUCCH and the PRACH to the mobile station 100_n in the cell 50 on the broadcast channel, for example. Alternatively, the frequency bands for the PUCCH and the PRACH may be defined in advance as a
35 predetermined parameter in the radio communication system 1000.

The call processing unit 210 also provides

the information about the frequency bands for the PUCCH and the PRACH to the baseband signal processing unit 208.

5 Next, the mobile station 100_n according to an embodiment of the present invention is explained below with reference to Fig. 10.

 The mobile station 100_n includes a transceiving antenna 102, an amplification unit 104, a transceiving unit 106, a baseband signal
10 processing unit 108, a call processing unit 110, and an application unit 112.

 Regarding downlink data, a radio frequency signal received by the transceiving antenna 102 is amplified by the amplification unit 104, and
15 frequency-converted into a baseband signal by the transceiving unit 106. The baseband signal undergoes FFT processing, error correction decoding, reception processing for the retransmission control, and so on, and is forwarded to the application unit
20 112.

 On the other hand, uplink packet data are input from the application unit 112 to the baseband signal processing unit 108. In the baseband signal processing unit 108, the uplink packet data
25 undergoes transmission processing for the retransmission control (Hybrid ARQ (H-ARQ)), transmission format selection, channel coding, Inverse Fast Fourier Transform (IFFT) processing, and so on, and is forwarded to the transceiving unit
30 106.

 The baseband signal processing unit 108 performs transmission processing of the control signal on the PUCCH. In a subframe in which both transmission timing for the control signal on the
35 PUCCH and transmission timing for the Sounding RS are provided, the baseband signal processing unit 108 in the mobile station 100_n transmits the control

signal and/or the Sounding RS, conforming to the transmission scheme of the control signal and/or the Sounding RS in the radio communication system 1000 as described with reference to Figs. 7 and 8. For
5 example, the control signal transmitted on the PUCCH includes CQI, HARQ ACK information, Scheduling Request, or the like. Alternatively, the control signal may include both CQI and HARQ ACK information.

In the transceiving unit 106, the baseband
10 signal output from the baseband signal processing unit 108 undergoes frequency conversion processing for converting the baseband signal to a radio frequency signal, which is then amplified by the amplification unit 104 and transmitted from the
15 transceiving antenna 102.

In addition, the baseband signal processing unit 108 demodulates and decodes information on a DL L1/L2 control channel to retrieve the information on the DL L1/L2 control
20 channel.

The baseband signal processing unit 108 also receives information about the frequency bands for the PUCCH and the PRACH from the call processing unit 110. The baseband signal processing unit 108
25 generates the Sounding RS based on the transmission band for the Sounding RS, which is determined based on the frequency bands for the PUCCH and the PRACH. The generated Sounding RS is transmitted via the transceiving unit 106, the amplification unit 104,
30 and the transceiving antenna 102 to the base station apparatus 200. The transmission band for the Sounding RS and the scheme for transmitting the Sounding RS conform to the transmission band and the transmission scheme in the radio system 1000 as
35 described with reference to Figs. 5, 6, 7, and 8. The baseband signal processing unit 108 receives information about the frequency bands for the PUCCH

and the PRACH from the call processing unit 110.

5 The call processing unit 110 performs management of communications with the base station apparatus 200. The application unit 112 performs processing on an upper layer higher than the physical layer and the MAC layer.

10 The call processing unit 110 also receives information on the broadcast channel via the transceiving antenna 102, the amplification unit 104, the transceiving unit 106, and the baseband signal processing unit 108, and then retrieves information about the frequency bands for the PUCCH and the PRACH on the broadcast channel. The call processing unit 110 provides the information about the
15 frequency bands for the PUCCH and the PRACH to the baseband signal processing unit 108.

Although the mobile station 100_n retrieves information about the frequency bands for the PUCCH and the PRACH on the broadcast channel, the mobile
20 station 100_n may know in advance the information about the frequency bands for the PUCCH and the PRACH as a predetermined parameter in the radio communication system 1000.

25 Next, a communication control method for transmitting the Sounding RS in the radio communication system 1000 according to the embodiment of the present invention is explained below with reference to Fig. 11.

30 The transmission band for the Sounding RS is determined based on mapping information of the PUCCH and the PRACH.

The transmission band for the Sounding RS is determined so as not to include (overlap) the transmission bands for the PUCCH, which is mapped to
35 both ends of the system band (step S11). The transmission band for the Sounding RS conforms to the transmission band in the radio system 1000 as

described with reference to Figs. 5 and 6.

It is determined whether the PRACH is transmitted in this (current) subframe (the subframe corresponding to the determined transmission band) (step S12).

When the PRACH is transmitted in the subframe (step S12: YES), the Sounding RS is transmitted with the frequency band except for the transmission band for the PRACH. Alternatively, the Sounding RS is not transmitted in the subframe (step S13). How to avoid using the transmission band for the PRACH conforms to the explanation of the transmission band for the Sounding RS in the radio communication system 1000 as described with reference to Figs. 5 and 6.

When the PRACH is not transmitted in the subframe (step S12: NO), the Sounding RS is transmitted with the transmission band determined at step S11 (step S14).

Although the transmission band for the Sounding RS is determined based on mapping information of both the PUCCH and the PRACH, the transmission band for the Sounding RS may be determined based on mapping information of either the PUCCH or the PRACH.

For example, the mapping information corresponds to information about which frequency band or which resource block a signal uses for transmission. Namely, the mapping information corresponds to the transmission band for the signal.

Next, a communication control method for transmitting the control signal on the PUCCH and the Sounding RS in the radio communication system 1000 according to the embodiment of the present invention is explained below with reference to Fig. 12.

This (current) subframe corresponds to timing for transmitting the Sounding RS (step S21).

If the subframe corresponds to timing for transmitting the control signal on the PUCCH (step S22: YES), the mobile station (UE) transmits the control signal on the PUCCH without transmitting the Sounding RS (step S23).

If the subframe does not correspond to timing for transmitting the control signal on the PUCCH (step S22: NO), the mobile station (UE) transmits the Sounding RS (step S24).

Next, another communication control method for transmitting the control signal on the PUCCH and the Sounding RS in the radio communication system 1000 according to the embodiment of the present invention is explained below with reference to Fig. 13.

This (current) subframe corresponds to timing for transmitting the control signal on the PUCCH (step S31).

If the subframe corresponds to timing for transmitting the Sounding RS (step S32: YES), the mobile station (UE) transmits the Sounding RS without transmitting the control signal on the PUCCH (step S33).

At step S33, the mobile station may transmit the control signal in the LB in which the Sounding RS is not transmitted. The transmission scheme for the control signal conforms to the transmission scheme for the control signal and/or the Sounding RS in the radio communication system 1000 as described with reference to Figs. 7 and 8.

If the subframe does not correspond to timing for transmitting the Sounding RS (step S32: NO), the mobile station (UE) transmits the control signal on the PUCCH (step S34).

According to an embodiment of the present invention, a base station apparatus, a mobile station, a radio communication system, and a

communication control method are achieved, in which
transmission of the Sounding RS is appropriately
controlled when the transmission band for the
Sounding RS overlaps with the transmission bands for
5 the PUCCH and the PRACH.

This international application claims the
benefit of the priority dates of Japanese Patent
Application No. 2007-035526 filed on February 15,
2007 and Japanese Patent Application No. 2007-077900
10 filed on March 23, 2007, the entire content of which
is herein incorporated hereby by reference.

CLAIMS

5 1. A radio communication system including
a mobile station and a base station apparatus for
communicating with the mobile station according to a
SC-FDMA (Single-Carrier Frequency Division Multiple
Access) scheme in uplink, the mobile station
10 comprising:

a transmitting unit configured to transmit
at least one of a first signal and a second signal;
and

15 a Sounding RS transmitting unit configured
to determine a transmission band for a Sounding
Reference Signal (Sounding RS) based on mapping
information of at least one of the first signal and
the second signal.

20

2. The radio communication system as
claimed in Claim 1, wherein:

25 the Sounding RS transmitting unit avoids
using at least one of a transmission band for the
first signal and a transmission band for the second
signal to transmit the Sounding RS.

30

3. The radio communication system as
claimed in Claim 1, wherein:

35 a SIR (Signal-to-Interference ratio) for
an adjacent RB (Resource block) or an immediately
preceding RB in which the Sounding RS is transmitted

is used in place of a SIR for a RB in which the Sounding RS is not transmitted.

5

4. The radio communication system as claimed in Claim 1, wherein:

10 the first signal corresponds to an uplink control channel (PUCCH: Physical Uplink Control Channel) and

the second signal corresponds to a random access channel (PRACH: Physical Random Access Channel).

15

20 5. A radio communication system including a mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, wherein:

25 a Sounding RS is not transmitted, when all or part of a transmission band for the Sounding RS overlaps all or part of a transmission band for a first signal or a second signal.

30

6. The radio communication system as claimed in Claim 5, wherein:

35 a SIR (Signal-to-Interference ratio) for an adjacent RB (Resource block) or an immediately preceding RB in which the Sounding RS is transmitted is used in place of a SIR for a RB in which the Sounding RS is not transmitted.

5 7. The radio communication system as
claimed in Claim 5, wherein:
 the first signal corresponds to an uplink
control channel (PUCCH) and
 the second signal corresponds to a random
10 access channel (PRACH).

15 8. A base station apparatus in a radio
communication system including a mobile station and
the base station apparatus for communicating with
the mobile station according to a SC-FDMA scheme in
uplink, comprising:
20 a receiving unit configured to receive a
first signal and a second signal;
 a Sounding RS receiving unit configured to
receive a Sounding RS whose transmission band is
determined based on mapping information of the first
25 signal and the second signal.

30 9. The base station apparatus as claimed
in Claim 8, wherein:
 the first signal corresponds to a PUCCH
and
 the second signal corresponds to a PRACH.
35

10. The base station apparatus as claimed
in Claim 8, wherein:

5 CQI and/or HARQ ACK information is
transmitted on the PUCCH.

10 11. A base station apparatus in a radio
communication system including a mobile station and
the base station apparatus for communicating with
the mobile station according to a SC-FDMA scheme in
uplink, comprising:

15 a receiving unit configured to receive
either a first signal or a third signal when
reception opportunities for the first signal and the
third signal are provided in a same subframe.

20

12. The base station apparatus as claimed
in Claim 11, wherein:

25 the first signal corresponds to a PUCCH
and

the third signal corresponds to a Sounding
RS.

30

13. The base station apparatus as claimed
in Claim 11, wherein:

35 CQI and/or HARQ ACK information is
transmitted on the PUCCH.

14. A base station apparatus in a radio
5 communication system including a mobile station and
the base station apparatus for communicating with
the mobile station according to a SC-FDMA scheme in
uplink, comprising:
a receiving unit configured to receive
10 part of a first signal and a third signal when
reception opportunities for the first signal and the
third signal are provided in a same subframe.

15

15. The base station apparatus as claimed
in Claim 14, wherein:
the part of the first signal corresponds
20 to SC-FDMA symbols other than symbols for receiving
the third signal.

25

16. The base station apparatus as claimed
in Claim 14, wherein:
the first signal corresponds to a PUCCH
and
30 the third signal corresponds to a Sounding
RS.

35

17. The base station apparatus as claimed
in Claim 14, wherein:

CQI and/or HARQ ACK information is transmitted on the PUCCH.

5

18. A mobile station in a radio communication system including the mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, comprising:

10 a transmitting unit configured to transmit a first signal and a second signal; and
a Sounding RS transmitting unit configured
15 to transmit a Sounding RS whose transmission band is determined based on mapping information of the first signal and the second signal.

20

19. The mobile station as claimed in Claim 18, wherein:
the first signal corresponds to a PUCCH
25 and
the second signal corresponds to a PRACH.

30

20. The mobile station as claimed in Claim 18, wherein:
CQI and/or HARQ ACK information is transmitted on the PUCCH.

35

21. A mobile station in a radio communication system including the mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, comprising:
a transmitting unit configured to transmit either a first signal or a third signal when transmission opportunities for the first signal and the third signal are provided in a same subframe.

22. The mobile station as claimed in Claim 21, wherein:
the first signal corresponds to a PUCCH
and
the third signal corresponds to a Sounding RS.

23. The mobile station as claimed in Claim 21, wherein:
CQI and/or HARQ ACK information is transmitted on the PUCCH.

24. A mobile station in a radio communication system including the mobile station and a base station apparatus for communicating with the mobile station according to a SC-FDMA scheme in uplink, comprising:

a transmitting unit configured to transmit part of a first signal and a third signal when transmission opportunities for the first signal and the third signal are provided in a same subframe.

5

25. The mobile station as claimed in Claim 10 24, wherein:
the part of the first signal corresponds to SC-FDMA symbols other than symbols for receiving the third signal.

15

26. The mobile station as claimed in Claim 24, wherein:
20 the first signal corresponds to a PUCCH
and
the third signal corresponds to a Sounding RS.

25

27. The mobile station apparatus as claimed in Claim 24, wherein:
30 CQI and/or HARQ ACK information is transmitted on the PUCCH.

35

28. A communication control method in a radio communication system including a mobile

station and a base station apparatus for
communicating with the mobile station according to a
SC-FDMA scheme in uplink, comprising the steps of:

- 5 determining, by the mobile station, a
frequency band for a Sounding RS based on mapping
information of a first signal and a second signal;
and
 transmitting, by the mobile station at
least one of the first signal, the second signal,
10 and the Sounding RS.

- 15 29. The communication control method as
claimed in Claim 28, wherein:
 the first signal corresponds to a PUCCH
and
 the second signal corresponds to a PRACH.
20