

- 1 -

DEPLOYABLE SPACE VEHICLE**TECHNOLOGICAL FIELD**

The presently disclosed subject matter relates to space vehicles in general and more specifically to space vehicles that are deployable from a compact configuration.

BACKGROUND ART

5 References considered to be relevant as background to the presently disclosed subject matter are listed below:

- US 8,531,524
- US 6,683,311
- WO 2017/055770
- 10 - US 9,389,411
- US 3,782,835
- CN 104155747
- US 8,967,545

Acknowledgement of the above references herein is not to be inferred as
15 meaning that these are in any way relevant to the patentability of the presently disclosed subject matter.

BACKGROUND

Space vehicles are generally designed for two different environments, the launch
20 environment and the orbital environment. At launch, a space vehicle must be packed into a launch vehicle, generally requiring that the space vehicle fits within some specific confined space. However, in an orbital environment, the structure may generally be large, since there are generally no size constraints upon the space vehicle once deployed. Spacecraft are thus typically constrained in their dimensions by the volume
25 available within the fairing of the launch rocket. Hence, a structure with an optical instrument cannot always be positioned in the reduced volume available under the nose

- 2 -

cone of a launch vehicle. This has led to the development of various types of deployable structures which can be stowed into a relatively small volume for launch, and later deployed to increase the dimensions of the spacecraft. Certain optical instruments put on board space vehicles have been equipped with a retractable optical element, mainly a
5 secondary mirror of an optical telescope. Such an optical element has a retracted or folded configuration when they are placed under the nose cone of the launch vehicle. They are generally clamped by devices called "stacking" devices which allow them to bear the accelerations and vibrations of the launch. When the space vehicle is separated from the launch vehicle, command devices allow the optical element to be brought into
10 an active or deployed configuration. To fit the system requirements after launch, the deployable structure is typically equipped with a robust calibration system. Moreover, after deployment, the position of the optical instruments should be adjusted with respect to other optical elements in the optical instrument and with respect to the space vehicle for accurate measurement performance. This deployment requires accuracy of
15 micrometers, and precision which may be less than that of micrometers.

GENERAL DESCRIPTION

The present invention exploits the free space (volume) defined by an interior cavity of an optical system body to reduce the general volume of the space vehicle. The space vehicle may be a satellite of any type or a spacecraft equipped with an optical
20 instrument. More specifically, in the space vehicle of the present invention, at least one control system configured for controlling operation of the vehicle is accommodated within the optical system (e.g. imaging system) in the free space between the optical elements of the optical system. In the configuration of the present invention, at least one control system is placed within the optical system when the space vehicle is in its
25 stowed position. After launch, the control system is deployed outwardly, leaving the space within the optical system and enabling imaging of incoming electromagnetic radiation. It should be noted that due to the special configuration of the deployable space vehicle of the present invention in which the control system(s) are deployed outwardly and not the optical elements, the required accuracy of the deployment is
30 much lower than the accuracy required for deployment of optical elements. In this way, the optical system might have a larger volume leading to an increase in the optical properties of the optical system and of the performance of the optical system, as well as

- 3 -

of the space vehicle. To provide high resolution imagery of distant extended scenes, relatively large aperture optical systems are required. Increasing the diameter of an optical system such as a telescope, increases its resolution of fine detail in proportion to the telescope diameter.

5 Therefore the present invention provides a space vehicle comprising an optical system having a field of view, the optical system comprising at least two optical elements spaced from one another along an optical axis of the optical system, thereby defining an interior cavity of the optical system; at least one control system, the control system comprising at least one physical element configured for performing one or more
10 functions for enabling operation of the vehicle; and at least one holding assembly for holding the at least one control system, the holding assembly comprising a folding mechanism configured and operable to move between a folded position corresponding to an inoperative mode of the optical system, and a deployed position corresponding to an operative mode of the optical system, such that in the folded position of the folding
15 mechanism, the control system that is held by the holding assembly is at least partially located in the interior cavity of the optical system for stowage, and in the deployed position of the folding mechanism, the control system that is held by the holding assembly is located outside the interior cavity and outside the field of view of the optical system, thereby allowing operation of the optical system.

20 In some embodiments, the optical system comprises a telescope having a primary optical element and a secondary optical element. The control system is then positioned in between the primary and secondary optical elements.

In some embodiments, the space vehicle comprises a plurality of control systems, each being configured to be deployable and mounted on a holding assembly
25 respectively. The control system(s) may comprise a processing unit configured to control space vehicle operations and/or an image processing module configured to process imaging data collected by the optical system and/or a guiding module configured for guiding the vehicle and/or a receiving/transmitting device configured for receiving/transmitting signals and/or an amplifier device operable for amplifying signals
30 received by the receiver and/or at least one power source configured for supplying voltage supply to the vehicle.

In some embodiments, the folding mechanism is configured and operable for being pivotally displaceable around an axis perpendicular to the optical axis, from the

- 4 -

folded position to the deployed position. Alternatively, the folding mechanism may be configured and operable for being pivotally displaceable around an axis parallel to the optical axis from the folded position to the deployed position. Alternatively, the folding mechanism may be configured and operable for being longitudinally displaceable along
5 an axis perpendicular to the optical axis.

In some embodiments, the space vehicle comprises a frame comprising a plurality of surfaces forming an internal cavity and at least one opening in the frame, wherein the at least one holding assembly is mounted on at least one of the plurality of surfaces and at least partially covering the at least one opening when in its folded
10 position. The folding mechanism may then comprise at least one support surface carrying the at least one control system and an axial hinge connecting between one of the surfaces of the frame and the support surface.

In some embodiments, in the deployed position, the support surface is substantially perpendicular to the optical axis of the optical system. Alternatively, in the
15 deployed position, the support surface is substantially parallel to the optical axis of the optical system.

In some embodiments, the axial hinge may have a main direction substantially parallel to the optical axis. Alternatively, the axial hinge may have a direction substantially perpendicular to the optical axis.

20 BRIEF DESCRIPTION OF THE DRAWINGS

In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, embodiments will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

25 **Fig. 1** represents a functional description of a possible configuration of the deployable space vehicle of the present invention;

Fig. 2 shows a schematic top view of a possible configuration of the deployable space vehicle in its folded position according to some embodiments of the present invention;

30 **Fig. 3** shows a schematic side view of a possible configuration of the deployable space vehicle in one possible deployed position according to some embodiments of the present invention;

- 5 -

Fig. 4 shows a schematic bottom view of a possible configuration of the deployable space vehicle in another possible deployed position according to some embodiments of the present invention; and

Fig. 5 shows a schematic side view of a possible configuration of the deployable
5 space vehicle in another possible deployed position according to some embodiments of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Reference is made to **Fig. 1** representing a block diagram of the main functional element of the deployable space vehicle **100** according to the teachings of the present
10 invention. Deployable space vehicle **100** comprises *inter alia* an optical system **102** having a certain field of view **FOV** and defining an interior cavity **I**. Optical system **102** comprises at least two optical elements **102A** and **102B** spaced from one another along an optical axis **O**. Optical elements **102A** and **102B** are configured for collecting and focusing incoming radiation to create a magnified image. The optical system **102** may
15 be an optical telescope or any other imaging system. If the optical system **102** is an optical telescope, it comprises an arrangement of optical elements including at least two surfaces i.e. primary and secondary optical elements **102A** and **102B**. The optical telescope may be a refracting telescope using lenses to form the image, a reflecting telescope using an arrangement of mirrors to form the image, or a catadioptric telescope
20 using an arrangement of mirrors and lenses to form an image. Deployable space vehicle **100** also comprises at least one holding assembly **106** for holding at least one control system **104** having at least one physical element configured for performing one or more functions for enabling operation of vehicle **100**. The holding assembly **106** comprises a folding mechanism configured and operable to move the control system **104** from a
25 folded position **104A** corresponding to an inoperative mode of the optical system **102** to a deployed position **104B** corresponding to an operative mode of the optical system **102**. The folding mechanism may be a mechanical element selectively moving control system **104** into and out of the free space (i.e. interior cavity **I**) of the optical system **102**.

30 In the folded position **104A** of the folding mechanism, the control system **104** is held by the holding assembly **106A** being at least partially located in the interior cavity **I** of the optical system **102** for stowage. In the folded position **104A**, control system **104**

- 6 -

is positioned in between optical elements **102A** and **102B** obtruding the field of view **FOV**. In the deployed position **104B** of the folding mechanism, the control system is held by the holding assembly **106B** being located outside the interior cavity and outside the field of view **FOV** of the optical system **102** thereby allowing operation of the
5 optical system **102**.

Reference is made to **Fig. 2**, representing a top view of a space vehicle **200** being, in this specific and non-limiting example, a satellite in its folded position. The deployable space vehicle of the present invention is not limited to any vehicle and may be a satellite such as an earth observation satellite, orbiting observation satellite, a
10 communications satellite, a navigation satellite or a weather satellite which may be configured for many tasks. The present invention can thus be used in any observation electro-optic satellite and is especially useful in small satellites such as nano-satellites in which the volume of the external frame is critical. Alternatively, the deployable space vehicle may be a spacecraft equipped with an optical instrument. In this specific
15 configuration, the optical system **102** is configured for imaging incoming radiation along optical axis **O**. The control system (not shown in the figure) is accommodated within the optical system **102** (represented as a cylinder) for stowage. In this way, for an optical system having a given volume, the volume of observation satellite **200** (e.g. of the external frame) at the time of launch may be significantly reduced as compared with
20 conventional space vehicles, in which the control system(s) are placed adjacently to the optical system. It should be understood that in these conventional configurations, the control system(s) occupy a space in the frame adjacent to the optical system to enable operation of the optical system and to not obstruct its field. The volume of such space vehicles is thus increased, as compared with the space vehicle of the present invention,
25 in which the inventors have found that the internal volume of the optical system can be exploited. In existing systems, this volume is not occupied. The present invention may thus solve the problem of volume at the time of launch by reducing the volume of the satellite by using the free space within the optical system. In other words, the folding of the control system(s) within the optical system enables to reduce the external volume of
30 the space vehicle to fit the volume of a canopy at the time of launch.

It should also be noted that by deploying the control systems, and not the optical element as conventionally used in deployable space vehicles, the accuracy requirements of the folding mechanism are lower by at least two orders of dimension than the

- 7 -

accuracy requirements of existing solutions. More specifically, the accuracy requirements of the folding mechanism of the present invention are in the order of millimeters, while the accuracy requirements of existing optical solutions are in the order of microns. Moreover, it should be noted that the configuration of the present invention, in which at least one control system is deployed, eliminates the need for calibration or adjustment of optical elements/instruments, for example: of the secondary mirror relative to the primary mirror, and of the direction of the optical element line of sight (LOS) relative to the space vehicle main axes after deployment. In the space vehicle of the present invention, there is no need for a directional means aimed at controlling the position of the different elements for directing the optical axis of the system.

Alternatively, exploitation of the free space within the optical system may enable to optimize the electro-optic performance of the space vehicle for a given volume of the external frame. For example, the optical system might have a larger volume leading to an increase in optical properties of the optical system and of performance of the optical system as well as of the space vehicle.

Reference is made to **Fig. 3**, representing a side view of a space vehicle **300** according to some embodiments of the present invention, being in this specific and non-limiting example a satellite in its deployed position. In this specific and non-limiting configuration, space vehicle **300** comprises a holding assembly **306** holding a control system(s) **304** and having a folding mechanism (not shown) being configured and operable for being pivotally displaceable around an axis **P** substantially perpendicular to the optical axis **O** of the optical system **102**. The axis of deployment **A** is in this case substantially perpendicular to the optical axis **O** of the optical system **102**. In the folded position, control system **304** is accommodated in the free space within the optical system **102**. The space vehicle may comprise a frame (e.g. body) **310** comprising a plurality of surfaces **312** (only two of them are shown in the figure) forming the internal cavity **I** and at least one opening **316** in the frame **310**. Holding assembly **306** is mounted on one of the plurality of surfaces **312** and at least partially covers the opening **316** when the control system **304** is in its folded position. Holding assembly **306** is configured to move the control system **304** between a folded position and a deployed position for operation out of the frame **310**. In this configuration, folding mechanism **308** comprises a support surface **314** carrying the control system **304** and an axial hinge

- 8 -

placed at the axis **P** connecting between one of the surfaces **312** of the frame and the support surface **314**. As illustrated, in the deployed position, the support surface **314** is substantially perpendicular to the optical axis **O** of the optical system. In this specific and non-limiting example, the axial hinge has a main direction **P** substantially perpendicular to the optical axis **O**. In this specific and non-limiting example, optical system **102** is a telescope disposed within the interior cavity **I**.

Reference is made to **Fig. 4** representing a bottom view of a space vehicle **400** according to some embodiments of the present invention being in this specific and non-limiting example a satellite in its deployed position. In this specific and non-limiting configuration, space vehicle **400** comprises a plurality of control systems **402** and **404** each being configured to be deployable and mounted on a holding assembly (not shown) respectively. The control system may be an Attitude and Orbital Control System (AOCS) and/or any other electronic unit and/or any other mechanical unit. For example, the control system may be configured for receiving and transmitting data signals. The control system may be an assembly of on-board equipment and software which provides the control function of a space vehicle aimed at, for example, setting it with the desired attitude and adjusting its orbit to the requirements of the mission. The electronic unit may comprise a transceiver permitting to be connected to a communication unit and to transmit and/or receive data. The control system may comprise any physical element performing one or more functions for enabling operation of the vehicle, such as a processing unit configured to control space vehicle operations and/or an image processing module configured to process imaging data collected by the optical system and/or a guiding module configured for guiding the vehicle and/or a receiving/transmitting device configured for receiving/transmitting signals and/or an amplifier device operable for amplifying signals received by the receiver and/or at least one power source configured for supplying voltage supply to the vehicle and/or inertia wheel(s), or any satellite system. In some embodiments, the control system may be configured as an electronic image module for collecting and processing imaging data. It should be noted that all required control operations (such as control space vehicle operations, processing imaging data, performing corresponding calculation operations, guiding the vehicle, receiving/transmitting signals, amplifying signals, supplying voltage supply to the vehicle ...) may be controlled by means of a processing unit, such as a DSP, microcontroller, FPGA, ASIC, etc., or any other conventional and/or

- 9 -

dedicated computing unit/system. The term "processing unit" should be expansively construed to cover any kind of electronic device with data processing capabilities, including, by way of non-limiting example, personal computers, servers, computing systems, communication devices, processors (e.g. digital signal processor (DSP),
5 microcontrollers, field programmable gate array (FPGA), application specific integrated circuit (ASIC), etc.) and other electronic computing devices. The processing unit may comprise a general-purpose computer processor, which is programmed in software to carry out the functions described hereinbelow. Also, operations in accordance with the teachings herein may be performed by a computer specially constructed for the desired
10 purposes or by a general purpose computer specially configured for the desired purpose by a computer program stored in a computer readable storage medium. The control system includes *inter alia* a signal generator, and at least one utility part (suitable software and/or hardware) for generating a signal indicative of an operation to be performed by any module of the space vehicle. The different elements of the control
15 system (electronic unit and/or mechanical unit) are connected to each other by wires or wireless. The software may be downloaded to the processing unit in electronic form, over a network, for example, or it may alternatively be provided on tangible media, such as optical, magnetic, or electronic memory media. Alternatively or additionally, some or all of the functions of the control unit may be implemented in dedicated hardware, such
20 as a custom or semi-custom integrated circuit or a programmable digital signal processor (DSP).

In this specific and non-limiting configuration, two holding assemblies are mounted on substantially parallel faced surfaces of space vehicle **400** holding control systems **402** and **404** respectively. Each holding assembly has a folding mechanism (not
25 shown) being configured and operable for being longitudinally displaceable along an axis **A** of deployment being substantially perpendicular to the optical axis **O** of the optical system. In this specific and non-limiting example, each axial hinge has a main direction **A** deploying each control system **402** and **404** in opposite longitudinal directions (leftward and rightward) along the axis of deployment **A**. In the folded
30 position, control systems **402** and **404** are accommodated in the free space within the optical system **102**. Each support surface may thus be hinged to one of the surfaces of the space vehicle **400** about a respective hinge axis to enable the control systems **402** and **404** to be selectively longitudinally displaced about the respective hinge axes with

- 10 -

respect to one another from an undeployed configuration to a deployed configuration. In this specific and non-limiting configuration, in the deployed position, the support surface(s) may be substantially parallel to the optical axis **O**. In the undeployed configuration, frame **410** of space vehicle **400** has a first length dimension **L1**, and in
5 the deployed configuration frame **410** has a second length dimension **L2**. The second length dimension **L2** is greater than first length dimension **L1**.

Reference is made to **Fig. 5**, representing a side view of a space vehicle **500** according to some embodiments of the present invention, being in this specific and non-limiting example a satellite in its partly deployed position. The figure shows the space
10 vehicle **500** at an intermediate stage of the deployment. In this specific and non-limiting configuration, space vehicle **500** comprises two holding assemblies **502** and **504** holding two control systems **506** and **508**. Each holding assembly **502** and **504** has a folding mechanism being configured and operable for being pivotally displaceable around an axis **P1** (not shown) and **P2** respectively substantially parallel to the optical
15 axis **O** of the optical system **102**. When completely deployed (position not illustrated in this figure), the axis of deployment **A** is substantially perpendicular to the optical axis **O** of the optical system **102**. In this specific and non-limiting configuration, two holding assemblies **502** and **504** are mounted on substantially parallel faced surfaces of space vehicle **500**. As illustrated, holding assembly **504** comprises an axial hinge **510** having a
20 main direction **P2** substantially parallel to the optical axis **O**. In the folded position, control systems **502** and **504** are accommodated in the free space within the optical system **102**.