

SYSTEMS AND METHODS FOR PROCESSING SAMPLES IN A CLOSED CONTAINER, AND RELATED DEVICES

RELATED APPLICATION

[0001] This application claims the benefit of priority to U.S. Provisional Application Serial Number 60/760,087, filed January 18, 2006, the contents of which are hereby incorporated by reference as if recited in full herein.

FIELD OF THE INVENTION

[0002] The present invention relates to automated processing of samples and materials, and may be particularly suitable for processing nucleic acids in a closed environment.

BACKGROUND OF THE INVENTION

[0003] Nucleic acid based amplification reactions are widely used in research and clinical laboratories to aid in the diagnosis of disease and/or identification of pathogenic organisms in a test sample. Such amplification reactions may also be used for development of vaccines, including, for example, autologous vaccines derived from a patient's own tumor cells. Amplification of nucleic acids isolated from tumor tissue allows for autologous vaccine production even from small tumors, and therefore affords the opportunity to treat patients with minimal tumor burden.

[0004] Generally stated, the currently known amplification schemes can be broadly grouped into two classes based on whether the enzymatic amplification reactions are driven by continuous cycling of the temperature between the denaturation temperature, the primer annealing temperature, and the amplicon (product of enzymatic amplification of nucleic acid) synthesis temperature, or whether the temperature is kept constant throughout the enzymatic amplification process (isothermal amplification). Typical cycling nucleic acid amplification technologies (thermal cycling) are polymerase chain reaction (PCR), and ligase chain reaction (LCR). Specific protocols for such reactions are discussed in, for

example, Short Protocols in Molecular Biology, 2nd Edition, *A Compendium of Methods from Current Protocols in Molecular Biology*, (Eds. Ausubel et al., John Wiley & Sons, New York, 1992) chapter 15. Isothermal reactions include transcription-mediated amplification (TMA), nucleic acid sequence-based amplification (NASBA), and strand displacement amplification (SDA).

[0005] Nucleic acid amplification is discussed in, for example, U.S. Pat. Nos. 4,683,195; 4,683,202; 5,130,238; 4,876,187; 5,030,557; 5,399,491; 5,409,818; 5,485,184; 5,409,818; 5,554,517; 5,437,990 and 5,554,516. It is well-known that methods such as those described in these patents permit the amplification and detection of nucleic acids without requiring cloning, and are responsible for sensitive assays for nucleic acid sequences. However, it is equally well recognized that, along with the sensitivity of detection possible with nucleic acid amplification, the risk of contamination by minute amounts of unwanted exogenous nucleic acid sequences is extremely great. The utility of amplification reactions may be enhanced by methods to control the introduction of unwanted exogenous nucleic acids and other contaminants.

[0006] In particular, for processing of biological samples, including for example the production of therapeutic agents, like vaccines for autologous therapy, current good manufacturing practice (GMP) typically requires manufacture in an aseptic environment.

[0007] Accordingly, there remains a need in the art to provide automated systems and methods for processing nucleic acids and other samples.

SUMMARY OF EMBODIMENTS OF THE INVENTION

[0008] Embodiments of the present invention are directed to systems, apparatus and methods for automated processing of one or more samples. The systems can be used to manipulate items in a closed environment, and may be particularly useful in the fields of medicine, diagnostics, biotechnology, electronics and nanotechnology. Embodiments of the invention may be particularly relevant for processing biological samples, including, but not limited to, tissues, blood,

blood products, nucleic acids (*e.g.*, RNA, DNA), proteins, cell cultures, and the like.

[0009] Embodiments of the present invention provide an apparatus for manipulating one or more items in a closed container. The container, also referred to herein as an "isolation container", comprises a tray defining an interior chamber, which is configured to hold any number of items to be manipulated, and a flexible barrier configured and dimensioned to cover the interior area and seal with the container tray. A tool for manipulating items within the interior area is attached to or integrated with or within the flexible barrier.

[0010] The tool can have a first interface that is accessible from an exterior side of the barrier that is configured to attach to a robotic device. The tool can also include a second interface that can extend from an opposite side of the barrier, such that it is disposed within the interior area when the flexible barrier is sealed with the container. The tool can be configured to manipulate items within the container when the robotic device is attached to the first interface. In some embodiments, the one or more items in the closed container comprise, for example, any of nucleic acids, other samples, reagents, wash fluids, pipette tips, vessels, other consumables and/or any combination thereof. Other tools or devices may also be disposed within the container, for example tools or devices for processing, manipulating, measuring, analyzing, sampling and/or storing samples or other items within the container.

[0011] In some embodiments, systems and methods for automated processing of nucleic acids and other samples include a single-use disposable isolation container assembly with a tray and a flexible barrier configured to seal with the tray, thereby providing a closed work area within the sealed tray. The closed work area may be aseptic.

[0012] A pipette head and/or other sample manipulation device can be attached to the inside of the barrier, and the barrier can include an interface for a robotic arm or other device that is used to manipulate items within the sealed work area. When the barrier is sealed over the tray, the barrier separates the contents of the tray from the robot or other manipulation device. The barrier is flexible, and allows the robotic arm to move the pipette head or other sample manipulation

devices throughout the work area of the tray. All samples, reagents, pipette tips and other consumables, tools or devices for processing nucleic acid samples may remain within the closed compartment provided by the isolation container during processing.

[0013] In another embodiment, methods of processing nucleic acids, (*e.g.*, RNA and/or DNA) utilize a disposable (single-use) isolation container to reduce the risk of contaminating subject material with undesired biological matter, *e.g.*, from an operator, another subject or the external environment. In some embodiments, the isolation container is designed for RNA isolation from a biological sample, including but not limited to one or more of the following: tumor tissue, blood, blood products, cells, pathogens, etc. In particular embodiments, the biological sample comprises a tumor homogenate, and the system provides all the features and functionality to convert clarified tumor homogenate into *in vitro* transcribed (IVT) RNA.

[0014] Typically, only the inside of the isolation container is exposed to the subject material, thereby preventing possible contamination of the processing system and reducing cleaning requirements between consecutive subject samples processed by the system. In some embodiments, the processing system processes samples in one isolation container at a time. In other embodiments, the systems can be configured to process samples in two or more isolation containers substantially concurrently.

[0015] In some embodiments, the present invention provides an apparatus for the transfer of fluid comprising working fluid and a working fluid pump that are separated from a sample device by a diaphragm. In use, a sample or other fluid may be drawn into or expelled from the sample device by a change in pressure which is transmitted across the diaphragm, *e.g.*, by movement of the diaphragm when the working fluid pump changes pressure of the working fluid. In one embodiment, the sample device is a pipette tip or other tube for uptake, dispensing and/or mixing fluidic samples, and/or for transferring a sample, reagent or other fluid from one location to another location. The pipette tip or tube may be of any suitable shape and size.

[0016] In yet other embodiments, the present invention provides an apparatus for measuring the volume of a fluid comprising: at least one light source or emitter and at least one receiver; a cuvette configured with a light path through which the receiver can detect a change in the light path associated with whether the cuvette contains fluid or is empty; and a fluid transfer device in communication with the receiver to determine the volume of fluid that has been removed from the cuvette.

[0017] Other embodiments are directed to biological sample processing containers. The containers include a single-use disposable tray having a substantially rigid body with a first workstation configured to hold a vessel for incubation in a thermal block (*e.g.*, a single tube, multi-well plate or strips, a PCR plate, etc.), a second workstation configured to hold reagents, and a third workstation configured to hold pipettes.

[0018] Some embodiments are directed to flexible barriers having an outer edge portion configured to seal to a tray to define a sealed closed interior chamber. The flexible barrier includes an elastomer and is sealably attached to a robotic arm interface at a medial portion of the barrier.

[0019] Yet other embodiments are directed to an automated pipette tip disengagement system. The system includes: (a) a tray having a sidewall; and (b) a robotic arm merging into a manipulation tool having an outwardly extending lever configured to contact the tray sidewall, whereby contact with the sidewall forces the lever to pivot and release a respective used pipette tip held by the manipulation tool. In some embodiments, the tray has an angled sidewall that contacts the manipulation tool lever.

[0020] Some embodiments are directed to systems for processing liquids. The systems include: (a) a robotic arm; and (b) a manipulation tool that cooperates with the robotic arm, the tool configured to releasably engage a pipette tip and automatically translate to pierce a cover on a vessel a plurality of times in different spaced apart locations before withdrawing fluid from the vessel through one of the pierced openings in the cover.

[0021] Other embodiments are directed to elution trays. The trays are sterile biocompatible elution trays having a plurality of spaced apart receptacles, a

plurality on a first side of an upwardly extending barrier and a plurality on an opposing side of the barrier. The receptacles have a channel that extends on each side of and tapers down in the direction of a primary tubular portion.

[0022] Still other embodiments are directed to kits for use with an automated processing system. The kits include: (a) a single-use disposable container comprising a tray and a flexible barrier configured to sealably attach thereto; (b) a single-use disposable reagent rack configured to reside in the container at a first workstation; (c) a single-use disposable binding column manifold configured to reside in the container; and (d) a single-use disposable pipette rack configured to reside in the container.

[0023] Some embodiments are directed to methods of transferring liquids. The methods include: (a) programmatically directing a robotic arm to move an interface tool releasably holding a pipette tip; (b) automatically piercing a sealant on a vessel holding a target liquid a plurality of times using the pipette tip; then (c) automatically withdrawing liquid from the vessel with the pierced sealant using the pipette tip.

[0024] Some embodiments are directed to methods of releasing liquids from pipettes. The methods include: (a) programmatically directing a robotic arm to move an interface tool releasably holding a pipette to orient the pipette in a downwardly extending angled orientation with the tip proximate to a receiving surface in a closed container; (b) then automatically moving the downwardly oriented angled pipette in a substantially straight line along a plane, while releasing a flowable substance from the pipette.

[0025] Yet other embodiments are directed to methods of aspirating liquids into pipettes. The methods include: (a) programmatically directing a robotic arm to move an interface tool releasably holding a pipette to engage a vessel holding a target fluid in a closed container; then (b) automatically moving the pipette inside the vessel to mix the liquid in the vessel; then (c) aspirating the mixed liquid into the pipette.

In some embodiments, the method can include aspirating and dispensing the liquid to mix the liquid (once or multiple times).

[0026] Still other embodiments are directed to automated methods of processing a sample in a closed system. The methods include: (a) providing a sample in a sealably closed container having a flexible barrier; and (b) programmatically directing a robotic arm to cooperate with the flexible barrier to move an interface tool inside the closed container through a series of operations while the closed container remains sealed to process the sample.

[0027] The method may optionally also include one or more of the following: (c) electronically and automatically measuring volume and concentration of the sample at a plurality of times during the amplification; (d) electronically and automatically monitoring seal integrity of the closed container before, after, and/or during use; and (e) capturing at least one amplified RNA sample in an aliquot vessel without disrupting the sealed status of the closed system.

[0028] Still other embodiments of the invention are directed to apparatus for manipulating items in a closed container. The apparatus include: (a) a container having an interior region configured to hold a plurality of items to be manipulated; and (b) a recirculating vacuum system configured to circulate air sealed within the interior region of the container in a closed loop.

[0029] Although described in some embodiments herein with respect to method aspects of the present invention, it will be understood that the present invention may also be embodied as systems and computer program products. Also, it is noted that any of the features claimed with respect to one type of claim, such as a system, apparatus, method or computer program, may be claimed or carried out as any of the other types of claimed operations or features.

[0030] Other systems, methods, system components and/or computer program products according to embodiments of the invention will be or become apparent to one with skill in the art upon review of the following drawings and detailed description. It is intended that all such additional systems, methods, and/or computer program products be included within this description, be within the scope of the present invention, and be protected by the accompanying claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] Other features of the present invention will be more readily understood from the following detailed description of exemplary embodiments thereof when read in conjunction with the accompanying drawings, wherein like references numerals represent like elements. The drawings are merely exemplary to illustrate certain features that may be used singularly or in combination with other features and the present invention should not be limited to the embodiments shown. Features shown with respect to one embodiment or figure may be used with other embodiments or figures.

[0032] **Figure 1** is a perspective view of a processing system according to embodiments of the present invention;

[0033] **Figure 2** is a side view of the upper portion of the system of **Figure 1**, including an isolation container on a work surface;

[0034] **Figure 3** is a perspective view of one embodiment of the work surface of the system of **Figure 1**, illustrated without the isolation container;

[0035] **Figure 4** is a perspective view of an isolation container assembly with the flexible barrier not yet attached according to embodiments of the present invention;

[0036] **Figure 5** is a cutaway perspective illustration of an isolation container assembly according to embodiments of the present invention;

[0037] **Figure 6** is a cutaway perspective view of the isolation container assembly of **Figure 5**;

[0038] **Figures 7A** and **7B** are side views of a syringe pump system according to embodiments of the present invention;

[0039] **Figures 8A** and **8B** are cross-sectional side views of a pipette head adapted to cooperate with a fluid pump system according to embodiments of the present invention;

[0040] **Figure 8C** is a top view of a flexible isolation diaphragm used in the pipette head of **Figure 8A**, according to embodiments of the present invention;

[0041] **Figure 8D** is a cross-sectional view of the flexible isolation diaphragm shown in **Figure 8C**;

[0042] **Figures 9A and 9B** are perspective and cross-sectional views, respectively, of a flexible barrier according to embodiments of the present invention;

[0043] **Figures 9C and 9D** are perspective and cross-sectional side views, respectively, of other embodiments of a flexible barrier;

[0044] **Figure 9E** is a perspective view of a flexible barrier with an integral coupler, the coupler in the barrier shown in partial section view, according to embodiments of the invention;

[0045] **Figure 9F** is a perspective view of a portion of a robotic arm having a coupler configured to engage the barrier coupler shown in **Figure 9E** according to embodiments of the present invention;

[0046] **Figure 9G** is a perspective view of the assembly of the components shown in **Figures 9E and 9F** (without the flexible barrier) and with the outer housing over the internal components shown transparent and in broken line;

[0047] **Figure 9H** is a perspective view of the assembly shown in **Figure 9G** with the flexible barrier attached according to embodiments of the present invention;

[0048] **Figure 10** is a cross-sectional view of a PCR plate and thermal cycler lid assembly according to embodiments of the present invention;

[0049] **Figure 11** is a perspective view of a thermal cycler assembly with a thermal cycler lid drive system according to embodiments of the present invention;

[0050] **Figure 12** is a perspective view of the thermal cycler lid drive system of **Figure 11** in use with a flexible thermal cycler lid seal of a container according to embodiments of the present invention;

[0051] **Figures 13A and 13B** are cross-sectional views of the lid seal of **Figure 12** during movement of the thermal lid into and out of the work space of the container according to embodiments of the present invention;

[0052] **Figure 13C** is a partial cutaway side perspective view of the lid seal and container shown in **Figures 13A and 13B**.

[0053] **Figure 14** is a perspective view of a manifold for housing DNA and RNA binding columns according to embodiments of the present invention;

[0054] **Figure 15** is a perspective view of the manifold of **Figure 14** during engagement with a pipette head to move the manifold between stations according to embodiments of the present invention;

[0055] **Figure 16** is a schematic side view depicting a closed vacuum system prior to use with an isolation container according to embodiments of the present invention;

[0056] **Figure 17** is a schematic side view of the vacuum system of **Figure 16** during use with the isolation container according to embodiments of the present invention;

[0057] **Figure 18** is a perspective view of a processing system work surface with a cutaway of an isolation tray, showing cooling units for controlling humidity and vapor concentrations according to embodiments of the present invention;

[0058] **Figure 19A** is a cross-sectional perspective view of a cuvette attached to an isolation tray according to embodiments of the present invention;

[0059] **Figure 19B** is a side perspective view of cooperating components of a spectrophotometer cuvette measuring system according to embodiments of the present invention.

[0060] **Figures 20A – 20D** are examples of operations of a system to measure volume in a volumetric cuvette according to embodiments of the present invention, each figure being a section view of the volumetric cuvette measuring system;

[0061] **Figure 20E** is a top, side perspective view of a multi-cuvette volume measurement system that can operate as described with respect to **Figures 20A-20D** according to embodiments of the invention;

[0062] **Figure 20F** is a bottom perspective view of the container shown in **Figures 4 and 5** illustrating cuvettes extending below the bounds of the container according to embodiments of the present invention;

[0063] **Figure 21A** is a perspective view of a reagent rack according to embodiments of the present invention;

[0064] **Figure 21B** is a schematic top perspective view of the reagent rack shown in **Figure 21A** illustrating a piercing technique according to embodiments of the present invention.

[0065] **Figure 22** is a series of schematic illustrations showing operation of an aliquot tube mechanism according to embodiments of the present invention;

[0066] **Figure 23A** is an illustration showing components that may be loaded into an isolation container tray according to embodiments of the present invention;

[0067] **Figure 23B** is a top perspective view of a partially assembled container using the kit components shown in **Figure 23A** according to embodiments of the present invention;

[0068] **Figure 23C** is a bottom view of the partially assembled kit shown in **Figure 23B**;

[0069] **Figure 23D** is a top view of the container in the kit shown in **Figure 23A** before kit components are attached at a use site according to embodiments of the invention;

[0070] **Figure 24** is an exploded view of the isolation container tray of **Figure 23A** illustrating sealing of the tray with a flexible barrier according to embodiments of the present invention;

[0071] **Figure 25** is a flow chart of operations that can be carried out according to embodiments of the present invention;

[0072] **Figures 26A and 26B** are enlarged side perspective views of the pipette head with lever according to embodiments of the present invention;

[0073] **Figure 26C** is a side perspective view of the lever shown in **Figures 26A and 26B** shown engaging with an interior surface of the container to release a pipette tip according to embodiments of the present invention;

[0074] **Figure 27** is a top perspective view of a trolley that can be used to load the container onto an instrument according to embodiments of the present invention;

[0075] **Figure 28A** is an enlarged side perspective view of a work surface with a biasing assembly configuration that can force the container into alignment with the robotic arm according to embodiments of the present invention;

[0076] **Figure 28B** is a bottom perspective view of a portion of the work surface shown in **Figure 28A** illustrating a spring used to force the container in a desired direction according to embodiments of the present invention;

[0077] **Figure 29A** is a top view of an elution tray according to embodiments of the present invention;

[0078] **Figure 29B** is a bottom perspective view of the tray shown in **Figure 29A**;

[0079] **Figure 29C** is a top perspective view of the tray shown in **Figure 29A**;

[0080] **Figure 30A** is a top perspective view of a waste tray cover;

[0081] **Figure 30B** is a bottom perspective view of the tray cover shown in **Figure 30A**;

[0082] **Figure 31** is a block diagram of a circuit used in automated systems contemplated by the present invention; and

[0083] **Figure 32** is a block diagram of a data processing system according to embodiments of the present invention.

DETAILED DESCRIPTION

[0084] While the invention may be made in modified and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will be described in detail. It should be understood, however, that there is no intent to limit the invention to the particular forms disclosed, but on the contrary, the invention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention. Like reference numbers signify like elements throughout the description of the figures.

[0085] In the figures, the thickness of certain lines, layers, components, elements or features may be exaggerated for clarity. Broken lines illustrate optional features or operations or hidden components unless specified otherwise. In the claims, the claimed methods are not limited to the order of any steps recited unless so stated thereat.

[0086] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As

used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items. As used herein, phrases such as "between X and Y" and "between about X and Y" should be interpreted to include X and Y. As used herein, phrases such as "between about X and Y" mean "between about X and about Y." As used herein, phrases such as "from about X to Y" mean "from about X to about Y."

[0087] Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the specification and relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein. Well-known functions or constructions may not be described in detail for brevity and/or clarity.

[0088] It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one element, component, region, layer or section from another region, layer or section. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the present invention. The sequence of operations (or steps) is not limited to the order presented in the claims or figures unless specifically indicated otherwise.

[0089] The terms "closed system" or "closed container" refers to systems and containers, respectively, that are sealed and operate in a substantially,

if not totally, closed manner to inhibit or prevent the introduction of exogenous or external materials into (or out of) the system or container during processing. The closed systems can be configured to inhibit or prevent contamination. In some embodiments, components of the closed systems or containers can be pre-sterilized prior to use at a manufacture site, sterilized at the point of use, and/or sterilized after a respective closed system is assembled and closed prior to use. The closed systems or containers can be pressure- or vacuum-tight to some target or predefined leak rate at certain atmospheric conditions. The leak rate may be detected by an internal and/or external sensor using a vacuum or pressure sensor test or other leak check system and the like. The typical atmospheric conditions may change with location of the apparatus, from sea level to higher altitudes. However, the closed systems contemplated by embodiments of the invention may be used in marine (subsurface, deep sea), flight, and/or space environments as well, with the seal being sufficient to substantially maintain the target leak rate at those atmospheric conditions. The closed systems or containers can be utilized for their respective intended purpose without breach to the integrity of the closed system. The closed systems or containers may be adapted for fluid transfers of target fluid samples in or out while maintaining asepsis, and/or can be connectable to other closed systems while maintaining the integrity of the closed systems. Filters may optionally be used in a flow path that may be open to atmosphere or other components during process. The filters may be configured to filter to a desired clean level or class, to facilitate the closed state, such as class 100,000, class 10,000, class 1000 filters or even class 100 filters.

[0090] The term "isolation container" refers to a container configured to hold, enclose and/or isolate internal components and the processing of one or more items or samples held therein from external pathogens, microorganisms and the like and/or other materials that may exist in an external environment. The isolation container may be a single-use disposable container. In some embodiments, the samples in the isolation container are or comprise nucleic acids, *e.g.*, for processing nucleic acids in tissues (*e.g.*, clarified tumor homogenate) into IVT RNA.

[0091] The term "single-use disposable" refers to a component that is not reused. That is, after completing its intended use, *i.e.*, processing or production

of a target sample or sample(s), it is disposed of. The isolation container can be single-use disposable (and may be labeled as such), such that the isolation container remains a closed system that is disposed of in the closed sealed state with its internal components held therein, to inhibit any inadvertent external release or exposure of its internal content(s) after processing/production of the target product.

[0092] The term "aliquot" refers to a desired amount of a target fluid; the amount of fluid may be in a predetermined and/or specific range. The term "aliquot tube" refers to a tube that permits removal of a fluid aliquot from the container. Typically, the term "aliquot tube" refers to a tube that is in communication with the interior of the isolation container to receive at least one (and typically a plurality of) fluid aliquot without breaching the closed status or sealed integrity of the isolation container. The aliquot tube can be flexible and sterile and may comprise an elastomer, such as PVC.

[0093] The term "cuvette" refers to a vessel configured to permit mechanical, electrical or optical measurement(s) of a substance, typically a fluid, and typically concentration or volume measurements, contained within that vessel. The cuvette may be sized to hold a relatively small amount of fluid, typically, in the range between about 0.001 mL to about 5.0 mL.

[0094] The term "pipette tip" refers to a tube open at both ends to be able to intake and/or discharge fluid, typically liquids in small volumes, and typically in amounts between about 0.1 μ L to about 1000 μ L. The tube may have an irregular or constant perimeter shape or size, typically tapering down at a lower tip from the head. A "pipette" can be defined by a plurality of matable components. That is, a pipette can include a tip portion and a head portion. The head portion can be defined on a manipulation tool attached to a robotic device (indirectly) that releasably attaches to different pipette tips during processing. Pipettes of different volumetric sizes may be used in a single container/processing system.

[0095] The term "Human Machine Interface (HMI)" is well known to those in the art and refers to an interface which allows an operator to input, direct, interact with or machines, and typically includes an electronic display with a "Graphic User Interface (GUI)" that programmatically provides information to and accepts control instructions from an operator.

[0096] The term "aseptic" refers to processing conditions that inhibit or prevent contamination of a target sample in an interior processing space of a container by external pathogenic microorganisms and/or undesired exogenous materials, and/or to inhibit or prevent contamination of the proximal exterior environment with the contents of the container.

[0097] The term "binding column" refers to a filtration/elution column that can be used for separating components of a sample or derivatives thereof. In some embodiments, the binding column can be used for nucleic acid (*e.g.*, DNA and/or RNA) isolation or purification. In some embodiments, the binding column may contain a silica membrane.

[0098] The term "tray" refers to a substrate having sufficient rigidity to hold one or more components. The tray may be substantially flat or may have a bowl-like shape. The tray may also have other shapes and configurations. The tray can be configured to define integral wells or holding regions or may be configured to sealably mate with and/or hold devices or containers, typically those components associated with at least one processing workstation.

[0099] The term "user" is a generic term for an operator, programmer, and/or maintainer.

[0100] The term "robot" refers to an automated device that can be programmatically directed to translate in desired directions to carry out defined processing steps or operations. The term "robot" is used broadly and includes a stationary mounted robotic arm with a multi-axis translation as well as a fully mobile robot and other appropriate robotic devices.

[0101] The present invention may be embodied as systems, methods, and/or computer program products. Accordingly, the present invention may be embodied in hardware and/or in software (including firmware, resident software, micro-code, *etc.*). Furthermore, the present invention may take the form of a computer program product on a computer-usable or computer-readable storage medium having computer-usable or computer-readable program code embodied in the medium for use by or in connection with an instruction execution system. In the context of this document, a computer-usable or computer-readable medium may be any medium that can contain, store, communicate, propagate, or transport the

program for use by or in connection with the instruction execution system, apparatus, or device.

[0102] The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific examples (a non-exhaustive list) of the computer-readable medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, and a portable compact disc read-only memory (CD-ROM). Note that the computer-usable or computer-readable medium could even be paper or another suitable medium, upon which the program is printed, as the program can be electronically captured, via, for instance, optical scanning of the paper or other medium, then compiled, interpreted, or otherwise processed in a suitable manner, if necessary, and then stored in computer (electronic) memory.

[0103] Apparatus and methods for automated processing in a closed environment are discussed below. The systems can be used, for example, to process, fabricate, assemble or otherwise manipulate anything in a closed environment, and is particularly useful in the fields of medicine, forensics, therapeutics, diagnostics, biotechnology, electronics and nanotechnology. For convenience of description, various aspects and features of the invention are described herein in the context of a system for processing nucleic acids. One skilled in the art will appreciate, however, that the following descriptions are intended to be merely illustrative of the invention and not restrictive. Various other applications are intended within the scope of the present invention, including, for example, systems and methods for fabricating, assembling, processing or otherwise manipulating any items in a closed container.

Overview of Exemplary Automated Systems

[0104] In overview, referring to **Figure 1**, the system **10** can be configured with a robotic arm **20** that manipulates one or more items within a

closed container assembly 12 with an interior chamber (also described as an interior work area or region, where the word "area" is used broadly and not in a two-dimensional mathematical manner). In some embodiments, the container assembly 12 has an interior region 18 configured to hold a plurality of items to be processed and/or otherwise manipulated. A flexible barrier 16 can be configured and dimensioned to cover the interior of and seal with a container tray 14. A tool for manipulating items within the chamber is attached to or integrated within the flexible barrier 16 and can extend into the interior region when the barrier 16 is attached to the tray 14. The tool can have an adapter or other interface that is accessible from an exterior side of the barrier, such that the tool may be manipulated by a robotic device from outside of the container when the barrier is sealed with or otherwise attached to the container tray. The tray 14 may be configured to include one or more workspaces, areas, stations, racks, holders, receptacles, wells or other devices for holding one or more items or process components or fluids in the closed container. Other tools or devices may also be disposed or otherwise accessible from within the container; for example, tools or devices for processing, manipulating, measuring, analyzing, sampling and/or storing samples or other items may reside within the chamber of the container.

[0105] Turning now to the figures, **Figure 1** shows an exemplary automated nucleic acid processing system 10. System 10 may include a container assembly 12. The container assembly 12 may be an isolation container 12. The system 10 also includes a robot 20 (typically a robotic arm) or other automated or manually directable device for manipulating items within and/or associated with the container assembly 12. The container assembly 12 comprises the tray 14 and the flexible barrier 16. The barrier 16 is configured to seal with or otherwise attach to the tray 14. An outer perimeter edge portion 16p of the barrier 16 can sealably engage the container tray 14, providing a closed, aseptic work area 18 within the container assembly 12. In some embodiments, the container assembly 12, or any portion thereof, is single-use disposable. In particular embodiments, the sample can be discharged, collected or captured outside of the container without opening the sealed container, and the sealed container 12 can be disposed of "intact" with the remainder internal contents.

[0106] The tray **14** can be substantially rigid and may be a molded body. In some embodiments, the tray **14** comprises a medical grade (such as USP Class VI or other suitable grade) molded polymer. The body of the tray **14** may comprise one or more substantially clear, translucent or transparent polished regions for optic visibility that provides for internal viewability. The tray **14** can be molded in a clean room mold and in a clean room molding facility to inhibit and/or minimize bioburden and particulates. The tray **14** may be sterilized prior to or after sealing the flexible barrier **16**, by using conventional sterilization techniques, such as, for example, surface decontamination with VHP (vaporous hydrogen peroxide), gamma irradiation or ethylene oxide vapor hydrogen peroxide. For shipment, the tray **14** may be enclosed in double elastomeric sterile packaging material, such as such as sealed double plastic wrapping/bagging.

[0107] The barrier **16** can be configured to allow the robot **20** to move a tool inside the work area **18** of the sealed container assembly **12** between about 4-24 inches vertically, and horizontally at least about the width and length of the tray **14**, without destroying the sealed integrity of the container assembly **12**. In some embodiments, the robot **20** can direct an internal interface to have between 6-12 inches of vertical movement in the sealed container assembly **12** without destroying the sealed integrity of the seal. The barrier **16** can be sized and configured relative to the tray **14** to provide for a sufficient volume of air to allow the desired range of movement of the robot **20** without overly compressing or decompressing the interior volume of the container **12**.

[0108] In some embodiments, the system **10** is used to process biological samples, including, but not limited to tissues, blood, blood products, nucleic acids, proteins, cell cultures, and the like inside the container assembly **12**. In such embodiments, the container **12** may comprise, for example, items such as biological samples, reagents, wash fluids, pipettes, pipette tips, vessels, other consumables or any combination thereof.

[0109] As shown, the system **10** can be a self-standing, self-contained unit. The system **10** can include a housing or chassis **70** for supporting an isolation container assembly **12** and other components of the automated system **10**, such as, for example, the robot **20**, a thermal block **30** (e.g., a heat block and/or cooling

block, etc...), an aliquot retrieval assembly **40** and related mechanisms for collecting processed samples, a user interface **60**, and various other components and mechanisms as described in the sections that follow. The thermal block **30** may cooperate with a thermal block assembly **1000** as shown, for example, in **Figures 10, 11**.

[0110] In some embodiments of a processing system **10**, an operator or maintainer may only need to access the front of the system **10** for normal operation. As shown in **Figure 1**, one or more access doors **110** may open, *e.g.*, by lifting substantially vertically or opening to a side or in another direction, to provide accessibility while installing or removing an isolation container **12**.

[0111] In some embodiments, due to the automated nature of system **10**, the door **110** may protect the operator from moving parts of the system during operation. The system **10** may incorporate an electronically controlled interlock or other mechanism to inhibit or prevent the operator from opening the door **110** while the system is in operation. A manual override may be provided to allow opening of the interlocked guards, and such an override may be employed, for example, if no power is available. The user interface **60**, also referred to as an HMI (Human Machine Interface), can be configured to allow an operator to initiate a processing operation or otherwise control the system **10**, and can be mounted on the front of the chassis **70** next to the access door **110**. In one embodiment, the display screen **61** and controls (touchscreen, keypad or other input) of the HMI may be positioned to allow the user to view and operate them while standing. In some embodiments, the rear and sides of the system **10** do not need to be routinely accessed by operators. Consequently the system can be positioned against a wall or another system.

[0112] In some embodiments, a lower section of the chassis **70** can contain electronic control systems, power supplies and other components, which may not require operator interaction. These components can be housed in dedicated enclosures that protect the components from accidental fluid ingress and protect the operator from possible electrical hazards. Removable panels **120, 130, 140** may be included to provide access to the electrical components and/or other components inside the enclosures. In some embodiments, only trained service

personnel are permitted or required to access the insides of these enclosures. The service access panels may or may not be interlocked, for example, to allow or disallow the system to continue to operate with the panels removed.

[0113] **Figure 2** shows an enlarged side view of an upper portion of system **10**, including isolation container **12** on a work surface **200**. A pipette head **220** and/or other manipulation device can be attached to or integrated with or within the barrier **16**, for example, such that at least a portion of a pipette head **220** extends into the interior work area **18** of container **12** when the barrier is attached to the tray **14** as shown. The pipette head **220** can include an interface on an opposite side of barrier **16** that is configured to releasably connect with an adapter **210** on an end portion of arm **230** of robotic device **20**. In some embodiments, a pipette head **220** or other manipulation device does not physically pass through the barrier **16**, and may not necessarily couple to a robot or other device through an adapter. Rather, such a pipette head may attach to or otherwise integrate with the inside of the barrier, and may be operated or manipulated from the opposite side of the barrier **16**, for example, using the robotic arm **230** attached to the opposite side of the barrier. In other embodiments, a pipette head or other sample manipulation device integrated with the barrier **16** (which can be substantially impermeable) may be operated by a magnet or other device that supports and/or communicates with the manipulation device through the barrier **16**.

[0114] When the barrier **16** is sealed over the tray **14**, the barrier **16** separates the contents of the tray **14** from the robot **20** or other device that manipulates the pipette head **220**. The seal between barrier **16** and tray **14** can be airtight, thereby providing a closed environment within the container **12**. In some embodiments, the barrier **16** is flexible and allows the robotic arm **230** to move the pipette head **220** throughout the work area **18** within tray **14**. All items or materials involved in processing the nucleic acid samples, including for example biological samples, reagents, pipette tips, or other consumables, and other tools or devices for processing the samples, can remain within the closed work area **18** during processing. The tray **14** may include a number of features or stations **242** which may be molded, formed, attached or otherwise integrated with base **240** of the tray **14**, or another portion of the tray **14**, to accommodate such items.

[0115] As shown, robotic device **20** may be attached to a wall of the chassis **70**. In other embodiments, robotic device **20** may comprise an arm, gantry or linkage system attached to work surface **200** or to another support structure. Suitable robotic devices are known in the art. Non-limiting examples include Stäubli TX90 robot, Epson E2L Scara robot, Kawasaki F Series robots, Yamaha YKL Scara robot, ST Robotics R17 Robot, etc. In some embodiments, the robotic device **20** is a FANUC LR MATE 200iB 5C, 6-axis robot or other suitable multi-axis robotic device, and is used to automatically perform the desired manipulations inside the closed container **12**, such as, for example, aspiration and transfer of fluids using pipette tips and sliding or lifting a binding column manifold during processing of samples.

[0116] The multi-axis robotic arm can be used to move an interface tool releasably holding a pipette to orient the pipette in a number of different directions to help mix the liquid upon aspiration or dispensing. For example, the pipette can be oriented in a downwardly extending angled orientation with the tip proximate to a receiving surface in a receiving vessel in the closed container, then, automatically, the downwardly oriented angled pipette can be moved in a substantially straight line along a plane (similar to a typically layering or dispensing of mustard), while releasing a flowable substance from the pipette. In other embodiments, the robotic arm can automatically move the pipette to mix the liquid in the vessel prior to aspiration, then aspirate the mixed liquid into the pipette. Alternatively or additionally, in some embodiments, the liquid can be aspirated and dispensed at least once to mix the liquid. In some embodiments, the receiving or dispense vessel has a lip, and the robotic arm is configured to direct the pipette tip to move around the perimeter of the lip.

[0117] As shown in **Figure 3**, the horizontal work surface **200**, which may be located inside of front access door **110**, for example, supports various components and mechanisms that interact with an isolation container **12**. The work surface **200** can include one or more guides **390**, that may include guide slots **390s** that engage components on an assembly support trolley **399** (**Figure 27**) to align the container, or other location features to orient and releasably clamp to the isolation container **12** (e.g., to base **240** of **Figure 2**) during processing.

[0118] As shown in **Figure 27**, a container assembly **12** can be prepared on a trolley **399** that can dock with the system **10**. The trolley **399** can include slots **399s** that align with slots **390s** defined by guide **390** on a support surface of the system **10**. To transfer the container assembly **12** to the system **10**, an operator can roll the trolley adjacent to the system **10**, so that the trolley **399** is aligned with the guide **390** of the system **10**. The container assembly **12** can slide into the slots **390s** of the system **10** into proper operative position without requiring that an operator lift the container assembly **12**.

[0119] As shown in **Figures 28A** and **28B**, the work surface **200** can include roller guides **381**, **382** that contact the lower portion of the container **12** when it is in position. The roller guide **382** can be in communication with a spring **383** that can bias the container **12** inwardly so as to fit snugly against the innermost slot wall **390** to be in the desired alignment with the robotic arm for registration of workstation locations.

[0120] Referring again to **Figure 3**, the work surface **200** may support a temperature control device, such as an incubation device for heating and/or cooling regions, vessels, or target objects or locations within the container. Such devices are known to those of skill in the art. In one embodiment, the system **10** includes a thermal cycler **30** for controlling temperature of a PCR plate **610** (**Figure 6**) or other vessel or component during some nucleic acid amplification reactions or other reactions or processes, for example, and a thermal cycler lid mechanism **310** for selectively covering the thermal cycler **30** during such reactions. In one embodiment, a vacuum pump assembly **320** and a pinch valve assembly **330** provide for control of vacuum and circulation of air within the isolation container **12** during processing. The vacuum pump assembly **320** can releasably engage a single-use disposable vacuum head **1602** and associated tubing **1650** (**Figure 23B**). The work surface **200** can also hold the container assembly **12** so as to allow a spectrophotometer **1900s** to communicate with components held by the container assembly **12** as will be discussed further herein.

[0121] One or more syringe pumps **350** (shown, for example, as two pumps) may be used to drive aspiration and dispense actions of pipette head **220** (**Figure 2**). In some embodiments, syringe pumps **350** may be used to pump a

working fluid, *e.g.*, from a reservoir **340**, through the pipette head adapter **210** shown in **Figure 2** to provide vacuum and pressure for operation of pipette head **220**. The working fluid may be substantially incompressible, and can, for example, comprise an aqueous solution of about 50% ethanol. Other fluids, even air, may be used. Additional details of an exemplary embodiment of a pump mechanism and pipette head **220** are described in greater detail below in connection with **Figures 7** and **8**.

[0122] Returning to **Figure 3**, a cuvette holder **360** (see also spectrophotometer cuvette in **Figure 19A**) can be coupled with a spectrophotometer **1900s** typically residing in a lower portion of the chassis **70**, to provide automatic concentration measurements at desired operations during processing. Optionally, the work surface **200** may include one or more cooling features, *e.g.*, a heat exchanger such as a chiller or Peltier cooling plates **370** and **372** are positioned to engage certain portions of the isolation container **12** and help control humidity and vapor concentrations within the sealed container **12**. A lever **380** or other mechanism or device may be used to secure the isolation container into place on the work surface **200**.

[0123] In some embodiments, an RNA processing system may operate in a stand-alone fashion isolated from a larger production system and any data management tools or systems. An internal or external computer system may control and/or monitor the automated components of the subsystem. Users may interact with the interface **60**, for example, to operate the system and monitor status. In other embodiments, the system **10** can communicate with other systems or a monitoring station (which may be in a different room or even in a different facility).

[0124] Additional details of the various components and assemblies, and exemplary methods of use, are described in sections that follow.

Exemplary Isolation Containers

[0125] Referring to the isolation container assembly **12**, tray **14** and flexible barrier **16** are described in greater detail. The tray **14** includes an interior work area **18** and may comprise a number of inserts, recesses, racks, or rack

mounting features and/or stations **242** for holding items within container **12**, *e.g.*, including one or more racks, manifolds or other holders for holding vessels, pipette tips, binding columns, other substrates and/or other consumables or devices for a desired assay or process. All items used to process the material to a desired finished state or product can be held within the container, *i.e.*, the consumables for the system can be self-contained and sealed during processing to minimize the risk of contaminating the interior of the container, or to prevent a sample from contaminating the environment or user. The barrier **16** can have an outermost perimeter portion **16p** (**Figure 5**) that can be configured to releasably or permanently seal with the tray **14**, for example about an annular edge **452** of tray **14** as shown in **Figure 5**. When the barrier **16** is sealed with the tray **14**, at least a portion of pipette head **220** and/or another sample manipulation tool or device extends from the barrier **16** into the work area **18**.

[0126] In some embodiments, the barrier **16** engages the tray **14** along a rigid top edge **452** (**Figure 5**). The outermost perimeter portion **16p** of the barrier **16** can reside against the top edge **452** (**Figure 5**). The top edge **452** may be configured as an upstanding lip with a gap space that receives an O-ring (not shown) that pinches against the barrier **16** to seal the barrier against the tray **14**.

[0127] To create a closed system or environment, the isolation container tray **14** and barrier **16** may be configured to form a physical barrier between items within the container **12** and external devices, mechanisms and pieces of equipment used for processing the items in the container. For example, a flexible thermal cycler lid seal **430** may be integrated within a wall **450** of the tray **14** as shown in **Figure 4**. Such a seal **430** may enclose and define a sleeve or closed channel that receives the lid **1010** (**Figure 11**) and be used to allow the thermal cycler lid mechanism **310** to extend the lid into an aperture **14a** (**Figure 5**) in the sidewall of the tray **14** to cover samples during heating by a thermal cycler block **30**, while providing a physical barrier between the lid mechanism **310** and items within the interior area **18** of container **12**.

[0128] Also, cooling plates **370**, **372** may engage portions of an external surface of the tray **14** to impart changes in temperature within the container **12** while not contacting any items within the isolated work area. In some

embodiments, cooling plates may engage with portions of the external surface of the tray **14** and/or container **12** to control the temperature of items (such as reagents) held inside the isolated work area/space.

[0129] Similarly, as shown in **Figure 3**, a cuvette holder **360** can selectively engage a cuvette **660** (**Figure 6**) extending from base **240** of tray **14** to perform measurements of concentration and/or volume, but the holder **360** may not contact any items within container **12**. Thus, in some embodiments, only the reagents, consumables and tools or devices that are required to directly contact the sample are contained within the isolation container. Such a configuration may have several benefits. For example, a sample can be processed in its own isolated environment and/or the processing equipment residing outside the container will not contact the sample and so is protected from possible contamination. At the conclusion of processing, a desired number of aliquots may be collected in aliquot tubes **440** (**Figure 4**) and removed from the container **12**, *e.g.*, without compromising the integrity of the collected samples or the isolation container, as will be discussed further below. In some embodiments, for example, the sealed isolation container **12**, along with the components contaminated by sample material, can be discarded after a processing cycle.

[0130] **Figures 5 and 6** show additional details of some components of exemplary isolation containers **12**, including the isolation tray **14** and the flexible barrier **16**. The interior work area **18** may be surrounded, for example, by base **240** and one or more walls **450**. The barrier **16** can include a pipette head **220** or other device or tool, which is described in more detail in a separate section below. The barrier **16** can be configured to cover and seal with the tray **14**, for example at a seal **510** along an annular edge **452** of the tray **14**, such that the work area **18** is a closed, typically air-tight, compartment when the barrier **16** is sealed with the tray **14**.

[0131] The tray **14** can be substantially rigid and includes a number of features and/or stations **242** which may be molded, formed, attached or otherwise integrated with tray to accommodate. Some or all of the following components are examples of features that may be integrated into the tray **14**:

- elution **630** and waste **632** stations;

- vacuum inlets and outlets;
- spectrophotometer (concentration) cuvettes **660** (**Figure 19A**);
- other vessels or cuvettes, *e.g.*, volume measurement cuvettes **2060** (**Figures 20A-E**);
- a thermal cycler PCR plate **610** and/or other substrate or vessel that may be heated and/or cooled with a temperature control device;
- reagent vessels **622** in a rack **620**;
- pipette tips **651** in a rack **650**;
- one or more additional tip racks **650** or other disposal container, *e.g.*, for used pipette tips **653**;
- a binding column manifold **50**, *e.g.*, which may include one or more binding columns for nucleic acid processing; and
- one or more aliquot tubes **440** for processing outputs: *e.g.*, nucleic acids, such as (*e.g.*, DNA, RNA, tumor total RNA and/or amplified tumor *in vitro* transcribed RNA and the like), microorganisms, cells, medicaments, etc.

[0132] In some embodiments, the flexible barrier **16** seals with and supports a manipulation tool that interfaces with the robotic device **20** on one side of the barrier and interfaces with internal components on the inside of the barrier **16**. The tool can include the pipette head **220** and additional manipulation features, such as handles **520** or other features or mechanism for engaging internal components, such as, for example, handles **50h** (**Figure 5**) on a binding column manifold **50** for transferring the manifold between the waste and elution stations **632**, **630**, respectively. The flexible barrier **16** can allow the pipette head **220** to move sufficiently to access all desired internal components housed by the tray **14**. The head **220** can also engage the binding column manifold **50** to be able to transfer the binding column manifold to and/or from the waste **632** and elution **630** stations. Although not shown, the internal interface may be a plurality of serially attachable interfaces. That is, the pipette head or first interface can be releasably held and interchanged for another manipulation tool inside the closed container. The

selection of manipulation tools can be held by tray **14** and/or an internal manipulation tool rack (not shown).

[0133] A mixer and/or centrifuge may cooperate with or be integrated into the tray to mix, homogenize, separate or otherwise blend or process a liquid or sample, such, as for example, a biological sample or other materials as desired (not shown). In other embodiments, the starting material may be pre-mixed, and then placed in the rack **620** or at another location. The mixer may be a rotating head mixer, a magnetic mixer or a homogenizer that can mix the desired material.

Exemplary Pipetting Systems

[0134] Referring to **Figures 7A and B**, a pipetting system **700** comprising a pipette head **220** and adapter **210** assembly may be used to perform fluid transfers inside the isolation container **12**. In keeping with a closed isolation container design, the pipette head **220** can be configured to maintain a barrier between the fluid being transferred and the pipette pump mechanism. A filter and/or a flexible diaphragm **710** can provide the physical contamination-resistant barrier between the interior of the isolation container **12** and the outside.

[0135] In some embodiments, to provide high volumetric accuracy, the pipetting system **700** may use two positive displacement syringe pumps **350-1, 350-2**, *e.g.*, one for low volume transfers (*e.g.*, between about 1 μ l and about 50 μ l) and one for the higher volumes (*e.g.*, between about 51 μ l and about 1000 μ l). In other embodiments, a single pump chamber with different reservoirs or a single reservoir with a means of metering the working fluid can be employed. The pump chambers may be hydraulically connected to the flexible diaphragm **710** via (substantially rigid) tubing and a buffer solution (working fluid). The buffer solution can be a substantially or totally incompressible hydraulic fluid that can reduce or minimize the elasticity of the pipetting system **700**. The robotic arm **230** is used to position the pipette head **220** at desired locations in the workspace. To reduce the potential for reagent carryover during pipette transfers, disposable tips **651** may be used for

fluid handling. That is, after each transfer, the used tip can be discharged into a "trash" receptacle, typically into a used rack, and a new sterile different tip from a sterile rack or supply station may be used for the next transfer. Other components of an exemplary embodiment of the pipetting system **700** are shown in **Figures 7A** and **7B**.

[0136] In some embodiments, the pipetting system **700** is primed to introduce liquid and remove air from the pipette line prior to initial use, and may be primed prior to each time a different pipette head **220** is connected to the pipette head adapter **210**, such as at the beginning of processing of a new closed container **12**. For example, a bleed line connects a bleed port in the pipette head to the working fluid reservoir via a solenoid valve **741**. The valve **741** may be opened during the priming sequence to allow air to be bled from the pumps **350**, through the fluid lines **222,223** (**Figure 8A**) and pipette head **220**, and back to the working fluid reservoir **340**. The robotic arm **230** can be directed to orient the fluid lines in the pipette head **220** so that they are angled during the priming. Once the system **700** is primed, the bleed valve **741** may be closed and the pipette head **220** is ready to perform fluid transfers. At the completion of the RNA process, the bleed valve **741** may be used to drain the fluid lines **222,223** and pipette head **220**. Filling the fluid lines with air may prevent the possibility of fluid spills during disconnection of the pipette head.

[0137] **Figures 8A** and **8B** show a cross-sectional view of the operation of a pressure transfer mechanism **800** for transferring pressure through the pipette head **220** and to the pipette tips **651, 653**. In some embodiments, the hydraulic working fluid, *e.g.*, from reservoir **340**, actuates the flexible isolation diaphragm **710** (*see also Figures 8C* and **8D**) and drives the pipetting action while maintaining physical separation between the working fluid and the fluids to be aspirated by the pipette. A reservoir of working fluid can reside on one side of the diaphragm **710**, which is sealed from working air on the other side. The flexible diaphragm **710** resides in the head **220** between the working fluid **340** and the internal pipette tip adapter **220a** (*i.e.*, pipette head) and aspirated fluid. **Figure 15** illustrates the adapter **220a** without the diaphragm and upper assembly.

[0138] Referring again to **Figures 8A and 8B**, displacement of the diaphragm **710** affects the working air volume **700a** under the diaphragm **710** and in the pipette tip adapter **220**, thereby causing the pipette tip to intake or discharge (typically metered) amounts of liquid. The overall elasticity of the pipetting system **700** may be directly related to dispense accuracy. In some embodiments, reducing the air volume **700a** can improve both the pipetting accuracy and precision.

[0139] In some embodiments, to facilitate thorough mixing of fluids within reagent vessels, spectrophotometer cuvettes **660** and PCR wells, a repeated aspirate/dispense cycle can be employed and/or the robotic arm **230** can be directed to move the tip of the pipette in multi-axis translation.

[0140] In some embodiments, the tray **14** and/or pipette head **220** may include one or more features to allow used tips **653** to be removed from the pipette tip adapter **220a** (**Figure 8B**). As shown in **Figures 26A-26C**, the pipette head **220** can include a lever **221** that pivots upon contact with a portion of the container proximate to the used pipette rack **650**. As shown in **Figure 26C**, the container sidewall **14w** or a member held thereon can be angled so that upon contact with the outer end of the lever **221**, the lever **221** pivots and pushes the used pipette tip **653** off the adapter **220a** and into a receiving space in the rack **650**. That is, as the pipette head **220** moves downward toward the used rack **650**, the lever **221** contacts the wall **14w**, which forces one end of the lever upward and the end over the pipette tip **653** downward to push the used tip into the rack **650**. Other release configurations may also be used. For example, the used rack **650** may be configured to restrict upward movement of the pipette tip **653** to pull, push or otherwise force or strip the tip from the adapter **220a**.

[0141] The pipette head **220** and/or adapter **210** may attach to fluid lines and load cell wiring which can be elevated to clear the flexible barrier **16**, and a flexible conduit back to the chassis **70**. The load cell wiring communicates with a load sensor in communication with the sterile or new pipette tips. The load cell provides data used to control the loading of new pipettes onto adapter **220a**. For example, the robotic arm can cause the pipette head **220** to advance down with a force between about 5N to about 50N to indicate the pipette tip **651** is properly attached. Adapter **210** can also include a collar for locking and unlocking the

adapter **210** to the pipette head **220**, *e.g.*, as a non-limiting alternative to an engage/release handle mechanism.

Exemplary Flexible Barriers

[0142] **Figures 9A-9E** illustrate exemplary flexible barriers **16** according to embodiments of the present invention. Any suitable material can be used for the barrier. The barrier **16** can be substantially impermeable to air, moisture, and ethanol vapor. The barrier **16** may be moldable without losing sufficient flexibility or impacting permeability. In some embodiments, the barrier **16** comprises a low-density polyethylene, but other alternatives could include a range of urethane materials. In particular embodiments, the flexible barrier is or comprises an "ARMORFLEX" material, available from ILC Dover Company, located in Frederica, Delaware.

[0143] The formed shape of the flexible barrier **16** can allow sufficient robot movement and give the pipette head (or other internal interface) access to the interior of the isolation container **12** without restriction or otherwise pinching or catching the flexible barrier. The shape of the molded flexible barrier **16** can be substantially self-supporting (*e.g.*, it will not collapse into the isolation container) once the flexible barrier **16** is sealed to the tray **14** forming the isolation container **12**.

[0144] In some embodiments, a portion **910** of the barrier **16** may be adapted to integrate with, receive, hold, attach to, mate with, seal with, support, or otherwise interact with a device for manipulating samples within the container, such as, for example a pipette head **220**, another fluid transfer device, and/or another manipulation tool. The portion **910** can be a substantially medial portion. The barrier **16** may include one or more folds, pleats or undulations described as "convolutions" **920**, some of which may be substantially concentric with others. **Figure 9B** illustrates that the portion **910** may include at least one stepped portion **17**, shown as a series of substantially vertically oriented stepped portions **17₁**, **17₂**, **17₃**.

[0145] In some embodiments, as shown for example in **Figures 9C** and **9D**, the barrier **16** may include one or more radial convolutions **930**. The radial and/or concentric convolutions may help facilitate a full range of movement of the pipette head (or other internal manipulation tool interface), and help control the barrier shape during movement of the pipette head. A rim **940**, flange or other feature may provide a surface for clamping, sealing, fixing, adhering, or otherwise attaching the barrier **16** to the tray **14**.

[0146] As shown in **Figures 9C** and **9D**, the flexible barrier **16** can comprise a unitary sheet of material that is stretched or formed into a series of substantially concentric folds, pleats or convolutions that can allow for the desired movement of head **220**. Outer perimeter regions of the barrier sheet **16t** may have a different thickness than a center region **16c**. In some particular embodiments, during fabrication, thicker material can be drawn down to the center during vacuum forming causing thinner central regions and thicker perimeter regions of the barrier sheet **16**. The center region **16c** may include a series of columnated steps **17₁-17₃**, arranged smaller to larger as the barrier **16** moves away from the workspace **18**. In other embodiments, rather than a unitary sheet of material, the flexible barrier **16** may comprise a plurality of co-joined sealed segments of the same or different suitable materials (not shown).

[0147] **Figure 9E** illustrates the flexible barrier **16** sealably attached to a lower portion of the pipette head **220** for subsequent engagement to the robotic arm **20**. A robotic arm coupler **910c** resides outside the barrier **16**. **Figure 9F** illustrates a cooperating coupler **210c** that is configured to engage the coupler **910c**. As shown in **Figure 9G**, fingers **211** are configured to enter apertures in the coupler body **910a** to releasably engage the barrier **16**. The assembly is shown in **Figure 9H** (without the lower container tray **14**).

Exemplary Thermal Block Assemblies

[0148] As shown in **Figure 10**, a nucleic acid processing system may incorporate a thermal block assembly **1000** or any other temperature control device. For example, a nucleic acid processing system can incorporate a thermal cycler for

synthesizing and amplifying nucleic acids. The thermal block assembly **1000** may include, for example, a thermal (heater) block **30**, which may be configured to receive a multiwell strip or plate such as a PCR plate **610**, and a thermal cycler heated lid **1010** which may be actuated by a lid mechanism **310** to cover the PCR plate **610**. For example, in some embodiments, the thermal cycler assembly is used for cDNA synthesis, cDNA amplification, IVT RNA synthesis and DNA removal steps of the process. Various types of thermal blocks and/or thermal cycler devices are available.

[0149] As shown in **Figure 10**, the PCR plate **610** may be incorporated into the isolation container tray **14**. In some embodiments, the perimeter of the PCR plate **610** can be sealed to an open (substantially rectangular) region formed in the base of the tray **14**. Lower portions of the plate **610** extend downwardly from the base of the tray to engage (typically reside in) a thermal cycler heater block **30** while the openings of wells **611** in the plate **610** are accessible from inside of the sealed container **12**. The PCR plate **610** can be sealed to the isolation container tray **14** so that the downwardly extending portions of wells **611** can be in direct contact with the thermal cycler or temperature control device.

[0150] In some embodiments, a compliant gasket, O-ring or other sealing mechanism may be used to attach the PCR plate **610** to the isolation container tray **14**. The compliant gasket may be attached with a heat-swaged clamping feature. In some embodiments, an over-molded thermoplastic elastomer (TPE) seal **1030** is used for attaching and sealing the PCR plate **610** to the isolation container tray **14** as shown in **Figure 10**. In other embodiments, PCR plate features may be formed, such as molded and/or machined, into the isolation container tray substrate. In other embodiments, a glue, tape and/or adhesive may be used to attach the PCR plate **610** to the tray **14**.

[0151] A lid, such as a heated thermal cycler lid **1010** may be used to reduce the loss of reaction fluid via evaporation. The lid **1010** may be lined, for example, with a flexible seal **430** to inhibit evaporated fluid escaping from some or each PCR well **611** and/or for maintaining isolation of the interior of the container **12**. The lid **1010** can be heated to inhibit vapor condensing on the lid or any surface other than the reaction mixture. To provide access to all of the PCR wells,

the thermal cycler lid **1010** may be lifted vertically to release the sealing pressure, then retracted substantially horizontally taking with it the flexible lid seal **430**.

[0152] A drive system **310** for controlling the automatic movement of the lid **1010** may be mounted to the work surface **200** of the processing system **10**, as shown in **Figure 3**. In other embodiments, the lid drive system **310** may be mounted at other locations above or below the work surface **200**. Referring now to **Figure 11**, an exemplary lid drive system **310** is shown with the lid **1010** in the retracted position. The arm **1122** is connected to the lid **1010** and communicates with motor **1150**; this provides for movement of the lid **1010** into and out of container **12**, *e.g.*, through a side-ingress/egress aperture **14a** in the wall of tray **14** where a lid seal (which can be described as a sleeve) is disposed between lid **1010** and the interior of the container as shown in **Figure 12**. Robotic tools or manual input may also be via the seal **430**.

[0153] **Figure 13A** illustrates an exemplary configuration of the lid **1010** in the container **12** and inside the chamber **430c** of the lid seal **430** when extended. **Figure 13B** illustrates the lid **1010** outside the container **12** in a retracted configuration.

[0154] The arm **1122** can be configured to direct the lid **1010** vertically as well as horizontally. In the embodiment shown in **Figure 11** and **12**, the drive system **310** includes a vertical movement mechanism **1124** that provides for vertical movement of the lid **1010**, *e.g.*, when lid **1010** is positioned over the PCR plate **610** within the container **12**. The vertical movement mechanism **1124** may provide a downward force sufficient to seal the lid **1010** with the plate **610** and/or the block **30** (**Figure 10**), for example, using one or more biasing members **1152**. One or more motors **1150**, actuators, gears, linkages or other electro-mechanical devices may be used to drive horizontal and/or vertical movement. As shown in **Figure 12**, the drive system **310** includes an upper plate **1123** with a slot **1123s**. The arm **1122** includes a keel **1122k** that slides in the slot **1123s**. The drive system **310** also includes a lower plate **1126** that is attached to the upper plate **1123** via pivots **1127** and biasing members **1152**. The vertical drive **1124** is attached to the upper and lower plates **1123**, **1126** and is configured to pull the upper plate **1123**

down to force the lid **1010** down once the lid **1010** is in the extended configuration inside the container.

[0155] A portion of the drive system **310** can be physically attached to the interior surface of the sleeve or lid seal **430** to facilitate the seal **430** moving appropriately with the lid **1010**. As shown, in **Figure 11**, in some embodiments vacuum cups **1140** may be incorporated onto the lid **1010** to engage the flexible lid seal **430** and to cause the seal **430** to remain in position during vertical and horizontal movement of the thermal cycler lid **1010**. In other embodiments, the lid seal **430** may be attached in other ways or may be sufficiently flexible to conform to the lid **1010** and move in concert therewith.

[0156] In some embodiments, to facilitate a reliable seal between the isolation container **12** and the flexible lid seal **430**, a clamp plate or other clamping member may be used to compress against an edge portion of the seal **430**, such as via one or more sealing ribs (not shown) on the lid seal against the outside wall of the tray **14**. In other embodiments, the lid seal **430** may be over-molded to the tray **14** using, for example, TPE as discussed above with respect to the PCR plate **610**. O-rings, gaskets, adhesives, tapes, and mounting or sealing members may be used to provide the sealed connection of the lid seal **430** and the tray **14**. **Figure 13A** shows the lid mechanism **310** with the lid **1010** and the seal **430** extended into the interior region of the tray **18** in an engaged position while **Figure 13B** shows the lid **1010** and retracted out through a wall of container **14**. **Figure 13A** illustrates the lid **1010** in position over a thermal cycler and 96-well plate. **Figure 13C** illustrates a partial side perspective cutaway view of the lid mechanism **310** with the lid **1010** extended into the interior region of the container **18**.

Exemplary Waste and Elution Systems

[0157] Various purification means can be used to process samples, such as nucleic acids, proteins, cells, tissues, and the like. Such purification devices include, but are not limited to, magnetic beads, size exclusion membranes, binding plates, filters, and binding columns. Such devices are known to those of skill in the art.

[0158] In one embodiment, the processing system **10** uses a technique of eluting from binding columns for tumor total RNA isolation, cDNA purification and IVT RNA purification. The binding column **1410** (**Figure 14**) can contain a silica membrane. A vacuum elution protocol can be integrated into the isolation container design. In other embodiments, a magnetic elution protocol can be integrated into the container.

[0159] One or more types/sizes of binding columns may be used. For example, in some embodiments, binding columns (e.g., Qiagen RNeasyTM columns) are used as they have a binding capacity suitable for the quantities of RNA, cDNA and IVT RNA that are processed. An additional, smaller Qiagen "Mini" column can be included to provide the ability to concentrate the RNA.

[0160] To inhibit the waste fluid from contaminating the elution vessels, the waste and elution stations **632**, **630**, respectively, can be separate as shown for example in **Figure 6**. In some embodiments, a manifold **50** is used to hold the binding columns (*see Figures 14 and 15*). The manifold **50** can be configured to hold one or more binding columns of various sizes/types, *e.g.*, Qiagen maxi-, midi- and/or mini-binding columns **1410**. The manifold **50** may include wells **50w** for each binding column, lifting members or arms forming lift members **50h** for the pipette head **220** to lift it, and one or more slidably movable lids **1430** that can be used to close off the unused binding columns. The lids **1430** can include a handle **1430h** that can allow the head **220** to slide the lid **1430** in a desired direction. In other embodiments, a manifold **50** may be configured to hold other types of substrates or devices to be used during a desired process. The lift members **50h** can be configured as any suitable lift, including one or more handles (as illustrated), wings, flanges, or other features to facilitate movement of the manifold **50** between stations.

[0161] **Figure 15** shows an example of a mechanism and method for moving a manifold **50** between two or more stations or area of the container **12**, *e.g.*, between the waste and elution stations **632**, **630**, respectively. The pipette head **220** and robot **20** may be used to move the binding column manifold **50** and the columns **1410** to and from, *i.e.*, between the two stations. In the embodiment shown, the manifold **50** may include handles **50h**, wings or other features that

interface with corresponding features **520** on the pipette head **220**, and are used to simplify the engagement between the robot **20** and the binding manifold **50**.

[0162] Each isolation and purification process can use a different set of columns; the pipette head robot may be used to reposition the lids **1430** to close the appropriate set of unused columns. This reduces or minimizes the airflow through the manifold **50**, allowing the pump to generate a sufficiently high vacuum during the isolation and/or purification processing steps. To reduce operator handling of the binding columns **1410** after sterilization, the columns **1410** may be loaded into the manifold **50**, and the assembly sealed into suitable packaging and gamma-sterilized in the manifold **50**. At the time of loading the isolation container at a use and/or assembly facility (such as in a suitable clean room), an operator can remove the packaging from the manifold **50** and place it into the waste station **632**, without ever needing to directly handle the binding columns.

[0163] The waste and elution station configurations can be flexible and/or scalable. The manifold **50** design can be large enough to allow modification or use to suit a 96-well format, or any other type of plate, well or columns, or changes in the combination of maxi-, midi- and mini- columns **1410**.

[0164] Referring now to **Figures 16 and 17**, the elution station **630** can include an elution tray **1610** configured to capture the final output of the binding columns (*e.g.*, fluid containing DNA, RNA, etc.). To inhibit and/or prevent possible cross contamination between DNA and RNA, each binding column **1410** can have its own receptacle **1612** below it in the elution tray **1610**. In some embodiments, the elution process employs a high vacuum, which may generate a significant airflow through the binding column(s) **1410**. The elution receptacles **1612** may be shaped to allow splashed fluids, if any, to run off and pool in a collection vessel while deflecting the air stream away from the pooled fluid. Additional features may reduce or minimize the airflow that passes from one receptacle over another. Further discussion of the tray **1610** will be provided with respect to **Figures 29A-29C**.

[0165] Waste station **632** may include a waste tray **1630** and waste tray cover **1640**. A waste tray cover **1640** may be incorporated into waste tray **1630** to minimize the evaporation of the waste fluid contained in the waste station **632**. The

waste tray cover **1640** may be shaped to direct all waste fluid to flow down into one or more (shown as a central) drain hole **1641** where it is protected from the main airflow below the cover **1640** inside the waste station **632**. **Figures 30A and 30B** illustrate another embodiment of the waste tray cover **1640** which employs a plurality of waste drain holes **1641** using a tray cover that is shaped substantially similar to the elution tray **1610**. In the shielded environment below the waste tray cover **1640**, the air directly above the waste fluid can maintain a high humidity, thus reducing further evaporation. Further discussion of the tray cover **1640** is provided with respect to **Figures 30A and 30B**.

[0166] In some embodiments, a vacuum system **1600** circulates air through container **12**. In some embodiments, the isolation container vacuum system **1600** is configured to eliminate the need for filters. The vacuum system can comprise tubing **1650**, typically flexible tubing, connected from a pump head **1602**, such as via a pinch valve **330** (**Figure 17**), to the waste **632** and elution **630** stations. The outlet of the pump head returns the aspirated air back into the isolation container **12**.

[0167] **Figure 17** shows a circulation path according to one embodiment of the vacuum system **1600**. In this embodiment, the tubing **1650** and disposable pump head **1602** may be attached to the isolation container tray **14** during manufacture. These can be sterilized and shipped as part of the assembly associated with the isolation container tray **14**. Once an isolation container **12** is loaded and sealed, the vacuum system **1600** can remain closed throughout the rest of the processing. During installation of an isolation container into the processing system **10**, the vacuum tubing **1650** can be inserted into the pinch valve **330** and the disposable pump head **1602** is connected to the vacuum pump **320**. In some embodiments, the pump **320** only operates when vacuum is required. The pinch valves **330** may be used to direct the vacuum to the appropriate station. When processing is completed, the tubing **1650** may be extracted from the valve **330** and the pump head **1602** is disconnected from the pump **320**. The tubing **1650** and pump head **1602** can be single-use disposable, along with the rest of the isolation container **12**.

[0168] **Figure 18** shows a cutaway view of a tray **14** in place on the work surface **200** of a processing system **10**, showing exemplary locations of the pinch valve **330** and disposable pump head **1602**. Peltier plates **370** and **372** may provide cooling for a segment of the rear wall **14p** of the tray **14** and for the waste station catchment in the base of the tray **14**, respectively. The wall segment **14p** may be substantially planar (typically substantially vertical, but may be angled) and project inward to define a receiving space for the plate **372**. The wall **14p** may be configured to cooperate with the plate **372** to define a condensation wall. It is noted that in **Figure 18**, the thermal cycler lid drive system **310** is shown with the lid extended into container, without the seal **430** in place and the disposable pump head **1602** is shown, without the flexible vacuum pump tubing **1650**, in place.

Exemplary Process Control and/or Yield Measurement Systems

[0169] In some embodiments, disposable cuvettes **660**, **2060** can be used, for example, as shown in **Figure 19A** and **Figure 20F**. One or more cuvettes **660**, **2060** may be fixedly or releasably mounted to isolation container tray **14**, *e.g.*, such that cuvettes **660**, **2060** extend vertically down from the bottom of tray **14**.

[0170] In some embodiments, the concentration and/or purity of samples, *e.g.* nucleic acids or proteins, can be measured using a spectrophotometer **1900s** (**Figures 3, 19B**) and cuvettes **660** (**Figures 19A, 20F**) or alternative optical methods for concentration measurements, *e.g.*, fluorometer, can be similarly incorporated in the system.

[0171] In some embodiments, as shown in **Figure 19A**, one or more disposable concentration cuvettes **660** are sealably mounted to the tray **14** via a flexible sealing member **1918**, such as a gasket or O-ring. The tray **14** includes mounting members **14m** that engage a clamp **1920** to hold the cuvette **660** tightly against the sealing member **1918**, thus sealing the cuvette **660** to the tray **14** and maintaining the sealed processing environment inside the isolation container. As shown, the cuvette **660** can include an outer edge that is formed as a rigid upper lip **661**. The clamp **1920** includes an inner upstanding arm **1921** that resides against the lip **1901** and an outer arm **1922** that engages the mounting member **14m** to

force the cuvette **660** against the tray **14**. The cuvette **660** includes a cuvette measurement window **660w**, typically at a lower portion thereof.

[0172] Alternatively, the cuvettes **660** (or cuvettes **2060**) can be molded into the tray, overmolded, mechanically clamped, solvent bonded, adhesively affixed, or the like. The spectrophotometer **1900s** (**Figure 3**) can be mounted on the processing system **10**, *e.g.*, beneath the isolation container **12**. The spectrophotometer **1900s** can be configured to make absorbance measurements through cuvettes **660** (**Figure 20F**) while remaining outside the isolation container.

[0173] In some embodiments, there is a cuvette **660**, **2060** for each measurement, such that no cuvette need be reused. The processing system **10** can be configured to move a spectrophotometer cuvette holder **360** (*see, e.g.*, **Figure 3**, **19B**) from cuvette **660** to **660** for each measurement as required. In some embodiments, cuvettes **660** and/or **2060** may be removed from the tray **14**, washed and reused in subsequent trays **14**. In other embodiments, removable cuvettes **660**, **2060** are single-use only (*i.e.*, single-use disposable).

[0174] Various types of spectrophotometers are known and may be utilized for nucleic acid concentration and purity measurements. The spectrophotometer **1900s** may be able to communicate with and be controlled by a controller associated with the processing system **10**. For example, the processing system **10** can command the spectrophotometer **1900s** to take a measurement and the spectrophotometer **1900s** can be able to return the absorbance measurements, typically at ultraviolet wavelengths, such as for example, at about 260 and/or 280 nm, or at any other wavelength of interest. Additionally, the geometry of the spectrophotometer **1900s** and particularly that of a cuvette holder **360** can be integrated with other components of the overall system.

[0175] **Figure 19B** illustrates a spectrophotometer head mechanism that is used to move a single detector head between a number of cuvettes **660**, shown as (4) cuvettes **660** in **Figure 20F**. A robotic operational platform may be used to position the spectrophotometer cuvette holder **360**, *e.g.*, to raise, lower and traverse between cuvettes **660**. The spectrophotometer **1900s** and light source may be mounted in an electrical cabinet of the system, *e.g.*, on a left or right side of the system. Optical fibers may be used to allow the cuvette holder **360** to move while

the spectrophotometer **1900s** and light source remain stationary. That is, as shown in **Figure 19B**, a spectrophotometer drive mechanism can be used to move a single detector head **1900h** to serially hold each of the different cuvettes **660**. The detector in the detector head **1900h** can be coupled to the spectrophotometer **1900s** via a plurality (typically two) optical fibers. In other embodiments, each cuvette **660** could be located in an individual cuvette holder **360** and the light source switched between the optical fibers connecting the light source to the multiple cuvette holders (not shown) to communicate with the spectrometer for measurements.

[0176] Volume measurement(s) of a sample may be used in combination with the concentration measurement(s) to determine yields. In some embodiments, a volume measurement unit **2000** utilizes the pipetting system and a fluid sensor in a dedicated vessel, *e.g.*, as shown in **Figures 20A-20E**. For example:

- **Figure 20A** shows an empty cuvette **2060** in a detector head **2002**, wherein light from two IR emitters **2010** does not pass through the cuvette **2060**, and is received by two IR receivers **2020** for reflected light.
- When a fluid **2040** to be measured is pooled in the volumetric cuvette **2060**, *e.g.*, as shown in **Figure 20B**, light from the two IR emitters **2010** is transmitted through the cuvette **2060** and the fluid **2040** and is not received by the two IR receivers **2020** for reflected light.
- While a control system monitors the presence of the fluid detected by the system **2000** at the bottom of the measurement vessel **2060**, the pipette head **220** is used to aspirate the sample **2040** into a pipette tip **651** as shown in **Figure 20C**.
- As shown in **Figure 20D**, when the sensor system **2000** reports fluid absent, the syringe pump **350** (**Figure 3**) can be stopped and the volume aspirated can be electronically determined and recorded. Thus, the cuvette **2060** has a prism design in the bottom. Using a light source with detectors the instrument can determine the presence or absence of liquid in the cuvette **2060** based on the reflection. This, in combination

with the pipetting device determines the volume by measuring the liquid it is removing until receiving the signal that no liquid is present. **Figure 20E** illustrates that the system **2000** can employ a plurality of spaced apart detector blocks **2002**, each having its own pair of transmitters **2010**. Each block **2002** can be configured to hold and cooperate with a respective cuvette **2060** for obtaining a volume measurement using the volume measurement system **2000**.

[0177] As shown in **Figure 20F**, the tray **14** can include a plurality of both the volume cuvettes **2060** (*e.g.*, volume measurement cuvette) and a plurality of spectrophotometer cuvettes **660** (the cuvettes **660** can be used for concentration measurements). The spectrophotometer cuvette **660** can be a standard UV visible plastic disposable such as BioRad "trUView cuvettes". The device **10** can include spectrophotometer components for measurements. Suitable spectrophotometer components can be obtained from Ocean Optics, having a place of business at Dunedin, Florida.

Exemplary Process Constituent Storage Systems

[0178] In some embodiments, reagent vessels are used to contain the reagents, the sample and mixing volumes of fluid combinations within the isolation container **12**. Reagent vessels with various different capacities may be used to accommodate the range of fluid volumes used during the process.

[0179] To reduce the risk of reagent contamination, evaporation or spillage, each vessel that contains reagent can be sealed, typically over a top surface, such as with polypropylene-lined foil, prior to loading into the tray **14**. The seal can be configured to be pierced by a pipette tip **651**. The seal allows reagents to be loaded and sealed into the appropriate reagent vessel and stored without the risk of contamination, spillage or evaporation.

[0180] An example of a reagent rack **620** is shown in **Figure 21A**. Rack **620** may have any desired layout, can accommodate any reagent vessel size, and can be adapted for any process. In the example shown, the reagent tray or rack **620** includes a base **2100** for housing a number of vessels **2110**, **2112**, **2114**, typically

tubes, of different sizes that may contain for example sample and reagents, as well as mixing vessels. Each of the vessels can be supported within the base **2100**, and a cover **2120** may be clipped or otherwise attached onto the rack **620** to ensure the vessels are kept securely in place. The cover **2120** includes apertures to allow the pipette tip to access the vessels held thereunder.

[0181] In some embodiments, reagents, samples, or other fluids can be loaded into the rack **620** as a sub-assembly, and the rack **620** is then loaded into the tray **14**. In some embodiments, the design of the reagent rack **620** is such that it can only be placed into the isolation container tray in one orientation. Alternatively, the reagent rack **620** may be molded or otherwise made an integral part of the isolation container tray **14**. Reagents may be loaded directly into an integral reagent tray or tubes or other vessels containing a reagent may be placed in the reagent tray. The placement of the vessels **2110**, **2112**, **2114** at a defined rack location (address) allows the robotic interface to automatically engage the correct vessel (reagent) at the correct time in the process.

[0182] In some embodiments, the tray layout allows access to all the vessels without the pipette tip having to pass over other dissimilar reagents, and thus reduces the chance of reagent cross contamination. Of course, other configurations may be used, for example, depending upon the desired processes to be performed.

[0183] **Figure 21B** illustrates that a multi-point (shown as a three-point) piercing sequence can be used to open the seal on a vessel **2110**, **2112**, **2114**, respectively, before withdrawing the (reagent) liquid. That is, the pipette **651** can be directed to pierce a seal covering at two outer locations before moving to the actual withdraw piercing (typically at a center location) to facilitate pipetting accuracy.

Exemplary Aliquot Removal Systems

[0184] During automated processing in system **10**, one or more aliquots of a sample and/or products may be used for process evaluation, control, quality

testing and/or storage for further processing (*e.g.*, *see* aliquots tubes 440 in **Figures 4 and 5**).

[0185] In some embodiments, the isolation container 12 and processing system 10 allow aliquot removal during processing without compromising the sealed nature of the isolation container 12. A plurality of flexible tubes can be in fluid communication with an interior sample capture region of the container 12 and extend from the system 10 to be externally accessible by an operator. Each flexible tube is presealed or has a closed end portion. Each aliquot may be aspirated into an individually labeled container 440, for example a tube, while the container 12 remains closed. An operator or an automated sealer may seal the aliquot into the tube 440, *e.g.*, upstream of the captured aliquot of fluid, such as by using an RF tube sealer, or other seal closure mechanism. Once sealed, an aliquot tube can be detached from the isolation container and taken away for storage, testing, or further processing.

[0186] In some embodiments, an aliquot assembly 40 is used for aspirating the aliquot fluid into the tube 440 and utilizes a clamping member and the elasticity of aliquot tubing 440 to draw the fluid from inside the container 12 into the tube. This mechanism can be automated to facilitate the tubing being clamped for a short time, thus reducing the likelihood of any change in the elasticity of the tubing caused by clamping deformation.

[0187] **Figure 22** illustrates an exemplary method 2200 of using an aliquot assembly 40, and shows a series of steps (from left to right and top to bottom) that can be used to load the aliquot tubes 440 with an aliquot fluid 445. As shown, an aliquot tube 440 with a closed end 441 is sealably attached to the tray 14 under a well 14w. In this example, a clamping member (tube expressor) 2210 is pressed against one or more aliquot tubes 440 to expel air from the tubes (as shown by the second and third figures). After or while air is discharged in response to the tube being completely compressed by clamp 2210 (with upper clamping member 2211 forced down against the tube and other clamp surface), the aliquot substance 445 is placed or dispensed in the well 14w in communication with the tube 440. Upon subsequent release of the clamping force, an aliquot of fluid 445 is drawn into the tube 440 by a negative pressure within the elastic tube. A tube sealer 2220

(such as an RF welder) may be used to seal (at **442**) and optionally cut the aliquot tube upstream of the seal to isolate the sample **445** within the tube. Other sealant mechanisms may also be used.

Exemplary Methods of Assembling a Container

[0188] **Figure 23A** is an exploded representation of a kit **2500** that can be provided to allow an operator to prepare a closed system for processing. The kit **2500** can include the tray **14**, the binding manifold **50**, the pipette tip rack **650** (and pipette tips **651**), and cuvettes **2060**, **660**. The tray **14** can be packaged and shipped to a use site with the aliquot tubes **440** attached and/or the vacuum head and associated tubing attached. The components can be sterilized and packaged (or packaged, then sterilized) in a sterile package for shipment and handling. The components may be surface sterilized at a point of use and the assembly of the components may be in a Class 10,000, 1000, or even 100 clean room. The components may also be provided separately or preloaded in other combinations.

[0189] **Figure 23B** is a partially assembled view of the kit shown in **Figure 23A**. **Figure 23C** is a bottom view of the partially assembled kit shown in **Figure 23B**. **Figure 23D** is a top view of the container **14** shown in **Figure 23A** prior to assembly of the discrete components shipped with or separate from the container or tray **14**.

[0190] **Figure 24** illustrates an exemplary method of sealing, respectively, an isolation container **12** according to embodiments of the invention (for example, for aseptic processing nucleic acids from one or more biological samples). For such aseptic processing, the barrier **16** and tray **14** sections of the isolation container assembly **12** may be individually pre-packaged and sterilized. When the isolation container **12** is needed for processing, the tray **14** and barrier **16** may be transferred to a biological safety cabinet or equivalent clean, controlled area for loading.

[0191] As shown in **Figure 23A**, the tray **14** of an isolation container **12** may be loaded with one or more reagent trays **620** comprising samples and reagents to be used in the desired process. The assembly and/or loading of the tray **14** can

take place with the tray **14** on the trolley **399** (**Figure 27**) as discussed above. One or more pipette tip racks **650** and binding column manifolds **50** may also be loaded into the working area **18** of the tray **14**. In some embodiments, one or more cuvettes **660**, **2060** are attached to the base of tray, for example, as shown in **Figure 20F**. Depending upon the desired assay or process to be performed, other samples, analytes, reagents, vessels, other consumables, devices, tools and/or other items may be loaded into tray **14**.

[0192] In some embodiments, after all of the desired items are placed within or attached to the tray **14**, the barrier **16** can be attached to the tray **14** to seal the assembled isolation container **12**, for example as shown in **Figure 24**. In some embodiments, an O-ring **2400** may be used to seal the flexible barrier **16** to the tray **14**. The O-ring can be forced snugly over the barrier **16** and into the perimeter slot on the tray **14**. In other embodiments, one or more gaskets, clips, clamps, fasteners, adhesives, and/or other attachment means may be used.

[0193] As shown in **Figure 27**, the tray **14** can be locked to a holding surface on a trolley during transport. After the tray **14** is loaded and sealed with the barrier **16**, the isolation container **12** may then be transferred to the work surface **200** of the processing system **10**. Alternatively, the isolation container can be assembled and sterilized. Then, reagents and samples can be introduced into a sealed isolation container using standard aseptic transfer methods or by other closed means. The trolley can also be used to hold the tray **14** during assembly. Alternatively, a separate barrier isolator trolley-assembly cart may be used when assembling the isolation container **12** (not shown). Such a barrier isolator trolley may be integrated into the barrier isolator itself and can mate with the transport trolley as discussed above.

[0194] The isolation container assembly **12** may be installed into the system **10** and connected to each piece of equipment used for processing the samples. To ensure correct alignment, the rigid tray **14** may be clamped onto the work surface **200**. The flexible barrier **16** and pipette head **220** may connect to the robotic pipette head adapter **210** (*see e.g.*, **Figure 2**). As shown for example, in **Figure 12**, thermal cycler evaporative seal **430** may connect to the thermal cycler lid **1010**, *e.g.*, using vacuum cups **1140** or other fasteners or attachment means, and

vacuum tubing and the disposable pump head for the waste and elution stations are fitted to the corresponding valves and pump. To remove an isolation container, the reverse procedure may be used.

[0195] **Figure 25** is a flow chart of operations that can be carried out at a manufacturing site according to embodiments of the invention. As shown, an input sample **3000** is provided (typically from a patient collection site or a subject's specimen storage site). When time-sensitive, the specimen can be shipped for receipt at the manufacturing site within 12-48 hours (such as overnight). At the manufacturing site, the isolation container **12** is prepared in a barrier isolator (block **3010**) and sample may also be prepared (block **3000p**) prior to placement in the container (*e.g.*, homogenized, mixed and/or centrifuged). The outer packaging of the isolation container components, *e.g.*, the tray **14**, the barrier **16** and the container contents can be sterilized (block **3002**). The assembled and sealed isolation container can be assembled (block **3004**) and integrity-tested (block **3006**) to confirm a sealed state.

[0196] The closed assembled isolation container can be moved to the instrument for processing (block **3020**). As shown, the RNA from the patient sample can be isolated (block **3022**) using silica membrane columns and appropriate RNA binding and elution reagents. Concentration and volume determinations are performed out to calculate yields and the concentration is normalized (block **3024**). The cDNA is synthesized by a reverse transcription (RT) reaction, amplified through PCR, and purified (block **3026**) using silica membrane columns and appropriate cDNA binding and elution reagents. Concentration and volume determinations are performed to calculate yield and the concentration is normalized (block **3028**). IVT RNA is produced from the resulting cDNA, treated with DNase and purified (block **3030**) using silica membrane columns and appropriate RNA binding and elution reagents. Concentration and volume determinations are performed to calculate yield and the concentration is normalized (block **3032**) resulting in the final amplified RNA (block **3034**). The RNA disposable can be integrity-checked (block **3036**) to confirm that the system is still sealed and isolated from the environment to thereby ensure that there was no

contamination during the process. Intermediate and/or final products can be output as one or more aliquot amounts (block 3050).

[0197] **Figures 29A-29C** show an exemplary elution tray **1610**. As shown, the receptacles **1612** are spaced apart and angled to inhibit splash-over during use of a respective receptacle **1612**. Two or more receptacles **1612** reside on each side of an upwardly extending barrier **1614** and the primary tubular receiving portion **1615** merges into a shallow channel **1616** that tapers downwardly and becomes deeper and narrower as it moves toward the tubular body portion **1615**. The forward portion of the channel **1616** is also tapered inwardly and downwardly to capture splash and to direct the liquid to flow to the primary tubular portion **1615**.

[0198] **Figures 30A-30B** illustrate a similar configuration for the waste tray cover **1640** but the tips **1632** of the receptacles are open or have apertures for draining the waste to the waste station **632** (**Figure 16**).

[0199] **Figure 31** is a schematic illustration of a control circuit **4000** that is in communication with sensors **4010**, **4020**, **4030** that can be used to monitor the status of the inside of the container or provide desired feedback to allow the automatic control of components (heaters, coolers, robotic arm movement and the like). As shown, the control circuit **4000** can be in communication with the user interface **61** (**Figure 1**). The sensors can include a load sensor **4010**, a temperature sensor **4020**, and a pressure sensor **4030**. The load sensor **4010** can be in communication with the new pipette rack to provide loading force data used to control the engagement force applied by the robotic arm to engage a new pipette. The temperature sensor **4020** can provide temperature data regarding the internal environment or a particular location within the closed container environment (*e.g.*, one or more of the workstations). The pressure sensor **4030** can be used to monitor the sealed integrity status of the closed environment and/or vacuum during isolation or purification procedures. Multiple sensors of each or some of the sensors can be used and other sensors may also be used. The control circuit **4000** may reside wholly or partially in the system **10** or wholly or partially with or on the container **12**.

[0200] As will be appreciated by one of skill in the art, embodiments of the invention may be embodied as a method, system, data processing system, or computer program product. Accordingly, the present invention may take the form of an entirely software embodiment or an embodiment combining software and hardware aspects, all generally referred to herein as a "circuit" or "module." Furthermore, the present invention may take the form of or use a computer program product on a computer-usable storage medium having computer-usable program code embodied in the medium. Any suitable computer readable medium may be utilized including hard disks, CD-ROMs, optical storage devices, a transmission media such as those supporting the Internet or an intranet, or magnetic or other electronic storage devices.

[0201] Computer program code for carrying out operations of the present invention may be written in PLC code such as Graph, Ladder or SCL. However, the computer code can be alternatively or additionally written in an object oriented programming language such as Java, Smalltalk or C++ and/or conventional procedural programming languages, such as the "C" programming language or in a visually oriented programming environment, such as VisualBasic.

[0202] Certain portions (or all) of the program code may execute entirely on one or more of the system's computer(s), partly on the system computer(s), as a stand-alone software package, partly on the system computer(s) and partly on a remote computer or entirely on the remote computer. In the latter scenario, the remote computer may be connected to the system computer through a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider). In some embodiments, some program code may execute on local computers and some program code may execute on one or more local and/or remote server. The communication can be done in real time or near real time or off-line using a volume data set provided from the imaging modality.

[0203] The invention is described in part with reference to flowchart illustrations and/or block diagrams of methods, systems, computer program products and data and/or system architecture structures according to embodiments of the invention. It will be understood that each block of the illustrations, and/or

combinations of blocks, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general-purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the block or blocks.

[0204] These computer program instructions may also be stored in a computer-readable memory or storage that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory or storage produce an article of manufacture including instruction means which implement the function/act specified in the block or blocks.

[0205] The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions/acts specified in the block or blocks.

[0206] As illustrated in **Figure 32**, embodiments of the invention may be configured as a data processing system **4116**, which can be used to carry out or direct operations of the rendering, and can include a processor circuit **4100**, a memory **4136** and input/output circuits **4146**. The data processing system may be incorporated in, for example, one or more of a programmable logic controller (PLC), personal computer, workstation, server, router or the like. The system **4116** can reside on one machine or between a plurality of machines. The processor **4100** communicates with the memory **4136** via an address/data bus **4148** and communicates with the input/output circuits **4146** via an address/data bus **4149**. The input/output circuits **4146** can be used to transfer information between the memory (memory and/or storage media) **4136** and another computer system or a network using, for example, an Internet protocol (IP) connection. These components may be conventional components such as those used in many

conventional data processing systems, which may be configured to operate as described herein.

[0207] In particular, the processor **4100** can be commercially available or custom microprocessor, microcontroller, digital signal processor or the like. The memory **4136** may include any memory devices and/or storage media containing the software and data used to implement the functionality circuits or modules used in accordance with embodiments of the present invention. The memory **4136** can include, but is not limited to, the following types of devices: ROM, PROM, EPROM, EEPROM, flash memory, SRAM, DRAM and magnetic disk. In some embodiments of the present invention, the memory **4136** may be a content addressable memory (CAM).

[0208] As further illustrated in **Figure 32**, the memory (and/or storage media) **4136** may include several categories of software and data used in the data processing system: an operating system **4152**; application programs **4154**; input/output device drivers **4158**; and data **4156**. As will be appreciated by those of skill in the art, the operating system **4152** may be any operating system suitable for use with a data processing system, such as IBM®, OS/2®, AIX® or zOS® operating systems or Microsoft® Windows®95, Windows98, Windows2000, WindowsXP or WindowsCE operating systems, Unix or Linux™. IBM, OS/2, AIX and zOS are trademarks of International Business Machines Corporation in the United States, other countries, or both while Linux is a trademark of Linus Torvalds in the United States, other countries, or both. Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both. The input/output device drivers **4158** typically include software routines accessed through the operating system **4152** by the application programs **4154** to communicate with devices such as the input/output circuits **4146** and certain memory **4136** components. The application programs **4154** are illustrative of the programs that implement the various features of the circuits and modules according to some embodiments of the present invention. Finally, the data **4156** represents the static and dynamic data used by the application programs **4154** the operating system **4152** the input/output device drivers **4158** and other software programs that may reside in the memory **4136**.

[0209] The data **4156** may include (substantially real-time, archived or stored) Process Sequence data sets **4126** and/or closed environment sensor feedback data **4127**. As further illustrated in **Figure 32**, according to some embodiments of the present invention application programs **4154** include an Automated Process Sequence and Monitoring Module **4125**. The application program **4154** may be located in a local server (or processor) and/or database or a remote server (or processor) and/or database, or combinations of local and remote databases and/or servers.

[0210] While the present invention is illustrated with reference to the application programs **4154** in **Figure 32**, as will be appreciated by those of skill in the art, other configurations fall within the scope of the present invention. For example, rather than being application programs **4154**, these circuits and modules may also be incorporated into the operating system **4152** or other such logical division of the data processing system. Furthermore, while the application program **4154** is illustrated in a single data processing system, as will be appreciated by those of skill in the art, such functionality may be distributed across one or more data processing systems in, for example, the type of client/server arrangement described above. Thus, the present invention should not be construed as limited to the configurations illustrated in **Figure 32**, as it may be provided by other arrangements and/or divisions of functions between data processing systems. For example, although **Figure 32** is illustrated as having various circuits and modules, one or more of these circuits or modules may be combined or separated without departing from the scope of the present invention.

Other Embodiments

[0211] The foregoing exemplary system **10** was provided to illustrate various aspects and features of the present invention, and is not intended to limit the scope of the present invention to systems, devices and methods for nucleic acid processing. Rather, one skilled in the art will appreciate that various other applications fall within the scope of the present invention, including, for example, systems and methods for fabricating, assembling, processing or otherwise

manipulating any items, typically in a closed container. The following sections provide additional examples of applications in which the apparatus and methods of the present invention may be employed.

Examples of Other Biological and/or Pharmaceutical Applications

[0212] In other aspects, the present invention provides methods of transferring a material, for example, a fluid, from a source to a target in a closed environment, wherein the closed environment is defined as the interior region or chamber in the container of an apparatus as described in the present application. A fluid to be transferred can contain, for example, a biologic; drug; toxin; isolate; radioisotope; virus; bacteria; eukaryotic cell; extract; analyte; biological specimen such as, for example, blood, plasma, saliva, etc.; vaccine; nucleic acid; protein; foodstuff; and the like, including suspensions, mixtures, and so on, thereof.

[0213] Applications for the instant systems and methods can be found, for example, where contamination of the material to be transferred inside the closed environment is to be avoided by substances potentially in the environment outside of container. In certain embodiments, the systems and methods can be directed to preparation of materials for, or for processing materials in, diagnostic assays, such as, by way of non-limiting examples, sterility assays, forensic analyses, or quality control assays, for example, to test purity of biologics to be used in clinical applications. In other embodiments, the instant methods can be for the preparation or manufacture of drugs and biologics, such as vaccines, and nucleic acids for experimental and/or clinical use. Various assays and methodologies that may be suitable for use in the systems and methods of the present invention are known to those of skill in the art as described, for example, in United States Pharmacopeia, *United States Pharmacopeia and National Formulary (USP 29-NF 24)* (2006), U.S. Department of Health and Human Services, *Guidance for Industry: Sterile Drug Products Produced by Aseptic Processing—Current Good Manufacturing Practice* (September 2004), each of which is incorporated by reference herein in its entirety.

[0214] It will be understood by those skilled in the art that a target to which a fluid is transferred can be any receptacle, such as, for example, a tube, vial,

vessel, and the like, that is intended to hold the transferred fluid. In some embodiments, the target is a substrate, such as a binding column, size exclusion column, chromatography media, or filter, or the like. However, depending upon the particular application in the methods provided, any flow-through device, that is, any device intended to capture and/or separate and/or concentrate one or more components of the transferred fluid from another component of the fluid, can be used.

[0215] **Figure 14** provides an example of a configuration of an exemplary apparatus wherein binding columns **1410** situated in the closed environment are a target for transferred fluid containing, for example, nucleic acids. In other embodiments, the manifold described in **Figure 14** can be adapted to fit filters or other devices discussed above.

[0216] In some embodiments, systems and methods provided by the invention can allow for aseptic preparation of an amplified nucleic acid product, comprising the steps of isolating RNA from a cell extract and amplifying a nucleic acid product from at least one RNA molecule from the isolated RNA, wherein the isolating and amplifying steps are performed in a closed environment as defined as the interior region or chamber in the container of an apparatus as described in the present application, thereby aseptically preparing the amplified nucleic acid product.

[0217] In certain embodiments for the aseptic preparation of an amplified nucleic acid product, the amplified nucleic acid product is derived from a pathogen, such as from a viral pathogen. In certain embodiments, the amplified nucleic acid product is derived from human tumor RNA. An amplified nucleic acid product from a human tumor RNA can be used, for example, in the preparation of a vaccine or immunotherapy.

[0218] The instant methods can be used for the sterilization of a material, for example, a biologic as defined under Title 21 of the United States Code of Federal Regulations, nucleic acid, and/or protein, and so forth, under aseptic conditions. Guidelines regarding the preparation of such materials for clinical applications are described in, *e.g.*, U.S. Department of Health and Human

Services, Guidance for Industry: Sterile Drug Products Produced by Aseptic Processing—Current Good Manufacturing Practice (September 2004).

[0219] Thus, in certain embodiments, methods are provided for the sterilization of a material comprising transferring a fluid comprising the material from a source to a filter and collecting the material after passage through the filter into a receptacle, wherein the source, filter and receptacle are contained in a closed environment as defined as the interior chamber or region in the container of an apparatus as described in the present application. Filters for sterilization are commercially available, for example, from Whatman Inc. (Florham Park, NJ).

[0220] It will also be recognized that transferring material, for example, dispensing the material into a vial, can be hazardous if the material comprises a pathogen, such as is the HIV virus, or other certain microorganisms, or comprises a biological toxin or a radioactive substance. Transferring such materials into receptacles in a closed environment such as defined in embodiments of the present invention can be used to reduce the potential exposure of the hazardous material to the individuals undertaking the transfer. Thus, in certain embodiments, methods are provided wherein a hazardous material is transferred from a source to a target in a closed environment as in the container of an apparatus as described in the present application. These methods can be applied to a variety of procedures and assays where hazardous materials are transferred between a source and a target, as will be known to those of skill in the art.

[0221] The apparatus of the present invention can be used for other applications typical of protein purification, nucleic acid purification, and other molecular biology processes. Such applications include, but are not limited to, cell lysing (*e.g.*, mechanical, chaotropic, thermal, or enzymatic lysing of cells), macromolecule purification (*e.g.*, ion exchange, bead, molecular weight cutoff), and recovery (silica elution, bead elution, membrane elution).

Exemplary Lithography, Microfabrication and Related Applications

[0222] Embodiments of the present invention can be used in any situation where clean room conditions are used or isolation is desired, such as, for

example, lithography and assembly processes. In some embodiments, the apparatus of the present invention satisfy the conditions of a class 1, class 10, class 100, class 1000, class 10,000, or class 100,000 clean room as set forth by the U.S. Federal Standard 209b for clean room classification. *See*, Federal Standard No. 209B 1992, "Clean Room and Work Station Requirements, Controlled Environment," dated April 24, 1973, which is hereby incorporated by reference in its entirety. As such, embodiments of the present invention can be used for a broad spectrum of processes that use a clean room environment. Such processes include lithography processes such as, but not limited to, wafer patterning (also known as photomasking, masking, photolithography, microlithography), doping (*e.g.*, thermal diffusion, ion implantation), heat treatment (*e.g.*, thermal, radiation). Specific patterning processes that can be conducted in the apparatus of the present invention include, but are not limited to (i) resist application (positive or negative); (ii) exposure (*e.g.* by contact, proximity, scanning projection, and stepper) to high pressure mercury, X-rays, or E-beams; (iii) imaging (*e.g.*, single layer resist, multilayer resist, application of antireflector layers, off-axis illumination, planarization, contrast enhancement; and (iv) etch (*e.g.*, wet chemistry-liquid/vapor, dry, plasma, lift-off, ion milling, reactive ion etching). Specific heat treatment processes include, but are not limited to, hot plate, convection, rapid thermal processing (RTP), and infrared. More description of these lithography processes are described in Van Zant, *Microchip Fabrication*, Fourth Edition, Chapter 4, 2000, McGraw-Hill, New York, which is hereby incorporated by reference in its entirety.

[0223] In addition to conventional lithographic techniques, the apparatus of the present invention can be used to house next-generation lithographies such as extreme ultraviolet lithography, X-ray lithography (*e.g.*, LIGA), charged-particle-beam lithography (*e.g.*, electron-beam, ion-beam), scanning probe lithography (*e.g.*, scanning tunneling microscope lithography, atomic force microscope lithography, scanning electrochemical microscope lithography), soft lithography (*e.g.*, replica mold, micro-contact printing, micro-molding in capillaries, micro-transfer molding, solvent-assisted micromolding, near-field conformal photolithography using an elastomeric phase-shifting mask) and three-dimensional lithography (*e.g.*, holographic lithography, lithography on non-planar substrates). Such techniques

are described in Madou, *Fundamentals of Microfabrication*, Second Edition, 2002, CRC Press LLC Boca Raton, Florida, pp. 48-68, which is hereby incorporated herein by reference in its entirety.

[0224] Embodiments of the present invention can be used for protein patterning microlithographic techniques that address, for example, the problem of non-specific protein absorption competing for detection sites in immunosensors. See, for example, Clementi *et al.*, *Structure and Motion: Membranes, Nucleic Acids, and Proteins*, Adenine Press, Schenectady, New York, 1985, which is hereby incorporated herein by reference in its entirety.

[0225] Devices, systems, apparatus and methods of the present invention can be used to perform dry etching techniques such as physical etching (*e.g.*, ion etching, sputtering, ion-beam milling), plasma etching (*e.g.*, radical etching), physical/chemical etching, deep reactive ion etching, vapor-phase etching without plasma, dry etching, and single-crystal reactive etching metallization (SCREAM) as disclosed in Chapter 2 of Madou *Fundamentals of Microfabrication*, Second Edition, 2002, CRC Press LLC Boca Raton, Florida, which is hereby incorporated herein by reference in its entirety.

[0226] The apparatus of the present invention can be used to perform pattern transfer with additive techniques such as silicon growth, doping of silicon, oxidation of silicon, physical vapor diffusion (*e.g.*, thermal evaporation, sputtering, molecular beam epitaxy, laser sputter deposition, ablation deposition, ion plating, cluster beam technology), chemical vapor deposition, silk-screening (screen printing), sol-gel deposition, plasma spraying, spray pyrolysis, and plasma-beam deposition as disclosed in Chapter 3 of Madou *Fundamentals of Microfabrication*, Second Edition, 2002, CRC Press LLC Boca Raton, Florida, which is hereby incorporated herein by reference in its entirety.

[0227] Embodiments of the present invention may be particularly useful in deposition and arraying methods used in the BIOMEMS field, which encompasses techniques for depositing organic materials for chemical and biological sensors, often arranged in some type of array configuration. Such techniques can be used, for example, to make organic gas permeable membranes, ion selective membranes, hydrogels, organic monolayers needed for room-

temperature gas sensors, ion selective electrodes, enzyme sensors, immunosensors, and DNA and protein arrays. Specific techniques in the BIOMEMS field that can be implemented on the apparatus of the present invention are spin coating, dip coating, plastic spraying, casting, type casting, glow discharge (plasma) polymerization, Langmuir-Blogett processes, ink-jetting, microspotting, and mechanical microspotting, as disclosed in Madou *Fundamentals of Microfabrication*, Second Edition, pp. 159-167, 2002, CRC Press LLC Boca Raton, Florida, which is hereby incorporated herein by reference in its entirety.

[0228] Embodiments of the present invention can be used for other clean room applications, such as packaging of small devices (*e.g.*, integrated circuits). Specific packaging techniques that can be performed using the apparatus of the present invention include, but are not limited to, packaging of integrated circuits, dicing, cavity sealing and bonding, multi-chip packaging, and partitioning as disclosed in Madou *Fundamentals of Microfabrication*, Second Edition, pp. 478-508, 2002, CRC Press LLC Boca Raton, Florida, which is hereby incorporated herein by reference in its entirety.

[0229] Embodiments of the present invention can be used for application of photoresists in lithographic processes. For instance, the apparatus of the present invention can be used to apply either positive or negative photoresist to a substrate in a clean room environment. As such, steps such as resist spin coating, softbake, hardbake, development, post-exposure bake, and multi-layer resists processes can be performed in the apparatus of the present invention as described in Levinson, *Principles of Lithography*, SPIE Press, Bellingham, Washington, 2001, Chapter 3, which is hereby incorporated herein by reference in its entirety. The apparatus of the present invention can be used for lithographic processes such as optical lithography, electron beam lithography, x-ray lithography, deep-UV resist application, photomask fabrication, as well as metrology methods in photolithography as described in *Microlithography, Micromachining, and Microfabrication*, ed. Rai-Choudhury, SPIE Press, Bellingham, Washington, 2001, Chapters 1-6, which is hereby incorporated herein by reference in its entirety. The systems, devices, apparatus and methods of the present invention can further be used to implement methods used to fabricate photovoltaic cells, including but not

limited to phosphorous diffusion, edge isolation, ARC deposition, front-contact printing, back-contact printing, co-firing, testing and sorting, as disclosed in *Handbook of Photovoltaic Science and Engineering*, Luque and Gege du eds., John Wiley & Sons, West Sussex, England, 2003, pp. 271-279, which is hereby incorporated herein by reference in its entirety.

[0230] All references cited herein are incorporated herein by reference in their entirety to the same extent as if each individual publication or patent or patent application was specifically and individually indicated to be incorporated by reference in its entirety. However, the incorporated by reference documents are not to be used to narrow an interpretation of a claim element of the pending application or any patent issuing thereon.

[0231] While the foregoing description and drawings represent embodiments of the present invention, it will be understood that various additions, modifications and substitutions may be made therein without departing from the spirit and scope of the present invention as defined in the accompanying claims. In particular, it will be clear to those skilled in the art that the present invention may be embodied in other specific forms, structures, arrangements, proportions, and with other elements, materials, and components, without departing from the spirit or essential characteristics thereof. The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims, and not limited to the foregoing description.

Claims

1. An apparatus for manipulating items in a closed container, comprising:
a container having an interior region configured to hold a plurality of items to be manipulated;
a flexible barrier configured to sealably attach to the container, wherein the flexible barrier is sized and configured to enclose a workspace in the interior region of the container and has a center portion that merges into an outer perimeter portion, and wherein the center portion of the flexible barrier can move relative to the outer perimeter portion; and
a tool integrated with or within the flexible barrier, the tool having a first interface and a second interface, wherein the first interface is configured to attach to a robotic device on a first side of the barrier outside of the interior region of the container and the second interface is disposed within the interior region of the container under the flexible barrier and is configured to manipulate the items in the interior region when the flexible barrier is sealably attached to the container.
2. The apparatus of claim 1, wherein the plurality of items comprise nucleic acid samples, wherein the tool is attached to a center portion of the flexible barrier, and wherein the flexible barrier is sealably attached to the container with sufficient flexibility so that the center portion of the flexible barrier is able to translate in three dimensions and change in shape while an outer perimeter portion of the flexible barrier remains sealably attached to the container to allow the robotic device to move the tool so that the second interface within the interior region of the container travels between about 4-24 inches in a vertical direction and about a length and width of the container.
3. The apparatus of claim 1, wherein the tool comprises a component of a pipetting device.
4. The apparatus of claim 2, wherein the container further comprises a plurality of stations for processing the nucleic acid samples.

5. The apparatus of claim 4, further comprising a manifold configured to hold at least one nucleic acid binding column, the manifold configured to releasably engage the second interface of the tool to automatically move between at least two of said plurality of stations.

6. The apparatus of claim 5, wherein the manifold comprises a handle, and wherein the second interface is configured to engage the handle to move the manifold to and from at least two stations.

7. An apparatus for manipulating items in a closed container, comprising:
a container having an interior region configured to hold a plurality of items to be manipulated;
a flexible barrier configured to sealably attach to the container;
a tool integrated with or within the flexible barrier, the tool having a first interface and a second interface, wherein the first interface is configured to attach to a robotic device on a first side of the barrier outside of the interior region of the container and the second interface is disposed within the interior region of the container under the flexible barrier and configured to manipulate the items in the interior region when the flexible barrier is sealably attached to the container; and
a single-well or multi-well vessel sealed to a base of said container and designed to fit into a thermal block, wherein the vessel is accessible from the interior region of the container.

8. The apparatus of claim 7, wherein the container further comprises a flexible seal sealably coupled to a sidewall of the container and extending over an aperture in the sidewall defining closed flexible side entry channel, the flexible side entry channel dimensioned to allow a lid to reciprocate in and out of the aperture in the sidewall inside the flexible seal and to travel vertically to close over and cover the vessel, whereby the flexible seal allows the lid to travel in and out of the interior

region of the container while maintaining a closed environment within the container.

9. The apparatus of claim 1, wherein the container and flexible barrier define a closed system, the apparatus further comprising a plurality of aliquot tubes extending outwardly from the container and being in fluid communication with the interior region of the container, the plurality of aliquot tubes configured to receive processed fluid samples.

10. The apparatus of claim 3, wherein the pipetting device comprises:
a pipette tip adapter for releasably engaging pipette tips stored within the container;

a working fluid chamber for communicating with a fluid pump outside of the sealed closed system container; and

a diaphragm or a filter for isolating the working fluid chamber from the pipette tip adapter and for transmitting pressure from the fluid pump to the pipette tip adapter.

11. The apparatus of claim 1, wherein the container comprises sidewalls that angle down to a base, wherein the apparatus further comprises a spectrophotometer for quantifying a sample, wherein the container comprises a connector for sealing a cuvette to the base of the container, said cuvette configured to hold the sample to be quantified by the spectrophotometer.

12. The apparatus of claim 1, further comprising a recirculating vacuum system configured to circulate air sealed within the interior region of the container in a closed loop when the flexible barrier is sealed to the container.

13. The apparatus of claim 1, wherein the vacuum system comprises a single-use disposable vacuum head and flexible tubing.

14. The apparatus of claim 13, further comprising at least one heat exchange device for controlling humidity and/or vapor concentration within the sealed container.

15. The apparatus of claim 1, wherein the container and the barrier are single-use disposable, the apparatus further comprising a robotic arm, wherein the robotic arm is the robotic device attached to the first interface, and wherein the robotic arm is configured to move a pipette tip held by the first interface inside the sealed container space to take on a downwardly angled non-vertical orientation with a lower portion of the tip positioned proximate a receiving surface of a receiving vessel in the closed container.

16. The apparatus of claim 9, wherein the processed fluid is discharged from the container while the container remains sealed without impacting the closed status of the closed system, and wherein the container and barrier remain sealed during and after use to define a closed-system disposable.

17. The apparatus of claim 1, further comprising a pressure sensor in communication with the closed container and a control circuit in communication with the pressure sensor configured to monitor pressure in the closed container to verify seal integrity.

18. The apparatus of claim 1, further comprising a system for measuring volume of a fluid, comprising:

at least one emitter configured to project a signal toward a predetermined position of a sample container held inside the barrier-sealed container;

at least one receiver configured to receive the signal after the signal interacts with the sample container, wherein a change in the signal received by the receiver indicates when the fluid has dropped below said predetermined position; and

a fluid transfer device in communication with the receiver and sample container,

wherein the fluid transfer device determines the volume of fluid that it has removed from the sample container when the receiver detects that the fluid has dropped below said predetermined position.

19. The apparatus of claim 18, wherein the emitter is a light emitter and the signal comprises light.

20. The apparatus of claim 18, wherein the fluid transfer device comprises at least a portion of a pipette.

21. The apparatus of claim 18, wherein the sample container comprises a cuvette.

22. The apparatus of claim 21, further comprising a plurality of sample containers held in the barrier-sealed container that are serially in communication with the emitter.

23. The apparatus of claim 1, further comprising an apparatus for measuring volume of a fluid, comprising:

at least one light source for emitting light;

at least one receiver for receiving light from the light source;

a cuvette held by the container through which a change in the light path dependent upon whether the cuvette contains fluid or is empty can be detected; and

a fluid transfer device in communication with the receiver to determine the volume of fluid that has been removed from the cuvette when the receiver detects that the cuvette is empty.

24. The apparatus of claim 23, wherein the fluid transfer device comprises at least a portion of a pipette.

25. The apparatus of claim 1, wherein the flexible barrier is substantially impermeable.

26. The apparatus of claim 4, wherein one of the stations hold a PCR plate, another of the stations holds a pipette rack with pipette tips, and another of the stations holds a tray of sealed reagent vessels.

27. The apparatus of claim 1, wherein the flexible barrier outer perimeter portion has an outer edge portion configured to seal to an upper perimeter portion of an upwardly extending sidewall of the container to define a sealed closed interior chamber, wherein the flexible barrier comprises an elastomer and is sealably attached to the first interface at the center portion of the barrier.

28. The barrier of claim 27, wherein the flexible barrier comprises a plurality of radial pleats.

29. The barrier of claim 27, wherein the flexible barrier comprises a plurality of substantially vertically oriented stepped portions.

30. The apparatus of claim 1, wherein the container has an upwardly extending sidewall, and wherein the tool inside the workspace has an outwardly extending lever configured to contact the sidewall, whereby contact with the sidewall forces the lever to pivot and release a respective used pipette tip held by the tool under the flexible barrier.

31. The system of claim 30, further comprising a pipette tip rack held in the interior region of the container, and wherein the container has a base which holds the pipette tip rack in a substantially horizontal orientation, wherein the sidewall angles down to the base and the pipette tip rack resides below and adjacent the angled sidewall.

32. The system of claim 30, further comprising a pipette tip rack held in the container interior region and a load sensor in communication with the pipette tip rack, wherein the tool is configured to advance to exert between about a 5N-50N load against a target pipette tip to engage a respective pipette tip held by the pipette tip rack.

33. The apparatus of claim 1, wherein the plurality of items to be manipulated include pipette tips held in the interior region of the container, wherein the container interior region holds a plurality of spaced apart vessels, wherein the tool second interface is configured to releasably engage a respective pipette tip and automatically translate to pierce a cover on a selected vessel a plurality of times in different spaced apart locations before withdrawing fluid from the vessel through one of the pierced openings in the cover.

34. An apparatus for manipulating items in a closed container, comprising:
a container having an interior region configured to hold a plurality of items to be manipulated, wherein the plurality of items comprise nucleic acid samples, and wherein the container further comprises (i) a plurality of stations in the interior region for processing the nucleic acid samples including an elution station and a waste station and (ii) a manifold with a handle, the manifold configured to hold at least one nucleic acid binding column, the manifold configured to move between at least two of said plurality of stations;

a flexible barrier configured to sealably attach to the container; and

a tool integrated with or within the flexible barrier, the tool having a first interface and a second interface, wherein the first interface is configured to attach to a robotic device on a first side of the barrier outside of the interior region of the container and the second interface is disposed within the interior region of the container under the flexible barrier and configured to manipulate the items in the interior region when the flexible barrier is sealably attached to the container,

wherein the second interface is configured to engage the manifold handle to move the manifold to and from at least two stations;

wherein the tool is attached to a center portion of the flexible barrier, and wherein the flexible barrier is sealably attached to the container with sufficient flexibility to allow the robotic device to move the tool within the interior region of the container between about 4-24 inches in a vertical direction and about a length and width of the container.

35. An apparatus for manipulating items in a closed container, comprising:
a container having an interior region configured to hold a plurality of items to be manipulated, wherein the plurality of items comprise nucleic acid samples, and wherein the container further comprises a plurality of stations in the interior region for processing the nucleic acid samples, wherein at least one of the stations comprises a reagent station;

a flexible barrier configured to sealably attach to the container; and

a tool integrated with or within the flexible barrier, the tool having a first interface and a second interface, wherein the first interface is configured to attach to a robotic device on a first side of the barrier outside of the interior region of the container and the second interface is disposed within the interior region of the container under the flexible barrier and configured to manipulate the items in the interior region when the flexible barrier is sealably attached to the container, wherein the second interface is configured to engage the manifold handle to move the manifold to and from at least two stations;

wherein the tool is attached to a center portion of the flexible barrier, and wherein the flexible barrier is sealably attached to the container with sufficient flexibility to allow the robotic device to move the tool within the interior region of the container between about 4-24 inches in a vertical direction and about a length and width of the container.

36. The apparatus of claim 35, further comprising a reagent rack disposed within the reagent station, the reagent rack holding a plurality of reagents for processing the nucleic acid samples.

37. The apparatus of claim 8, further comprising a drive member with an automated drive system for automatically moving the lid in and out of the sidewall aperture of the container while held in the flexible seal.

38. The apparatus of claim 9, further comprising an aliquot tube expressor for drawing the plurality of processed samples into the plurality of aliquot tubes.

39. The apparatus of claim 38, wherein the aliquot tube expressor comprises a tube sealer to seal one or more of the plurality of aliquot tubes.

40. The apparatus of claim 1, further comprising a housing with a work surface having a container position guide, the apparatus further comprising a trolley configured to hold a container with the flexible barrier, then allow an operator to align the trolley with the housing to slidably transfer the closed container to proper operative position on the work surface using the container position guide.

41. The apparatus of claim 40, wherein the work surface container position guide comprises spaced apart slots, and wherein the trolley comprises corresponding slots that align with the slots on the work surface, whereby the closed container can be slidably transferred from the trolley to the work surface into proper operative position.

42. The apparatus of claim 40, further comprising a spring-biased member that pushes against the closed container on the work surface to force the closed container to a desired operative position under a robotic arm associated with the robotic device.

43. The apparatus of Claim 1, further comprising a robotic arm, wherein the robotic arm is the robotic device attached to the tool first interface, wherein the robotic arm resides outside the closed workspace.

44. An apparatus for manipulating items in a closed container, comprising:
a container having an outer wall surrounding an interior region configured to hold a plurality of items to be manipulated;

a flexible barrier defining a cover having an outer perimeter portion and a medial portion, wherein the flexible barrier outer perimeter portion is sealably attached to the container outer wall to enclose a sealed closed container workspace in the interior region of the container; and

a tool sealably attached to a medial portion of the flexible barrier, the tool having a first interface and a second interface, wherein the first interface is configured to attach to a robotic device on a first side of the barrier outside of the interior region of the container and the second interface is disposed within the interior region of the container under the flexible barrier and is configured to manipulate the items in the interior region when the flexible barrier is sealably attached to the container,

wherein the medial portion of the flexible barrier is able to translate in three dimensions and move relative to the outer portion of the flexible barrier while the outer portion of the flexible barrier remains sealably attached to the container to allow the robotic device to move the tool in a vertical direction and about a length and width of the container.

45. The apparatus of Claim 44, further comprising a robotic device attached to the tool first interface configured to move the tool in three-dimensions in the interior region of the container, wherein the container comprises an upper portion with a circular open space defined by a downwardly extending concave sidewall that merges into a lower substantially planar base, and wherein the flexible barrier resides over the container upper portion and is sealably attached to the upper portion of the container.