

Description

THIS INVENTION relates to the construction of walls, revetments, roads, suspended floor spans and the like. In particular, it is directed to a set of construction implements and the use thereof in a general method of construction which is of use in a number of areas.

When constructing a new building or the like, it is nearly always necessary to first excavate the ground upon which the building is to be erected so that the required footings can be constructed. The usual procedure is to excavate a suitable hole in the ground. The walls of this hole require support so that they will not collapse while the footings are constructed. This support is especially required when constructing a building very close to an existing building. In the absence of a suitable support, the foundations of the existing building may at least move or, at worse, collapse into the adjacent excavation.

For the deep excavations necessary for modern tall buildings such as office blocks and hotels, it is often a requirement that the ground be excavated to a depth of at least six metres. Further, to prevent any movement of adjacent buildings, it is often a requirement that the retaining wall(s) be constructed below ground level before any excavation is undertaken.

Similarly, when constructing a new dam, it is often necessary to provide some form of retaining wall around the dam site to prevent passage of the soil etc into the body of water as the dam fills and, also, to retain the body of water itself in the designated area.

Traditionally, such retaining walls have been constructed by the technique of "piling" wherein interlocking piles, each pile being approximately 0.33 m wide and up to 6 m long, are driven (by the repetitive application of a large impact force) into the ground to form a wall of the required width. This method is time consuming and expensive as a large number of piles have to be first driven into the ground and subsequently removed after the building foundations, walls etc have been constructed. Further, the bulk of the piles and the equipment necessary to first support and then drive them into the ground prevents a below-ground retaining wall from being built extremely close to an existing wall of a building or the like. In addition, the large force necessary (eg from an impact driver) to drive the piles into the ground results in shock waves through the ground which can damage the foundations of an adjacent existing building.

One alternative method that has been tried is to replace the afore-mentioned piles with sheets of metal. These sheets of metal, which are substan-

tially wider than the piles, are also driven into the ground. However, although this alternative method reduces the time required to erect a retaining wall of given length, it is still necessary to remove the sheets after the building foundations, walls etc have been constructed as the sheets are too expensive to be used once only and thus left in the ground for all time. Further, the gauge of these sheets are such that, to position these sheets, it still requires the above mentioned traditional bulky equipment and the application of large impact forces with their attendant problems.

A modification of this known technique is first to drive a preliminary ramming plate of relatively heavy gauge into the ground which is then withdrawn and a second plate - of lesser gauge - is then inserted into the "slot" thus created.

Although this modified method (which uses a lesser gauge and thus cheaper to manufacture sheet) allows the second plate to remain in the ground for all time, it is essential always to create the "slot" before the actual second plate can be inserted into the ground. Thus the time to erect a retaining wall is not significantly reduced and the ramming of the first plate into the ground still involves large impact forces with their accompanying problems.

Other attempted modifications include the use of corrugated sheeting as described in, for example, US Patents Nos. 4,211,504 and 2,865,180, and Swiss Patent No. 542,327. One disadvantage of this prior art is that a differing profile of the sheeting is apparently required, dependent on its application.

When constructing a revetment, it is nearly always necessary first to drain the water from where the revetment is to be erected so that the required footings can be constructed. Alternatively, where draining is not practical (eg, on a foreshore), work on footings and the like can only be undertaken at low tide or by first diverting the flow of water away from the construction area.

The revetments are then traditionally constructed from rock or stone which is positioned where required, either dry-stacked or, if necessary, further held in position by cement or by placing a net-like structure (usually manufactured from metal) thereover. These methods are time consuming and expensive as they are labour intensive and, usually, the rock or stone has to be carted from an area remote from the revetment construction.

One alternative method that has been tried is to prepare the land where the revetment is required to provide the desired contour for the revetment, for example, by excavation or mounding with earth or rubble and placing thereover a double walled mattress which is then filled with concrete by pressure injection. This alternative method is still not

totally satisfactory as, for example, if excavation is required to set the desired contour, draining or diverting of water may still be required.

Further problems with the known prior art include (1) for the deep excavations necessary for modern tall buildings, the required retaining walls often have an exposed face which is of substantial depth and thus the ground pressure on the other side can be substantial and may cause these retaining walls to move inward away from the required angle under the influence of this pressure; and (2) similarly, when such walls or revetments are placed in soft soils such as sand or similar, particularly when wet, movement of the walls is likely.

Traditionally, such retaining walls have been anchored by using a concrete grout wherein a threaded hole is bored into the soil, concrete is then poured into the hole and metal cables are embedded therein. Once the concrete has cured, the metal cables are secured to the retaining wall to prevent movement thereof.

Disadvantages of this traditional method include (1) soil has to be removed before the concrete is poured in, requiring special drilling equipment; (2) several days are required for the concrete to cure before the grout can be used; (3) if insufficient grout is added to replace the removed soil, subsidence can occur of the surrounding area; (4) the drilling equipment is bulky and problems thus arise if the grout has to be placed near existing foundations of, for example, an adjacent building; (5) the anchoring system has to be "destressed" in due course; (failure to destress is highly likely to allow subsidence and other movement of the surrounding soil which could cause damage to the new construction and/or to adjacent buildings); and (6) a concrete grout is permanent, there being no reusable materials.

The above discussion has described existing problems associated with the construction of support walls which are to be erected in an essentially vertical position. However, "horizontal" supports of considerable strength are also required, for example, in large suspended floor spans such as those necessary in modern office and retail complexes and, particularly, in the construction of roads, bridges and the like.

The traditional bridge building material, timber, is now out of favour as its cost is increasing and supplies are becoming more difficult to obtain. Timber bridges also require significant regular maintenance. Accordingly, the repair and replacement of the decking of existing wooden bridges and the construction of new bridges now tends to be undertaken using alternative materials, most commonly reinforced concrete or steel sheets covered by some suitable load bearing material.

Although reinforced concrete is immensely strong and durable, large and thus expensive quantities are required if the concrete is to be the only supporting surface. Extensive formwork is also required to contain the concrete until it has set. Therefore, in an attempt to overcome this problem, steel decking has been utilised whereby profiled steel panels are first laid down and then covered with any suitable infill material. A typical example of such profiled steel panels is disclosed in Japanese Patent Application No. 59-245379. Fill materials vary from compacted earth to steel plates to structural grade concrete.

A disadvantage of this steel decking alternative is that the road surface is not load bearing until the infill material has been positioned. This usually necessitates the infill material to be positioned manually as the initial steel decking is not strong enough to support the large and heavy vehicles, such as concrete-containing vehicles, which deliver the material. The required manual distribution of the infill material is time consuming, labour intensive and thus relatively expensive.

It is a general object of the present invention to overcome, or at least ameliorate, one or more of the above problems and to provide construction methods which are suitable for a wide range of applications whereby substantial load bearing support is required in essentially any direction.

It has been discovered by the present inventors that, if the known sheets are replaced with sheets of a particular profile, the sheets thus profiled are immensely strong and can, for example, be positioned using less bulky equipment. If necessary, they can be positioned in the ground by the application of much lower driving forces and, further, can be produced economically enough to remain in the ground for all time if their removal is impractical. Also, the insertion of the sheets into the ground can be direct thus eliminating the need for any preliminary ramming plate to carve a "slot" for the sheets. Should conditions require, the sheets can be further tied to the ground by use of an anchor(s) also developed by the present inventors. In addition, the sheets can be positioned horizontally and, in this application, are ready for immediate use as they are sufficiently load bearing without further treatment.

Thus, according to a first aspect of the present invention, there is provided a method of constructing a load bearing surface such as a retaining wall, floor span, roadway or the like of the type having one or more inter-connected essentially quadrangular corrugated support sheets, each sheet of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:

(a) providing an adaptor also comprising an essentially quadrangular corrugated sheet having corrugations complementary to those of said sheet, said adaptor having means for temporary attachment to said sheet;

(b) using said adaptor to place said sheet into its required position; and

(c) removing said adaptor.

Preferably, the means to releasably attach the adaptor to the top of the support sheet comprises (a) two L-shaped brackets affixed so that said support sheet can be positioned between the planar sheet of the adaptor and each said bracket and (b) holes in said brackets and in said support sheet which are aligned when said adaptor is in use, allowing a bolt or similar to be passed through to connect said adaptor and said support sheet together.

Optionally, the support sheets can be coated with any suitable preservative composition to increase resistance to abrasion, water erosion, rusting etc.

In their application as part of, for example, a retaining wall, as the support sheets of the present invention are of a lesser gauge than the conventional prior art sheets, it has been found that a much lower driving force is necessary to drive the sheets into the ground. However, because of the lesser gauge and thus reduced rigidity of the sheets, there could be a tendency for the sheets to buckle under the driving force in certain circumstances, but this problem is overcome by use of the adaptor. It has been found that, by applying a vibrating force to the adaptor, the sheet can be driven almost to its full length into the ground. The adaptor is then removed and the sheet is driven to ground level, if required, by the aid of an attachment fitted between the sheet and the source of the vibrating force.

Preferably, said attachment comprises:

(a) an elongated member defining a channel of a width slightly greater than the depth of one of said ridges or said troughs; and

(b) means to releasably connect said elongated member to a source of a vibrating source; wherein each side of said channel is further adapted to comprise a short extension, each said extension comprising a corrugated sheet having corrugations complementary to those of said sheet.

Preferably, said elongated member is a channel of square C cross-section.

Although the number and position of the ridges and troughs on the sheets and adaptor may vary dependent on the application required, preferably, the support sheet and the adaptor each comprise a series of double folds (pleats) symmetrically placed along the full width of the respective sheets. More

preferably, each sheet and the adaptor are folded between five and seven times.

It has also been discovered by the present inventors that the support sheets as hereinbefore described and their method of use can be used to produce any required contour for any particular revetment. After the sheets have been positioned, if necessary, the soil or the like is excavated from the water side of the proposed revetment and a casing is overlaid onto the water side face of the sheet and the casing is filled with a suitable robust material.

Thus, as a second aspect of the present invention, there is provided a method of constructing a revetment of the type having one or more interconnected essentially quadrangular corrugated support sheets, each sheet of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:

(a) providing an adaptor also comprising an essentially quadrangular corrugated sheet having corrugations complementary to those of said sheet, said adaptor having means for temporary attachment to said sheet;

(b) using said adaptor to place said sheet into its required position;

(c) removing said adaptor;

(d) excavating any soil or the like that may be present from one face of said sheet;

(e) overlying a casing or the like on said one face, wherein said casing can be filled with a suitable robust material.

If necessary, after removing said adaptor, an attachment as hereinbefore described can be used to drive the support sheet to ground level.

Preferably, said casing is a double walled nylon mattress woven of multi-filament nylon wrap held together at intervals by filter points which remain free of the robust filling and are designed to relieve hydrostatic pressure.

Preferably, the robust material used as the filling is sand or concrete. More preferably, the filling is fine aggregate concrete which is pressure injected into the casing.

In some circumstances, it is known that, below ground, there may be tree roots, rocks and other debris which may prevent the easy penetration of the support sheet.

Similarly, after commencement of the driving of the support sheet, progress may be halted as one unexpectedly encounters roots, rocks etc. This problem can be overcome by the optional use in the above-defined methods of a cutter sheet - of complementary shape to the aforescribed support sheet but of heavier gauge - which is first driven into the ground and then removed to create a passage for the support sheet.

-Of course, it will be appreciated that, if necessary, for all of the above methods a second support sheet can be driven into the ground so that it partially overlaps the adjacent first support sheet. Similarly, if extraordinary depth is required - a depth which is impractical to achieve using a single support sheet - a first support sheet can be driven to ground level and then a second sheet - with suitable hooks attached at its lower edge - affixed to the top edge of the thus-driven first sheet. This second sheet is then driven into the ground forcing the first sheet to below ground level. These processes can be repeated until a retaining wall of the required length and/or depth has been constructed. Optionally, a high tensile bolt is used to hold the overlapped sheets closely together at or near the top of the sheets, it being found that ground pressure is sufficient for close contact at the base of the sheets.

In some soils, or where very deep excavation is required, it may be necessary to anchor the above-described support sheets and revetment to prevent their excessive movement.

Thus, for use with the above-defined methods is an anchor, whereby the said methods are further characterized by:

passing through at least one of said sheets at least one anchor of the type consisting of an elongated rod having a blade-like soil engaging means pivotally connected at one end and capable of movement from a first closed position to a second open position, and the other end of said rod being adapted to be secured to said sheet in said first closed position, into the ground at the required angle and to the necessary depth;

causing said blade-like means to assume said second open position; and

subsequently or simultaneously with assuming said second open position, securing said other end of said rod to said sheet in such a manner to substantially prevent any movement of said sheet under the influence of ground or other pressure or similar.

Preferably, the rod is externally threaded along its whole length and is capable of being secured to said retaining wall, revetment and the like by means of a conventional threaded nut.

The shape of the anchor, its manner of insertion into the soil and its overall operation varies dependent on the type of soil in which the retaining wall, revetment or similar is being constructed.

For example, in soft or wet soil, sand or the like a relatively broad, blade-like soil engaging means is required. An outer casing is positioned over said rod, one end of said casing being releasably affixed to a first adaptor which engages said blade-like means to releasably retain said means in the first closed position, the other end of the outer

casing being affixed to a second adaptor which, in turn, is releasably affixed to a source of a repetitive impact force.

The anchor, secured in its closed position, is driven into the ground at the required angle and to the necessary depth. The outer casing and both adaptors are removed and the end of the rod secured to the necessary tension to the retaining wall, revetment or similar.

On the other hand, in heavily compacted or rocky-type soils, a relatively narrow blade-like soil engaging means may be required. The necessary channel is first created in the soil at the required angle and to the necessary depth and the anchor, with threaded rod attached, is manually inserted into the channel. The end of the threaded rod is then secured to the retaining wall, revetment or similar.

It has been further discovered by the present inventors that the above-discussed support sheets are also load bearing in an essentially horizontal position and thus find use in the construction of suspended floor spans, roadways, bridges and the like.

Thus, according to a third aspect of the present invention, when constructing a roadway, bridge or the like, the method of constructing a load bearing surface as hereinbefore defined is further characterized by:

(a) further adapting said sheet to comprise a narrow flange along the full length of each of its two longitudinal edges; and

(b) positioning the resultant sheet such that the corrugations are transverse to the flow of the traffic that will use said roadway or the like; any successive sheet being positioned such that adjacent said narrow flanges overlap.

Preferably, conventional metal mesh, such as that used for the reinforcement of concrete road ways, is affixed to the upper surface of the support sheets; a continuous-type edge capping is secured to either side of the support sheets to assist in the retention of infill material; and any suitable infill material is positioned on the upper surface of the support sheets and between the side edge capping to the required depth.

Preferred embodiments of the present invention will now be described with reference to the accompanying drawings in which:

FIG. 1 is a sketch of a cutter sheet constructed in accordance with the present invention;

FIG. 2 is a perspective sketch of a support sheet constructed in accordance with the present invention;

FIG. 3a and 3b and FIGS. 3c and 3d, respectively are sketches of two adapters for use with the support sheet illustrated in FIG. 2;

FIGS. 4a and 4b and FIGS. 4c and 4d, respectively are sketches of the adapters illustrated in FIGS. 3a and 3b and FIGS. 3c and 3d respectively, connected to the support sheet depicted in FIG. 2.

FIGS. 5a and 5b and FIGS. 5c and 5d, respectively are sketches of two forms of an attachment constructed in accordance with the present invention.

FIG. 6 is a retaining wall constructed in accordance with the present invention.

FIG. 7 is a sketch of a building element constructed in accordance with the present invention;

FIG. 8 is a sketch of a breakwater constructed in accordance with the present invention.

FIGS. 9a and 9b are sketches of a first anchor constructed in accordance with the present invention;

FIG. 10 is a sketch of a first adapter constructed in accordance with the present invention;

FIG. 11 is a sketch of the anchor illustrated in FIGS. 9a and 9b with the outer casing and first and second adapters attached;

FIGS. 12a to 12c is a schematic series sketch of the anchor described in FIGS. 9 and 11 being placed in position;

FIGS. 13a to 13c are sketches of a second anchor constructed in accordance with the present invention.

FIGS. 14(a,b) are sketches of two embodiments for setting the required tension on the anchors illustrated in the previous FIGS.

FIG. 15a is a sketch of a bridge across a river constructed in accordance with the present invention.

FIG. 15b is a partial cross-sectional view of the bridge illustrated in FIG. 15a.

FIG. 16 is a sketch of the edge capping of the bridge illustrated in FIG. 15.

The cutter illustrated in FIG. 1 comprises an essentially rectangular sheet (1) folded along a number of equi-spaced longitudinal axes (2) to produce the depicted series of pleats. Short sections 12(a,b) of the outside edges 3(a,b) of the two outer folds are angled inward.

In the support sheet depicted in FIG. 2, the rectangular sheet (1), pleats and the short sections 12(a,b) are substantially as in the cutter sheet of FIG. 1. However, the thickness of the support sheet is less than that of the cutter sheet. Further, holes 4(a, b) are positioned near the top edge (5).

FIGS. 3a and 3b and FIGS 3c and 3d respectively depict two adapters for use with the support sheet. Each adapter comprises an essentially rectangular sheet (6) folded about its shorter axis in a similar manner as the support sheet of FIG. 2. In the adapter illustrated in FIGS 3a and 3b, a plate

(14) is affixed across the central fold. (The plate (14), apart from imparting rigidity to the adapter, can also be used as a connection point for attaching the adapter to the source of repetitive impact force.) In each adapter, brackets (7) are affixed at the top edge (8); and holes 9 and 10 are positioned in the brackets (7) and sheet (6) respectively such that they can align with the holes 4(a,b) of the support sheet (3) to allow bolts (11) to pass through as illustrated in FIGS. 4a to 4d.

The two attachments (17) illustrated in FIGS. 5a and 5b and 5c and 5d, respectively each comprise an elongated channel (15) of "square C" cross-section. The width of the channel (15) is slightly greater than the depth of the pleats of the support sheet illustrated in FIG. 2. A member (16) of H cross section is affixed approximately mid centre of the channel (15) and extends away from the open section of the elongated channel (15).

In use, the cutter sheet, if required, can be gripped by any suitable means, eg, by the well known pile-driver, and driven longitudinally into the ground to cut tree roots etc. The cutter sheet is then removed by any conventional means. If necessary, the adapter is attached to the support sheet as illustrated in FIGS. 4a to 4d before driving the sheet into the ground. Also, if necessary, after the adapter has been removed, the member (16) of the attachment (17) is affixed to, eg, the pile driver, and the channel member (15) positioned over the top of the support sheet so that the top fits into the mouth of the channel. The support sheet is then driven to ground level. After the support sheet is at the required depth, if required, a second (and any subsequent) support sheet is driven into the ground, overlapping the first support sheet as illustrated in FIG. 6.

In the building element illustrated in FIG. 7, the rectangular sheet (1), pleats, short sections 12(a,b) and holes 4(a,b) (optional) (not illustrated) are substantially as in the support sheet depicted in FIG. 2. A casing (18) is affixed to the sheet (1) by any suitable means, the casing comprising a double walled nylon mattress (20) held together at intervals by filter points (19). The casing is filled with, for example, fine aggregate concrete (21) by pressure injection until the mattress is inflated to assume a position which essentially follows the contours of the sheet but leaving a gap g between the wall of the mattress and the base b of each fold. The filter points (19) remain free of concrete. The gap g further assists wave energy dissipation as the waves attempt to force the mattress into closer contact with the sheet.

In use, the required number of sheets (1) are driven into the ground at the required angle and to the required depth following the procedure described above. If necessary, excavation of the soil

or the like is undertaken from the water side of the revetment. A casing (18) as described with reference to FIG. 7 is then placed over one face of the sheets and then pumped full of fine aggregate concrete.

It should be noted that the positioning of the casing and the subsequent filling with concrete can be undertaken even through the sheet(s) may be under water.

This feature is particularly advantageous for the construction of groins, breakwaters and the like where it is impossible to drain, or to divert the flow of, the water. As illustrated in FIG. 8, spaced walls 22(a,b) can extend from the shoreline (24) out to sea for the required distance and an end wall (23) is then positioned. Each spaced and end walls are as described above with reference to FIG. 7. The breakwater is then completed by positioning rocks (25), pumping sand or other suitable fill between the walls. (Although the casing (18) is illustrated as covering only one face of each sheet (1), in practice, it is more likely that the casing (18) will extend over the top edge of each sheet and down the other face thereof, each end of the casing (18) then being buried below ground/sea bed level.)

In FIGS. 9a and 9b, the anchor comprises a soil engaging means (26) consisting of a plate (27) two sides of which taper to a point (28) at one end. The other end is bifurcated providing segments (80) each of which are curved at an inclination to the plane of the plate (27) and sufficiently separated to provide a significant straight edge (44). Additional shaped, curved wing segments 30(a,b), one affixed to each side of the plate, are positioned to follow the inclination set by the plate (27) and its bifurcated end. A key-hole shaped aperture (29) is positioned in the plate (27) near to the point (28). A pivot arm (31) is secured across the aperture (29) and at approximate right angles to the longitudinal axis of the plate (27). Pivotaly connected to the arm (31), via a plate (33), is a short internally threaded open ended tube (32). The aperture (29), pivot arm (31) and tube (32) are adapted such that the tube (32) can be positioned initially substantially parallel to the said longitudinal axis but allows the outer side (81) of the tube (32) to abut the inner edge (34) of the aperture (29) when the plate (27) pivots through 90 degrees as illustrated in FIG. 9b.

FIG. 10 illustrates an adapter (42) comprising a substantially bullet shaped member (36). An externally threaded tube (37) is affixed to the rear of the member (36). A section of the member (36) is removed to create a flat surface (38). A triangular segment (39) is affixed to the member (36) and extends forward over the flat surface (38) to create a slot (40). A hole (41) passes through the entire length of the adapter.

In use, as illustrated in FIG 11, a threaded rod (35) is screwed to the open ended tube (32). An elongated tube (43) - which is internally threaded for a short distance from either end - is attached to the threaded tube (37) of the adapter (42) and the rod (35) passed through until the slot (40) engages the edge (44) of the plate (27) thus holding the blade (26) in a closed position. The rod (35) protrudes from the other end of the tube (43) for a short distance. A second adapter (45) comprising a hexagonal nut (46) - either side of which is attached short externally threaded tubes 47(a,b) - is placed over the protruding end of the rod (35) and screwed into the end of the tube (43) until the nut (46) abuts the end edge of the tube (43).

As illustrated in FIGS. 12a-12c, a hole is positioned in the retaining wall (47) of sufficient diameter to allow the anchor to be placed through with the blade (26) in its closed position (FIG. 12a). By applying a force to the end of the second adapter (45), the anchor can be driven into the ground at the required angle and to the required depth. Although any suitable means can be used to drive the anchor into the ground, an air driven machine is preferred as a secondary benefit of the air flowing down through the second adapter (45), tube (43) and first adapter (42) is that the threads of the rod (35) are kept clear of soil, grit etc as the anchor passes through the ground. As illustrated in FIG 12b, the second adapter (45) is removed and the tube (43) disengaged from the plate (27) (for example, by application of a force to the rod (35) to move the anchor further into the ground or by partial or total removal of the tube (43) from the ground). A plate (50) - of a shape identical to a single fold of the sheet (1) - with an aperture is placed in position on the outside of the wall (47) and a nut (51) positioned on the rod (35) is tightened. As the nut (51) is tightened the movement of the rod (35) causes the blade (26) to assume its open position (FIG. 12c) thus causing resistance to its passage through the soil. The nut (51) is tightened until the required tension is reached.

The anchor illustrated in FIGS 13a and 13b comprises a blade (52) consisting of a narrow plate (53) two sides of which taper to a point (54) at one end. The other end of the plate (53) is curved at an inclination to the plane of the plate (53) to form a tail (55). The edge (56) of the tail (55) is roughly serrated. A key-hole shaped aperture (57) is positioned in the plate (53) near to the point (54). A pivot arm (58) is secured across the aperture (57) and at approximate right angles to the longitudinal axis of the plate (53). Pivotaly connected to the arm (58) - via a plate (59) - is a short internally threaded open ended tube (60). The aperture (57), pivot arm (58) and tube (60) are adapted such that the tube (60) can be positioned initially substan-

tially parallel to the said longitudinal axis but allows the outer side (61) of the tube (60) to abut the inner edge (62) of the aperture (57) when the plate (53) pivots through 90 degrees as illustrated in FIGS. 13a and 13c. An externally threaded rod (35) is connected to the tube (60).

In use, a hole is first drilled by any conventional means to establish a passageway for the anchor depicted in FIGS. 13a-c. A hole is positioned in the retaining wall of sufficient diameter to allow the anchor-attached to the rod (35) - to be passed through and down the afore-said predrilled passageway. (To insert, the tail (55) is inclined upwards, the plate (53) thus resting on the threaded rod (35).) When the anchor is at the required depth, the rod is turned to enable the blade (52) to assume a partial open position under the influence of gravity. The protruding end of the rod (35) is affixed to the retaining wall in a similar manner to that described above with reference to FIGS 12a-c. This initial tensioning beds the anchor into the ground. The tension is removed and the passageway filled with cement grout and the anchor is again re-tensioned. The retaining wall is ready for immediate use even though the cement grout has not set, however, if required, further re-tensioning can occur once the grout has set.

A number of devices can be used to monitor the required tension for either anchor. For example (FIG. 14a), prior to any tensioning, a floating nut (64) can be placed on the rod (35) and abutted to the plate (50). A bridge (65) can then be positioned over the rod (35) followed by a pre-graded compression spring (66) and, if necessary, a washer (67). The spring (66) is compressed by turning a second nut (68) positioned on the rod (35) until the required tension is reached. The floating nut (64) is periodically tightened against the wall (1).

Alternatively, a conventional pressure measuring gauge (not illustrated) can be used in place of the spring (66).

Yet another alternative is to provide a waler (69) which comprises a hollow tube of rectangular cross section. This waler is pretested so that it is known to deform at a certain pressure. Therefore, the waler can be positioned as illustrated in FIG. 14b and the nut (70) tightened until the surface (71) deforms. A waler is a particularly advantageous embodiment as a single waler can be used to tension a number of anchors as also illustrated in FIG. 14b.

The road way illustrated in FIGS. 15a (depicted bridging a waterway) and 15b comprises a number of rectangular sheets (72) each folded about its longitudinal axis to produce a series of pleats. A narrow flange (73) extends from both longitudinal edges. Adjacent sheets (72) are positioned such that the respective flanges (73) overlap and are

joined together by a conventional nut and bolt arrangement (74). Optionally, the underside of each sheet (72) may be coated with any suitable corrosion-resistant material. Conventional metal mesh (90) is laid over the sheets (72) and, for example, spot welded thereto. An edge capping (75) of the profile illustrated in FIG. 16 is fixed along the open ends of the pleats. The lower lip (76) of the capping (75) sits under the sheets (72) and is attached thereto by bolts passing through the lip (76) and flanges (73). The edge (77) abuts the ends of the sheets and the lip (78) is approximately at the same height as the top of the pleats. The upper lip (79) is at a height corresponding to the required depth of the infill material. The upper surface of this lip (79) provides a convenient screed level for the infill material.

By using the present invention, a significant number of advantages are apparent. These advantages include:

The cost of the thinner gauge support sheets is sufficiently reduced such that it can be economical for them to remain in the ground after their purpose has been fulfilled. This is particularly advantageous when working in narrow confines where it can be almost impossible to retrieve the support sheets without damage to either the newly formed footings, walls etc or to an existing adjacent building.

A further advantage of this disposability of the support sheets is that, by remaining in situ, they can also be used as framework for the foundations and the like of the new construction. This provides economic advantages in that, after constructing the retaining wall, it may not be necessary to utilise additional resources and personnel in erecting the required formwork for, for example, the subsequent pouring of the concrete for the foundations.

The lower impact forces required to drive the support sheets into the ground give rise to much lower shock waves through the ground which reduces the chance of damage to existing adjacent buildings.

The overall lesser bulk of the implements of the invention and the equipment necessary to drive the sheets into the ground enables retaining walls and the like to be erected closer to existing buildings than is possible using other known methods.

In this regard, as the sheets can be positioned at reverse angles, they can be placed close to existing buildings without any eaves etc to be removed first as is the case with the prior art piles.

To a certain extent, the required "strength" of a retaining wall can be varied by altering the degree of "overlap" of adjacent sheets. For example, an overlap of two "folds" provides, in effect, a strengthened pole every few metres - such an arrangement is extremely strong and stable. This strength is superior to the prior art interlocking

piles but the sheets can readily be removed again if desired.

As rust, dirt etc collects in the grooves of the prior art piles, they virtually lock solid, it requiring a tremendous force to remove them. This is not a problem with the support sheets of the present invention should it be necessary to remove the sheets from the ground.

A retaining wall can be constructed in a body of water such as a dam or a lake which is sufficiently water tight to enable partial draining of the dam or the like from one side of the wall. After the required work has been undertaken on the drained side, a support sheet can be slowly removed allowing a controlled flow of water to pass under thereof.

It is possible to construct a support wall for a revetment before any excavation is undertaken: the angle of the support wall can be chosen to reduce wave run up at wave deflection off the revetment; and as the support wall is essentially water tight, should any excavation of the water side be required, this can be undertaken from the dry side of the wall.

By using the thinner gauge sheets and an overlaid casing, the costs of manufacturing a breakwater and the like can be significantly reduced but the overall strength is improved.

The present invention is particularly suited to revetments - both above and below water - for use in beach shoreline protection, bridge abutments, road and rail embankments, dams, rivers, spillways, irrigation and stormwater canals, slipways, retaining walls, breakwaters and the like.

Should it be necessary to strengthen any retaining wall or the like, an anchor can be relatively quickly positioned for immediate use. The compact nature of the anchor when in the closed position and the fact that it can be positioned by means remote from the blade end provides a major advantage in that the anchor can be easily positioned close to, for example, the existing foundations of any adjacent building. Further advantages include the cost which is substantially less than existing devices and that a number of items from the anchor are reusable. An important advantage is that no destressing of the anchor is required after it has been positioned and served its intended purpose. A further advantage is that the anchor can be re-tensioned at any time throughout its structural life, unlike prior art anchors. Alternatively, if it is no longer necessary to maintain constant tension on the retaining wall, the anchor and its method of insertion can be designed such that all components of the anchor, with the exception of the blade, can readily be removed from the ground.

The basic support sheet can also be used as a road way surface which is load bearing for vehicles and the like even before any final surface material

is laid. Thus, for example, the sheets can be laid directly on the existing ground surface and essentially be ready for immediate use.

Another major advantage is that the various sheets and anchors of the present invention can be prepared on site. The steel can be delivered on site and as the machines for folding and cutting the steel are portable, the required number and shape of items can be manufactured on site. This represents a significant reduction in transportation and manufacturing costs. It is estimated that the present invention is much stronger than known existing systems but can be put into effect for approximately 25% of the cost.

It will be appreciated that the above described embodiments are examples only and that modifications can be made to the present invention described herein without departing from the inventive concept as defined in the following claims.

Claims

1. A method of constructing a load bearing surface such as a retaining wall (47), floor span, roadway or the like of the type having one or more interconnected essentially quadrangular corrugated sheets, each sheet (1) of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:
 - (a) providing an adaptor also comprising an essentially quadrangular corrugated sheet (6) having corrugations complementary to those of said sheet (1), said adaptor having means (7, 9, 10) for temporary attachment to said sheet (1);
 - (b) using said adaptor to place said sheet (1) into its required position; and
 - (c) removing said adaptor.
2. A method of constructing a load bearing surface such as a retaining wall (47), floor span, roadway or the like of the type having one or more interconnected essentially quadrangular corrugated sheets, each sheet (1) of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:
 - (a) providing an adaptor also comprising an essentially quadrangular corrugated sheet (6) having corrugations complementary to those of said sheet (1), said adaptor having means (7, 9, 10) for temporary attachment to said sheet (1);
 - (b) using said adaptor to place said sheet (1) to an approximation of its required posi-

piles but the sheets can readily be removed again if desired.

As rust, dirt etc collects in the grooves of the prior art piles, they virtually lock solid, it requiring a tremendous force to remove them. This is not a problem with the support sheets of the present invention should it be necessary to remove the sheets from the ground.

A retaining wall can be constructed in a body of water such as a dam or a lake which is sufficiently water tight to enable partial draining of the dam or the like from one side of the wall. After the required work has been undertaken on the drained side, a support sheet can be slowly removed allowing a controlled flow of water to pass under thereof.

It is possible to construct a support wall for a revetment before any excavation is undertaken; the angle of the support wall can be chosen to reduce wave run up at wave deflection off the revetment; and as the support wall is essentially water tight, should any excavation of the water side be required, this can be undertaken from the dry side of the wall.

By using the thinner gauge sheets and an overlaid casing, the costs of manufacturing a breakwater and the like can be significantly reduced but the overall strength is improved.

The present invention is particularly suited to revetments - both above and below water - for use in beach shoreline protection, bridge abutments, road and rail embankments, dams, rivers, spillways, irrigation and stormwater canals, slipways, retaining walls, breakwaters and the like.

Should it be necessary to strengthen any retaining wall or the like, an anchor can be relatively quickly positioned for immediate use. The compact nature of the anchor when in the closed position and the fact that it can be positioned by means remote from the blade end provides a major advantage in that the anchor can be easily positioned close to, for example, the existing foundations of any adjacent building. Further advantages include the cost which is substantially less than existing devices and that a number of items from the anchor are reusable. An important advantage is that no distressing of the anchor is required after it has been positioned and served its intended purpose. A further advantage is that the anchor can be re-tensioned at any time throughout its structural life, unlike prior art anchors. Alternatively, if it is no longer necessary to maintain constant tension on the retaining wall, the anchor and its method of insertion can be designed such that all components of the anchor, with the exception of the blade, can readily be removed from the ground.

The basic support sheet can also be used as a road way surface which is load bearing for vehicles and the like even before any final surface material

is laid. Thus, for example, the sheets can be laid directly on the existing ground surface and essentially be ready for immediate use.

Another major advantage is that the various sheets and anchors of the present invention can be prepared on site. The steel can be delivered on site and as the machines for folding and cutting the steel are portable, the required number and shape of items can be manufactured on site. This represents a significant reduction in transportation and manufacturing costs. It is estimated that the present invention is much stronger than known existing systems but can be put into effect for approximately 25% of the cost.

It will be appreciated that the above described embodiments are examples only and that modifications can be made to the present invention described herein without departing from the inventive concept as defined in the following claims.

Claims

1. A method of constructing a load bearing surface such as a retaining wall (47), floor span, roadway or the like of the type having one or more interconnected essentially quadrangular corrugated sheets, each sheet (1) of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:
 - (a) providing an adaptor also comprising an essentially quadrangular corrugated sheet (6) having corrugations complementary to those of said sheet (1), said adaptor having means (7, 9, 10) for temporary attachment to said sheet (1);
 - (b) using said adaptor to place said sheet (1) into its required position; and
 - (c) removing said adaptor.
2. A method of constructing a load bearing surface such as a retaining wall (47), floor span, roadway or the like of the type having one or more interconnected essentially quadrangular corrugated sheets, each sheet (1) of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:
 - (a) providing an adaptor also comprising an essentially quadrangular corrugated sheet (6) having corrugations complementary to those of said sheet (1), said adaptor having means (7, 9, 10) for temporary attachment to said sheet (1);
 - (b) using said adaptor to place said sheet (1) to an approximation of its required position;



- tion;
 (c) removing said adaptor;
 (d) placing an attachment (17) in temporary communication with the top (5) of said sheet (1) and further positioning said sheet (1) to its required relationship to the ground; and
 (e) removing said attachment;
 wherein said attachment comprises:
 (a) an elongated member (15) defining a channel of a width slightly greater than the depth of one of said ridges or said troughs;
 (b) means (16) to releasably connect said elongated member (15) to a source of a vibrating source;
 wherein each side of said channel is further adapted to comprise a short extension, each said extension comprising a corrugated sheet having corrugations complementary to those of said sheet (1).
3. A method as defined in Claim 1 or Claim 2 wherein, prior to placing said sheet (1) into said required position, a sheet is first driven into the ground at the required angle and to the required depth to cut tree roots, to split rocks and the like, said sheet then being removed, characterised in that said sheet comprises an essentially quadrangular corrugated sheet having corrugations complementary to those of said sheet (1).
4. A method of constructing a revetment of the type having one or more inter-connected essentially quadrangular corrugated sheets, each sheet (1) of the type having one or more alternating radiused ridges and radiused troughs connected by linear webs, characterised in that said method comprises:
 (a) providing an adaptor also comprising an essentially quadrangular corrugated sheet (6) having corrugations complementary to those of said sheet (1), said adaptor having means (7, 9, 10) for temporary attachment to said sheet (1);
 (b) using said adaptor to place said sheet (1) into its required position;
 (c) removing said adaptor;
 (d) excavating any soil or the like that may be present from one face of said sheet (1);
 (e) overlying a casing (18) or the like on said one face, wherein said casing can be filled with a suitable robust material (21).
5. A method of constructing a revetment of the type having one or more inter-connected essentially quadrangular corrugated sheets, each sheet (1) of the type having one or more alternating radiused ridges and radiused
- troughs connected by linear webs, characterised in that said method comprises:
 (a) providing an adaptor also comprising an essentially quadrangular corrugated sheet (6) having corrugations complementary to those of said sheet (1), said adaptor having means (7, 9, 10) for temporary attachment to said sheet (1);
 (b) using said adaptor to place said sheet (1) to an approximation of its required position;
 (c) removing said adaptor;
 (d) placing an attachment (17) in temporary communication with the top (5) of said sheet (1) and further positioning said sheet (1) to its required relationship to the ground;
 (e) removing said attachment;
 (f) excavating any soil or the like that may be present from one face of said sheet;
 (g) overlying a casing (18) or the like on said one face, wherein said casing can be filled with a suitable robust material (21);
 wherein said attachment comprises:
 (a) an elongated member (15) defining a channel of a width slightly greater than the depth of one of said ridges or said troughs;
 (b) means (16) to releasably connect said elongated member (15) to a source of a vibrating source;
 wherein each side of said channel is further adapted to comprise a short extension, each said extension comprising a corrugated sheet having corrugations complementary to those of said sheet (1).
6. A method as defined in Claim 4 or Claim 5 wherein, prior to placing said sheet (1) into said required position, another sheet is first driven into the ground at the required angle and to the required depth to cut tree roots, to split rocks and the like, said another sheet then being removed, characterised in that said another sheet comprises an essentially quadrangular corrugated sheet having corrugations complementary to those of said sheet (1).
7. A method as defined in any one of Claims 1 to 6, further characterized by:
 passing through at least one of said sheets at least one anchor of the type consisting of an elongated rod (35) having a blade-like soil engaging means (26) pivotally connected at one end and capable of movement from a first closed position to a second open position, and the other end of said rod (35) being adapted to be secured to said sheet in said first closed position, into the ground at the required angle and to the necessary depth;



causing said blade-like means (26) to assume said second open position; and

subsequently or simultaneously with assuming said second open position, securing said other end of said rod (35) to said sheet (1) in such a manner to substantially prevent any movement of said sheet (1) under the influence of ground or other pressure or similar; further characterized in that said soil engaging means (26) comprises:

(a) a plate (27), two sides of which taper to a point (28);

(b) the end of said plate (27) opposite to said point (28) being bifurcated to provide segments (80), each segment (80) being curved at an inclination to the plane of said plate (27);

(c) curved wing segments (30a, b) one affixed to each side of said plate (27), each wing segment (30) following the inclination set by said plate (27) and its said bifurcated end;

(d) an aperture (29) in said plate (27);

(e) means (32, 33) pivotally connected across said aperture (29) to allow said plate (27) to rotate through no more than approximately 90 degrees.

8. A method as defined in any one of Claims 1 to 6, further characterized by:

passing through at least one of said sheets at least one anchor of the type consisting of an elongated rod (35) having a blade-like soil engaging means (52) pivotally connected at one end and capable of movement from a first closed position to a second open position, and the other end of said rod (35) being adapted to be secured to said sheet, into the ground at the required angle and to the necessary depth;

causing said blade-like means (26) to assume said second open position; and

subsequently or simultaneously with assuming said second open position, securing said other end of said rod (35) to said sheet (1) in such a manner to substantially prevent any movement of said sheet (1) under the influence of ground or other pressure or similar; further characterized in that said soil engaging means (52) comprises:

(a) a plate (53), two sides of which taper to a point (54), the other end of said plate (53) being curved at an inclination to the plane of said plate (53);

(b) an aperture (57) in said plate (53); and

(c) means (58) pivotally connected across said aperture to allow said plate (53) to rotate through no more than approximately 90 degrees.

9. A method as defined in Claim 7, wherein said anchor is first attached to a rod (35), an outer casing (43) is then positioned over said rod (35), one end of said casing (43) being releasably affixed to a first adaptor (42) which holds said anchor in said closed position, the other end of said outer casing (43) being affixed to a second adaptor (45) which, in turn, is releasably affixed to a source of a repetitive impact force, before or simultaneously with - passing said anchor through said sheet (1).

10. A method as defined in Claim 9 wherein, prior to said passing of said anchor through said sheet (1), a channel is first created in said soil to accommodate said anchor attached to said rod (35) and said outer casing (43).

11. A method as defined in Claim 9 or Claim 10, further characterized in that said first adaptor (42) comprises:

(a) a cylindrical body member;

(b) a frusto-conical member extending from one end of, and coaxially with, said body member, said frusto-conical member having a section removed to create essentially a flat surface (38) on one side thereof;

(c) a holding member (39) affixed to said body member and extending from said one end such that a slot (40) is formed between said holding member (39) and said flat surface (38) of said frusto-conical member;

(d) an externally threaded tube (37) extending from the other end of, and coaxially with, said body member;

(e) a bore (41) passing through the entire longitudinal length of said first adaptor (42); wherein said rod (35) of said anchor can pass through said bore (41) and wherein said plate (27) of said anchor can be retained in said slot to retain said anchor in said first closed position.

12. A method of constructing a roadway or the like as defined in any one of Claims 1 to 3, or as defined in any one of Claims 7 to 11 when appended to any one of Claims 1 to 3, characterised in that said method comprises:

(a) further adapting said sheet (1, 72) to comprise a narrow flange (73) along the full length of each of its two longitudinal edges;

(b) positioning the resultant sheet such that the corrugations are transverse to the flow of the traffic that will use said roadway or the like; any successive sheet being positioned such that adjacent said narrow flanges (73) overlap.



13. A method as defined in Claim 12, further characterised in that suitable infill material is positioned on that surface of said sheet which will be in direct contact with said traffic.

14. A method is defined in Claim 13 wherein said infill material is retained on said surface between continuous-type edge cappings (75) extending parallel to said flow and connected to said flanges.

Patentansprüche

1. Verfahren zum Bau einer lasttragenden Fläche, wie beispielsweise einer Stützwand (47), eines mit Spannelementen versehenen Bodens, einer Straße o.ä., die eine oder mehrere miteinander verbundene, im wesentlichen viereckige, gewellte Schichten enthält, wobei jede dieser Schichten (1) eine oder mehrere abwechselnd angeordnete, gerundete Rippen und gerundete Rillen enthält, die durch linear verlaufende Stege verbunden sind, gekennzeichnet durch folgende Verfahrensschritte:

a) es ist ein Adapter vorgesehen, der gleichfalls eine im wesentlichen viereckige, gewellte Schicht (6) umfaßt, die eine zur Schicht (1) komplementär gestaltete Wellenform aufweist, wobei der Adapter Einrichtungen (7, 9, 10) zur zeitweiligen Befestigung an der Schicht (1) enthält;

b) der Adapter wird verwendet, um die Schicht (1) in ihre gewünschte Position zu bringen; und

c) der Adapter wird entfernt.

2. Verfahren zum Bau einer lasttragenden Fläche, wie beispielsweise einer Stützwand (47), eines mit Spannelementen versehenen Bodens, einer Straße o.ä., die eine oder mehrere miteinander verbundene, im wesentlichen viereckige, gewählte Schichten aufweist, wobei jede dieser Schichten (1) eine oder mehrere abwechselnd angeordnete, gerundete Rippen und gerundete Rillen enthält, die durch linear verlaufende Stege verbunden sind, gekennzeichnet durch folgende Verfahrensschritte:

a) es ist ein Adapter vorgesehen, der gleichfalls eine im wesentlichen viereckige, gewellte Schicht (6) aufweist, die eine komplementär zur Schicht (1) gestaltete Wellenform aufweist, wobei der Adapter Einrichtungen (7, 9, 10) zur zeitweiligen Befestigung an der Schicht (1) enthält;

b) der Adapter wird verwendet, um die Schicht (1) nahe ihrer gewünschten Position

anzuordnen;

c) der Adapter wird entfernt;

d) ein Zubehöriteil (17) wird in zeitweiliger Verbindung mit der Oberseite (5) der Schicht (1) angeordnet, und die Schicht (1) wird weiterhin in ihrer gewünschten Beziehung zum Untergrund angeordnet; und

e) das Zubehöriteil wird entfernt;

wobei das Zubehöriteil enthält:

a) ein längliches Teil (15), das einen Kanal mit einer Breite bildet, die geringfügig größer ist als die Tiefe einer der Rippen oder der Wellen;

b) eine Einrichtung (16) zur lösbaren Verbindung des länglichen Teils (15) mit einer Quelle einer Vibrationsquelle;

wobei jede Seite des Kanals weiterhin so ausgebildet ist, daß sie eine kurze Verlängerung enthält, von der jede eine gewellte Schicht aufweist, die eine komplementär zur Schicht (1) gestaltete Wellenform aufweist.

3. Verfahren nach Anspruch 1 und 2, wobei vor der Anordnung der Schicht (1) in der gewünschten Position zunächst eine Schicht in dem erforderlichen Winkel und der erforderlichen Tiefe in den Untergrund getrieben wird, um auf diese Weise Baumwurzeln abzuschneiden oder Steine u.ä. zu zertrennen, wobei die Schicht dann entfernt wird, dadurch gekennzeichnet, daß die Schicht eine im wesentlichen viereckige, gewellte Schicht enthält, die eine der Schicht (1) entsprechend geformte Wellenform aufweist.

4. Verfahren zum Bau einer Verkleidung mit einer oder mehreren miteinander verbundenen, im wesentlichen viereckigen gewellten Schichten, wobei jede dieser Schichten (1) eine oder mehrere abwechselnd angeordnete, gerundete Rippen und gerundete Rillen enthält, die durch linear verlaufende Stege verbunden sind, gekennzeichnet durch folgende Verfahrensschritte:

a) ein Adapter ist vorgesehen, der gleichfalls eine im wesentlichen viereckige, gewellte Schicht (6) enthält, die eine komplementär zur Schicht (1) gestaltete Wellenform aufweist, wobei der Adapter Einrichtungen (7, 9, 10) zur zeitweiligen Befestigung an der Schicht (1) aufweist;

b) der Adapter wird verwendet, um die Schicht (1) in ihrer gewünschten Position anzuordnen;

c) der Adapter wird entfernt;

d) Bodenmaterial o.ä., das auf einer Seite der Schicht (1) vorhanden sein kann, wird entfernt;



e) auf dieser Seite wird ein Gehäuse (18) o.ä. überlagert, das mit einem geeigneten, robusten Material (21) gefüllt werden kann.

5. Verfahren zum Bau einer Verkleidung mit einer oder mehreren miteinander verbundenen, im wesentlichen viereckigen gewellten Schichten, wobei jede dieser Schichten (1) eine oder mehrere abwechselnd angeordnete, gerundete Rippen und gerundete Rillen enthält, die durch linear verlaufende Stege verbunden sind, gekennzeichnet durch folgende Verfahrensschritte:

- a) ein Adapter ist vorgesehen, der gleichfalls eine im wesentlichen viereckige, gewellte Schicht (6) aufweist, die eine komplementär zur Schicht (1) gestaltete Wellenform aufweist, wobei der Adapter Einrichtungen (7, 9, 10) zur zeitweiligen Befestigung an der Schicht (1) umfaßt;
- b) der Adapter wird verwendet, um die Schicht (1) nahe ihrer gewünschten Position anzuordnen;
- c) der Adapter wird entfernt;
- d) ein Zubehörteil (17) wird in zeitweiliger Verbindung mit der Oberseite (5) der Schicht (1) angeordnet, und die Schicht (1) wird in ihrer gewünschten Beziehungslage zum Untergrund positioniert;
- e) das Zubehörteil wird entfernt;
- f) Bodenmaterial o.ä., das auf einer Seite der Schicht vorhanden sein kann, wird entfernt;
- g) auf dieser Seite wird ein Gehäuse (18) o.ä. überlagert, wobei das Gehäuse mit einem geeigneten, robusten Material (21) befüllt werden kann;

wobei das Zubehörteil enthält:

- a) ein längliches Teil (15), das einen Kanal mit einer Weite bildet, die geringfügig größer ist als die Tiefe einer der Rippen oder der Rillen;
- b) eine Einrichtung (16) zur lösbaren Verbindung des länglichen Teils (15) mit einer Quelle einer Vibrationsquelle;

wobei jede Seite des Kanals weiterhin so gestaltet ist, daß sie eine kurze Verlängerung enthält, wobei jede Verlängerung eine gewellte Schicht umfaßt, die eine komplementär zur Schicht (1) gestaltete Wellenform aufweist.

6. Verfahren nach Anspruch 4 oder 5, wobei vor der Anordnung der Schicht (1) in der gewünschten Position eine weitere Schicht zunächst in dem gewünschten Winkel und der erforderlichen Tiefe in den Untergrund getrieben wird, um auf diese Weise Baumwurzeln zu zerschneiden und Steine u.ä. zu zertrennen.

wobei diese andere Schicht anschließend entfernt wird, dadurch gekennzeichnet, daß diese andere Schicht eine im wesentlichen viereckige, gewellte Schicht umfaßt, die eine komplementär zur Schicht (1) gestaltete Wellenform aufweist.

7. Verfahren nach einem der Ansprüche 1 bis 6, weiterhin dadurch gekennzeichnet, daß:

durch wenigstens eine der Schichten in den Untergrund im gewünschten Winkel und der erforderlichen Tiefe wenigstens ein Anker geführt wird, der einen länglichen Stab (35) aufweist, der eine klingenartige, in den Grund eingreifende Einrichtung (26) aufweist, die schwenkbeweglich an einem Ende befestigt ist und aus einer ersten geschlossenen Position in eine zweite geöffnete Position beweglich ist, wobei das andere Ende des Stabes (35) an der Schicht in der ersten geschlossenen Position befestigt werden kann;

die klingenartige Einrichtung (26) die zweite, offene Position einnimmt;

anschließend oder gleichzeitig mit der Einnahme der zweiten, offenen Position, das andere Ende des Stabes (35) an der Schicht (1) derart befestigt wird, daß jegliche Bewegung der Schicht (1) unter der Einwirkung des Untergrundes, eines anderen Drucks o.ä. im wesentlichen verhindert wird;

weiterhin dadurch gekennzeichnet, daß die in den Grund eingreifende Einrichtung (26) enthält:

- a) eine Platte (27), von der zwei Seiten zu einer Spitze (28) zulaufen;
- b) wobei das Ende der Platte (27) gegenüber der Spitze (28) sich gabelt, um auf diese Weise Segmente (80) zu bilden, die in einem Winkel zur Ebene der Platte (27) gekrümmt sind;
- c) gekrümmte Flügelsegmente (30a, 30b), die jeweils mit einer Seite der Platte (27) verbunden sind und die beide der durch die Platte (27) gesetzten Neigung und ihrem gegabelten Ende folgen;
- d) eine Öffnung (29) in der Platte (27);
- e) Einrichtungen (32, 33), die schwenkbeweglich über der Öffnung (29) verbunden sind, um auf diese Weise eine Drehbewegung der Platte (27) um nicht mehr als etwa 90° zu ermöglichen.

8. Verfahren nach einem der Ansprüche 1 bis 6, weiterhin dadurch gekennzeichnet, daß

durch wenigstens eine der Schichten in den Untergrund im gewünschten Winkel und bis in die erforderliche Tiefe hinein wenigstens ein Anker geführt wird, der einen länglichen



Stab (35) aufweist, der eine klingenartige, mit dem Boden in Eingriff kommende Einrichtung (52) enthält, die schwenkbeweglich an einem Ende befestigt ist und zwischen einer ersten geschlossenen Position und einer zweiten geöffneten Position beweglich ist, wobei das andere Ende des Stabs (35) an der Schicht befestigt werden kann;

die klingenartige Einrichtung (26) die zweite geöffnete Position einnehmen kann;

anschließend oder gleichzeitig mit der Einnahme der zweiten geöffneten Position das andere Ende des Stabs (35) an der Schicht (1) derart befestigt wird, daß eine Bewegung der Schicht (1) unter der Einwirkung des Grundes, eines anderen Drucks o.ä. verhindert wird; weiterhin dadurch gekennzeichnet, daß die in den Boden eingreifende Einrichtung (52) enthält:

a) eine Platte (53), von der zwei Seiten sich zu einer Spitze (54) verjüngen, wobei das andere Ende der Platte (53) in einem Neigungswinkel zur Ebene der Platte (53) gekrümmt ist;

b) eine Öffnung (57) in der Platte (53); und

c) eine Einrichtung (58), die schwenkbeweglich oberhalb der Öffnung verbunden ist, um auf diese Weise eine Drehbewegung der Platte (53) um nicht mehr als etwa 90° zu ermöglichen.

9. Verfahren nach Anspruch 7, wobei der Anker zunächst an einem Stab (35) befestigt wird und anschließend ein äußeres Gehäuse (43) über dem Stab (35) positioniert wird, wobei ein Ende des Gehäuses (43) lösbar an einem ersten Adapter (42) befestigt wird, der den Anker in der geschlossenen Position hält, wobei das andere Ende des äußeren Gehäuses (43) an einem zweiten Adapter (45) befestigt ist, der seinerseits lösbar mit einer Repetitiv-Aufprallkraft-Quelle verbunden ist, wobei dies vor- oder gleichzeitig mit - dem Durchführen des Ankers durch die Schicht (1) geschieht.

10. Verfahren nach Anspruch 9, wobei vor der Durchführung des Ankers durch die Schicht (1) zunächst ein Kanal im Boden zur Unterbringung des Ankers ausgebildet wird, der mit dem Stab (35) und dem äußeren Gehäuse (43) verbunden ist.

11. Verfahren nach Anspruch 9 oder 10, weiterhin dadurch gekennzeichnet, daß der erste Adapter (42) enthält:

a) ein zylindrisches Körperteil;

b) ein stumpf-konisches Teil, das sich von einem Ende des Körperteils und coaxial

dazu erstreckt, und das einen Anschnitt aufweist, der entfernt ist, um auf diese Weise eine im wesentlichen flache Oberfläche (38) auf einer seiner Seiten auszubilden;

c) ein Halteteil (39), das an dem Körperteil befestigt ist und sich von dem einen Ende erstreckt, so daß ein Schlitz (40) zwischen dem Halteteil (39) und der flachen Oberfläche (38) des stumpfkonischen Teils ausgebildet wird;

d) ein auf seiner Außenseite mit einem Gewinde versehenes Rohr (37), das sich von dem anderen Ende des Körperteils und coaxial dazu erstreckt;

e) ein Bohrloch (41), das sich durch die gesamte Länge des ersten Adapters (42) in Längsrichtung erstreckt;

wobei der Stab (35) des Ankers durch das Bohrloch (41) greifen kann und wobei die Platte (27) des Ankers in dem Schlitz zurückgehalten werden kann, um den Anker in der ersten geschlossenen Position zu halten.

12. Verfahren zum Bau einer Straße o.ä. nach einem der Ansprüche 1 bis 3, oder nach einem der Ansprüche 7 bis 11, soweit abhängig von einem der Ansprüche 1 bis 3, gekennzeichnet durch folgende Verfahrensschritte:

a) die Schicht (1, 72) ist weiterhin so gestaltet, daß sie einen schmalen Flansch (73) über die gesamte Länge ihrer beiden Längskanten aufweist;

b) die so gebildete Schicht wird derart angeordnet, daß die Wellenform quer zum Verkehrsfluß auf der Straße o.ä. verläuft; jede weitere Schicht wird derart angeordnet, daß die benachbarten schmalen Flansche (73) einander überlappen.

13. Verfahren nach Anspruch 12, weiterhin dadurch gekennzeichnet, daß geeignetes Füllmaterial auf der Oberfläche der Schicht positioniert wird, die in unmittelbarem Kontakt mit dem Verkehrsfluß ist.

14. Verfahren nach Anspruch 13, wobei das Füllmaterial auf der Oberfläche zwischen endlosen Kantenkappen (75) gehalten wird, die parallel zum genannten Verkehrsfluß verlaufen und mit den Flanschen verbunden sind.

Revendications

1. Méthode de construction d'une surface de support d'une charge telle qu'un mur de retenue (47), une portée de plancher, une voie ou analogue du type comprenant une ou plusieurs



- feuilles ondulées pour l'essentiel quadrangulaires reliées entre elles, chaque feuille (1) étant du type qui présente en alternance un ou plusieurs sommets arrondis et creux arrondis reliés par des âmes linéaires, caractérisée en ce qu'elle comprend les opérations consistant :
- (a) à prévoir un adaptateur qui comprend aussi une feuille ondulée (6) pour l'essentiel quadrangulaire présentant des ondulations complémentaires de celles de la dite feuille (1), ledit adaptateur comportant des moyens (7,9,10) de fixation temporaire à la dite feuille (1) ;
 - (b) à utiliser ledit adaptateur pour placer la dite feuille (1) dans sa position désirée ; et
 - (c) à retirer le dit adaptateur.
2. Méthode de construction d'une surface de support d'une charge telle qu'un mur de retenue (47), une portée de plancher, une voie ou analogue, du type comprenant une ou plusieurs feuilles ondulées, pour l'essentiel quadrangulaires, reliées entre elles, chaque feuille (1) étant du type qui présente en alternance un ou plusieurs sommets arrondis et creux arrondis qui sont reliés par des âmes linéaires, caractérisée en ce que la dite méthode comprend les opérations qui consistent :
- (a) à prévoir un adaptateur qui comprend aussi une feuille ondulée (6) essentiellement quadrangulaire présentant des ondulations complémentaires de celles de la dite feuille (1), le dit adaptateur comportant des moyens (7,9,10) de fixation temporaire à la feuille (1) ;
 - (b) à utiliser le dit adaptateur pour disposer la dite feuille (1) approximativement dans la position désirée ;
 - (c) à retirer le dit adaptateur ;
 - (d) à placer une fixation (17) en communication temporaire avec le sommet (5) de la dite feuille (1) et à disposer de plus la dite feuille (1) dans sa position désirée par rapport au sol ; et
 - (e) à retirer la dite fixation ;
- la dite fixation comprenant :
- (a) un organe allongé (15) définissant un canal d'une largeur légèrement supérieure à la profondeur de l'un des dits sommets ou des dits creux ;
 - (b) un moyen (16) pour relier de façon amovible le dit organe allongé (15) à une source de source vibrante ;
3. Méthode selon la revendication 1 ou la revendication 2 dans laquelle, avant de placer la dite feuille (1) dans la dite position désirée, on dispose d'abord une feuille dans le sol selon l'angle désiré et à la profondeur désirée pour couper les racines d'arbre, pour casser les rochers et analogues, la feuille étant ensuite retirée, caractérisée en ce que la dite feuille est constituée par une feuille ondulée, pour l'essentiel quadrangulaire, dont les ondulations sont complémentaires de celles de la dite feuille (1).
4. Méthode de construction d'un revêtement du type présentant une ou plusieurs feuilles ondulées, pour l'essentiel quadrangulaires, reliées entre elles, chaque feuille (1) étant du type qui comprend en alternance un ou plusieurs sommets arrondis et creux arrondis, qui sont reliés par des âmes rectilignes, caractérisée en ce qu'elle comprend les opérations consistant :
- (a) à prévoir un adaptateur qui comprend aussi une feuille ondulée (6), essentiellement quadrangulaire, présentant des ondulations complémentaires de celles de la dite feuille (1), le dit adaptateur comportant des moyens (7,9,10) de fixation temporaire à la dite feuille (1) ;
 - (b) à utiliser le dit adaptateur pour placer la dite feuille (1) dans sa position désirée ;
 - (c) à retirer le dit adaptateur ;
 - (d) à creuser toute terre ou analogue qui peut se présenter à partir d'une face de la dite feuille (1) ;
 - (e) à recouvrir la dite face d'un entourage (18) ou analogue, le dit entourage pouvant être rempli d'un matériau robuste approprié.
5. Méthode de construction d'un revêtement du type comprenant une ou plusieurs feuilles ondulées, pour l'essentiel quadrangulaires, qui sont reliées entre elles, chaque feuille (1) étant du type présentant en alternance un ou plusieurs sommets arrondis et creux arrondis reliés par des âmes rectilignes, caractérisée en ce qu'elle comprend les opérations consistant :
- a) à prévoir un adaptateur qui comprend aussi une feuille ondulée (6) pour l'essentiel quadrangulaire présentant des ondulations complémentaires de celles de la dite feuille (1), le dit adaptateur comportant un moyen (7,9,10) de fixation temporaire à la dite feuille (1) ;
 - b) à utiliser le dit adaptateur pour placer la dite feuille (1) approximativement dans la position désirée ;
 - c) à retirer le dit adaptateur ;
 - d) à placer une fixation (17) en communication temporaire avec le sommet (5) de la dite feuille (1) et à placer en plus la dite feuille (1) dans sa position désirée par rapport au sol ;



- e) à retirer la dite fixation ;
 f) à creuser toute terre ou analogue pouvant se présenter à partir d'une face de la dite feuille ;
 g) à recouvrir la dite face par un entourage (18) ou analogue, ledit entourage pouvant être rempli par un matériau robuste (21) approprié ;
 la dite fixation comprenant :
 a) un organe allongé (15) définissant un canal d'une largeur légèrement supérieure à la profondeur de l'un des dits sommets ou fonds ;
 b) un moyen (16) pour fixer de façon détachable le dit organe allongé (15) à une source d'une source vibrante ; chaque côté du dit canal étant conçu de plus pour présenter un court prolongement, chaque court prolongement comprenant une feuille ondulée dont les ondulations sont complémentaires de celles de la feuille (1).
6. Méthode selon la revendication 4 ou la revendication 5 dans laquelle, avant de placer la dite feuille (1) dans la dite position désirée, on place d'abord dans le sol une autre feuille selon l'angle désiré et à la profondeur désirée de façon à couper les racines d'arbres, à briser les rochers et similaires, la dite autre feuille étant alors retirée, caractérisée en ce que la dite autre feuille comprend une feuille ondulée, pour l'essentiel quadrangulaire, dont les ondulations sont complémentaires de celles de la feuille (1).
7. Méthode selon l'une quelconque des revendications 1 à 6, caractérisée de plus par le fait que :
 au moins l'une des dites feuilles est traversée par au moins un organe d'ancrage du type consistant en une tige allongée (35) qui présente un moyen (26) en forme de lame pour engager la terre, relié de façon pivotante à une extrémité et qui peut se déplacer depuis une première position fermée jusqu'à une seconde position ouverte, et l'autre extrémité de la dite tige (35) étant destinée, dans ladite première position fermée, à être fixée à la dite feuille disposée dans le sol selon l'angle désiré et à la profondeur nécessaire ;
 on fait passer le dit moyen en forme de plaque (26) dans ladite seconde position ouverte ; et
 à la suite du passage dans ladite seconde position ouverte, ou simultanément à ce passage, on fixe la dite autre extrémité de la dite tige (35) à la dite feuille (1) de façon à empêcher pratiquement tout déplacement de la dite

feuille (1) sous l'influence du sol, ou d'une autre pression ou analogue ;
 et caractérisée de plus par le fait que le moyen d'engagement de la terre (26) comprend :

- a) une plaque (27), dont deux côtés se terminent en pointe en un point (28) ;
 b) l'extrémité de cette plaque (27) opposée au dit point (28) présentant une bifurcation qui procure des segments (80), chaque segment (80) étant incurvé pour présenter une inclinaison par rapport au plan de la dite plaque (27) ;
 c) des segments d'aile courbes (30a,b), l'un fixé à chaque côté de la dite plaque (27), chaque segment d'aile (30) suivant l'inclinaison prise par la dite plaque (27) et sa dite extrémité en forme de bifurcation ;
 d) une ouverture (29) ménagée dans la dite plaque (27) ;
 e) un moyen (32,33) pivotant autour d'un axe transversal à la dite ouverture (29) pour permettre à la dite plaque (27) de tourner selon un angle qui ne soit pas supérieur à environ 90 degrés.
8. Procédé selon l'une quelconque des revendications 1 à 6, caractérisé de plus par le fait que :
 au moins l'une des dites feuilles est traversée par au moins un organe d'ancrage du type consistant en une tige allongée (35) qui présente un moyen (52) en forme de lame destiné à engager la terre, qui présente une liaison pivotante à une extrémité et qui peut se déplacer depuis une première position fermée jusqu'à une seconde position ouverte, et l'autre extrémité de la dite tige (35) étant destinée à être fixée à la dite feuille disposée dans le sol selon l'angle désiré et à la profondeur nécessaire ;
 on fait passer le dit moyen en forme de plaque (26) dans ladite seconde position ouverte ; et
 à la suite du passage dans la dite seconde position ouverte, ou simultanément à ce passage, on fixe la dite autre extrémité de la dite tige (35) à la dite feuille (1) de façon à empêcher pratiquement tout déplacement de la dite feuille (1) sous l'influence du sol, d'une autre pression ou analogue ;
 et caractérisée de plus par le fait que le moyen d'engagement de la terre (52) comprend :
 a) une plaque (53), dont deux côtés se terminent en pointe en un point (54), l'autre extrémité de cette plaque (53) étant incurvée pour présenter une inclinaison par rap-



port au plan de la dite plaque (53) ;

b) une ouverture (57) ménagée dans la dite plaque (53) ; et

c) un moyen (58) pivotant autour d'un axe transversal à la dite ouverture pour permettre à la dite plaque (53) de tourner selon un angle qui ne soit pas supérieur à environ 90 degrés.

9. Méthode selon la revendication 7, dans laquelle on fixe d'abord le dit organe d'ancrage à une tige (35), on place ensuite un entourage extérieur (43) sur la dite tige (35), une extrémité du dit entourage (43) étant fixé de façon détachable à un premier adaptateur (42) qui maintient le dit organe d'ancrage dans la dite position fermée, l'autre extrémité du dit entourage extérieur (43) étant fixée à un second adaptateur (45) qui, à son tour, est fixé de façon détachable à une source d'une force d'impact répétitive, avant de faire traverser la dite feuille (1) par le dit élément d'ancrage, ou simultanément à cela.

10. Méthode selon la revendication 9 dans laquelle, avant la dite traversée de la dite feuille (1) par le dit organe d'ancrage, on ménage d'abord un canal dans la dite terre, pour recevoir ledit organe d'ancrage fixé à la dite tige (35) et le dit entourage extérieur (43).

11. Méthode selon la revendication 9 ou la revendication 10, caractérisée de plus en ce que le dit premier adaptateur (42) comprend :

a) un élément de corps cylindrique ;

b) un élément tronconique, s'étendant à partir d'une extrémité du dit élément de corps et coaxialement à lui, une partie du dit élément tronconique étant enlevée pour créer sur l'un de ses côtés une surface (38) plate pour l'essentiel ;

c) un élément de maintien (39) fixé au dit élément de corps et s'étendant à partir de la dite extrémité de façon à ménager une fente (40) entre ledit élément de maintien (39) et la dite surface plate (38) du dit élément tronconique ;

d) un tube fileté extérieurement (37) qui s'étend à partir de l'autre extrémité de l'élément de corps et coaxialement à lui ;

e) un trou (41) traversant toute la longueur longitudinale du dit premier adaptateur (42) ;

la dite tige (35) du dit élément d'ancrage pouvant traverser le dit trou (41) et la dite plaque (27) du dit organe d'ancrage pouvant être retenue dans la dite fente pour retenir le dit organe d'ancrage dans la dite première position fer-

mée.

12. Méthode de construction d'une voie ou analogue selon l'une quelconque des revendications 1 à 3 ou selon l'une quelconque des revendications 7 à 11 lorsqu'elles sont rattachées à l'une quelconque des revendications 1 à 3, caractérisée en ce qu'elle comprend les opérations consistant :

a) à adapter de plus la dite feuille (1,72) pour qu'elle présente un rebord étroit (73) sur toute la longueur de chacun de ses deux bords longitudinaux ;

b) à placer la feuille résultante de façon que ses ondulations soient disposées transversalement à la circulation qui empruntera la voie ou analogue ; toute feuille successive étant placée de façon que les rebords étroits (73) se chevauchent.

13. Méthode selon la revendication 12, caractérisée de plus en ce qu'un matériau de remplissage convenable est placé sur la surface de la dite feuille destinée à être en contact direct avec la circulation.

14. Méthode selon la revendication 13, dans laquelle le dit matériau de remplissage est retenu, sur la dite surface, entre les chapes de bordure (75) qui s'étendent parallèlement au dit écoulement et sont reliées aux dits rebords.

