

Description

This invention relates to Raman Converters and to Raman Laser Systems comprising such converters.

BACKGROUND:

Raman shifting devices include a Raman scattering medium, usually a high pressure gas cell. The scattering medium is chosen for conversion of the laser radiation to the desired wavelength. By using methane which has a frequency shift of 2916 cm^{-1} it is possible to convert the 1.06 micron radiation of the Neodymium:YAG laser to 1.54 micron which is an "eyesafe" wavelength.

Several conversion schemes are known in the prior art. For example in US Patent No. 3,668,420 issued to Vanderslice in 1972, the Raman converter used includes two mirrors which form a resonator for the shifted wavelength. In European Patent No. 63205, Bess and Ruger (1985), a single mirror is used to form a "semi resonator". A more comprehensive description is given by Parazzoli et al in IEEE Journal of Quantum Electronics Vol. 24 (1988) p. 872. In both of these designs the mirrors used must be aligned with respect to the pump source radiation in order to reflect the wavelength-shifted radiation to the region in which the pump source radiation is focused. This alignment is critical for the suppression of the competing process of stimulated Brillouin scattering and must be precisely maintained thereby complicating the mechanical construction of the converter.

In an attempt to overcome this drawback, Brueselbach and Whirst described in their international patent application WO 86/02784 a design in which the mirror of the Raman semi-resonator is also the output mirror of the laser source. This design does not guarantee however an automatic alignment of the Raman converter since the laser beam may deviate from the normal to the output mirror as a result of thermal effects in the active medium or in the Q-switching material or due to misalignment of the laser mirrors.

SUMMARY OF THE INVENTION

It is an object of this invention to overcome the above mentioned drawbacks and to provide a simple Raman converter which does not need precise alignment of optical elements.

A Raman converter according to the invention and a Raman laser comprising such a converter are defined in claims 1 and 9, respectively. Claim 10 is related to a method of Raman converting the wavelength of laser radiation.

The advantages are realized according to the present invention by using a backward Raman converter for Raman-shifting the beam of a pump laser.

This backward Raman converter includes a Raman medium in which the pump laser beam interacts with a Raman medium to generate Raman-shifted radiation, a dichroic coupler positioned between said pump laser and one side of said Raman medium for directing said pump laser beam to said Raman medium, and reflection means positioned on the other side of said Raman medium for reflecting said Raman-shifted radiation back into said Raman cell where it is amplified by interacting with said Raman medium and the incoming pump laser beam. The amplified Raman-shifted beam is coupled out of the system by said dichroic coupler.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic illustration of a Raman converter according to the present invention.

Figure 2 is a schematic illustration of a preferred embodiment of a Raman converter according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The following description, which refers to certain types of lasers, etc., is by way of illustration only and ought to be construed in a non-limitative manner.

A more detailed description of the invention will be given now with reference to Figure 1. A Raman converter 11 of the invention is illustrated in operation with a pump laser 10, which is a Neodymium:YAG laser producing a pump laser beam 12 at a wavelength of 1.06 micron. The dichroic coupler 16 consists of a glass plate with a dichroic dielectric coating transmitting the pump laser beam 12 and reflecting the beam at the Raman-shifted wavelength of 1.54 micron.

Raman cell 20 is a container with windows 24 and 26, containing methane gas 22 at a high pressure. Within said Raman cell 20, the pump laser beam interacts with molecules of the methane gas 22 to produce by stimulated Raman scattering Raman-shifted radiation 30 at a wavelength of 1.54 micron, which is reflected by reflector 33 back to the Raman cell 20 where it is amplified by backward stimulated Raman scattering of the incoming pump laser beam 12. The amplified Raman-shifted beam 36 is reflected by the dichroic coupler 16 as Raman-shifted output beam 38.

In this Raman converter the conversion is essentially performed by backward Raman scattering within the gas 22, this scattering being enhanced by a feedback of the forward scattered Raman-shifted radiation 30. This converter may be also interpreted as a kind of "semi-resonator" converter, as only a single reflector is used for feedback of the Raman-shifted radiation. A preferred embodiment of the invention comprises a retro-reflector as reflecting means rendering the converter insensitive to possible tilting of

the reflecting means or to possible wandering of the pump beam. In this way the mechanical construction of the converter is simplified.

Figure 2 illustrates a preferred embodiment of the invention. It is known that for a good conversion efficiency in a compact Raman shifting device it is necessary to focus the pump laser beam within the Raman cell to produce there the high power density needed for efficient Raman interactions. This is attained in the Raman converter of the present invention by focusing means comprising a pair of lenses 54 and 56 positioned one on each side of the Raman cell 20. Alternatively, lenses 54 and 56 may respectively replace the windows 24 and 26 of the Raman cell 20. The reflecting means is a corner reflector 58 consisting of a glass prism with three mutually perpendicular faces. Three total internal reflections of the incident beam at these faces result in retro-reflection of that beam. An alternative to this type of retro-reflector is the hollow retro-reflector consisting of three mirrors mounted perpendicular to each other. In operation, the pump laser beam 12 transmitted through the dichroic coupler 16 is focused by lens 54 to a focal region 60 within the Raman cell 20 to produce there a high power density of the order of several Gigawatts per square centimeter for an efficient Raman interaction to take place. It is in this focal region 60 that the Raman-shifted radiation 62 is generated. This radiation diverges and is collimated by the lens 56 to collimated beam 64 that is reflected backwards by corner reflector 58, and after such reflection, is focused by lens 56 to the focal region 60 where it is amplified by backward stimulated Raman scattering of the pump laser beam 12. The amplified Raman-shifted beam 66 diverges and is collimated by lens 54 to collimated beam 68 which is reflected by the dichroic coupler 16 resulting in Raman-shifted output beam 69.

In operation, even a weak reflected Raman-shifted radiation 62 is sufficient to enhance backward Raman scattering in the focal region. As a result, most of the Raman scattering is in the backward direction. In this way the pump laser beam 12 is attenuated before reaching the focal point, thereby enabling operation of the converter at higher energies before the occurrence of electrical breakdown in the focal region 60. For some applications this may be a significant advantage compared with the prior art designs.

The advantage of using a corner reflector as reflecting means is that it does not need exact alignment and irrespective of its orientation it reflects the collimated beam 64 back on itself so that it is focused exactly to the focal region 60 for an additional interaction. As was verified experimentally this insensitivity to misalignment results in a significant improvement in the energy stability of the Raman shifted output beam. According to the invention, reflecting means such as a mirror, a porro prism or other types

of roof reflectors known in the art can be used.

Additional improvements can be applied to the Raman converter:

As is well known, the efficiency of Raman-shifting devices depends strongly on the competition between the Raman scattering and the Brillouin scattering processes. Depending on the type of Raman medium used and on the wavelength of the pump laser, it may be sometimes advantageous to add between the Raman cell 20 and reflecting means 33 in Figure 1 a filter that removes the remaining radiation at the pump wavelength thereby preventing its back reflection to the focal region 60. Such a feedback at the pump wavelength is undesirable since it may enhance the Stimulated Brillouin scattering thereby reducing the Raman conversion efficiency. Such an undesirable feedback at the pump wavelength can be prevented by using a suitable absorber, or by a reflective filter or by the use of dispersive elements such as a grating or prism. If a reflective filter is positioned between Raman cell 20 and reflecting means 33 in Figure 1, the reflection at the pump wavelength can be utilized as a secondary output beam thereby providing a dual wavelength laser system. Another solution can be provided by using as reflecting means 33 a reflector which selectively reflects the Stokes shifted radiation at 1.54 micron but not the radiation at 1.06 micron.

In another modification of the preferred embodiment, a phase conjugating reflector is used as the reflecting means 58 in Figure 2. Like the corner reflector, the phase conjugating reflector provides retro-reflection of the Raman shifted radiation 62. Its advantage is that, due to a reversal of the radiation wavefront, any wavefront deformation induced by the first passage of the Raman shifted radiation through the focal region 60 within the Raman medium, is cancelled after a second pass along the same path. In this way an undistorted output beam is obtained even in cases where the Raman medium induces optical distortions due to its heating for example. Various types of phase-conjugating reflectors are known in the prior art. In such devices a phase-conjugated beam is produced by a nonlinear optical interaction of the incident beam with the phase-conjugating material. Stimulated Brillouin scattering (SBS) is one of the nonlinear interactions known in the prior art to produce phase conjugation of laser beams. This type of phase conjugation can be easily combined with the converter described in Figure 2. This can be done for example by replacing window 26 with a short focus concave mirror which focuses the Raman-shifted radiation 62 into a small focal point within the gas from which stimulated Brillouin backscattering provides the phase-conjugate reflection.

A Raman converter was built in accordance with Figure 2. The pump laser used was a Q-switched Nd:YAG laser producing 120 millijoules per pulse of

16 nsec of 1.06 micron radiation. Using high pressure methane as the Raman medium, a corner reflector as the reflecting means and a dichroic mirror as the dichroic coupler, a Raman shifted output beam was generated with 40 millijoules per pulse.

The invention provides a Raman converter that is insensitive to optical misalignment or to wandering of the pump laser beam.

Claims

1. A Raman converter for converting a laser beam (12) at a first wavelength, generated in a separate laser module (10), into a Raman-shifted beam (38) at a second wavelength, said Raman converter (11) being external to said laser module and comprising a sequence of a dichroic coupler (16), a Raman medium (22) and reflecting means (33) positioned optically aligned after the laser module, so that the laser beam passes first through the dichroic coupler, which directs the laser beam into the Raman medium, thus scattering Raman shifted radiation in a forward and a backward direction, said reflecting means returning the forward scattered radiation (30) to the Raman medium, thus increasing the intensity of the backward scattered Raman-shifted radiation (36), which is coupled out by the dichroic coupler.
2. A Raman converter according to claim 1, wherein the reflecting means are retro-reflecting means or phase-conjugating means.
3. A Raman converter according to claim 1, wherein focusing means are provided for focusing the laser radiation to a focal region within said Raman medium, optical means being disposed between said Raman medium and said reflection means for collimating the Raman-shifted radiation scattered forward from said focal region to a collimated beam and for focusing said collimated beam after its reflection by the reflection means, to said focal region.
4. A Raman converter according to claim 1, wherein the first wavelength is about 1.06 micron, and the second wavelength is about 1.54 micron and where said gas is methane.
5. A Raman converter according to claim 1, wherein a filter is provided between said Raman medium and said reflection means to avoid return of laser radiation at said first wavelength to said Raman medium.
6. A Raman converter according to claim 1, wherein said reflection means selectively reflects laser radiation at said second wavelength and not at said first wavelength.
7. A Raman converter according to claim 1, wherein said reflecting means is the only feedback element used.
8. A Raman converter according to claim 1, wherein said dichroic coupler is a mirror substantially reflecting at one of the said first and second wavelengths and substantially transmitting the other wavelength.
9. A Raman laser system comprising a Raman converter according to any one of the preceding claims, and a pump laser for producing said laser radiation.
10. A method of Raman converting the wavelength of laser radiation which comprises:
 - a. generating laser radiation at a first wavelength,
 - b. directing said laser radiation via a dichroic coupler into a Raman medium, both being external to said laser radiation sources,
 - c. converting in said Raman medium, by stimulated Raman scattering, the energy of said laser radiation to Raman-shifted radiation at a second wavelength scattered substantially in the forward and backward directions relative to said laser beam,
 - d. reflecting the forward scattered Raman-shifted radiation back into said Raman medium thereby enhancing the backward scattering of Raman-shifted radiation,
 - e. coupling out, by said dichroic coupler, the backward scattered Raman-shifted radiation.
11. A method according to claim 10, where the said laser radiation directed to said Raman medium is focused to a focal region therein, and where the reflected forward scattered Raman-shifted radiation is focused again to said focal region.
12. A method according to claim 11, where said focusing is performed by two lenses or lens system, one at each side of the Raman medium.
13. A method according to claim 11, where the Raman-shifted radiation is reflected by a retro-reflector, by a phase-conjugating reflector, or by a roof reflector.
14. A method according to claim 11, where the Raman medium is a gas suitable for Raman scattering.



16 nsec of 1.06 micron radiation. Using high pressure methane as the Raman medium, a corner reflector as the reflecting means and a dichroic mirror as the dichroic coupler, a Raman shifted output beam was generated with 40 millijoules per pulse.

The invention provides a Raman converter that is insensitive to optical misalignment or to wandering of the pump laser beam.

Claims

1. A Raman converter for converting a laser beam (12) at a first wavelength, generated in a separate laser module (10), into a Raman-shifted beam (38) at a second wavelength, said Raman converter (11) being external to said laser module and comprising a sequence of a dichroic coupler (16), a Raman medium (22) and reflecting means (33) positioned optically aligned after the laser module, so that the laser beam passes first through the dichroic coupler, which directs the laser beam into the Raman medium, thus scattering Raman shifted radiation in a forward and a backward direction, said reflecting means returning the forward scattered radiation (30) to the Raman medium, thus increasing the intensity of the backward scattered Raman-shifted radiation (36), which is coupled out by the dichroic coupler.
2. A Raman converter according to claim 1, wherein the reflecting means are retro-reflecting means or phase-conjugating means.
3. A Raman converter according to claim 1, wherein focusing means are provided for focusing the laser radiation to a focal region within said Raman medium, optical means being disposed between said Raman medium and said reflection means for collimating the Raman-shifted radiation scattered forward from said focal region to a collimated beam and for focusing said collimated beam after its reflection by the reflection means, to said focal region.
4. A Raman converter according to claim 1, wherein the first wavelength is about 1.06 micron, and the second wavelength is about 1.54 micron and where said gas is methane.
5. A Raman converter according to claim 1, wherein a filter is provided between said Raman medium and said reflection means to avoid return of laser radiation at said first wavelength to said Raman medium.
6. A Raman converter according to claim 1, wherein said reflection means selectively reflects laser radiation at said second wavelength and not at said first wavelength.
7. A Raman converter according to claim 1, wherein said reflecting means is the only feedback element used.
8. A Raman converter according to claim 1, wherein said dichroic coupler is a mirror substantially reflecting at one of the said first and second wavelengths and substantially transmitting the other wavelength.
9. A Raman laser system comprising a Raman converter according to any one of the preceding claims, and a pump laser for producing said laser radiation.
10. A method of Raman converting the wavelength of laser radiation which comprises:
 - a. generating laser radiation at a first wavelength,
 - b. directing said laser radiation via a dichroic coupler into a Raman medium, both being external to said laser radiation sources,
 - c. converting in said Raman medium, by stimulated Raman scattering, the energy of said laser radiation to Raman-shifted radiation at a second wavelength scattered substantially in the forward and backward directions relative to said laser beam,
 - d. reflecting the forward scattered Raman-shifted radiation back into said Raman medium thereby enhancing the backward scattering of Raman-shifted radiation,
 - e. coupling out, by said dichroic coupler, the backward scattered Raman-shifted radiation.
11. A method according to claim 10, where the said laser radiation directed to said Raman medium is focused to a focal region therein, and where the reflected forward scattered Raman-shifted radiation is focused again to said focal region.
12. A method according to claim 11, where said focusing is performed by two lenses or lens system, one at each side of the Raman medium.
13. A method according to claim 11, where the Raman-shifted radiation is reflected by a retro-reflector, by a phase-conjugating reflector, or by a roof reflector.
14. A method according to claim 11, where the Raman medium is a gas suitable for Raman scattering.



Patentansprüche

1. Ramankonverter zum Umwandeln eines Laserbündels (12) mit einer ersten Wellenlänge, das in einem separaten Lasermodul (10) erzeugt wird, in ein ramanverschobenes Bündel (38) mit einer zweiten Wellenlänge, wobei der Ramankonverter (11) außerhalb des Lasermoduls ist und eine Aufeinanderfolge von einem dichroitischen Koppler (16), einem Ramanmedium (22) und reflektierenden Mitteln (33) umfaßt, die optisch fluchtend nach dem Lasermodul positioniert sind, so daß das Laserbündel zunächst durch den dichroitischen Koppler hindurchgeht, welcher das Laserbündel in das Ramanmedium richtet, so daß demgemäß ramanverschobene Strahlung in einer Vorwärts- und einer Rückwärtsrichtung gestreut wird, wobei das reflektierende Mittel die vorwärtsgestreute Strahlung (30) zu dem Ramanmedium zurückschickt, so daß demgemäß die Intensität der rückwärtsgestreuten ramanverschobenen Strahlung (36), welche durch den dichroitischen Koppler ausgekoppelt wird, erhöht wird.
2. Ramankonverter gemäß Anspruch 1, worin die reflektierenden Mittel retroreflektierende Mittel oder phasenkonjugierende Mittel sind.
3. Ramankonverter gemäß Anspruch 1, worin fokussierende Mittel zum Fokussieren der Laserstrahlung zu einem Fokalbereich innerhalb des Ramanmediums vorgesehen sind, wobei optische Mittel zwischen dem Ramanmedium und den Reflexionsmitteln zum Kollimieren der von dem Fokalbereich nach vorwärts gestreuten ramanverschobenen Strahlung zu einem Parallelstrahlenbündel und zum Fokussieren des Parallelstrahlenbündels nach seiner Reflexion durch die Reflexionsmittel zu dem Fokalbereich angeordnet sind.
4. Ramankonverter gemäß Anspruch 1, worin die erste Wellenlänge etwa 1,06 Mikron ist und die zweite Wellenlänge etwa 1,54 Mikron ist, und das Gas Methan ist.
5. Ramankonverter gemäß Anspruch 1, worin ein Filter zwischen dem Ramanmedium und dem Reflexionsmittel zum Vermeiden eines Zurückschickens der Laserstrahlung mit der ersten Wellenlänge zu dem Ramanmedium vorgesehen ist.
6. Ramankonverter gemäß Anspruch 1, worin die Reflexionsmittel selektiv Laserstrahlung mit der zweiten Wellenlänge und nicht mit der ersten Wellenlänge reflektieren.

7. Ramankonverter gemäß Anspruch 1, worin das Reflexionsmittel das einzige verwendete Rückkopplungselement ist.

8. Ramankonverter gemäß Anspruch 1, worin der dichroitische Koppler ein Spiegel ist, der im wesentlichen bei einer von der ersten und zweiten Wellenlänge reflektiert und die andere Wellenlänge im wesentlichen durchläßt.

9. Ramanlasersystem, umfassend einen Ramankonverter gemäß irgendeinem der vorhergehenden Ansprüche und einen Pumplaser zum Erzeugen der Laserstrahlung.

10. Verfahren des Ramankonvertierens der Wellenlänge von Laserstrahlung, welches umfaßt:

- a. Erzeugen von Laserstrahlung mit einer ersten Wellenlänge,
- b. Richten der Laserstrahlung über einen dichroitischen Koppler in ein Ramanmedium, wobei beide außerhalb der Laserstrahlungsquellen sind,
- c. Umwandeln der Energie der Laserstrahlung in dem Ramanmedium durch stimulierte Ramanstreuung in ramanverschobene Strahlung mit einer zweiten Wellenlänge, die im wesentlichen in der Vorwärts- und Rückwärtsrichtung relativ zu dem Laserbündel gestreut ist,
- d. Reflektieren der vorwärtsgestreuten ramanverschobenen Strahlung zurück in das Ramanmedium, so daß dadurch die Rückwärtstreuung der ramanverschobenen Strahlung erhöht wird,
- e. Auskoppeln der rückwärtsgestreuten ramanverschobenen Strahlung durch den dichroitischen Koppler.

11. Verfahren gemäß Anspruch 10, worin die zu dem Ramanmedium gerichtete Laserstrahlung auf einen Fokalbereich darin fokussiert wird, und worin die reflektierte vorwärtsgestreute ramanverschobene Strahlung wieder auf den Fokalbereich fokussiert wird.

12. Verfahren gemäß Anspruch 11, worin das Fokussieren durch zwei Linsen oder Linsensystem, eine bzw. eines auf jeder Seite des Ramanmediums, ausgeführt wird.

13. Verfahren gemäß Anspruch 11, worin die ramanverschobene Strahlung mittels eines Retroreflektors, mittels eines phasenkonjugierenden Reflektors oder mittels eines Dachreflektors reflektiert wird.

14. Verfahren gemäß Anspruch 11, worin das



Ramanmedium ein für Ramanstreuung geeignetes Gas ist.

Revendications

1. Convertisseur Raman pour convertir un faisceau laser (12) d'une première longueur d'onde, engendré dans un module laser séparé (10), en un faisceau décalé par effet Raman (38) d'une deuxième longueur d'onde, ledit convertisseur Raman (11) étant extérieur audit module laser et comprenant une séquence formée d'un coupleur dichroïque (16), d'un milieu Raman (22) et de moyens de réflexion (33) positionnés en alignement optique après le module laser, de sorte que le faisceau laser traverse d'abord le coupleur dichroïque, qui dirige le faisceau laser dans le milieu Raman, dispersant ainsi le rayonnement décalé par effet Raman vers l'avant et vers l'arrière, lesdits moyens de réflexion renvoyant le rayonnement dispersé vers l'avant (30), vers le milieu Raman, augmentant ainsi l'intensité du rayonnement décalé par effet Raman et dispersé vers l'arrière (36), qui est capté à la sortie par le coupleur dichroïque.
2. Convertisseur Raman suivant la revendication 1, dans lequel les moyens de réflexion sont des moyens rétro-réfléchissants ou des moyens de conjugaison de phase.
3. Convertisseur Raman suivant la revendication 1, dans lequel des moyens de focalisation sont prévus pour concentrer le rayonnement laser vers une région focale à l'intérieur du dit milieu Raman, des moyens optiques étant disposés entre ledit milieu Raman et lesdits moyens de réflexion pour collimater le rayonnement décalé par effet Raman, dispersé vers l'avant à partir de ladite région focale, en un faisceau collimaté et pour focaliser ledit faisceau collimaté, après sa réflexion par les moyens de réflexion, vers ladite région focale.
4. Convertisseur Raman suivant la revendication 1, dans lequel la première longueur d'onde est de 1,06 μm environ et la deuxième longueur d'onde est de 1,54 μm environ, et ledit gaz est du méthane.
5. Convertisseur Raman suivant la revendication 1, dans lequel un filtre est prévu entre ledit milieu Raman et lesdits moyens de réflexion, pour éviter le retour du rayonnement laser ayant ladite première longueur d'onde vers ledit milieu Raman.
6. Convertisseur Raman suivant la revendication 1,
7. Convertisseur Raman suivant la revendication 1, dans lequel lesdits moyens de réflexion constituent le seul élément de réaction utilisé.
8. Convertisseur Raman suivant la revendication 1, dans lequel ledit coupleur dichroïque est un miroir qui est sensiblement réfléchissant à une desdites première et deuxième longueurs d'onde et qui transmet sensiblement l'autre longueur d'onde.
9. Système de laser Raman comprenant un convertisseur Raman suivant une quelconque des revendications précédentes, et un laser à pompe pour produire ledit rayonnement laser.
10. Méthode de conversion Raman de la longueur d'onde d'un rayonnement laser, qui comprend :
 - (a) la génération d'un rayonnement laser à une première longueur d'onde,
 - (b) la direction dudit rayonnement laser, par l'intermédiaire d'un coupleur dichroïque, dans un milieu Raman, ces deux éléments étant extérieurs auxdites sources de rayonnement laser,
 - (c) la conversion dans ledit milieu Raman, par dispersion Raman stimulée, de l'énergie dudit rayonnement laser en rayonnement décalé par effet Raman à une deuxième longueur d'onde et dispersé sensiblement dans les directions avant et arrière par rapport audit faisceau laser,
 - (d) la réflexion du rayonnement décalé par effet Raman et dispersé vers l'avant, en retour dans ledit milieu Raman afin de renforcer la dispersion vers l'arrière du rayonnement décalé par effet Raman, et
 - (e) le couplage de sortie, par ledit coupleur dichroïque, du rayonnement décalé par effet Raman et dispersé vers l'arrière.
11. Méthode suivant la revendication 10, dans laquelle ledit rayonnement dirigé vers ledit milieu Raman est focalisé à une région focale dans ce dernier, et dans laquelle le rayonnement décalé par effet Raman dispersé vers l'avant et réfléchi est focalisé à nouveau à la dite région focale.
12. Méthode suivant la revendication 11 dans laquelle ladite focalisation est effectuée par deux lentilles ou un système de lentilles, une de chaque côté du milieu Raman.
13. Méthode suivant la revendication 11, dans laquelle



le le rayonnement décalé par effet Raman est réfléchi par un rétro-rélecteur, par un réflecteur à conjugaison de phase ou par un réflecteur de toit.

14. Méthode suivant la revendication 11, dans laquelle le milieu Raman est un gaz convenant pour une dispersion par effet Raman.

5

10

15

20

25

30

35

40

45

50

55

7