(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
4 April 2002 (04.04.2002)

PCT

(10) International Publication Number
WO 02/27509 A3

(51) International Patent Classification[7]: G06F 13/38

(21) International Application Number: PCT/US01/30199

(22) International Filing Date:
27 September 2001 (27.09.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/675,873 29 September 2000 (29.09.2000) US

(71) Applicant *(for all designated States except US)*: **INTEL CORPORATION** [US/US], 2200 Mission College Boulevard, Santa Clara, CA 95052 (US).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **ESCHMANN, Michael** [US/US]; 104 Egloff Circle, Folsom, CA 95630 (US) **DERR, Michael** [US/US]; 1261 Morning Song Court, El Dorado Hills, CA 95762 (US).


(74) Agents: **MALLIE, Michael, J.** et al.; Blakely Sokoloff Taylor & Zafman, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US)

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: STREAMLINING ATA DEVICE INITIALIZATION



(57) Abstract: The invention includes a platform having a controller coupled to a central processing unit through a system bus. The platform also includes a register device coupled between the central processing unit and the controller. Moreover, the platform also includes a bus coupled to the controller having an end that is adapted to receive a device. The register device includes a depth that is adapted to hold all instruction packets from the central processing unit without presenting delays due to full conditions.

WO 02/27509 A3

patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:
13 June 2002

For two-letter codes and other abbreviations refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette