WHAT IS CLAIMED IS:

1. A carrier for holding a plurality of containers, the carrier comprising:

a plurality of panels comprising at least one central panel and at least one attachment panel configured to receive a portion of one or more containers of the plurality of containers,

the at least one central panel comprises a plurality of openings and is for being positioned between and attached to adjacent containers of the plurality of containers,

the plurality openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.

2. The carrier of claim 1, wherein the at least one central panel is for being adhered to adjacent containers of the plurality of containers.

3. The carrier of claim 1, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

4. The carrier of claim 3, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

5. The carrier of claim 4, wherein the first plurality openings comprises a first front row of openings and a second front row of openings spaced apart from the first front row of openings, and the second plurality of openings comprises a first back row of openings and a second back row of openings spaced apart from the first back row of openings.

6. The carrier of claim 5, wherein the front central panel is foldably connected to the back central panel at a fold line, the first front row of openings is spaced a first distance from the fold line, and

the second front row of openings is spaced a second distance from the fold line, the second distance is greater than the first distance.

7. The carrier of claim 6, wherein the first back row of openings is spaced a third distance from the fold line and the second back row of openings is spaced a fourth distance from the fold line, the fourth distance is greater than the third distance.

8. The carrier of claim 7, wherein the second distance is greater than the fourth distance, the fourth distance is greater than the first distance, and the first distance is greater than the third distance.

9. The carrier of claim 4, wherein the first plurality of openings are offset from the second plurality of openings.

10. The carrier of claim 9, wherein the front central panel and the back central panel are in contact such that a respective portion of the back central panel is exposed through the first plurality of openings and a respective portion of the front central panel is exposed through the second plurality of openings, the respective portion of the front central panel and the respective portion of the back central panel are for receiving an adhesive.

11. The carrier of claim 1, wherein the at least one attachment panel comprises a plurality of cuts that define edges for engaging respective containers of the plurality of containers.

12. The carrier of claim 11, wherein the plurality of cuts defines a respective plurality of container retention tabs.

13. The carrier of claim 12, wherein the plurality of cuts are for receiving at least a portion of respective containers of the plurality of containers therethrough.

14. The carrier of claim 1, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

15. The carrier of claim 14, wherein the at least one handle opening comprises a longitudinal section and at least one lateral section diverging away from the longitudinal section.

16. The carrier of claim 15, wherein the plurality of panels further comprises a top panel overlying at least a portion of the at least one attachment panel.

17. The carrier of claim 16, wherein the top panel comprises at least one handle feature aligned with the at least one handle opening.

18. The carrier of claim 17, wherein the at least one handle feature comprises a first handle feature and a second handle feature, and the at least one handle opening comprises a first handle opening and a second handle opening.

19. The carrier of claim 18, wherein at least one of the first handle feature and the second handle feature comprises a plurality of lines of weakening.

20. A blank for forming a carrier for holding a plurality of containers, the blank comprising:

a plurality of panels comprising at least one central panel and at least one attachment panel configured to receive a portion of one or more containers of the plurality of containers,

the at least one central panel comprises a plurality of openings and is for being positioned between and attached to adjacent containers of the plurality of containers when the carrier is formed from the blank,

the plurality openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.

21. The blank of claim 20, wherein the at least one central panel is for being adhered to adjacent containers of the plurality of containers.

22. The blank of claim 20, wherein the first row of openings is spaced a first distance from a longitudinal centerline of the blank, and the second row of openings is spaced a second distance from the longitudinal centerline of the blank, the second distance is greater than the first distance.

23. The blank of claim 22, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings

is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings.

24. The blank of claim 23, wherein the first plurality openings comprises a first front row of openings and a second front row of openings spaced apart from the first front row of openings, and the second plurality of openings comprises a first back row of openings and a second back row of openings spaced apart from the first back row of openings.

25. The blank of claim 24, wherein the front central panel is foldably connected to the back central panel at a fold line, the first front row of openings is spaced a first distance from the fold line, and the second front row of openings is spaced a second distance from the fold line, the second distance is greater than the first distance.

26. The blank of claim 25, wherein the first back row of openings is spaced a third distance from the fold line and the second back row of openings is spaced a fourth distance from the fold line, the fourth distance is greater than the third distance.

27. The blank of claim 26, wherein the second distance is greater than the fourth distance, the fourth distance is greater than the first distance, and the first distance is greater than the third distance.

28. The blank of claim 23, wherein the first plurality of openings are for being positioned offset from the second plurality of openings when the carrier is formed from the blank.

29. The blank of claim 20, wherein the at least one attachment panel comprises a plurality of cuts that define edges for engaging respective containers of the plurality of containers.

30. The blank of claim 29, wherein the plurality of cuts defines a respective plurality of container retention tabs.

31. The blank of claim 20, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

32. The blank of claim 31, wherein the at least one handle opening comprises a longitudinal section and at least one lateral section diverging away from the longitudinal section.

33. The blank of claim 32, wherein the plurality of panels further comprises a top panel.

34. The blank of claim 33, wherein the top panel comprises at least one handle feature for being positioned in alignment with the at least one handle opening when the carrier is formed from the blank.

35. The blank of claim 34, wherein the at least one handle feature comprises a first handle feature and a second handle feature, and the at least one handle opening comprises a first handle opening and a second handle opening.

36. The blank of claim 35, wherein at least one of the first handle feature and the second handle feature comprises a plurality of lines of weakening.

37. A method of forming a carrier for holding a plurality of containers, the method comprising:

obtaining a blank comprising a plurality of panels comprising at least one central panel and at least one attachment panel configured to receive a portion of one or more containers of the plurality of containers, the at least one central panel comprises a plurality of openings, the plurality openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings;

folding the plurality of panels such that the at least one central panel is positioned between adjacent containers of the plurality of containers; and

attaching at least one container of the plurality of containers to the at least one central panel.

38. The method of claim 37, wherein the at least one central panel is adhered to adjacent containers of the plurality of containers.

39. The method of claim 37, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

40. The method of claim 39, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

41. The method of claim 40, wherein the first plurality openings comprises a first front row of openings and a second front row of openings spaced apart from the first front row of openings, and the second plurality of openings comprises a first back row of openings and a second back row of openings spaced apart from the first back row of openings.

42. The method of claim 41, wherein the front central panel is foldably connected to the back central panel at a fold line, the first front row of openings is spaced a first distance from the fold line, and the second front row of openings is spaced a second distance from the fold line, the second distance is greater than the first distance.

43. The method of claim 42, wherein the first back row of openings is spaced a third distance from the fold line and the second back row of openings is spaced a fourth distance from the fold line, the fourth distance is greater than the third distance.

44. The method of claim 43, wherein the second distance is greater than the fourth distance, the fourth distance is greater than the first distance, and the first distance is greater than the third distance.

45. The method of claim 41, wherein the first plurality of openings are offset from the second plurality of openings.

46. The method of claim 45, wherein the front central panel and the back central panel are in contact such that a respective portion of the back central panel is exposed through the first plurality of openings and a respective portion of the front central panel is exposed through the second plurality of openings, the respective portion of the front central panel and the respective portion of the back central panel are for receiving an adhesive.

47. The method of claim 37, wherein the at least one attachment panel comprises a plurality of cuts that define edges for engaging respective containers of the plurality of containers.

48. The method of claim 47, wherein the plurality of cuts defines a respective plurality of container retention tabs.

49. The method of claim 48, wherein the plurality of cuts are for receiving at least a portion of respective containers of the plurality of containers therethrough.

50. The method of claim 37, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

51. The method of claim 50, wherein the at least one handle opening comprises a longitudinal section and at least one lateral section diverging away from the longitudinal section.

52. The method of claim 51, wherein the plurality of panels further comprises a top panel overlying at least a portion of the at least one attachment panel.

53. The method of claim 52, wherein the top panel comprises at least one handle feature aligned with the at least one handle opening.

54. The method of claim 53, wherein the at least one handle feature comprises a first handle feature and a second handle feature, and the at least one handle opening comprises a first handle opening and a second handle opening.

55. The method of claim 54, wherein at least one of the first handle feature and the second handle feature comprises a plurality of lines of weakening.

56. A package comprising:

a plurality of containers; and

a carrier for holding the plurality of containers, the carrier comprising:

a plurality of panels comprising at least one central panel and at least one attachment panel receiving a portion of one or more containers of the plurality of containers, the at least one central panel comprises a plurality of openings and is positioned between and

attached to adjacent containers of the plurality of containers, the plurality openings comprises a first row of openings and a second row of openings spaced apart from the first row of openings.

57. The package of claim 56, wherein the at least one central panel is adhered to adjacent containers of the plurality of containers.

58. The package of claim 56, wherein the first row of openings is spaced a first distance from a bottom edge of the at least one central panel, and the second row of openings is spaced a second distance from the bottom edge of the at least one central panel, the second distance is greater than the first distance.

59. The package of claim 58, wherein the at least one central panel is a front central panel, the plurality of panels further comprises a back central panel, the at least one attachment panel is a front attachment panel foldably connected to the front central panel, and the plurality of panels further comprises a back attachment panel foldably connected to the back central panel, the plurality of openings is a first plurality of openings in the front central panel, and the back central panel comprises a second plurality of openings such that the first plurality of openings are in communication with the back central panel and the second plurality of openings are in communication with the front central panel.

60. The package of claim 59, wherein the first plurality openings comprises a first front row of openings and a second front row of openings spaced apart from the first front row of openings, and the second plurality of openings comprises a first back row of openings and a second back row of openings spaced apart from the first back row of openings.

61. The package of claim 60, wherein the front central panel is foldably connected to the back central panel at a fold line, the first front row of openings is spaced a first distance from the fold line, and the second front row of openings is spaced a second distance from the fold line, the second distance is greater than the first distance.

62. The package of claim 61, wherein the first back row of openings is spaced a third distance from the fold line and the second back row of openings is spaced a fourth distance from the fold line, the fourth distance is greater than the third distance.

63. The package of claim 62, wherein the second distance is greater than the fourth distance, the fourth distance is greater than the first distance, and the first distance is greater than the third distance.

64. The package of claim 59, wherein the first plurality of openings are offset from the second plurality of openings.

65. The package of claim 64, wherein the front central panel and the back central panel are in contact such that a respective portion of the back central panel is exposed through the first plurality of openings and a respective portion of the front central panel is exposed through the second plurality of openings, the respective portion of the front central panel and the respective portion of the back central panel are for receiving an adhesive.

66. The package of claim 56, wherein the at least one attachment panel comprises a plurality of cuts that define edges that engage respective containers of the plurality of containers.

67. The package of claim 66, wherein the plurality of cuts defines a respective plurality of container retention tabs.

68. The package of claim 67, wherein the plurality of cuts receive at least a portion of respective containers of the plurality of containers therethrough.

69. The package of claim 56, wherein at least one of the at least one central panel and the at least one attachment panel includes at least one handle opening.

70. The package of claim 69, wherein the at least one handle opening comprises a longitudinal section and at least one lateral section diverging away from the longitudinal section.

71. The package of claim 70, wherein the plurality of panels further comprises a top panel overlying at least a portion of the at least one attachment panel.

72. The package of claim 71, wherein the top panel comprises at least one handle feature aligned with the at least one handle opening.

73. The package of claim 72, wherein the at least one handle feature comprises a first handle feature and a second handle feature, and the at least one handle opening comprises a first handle opening and a second handle opening.

74. The package of claim 73, wherein at least one of the first handle feature and the second handle feature comprises a plurality of lines of weakening.