

**TITLE: SMALL CORE GENERATION AND ANALYSIS AT-BIT AS LWD
TOOL**

INVENTOR: KUMAR, Sunil

FIELD OF THE DISCLOSURE

[0001] This disclosure generally relates to the testing and sampling of underground formations or reservoirs. More specifically, this disclosure relates to preparing a core sample without interrupting drilling operations, and, in particular, processing the core sample for analysis of fluids using extraction and/or encapsulation methods and apparatuses.

BACKGROUND OF THE DISCLOSURE

[0002] Hydrocarbons, such as oil and gas, often reside in porous subterranean geologic formations. Often, it can be advantageous to use a coring tool to obtain representative samples of rock taken from the wall of the wellbore intersecting a formation of interest. Rock samples obtained through vertical and side wall coring are generally referred to as "core samples." Analysis and study of core samples enables engineers and geologists to assess important formation parameters such as the reservoir storage capacity (porosity), the flow potential (permeability) of the rock that makes up the formation, the composition of the recoverable hydrocarbons or minerals that reside in the formation, and the irreducible water saturation level of the rock. These estimates are crucial to subsequent design and implementation of the well completion program that enables production of selected formations and zones that are determined to be economically attractive based on the data obtained from the core sample

[0003] Coring typically requires drilling to be stopped after a core sample is formed, so that the core sample may be brought to the surface. Core samples are often tested after being brought to the surface, however, travel to the surface may result in contamination of or damage to the core samples as they travel to the surface. The drilling stoppage takes time and effort that could be reduced if drilling could

continue while core samples were taken. It would be advantageous to perform uninterrupted drilling while coring. It would also be advantageous to perform testing on core samples in situ without requiring travel to the surface or to protect core samples from encounters with damaging objects and contaminating fluids while traveling to the surface. The present disclosure provides apparatuses and methods for preparing core samples for in situ analysis and/or protecting the core samples for travel to the surface while drilling remains uninterrupted.

SUMMARY OF THE DISCLOSURE

[0004] In aspects, the present disclosure generally relates to the testing and sampling of underground formations or reservoirs. More specifically, this disclosure relates to preparing a core sample without interrupting drilling operations, and, in particular, processing the core sample for analysis of fluids using extraction and/or encapsulation methods and apparatuses.

[0005] One embodiment according to the present disclosure may include an apparatus for forming a sample in a wellbore, comprising: a drill bit configured to form a core; and at least one retractable cutter internal to the drill bit configured to cut the sample from the core.

[0006] Another embodiment according to the present disclosure may include an apparatus for encapsulating a sample in a wellbore, comprising: a drill bit configured to form a core; a chamber configured to receive the sample from the core; and an encapsulator operably coupled to the chamber and configured to at least partially encapsulate at least part of the sample in an encapsulating material.

[0007] Another embodiment according to the present disclosure may include a method of taking a sample in a wellbore, comprising: using a drill bit conveyed into the wellbore to form a core; and using at least one retractable cutter internal to the drill bit for cutting the sample from the core.

[0008] Another embodiment according to the present disclosure may include a method for encapsulating a sample in a wellbore, comprising: using a drill bit in the wellbore for forming a core; using a retractable cutter internal to the drill bit for cutting a sample from the core and conveying the sample to a receiving chamber; and using an encapsulator operably coupled to the receiving chamber for at least partially encapsulating at least part of the sample in an encapsulating material.

[0009] Examples of the more important features of the disclosure have been summarized rather broadly in order that the detailed description thereof that follows may be better understood and in order that the contributions they represent to the art may be appreciated.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] For a detailed understanding of the present disclosure, reference should be made to the following detailed description of the embodiments, taken in conjunction with the accompanying drawings, in which like elements have been given like numerals, wherein:

Fig. 1 shows a schematic of a coring drill bit deployed in a borehole along a according to one embodiment of the present disclosure;

Fig. 2 shows a schematic of a drill bit configured for testing core sample fluids according to one embodiment of the present disclosure;

Fig. 3 shows a schematic of another drill bit configured for testing core sample fluids according to one embodiment of the present disclosure;

Fig. 4 shows a schematic of a drill bit configured for testing a core sample according to one embodiment of the present disclosure;

Fig. 5 shows a schematic of a drill bit configured for protecting a core sample according to one embodiment of the present disclosure;

Fig. 6 shows a schematic of a drill bit configured for protecting and storing a core sample according to one embodiment of the present disclosure;

Fig. 7A shows a schematic of a drill bit configured for cutting a core sample according to one embodiment of the present disclosure;

Fig. 7B shows a schematic of a drill bit configured for cutting multiple core samples according to one embodiment of the present disclosure;

Fig. 8 shows a flow chart of a method for analyzing a fluid from a core sample in situ according to one embodiment of the present disclosure;

Fig. 9 shows a flow chart of a method for protecting a core sample for transport according to one embodiment of the present disclosure; and

Fig. 10 shows a schematic of a drill bit configured for pressurizing a core sample according to one embodiment of the present disclosure.

DETAILED DESCRIPTION

[0011] This disclosure generally relates to the testing and sampling of underground formations or reservoirs. In one aspect, this disclosure relates to preparing a core sample without interrupting drilling operations, and, in another aspect, to processing the core sample for analysis of fluids using extraction or encapsulation methods and apparatuses. The present disclosure is susceptible to embodiments of different forms. There are shown in the drawings, and herein will be described in detail, specific embodiments of the present disclosure with the understanding that the present disclosure is to be considered an exemplification of the principles of the disclosure, and is not intended to limit the disclosure to that illustrated and described herein. Indeed, as will become apparent, the teachings of the present disclosure can be utilized for a variety of well tools and in all phases of well construction and production. Accordingly, the embodiments discussed below are merely illustrative of the applications of the present invention.

[0012] **Fig. 1** shows a schematic diagram of an exemplary drilling system **10** with a drill string **20** carrying a drilling assembly **90** (also referred to as the bottomhole assembly, or "BHA") conveyed in a "wellbore" or "borehole" **26** for drilling the borehole. The drill string **20** may include one or more of: jointed tubular and coiled tubing. The drilling system **10** includes a conventional derrick **11** erected on a floor **12** which supports a rotary table **14** that is rotated by a prime mover such as an electric motor (not shown) at a desired rotational speed. The drill string **20** includes tubing such as a drill pipe **22** or a coiled-tubing extending downward from the surface into the borehole **26**. The drill string **20** is pushed into the borehole **26** when a drill pipe **22** is used as the tubing. For coiled-tubing applications, a tubing injector, such as an injector (not shown), however, is used to move the tubing from a source thereof, such as a reel (not shown), to the borehole **26**. The drill bit assembly

50 attached to the end of the drill string breaks up the geological formations when it is rotated to drill the borehole **26**. If a drill pipe **22** is used, the drill string **20** is coupled to a drawworks **30** via a kelly joint **21**, swivel **28**, and line **29** through a pulley **23**. During drilling operations, the drawworks **30** is operated to control the weight on bit, which is an important parameter that affects the rate of penetration. The operation of the drawworks is well known in the art and is thus not described in detail herein.

[0013] During drilling operations, a suitable drilling fluid **31** from a mud pit (source) **32** is circulated under pressure through a channel in the drill string **20** by a mud pump **34**. The drilling fluid passes from the mud pump **34** into the drill string **20** via a desurger (not shown), fluid line **38** and kelly joint **21**. The drilling fluid **31** is discharged at the borehole bottom **51** through an opening in the drill bit assembly **50**. The drilling fluid **31** circulates uphole through the annular space **27** between the drill string **20** and the borehole **26** and returns to the mud pit **32** via a return line **35**. The drilling fluid acts to lubricate the drill bit assembly **50** and to carry borehole cutting or chips away from the drill bit assembly **50**. A sensor **S1** placed in the line **38** can provide information about the fluid flow rate. A surface torque sensor **S2** and a sensor **S3** associated with the drill string **20** respectively provide information about the torque and rotational speed of the drill string. Additionally, a sensor (not shown) associated with line **29** is used to provide the hook load of the drill string **20**.

[0014] In one embodiment of the disclosure, the drill bit assembly **50** is rotated by only rotating the drill pipe **22**. In another embodiment of the disclosure, a downhole motor **55** (mud motor) is disposed in the drilling assembly **90** to rotate the drill bit assembly **50** and the drill pipe **22** is rotated usually to supplement the rotational power, if required, and to effect changes in the drilling direction.

[0015] In one embodiment of **Fig. 1**, the mud motor **55** is coupled to the drill bit assembly **50** via a drive shaft (not shown) disposed in a bearing assembly **57**. The mud motor rotates the drill bit assembly **50** when the drilling fluid **31** passes through the mud motor **55** under pressure. The bearing assembly **57** supports the radial and axial forces of the drill bit assembly. A stabilizer **58** coupled to the bearing assembly **57** acts as a centralizer for the lowermost portion of the mud motor assembly.

[0016] In one embodiment of the disclosure, a drilling sensor module **59** is placed near the drill bit assembly **50**. Drill bit assembly **50** may include one or more

of: (i) a drill bit, (ii) a drill bit box, (iii) a drill collar, and (iv) a storage sub. The drilling sensor module may contain sensors, circuitry, and processing software and algorithms relating to the dynamic drilling parameters. Such parameters can include bit bounce, stick-slip of the drilling assembly, backward rotation, torque, shocks, borehole and annulus pressure, acceleration measurements, and other measurements of the drill bit assembly condition. A suitable telemetry or communication sub **77** using, for example, two-way telemetry, is also provided as illustrated in the drilling assembly **90**. The drilling sensor module processes the sensor information and transmits it to the surface control unit **40** via the communication sub **77**.

[0017] The communication sub **77**, a power unit **78** and an MWD tool **79** are all connected in tandem with the drill string **20**. Flex subs, for example, are used in connecting the MWD tool **79** in the drilling assembly **90**. Such subs and tools may form the bottom hole drilling assembly **90** between the drill string **20** and the drill bit assembly **50**. The drilling assembly **90** may make various measurements including the pulsed nuclear magnetic resonance measurements while the borehole **26** is being drilled. The communication sub **77** obtains the signals and measurements and transfers the signals, using two-way telemetry, for example, to be processed on the surface. Alternatively, the signals can be processed using a downhole processor at a suitable location (not shown) in the drilling assembly **90**.

[0018] The surface control unit or processor **40** may also receive one or more signals from other downhole sensors and devices and signals from sensors **S₁-S₃** and other sensors used in the system **10** and processes such signals according to programmed instructions provided to surface control unit **40**. The surface control unit **40** may display desired drilling parameters and other information on a display/monitor **44** utilized by an operator to control the drilling operations. The surface control unit **40** can include a computer or a microprocessor-based processing system, memory for storing programs or models and data, a recorder for recording data, and other peripherals. The control unit **40** can be adapted to activate alarms **42** when certain unsafe or undesirable operating conditions occur.

[0019] The apparatus for use with the present disclosure may include one or more downhole processors that may be positioned at any suitable location within or near the bottom hole assembly. The processor(s) may include a microprocessor that

uses a computer program implemented on a suitable machine readable medium that enables the processor to perform the control and processing. The machine readable medium may include ROMs, EPROMs, EAROMs, EEPROMs, Flash Memories, RAMs, Hard Drives and/or Optical disks. Other equipment such as power and data buses, power supplies, and the like will be apparent to one skilled in the art.

[0020] Fig. 2 shows an exemplary embodiment of drill bit assembly **50** configured for generating a core sample that may be tested in situ. The drill bit assembly **50** may include a core mouth **210** configured to receive a core sample **220** of material from the borehole bottom **51**. The core sample **220** may be formed by the teeth **230** of drill bit assembly **50**. Drill bit assembly **50** may include a recessed section or chamber **215** configured to store core sample **220**. Within chamber **215**, drill bit assembly **50** may include retractable cutters **280** to separate the core sample **220** from the formation **51**. One or more seals **240** may be configured to hold core sample **220** and may isolate the core sample **220** within chamber **215**. A probe **250** may be used to extract fluid **255** from the core sample **220**. The extracted fluid **255** may be transported to a fluid analysis module **260** by a tube **265**. The extracted fluid **255** may be forced into tube **265** by pressurized fluid **275** being applied to core sample **220** through a pressurized tube **270** that may be configured to apply pressure on the core sample **220**. The use of pressurized fluid to extract fluid from the core sample is exemplary and illustrative only, as other devices may be used to extract fluid, including, but not limited to, one or more of: (i) an acoustic driver (an ultrasonic driver is one type of acoustic driver) and (ii) a mechanical crusher. In some embodiments, a filter may be incorporated into drill bit assembly **50** so that the core sample **220** may be crushed, smashed, and/or pulverized, and then the remains may be filtered to extract the fluids **255**. Fluid **255** may be a fluid including, but not limited to, one or more of: (i) drilling fluid, (ii) production fluid, and (iii) formation fluid. Fluid analysis module **260** may include sensors or test equipment configured to estimate chemical, physical, electrical, and/or nuclear properties of the extracted fluid **255**, including, but not limited to, one or more of: (i) pH, (ii) H₂S, (iii) density, (iv) viscosity, (v) temperature, (vi) rheological properties, (vii) thermal conductivity, (viii) electrical resistivity, (ix) chemical composition, (x) reactivity, (xi) radiofrequency properties, (xii) surface tension, (xiii) infra-red absorption, (xiv) ultraviolet

absorption, (xv) refractive index, (xvi) magnetic properties, and (xvii) nuclear spin. In some embodiments, the drill bit assembly **50** may use the device used to apply pressure to the core sample **220** or an additional mechanism (not shown) applying pressure to the core sample **220** such that rock mechanics tests may be performed on the core sample **220** in-situ. Rock mechanics tests may include, but are not limited to, one or more of: (i) a compression test, (ii) a strain test, and (iii) a fracture test. Further, in some embodiments, testing data obtained through rock mechanics tests may be used to modify and/or optimize drilling parameters. Modification and/or optimization of drilling parameters, (such as, but not limited to, weight on bit, rotational speed of the drill bit, flow rate of drilling fluid, and geosteering parameters) may be determined downhole or at the surface, and modification of drilling parameters may take place in real-time.

[0021] **Fig. 3** shows another exemplary embodiment of drill bit assembly **50** configured to use a gas chromatograph **300**. Core sample **220** may be heated by heater **310** to a desired temperature to cause gases **320** to be generated. Heater **310** may heat core sample **220** using, but not limited to, one or more of: (i) electric induction, (ii) radiative heating, and (iii) electrical resistive heating. Heater **310** may be controlled to operate at various temperatures to provide a variety of gas samples **320** to the gas chromatograph **300**. The gases **320** may be directed from chamber **215** into gas chromatograph **300** via a connecting tube **330**. The heating of the core sample **220** may also result in the release of fluids **340** from the core sample **220**. These fluids **340** may flow along the bottom **350** of chamber **215** into a heavy fluid analysis module **360**. The bottom **350** may be formed by the top of the seals **240** or a separate isolation barrier (not shown). Heavy fluid analysis module **360** may include sensors or test equipment configured to estimate chemical, physical, and/or nuclear properties of the fluids **340**, including, but not limited to, one or more of: (i) pH, (ii) H₂S, (iii) density, (iv) viscosity, (v) temperature, (vi) rheological properties, (vii) thermal conductivity, (viii) electrical resistivity, (ix) chemical composition, (x) reactivity, (xi) radiofrequency properties, (xii) surface tension, (xiii) infra-red absorption, (xiv) ultraviolet absorption, (xv) refractive index, (xvi) magnetic properties, and (xvii) nuclear spin.

[0022] Fig. 4 shows another exemplary embodiment of drill bit assembly **50** configured to expose the core sample **220** within chamber **215** to a strong magnetic field from a nuclear magnetic resonance (NMR) module **400**. The NMR module **400** may be equipped to generate a strong magnetic field and to detect a response of the core sample **220** to the strong magnetic field. The NMR module **400** may be controlled to regulate the power of the magnetic field being applied to the core sample **220**. In some embodiments, the drill bit assembly **50** may be equipped with a radio frequency generator and/or receiver configured to apply a radio signal to the core sample **220** and detect a radio frequency response caused by the interaction of the radio signal with the core sample **220**.

[0023] Fig. 5 shows another exemplary embodiment of drill bit assembly **50** configured to at least partially encapsulate a core sample **220** in a chamber **215** with an encapsulating material **500**. The chamber **215** may include one or more retractable cutters **280** configured to separate the core sample **220** from the borehole bottom **51**. Within the drill bit assembly **50** may be a reservoir **510** to store encapsulating material **500**. Once a core sample **220** is within the chamber **215** and isolated from the borehole bottom **51**, the encapsulating material **500** may be applied to the core sample **220**. A tube **530** may allow the encapsulating material **500** to flow from the reservoir **510** and into chamber **215**. Once in contact with the core sample **220** the encapsulating material **500** forms an encapsulating coating **540** that at least partially surrounds core sample **220**. Drill bit assembly **50** may also include a tagging device **550** with access to chamber **215**. Tagging device **550** may be configured to insert or implant a tag **560** (such as a radio frequency identification device (RFID) chip) within the encapsulating coating **540** so that a core sample may be identified. In some embodiments, the tagging device **550** may be configured to etch or mark an identifier on the core sample **220** or on the encapsulating coating **540**. The tagging device may include, but is not limited to, one of: (i) a laser marker, (ii) an ultrasonic blasting tool, (iii) a powder blasting tool, (iv) radioactive tracers, (v) magnetic particles, and (vi) a chip inserter. The encapsulating material **500** may include, but is not limited to, one or more of: (i) a polymer, (ii) a gel, (iii) a metallic coating, and (iv) a clay.

[0024] Fig. 6 shows another exemplary embodiment of drill bit assembly **50** configured with a storage module **600** for storing one or more core samples **220**. The

storage module **600** may include a storage chamber **610** that is configured to receive a core sample **220** from the chamber **215**. The storage module may also include a transporter **620** located within storage chamber **610** configured to grip or hold the core sample **220** for conveyance into and/or within the storage chamber **610**. The transporter **620** may include a series of teeth **630** configured to grip or hold the core sample **220** so that it may be moved deeper within the storage chamber **610**. The storage module **600** may also include bellows or bladders **640** configured to hold core samples **220** firmly within the deeper recesses of the storage chamber **610**, which may allow multiple sample cores **220** to be stored within the storage chamber **610**. The bellows **640** and/or the teeth **630** may be configured to minimize the chance of the encapsulating coating **540** being damaged by the transport or storage of the core sample **220**. In some embodiments (not shown) the storage module may be located behind the drill bit assembly in the bit shank or a sub. While a transporter **620** is shown with mechanical teeth **630**, this is illustrative and exemplary only, as transporter **620** may use any device known to those of skill in the art to move the core sample **220** within the chambers **215**, **610**, including, but not limited to, (i) gears, (ii) a helical drive, (iii) a spiral drive, (iv) a piston, and (v) a robotic arm.

[0025] Fig. 7A shows an exemplary drill bit assembly **50** equipped with core cutters **700** in addition to the drill bit teeth **230**. The core cutters may be located adjacent to the core mouth **210**. The core cutters **700** may include, but are not limited to, one of: (i) elongated cutting blades, (ii) ultrasonic cutters, (iii) acoustic ablaters, (iv) fluid blasters, (v) powder blasters, and (vi) laser cutters.

[0026] Fig. 7B shows an exemplary drill bit assembly **50** configured to cut multiple core samples **220**. The face of the drill bit assembly **220** may include core mouths **210** that open into multiple sample chambers **215**. One or more of the core mouths **210** may have core cutters **700** mounted adjacent to the core mouth **210** on the drill bit assembly **50**. In operation, individual or multiple core samples **220** may be received by the core chamber **215** by controlling which core cutters **700** are in operation.

[0027] While Figs. 2-7B show various embodiments according to the present disclosure with individual features, some or all of these may be combined to form a drill bit assembly configured to perform one or more tests and to encapsulate a core

sample **220**. Some embodiments may be configured to allow collection of multiple core samples where some core samples have fluid extraction, others have fluids extracted and tested, and still others are encapsulated with or without prior testing. While various embodiments are shown for forming a core sample in front of the drill bit assembly, this is illustrative and exemplary only; as embodiments of the present disclosure include apparatus to take side core samples as well.

[0028] **Fig. 8** shows an exemplary method **800** according to one embodiment of the present disclosure for testing the core sample or fluids derived from the core sample. In method **800**, drill bit assembly **50** may be positioned against borehole bottom **51** within borehole **26** in step **810**. In step **820**, at least one core sample **220** may be cut from borehole bottom **51** using drill bit teeth **230** or specialized core cutters **700** and received into the chamber **215** through core mouth **210**. In some embodiments, multiple core samples **220** may be cut simultaneously during step **820**. In step **830**, a stimulus may be applied to the core sample **220**. The stimulus applied to the core sample **220** may include, but is not limited to, one or more of: (i) pressure, (ii) heat, (iii) acoustic energy, (iv) a magnetic field, and (v) electromagnetic radiation. In step **840**, liquid or gaseous fluids **255**, **320**, **340** from the core sample **220** may be tested to estimate at least one chemical, physical, electrical, and/or nuclear property, including, but not limited to, one or more of: (i) pH, (ii) H₂S, (iii) density, (iv) viscosity, (v) temperature, (vi) rheological properties, (vii) thermal conductivity, (viii) electrical resistivity, (ix) chemical composition, (x) reactivity, (xi) radiofrequency properties, (xii) surface tension, (xiii) infra-red absorption, (xiv) ultraviolet absorption, (xv) refractive index, (xvi) magnetic properties, and (xvii) nuclear spin. In step **845**, the core sample **220** may be tested for its response to exposure to one or more of: (i) a magnetic field, (ii) radio frequency energy, (iii) electromagnetic radiation, (iv) an electric field, (v) temperature, (vi) density, (vii) resistivity properties, (viii) acoustic radiation, and (ix) pressure. Step **840**, step **845**, or both may be performed in different embodiments of method **800**. In step **850**, the at least one property estimated in one or both of step **840** and step **845**, may be used to estimate a parameter of interest of the formation at the bottom of the borehole **51**. In some embodiments, step **855** may be performed such that the response to stimulus obtained

in step **845** may be used to modify at least one drilling parameter. Step **855** may be performed in real-time.

[0029] **Fig. 9** shows an exemplary method **900** according to one embodiment of the present disclosure for encapsulating the core sample. In method **900**, drill bit assembly **50** may be positioned against borehole bottom **51** within borehole **26** in step **910**. In step **920**, at least one core sample **220** may be cut from borehole bottom **51** using drill bit teeth **230** or specialized core cutters **700** and received into the chamber **215** through core mouth **210**. In some embodiments, multiple core samples **220** may be cut simultaneously during step **920**. In step **930**, the core sample **220**, may be pinched off or separated from the formation by retractable cutters **280**. In step **940**, core sample **220** may be at least partially encapsulated by an encapsulating coating **540** provided from a reservoir **510** of encapsulating material **500**. The encapsulating process may include, but is not limited to, one of: (i) spraying, (ii) immersing partially, (iii) immersing completely, (iv) pouring, (v) wrapping, and (vi) thermal evaporation coating. In step **950**, core sample **220** may be moved from chamber **215** to a storage chamber **610** by transporter **620**. In step **960**, the drill bit assembly **50** may be transported to the surface for retrieval of the core samples **220**. In some embodiments, step **950** may be optional. In some embodiments, prior to, during, or immediately after encapsulation, a tagging device may attach an identification tag to the core sample **220**. In other embodiments, the tagging device may etch or mark the sample or the encapsulating coating with an identifier. The tagging device may include, but is not limited to, one of: (i) a laser marker, (ii) an ultrasonic blasting tool, (iii) a powder blasting tool, (iv) radioactive tracers, (v) magnetic particles, and (vi) a chip inserter.

[0030] While **Fig. 8** describes an embodiment of a method according to the present disclosure for extracting and testing a fluid or a core sample, and **Fig. 9** describes an embodiment of a method according to the present disclosure for encapsulating a core sample, in some embodiments, the method may include extracting a fluid, testing the fluid or the core sample, and encapsulating the core sample.

[0031] **Fig. 10** shows another exemplary embodiment of drill bit assembly **50** configured with to at least partially encapsulate a core sample **220** in a chamber **215**

with an encapsulating material **500** while the chamber **215** is pressurized. A second set of seals **1010** may be located near the top of chamber **215** such that, when seals **1010** and seals **240** are closed, a section of chamber **215** holding core sample **220** is isolated from storage chamber **610** (**Fig. 6**). While the core sample **220** is isolated, any fluid **1050** in chamber **215** may be pressurized by a pressure applicator **1000**. In this example, pressure applicator **1000** may include a force applicator **1030** piston **1020**, and cylinder **1040** where force applicator **1030** is configured to move piston **1020** to reduce the combined volume of chamber **215** and cylinder **1040** resulting in increased pressure within chamber **215**. Increasing the pressure on the core sample **220** may intensify pore pressure within the core sample **220**. Pressure may be reduced or returned to ambient pressure by moving piston **1020** to increase the combined volume of chamber **215** and piston cylinder **1040**. After pressure has been reduced, the core sample **220** may be encapsulated as shown above. In some embodiments, encapsulating material **500** may be applied to the core sample **220** while the pressure in chamber **215** is above ambient pressure. Encapsulating material **500** may be stored in reservoir **510** at a pressure sufficient to allow encapsulating material **500** to enter chamber **215**, or a mechanism (not shown), such as a pump, may be used to increase the pressure of the encapsulating material **500** such that it may flow out of tube **530** against the pressure in chamber **215**. The use of a piston and cylinder to modify the pressure in chamber **215** is exemplary and illustrative only, as other mechanisms, such as, but not limited to, a drilling fluid pressure, adjustable bladders, pumps, and displacement devices may be used to modify the pressure in chamber **215**.

[0032] While the foregoing disclosure is directed to the one mode embodiments of the disclosure, various modifications will be apparent to those skilled in the art. It is intended that all variations be embraced by the foregoing disclosure.

CLAIMS

We claim:

1. An apparatus for forming a sample in a wellbore, comprising:
a drill bit configured to form a core; and
at least one retractable cutter internal to the drill bit configured to cut the sample from the core.
2. The apparatus of claim 1, the drill bit further comprising:
a chamber configured to receive the sample.
3. The apparatus of claim 2, further comprising:
an extractor disposed adjacent to the chamber and configured to extract the fluid from the sample.
4. The apparatus of claim 3, further comprising:
at least one analysis module operably coupled to the extractor and configured to analyze the extracted fluid.
5. The apparatus of claim 3, wherein the at least one analysis module includes at least one of: (i) a gas chromatograph and (ii) a fluid analyzer.
6. The apparatus of claim 3, wherein the extractor comprises at least one of: (i) a heater, (ii) a mechanical pulverizer, (iii) an acoustic driver, and (iv) a filter.
7. The apparatus of claim 3, wherein the extractor is configured perform on the sample at least one of: (i) a compression test, (ii) a strain test, and (iii) a fracture test.
8. The apparatus of claim 2, further comprising:
an analysis module positioned adjacent to the chamber and configured to apply a stimulus to the sample.
9. The apparatus of claim 8, wherein the stimulus is at least one of: (i) pressure, (ii) heat, (iii) acoustic energy, (iv) a magnetic field, (v) electromagnetic radiation, and (vi) force.

10. The apparatus of claim 8, further comprising:

a processor configured to modify at least one drilling parameter using data acquired by the analysis module.

11. The apparatus of claim 2, further comprising:

an encapsulater operably coupled to the chamber and configured to at least partially encapsulate at least part of the sample in an encapsulating material.

12. The apparatus of claim 11, wherein the encapsulating material is at least one of:

(i) a polymer, (ii) a gel, (iii) a metallic coating, and (iv) a clay.

13. The apparatus of claim 11, wherein the encapsulating material is easily distinguishable from drilling fluid and unencapsulated materials from the wellbore.

14. The apparatus of claim 2, further comprising:

a tagging device adjacent to the chamber and configured to tag the sample.

15. The apparatus of claim 14, wherein the tagging device is configured to tag the sample using at least one of: (i) a laser marker, (ii) an ultrasonic blasting tool, (iii) a powder blasting tool, (iv) radioactive tracers, (v) magnetic particles, and (vi) a chip inserter.

16. The apparatus of claim 2, further comprising:

a pressure applicator disposed adjacent to the chamber and configured to modify the pressure of the chamber.

17. The apparatus of claim 1, wherein the sample is at least one of: (i) a core sample and (ii) a cutting.

18. An apparatus for encapsulating a sample in a wellbore, comprising:

a drill bit configured to form a core;

a chamber configured to receive the sample from the core; and

an encapsulater operably coupled to the chamber and configured to at least partially encapsulate at least part of the sample in an encapsulating material.

19. The apparatus of claim 18, wherein the encapsulating material is at least one of: (i) a polymer, (ii) a gel, (iii) a metallic coating, and (iv) a clay.

20. The apparatus of claim 18, wherein the encapsulating material is easily distinguishable from drilling fluid and unencapsulated materials from the wellbore.

21. An apparatus of claim 18, further comprising:

at least one retractable cutter internal to the drill bit configured to cut the sample from the core.

22. A method of taking a sample in a wellbore, comprising:

using a drill bit conveyed into the wellbore to form a core; and

using at least one retractable cutter internal to the drill bit for cutting the sample from the core.

23. The method of claim 22, further comprising:

estimating a value of a property of interest using a response of the sample to a stimulus.

24. The method of claim 23, further comprising:

applying the stimulus to the sample.

25. The method of claim 24, further comprising:

modifying at least one drilling parameter using a response of the sample to the stimulus.

26. The method of claim 23, further comprising applying the stimulus by using, at least one of: (i) pressure, (ii) heat, (iii) acoustic energy, (iv) a magnetic field, (v) electromagnetic radiation, and (vi) force.

27. The method of claim 22, further comprising:

extracting a fluid from the sample.

28. The method of claim 27, further comprising:

estimating a property of interest using the extracted fluid.

29. The method of claim 27, using, to extract the fluid, at least one of: (i) fluid pressure, (ii) mechanical compression, (iii) heating, (iv) acoustic waves, and (v) a filter.

30. The method of claim 27, using, to estimate the property of interest, at least one of: (i) a gas chromatograph and (ii) a fluid analyzer.

31. The method of claim 22, further comprising:

encapsulating at least part of the sample in an encapsulating material.

32. The method of claim 31, using, as the encapsulating material, at least one of: (i) a polymer, (ii) a gel, (iii) a metallic coating, and (iv) a clay.

33. The method of claim 22, further comprising:

marking the sample using a tagging device.

34. The method of claim 33, using, for the tagging device, at least one of: (i) a laser marker, (ii) an ultrasonic blasting tool, (iii) a powder blasting tool, (iv) radioactive tracers, (v) magnetic particles, and (vi) a chip inserter.

35. The method of claim 34, further comprising:

marking the encapsulating material using a tagging device.

36. A method for encapsulating a sample in a wellbore, comprising:

using a drill bit in the wellbore for forming a core;

using a retractable cutter internal to the drill bit for cutting a sample from the core and conveying the sample to a receiving chamber; and

using an encapsulater operably coupled to the receiving chamber for at least partially encapsulating at least part of the sample in an encapsulating material.

37. The method of claim 36, using, as the encapsulating material, at least one of: (i) a polymer, (ii) a gel, (iii) a metallic coating, and (iv) a clay.
38. The method of claim 36, further comprising:
- marking the encapsulating material using a tagging device.