

## DESCRIPTION

### 【Invention Title】

COSMETIC CONTAINER PROVIDED WITH RUBBER DISCHARGE PAD

### 5       【Technical Field】

The present invention relates to a cosmetic container provided with a rubber discharge pad, and more particularly, to a cosmetic container provided with a rubber discharge pad, in which a rubber discharge pad having a plurality of outlets is  
10 coupled to a container body, and when the rubber discharge pad is pressed, the rubber discharge pad is pressed to the bottom of the container body by elasticity such that the contents contained in the container body may be used without any residual contents; and since the contents contained in the  
15 container body are discharged through the outlets of the rubber discharge pad, the expansion sizes of the outlets vary according to pressure on the discharge pad such that a discharge quantity of the contents may be adjusted.

In addition, the embodiment relates to a cosmetic  
20 container provided with a rubber discharge pad, in which the rubber discharge pad having the outlets and a tension cap having a tension protrusion are coupled to the container body such that the tension protrusion presses a rim of the rubber discharge pad to be tense, and the tension cap is firmly  
25 coupled to the container body such that the rubber discharge

pad is prevented from being separated from the container body when the rubber discharge pad is pressed.

#### **【Background Art】**

In general, cosmetics, which are used to make the face of  
5 a user look beautiful, may be classified into base cosmetics,  
functional cosmetics and color cosmetics according to the  
functions.

The color cosmetics are used to beautifully adorn the skin  
color of a user and make a skin defect invisible, which cannot  
10 be capped with the base cosmetics, by applying the color  
cosmetics to a human body such as a face or nails.

In addition, the color cosmetics may protect a skin from  
pollution, dust and ultraviolet rays and correct the contour of  
a face to give a three-dimensional effect, so that the color  
15 cosmetics are widely used.

The color cosmetics, which cap a skin defect to make skin  
look smooth as described above, include a powder pact. The  
powder pact contains powder-type contents and is used in such a  
manner that the powder-type contents are applied on a cosmetic  
20 portion with a puff.

However, when the powder pact is used, the powder-type  
contents are scattered in use and the adhesion is deteriorated  
when being applied on a face.

To overcome the problems described above, there has been  
25 developed a foundation having gel-type contents. The foundation

cosmetic contents are prepared by mixing a color power material with components such as binder or emulsifier, melting the mixture at a predetermined temperature and cooling the melted mixture. Then, the foundation cosmetic contents are contained  
5 in a cosmetic container such as a foundation case, so that the foundation cosmetics are produced as a complete product.

One example of a foundation container according to the related art had been disclosed in Korean Registered Utility Model No. 20-0362370. As shown in FIG. 1, a foundation  
10 container according to the related art includes an inner container 1 containing a cosmetic material and provided on an outer periphery thereof with a screw, a lower container 3 inserted into a container receiving space 2 provided in the inner container 1, an upper container having an opened lower  
15 portion to be screw-coupled to a screw thread formed on an outer periphery of the lower container 3 and provided on an upper portion thereof with a puff containing space 4 in which a puff is kept, and a lid 6 hinge-coupled to a hinge formed on one side surface of the upper container 5 to be opened or  
20 closed.

However, according to the foundation container of the related art, since the cosmetic contents contained in the upper container 5 are stuck on a puff for use after the upper container 5 is separated from the lower container 3 when  
25 makeup is applied, too much cosmetics are stuck on the puff at

a time.

To solve the problem, there had been disclosed a product applied by the same applicant as the present invention in Korean Registered Patent No. 10-1159877. As shown in FIG. 2, gel-type cosmetic contents are contained in a compact container 100 while being impregnated into an impregnation member 200.

However, according to the related art, since the gel-type contents impregnated into the impregnation member 200 are stuck on a puff for use, the contents gradually move to an upper portion of the impregnation member 200 due to gravity while being used up, the contents impregnated to a lower portion of the impregnation member 200 cannot be used.

In addition, since the contents impregnated to the impregnation member 200 are used after being stuck on a puff, it is difficult for a user to arbitrarily adjust a discharge quantity of cosmetic contents.

#### **【Disclosure】**

#### **【Technical Problem】**

To solve the problems described above, an object of the present invention is to provide a cosmetic container provided with a rubber discharge pad, in which a rubber discharge pad having a plurality of outlets is coupled to a container body, and when the rubber discharge pad is pressed, the rubber discharge pad is pressed to the bottom of the container body by

elasticity such that the contents contained in the container body may be used without any residual contents.

Another object of the present invention is to provide a cosmetic container provided with a rubber discharge pad, in which the contents contained in the container body are discharged through the outlets of the rubber discharge pad, such that the expansion sizes of the outlets may vary according to pressure on the discharge pad, thereby adjusting a discharge quantity of the contents.

Still another object of the present invention is to provide a cosmetic container provided with a rubber discharge pad, in which the rubber discharge pad having the outlets and a tension cap having a tension protrusion are coupled to the container body such that the tension protrusion presses a rim of the rubber discharge pad to be tense, and the tension cap is firmly coupled to the container body such that the rubber discharge pad is prevented from being separated from the container body when the rubber discharge pad is pressed.

#### **【Technical Solution】**

According to the present invention, there is provided a cosmetic container provided with a rubber discharge pad, which includes an outer container (10) provided with a container body containing groove, and an outer container lid (20) hinge-coupled to the outer container (10) to be opened or closed. The cosmetic container includes:

a container body (30) contained in the outer container (10) and provided with an inner wall (32);

a container lid (40) hinge-coupled to the container body (30);

5 a rubber discharge pad (50) coupled to an upper end of the container body (30) and provided with an outlet (51); and

a tension cap (60) for fixing the rubber discharge pad (50) to the container body (30) while pressing the rubber discharge pad (50),

10 wherein the rubber discharge pad (50) is provided on an end thereof with an inserting part (52), the inserting part (52) is fitted with the inner wall (32) of the container body (30) to fixedly couple the rubber discharge pad (50) to the inner wall (32) of the container body (30),

15 the tension cap (60) is provided with a tension protrusion (61) and coupled to the container body (30), and

the tension protrusion (61) presses a rim of the rubber discharge pad (50) to expand the rubber discharge pad (50).

In addition, the container body (30) is provided at a side 20 thereof with the inner wall (32) and an outer wall (33).

In addition, a fitting protrusion (34) is formed on the inner wall (32) of the container body (30).

In addition, a sealing piece (42) is formed below the container lid (40).

25 In addition, the outlet (51) has a size in a range of 0.01

mm to 1.2 mm.

In addition, 100 to 600 the outlets are distributed onto the rubber discharge pad (50). Preferably, the number of the outlets is in the range of 300 to 500

5 In addition, the cosmetic container further includes a frame (70) and the rubber discharge pad (50) is coupled between the tension cap (60) and the frame (70) such that the rubber discharge pad (50) is coupled to the container body (30).

In addition, the cosmetic container further includes  
10 impregnation member (80) formed on an inside of the container body (30).

#### **【Advantageous Effects】**

According to the cosmetic container provided with a rubber discharge pad of the present invention, the rubber discharge  
15 pad having a plurality of outlets is coupled to a container body to allow the rubber discharge pad to be pressed to the bottom of the container body, so that the contents contained in the container body may be used without any residual contents.

In addition, according to the cosmetic container provided  
20 with a rubber discharge pad, since the contents contained in the container body are discharged through the outlets of the rubber discharge pad, the expansion sizes of the outlets may vary according to pressure on the discharge pad, thereby adjusting a discharge quantity of the contents.

25 In addition, according to the cosmetic container provided

with a rubber discharge pad, since the rubber discharge pad having the outlets and a tension cap having a tension protrusion are coupled to the container body such that the tension protrusion allows the rubber to be firmly coupled to the container body, the rubber discharge pad may be prevented  
5 from being separated from the container body when the rubber discharge pad is pressed.

**【Description of Drawings】**

10 FIG. 1 is a sectional view of a foundation container according to the related art.

FIG. 2 is a perspective view illustrating a state that the foundation container according to the related art is opened.

FIG. 3 is a perspective view illustrating a state that a  
15 cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is opened.

FIG. 4 is an exploded perspective view of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention.

20 FIG. 5 is a sectional view illustrating a state that a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is opened.

FIG. 6A is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber  
25 discharge pad according to an embodiment of the present

invention is coupled to the rubber discharge pad.

FIG. 6B is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is coupled to the rubber discharge pad.

FIG. 6C is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is coupled to a tension cap.

FIG. 6D is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is coupled to a tension cap.

FIG. 7 is a sectional view illustrating a state that an impregnation member is opened and installed to a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention.

FIG. 8A is a sectional view illustrating a state that a tension cap, a rubber discharge pad and a frame of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention are coupled to each other.

FIG. 8B is a sectional view illustrating a state that a tension cap, a rubber discharge pad and a frame of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention coupled to a container body

after being coupled to each other.

FIG. 8C is a sectional view illustrating a state that a tension cap, a rubber discharge pad and a frame of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention coupled to a container body  
5 after being coupled to each other.

**【Best Mode】**

**【Mode for Invention】**

10 Hereinafter, a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention will be described with reference to accompanying drawings.

FIG. 3 is a perspective view illustrating a state that a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is opened.  
15 FIG. 4 is an exploded perspective view of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention. FIG. 5 is a sectional view illustrating a state that a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is opened. FIG. 6A is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is coupled to the rubber discharge pad. FIG.  
20  
25

6B is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is coupled to the rubber discharge pad. FIG. 6C is a sectional  
5 view illustrating a state that a container body of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention is coupled to a tension cap. FIG. 6D is a sectional view illustrating a state that a container body of a cosmetic container provided with a rubber  
10 discharge pad according to an embodiment of the present invention is coupled to a tension cap. FIG. 7 is a sectional view illustrating a state that an impregnation member is opened and installed to a cosmetic container provided with a rubber discharge pad according to an embodiment of the present  
15 invention. FIG. 8A is a sectional view illustrating a state that a tension cap, a rubber discharge pad and a frame of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention are coupled to each other. FIG. 8B is a sectional view illustrating a state  
20 that a tension cap, a rubber discharge pad and a frame of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention coupled to a container body after being coupled to each other. FIG. 8C is a sectional view illustrating a state that a tension cap, a  
25 rubber discharge pad and a frame of a cosmetic container

provided with a rubber discharge pad according to an embodiment of the present invention coupled to a container body after being coupled to each other.

According to the present invention, there is provided a  
5 cosmetic container provided with a rubber discharge pad, which includes an outer container 10 provided with a container body containing groove, and an outer container lid 20 hinge-coupled to the outer container 10 to be opened or closed.

The cosmetic container includes a container body 30  
10 contained in the outer container 10 and provided with an inner wall 32, a rubber discharge pad 50 coupled to an upper end of the container body 30 and provided with an outlet 51, and a tension cap 60 for fixing the rubber discharge pad 50 to the container body 30 while pressing the rubber discharge pad 50.

15 The outer container 10 includes a push button 11 formed on one side surface thereof with a locking sill 12 and a hinge formed at a side facing the push button 12, such that the outer container 10 is hinge-coupled to an outer container lid 20. The outer container 10 includes a container body containing groove  
20 15 provided therein, a coupling protrusion 13 formed on an inner periphery surface thereof, and a hinge bracket installing groove 14 formed on an inner periphery thereof.

The push button 11 may allow the locking sill 12 extending from an upper portion of the push button 11 to easily move back  
25 according to a pushing operation by a user, such that the

locking sill 12 is separated from a locking protrusion 21 of the outer lid 20.

The coupling protrusion 13 is formed on an inner periphery surface of the outer container 10 such that the coupling  
5 protrusion 13 is coupled to the container body 30.

The hinge bracket 36 of the container body 30 is installed into the hinge bracket installing groove 14 and the container body 30 is placed in the container body containing groove 15.

The outer container lid 20, which covers an upper portion  
10 of the outer container 10, is hinge-coupled to the outer container 10 to open or close the outer container 10.

The locking protrusion 21 is formed at one side of the outer container lid 20 and has a protrusion shape corresponding to the locking sill 12 of the outer container 10.

15 The container body 30 has a content containing space 31. The container body 30 is provided on a side surface thereof with inner and outer walls 32 and 33 and is formed on an outer periphery surface of the outer wall with the coupling groove  
35.

20 Contents are contained in the content containing space 31.

In addition, as shown in FIG. 7, an impregnation member 80 may be further installed into the content containing space 31 of the container body 30.

The impregnation member may include at least one selected  
25 from the group consisting of butadiene rubber, styrene

butadiene rubber, natural rubber, acrylonitrile-butadiene rubber, wet urethane, dry urethane, polyether, polyester, polyvinyl chloride, polyethylene, latex, silicon, polyvinyl alcohol, silicone agent elastomer, nitrile rubber, butyl rubber  
5 and neoprene.

A fitting protrusion 34 is formed on an upper end of the inner wall 32. As shown in FIG. 6D, the fitting protrusion 34 is fittingly coupled to a fitting part 52 of the rubber discharge pad 50.

10 The outer wall 33 is fitted with a sealing piece 42 of the container lid 40, such that the air-tightness of the container body 30 is enhanced.

The tension cap 60 is fittingly coupled between the inner and outer walls 32 and 33.

15 The coupling groove 35, which is formed on an outer periphery surface of the outer wall 33, is coupled to the coupling protrusion 13 of the outer container 10 to fix coupled when the container body 30 is contained in the container body containing groove 15 of the outer container 10.

20 In addition, the container body 30 is provided with the hinge bracket 36 and a hinge pin 37 such that the container body 30 is coupled to the container lid 40.

The hinge bracket 36 is formed on a side surface of the container body 30 and is installed into the hinge bracket  
25 installing groove 14, such that the hinge bracket 36 is hinge-

coupled to the container lid 40 with the hinge pin 37.

An opening/closing handle 41 is formed on one side surface of the container lid 40 to easily open or close the container lid 40.

5       The sealing piece 42 is formed on a lower end of the container lid 40. The sealing piece 42 is inserted into the outer wall 33 of the container body 30 so that the airtightness of the container body 30 is enhanced.

10       The hinge protrusion 43 is formed at one side of the container lid 40 and the hinge protrusion 43 is inserted into the hinge bracket 36 of the container body 30 such that the container lid 40 is fixed to the container body 30 with the hinge pin 37.

15       A puff keeping space 44 is formed on an upper surface of the container lid 40 to keep a puff (not shown) as a cosmetic tool.

The rubber discharge pad 50 is provided with the plurality of outlets 51 to allow contents to be discharged therethrough and provided on an end thereof with the fitting part 52.

20       The rubber discharge pad 50 is pressed to the bottom of the container body 30 by elasticity so that the contents contained in the container body 30 may be used without any residual. Since the contents are discharged through the outlets 51 of the rubber discharge pad 50, the discharge quantity of  
25       the contents contained in the container body 30 may be adjusted

according to pressure on the rubber discharge pad 50, so that the contents are prevented from being wasted.

The rubber discharge pad 50 may be formed of at least one of natural rubber, elastomer, silicon rubber, acrylonitrile-  
5 butadiene rubber, and synthetic resin having excellent elasticity.

A size of the outlet 51 is in the range of 0.01 mm to 1.2 mm. The number of outlets 51 is in the range of 100 to 600 and distributed on the rubber discharge pad 50. Preferably, the  
10 number of outlets 51 is in the range of 300 to 500.

A total of 50 women in their 20s and 30s have been surveyed about usability of the rubber discharge pads of following embodiments 1 to 6.

15 [Experiment example 1] Usability measurement according to size of outlet of rubber discharge pad

The usability of a consumer has been measured according to a size of an outlet of a rubber discharge pad.

[Table 1]

|                    | Embodiment<br>1 | Embodiment<br>2 | Embodiment<br>3 | Embodiment<br>4 | Embodiment<br>5 | Embodiment<br>6 |
|--------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Outlet<br>size     | 0.007 mm        | 0.01 mm         | 0.05 mm         | 0.8 mm          | 1.2 mm          | 1.5 mm          |
| Usability<br>score | 2.42            | 4.24            | 4.65            | 4.82            | 4.18            | 2.78            |

20

(1.0: Very bad, 2.0: Bad, 3.0: Normal, 4.0: Good, 5.0:

Very good)

As a result of measuring consumer usability according to a size of the outlet 51 of the rubber discharge pad 50, when the size of the outlet 51 is less than 0.01 mm, the particles of contents are not smoothly discharged due to surface tension, so that the usability is bad. When the size of the outlet 51 exceeds 1.2 mm, the contents are excessively discharged so that the customer usability is bad. Thus, the rubber discharge pad 50 cannot adjust the discharge quantity of contents.

10

[Experiment example 2] Usability measurement according to number of outlet of rubber discharge pad

To measure the usability of a consumer according to the number of outlets 51 of the rubber discharge pad 50, after

15 [Table 2]

|                      | Embodiment<br>1 | Embodiment<br>2 | Embodiment<br>3 | Embodiment<br>4 | Embodiment<br>5 | Embodiment<br>6 |
|----------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Number of<br>outlets | 70              | 100             | 300             | 400             | 600             | 650             |
| Usability<br>score   | 2.36            | 4.18            | 4.85            | 4.90            | 4.24            | 2.72            |

(1.0: Very bad, 2.0: Bad, 3.0: Normal, 4.0: Good, 5.0: Very good)

As a result of measuring consumer usability according to the number of the outlets 51 of the rubber discharge pad 50, when the number of the outlets 51 is less than 100, the

contents are not smoothly discharged, so that the usability of a customer is bad. When the number of the outlets 51 exceeds 600, the quantity of contents is too much discharged so that the customer usability is bad. Thus, the rubber discharge pad 50 cannot adjust the discharge quantity of contents.

In addition, as shown in Table 2, when the number of the outlets 51 is in the range of 300 to 400, the discharge quantity of contents is most suitable and the usability is very excellent.

That is, since the contents are discharged through the outlets 61 of the rubber discharge pad 50, the outlets are formed to have a size in the range of 0.01 mm to 1.2 mm. When the number of the outlets is in the range of 100 to 600, the customer usability may be excellent and the discharge quantity of contents may be suitably adjusted.

The rubber discharge pad 50 is formed on the end thereof with the fitting part 52 and the fitting 52 is fitted with the inner wall 32 of the container body 30 such that the rubber discharge pad 50 is fixedly coupled to the inner wall 32 of the container body 30.

Although the rubber discharge pad 50 is directly and fixedly coupled to the inner wall 32 of the container body 30 in an embodiment of the present invention, as shown in FIGS. 8A to 8C, the frame 70 is further included in another embodiment. After the rubber discharge pad 50 is coupled between the

tension cap 60 and the frame 70, the rubber discharge pad 50 is coupled to the container body 30.

The coupling protrusion 71 is formed on the upper end of the frame 70 and the fitting part 52 of the rubber discharge  
5 pad 50 is fittingly coupled to the coupling protrusion 71.

As shown in FIGS. 8B and 8C, after being fitted with the frame 70, when the rubber discharge pad 50 is coupled to the tension cap 60 and coupled to the fitting protrusion 34 of the inner wall 32 of the container body 30, the rubber discharge  
10 pad 50 may be coupled more firmly than that coupled without any frames 70.

In addition, when the rubber discharge pad 50 is assembled with the container body 30 after the frame 70 coupled to the rubber discharge pad 50 is coupled to the tension cap 60 in  
15 advance, the components are modularized so that the process of producing a cosmetic container having a rubber discharge pad according to the present invention is simplified and the producing speed is improved.

The tension protrusion 61 is formed on the upper surface  
20 of the tension cap 60 and the tension cap 60 is fittingly coupled between the inner and outer walls 32 and 33 of the container body 30.

As shown in FIGS. 5, 6D, 7 and 8C, the tension protrusion 61 presses a portion of a rim of the rubber discharge pad 50,  
25 such that the rubber discharge pad 50 is tightened and the

tension cap 60 allows the rubber discharge pad 50 to be firmly coupled to the container body 30. Thus, when the rubber discharge pad 50 is pressed, the rubber discharge pad 50 is prevented from being separated from the container body 30.

5 Hereinafter, the assembling method of a cosmetic container provided with a rubber discharge pad according to an embodiment of the present invention and the state of using the same will be described in detail as follows.

According to the present invention, the container body 30  
10 is coupled into the inside of the outer container 10 which is formed with the container body containing groove 15 and hinge-coupled to the outer container lid 20.

The container body 30 is hinge coupled to the container lid 40.

15 After the rubber discharge pad 50 is coupled to the upper end of the container body 30 as shown in FIG. 6A and 6B, the container body 30 is fitted with the tension cap 60 as shown in FIGS. 6C and 6D, so that the assembly of the cosmetic container provided with a rubber discharge pad according to the present  
20 invention is completed.

In addition, the rubber discharge pad 50 is not directly coupled to the container body 30, and as shown in FIGS. 8A to 8C, the rubber discharge pad 50 is coupled to the frame 70, thereby being coupled to the container body 30.

25 To use the cosmetic container provided with a rubber

discharge pad which is assembled according to the above-described scheme, the rubber discharge pad 50 is pressed with a puff.

When the rubber discharge pad 50 is pressed, the rubber  
5 discharge pad 50 is pressed downwardly of the container body 30, so that the contents contained in the container body 30 may be used without any residual.

In addition, since the contents contained in the container body 30 are discharged through the outlets 51 of the rubber  
10 discharge pad 50, the expansion sizes of the outlets 51 are changed as the rubber discharge pad 50 is pressed, so that the discharge quantity of contents may be adjusted.

As shown in FIGS. 5, 6D, 7 and 8C, the tension protrusion 61 of the tension cap 60 presses the rim portion of the rubber  
15 discharge pad 50 so that the rubber discharge pad 50 is expanded. In addition, the tension cap 60 allows the rubber discharge pad 50 to be firmly coupled to the container body 30, so that the rubber discharge pad 50 may be prevented from being separated from the container body 30 when a user uses the  
20 cosmetic container according to the present invention.

As shown in FIG. 7, the impregnation member 80 may be further included in the container body 30. When a low-viscosity water-in-oil product according to the related art is kept in the container for a long time during circulation, the aqueous  
25 materials of internal phase and the oil materials of external

phase may be separated from each other. However, when the contents are impregnated into the impregnation member 80, the contents are contained in a small cell of the impregnation member 80 of a sponge type, the contents are prevented from  
5 being divided into the aqueous and oil materials due to surface tension in the cell.

As described above, the cosmetic container provided with a rubber discharge pad described in this disclosure is an illustrative purpose only, and the present invention is not  
10 limited thereto. Thus, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art within the spirit and scope of the present invention and they will fall within the scope of the present invention.

15

**【Description of Reference Numeral】**

- 10: Outer container
- 11: Push button
- 12: Latching sill
- 20 13: Coupling protrusion
- 14: Hinge bracket installing groove
- 15: Container body containing groove
- 20: Outer container lid
- 21: Locking protrusion
- 25 30: Container body

|    |                              |
|----|------------------------------|
|    | 31: Content containing space |
|    | 32: Inner wall               |
|    | 33: Outer wall               |
|    | 34: Fitting protrusion       |
| 5  | 35: Coupling groove          |
|    | 36: Hinge bracket            |
|    | 37: Hinge pin                |
|    | 40: Container lid            |
|    | 41: Opening/closing handle   |
| 10 | 42: Sealing piece            |
|    | 43: Hinge protrusion         |
|    | 44: Puff keeping space       |
|    | 50: Rubber discharge pad     |
|    | 51: Outlet                   |
| 15 | 52: Fitting part             |
|    | 60: Tension cap              |
|    | 61: Tension protrusion       |
|    | 70: Frame                    |
|    | 71: Coupling protrusion      |
| 20 | 80: Impregnation member      |

## CLAIMS

### 【Claim 1】

A cosmetic container provided with a rubber discharge pad,  
5 which includes an outer container (10) provided with a  
container body containing groove (15), and an outer container  
lid (20) hinge-coupled to the outer container (10) to be opened  
or closed, the cosmetic container comprising:

a container body (30) contained in the outer container  
10 (10) and provided with an inner wall (32);

a rubber discharge pad (50) coupled to an upper end of the  
container body (30) and provided with an outlet (51); and

a tension cap (60) for fixing the rubber discharge pad  
(50) to the container body (30) while pressing the rubber  
15 discharge pad (50),

wherein the rubber discharge pad (50) is provided on an  
end thereof with an inserting part (52), the inserting part  
(52) is fitted with the inner wall (32) of the container body  
(30) to fixedly couple the rubber discharge pad (50) to the  
20 inner wall (32) of the container body (30),

the tension cap (60) is provided with a tension protrusion  
(61) and coupled to the container body (30), and the tension  
protrusion (61) presses a rim of the rubber discharge pad (50)  
to expand the rubber discharge pad (50).

25

**【Claim 2】**

A cosmetic container comprising an outer container (10) provided with a container body containing groove (15), and an outer container lid (20) hinge-coupled to the outer container  
5 (10),

wherein a container body (30) provided with an inner wall (32) is coupled to an inside of the outer container (10),

a rubber discharge pad (50) is coupled to an upper end of the container body (30) and is provided with an outlet (51),

10 a tension cap (60) provided with a tension protrusion (61) is fittingly coupled to the container body (30),

an inserting part (52) is formed on an end of the rubber discharge pad (50), and

the inserting part (52) is fitted with the inner wall (32)  
15 of the container body (30) such that the rubber discharge pad (50) is fixedly coupled to the inner wall (32) of the container body (30).

**【Claim 3】**

20 A cosmetic container provided with a rubber discharge pad, which includes an outer container (10) provided with a container body containing groove (15), and an outer container lid (20) hinge-coupled to the outer container (10) to be opened or closed, the cosmetic container comprising:

25 a container body (30) contained in the outer container

(10) and provided with an inner wall (32);

a frame (70) coupled to an upper end of the container body (30);

a rubber discharge pad (50) coupled to an upper end of  
5 frame (70) and provided with an outlet (51); and

, a tension cap (60) coupled to the rubber discharge pad (50) and the frame (70),

wherein the rubber discharge pad (50) is provided on an end thereof with an inserting part (52), the inserting part  
10 (52) is fitted with a coupling protrusion (71) of the frame (70) to fixedly couple the frame (70) to the inner wall (32) of the container body (30),

the tension cap (60) is provided with a tension protrusion (61) and coupled to the container body (30), and the tension  
15 protrusion (61) presses a rim of the rubber discharge pad (50) to expand the rubber discharge pad (50).

#### **【Claim 4】**

The cosmetic container of one of claims 1 to 3, further  
20 comprising a container lid (40) hinge-coupled to the container body (30).

#### **【Claim 5】**

The cosmetic container of one of claims 1 to 3, further  
25 comprising an outer wall (33) formed on a side surface of the

inner wall (32) of the container body (30).

**【Claim 6】**

The cosmetic container of one of claims 1 to 3, wherein a  
5 fitting protrusion (34) is formed on the inner wall (32) of the  
container body (30).

**【Claim 7】**

The cosmetic container of one of claims 1 to 3, further  
10 comprising an impregnation member (80) mounted on an inside of  
the container body (30).

**【Claim 8】**

The cosmetic container of claim 7, wherein the  
15 impregnation member (80) includes at least one selected from  
the group consisting of butadiene rubber, styrene butadiene  
rubber, natural rubber, acrylonitrile-butadiene rubber, wet  
urethane, dry urethane, polyether, polyester, polyvinyl  
chloride, polyethylene, latex, silicon, polyvinyl alcohol,  
20 silicone agent elastomer, nitrile rubber, butyl rubber and  
neoprene.

**【Claim 9】**

The cosmetic container of one of claims 1 to 3, wherein a  
25 sealing piece (42) is formed below the container lid (40).

**【Claim 10】**

The cosmetic container of one of claims 1 to 3, wherein the outlet (51) has a size in a range of 0.01 mm to 1.2 mm.

5

**【Claim 11】**

The cosmetic container of one of claims 1 to 3, wherein 100 to 600 outlets (51) are distributed onto the rubber discharge pad (50).

10

**【Claim 12】**

The cosmetic container of claim 11, wherein 300 to 500 outlets (51) are distributed onto the rubber discharge pad (50).

15