

(51) International Patent Classification:  
*E05C 1/04* (2006.01)(21) International Application Number:  
PCT/AU2011/000457(22) International Filing Date:  
20 April 2011 (20.04.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2010902217 21 May 2010 (21.05.2010) AU(71) Applicant (for all designated States except US): **STEEL STORAGE HOLDINGS PTY LTD** [AU/AU]; Northport Business Park, Unit 1, 425 Nudgee Road, Hendra, Brisbane, Queensland 4011 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PERRINS, Jon** [AU/AU]; Northport Business Park, Unit, 425 Nudgee Road, Hendra, Brisbane, Queensland 4011 (AU). **RYAN, Gerard** [AU/AU]; 52 Terrace Street, Toowong, Brisbane, Queensland 4066 (AU).(74) Agent: **WYNNES PATENT AND TRADE MARK ATTORNEYS**; PO Box 7053, Holland Park East, Brisbane, Queensland 4121 (AU).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: DOOR LATCH ASSEMBLY



(57) **Abstract:** A door latch assembly particularly for use in doors in self storage facilities. The door latch assembly comprises a latch, handle and locking arrangement in a single assembly. The assembly can be recessed to be substantially flush with the face of the door so as not to protrude into a passageway. The latch assembly can be inverted for right or left hand use. The assembly includes a base plate (11) having a grip aperture (18), a tongue (12) with a protruding grip portion (19) at the distal end from the locking end, a back guide (13) to locate and retain the tongue (12) with the base plate (11), said back guide (13) is fixable to the base plate (11), a handle member (14) comprising a finger grip recess (29) fixable to the base plate (11), wherein when assembled the grip portion (19) protrudes through the grip aperture (18) and the tongue (12) can slide between a laterally extended and a non-extended position relative to the base plate. The assembly further includes holes (22, 25) to accommodate the shackle of a padlock. On the base plate (11) adjacent the grip aperture (18) is two tabs (20, 21) with holes (22) which can align with two tabs (23, 24) also with holes (25) on the grip portion (19), when the holes align at either the extended or non-extended positions, the shackle of a padlock can pass through the aligned holes (22, 25) and lock the tongue (12) from moving.

