

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)

PCT

(10) International Publication Number
WO 03/059553 A2

(51) International Patent Classification⁷: **B22D**

(21) International Application Number: PCT/BR02/00192

(22) International Filing Date:
20 December 2002 (20.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PI 0106597-1 28 December 2001 (28.12.2001) BR

(71) Applicant (for all designated States except US): **EMPRESA BRASILEIRA DE COMPRESSORES S/A - EMBRACO** [BR/BR]; Rua Rui Barbosa, 1020, CEP-89219-901 Joinville, SC (BR).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **RAMIREZ, Rívio, Arturo** [BR/BR]; Rua Jacob Eisenhut, 400 - apt. 1102, CEP-89203-070 Joinville, SC (BR). **KRZEMINSKI, Edison** [BR/BR]; Rua Marquês de Olinda, 2016, CEP-89218-250 Joinville, SC (BR). **DROZDEK, Cláudio, Antonio** [BR/BR]; Rua Senador Teotônio Vilela, 86, CEP-89219-310 Joinville, SC (BR).

(74) Agents: **ARNAUD, Antonio, M., P.** et al.; Rua José Bonifácio, 93 - 9th floor, CEP-01003-901 São Paulo, SP (BR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG,

[Continued on next page]

(54) Title: PROCESS FOR THE INJECTION OF AN ELECTRIC MOTOR ROTOR



(57) Abstract: A process for the injection of an electric motor rotor, said rotor comprising: a lamination stack (10) having a central axial bore (11) and a plurality of axial channels (12); and a cage (30) of aluminum, which is formed by an upper end ring (31) and a lower end ring (32), which are interconnected by a plurality of bars (33) molten in the axial channels (12). The process comprises the steps of: mounting, at the upper end portion of the central axial bore (11), a stamping pin (40), which has a widened head (41) seated against the upper end lamination of the lamination stack (10); heating the lamination stack, as well as an upper cavity (21) and a lower cavity (22) of a mold (20); positioning the lamination stack (10) inside the mold (20); rotating the mold (20) and pouring the aluminum into the inside thereof through the inlet channel (23); removing, from the mold (20), the rotor (R) with the cage (30) already formed and comprising an upper plate (35) that covers the stamping pin (40); and axially extracting the stamping pin (40) in order to break, centrally, the upper plate (35), transforming it in the upper ring (31) of the cage (30).



WO 03/059553 A2



SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.