CLAIMS

1. A computer-implemented method for transaction processing ~~method~~, comprising:

receiving, by a server, a group establishment request from an initial node for establishing an online social networking group, the group establishment request comprising a condition of acquiring a predetermined resource from each member of the online social networking group;

receiving, by the server, the predetermined resource from the initial node, the predetermined resource being placed into a shared resource pool that is accessible to each member of the online social networking group;

generating, by the server, the online social networking group that includes the initial node as a first member;

receiving, by the server, a correlation request ~~for correlating~~ from an object node to ~~a node~~join the online social networking group;

initiating, by the server, a resource acquisition request preset by the ~~node~~ condition of joining the online social networking group to the object node;

querying, by the server, creditable resources of the object node, and verifying whether the creditable resources comprise ~~a target~~the predetermined resource required by the resource acquisition request~~; and~~

~~when the~~ to provide a verification result; and

when the verification result is yes,

extracting, by the ~~target~~server, the predetermined resource from the creditable resources of the object node, ~~and correlating the object node to the node group.~~

injecting, by the server, the predetermined resource extracted from the creditable resources of the object node into the shared resource pool of the online social networking group, and

adding, by the server, the object node to the online social networking group as a second member, wherein after joining the online social networking group, the object node is capable of accessing resources in the shared resource pool.

2. The computer-implemented method of claim 1, wherein the group establishment request includes the resource acquisition request.

3. The computer-implemented method of claim 1, further comprising:

~~injecting~~generating, by the ~~target~~server, a group identifier in response to receiving the group establishment request from the initial node; and

correlating, by the server, the group identifier with the resource ~~extracted from the creditable resources~~acquisition request.

4. The computer-implemented method of claim 3, wherein the group identifier identifies a correlation relationship between a node and a corresponding node group.

5. The computer-implemented method of claim 1, wherein the initial node is a first instant messaging node and the object node is a second instant messaging node.

6. A computer-implemented system for transaction processing, comprising one or more computers, and one or more computer memory devices interoperably coupled with the one or more computers and having tangible, non-transitory, machine-readable media storing instructions that, when executed by the one or more computers, perform operations comprising:

receiving, by a server, a group establishment request from an initial node for establishing an online social networking group, the group establishment request comprising a condition of acquiring a predetermined resource from each member of the online social networking group;

receiving, by the server, the predetermined resource from the initial node, the predetermined resource being placed into a shared resource pool that is accessible to each member of the ~~node~~online social networking group~~.~~;

~~3. A transaction processing method, comprising:~~

~~sending a correlation request to an object node, the~~generating, by the server, the online social networking group that includes the initial node as a first member;

receiving, by the server, a correlation request ~~comprising a resource acquisition request preset by a node~~from an object node to join the online social networking group;

initiating, by the server, a resource acquisition request preset by the condition of joining the online social networking group to the object node;

querying, by the server, creditable resources of the object node, and verifying whether the creditable resources comprise ~~a target~~the predetermined resource required by the resource acquisition request to provide a verification result; and

when the verification result is yes, ~~extracting the target resource from the creditable resources of the object node, and correlating the object node to the node group.~~

~~4. The method of claim 3, further comprising:~~

extracting, by the server, the predetermined resource from the creditable resources of the object node,

injecting, by the ~~target~~server, the predetermined resource extracted from the creditable resources of the object node into ~~a~~the shared resource pool of the ~~node~~online social networking group~~.~~, and

adding, by the server, the object node to the online social networking group as a second member, wherein after joining the online social networking group, the object node is capable of accessing resources in the shared resource pool.

7. The computer-implemented system of claim 6, wherein the group establishment request includes the resource acquisition request.

8. The computer-implemented system of claim 6, wherein the operations further comprise:

generating, by the server, a group identifier in response to receiving the group establishment request from the initial node; and

correlating, by the server, the group identifier with the resource acquisition request.

9. The computer-implemented system of claim 8, wherein the group identifier identifies a correlation relationship between a node and a corresponding node group.

10. The computer-implemented system of claim 6, wherein the initial node is a first instant messaging node and the object node is a second instant messaging node.

11.~~5.~~ A computer-implemented method for transaction processing ~~method~~, comprising:

~~receiving a correlation request for correlating an object user to a user group;~~

~~initiating a payment request preset by the user group to the object user;~~

receiving, by a server, a group establishment request from an initial node for establishing an online social networking group, the group establishment request comprising a condition of acquiring a predetermined resource from each member of the online social networking group;

receiving, by the server, the predetermined resource from the initial node, the predetermined resource being placed into a shared resource pool that is accessible to each member of the online social networking group;

generating, by the server, the online social networking group that includes the initial node as a first member;

transmitting, by the server, a correlation request to an object node, the correlation request comprising a resource acquisition request preset by the condition of joining the online social networking group;

querying ~~an available amount of money of an account~~, by the server, creditable resources of the object ~~user~~node, and verifying whether the ~~available amount of money is greater than or equal to a target amount of money~~creditable resources comprise the predetermined resource required by the ~~payment request~~resource acquisition request to provide a verification result; and

when the verification result is yes,

extracting, by the ~~target amount of money~~server, the predetermined resource from the ~~available amount of money of the account~~creditable resources of the object ~~user, and correlating the object user to the user group.~~node,

~~6. The method of claim 5, further comprising:~~

injecting ~~the target amount of money extracted from the available amount of money of the account of the object user into a shared account of the user group.~~

~~7. The method of claim 5, wherein~~

~~the object user is an instant messaging user;~~

~~the user group is an instant messaging group; and~~

~~the correlation request and the payment request are transmitted by using instant messages.~~

~~8. A transaction processing method, comprising:~~

~~sending a correlation request to an object user, the correlation request comprising a payment request preset by a user group;~~

~~querying an available amount of money of an account of the object user, and verifying whether the available amount of money is greater than or equal to a target amount of money required by the payment request; and~~

~~when the verification result is yes, extracting the target amount of money from the available amount of money of the account of the object user, and correlating the object user to the user group.~~

~~9. The method of claim 8, further comprising:~~

~~injecting the target amount of money extracted from the available amount of money of the account of the object user into a shared account of the user group.~~, by the server, the predetermined

~~10.~~ ~~The method of claim 8, wherein~~

~~the object user is an instant messaging user;~~

~~the user group is an instant messaging group; and~~

~~the correlation request and the payment request are transmitted by using instant messages.~~

~~11.~~ ~~A transaction processing system, comprising:~~

~~a receiving unit configured to receive a correlation request for correlating an object node to a node group;~~

~~a sending unit configured to initiate a resource acquisition request preset by the node group to the object node;~~

~~a verification unit configured to query creditable resources of the object node, and verify whether the creditable resources comprise a target resource required by the resource acquisition request; and~~

~~a correlation unit configured to, when the verification result is yes, extract the target resource from the creditable resources of the object node, and correlate the object node to the node group.~~

~~12. The system of claim 11, wherein the system further comprises a resource combination unit configured to inject the target resource extracted from the creditable resources of the object node into a shared resource pool of the node group.~~

~~13. A transaction processing system, comprising:~~

~~a sending unit configured to send a correlation request to an object node, the correlation request comprising a resource acquisition request preset by a node group;~~

~~a verification unit configured to query creditable resources of the object node, and verify whether the creditable resources comprise a target resource required by the resource acquisition request; and~~

~~a correlation unit configured to, when the verification result is yes, extract the target resource from the creditable resources of the object node, and correlate the object node to the node group.~~

~~14. The system of claim 13, wherein the system further comprises a resource combination unit configured to inject the target~~ resource extracted from the creditable resources of the object node into ~~a~~the shared resource pool of the ~~node~~online social networking group~~.~~, and

adding, by the server, the object node to the online social networking group as a second member, wherein after joining the online social networking group, the object node is capable of accessing resources in the shared resource pool.

12. The computer-implemented method of claim 11, wherein the group establishment request includes the resource acquisition request.

13.~~15. A transaction processing system,~~ The computer-implemented method of claim 11, further comprising:

~~a~~ generating, by the server, a group identifier in response to receiving the group establishment request from the initial node; and

correlating, by the server, the group identifier with the resource acquisition request.

14.~~unit configured to receive~~ The computer-implemented method of claim 13, wherein the group identifier identifies a correlation ~~request for correlating an object user to~~relationship between a ~~user~~node and a corresponding node group~~;~~.

~~a sending unit configured to initiate a payment request preset by the user group to the object user;~~

~~a verification unit configured to query an available amount of money of an account of the object user, and verify whether the available amount of money is greater than or equal to a target amount of money required by the payment request; and~~

~~a correlation unit configured to, when the verification result~~

15. The computer-implemented method of claim 11, wherein the initial node is ~~yes, extract the target amount of money from the available amount of money of the account of the object user, and correlate the object user to the user group.~~

~~16. The system of claim 15, wherein the system further comprises a resource combination unit configured to inject the target amount of money extracted from the available amount of money of the account of the object user into a shared account of the user group.~~

~~17. The system of claim 15, wherein~~

~~the object user is an~~a first instant messaging ~~user;~~

node and the ~~user group~~object node is ~~an~~a second instant messaging ~~group; and~~

~~the correlation request and the payment request are transmitted by using instant messages.~~

~~18. A transaction processing system, comprising:~~

~~a sending unit configured to send a correlation request to an object user, the correlation request comprising a payment request preset by a user group;~~

~~a verification unit configured to query an available amount of money of an account of the object user, and verify whether the available amount of money is greater than or equal to a target amount of money required by the payment request; and~~

~~a correlation unit configured to, when the verification result is yes, extract the target amount of money from the available amount of money of the account of the object user, and correlate the object user to the user group.~~

~~19. The system of claim 18, wherein the system further comprises a resource combination unit configured to inject the target amount of money extracted from the available amount of money of the account of the object user into a shared account of the user group.~~

~~20. The system of claim 18, wherein~~

~~the object user is an instant messaging user;~~

~~the user group is an instant messaging group; and~~

~~the correlation request and the payment request are transmitted by using instant messages.~~ node.