

Cleveland John

PATENT SPECIFICATION (11)

1 407 536

1 407 536

- (21) Application No. 49210/73 (22) Filed 23 Oct. 1973 (19)
(31) Convention Application No. 323 145 (32) Filed 12 Jan. 1973 in
(33) United States of America (US)
(44) Complete Specification published 24 Sept. 1975
(51) INT. CL.³ B65D 83/14
(52) Index at acceptance

FIR 3A3D11 3A3D12D 3A3D2 3A3D4A



(54) PRESSURISED AEROSOL SPRAY CAN

(71) I, THOMAS JOHN SMRT, a citizen of the United States of America, of 4N 671, Route 59, Bartlett, Illinois 60103, United States of America, do hereby declare the invention, for which I pray that a patent may be granted to me, and the method by which it is to be performed, to be particularly described in and by the following statement:—

This invention relates to pressurized aerosol spray cans, and, more particularly, to an actuating assembly for an aerosol spray can which sprays its contents when inverted.

The use of aerosol spray can to spray marking material on pavement, walkways, grass, and other surfaces is becoming increasingly common. Aerosol spray cans conventionally include a cylindrical body and a valve mounted in the top of the can. The valve includes a valve stem which opens the valve when moved, and a spray nozzle is mounted on the valve stem. Most aerosol cans also include a dip tube which extends from the valve to the bottom of the can so that the marking material within the can is expelled through the dip tube by the aerosol propellant when the can is upright.

A can having a dip tube is not convenient for spraying horizontal surfaces. The can must be held upwardly inclined relative to the horizontal so that the marking material covers the bottom of the dip tube and is pushed through the dip tube by the propellant. This means that the marking material will be sprayed onto the surface at an angle, which will decrease the accuracy or the control of the spraying, and the spray nozzle will be spaced from the surface, which might permit the spray to be blown by the wind before it reaches the surface. The necessity of holding the can upwardly inclined when spraying also makes the spraying procedure awkward and tiring, particularly when a large number of marks are to be made at different locations. The operator must squat or kneel in order to hold the can inclined upwardly yet relatively close to the surface, and the continual bending and straightening up at each spot to be marked can be very tiring. Simply bending from the

waist will not position the can close enough to the surface.

The invention utilizes a valve-equipped spray can that is not provided with a dip tube so that the contents of the can are sprayed when the can is inverted. The valve is opened when tilted, and the trigger of the actuating assembly can be easily pressed with one finger to move the valve when the can is pointed downwardly. Since the can can be actuated when pointed straight down, the operator need not assume an awkward, stooped position in order to spray but need only bend slightly from the waist. An opening in the cap exposes the trigger for actuation when desired, and when the can is not to be used, the cap can be rotated to move an at least substantially continuous portion of the wall of the cap into protecting relationship with the trigger.

An embodiment of the invention will be described by way of example, reference being made to the drawings in which:—

Fig. 1 is an exploded perspective view of an aerosol spray can;

Fig. 2 is a fragmentary sectional view through the top of the can and the actuating apparatus;

Fig. 3 is a view similar to Fig. 2 showing the actuation of the valve;

Fig. 4 is a fragmentary sectional top plan view of Fig. 2; and

Fig. 5 is a sectional view of the actuator without the spray nozzle taken along the line 5—5 of Fig. 4.

The numeral 10 designates an aerosol spray can having a cylindrical body 11 and a dome-shaped top 12. The top is provided with a central opening which is closed by a valve assembly 13. The valve assembly includes a cup 14 which is crimped over the edges of the top opening to form a gas-tight seal and an upwardly extending valve stem 15. The valve stem is connected to an aerosol valve within the valve assembly, and the valve is of the type that is opened when the valve stem is tilted. The can contains marking material, such as paint, and a conventional aerosol propellant, such as a blend of isobutane and propane. The marking ma-

[Price 33p]

9 5 P

terial is heavier than the propellant, and the marking material occupies the bottom of the can when the can is upright with the propellant thereabove. The valve assembly does not include a dip tube which conventionally extends downwardly from the valve to the bottom of the can. Thus, marking material is propelled from the can by the propellant when the can is inverted rather than when it is upright as shown.

The valve is opened or actuated when desired by an actuating assembly 16, which includes an integrally molded plastic actuator 17 and a cap 18. The actuator includes a generally cylindrical spray nozzle portion 19 provided with a central bore 20 which comprises three portions of decreasing diameter. A first or attaching portion 21 is sized to snugly receive the valve stem 15 so that the actuator is frictionally retained thereon, a reduced diameter intermediate portion 22 prevents the stem from being inserted too far into the bore, and a small diameter end portion 23 provides the spray orifice for marking material.

The actuator also includes a trigger portion 24 which extends outwardly from the nozzle portion and includes an outer finger portion 25 and a connecting or intermediate portion 26. The finger portion 25 extends through an arc of about 90° and includes a downwardly and outwardly curved or arcuate wall 27 which is adapted to be pressed by a finger and which is provided with arcuately extending ribs 28a and radially extending serrations 28b to prevent slipping. The connecting portion includes a flat generally sector-shaped top wall 29 which extends radially outwardly from the top of the nozzle portion to the top of the arcuate wall 27 and three radially extending ribs 30.

The cap 18 includes a cylindrical side wall 32 and a flat top wall 33. The side wall is provided with an opening 34, and the top wall is provided with an opening 35 directly above the spray nozzle. The lower edge of the side wall terminates in a curved rim 36 which can be snapped into a groove 37 formed in the can top 12.

The groove 37 is curved in cross section and extends for slightly more than a semi-circle so that when the curved rim 36 is snapped into the groove it is retained therein. The cap can be removed from the can when desired by exerting an upward force sufficient to compress the curved rim slightly to permit it to be withdrawn from the groove. When the rim is positioned within the groove, the cap is rotatable with respect to the can, but the groove frictionally retains the rim in any desired position.

When the contents of the can are to be sprayed, the cap is rotated to bring the side opening 34 adjacent the finger portion 25 of the trigger. The trigger terminates just

inwardly of the side wall of the cap, and the finger portion is readily accessible when exposed by the side opening. The can is pointed downwardly toward the surface to be sprayed, and the operator merely inserts his finger through the opening 34 to engage the trigger. When the finger portion 25 of the trigger is pressed toward the top of the can as shown in Fig. 3, the actuator is caused to pivot about the connection of the stem with the valve, and the pivoting of the stem opens the valve to spray the contents of the can through the nozzle as indicated at S. Although the can is shown upright in Fig. 3 for convenience of illustration, it will be understood that since the can is not provided with a dip tube, the marking material within the can is sprayed when the can is pointed downwardly.

The can can be conveniently held in one hand with the index finger extending through the side opening and engaging the trigger. Since the can is operated when it is pointed downwardly, the operator need only bend slightly at the waist to bring the nozzle into the desired spraying position relative to the surface. The operator can therefore quickly spray a large number of markings at different locations without discomfort or fatigue.

The bottom edge of the curved wall 27 has substantially the same curvature as the adjacent portion of the dome-shaped top 12, and this bottom edge is engageable with the dome-shaped top to prevent excessive movement of the actuator and nozzle. Excessive movement of the nozzle might decrease the accuracy of the sprayed material, cause some of the spray to hit the top of the can rather than passing through the opening therein, and excessively stress the connection between the valve stem and the valve.

When the can is not to be used for a period of time, the operator can prevent inadvertent actuation of the valve merely by rotating the cap 18 to move the side opening 34 away from the finger portion of the trigger. For example, rotation of the cap by only about 90° will bring an imperforate or at least substantially continuous portion of the side wall adjacent to the finger portion, the maximum dimension of the opening also extending through an arc of about 90°. The cap will be frictionally retained in a non-actuating position until the can is to be used again, at which time the cap is merely rotated to permit the side opening to expose the trigger. When the cap is in the non-actuating position, it can be carried in a packet, tool box, or the like without danger of the contents of the can being sprayed.

Referring to Fig. 2, the trigger is seen to be located inwardly of the side wall of the

cap, and even when the cap is in the actuating position shown, inadvertant actuation of the valve is unlikely.

5 WHAT I CLAIM IS:—

1. A pressurised aerosol spray can having a valve-equipped top, the valve being adapted to open when tilted; an actuator comprising a spray nozzle portion mounted on the valve and discharging in the direction of the longitudinal axis of the can, an intermediate portion extending outwardly from the nozzle portion generally transversely thereto, and a finger portion extending arcuately outwardly and downwardly from the intermediate portion whereby the valve can be opened by pressing the finger portion; and a cap rotatably mounted on the top of the can, the finger portion of the actuator being positioned inwardly of the cap, the cap having an opening through which the contents of the can are sprayed when the valve is opened, the cap being rotatable on the can between an actuating position in which an opening in the cap exposes the finger portion of the actuator and permits the actuator to be pressed to open the valve and non-actuating positions in which an at

least substantially continuous portion of the wall of the cap is adjacent to the finger portion of the actuator to prevent the actuator from being pressed, the top of the can being generally dome-shaped and the lower periphery of the finger portion of the actuator having substantially the same curvature as the dome-shaped top, the spacing between the lower periphery of the finger portion and the dome-shaped top when the valve is closed being such that the lower periphery of the finger portion engages the dome-shaped top, before the actuator is pressed sufficiently to spray the contents of the can against the cap.

2. The can of claim 1 in which the finger portion of the actuator is provided with a plurality of ribs, each rib extending in a plane transverse to the axis of the can.

3. A pressurised aerosol spray can substantially as hereinbefore described with reference to the accompanying drawings.

CLEVELAND & JOHNSON,
Chartered Patent Agents,
Agents for the Applicants,
Chancery House,
Chancery Lane,
London, WC2A 1QU.

Printed for Her Majesty's Stationery Office by Burgess & Son (Abingdon), Ltd.—1975.
Published at The Patent Office, 25 Southampton Buildings, London, WC2A 1AY,
from which copies may be obtained.

RECEIVED BY THE PATENT OFFICE INCLUDING THE DRAWINGS AND THE SPECIFICATION
AND THE OFFICE COPY OF THE SPECIFICATION AND DRAWINGS

THE PATENT OFFICE, 25 Southampton Buildings, London, WC2A 1AY

23 JUN 1977



cap, and even when the cap is in the actuating position shown, inadvertant actuation of the valve is unlikely.

5 WHAT I CLAIM IS:—

1. A pressurised aerosol spray can having a valve-equipped top, the valve being adapted to open when tilted; an actuator comprising a spray nozzle portion mounted 10 on the valve and discharging in the direction of the longitudinal axis of the can, an intermediate portion extending outwardly from the nozzle portion generally transversely thereto, and a finger portion extending arcuately outwardly and downwardly from the 15 intermediate portion whereby the valve can be opened by pressing the finger portion; and a cap rotatably mounted on the top of the can, the finger portion of the actuator 20 being positioned inwardly of the cap, the cap having an opening through which the contents of the can are sprayed when the valve is opened, the cap being rotatable on the can between an actuating position in 25 which an opening in the cap exposes the finger portion of the actuator and permits the actuator to be pressed to open the valve and non-actuating positions in which an at

least substantially continuous portion of the wall of the cap is adjacent to the finger portion of the actuator to prevent the actuator 30 from being pressed, the top of the can being generally dome-shaped and the lower periphery of the finger portion of the actuator having substantially the same curvature as the dome-shaped top, the spacing between 35 the lower periphery of the finger portion and the dome-shaped top when the valve is closed being such that the lower periphery of the finger portion engages the dome-shaped top, before the actuator is pressed 40 sufficiently to spray the contents of the can against the cap.

2. The can of claim 1 in which the finger portion of the actuator is provided with a 45 plurality of ribs, each rib extending in a plane transverse to the axis of the can.

3. A pressurised aerosol spray can substantially as hereinbefore described with 50 reference to the accompanying drawings.

CLEVELAND & JOHNSON,
Chartered Patent Agents,
Agents for the Applicants,
Chancery House,
Chancery Lane,
London, WC2A 1QU.

Printed for Her Majesty's Stationery Office by Burgess & Son (Abingdon), Ltd.—1975.
Published at The Patent Office, 25 Southampton Buildings, London, WC2A 1AY,
from which copies may be obtained.

I CERTIFY THAT, INCLUDING THE DRAWINGS, HEREIN, PART HEREON,
TO THE PATENT OFFICE COPY OF THE SPECIFICATION AS ACCEPTED

ACTING FOR CONTROLLER

THE PATENT OFFICE, 25 Southampton Buildings, London, WC2A 1AY

23 JUN 1977