

TANGENTIAL CUTTING INSERT AND MILLING CUTTER

FIELD OF THE INVENTION

The present invention relates to a tangential indexable cutting insert and a milling cutter for use in metal cutting processes in general and for milling a square shoulder in a workpiece in particular.

5

BACKGROUND OF THE INVENTION

Tangential cutting inserts, also known as on-edge, or lay down, cutting inserts, are oriented in an insert holder in such a manner that during a cutting operation on a workpiece the cutting forces are directed along a major (thicker) dimension of the cutting insert. An advantage of such an arrangement being that the cutting insert can withstand greater cutting forces than when oriented in such a manner that the cutting forces are directed along a minor (thinner) dimension of the cutting insert.

There is disclosed in EP 0 769 341 a face milling cutter employing a double-sided indexable tangential cutting insert having a prismatic shape with two opposed generally rectangular rake surfaces connected by side surfaces. The cutting insert has a basic "negative" geometry and therefore in order to provide the necessary clearance between the cutting insert and the workpiece, when mounted in a face-mill, the cutting insert is oriented with a negative axial rake

- 2 -

angle. However, negative axial rake angles are disadvantageous, e.g., they have been found to be deficient in cutting efficiency for applications involving difficult to machine materials.

A double-sided indexable tangential cutting insert for a boring tool head is disclosed in US 5,333,972. The insert is provided at each end with a protruding flat island. Each long cutting edge is inclined at an angle of 3° relative to the protruding flat island, defining an "insert axial rake angle". Rearward of each cutting edge is a descending land surface that merges with an increasing incident angle surface to form a chip breaker groove. Each increasing incident angle surface extends from its associated descending land surface to an adjacent island, at either the top or the bottom of the cutting insert. The cutting insert is left or right handed. It is manufactured to be right-handed and, when flipped around, is left-handed. It will be appreciated that the magnitude of the insert axial rake angle is limited for practical reasons. Any increase in the insert axial rake angle will result in an increase in the "vertical" extent of the increasing incident angle surface (see Fig. 3 of US 5,333,972) that will have an adverse effect on chip development and evacuation.

There is disclosed in WO 96/35536 a double-sided indexable tangential cutting insert which when mounted in a face-mill has a positive axial rake angle, even when the necessary clearance between the cutting insert and the workpiece is provided. This cutting insert presents two peripheral cutting edges for a right-hand face mill and two peripheral cutting edges for a left-hand face mill. In a side view (see Fig. 9) the cutting insert is generally rhomboidal in shape. The main cutting edges of each end surface are parallel (see also Figs. 7 and 8) to each other and to a centrally located protruding abutment member 12. The cutting insert is retained in an insert pocket with the abutment member of a non-operative end surface and an adjacent non-operative relief surface in abutment with respective support surfaces of the insert pocket. The abutment member of the non-operative end surface and the adjacent non-operative relief

- 3 -

surface merge at an acute-angled mounting corner. In order to change the axial rake angle of the operative cutting edge, either the insert pocket has to be rotated, or a cutting insert having a mounting corner with a different mounting angle has to be used. In either case, a different milling cutter has to be used. Moreover, 5 the axial rake and relief angles are interdependent and any change in the axial relief angle results in a corresponding change in the relief angle, which is not always desirable.

It is an object of the present invention to provide a double-sided indexable tangential cutting insert that substantially overcomes the above- 10 mentioned problems.

It is a further object of the present invention to provide a double-sided indexable tangential cutting insert having four main cutting edges, for a given direction of rotation of the milling cutter, each main cutting edge having a positive axial rake angle when mounted as an operative cutting edge in a milling 15 cutter.

It is yet a further object of the present invention to provide a double-sided indexable tangential cutting insert capable of milling a square shoulder in a workpiece.

20 SUMMARY OF THE INVENTION

In accordance with the present invention there is provided a tangential cutting insert, for use in a milling cutter, comprising:

two identical opposing end surfaces of a generally rectangular shape in an end view of the cutting insert;

25 a peripheral side surface extending between the two opposing end surfaces, the peripheral side surface comprising two identical opposing major side surfaces of a generally parallelogrammatic shape, two opposing minor side surfaces and corner side surfaces located between adjacent major and minor side surfaces; and a peripheral edge formed at the intersection of each end surface and the

- 4 -

peripheral side surface, two sections of each peripheral edge constituting cutting edges;

each end surface having four corners, two diagonally opposed lowered corners and two diagonally opposed raised corners, the lowered corners being
5 closer to a median plane of the cutting insert than the raised corners;

each cutting edge comprising a major cutting edge formed by the intersection of a given major side surface with a given end surface;

each end surface being provided with an abutment member having an abutment surface;

10 wherein, in each cross section of the cutting insert taken in a plane parallel to a minor plane of the cutting insert, the abutment surface of a particular end surface is closer to the median plane than a leading section of one of the major cutting edges of the particular end surface.

Typically, the leading section of each major cutting edge extends from
15 adjacent a respective raised corner to at least the minor plane.

Preferably, each cutting edge further comprises a minor cutting edge and a corner cutting edge formed, respectively, by the intersection of minor and corner side surfaces with either end surface.

Further preferably, the two end surfaces have 180° rotational
20 symmetry about a first axis passing therethrough.

Yet further preferably, the major side surfaces have 180° rotational symmetry about a second axis passing therethrough, the second axis being perpendicular to the first axis.

Yet further preferably, the two minor side surfaces have 180°
25 rotational symmetry about a third axis passing therethrough, the third axis being perpendicular to the first axis and the second axis.

If desired, each minor side surface is divided into two minor side sub-surfaces by a major plane along a join where the major plane intersects the minor side surface, each minor side sub-surface extending away from the join at an

- 5 -

angle α with respect to a plane passing through the join and parallel to the minor plane.

Generally, the angle α is in the range of one to two degrees.

In accordance with the present invention, in an end-view of the cutting
5 insert the abutment surface is elongated in form having two long edges extending between two short edges.

Preferably, the two short edges are substantially parallel.

Further preferably, a larger portion of one of the two short edges is located on one side of the major plane and a larger portion of the other one of the
10 two short edges is located on the opposite side of the major plane.

There is also provided in accordance with the present invention, a milling cutter comprising:

at least one cutting insert in accordance with the present invention; and

a cutter body having at least one insert pocket in which the at least one
15 cutting insert is retained, the at least one insert pocket comprising adjacent side and rear walls generally transverse to a base, the rear wall being generally convex; the side wall being provided with an axial location surface that abuts a given minor side surface of the at least one cutting insert at a given axial abutment region; the rear wall being provided with two protruding tangential location surfaces, located
20 on either side of a central region of the rear wall, a first of the two tangential location surfaces abuts a first tangential abutment surface located on the abutment surface of the at least one cutting insert, a second of the two tangential location surfaces abuts a second tangential abutment surface located on the abutment surface.

25 In accordance with the present invention, the given axial abutment region is located on a forward region of a radially outer minor side sub-surface of the given minor side surface, the forward region being distal the rear wall of the insert pocket.

Further in accordance with the present invention, the first and second

tangential abutment surfaces are located on opposite sides of the minor plane.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding, the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Fig. 1 is a perspective view of a cutting insert in accordance with the present invention;

Fig. 2 is a first side view of the cutting insert in Fig. 1;

Fig. 3 is an end view of the cutting insert shown in Fig. 1;

Fig. 4 is a second side view of the cutting insert shown in Fig. 1;

Fig. 5 is a cross-sectional view of the cutting insert shown in Fig. 1 taken along V-V in Fig. 4;

Fig. 6A is a partial cross section of the cutting insert shown in Fig. 1 taken along VIA-VIA in Fig. 3.

Fig. 6B is a partial cross section of the cutting insert shown in Fig. 1 taken along VIB-VIB in Fig. 3.

Fig. 6C is a partial cross section of the cutting insert shown in Fig. 1 taken along VIC-VIC in Fig. 3.

Fig. 7 is a perspective view of a milling cutter in accordance with the present invention; and

Fig. 8 is a perspective view of a portion of the cutter body of the milling cutter in accordance with the present invention, showing in detail an insert pocket.

DETAILED DESCRIPTION OF THE INVENTION

Attention is first drawn to Figs. 1 to 5, showing a cutting insert **10** in accordance with the present invention there. The cutting insert **10** is tangential and indexable, and is typically manufactured by form-pressing and sintering carbide powders. The cutting insert **10** is generally rectangular in an end view and has two identical opposing end surfaces **12**. Each end surface **12** has 180°

- 7 -

rotational symmetry about a first axis **A1** passing through the two end surfaces **12**.

A peripheral side surface **14** extends between the two opposing end surfaces **12** and comprises two opposed identical minor side surfaces **16**, two
5 opposed identical major side surfaces **18**, and four opposed corner side surfaces **22**. Each pair of adjacent minor and major side surfaces **16**, **18** merge at a common corner side surface **22**. The two identical opposing major side surfaces **18** each have 180° rotational symmetry about a second axis **A2** which is perpendicular to the first axis **A1** and passes through the opposing major side
10 surfaces **18**. Similarly, the two identical opposing minor side surfaces **16** each have 180° rotational symmetry about a third axis **A3** passing through the opposing minor side surfaces **16**. The third axis **A3** is perpendicular to the first axis **A1** and to the second axis **A2**. A minor plane **P1** of the cutting insert is defined by the first axis **A1** and the second axis **A2**, a major plane **P2** of the
15 cutting insert **10** is defined by the first axis **A1** and the third axis **A3** and a median plane **M** is defined by the second axis **A2** and the third axis **A3**.

Each end surface **12** has four corners, two diagonally opposed lowered corners **24** and two diagonally opposed raised corners **26**. The lowered corners **26** are closer to the median plane **M** than the raised corners **24**. Each corner side
20 surface **22** extends between a given raised corner **26** of one of the two opposing end surfaces **12** and a given lowered corner **26** of the other of one of the two opposing end surfaces **12**. Each end surface **12** is provided with an abutment member **28** having an abutment surface **30** which is generally concave or V-shaped in form. In accordance with a preferred embodiment the abutment
25 surface **30** comprises three generally flat portions, two outer portions **32** with an inner portion **34** therebetween.

Referring to Fig. 3, it can be seen that in an end-view of the cutting insert **10** the abutment surface **30** has the form of a distorted parallelogram, having two long edges **36** extending between two short edges **38**. Therefore,

- 8 -

each outer flat portion 32 of the abutment surface 30, extends from a respective short edge 38 to the inner flat portion 34. The two short edges 38 are preferably substantially parallel to each other. As can be seen in Fig. 3, in an end view of the cutting insert 10, a longitudinal axis C of the abutment member 28 makes an acute angle β with the major plane P2, so that the two short edges 38 are substantially located on opposite sides of the major plane P2. In other words, a larger portion of one of the two short edges 38 is located on one side of the major plane P2 and a larger portion of the other one of the two short edges 38 is located on the opposite side of the major plane.

10 A peripheral edge 40 is formed at the intersection of each end surface 12 and the peripheral side surface 14. For each end surface 12, the peripheral edge 40 comprises two major edges 42, formed by the intersection of the major side surfaces 18 with the end surface 12; two minor edges 44, formed by the intersection of the minor side surfaces 16 with the end surface 12; and two corner edges 42, formed by the intersection of the corner side surfaces 22 with the end surface 12.

In the cutting insert 10 of the present invention at least two sections of each peripheral edge 40 constitute cutting edges 52. Each cutting edge 52 comprises a major cutting edge 54, extending from a respective raised corner 24 along substantially the whole length of its associated major edge 42; a minor cutting edge 56, extending along at least half of the length of its associated minor edge 44; and a corner cutting edge 58, associated with a raised corner 24 and at which the major and minor cutting edges 54, 56 merge. Adjacent each cutting edge 52 in the end surfaces 12 is a rake surface 60 along which chips, removed from a workpiece during a milling operation, flow. A leading section 54' of each major cutting edge 54 extends from adjacent a respective raised corner 24 to at least the minor plane P1 and a trailing section 54'' extends from the leading section 54' to a respective lowered corner 26. Between the rake surface 60 adjacent the trailing section 54'' and the abutment member 28 there is a chip

groove 62. The portion of the abutment member 28 adjacent the chip forming groove 62 constitutes a chip deflector 64.

Referring to Fig. 2, it is seen that each minor side surface 16 is divided into two minor side sub-surfaces 70 by a join 72 where the major plane P2 intersects the minor side surface 16. Each minor side sub-surface 70 extends away from the join 72 at an acute angle α with respect to a plane P3 passing through the join 72 and parallel to the minor plane P1. In accordance with a specific application this angle is approximately 1.5°. The cutting insert is provided with a through bore 74 extending between the major side surfaces 18 and having a bore axis B coinciding with the second axis A2.

As can be seen in Figs. 6A to 6C, in each cross section of the cutting insert taken in a plane parallel to the minor plane P1 of the cutting insert 10, the abutment surface 30 of a particular end surface 12 is closer to the median plane M than a leading section 54' of one of the major cutting edges 54 of the particular end surface 12. For example, in the cross section shown in Fig. 6A, the leading section 54' of the major cutting edge 54 to the left of the figure, is located at a distance D1 from the median plane M, whereas, the respective abutment surface 30 is located at a distance d1, where D1 is greater than d1. Similarly, in the cross section shown in Fig. 6B, the leading section 54' of the major cutting edge 54 is located at a distance D2 from the median plane M, whereas, the abutment surface 30 is located at a distance d2, where D2 is greater than d2. Similarly, in the cross section shown in Fig. 6C, taken at the location of the minor plane P1, the leading section 54' of the major cutting edge 54 is located at a distance D3 from the median plane M, whereas, the abutment surface 30 is located at a distance d3, where D3 is greater than d3. In other words, the abutment member 28 in the region of the leading section 54' of major cutting edge 54 and up to, and a little beyond the minor plane P1 (as can be seen in Fig. 4), does not protrude above the major cutting edge 54. As a consequence, chips cut from a workpiece in the region leading section 54' of the major cutting edge

- 10 -

54 are well formed during a milling process. However, in the region of the trailing section **54''** of the major cutting edge **54**, the chip deflector **64** protrudes above the major cutting edge **54** (as can be seen in Fig. 4 and on the right hand side of Figs 6A and 6B), which can disturb the development of the chips.

5 In order to reduce the influence of the chip deflector **64** in the region of the trailing section **54''**, the abutment member **28** is designed to be more distant from the major cutting edge **54** in the region of the trailing section **54''** than it is in the region of the leading section **54'**. Consequently, as described above, in an end view of the cutting insert **10**, the longitudinal axis **C** of the
10 abutment member **28** makes an acute angle β with the major plane **P2**. Although the shape of the major cutting edge **54** is shown in Fig. 4 to be generally straight in a side view, it can have any desired shape as long as generally slopes downwardly from the raised corner **24** to the lowered corner **26**. With reference to Fig. 2, it can be seen that in a side view of the minor side surface **16**, the minor
15 edge **44** is clearly divided into two sections, a first section **46** extending from the raised corner **24** to a little way before the major plane **P2** and a second section **48** extending from the first section **46** to the lowered corner **26**. The first section **46** is approximately straight and is perpendicular to the major side surface **18** in a side view (see Fig. 2) and is oriented at the angle α with respect to the plane **P3**
20 in an end view (see Fig. 3). The second section **48** extends from adjacent the major plane **P2** slopingly towards the lowered corner **26** in a side view (see Fig. 2) and is oriented at the angle α with respect to the plane **P3** in an end view (see Fig. 3). It is the first section **46** of the minor edge **44** that forms the minor cutting edge **56**.

25 Attention is now drawn to Fig. 7, showing a milling cutter **80** with an axis of rotation **R**, having a cutter body **82** provided with a plurality of insert pockets **84**. In each insert pocket **84** a cutting insert **10** in accordance with the present invention is clamped by means of a clamping screw (not shown). The axial rake angle will generally be in the range of 5° to 20°. As can be seen, each

cutting insert is seated so that there will be a clearance between a workpiece (not shown) and the cutting insert's minor side surface 16 adjacent the milling cutter's face 86. The structure of the insert pocket 84 is shown in detail in Fig. 8. The insert pocket 84 comprises adjacent side and rear walls 88, 90 generally transverse to a base 92.

The rear wall 90 is generally convex and the side wall 88 is provided with an axial location surface 94 for abutting a given minor side surface 16 of the cutting insert 10 at an axial abutment region 96. The rear wall 90 is provided with two protruding tangential location surfaces, an upper tangential location surface 98, adjacent the pocket side wall 88 and a lower tangential location surface 100. The two tangential location surfaces are located on either side of a central region 102 of the rear wall 90. The upper tangential location surface 98 abuts an upper tangential abutment surface 104 located on the abutment surface 30 of the cutting insert 10. The lower tangential location surface 100 abuts a lower tangential abutment surface 106 located on the abutment surface 30. Clearly, the terms "lower" and "upper" used here with respect to the abutment surface 30 are used only when the cutting insert 10 is mounted in the milling cutter 80, and with respect to the orientation shown in Fig. 7. Similarly, with respect to Fig. 7, the axial abutment region 96 is located on a forward region 108 of a radially outer minor side sub-surface 110, the forward region being distal the rear wall of the insert pocket 90.

As can be seen in Fig. 3, the two tangential abutment surfaces 104, 106 on each abutment surface 30 are located on opposite sides of the minor plane. As can be seen in Fig. 2, each minor side sub-surface 70 is provided with one axial abutment region 96 adjacent a lowered corner 26. The base 92 of the insert pocket 84 is provided with a threaded bore 112 for receiving a clamping screw in order to secure the cutting insert 10 in the insert pocket 84. When the cutting insert 10 is secured in the insert pocket 84, a radially inner major side surface 20 will abut the base 92 of the insert pocket 84. Preferably, the major side surfaces 18 of the cutting insert 10 are ground. Further preferably, the minor side sub-

- 12 -

surfaces **70** are ground. With these surfaces ground, good positioning of the cutting insert **10** in the insert pocket **84** is ensured.

Although the present invention has been described to a certain degree of particularity, it should be understood that various alterations and modifications
5 could be made without departing from the spirit or scope of the invention as hereinafter claimed.

CLAIMS:

1. A tangential cutting insert (10), for use in a milling cutter (80), comprising:

two identical opposing end surfaces (12) of a generally rectangular shape in
5 an end view of the cutting insert (10);

a peripheral side surface (14) extending between the two opposing end surfaces (12), the peripheral side surface (14) comprising two identical opposing major side surfaces (18) of a generally parallelogrammatic shape, two opposing minor side surfaces (16) and corner side surfaces (22) located between adjacent
10 major and minor side surfaces (18, 16); and

a peripheral edge (40) formed at the intersection of each end surface (12) and the peripheral side surface (14), two sections of each peripheral edge (40) constituting cutting edges (52);

each end surface (12) having four corners (24, 26), two diagonally opposed
15 lowered corners (26) and two diagonally opposed raised corners (24), the lowered corners (26) being closer to a median plane **M** of the cutting insert (10) than the raised corners (24);

each cutting edge (52) comprising a major cutting edge (54) formed by the intersection of a given major side surface (18) with a given end surface (12);

20 each end surface (12) being provided with an abutment member (28) having an abutment surface (30);

wherein, in each cross section of the cutting insert (10) taken in a plane parallel to a minor plane **P1** of the cutting insert (10), the abutment surface (30) of a particular end surface (12) is closer to the median plane **M** than a leading
25 section (54') of one of the major cutting edges (54) of the particular end surface (12).

2. The cutting insert (10) according to claim 1, wherein the leading section (54') of each major cutting edge (54) extends from adjacent a respective raised corner (24) to at least the minor plane **P1**.

- 14 -

3. The cutting insert (10) according to claim 1, wherein each cutting edge (52) further comprises a minor cutting edge (56) and a corner cutting edge (58) formed, respectively, by the intersection of minor and corner side surfaces (16, 22) with either end surface (12).
- 5 4. The cutting insert (10) according to claim 1, wherein the two end surfaces (12) have 180° rotational symmetry about a first axis **A1** passing therethrough.
5. The cutting insert (10) according to claim 2, wherein the major side surfaces (18) have 180° rotational symmetry about a second axis **A2** passing
10 therethrough, the second axis **A2** being perpendicular to the first axis **A1**.
6. The cutting insert (10) according to claim 1, wherein the two minor side surfaces (16) have 180° rotational symmetry about a third axis **A3** passing therethrough, the third axis **A3** being perpendicular to the first axis **A1** and the second axis **A2**.
- 15 7. The cutting insert (10) according to claim 1, wherein each minor side surface (16) is divided into two minor side sub-surfaces (70) by a major plane **P2** along a join (72) where the major plane **P2** intersects the minor side surface (16), each minor side sub-surface (70) extending away from the join (72) at an angle α with respect to a plane **P3** passing through the join (72) and parallel to the minor
20 plane **P1**.
8. The cutting insert (10) according to claim 1, wherein the angle α is in the range of one to two degrees.
9. The cutting insert (10) according to claim 8, wherein in an end-view of the cutting insert (10) the abutment surface (30) is elongated in form having
25 two long edges (36) extending between two short edges (38).
10. The cutting insert (10) according to claim 8, wherein the two short edges (38) are substantially parallel.
11. The cutting insert (10) according to claim 9, wherein a larger portion of one of the two short edges (38) is located on one side of the major plane **P2**

- 15 -

and a larger portion of the other one of the two short edges (38) is located on the opposite side of the major plane **P2**.

12. A milling cutter (80) comprising:

at least one cutting insert (10) in accordance with any one of claims 1 to 11;

5 and

a cutter body (82) having at least one insert pocket (84) in which the at least one cutting insert (10) is retained, the at least one insert pocket (84) comprising adjacent side and rear walls (88, 90) generally transverse to a base (92), the rear wall (90) being generally convex; the side wall (88) being provided with an axial
10 location surface (94) that abuts a given minor side surface (16) of the at least one cutting insert (10) at a given axial abutment region (96); the rear wall (90) being provided with two protruding tangential location surfaces (98, 100), located on either side of a central region (102) of the rear wall (90), a first of the two tangential
15 location surfaces (98, 100) abuts a first tangential abutment surface located on the abutment surface (30) of the at least one cutting insert (10), a second of the two tangential location surfaces (98, 100) abuts a second tangential abutment surface located on the abutment surface (30).

13. The milling cutter (80) according to claim 12, wherein the given axial abutment region (96) is located on a forward region (108) of a radially outer minor
20 side sub-surface (110) of the given minor side surface (16), the forward region (108) being distal the rear wall (90) of the insert pocket (84).

14. The milling cutter (80) according to claim 12, wherein the first and second tangential abutment surfaces (104, 106) are located on opposite sides of the minor plane P1.