

## CLAIMS

1. A computer-implemented method comprising:

presenting, via a display, multiple interfaces associated with multiple respective applications within a multi-application environment, a first ~~at least~~ one of the multiple

5 interfaces being a first ~~an~~ immersive interface occupying a first region of the multi-application environment, a second one of the multiple interfaces being a second immersive interface occupying a second region of the multi-application environment, the first immersive interface presenting a desktop that includes at least one windows-based interface and a taskbar through which interaction with the first immersive interface is  
10 enabled;~~and~~

presenting first content through ~~at least one of the~~ first immersive ~~multiple~~ interfaces and second content through the second immersive interface, the second content being moving, visual media content;

receiving, via a first portion of a gesture, initiation of user selection to present,  
15 within the multi-application environment, a third interface associated with a previously-interacted-with application;

presenting, responsive to initiation of the user selection, an image representing the third interface over the multi-application environment, the image being a reduced-sized image of content previously-presented via the third interface;

20 determining, based on a second portion of the gesture that completes the user selection, selection of the first region or second region in which to present the third interface, the second portion of the gesture indicated by movement of the image over the first region or second region; and

responsive to selection of the first region, expanding, based on a size of the first region, the image representing the third interface into at least a portion of the first region effective to present the third interface in the first region while concurrently reducing a size of, or removing, the first immersive interface from the first region of the multi-interface environment; or

25 responsive to selection of the second region, expanding, based on a size of the second region, the image representing the third interface into at least a portion of the second region effective to present the third interface in the second region while concurrently reducing a size of, or removing, the second immersive interface from the second region of the multi-application environment.  
30

~~2. A computer-implemented method as described in claim 1, further comprising presenting second content concurrently with presenting the first mentioned content, the second content presented through another of the multiple interfaces.~~

2. A computer-implemented method as described in claim 1, wherein the third interface is a third immersive interface and the reduced-sized image represents content previously-presented by the third immersive interface.

3. A computer-implemented method as described in claim 12, wherein presenting the first-~~mentioned~~ content presents first moving, visual media in real time and presenting the second content presents the second content ~~moving, visual media~~ in real time.

~~4. A computer-implemented method as described in claim 1, wherein the immersive interface represents a desktop, the desktop having at least one windows-based interface or a taskbar.~~

5.4. A computer-implemented method as described in claim 14, further comprising enabling interaction with an application associated with the windows-based interface and through the multi-application environment.

~~6. A computer-implemented method as described in claim 4, wherein the desktop further includes a task bar, and further comprising enabling interaction, through the multi-application environment, with the task bar.~~

7.5. A computer-implemented method as described in claim 1, wherein the first content or the second content is received by the multi-application environment from one of the multiple respective applications.

~~8. A computer-implemented method as described in claim 1, wherein another of the multiple interfaces is a windows-based interface.~~

9.6. A computer-implemented method as described in claim 1, wherein the first immersive interface, second immersive interface, and third interface multi-application environment does not include a visible control.

~~10. A computer-implemented method as described in claim 1, further comprising:  
enabling selection to alter a size or a location in the multi-application environment or remove from the multiple application environment at least one of the multiple interfaces; and~~

~~responsive to receiving the selection, altering the size of, altering the location of, or removing the selected interface from the multi-application environment.~~

~~presenting content through two or more of the multiple interfaces and at a same time;~~

~~enabling selection to alter a size or a location of one of the multiple interfaces; and  
responsive to receiving the selection, concurrently altering the size or the location  
of the one of the multiple interfaces and another of the multiple interfaces.~~

7. One or more hardware-based computer-readable storage media comprising  
instructions that, responsive to execution by one or more hardware-based processors,  
cause the one or more hardware-based processors to perform operations comprising:

presenting, via a display, multiple interfaces associated with multiple respective  
applications within a multi-application environment, a first one of the multiple interfaces  
being a first immersive interface occupying a first region of the multi-application  
environment, a second one of the multiple interfaces being a second immersive interface  
occupying a second region of the multi-application environment, the first immersive  
interface presenting a desktop that includes at least one windows-based interface and a  
taskbar through which interaction with the first immersive interface is enabled;

presenting first content through the first immersive interface and second content  
through the second immersive interface, the second content being moving, visual media  
content;

receiving, via a first portion of a gesture, initiation of user selection to present,  
within the multi-application environment, a third interface associated with a previously-  
interacted-with application;

presenting, responsive to initiation of the user selection, an image representing the  
third interface over the multi-application environment, the image being a reduced-sized  
image of content previously-presented via the third interface;

determining, responsive to receiving a second portion of the gesture that completes  
the user selection, selection of the first region or second region in which to present the  
third interface, reception of the second portion of the gesture indicated by movement of  
the image over the first region or second region; and

responsive to selection of the first region, expanding the image representing the  
third interface into at least a portion of the first region effective to present the third  
interface in the first region and reducing a size of, or removing, the first immersive  
interface from the first region of the multi-interface environment; or

responsive to the selection of the second region, expanding the image representing  
the third interface into at least a portion of the second region effective to present the third  
interface in the second region and reducing a size of, or removing, the second immersive  
interface from the first region of the multi-application environment.

8. The one or more hardware-based computer-readable storage media as described in claim 7, wherein a size of the first region is different from a size of the second region and the method further comprises moving, based on a pre-determined size of the third interface, an immersive interface divider to alter the size of the first region or the size of the second region.

9. The one or more hardware-based computer-readable storage media as described in claim 8, wherein altering the size of the first region or the second region includes sizing the first region or the second region to a respective predetermined size of the first immersive interface or the second immersive interface.

10. The one or more hardware-based computer-readable storage media as described in claim 8, wherein altering the size of the first region or the size of the second region includes switching the sizes of the first region and the second region.

11. The one or more hardware-based computer-readable storage media as described in claim 7, wherein the display is a gesture-sensitive display and the first and second portions of the gesture are received through the gesture-sensitive display and over the multi-application environment.

12. The one or more hardware-based computer-readable storage media as described in claim 11, wherein the first portion of the gesture has a start point at an edge of the multi-application environment and a later point not at the edge of the multi-application environment.

13. A system comprising:  
one or more hardware-based processors; and  
one or more computer-readable storage media storing instructions thereon that, responsive to execution by the one or more hardware-based processors, cause the one or more hardware-based processors to perform operations comprising:

presenting multiple interfaces associated with multiple respective applications within a multi-application environment, a first one of the multiple interfaces being a first immersive interface occupying a first region of the multi-application environment, a second one of the multiple interfaces being a second immersive interface occupying a second region of the multi-application environment, the first immersive interface presenting a desktop that includes at least one windows-based interface and a taskbar through which interaction with the first immersive interface is enabled;

presenting first content through the first immersive interface and second content through the second immersive interface, the second content being moving, visual media content;

5 receiving, via a first portion of a gesture, initiation of user selection to present, within the multi-application environment, a third interface associated with a previously-interacted-with application;

presenting, responsive to initiation of the user selection, an image representing the third interface over the multi-application environment, the image being a reduced-sized image of content previously-presented via the third interface;

10 determining, responsive to receiving a second point of the gesture that completes the user selection, selection of the first region or second region in which to present the third interface, the second portion of the gesture indicated by movement of the image over the first region or second region; and

15 responsive to selection of the first region, expanding the image representing the third interface into at least a portion of the first region effective to present the third interface in the first region and reducing a size of , or removing, the first immersive interface from the first region of the multi-interface environment; or

20 responsive to the selection of the second region, expanding the image into at least a portion of the second region effective to present the third interface in the second region and reducing a size of , or removing, the second immersive interface from the second region of the multi-interface environment.

14. A system as described in claim 13, wherein the third interface is a third immersive interface and the reduced-sized image represents content previously-presented by the third immersive interface.

25 15. A system as described in claim 13, wherein the first immersive interface, second immersive interface, or third interface does not include a visible control.

16. A system as described in claim 13, wherein the first immersive interface or the second immersive is removed from the respective region and the operations further comprise moving the immersive interface removed from the respective region to a fourth region of the multi-application environment.

30 17. A system as described in claim 13, wherein the display is a gesture-sensitive display and the first and second portions of the gesture are received through the gesture-sensitive display.

18. A system as described in claim 13, wherein the first portion of the gesture has a start point at an edge of the multi-application environment and a later point not at the edge of the multi-application environment.

5 19. A computer-implemented method as described in claim 1, wherein the first immersive interface or the second immersive is removed from the respective region and the operations further comprise moving the immersive interface removed from the respective region a fourth region of the multi-application environment.

10 20. A computer-implemented method as described in claim 1, wherein the first immersive interface or the second immersive is removed from the respective region and third interface is presented such that the third interface fully occupies the respective region.