

HARNESS FOR STRETCHING THE PENIS

TECHNICAL FIELD

The present invention relates to harnesses for stretching of human tissue, and in particular the penis. The present invention utilizes originally constructed harness to accomplish stretching of the penis.

BACKGROUND ART

5 Numerous attempts have been made in order to solve the problem of phallus elongating and enlargening. The following art defines present state of this field : Jorn (EP0814733), Jakob (WO9728764), Heinz-Guenther (DE19915407 and DE19620719), Daniel (US5599275), Didier (EP0370932) etc, all describe mechanical devices for stretching the penis by using mechanical
10 and/or gravitational forces, while Roland (US5836864) uses the same forces adding a vacuum in his invention for obtaining the same purpose. All aforesaid devices have one big drawback: they are not designed for whole-day use. Mechanical parts this devices are made of are: rigid, sensitive to human body movement, uncomfortable for use and due to their's bulky size they are very well noticeable under the clothing. All these shortcomings reduce the use of these
15 apparatuses only on for home use i.e. for conditions of privacy use, and consequently cause their's low efficiency. With respect to a fact that for elongation and enlargement of the penis a man need to wear these devices constantly and for a long period of time (e.g. 1 year, 6-8 hours each day for 2-3cm gain approximately), the most important thing, one has to concern about while constructing such device, is to make it comfortable and practical for use in any occasion
20 (walking, sitting on work, car driving, bus riding, physical work, physical activities and sports etc.). Chan (CA2444663) with penis enlargement underwear and especially Jochum (WO9918897) with penis extension harness disclose means for penis enlargening which can be worn during whole day, but both means do not effectively solve the problem of fast and easy stretching force adjustment.

DISCLOSURE OF THE INVENTION

25 Accordingly, the primary object of the present invention is to provide a harness for stretching a human penis that is comfortable and practical for a long time and whole-day use.

Another object of the present invention is to provide a harness for stretching a human penis of any size, with the possibility of attaining strong tractive forces, and with the possibility of
30 fast and easy regulation of said forces.

To meet the aforesaid needs, according to the invention a harness for stretching the penis comprises a belt, adapted to be worn around one's waist, connected at the rear side via small rotating snap-hooks with two inextensible cinching straps, said straps each having a pair of

half-rings for length adjustment. One said strap on lower end carrying adjustable rope loop to be placed around penis base. Second said strap on lower end is connected via L-shaped connecting member with flexible adjustable loop being encircled and tightened around penis next to the penis head. Tightening of the said straps provides permanent penis stretching force, which force in a sufficiently long time, by the process of tissue mass increasing (which process was, and still is very well known to many primitive tribes), provides penis elongation and enlargement. The provided harness is accomplished from flexible, human-body-friendly materials, do not contain bulky rigid parts and is therefore easy to wear and to bear. The harness is not noticeable not only under the trousers, but also under the shorts, boxers etc. While using it one can freely walk, do everyday activities, work, drive a car, even run, swim and do many other activities. Furthermore, using adequate fingers' moves over the clothing or through the pockets (even while walking, without stopping), a man can easily and quickly adjust stretching force on straps. By this harness is possible to provide heavy traction on penis, due to its construction and due to a fact it is made of strong inextensible band at the rear side of the belt, of inextensible cinching straps and of very low elastic rope loop (the only needed-to-be flexible part is silicone i.e. rubber loop), providing this way the harness can be used for stretching the penis of any (even big) size. Minimal size (the same minimal size for all sizes of the penises), weight and single-part feature of L-shaped connecting member facilitate a harness to be "imperceptible" while in use, while U-shaped aperture on said member provides a wide range of angles and positions penis can be stretched in. Comfortability of the harness is further provided with possibility of easy changing of the sides of the cinching straps (i.e. change of penis placement and stretching side). Comfortability is also conducted with fast-release function of both rope and elastic loops in order to prevent any kind of pain arising and side-effects. This harness is very easy to disassemble and to wash. Regarding to durable materials harness is made of, it can be used for years.

This and other features and advantages of the present invention will become apparent from the following more detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings illustrate the present invention. In such drawings:

- FIG. 1 is a view in front elevation of the present invention
- FIG. 2 is a view in front elevation of present invention disassembled on its 3 subsystems
- FIG. 3 is a view in front elevation of the present invention as worn by a user
- FIG. 4 is a view in rear elevation of the present invention as worn by a user
- FIG. 5 illustrate a rope regulator means

FIG. 6 illustrate a L-shaped connecting member

BEST MODE FOR CARRYING OUT THE INVENTION

Referring now to FIGS. 1 - 4, the illustrated harness for stretching the penis includes stretchable belt 1, manufactured from mixture of cotton and synthetic fibres or like, having adjusting means 2 for securing around one's waist. Adjusting means 2 can have a wide variety of embodiments. In this preferred embodiment it comprises a simple plastic light-weight buckle. Referring to FIG. 4, unstretchable strong thin string 3 and, over said string, unstretchable strong band with holes 4, both made from synthetic fibres, are attached to the rear outer side of the belt 1, along with the upper edge thereof. String 3 is attached to the belt 1 at three points : at the both left and right ends and at the middle, and said string is pulled out twice ie. through the two of holes of the band 4 (through which two holes depends on a user's waist size - see FIG. 4) such forming two loops 5 and 6. In loops 5 and 6 are plugged subsystems A and B (see FIG. 2) using small metal rotating snap-hooks 7 and 14 respectively. In accordance with the provided functionality of the present invention and for the sake of easier description three functional parts of the present invention are further signed as belt means subsystem, subsystem A and subsystem B. Subsystem B provides tractive forces to the penis and to the belt 1 in certain directions, while subsystem A provides tractive forces in opposite direction relating to subsystem B to the penis, but also to the belt 1, in order to prevent belt 1 rotation around wearer's waist and consequently loose and total absence of stretching forces. A further object of subsystem A is to provide means for disabling testicles pulling-up under the influence of tractive force, leaving them freely hanging, such preventing any pain arousal and side effects emersion.

Subsystem A consist of (see FIG. 2) unstretchable cotton cinching strap 8 having two metal half-rings 9 for strap length adjustment, which said strap upper part is inserted through loop on snap-hook 7 and lower part is inserted around part of the rope 11 which part is threaded through holes 24a and 24b on rope regulator means 10 (see FIG. 5). Subsystem A further includes said rope regulator means 10 and said rope 11 with protective pad 12, which rope 11 is threaded thorough holes 24a and 24b on rope regulator means 10, thus rope 11 forming in use adjustable loop 13 for penis base abutment.

Subsystem B consist of (see FIG. 2) unstretchable cotton cinching strap 15 having two metal half-rings 16 for strap length adjustment, which said strap upper part is inserted through loop on snap-hook 14 and lower part is inserted through U-shaped aperture 20 on L-shaped generally planar connecting member 17 (see FIG. 6). Subsystem B further includes said member 17 having two holes 21, through which holes elastic cord-like member 18 is inserted,

thus said cord-like member 18 forming in use adjustable loop 19 for enabling stretching force appliance on the edge of the head of the penis.

Rope 11 is of 9 - 10 mm diameter and is preferably made of synthetic fibres. Rope regulator means 10 and connecting member 17 are manufactured of heavy-duty unflexible material, under this exemplary embodiment from transparent plastic, but may be also manufactured of metal, woods etc, and both may be partially coated with some thin, soft and skin-cosy material. L-shaped connecting member 17 is, in this preferred embodiment, preferably of the smallest size it can be embodied respective to all of the including constitutive elements and functionality (see FIG. 6). Elastic cord-like member 18 is of 5 - 6 mm diameter, preferably formed of silicone, but may be manufactured of soft rubber too, and is preferably hose-like (hollow inside), but may be cord-like (full profile).

Referring now to FIG. 2, harness for stretching the penis according to the present invention is shown disassembled on its subsystems, while in use, first, belt 1 is loosely secured (it is not needed a belt 1 to be firmly tightened since all the forces are applied at its rear portion to the band 4) around a male's waist using buckle 2, thus that buckle 2 is not placed on the middle of the wearer's body, in order not to interact with eventually present trouser's buckle. Then, the head of the penis (optionally being previously wrapped with 1 or 2 layers of the protective gauze) is inserted through elastic loop 19 formed of elastic cord-like member 18 in conjunction with connecting member 17, whereby cinching strap 15 with snap-hook 14 and half-rings 16 are freely hanging down. Said cord-like member 18 is then cinched around penis next to the penis head, and said cord-like member 18 is finally being fixed using channels 22a and 22b on said connecting member 17, thus providing fulcrum for stretching force application. After that, in use, subsystem A is being connected by the snap-hook 7 to the belt 1 via loop 5, and penis and subsystem B (being already connected with) together are inserted through rope loop 13, formed of rope regulator means 10, rope 11 and protective pad 12, having said pad 12 placed on the top (dorsal) side of the base of the penis. Further, snap-hook 14 is connected to loop 6 on belt 1 providing the harness for stretching the penis to be ready for use. Finally, cinching straps 8 and 15 are gradually and alternately tightened, until desired tractive force is attained.

Desired angle of torsion of the penis while stretching is provided by strap's 15 lower part gliding along the aperture 20 (in a direction of the arrows e or f, see FIG. 3) which adjustment of the torsion angle is possible due to a U-shape and at the same time L-shape design of aperture 20 (see FIG. 6).

Respecting that the cinching straps 8 and 15 freely glide on its upper parts through loops of the snap-hooks 7 and 14 respectively, and said straps freely glide on its lower parts through

part of the rope 11 and through aperture 20 on connecting member 17 respectively, it is very easy to place pairs of half-rings 9 and 16 respectively (by in-one-point traction of said strap's side next to the wearer's body or that strap's second side carrying half rings, where traction is realised either in a direction of the arrow c or in a direction of the arrow d, see FIG. 3) in a place on one's body where said half-rings are easiest to manage and hence to adjust stretching forces, even over the clothing, and even while walking.

Fast and easy unplugging of snap-hooks 7 and 14, which hold on subsystems A and B to the belt 1, from loops 5 and 6, and replacement of the positions of said snap-hooks and consequently said subsystems provides fast and easy alternation of one's body side where penis is settled, meaning that the penis is stretched while settled in left or in right groin groove, all of this towards better comfortability of the harness and towards side-effects preventing.

While preferred embodiment of the present invention have been shown and described, various modifications may be made without departing from the scope of the present invention, and all such equivalents and modifications are intended to be covered.

CLAIMS

What is claimed is :

1. A harness for stretching the penis comprising
a belt (1) for encircling the waist of the user with a fastening means (2),
a means (A) for application of tractive forces at the base of the penis and at the said belt and
5 for preventing testicles from unpleasant pulling-up caused by the stretching force,
a means (B) for application of tractive forces at the edge of the head of the penis and at the
said belt **characterized by**

that the belt (1) comprises at a rear side two string loops (5,6) with adjustable position for
connecting said means (A) and said means (B) with said belt.

- 10 2. Harness for stretching the penis according to claim 1 **characterized by** that the loops
(5,6) for connecting two cinching straps (8,15) are constructed of a string (4) which is pulled
out twice through two of a holes in a holed-band (3), and both said string and said holed-band
are attached at an upper part of an outer side of a rear portion of the said belt (1), whereby
having said holed band attached over said string.

- 15 3. Harness for stretching the penis according to claim 1 **characterized by** that the means
(A) for applying tractive force at the base of the penis and at the belt (1) and for preventing
testicles from unpleasant pulling-up caused by the stretching force comprises a cinching strap
(8), the strap (8) further includes a rotating snap-hook (7) for connecting the cinching strap (8)
to the belt (1), two half-rings (9) for said strap length adjustment, a rope (11) with a protective
20 pad (12) and a rope regulator means (10) for forming an adjustable loop (13) for the penis base
abutment.

4. Harness for stretching the penis according to claim 1 **characterized by** that the means
(B) for applying tractive force at the edge of the head of the penis and at the belt (1) comprises
a cinching strap (15), the strap (15) further includes a rotating snap-hook (14) for connecting
25 the strap (15) to the belt (1), two half-rings (16) for the strap (15) length adjustment, a flexible
and slightly extensible cord-like member (18) and a L-shaped connecting member (17) for
connecting the penis with the cinching strap (15) and for forming an adjustable loop (19) for
encircling around the penis next to the edge of the penis head and hence for enabling tractive
force appliance thereto.

- 30 5. Harness for stretching the penis according to claim 3 **characterized by** that the rope
regulator means (10), for forming the adjustable loop for penis base abutment (13), is a single
U-shaped rigid member having a pair of slightly overlapping holes (23a with 24a, 23b with 24b)
on

each of a two U-branches, said holes (23a,24a,23b,24b) for the rope (11) leading and securing, said holes having diameter equal to diameter of said rope.

- 5 6. Harness for stretching the penis according to claim 4 characterized by that the L-shaped connecting member (17), for connecting the penis with the cinching strap (15) and for forming the adjustable loop (19) for encircling around the penis next to the edge of the penis head and hence for enabling tractive force appliance thereto, is a single rigid planar L-shaped member, having an U-shaped aperture (20) on a L-shape's shorter portion for the cinching strap (15) passing through, having a pair of channels (22a,22b) on each of a sides of a L-shape's longer portion for the cord-like member (18) adjusting, securing and fast releasing, said channels
10 dimensioned for tight cord-like member (18) passing through, and said connecting member (17) having a two adjacent holes (21) in a middle of a lower end of said L-shape's longer portion for said cord-like member (18) passing through, which said cord-like member such forms the adjustable loop (19) for encircling the penis next to the penis head, said holes (21) having diameter greater than diameter of said cord-like member.