

A LOW TEMPERATURE GASIFICATION FACILITY WITH A HORIZONTALLY ORIENTED GASIFIER

FIELD OF THE INVENTION

5 The present invention pertains to the field of carbonaceous feedstock gasification and to its conversion into syngas and subsequent use to generate energy.

BACKGROUND OF THE INVENTION

Gasification is a process that enables the conversion of carbonaceous feedstock, such as municipal solid waste (MSW), biomass, coal, into a combustible gas. The gas can be used to generate electricity, steam or as a basic raw material to produce chemicals and liquid fuels.
10

Possible uses for the gas include: the combustion in a boiler for the production of steam for internal processing and/or other external purposes, or for the generation of electricity through a steam turbine; the combustion directly in a gas turbine or a gas engine for the production of electricity; fuel cells; the production of methanol and other liquid fuels; as a further feedstock for the production of chemicals such as plastics and fertilizers; the extraction of both hydrogen and carbon monoxide as discrete industrial fuel gases; and other industrial applications.
15

Generally, the gasification process consists of feeding carbonaceous feedstock into a heated chamber (the gasifier) along with a controlled and/or limited amount of oxygen and optionally steam. In contrast to incineration or combustion, which operate with excess oxygen to produce CO₂, H₂O, SO_x, and NO_x, gasification processes produce a raw gas composition comprising CO, H₂, H₂S, and NH₃. After clean-up, the primary gasification products of interest are H₂ and CO.
20

Useful feedstock can include any municipal waste, waste produced by industrial activity and biomedical waste, sewage, sludge, coal, heavy oils, petroleum coke, heavy refinery residuals, refinery wastes, hydrocarbon contaminated soils, biomass,
25

and agricultural wastes, tires, and other hazardous waste. Depending on the origin of the feedstock, the volatiles may include H_2O , H_2 , N_2 , O_2 , CO_2 , CO , CH_4 , H_2S , NH_3 , C_2H_6 , unsaturated hydrocarbons such as acetylenes, olefins, aromatics, tars, hydrocarbon liquids (oils) and char (carbon black and ash).

- 5 As the feedstock is heated, water is the first constituent to evolve. As the temperature of the dry feedstock increases, pyrolysis takes place. During pyrolysis the feedstock is thermally decomposed to release tars, phenols, and light volatile hydrocarbon gases while the feedstock is converted to char.

- Char comprises the residual solids consisting of organic and inorganic materials.
10 After pyrolysis, the char has a higher concentration of carbon than the dry feedstock and may serve as a source of activated carbon. In gasifiers operating at a high temperature ($> 1,200^\circ\text{C}$) or in systems with a high temperature zone, inorganic mineral matter is fused or vitrified to form a molten glass-like substance called slag.

- Since the slag is in a fused, vitrified state, it is usually found to be non-hazardous and
15 may be disposed of in a landfill as a non-hazardous material, or sold as an ore, road-bed, or other construction material. It is becoming less desirable to dispose of waste material by incineration because of the extreme waste of fuel in the heating process and the further waste of disposing ash as a residual waste, material that can be converted into a useful syngas and solid material.

- 20 The means of accomplishing a gasification process vary in many ways, but rely on four key engineering factors: the atmosphere (level of oxygen or air or steam content) in the gasifier; the design of the gasifier; the internal and external heating means; and the operating temperature for the process. Factors that affect the quality of the product gas include: feedstock composition, preparation and particle size; gasifier
25 heating rate; residence time; the plant configuration including whether it employs a dry or slurry feed system, the feedstock-reactant flow geometry, the design of the dry ash or slag mineral removal system; whether it uses a direct or indirect heat generation and transfer method; and the syngas cleanup system. Gasification is usually carried out at a temperature in the range of about 650°C to 1200°C , either
30 under vacuum, at atmospheric pressure or at pressures up to about 100 atmospheres.

There are a number of systems that have been proposed for capturing heat produced by the gasification process and utilizing such heat to generate electricity, generally known as combined cycle systems.

5 The energy in the product gas coupled with substantial amounts of recoverable sensible heat produced by the process and throughout the gasification system can generally produce sufficient electricity to drive the process, thereby alleviating the expense of local electricity consumption. The amount of electrical power that is required to gasify a ton of a carbonaceous feedstock depends directly upon the chemical composition of the feedstock.

10 If the gas generated in the gasification process comprises a wide variety of volatiles, such as the kind of gas that tends to be generated in a low temperature gasifier with a "low quality" carbonaceous feedstock, it is generally referred to as off-gas. If the characteristics of the feedstock and the conditions in the gasifier generate a gas in which CO and H₂ are the predominant chemical species, the gas is referred to as
15 syngas. Some gasification facilities employ technologies to convert the raw off-gas or the raw syngas to a more refined gas composition prior to cooling and cleaning through a gas quality conditioning system.

Utilizing plasma heating technology to gasify a material is a technology that has been used commercially for many years. Plasma is a high temperature luminous gas that is
20 at least partially ionized, and is made up of gas atoms, gas ions, and electrons. Plasma can be produced with any gas in this manner. This gives excellent control over chemical reactions in the plasma as the gas might be neutral (for example, argon, helium, neon), reductive (for example, hydrogen, methane, ammonia, carbon monoxide), or oxidative (for example, air, oxygen, carbon dioxide). In the bulk phase,
25 a plasma is electrically neutral.

Some gasification systems employ plasma heat to drive the gasification process at a high temperature and/or to refine the offgas/syngas by converting, reconstituting, or reforming longer chain volatiles and tars into smaller molecules with or without the addition of other inputs or reactants when gaseous molecules come into contact with
30 the plasma heat, they will disassociate into their constituent atoms. Many of these

atoms will react with other input molecules to form new molecules, while others may recombine with themselves. As the temperature of the molecules in contact with the plasma heat decreases all atoms fully recombine. As input gases can be controlled stoichiometrically, output gases can be controlled to, for example, produce substantial
5 levels of carbon monoxide and insubstantial levels of carbon dioxide.

The very high temperatures (3000 to 7000°C) achievable with plasma heating enable a high temperature gasification process where virtually any input feedstock including waste in as-received condition, including liquids, gases, and solids in any form or combination can be accommodated. The plasma technology can be positioned within
10 a primary gasification chamber to make all the reactions happen simultaneously (high temperature gasification), can be positioned within the system to make them happen sequentially (low temperature gasification with high temperature refinement), or some combination thereof.

The gas produced during the gasification of carbonaceous feedstock is usually very
15 hot but may contain small amounts of unwanted compounds and requires further treatment to convert it into a useable product. Once a carbonaceous material is converted to a gaseous state, undesirable substances such as metals, sulfur compounds and ash may be removed from the gas. For example, dry filtration systems and wet scrubbers are often used to remove particulate matter and acid gases from the gas
20 produced during gasification. A number of gasification systems have been developed which include systems to treat the gas produced during the gasification process.

These factors have been taken into account in the design of various different systems which are described, for example, in U.S. Patent Nos. 6,686,556, 6,630,113, 6,380,507; 6,215,678, 5,666,891, 5,798,497, 5,756,957, and U.S. Patent Application
25 Nos. 2004/0251241, 2002/0144981. There are also a number of patents relating to different technologies for the gasification of coal for the production of synthesis gases for use in various applications, including U.S. patent Nos. 4,141,694; 4,181,504; 4,208,191; 4,410,336; 4,472,172; 4,606,799; 5,331,906; 5,486,269, and 6,200,430.

Prior systems and processes have not adequately addressed the problems that must be
30 dealt with on a continuously changing basis. Some of these types of gasification

systems describe means for adjusting the process of generating a useful gas from the gasification reaction. Accordingly, it would be a significant advancement in the art to provide a system that can efficiently gasify carbonaceous feedstock in a manner that maximizes the overall efficiency of the process, and/or the steps comprising the
5 overall process.

This background information is provided for the purpose of making known information believed by the applicant to be of possible relevance to the present invention. No admission is necessarily intended, nor should be construed, that any of the preceding information constitutes prior art against the present invention.

10

SUMMARY OF THE INVENTION

An object of the present invention is to provide a low temperature gasification facility with a horizontally oriented gasifier.

15

In accordance with an aspect of the present invention, there is provided a low-temperature system for the conversion of carbonaceous feedstock into syngas of a defined composition, said system comprising a horizontally oriented gasifier for conversion of carbonaceous feedstock into off-gas and solid residue, said gasifier having a feedstock input means, gas outlet means and a solid residue outlet means and comprising a stepped floor, wherein each step is provided with a moving shelf lateral
20 transfer means for moving material through said gasifier during processing; a gas reformulating subsystem for the conversion of off-gas produced in said gasifier into syngas containing CO and H₂; a residue conditioning subsystem for melting and homogenizing said solid residue, and a control system to regulate the operation of the system.

25

BRIEF DESCRIPTION OF THE FIGURES

Embodiments of the present invention will now be described, by way of example only, with reference to the attached Figures.

Figure 1 is a flow diagram showing the different regions of the gasifier in general terms.

Figure 2 is a representation of the gasification processes occurring in Regions 1, 2 and 3 of one embodiment of the gasifier.

- 5 Figure 3 depicts an overview process flow diagram of a low-temperature gasification facility incorporating an exemplary gas conditioning system according to one embodiment of the invention, integrated with downstream gas engines.

Figure 4 is a site layout for the entire gasification system.

Figure 5 shows the layout of the storage building for the municipal solid waste.

- 10 Figure 5A shows the view of the waste handling system.

Figure 5B shows a schematic of the plastics handling system.

Figure 6 is a perspective view of one embodiment of the gasifier, detailing the feedstock input, gas outlet, residue outlet, carrier-ram enclosure and access ports.

- 15 Figure 7 is a side view of the gasifier illustrated in Figure 6 detailing the air boxes, residue can and dust collector.

Figure 8 is a central longitudinal cross-sectional view through the gasifier illustrated in Figures 6 and 7, detailing the feedstock input, gas outlet, residue outlet, lateral transfer means, thermocouples and access ports.

- 20 Figure 9 illustrates a blown up cross sectional view detailing the air boxes, carrier-ram fingers, residue extractor screw and serrated edge of step C.

Figure 10 is a sectional view of the gasifier of Figures 6 and 7 detailing the refractory.

Figure 11 details the air box assembly of Step A and B of the gasifier illustrated in Figures 6 to 10.

- 25 Figure 12 illustrates a cross sectional view of the Step C air box of the gasifier illustrated in Figures 6 to 10.

Figure 13 illustrates a cross sectional view of the gasifier of Figures 6 to 10 detailing an air box.

Figure 14 details the dust seal of the multi-finger carrier-ram of the gasifier illustrated in Figures 6 to 10.

- 5 Figure 15 showing the dust removal system of one embodiment of the gasifier illustrated in Figures 6 to 10 detailing the dust pusher, dust can attachment, shutter, operator handle and chain mechanism.

Figure 16 details the carrier-ram enclosure of the gasifier illustrated in Figures 6, 7, 8, 9 & 10 detailing the carrier-ram structure.

- 10 Figure 17 is an illustration detailing the level switch locations in one embodiment of the invention.

Figure 18 shows the setup of the gasifier, gas reformulating chamber and the residue conditioning chamber.

- 15 Figure 19 is a cross-sectional view of the setup of the gasifier, gas reformulating chamber and the residue conditioning chamber.

Figure 20 is a schematic of the gas reformulating chamber.

Figure 21 is a view of the inner wall of the reformulating chamber.

Figure 22 is a top-down view of the reformulating chamber showing the position of the torches, and the air and steam nozzles.

- 20 Figure 23 shows the arrangement of the swirl inlets around the reformulating chamber.

Figure 24 shows the attachment of a plasma torch on the reformulating chamber.

Figure 25A is a cross-sectional view of the reformulating chamber of Figure 20.

- 25 Figure 25B is a diagram illustrating the air-flow within a gasifier comprising the gas reformulating system of the invention including the reformulating chamber of Figure

20.

Figure 25C illustrates the injection of air from the air inputs into the reformulating chamber of Figure 20 and its effect on air-flow within;

Figure 26 is a functional block diagram of the residue conditioning system.

- 5 Figure 27 shows a view of the actual implementation of the residue conditioning system and its connections to the gasifier and the baghouse filter.

Figure 28 shows a cross-sectional view of the residue conditioning chamber.

Figure 29 shows another view of the residue conditioning chamber.

- Figure 30 shows a view of the residue conditioning chamber and the quench tank with
10 the conveyor used for the transfer of vitrified slag to the slag stockpile.

Figure 31 shows the entire residue conditioning system from another angle and also shows the support structure used for the residue conditioning chamber.

Figure 32 shows the arrangement of the residue gas conditioning system with the residue conditioning chamber.

- 15 Figure 32B shows another view of the residue gas conditioning system with the residue conditioning chamber.

Figure 33 depicts a process flow diagram of the entire system, and in particular the gas conditioning system (GCS).

- Figure 34 depicts the setup of the gas conditioning system integrated with a syngas
20 regulation system according to one embodiment of the present invention.

Figure 35 is a more detailed drawing of the heat exchanger and shows the process air blower used for the control of the air input to the heat exchanger.

- Figure 36 depicts a dry injection system whereby activated carbon or other adsorbents is held in a storage hopper and is fed into the syngas stream by rotating screw. The
25 syngas stream pipe is angled so that carbon not entrained in the gas stream rolls into

the baghouse.

Figure 37 presents an exemplary schematic diagram of the dry injection system in combination with the baghouse.

Figure 38 presents an exemplary schematic diagram of the HCl scrubber and associated components.

Figure 39 shows a system for collecting and storing waste water from the gas conditioning system.

Figure 40 depicts a process flow diagram of an H₂S removal process using a Thiopaq-based bioreactor, in accordance with one embodiment of the invention.

Figure 41 is an illustration of a gas homogenization system, in accordance with one embodiment of the invention, where gas is delivered from a single source to a single homogenization chamber and then delivered to multiple engines, each engine having its own gas/liquid separator and heater.

Figure 42 is an illustration of a fixed-volume homogenization chamber, in accordance with an embodiment of the invention.

Figure 43 is a high-level schematic diagram of a gasification system and control system therefore;

Figure 44 is an alternative diagrammatic representation of the gasification and control systems of Figure 43;

Figure 45 is a flow diagram of a control scheme for controlling the gasification system of Figures 43 and 44;

Figure 46 is a flow diagram of an alternative control scheme for controlling the gasification system of Figures 43 and 44, wherein this system is further adapted for using process additive steam in a gasification process thereof.

Figure 47 is a cross-sectional view through one embodiment of the gasifier, detailing the feedstock input, gas outlet, ash outlet, lateral transfer system, additive ports and

access ports.

Figure 48 is a central longitudinal cross-sectional view through the embodiment of the gasifier illustrated in Figure 47, detailing the thermocouples and process additive ports.

- 5 Figure 49 is a perspective view of the embodiment of the gasifier illustrated in Figures 47 and 48.

Figure 50 illustrates a view of the outside of the embodiment of the gasifier illustrated in Figures 47 to 49 detailing the external elements of the lateral transfer system.

- Figure 51 illustrates a portion of a lateral transfer unit of the gasifier illustrated in
10 Figures 47 to 49.

Figure 52 illustrates a bottom view of the lateral transfer unit illustrated in Figure 51.

Figure 53 illustrates an alternative embodiment of the lateral transfer unit illustrated in Figure 51.

- Figure 54 is a schematic of one embodiment gas reformulating system of the
15 invention coupled to two gasifiers.

- Figure 55 A and B illustrates an arrangement of baffles in one embodiment of the gas reformulating chamber of the invention. Figure 6A is a diagram illustrating air-flow within the gas reformulating chamber comprising bridge wall baffles. Figure 6B is a diagram illustrating air-flow within the gas reformulating chamber comprising
20 turbulator or choke ring baffles.

Figure 56 is a schematic of a transport reactor comprising one embodiment of the gas reformulating system.

Figure 57 is a schematic of two entrained flow gasifiers comprising one embodiment of the gas reformulating system.

- 25 Figure 58 is a schematic of two fixed bed gasifier comprising one embodiment of the gas reformulating system.

Figure 59 is a schematic of a cyclonic gasifier comprising one embodiment of the gas reformulating system.

- Figure 60 is a block flow diagram of the recovery of heat from the syngas product of the gasification process using a heat exchanger and a heat recovery steam generator,
5 according to one embodiment of the present invention.

Figure 61 is a block flow diagram of a system for cooling hot raw syngas products, including a heat exchanger for recovery of heat from the raw syngas product of the gasification process, and a quench step for further syngas cooling, according to one embodiment of the present invention.

- 10 Figure 62A is a schematic diagram showing the functional requirements for a converter gas-to-air heat exchanger, according to one embodiment of the present invention.

Figure 62B is a schematic diagram depicting a gas-to-air heat exchanger, according to one embodiment of the present invention.

- 15 Figure 63 is a schematic diagram showing a piping system to transfer the exchange-air to the converter, according to one embodiment of the present invention.

Figure 64 is a schematic diagram depicting the relationship between a gas-to-air heat exchanger and a heat recovery steam generator, according to one embodiment of the present invention.

- 20 Figure 65 is a schematic diagram showing a high level view of a syngas flow/pressure is control subsystem, according to one embodiment of the present invention.

Figure 66 is a schematic diagram depicting a high level concept of various temperature controls within the system, according to one embodiment of the present invention.

- 25 Figure 67A to 67 K are block flow diagrams depicting overviews of various embodiments of the present invention.

Figures 68 to 75 depict various combinations of processes comprising different embodiments of the GCS.

Figure 76 is a block flow diagram showing the inputs, optional inputs and outputs of a residue conditioning system of the present invention;

- 5 Figure 77 is a schematic representation of a typical residue conditioning chamber in accordance with the present invention;

Figure 78A is a schematic depiction of a residue conditioning chamber in indirect communication with two residue sources, in accordance with one embodiment of the present invention;

- 10 Figure 78B is a schematic depiction of a residue conditioning chamber in indirect communication with one residue source, in accordance with one embodiment of the present invention;

Figure 79 illustrates a cross-sectional view of one embodiment of a residue conditioning chamber integrated with a residue conditioning chamber;

- 15 Figure 80 is a partial cross-sectional view of an S-spout type slag outlet, in accordance with one embodiment of the present invention;

Figure 81 is a partial cross-sectional view of a tiltable slag crucible in a residue conditioning chamber in accordance with one embodiment of the present invention;

- 20 Figure 82 is a partial cross-sectional view of one embodiment of a slag outlet, in accordance with the present invention;

Figure 83 is a partial cross-sectional view of one embodiment of a slag outlet, in accordance with the present invention;

Figure 84 is a partial cross-sectional view of one embodiment of a slag outlet, in accordance with the present invention;

- 25 Figure 85 is a partial cross-sectional view of one embodiment of a slag outlet, in accordance with the present invention;

Figure 86 is an illustration of a gas homogenization system, in accordance with one embodiment of the invention, where gas is delivered from a single source to a single homogenization chamber and then delivered to a single engine by way of a gas conditioning skid.

- 5 Figure 87 is an illustration of a gas homogenization system, in accordance with one embodiment of the invention, where gas is delivered from a single source to a single homogenization chamber and then delivered to a single engine by way of a heater, filter and a pressure regulator valve.

- 10 Figure 88 is an illustration of a gas homogenization system, in accordance with one embodiment of the invention, where gas is delivered from a single source to a single homogenization chamber and then delivered to multiple engines by way of a heater and a plurality of filters and pressure regulator valves.

- 15 Figure 89 is an illustration of a gas homogenization system, in accordance with one embodiment of the invention, where gas is delivered from multiple sources to a single homogenization chamber and then delivered to multiple engines, each engine having its own gas conditioning skid.

- 20 Figure 90 is an illustration of a gas homogenization system, in accordance with one embodiment of the invention, where gas is delivered to multiple engines from two parallel streams, each stream comprising a single source of gas delivered to a single homogenization chamber.

Figure 91 is an illustration of a constant-volume homogenization chamber, in accordance with one embodiment of the invention.

- 25 Figure 92 is an illustration of a homogenization chamber configured as pressure vessel and compressor combination, in accordance with one embodiment of the invention.

Figure 93 is an illustration of a homogenization chamber configured as a double membrane gas holder, in accordance with one embodiment of the invention.

Figure 94 is an illustration of a homogenization chamber configured as an absorption-type gas holder, in accordance with one embodiment of the invention.

Figure 95 is an illustration of a plurality of constant-volume homogenization chambers arranged in parallel, in accordance with one embodiment of the invention.

- 5 Figure 96 is a flow diagram depicting the use of a control system to control a gasification process for converting a carbonaceous feedstock into gas, in accordance with one embodiment of the present invention.

Figure 97 is a schematic diagram of a computing platform, and exemplary components thereof, of a control system to control a gasification process for
10 converting a carbonaceous feedstock into a gas, in accordance with one embodiment of the present invention.

Figure 98 is a schematic diagram of a centralized control system, in accordance with one embodiment of the present invention.

- Figure 99 is a schematic diagram of an at least partially distributed control system, in
15 accordance with one embodiment of the present invention.

Figure 100 is a schematic diagram depicting exemplary sensing and response signals respectively received from and transmitted to a gasification system by a control system to control one or more processes implemented therein, in accordance with one embodiment of the present invention.

- 20 Figure 101 is a schematic diagram depicting exemplary sensing and response access points of the integrated system control system to various devices, modules and subsystems of a system for the conversion of carbonaceous feedstocks to a gas of a specified composition, along with various possible downstream applications, in accordance with various exemplary embodiments of the present invention.

- 25 Figure 102 is a schematic diagram depicting a control system for controlling inputs to a converter of a system for the conversion of carbonaceous feedstock into a gas, in accordance with one embodiment of the present invention.

Figure 103 is a flow diagram of a control scheme for controlling the gasification system.

Figure 104 is a flow diagram of an alternative control scheme for controlling the gasification system, wherein this system is further adapted for using process additive
5 steam in a gasification process thereof.

Figure 105 is a flow diagram of an alternative control scheme for controlling a gasification process, in accordance with a further exemplary embodiment of the present invention.

Figure 106 is a flow diagram of an alternative control scheme for controlling a
10 gasification process, in accordance with a further exemplary embodiment of the present invention.

Figures 107 to 110 depict various combinations of how the processes of the facility can be constructed, wherein "1" depicts zone 1 (a gasifier), "2" depicts zone 2 (a residue conditioner) and "3" depicts zone 3 (a gas reformulating system).

15 DETAILED DESCRIPTION OF THE INVENTION

Definitions

As used herein, the term "about" refers to a +/-10% variation from the nominal value. It is to be understood that such a variation is always included in any given value provided herein, whether or not it is specifically referred to.

20 The terms "carbonaceous feedstock" and "feedstock," as used interchangeably herein, are defined to refer to carbonaceous material that can be used in the gasification process. Examples of suitable feedstock include, but are not limited to, waste materials, including municipal wastes; wastes produced by industrial activity; biomedical wastes; carbonaceous material inappropriate for recycling, including non-
25 recyclable plastics; sewage sludge; coal; heavy oils; petroleum coke; heavy refinery residuals; refinery wastes; hydrocarbon contaminated solids; biomass; agricultural

wastes; municipal solid waste; hazardous waste and industrial waste. Examples of biomass useful for gasification include, but are not limited to, waste wood; fresh wood; remains from fruit, vegetable and grain processing; paper mill residues; straw; grass, and manure.

- 5 The term "waste materials" is defined to refer to carbonaceous hazardous and non-hazardous wastes. These can include municipal wastes, wastes produced by industrial activity and biomedical wastes. Waste materials also include carbonaceous material inappropriate for recycling, including non-recyclable plastics, and sewage sludge.

10 The term "controllable solids movement means" is defined to refer to one or more devices for removing solids from the gasifier in a controllable manner. Examples of such devices include, but are not limited to, rotating arms, rotating wheels, rotating paddles, moving shelves, pusher rams, screws, conveyors, and combinations thereof.

15 The term "sensing element" is defined to describe any element of the system configured to sense a characteristic of a process, a process device, a process input or process output, wherein such characteristic may be represented by a characteristic value useable in monitoring, regulating and/or controlling one or more local, regional and/or global processes of the system. Sensing elements considered within the context of a gasification system may include, but are not limited to, sensors, detectors, monitors, analyzers or any combination thereof for the sensing of process, fluid and/or material temperature, pressure, flow, composition and/or other such characteristics, as well as material position and/or disposition at any given point within the system and any operating characteristic of any process device used within the system. It will be appreciated by the person of ordinary skill in the art that the above examples of sensing elements, though each relevant within the context of a gasification system, 20 may not be specifically relevant within the context of the present disclosure, and as such, elements identified herein as sensing elements should not be limited and/or inappropriately construed in light of these examples.

30 The term "response element" is defined to describe any element of the system configured to respond to a sensed characteristic in order to operate a process device operatively associated therewith in accordance with one or more pre-determined,

computed, fixed and/or adjustable control parameters, wherein the one or more control parameters are defined to provide a desired process result. Response elements considered within the context of a gasification system may include, but are not limited to static, pre-set and/or dynamically variable drivers, power sources, and any other element configurable to impart an action, which may be mechanical, electrical, magnetic, pneumatic, hydraulic or a combination thereof, to a device based on one or more control parameters. Process devices considered within the context of a gasification system, and to which one or more response elements may be operatively coupled, may include, but are not limited to, material and/or feedstock input means, heat sources such as plasma heat sources, additive input means, various gas blowers and/or other such gas circulation devices, various gas flow and/or pressure regulators, and other process devices operable to affect any local, regional and/or global process within a gasification system. It will be appreciated by the person of ordinary skill in the art that the above examples of response elements, though each relevant within the context of a gasification system, may not be specifically relevant within the context of the present disclosure, and as such, elements identified herein as response elements should not be limited and/or inappropriately construed in light of these examples.

The term "real-time" is defined to define any action that is substantially reflective of the present or current status of the system or process, or a characteristic thereof, to which the action relates. A real-time action may include, but is not limited to, a process, an iteration, a measurement, a computation, a response, a reaction, an acquisition of data, an operation of a device in response to acquired data, and other such actions implemented within the system or a given process implemented therein. It will be appreciated that a real-time action related to a relatively slow varying process or characteristic may be implemented within a time frame or period (e.g. second, minute, hour, etc.) that is much longer than another equally real-time action related to a relatively fast varying process or characteristic (e.g. 1ms, 10ms, 100ms, 1s).

The term "continuous" is defined to define any action implemented on a regular basis or at a given rate or frequency. A continuous action may include, but is not limited to, a process, an iteration, a measurement, a computation, a response, a reaction, an

acquisition of data via a sensing element, an operation of a device in response to acquired data, and other such actions implemented within the system or in conjunction with a given process implemented therein. It will be appreciated that a continuous action related to a relatively slow varying process or characteristic may be
5 implemented at a rate or frequency (e.g. once/second, once/minute, once/hour, etc.) that is much slower than another equally continuous action related to a relatively fast varying process or characteristic (e.g. 1KHz, 100Hz, 10Hz, 1Hz).

As used herein, the term "converter" refers to the system used to convert carbonaceous feedstock into a gas product prior to cooling and conditioning. The
10 conversion process can occur in one chamber, one chamber with multiple zones, or multiple chambers. In one embodiment, the converter comprises a gasifier and a gas reformulation system.

As used herein, the term "product gas" means generally, the gas generated by the gasification facility, prior to cooling and cleaning by processes designated to remove
15 contaminants. Depending on the design of the gasification facility it can be used to refer to, for example, raw offgas, raw syngas, reformulated offgas or reformulated syngas.

As used herein, the term "gas reformulating" means further processing raw syngas or raw off-gas to generate gas of a different chemical composition. Air, enriched air,
20 steam, etc, can be used in combination with plasma heat to change the levels of CO/CO₂ and H₂/H₂O (desired heating value).

As used herein, the term "reformulated syngas" means off-gas that has been passed through a reformulating step whereby additives such as heat, air and/or steam have been used to transform the gas from one chemical composition to gas of another
25 chemical composition (optimized heating value). For example, this gas has passed through a Gas Reformulating System (GRS).

As used herein, the term "reformulated off-gas" means off-gas that has been passed through a reformulating step whereby additives such as heat, air and/or steam have been used to transform the gas from one chemical composition to gas of another

chemical composition (desired heating value). For example, this gas has passed through a Gas Reformulating System (GRS).

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs.

This invention provides a gasification facility for the conversion of carbonaceous feedstock into gas with further optional downstream applications such as the generation of energy. The facility comprises a number of systems that work together to function as an integrated system for the conversion feedstock into electricity. One skilled in the art can appreciate, however, that each subsystem on its own can be considered as a system that could function with other systems and/or be incorporated into other facilities. The subsystems comprising the facility of this invention are: a Municipal Solid Waste Handling System; a Plastics Handling System; a Horizontally Oriented Gasifier with Lateral Transfer Units System; a Gas Reformulating System; a Heat Recycling System; a Gas Conditioning System; a Residue Conditioning System; a Gas Homogenization System and a Control System.

The configuration of the various components that are comprised by the gasification facility in one embodiment of the present invention is depicted schematically in Figure 3.

In accordance with one embodiment of the present invention, the gasification system comprises an integrated control system for controlling the gasification process implemented therein, which may include various independent and interactive local, regional and global processes.

A high-level process control schematic that depicts various sensing and response elements comprised by or associated with the components of the gasification facility in one embodiment of the invention is depicted in Figure 43.

The control system may be configured to enhance, and possibly optimise the various

processes for a desired front end and/or back end result.

For instance, a front-to-back control scheme could include facilitating the constant throughput of feedstock, for example in a system configured for the gasification of MSW, while meeting regulatory standards for this type of system. Such front-to-back
5 control scheme could be optimised to achieve a given result for which the system is specifically designed and/or implemented, or designed as part of a subset or simplified version of a greater control system, for instance upon start-up or shut-down of the process or to mitigate various unusual or emergency situations.

A back-to-front control scheme could include the optimisation of a product gas
10 quality or characteristic for a selected downstream application, namely the generation of electricity via downstream gas engine(s) in this example. While the control system could be configured to optimise such back-end result, monitoring and regulation of front-end characteristics could be provided in order to ensure proper and continuous function of the system in accordance with regulatory standards, when such standards
15 apply.

It will be apparent to the person of skill in the art that the above examples are not meant to be limiting and that other examples of front-end and back-end results may be considered herein without departing from the general scope and nature of the present disclosure. Furthermore, the person of skill in the art will appreciate that the control
20 system may be configured to provide complimentary results which may be best defined as a combination of front-end and back-end results, or again as a result flowing from any point within the system.

Municipal Solid Waste (MSW) Handling System

The initial MSW handling system is designed to take into account: (a) storage
25 capability for supply of four days; (b) avoidance of long holding periods and excess decomposition of MSW; (c) prevention of debris being blown around; (d) control of odour; (e) access and turning space for garbage trucks to unload; (f) minimization of driving distance and amount of turning required by the loader transporting MSW from the MSW stockpile to the MSW shredding system (g) avoidance of operational

interference between loader and garbage trucks; (h) possibility of additional gasification streams to allow for plant expansion; (i) minimum intrusion by trucks into the facility, especially into hazardous areas; (j) safe operation with minimum personnel; (k) indication for the loader operator of the fill levels in the conveyor input hoppers; (l) shredding the as-received waste to a particle size suitable for processing; and (m) remote controllability of MSW flow rate into the processor and independent control of the plastics feed rate.

The MSW handling system comprises a MSW storage building, a loader, a MSW shredding system, a magnetic separator and a feed conveyor. A separate system is also designed for storing, shredding, stockpiling and feeding plastics, the feed-rate of which is used as an additive in the gasification process. All processing of both MSW and the plastics are done inside buildings to contain debris and odor. A first-in-first-out (FIFO) scheduling approach is used to minimize excessive decomposition of the MSW. A mechanized, bucket-based loader is used to transfer material from the stockpile to the shredding system.

The MSW shredding system consists of an input conveyor, a shredder and a pick conveyor. The input conveyor transports the MSW from inside the building into a shredder. The conveyor is controlled remotely by the process controller to match process demands. The shredder ensures that the as-received MSW is suitable for processing. The shredder is equipped to detect any possible jams and take appropriate action. The shredded waste is dropped onto a belt conveyor, transported under a magnetic pick-up system that avoids inadvertent feeding of excessive amounts of ferrous metals through the gasifier. After this step, the MSW is dropped onto a screw conveyor which feeds the MSW into the gasifier. The feed rate of the screw conveyor is controlled by the process controller to meet process demands. The MSW feed conveyor has an additional entry to accept shredded plastic.

Plastics Handling System

The system for handling plastics provides storage for the plastic, shred it, place it into a stockpile and feed it under independent control into the processor. The system comprises a storage facility, a shredder with input hopper, a take-away conveyor and

a stockpile, all located in a common building to control debris. A feed conveyor moves the shredded plastic into the gasifier. The conveyor trough is sealed to the trough of the MSW conveyor such that the plastic is introduced into the gasifier via the MSW conveyor to reduce openings into the gasifier. The conveyor is a screw conveyor with the hopper sealed to it to provide gas sealing when it contains material.

A Horizontally Oriented Gasifier With Lateral Transfer Units System

This system comprises a horizontally-oriented gasification chamber having one or more feedstock inputs, one or more gas outputs and a solid residue output; a chamber heating system; one or more lateral transfer units for moving material through said gasifier during processing; and a control system for controlling movement of said one or more lateral transfer units.

This system enables extraction of volatiles throughout the various stages of gasification of carbonaceous feedstock to be optimized. Feedstock is introduced at one end of the gasifier and is moved through the gasifier during processing by one or more lateral transfer units. The temperature at the top of the material pile generally increases as gasification proceeds through drying, volatilization, char-to-ash conversion with the simultaneous production of CO and CO₂. A control system obtains information from measurable parameters such as temperature and pile height or profile and manages the movement of each lateral transfer unit independently.

To facilitate movement of reactant material, the individual lateral transfer units can be controlled independently or a group of two or more lateral transfer units can be controlled in a coordinated manner. The preferred number of lateral transfer units in a particular gasifier is dependent on the path length reactant material must travel and the distance reactant material can be moved by each lateral transfer unit and is a compromise between minimizing the magnitude of process disturbances caused by each discrete transfer and mechanical complexity, cost, and reliability.

Thus, each area in the horizontally-oriented gasifier can experience temperature ranges and optional process additives (such as air, oxygen and/or steam) that promote a certain stage of the gasification process. In a pile of reactant material, all stages of

gasification are occurring concurrently, however individual stages are favored at a certain temperature range.

By physically moving the material through the gasifier, the gasification process can be facilitated by allowing as much drying as energetically efficient to occur prior to
5 raising the temperature of the material to promote volatilization. The process then seeks to allow as much volatilization as energetically efficient to occur prior to raising the temperature of the material to promote char-to-ash conversion.

In one embodiment, the ash is translocated into an ash collection chamber. Appropriate ash collection chambers are known in the art and accordingly, a worker
10 skilled in the art having regard to the requirements of the system would readily know the size, shape and manufacture of an appropriate ash collection chamber. In one embodiment, the ash will be translocated into a water tank for cooling, from which the gasifier residue is transmitted through a conduit, optionally, under control of a valve, to a point of discharge. In one embodiment, the ash is translocated into a separate
15 slag conversion chamber for the conversion of ash-to-slag.

During processing, feedstock is introduced into the chamber at one end; hereafter referred to as the feed end, through the feedstock input and is transported from the feed end through the various regions in the gasification chamber towards the ash (solid residue) output or ash end. As the feed material progresses through the
20 chamber, it loses its mass and volume as its volatile fraction is volatilized to form off-gas and the resulting char is reacted to form additional off-gas and ash.

Due to this progressive conversion, the height of the material (pile height) decreases from the feed end to the ash end of the chamber and levels off when only solid residue (ash) remains.

25 In one embodiment, the off-gas escapes through the gas output into, for example, a gas refinement chamber where it can undergo further processing or into a storage chamber or tank. The solid residue (ash) is transported through the ash output to, for example, an ash collection chamber or a solid residue conditioning chamber for further processing.

In one embodiment, as shown in Figure 47, the gasifier has a stepped floor having a plurality of floor levels or steps. Optionally, each floor level is sloped between about 5 and about 10 degrees.

In one embodiment of the step-floor gasifier, the individual steps (floor levels) correlate, at least in part, with the individual regions discussed above, with each region or step having conditions optimized for different degrees of drying, volatilization and carbon conversion. For convenience, the uppermost step will be referred to as step A; the next step will be referred to as step B, *etc.* Corresponding lateral transfer units will be identified with the same letter, *i.e.* lateral transfer unit A or ram A services step A, lateral transfer unit B or ram B services step B.

In the three step embodiment, there is an upper step or step A, middle step or step B and a lower step or step C. The feed material is fed onto the first step (step A). The normal temperature range for this step (as measured at the bottom of the material pile) lies between 300 and 900°C. Step B is designed to have a bottom temperature range between 400 and 950°C to promote volatilization with the remainder of the drying operation as well as a substantial amount of carbon conversion. Step C temperature range lies between 500 and 1000°C. The major process in Step C is that of carbon conversion with a lesser amount (the remainder) of volatilization. In one embodiment, movement over the steps is facilitated by the lateral transfer system with each step optionally being serviced by an independently controlled lateral transfer unit.

During processing, air as a source of oxygen is introduced into the chamber. Optionally, the method of injecting process air can be selected to facilitate an even flow of air into the gasification chamber, prevent hot spot formation and/or improve temperature control. The air can be introduced through the sides of the chamber, for example as shown in Figures 47 and 48, optionally from near the bottom of the chamber, or can be introduced through the floor of the chamber, or through both.

Also to be considered in the design of the gasifier is the position, orientation and number of the process additive inputs. The process additives can optionally be injected into the gasifier at locations where they will ensure most efficient reaction to

achieve the desired conversion result. In one embodiment, the floor of the gasification chamber is perforated to varying degrees to allow for introduction of process additives, such as air at the base of the material pile.

5 In one embodiment, the side-walls of the chamber slope inwards towards the bottom to achieve a small enough width for good air penetration from the sides while still having the required volume of material. The slope angle can optionally be made steep enough to assure that the material will drop towards the bottom of the chamber during processing.

10 The gasification chamber is a partially or fully refractory-lined chamber with an internal volume sized to accommodate the appropriate amount of material for the required solids residence time. The refractory protects the gasification chamber from the high temperature and corrosive gases and minimizes unnecessary loss of heat from the process. The refractory material can be a conventional refractory material well-known to those skilled in the art and which is suitable for use for a high temperature
15 *e.g.* up to about 1100°C, un-pressurized reaction. When choosing a refractory system factors to be considered include internal temperature, abrasion; erosion and corrosion; desired heat conservation/limitation of temperature of the external vessel; desired life of the refractory. Examples of appropriate refractory material include high temperature fired ceramics, *i.e.*, aluminum oxide, aluminum nitride, aluminum silicate
20 boron nitride, zirconium phosphate, glass ceramics and high alumina brick containing principally, silica, alumina, chromia and titania. To further protect the gasification chamber from corrosive gases the chamber is, optionally, partially or fully lined with a protective membrane. Such membranes are known in the art and, as such, a worker skilled in the art would readily be able to identify appropriate membranes based on
25 the requirements of the system and, for example, include Sauereisen High Temperature Membrane No 49.

In one embodiment, the refractory is a multilayer design with a high density layer on the inside to resist the high temperature, abrasion, erosion and corrosion. Outside the high density material is a lower density material with lower resistance properties but
30 higher insulation factor. Optionally, outside this layer is a very low density foam

board material with very high insulation factor and can be used because it will not be exposed to abrasion or erosion. Appropriate materials for use in a multilayer refractory are well known in the art. In one embodiment, the multilayer refractory comprises an internally oriented chromia layer; a middle alumina layer and an outer
5 insboard layer. The wall of the chamber can optionally incorporate supports for the refractory lining or refractory anchors. Appropriate refractory supports and anchors are known in the art.

Lateral transfer system

Material is moved through the gasification chamber in order to promote specific
10 stages of the gasification process (drying, volatilization, char-to-ash conversion). To facilitate control of the gasification process material movement through the gasification chamber can be varied (variable movement) depending on process requirements. This lateral movement of material through the gasifier is achieved via the use of a lateral transfer system comprising one or more lateral transfer units.
15 Movement of reactant material by the lateral transfer system can be optimized by varying the movement speed, the distance each lateral transfer unit moves and the sequence in which the plurality of lateral transfer units are moved in relation to each other. The one or more lateral transfer units can act in coordinated manner or individual lateral transfer units can act independently. In order to facilitate control of
20 the material flow rate and pile height the individual lateral transfer units can be moved individually, at varying speeds, at varying movement distances, at varying frequency of movement.

The individual lateral transfer units comprise a moving element and a guiding element or alignment element. It would be apparent to a worker skilled in the art that the
25 moving element can be equipped with appropriate guide engagement elements. The moving element can include, but is not limited to, a shelf / platform, ram, plow, screw element, carrier ram, conveyor or a belt.

The carrier ram can include a single ram or multiple-finger ram. In one embodiment, the gasifier design will allow for the use of a single ram or multiple-finger ram. The
30 use of a multiple-finger ram may be preferably when minimum interference with gas

flows is desirable during operation of the rams. In the multiple-finger ram design, the multiple-finger ram may be a unitary structure or a structure in which the ram fingers are attached to a ram body, with individual ram fingers optionally being of different widths depending on location. The gap between the fingers in the multiple-finger ram design is selected to avoid particles of reactant material from bridging.

In certain embodiments in which the system operates at very high temperatures, cooling can optionally be provided for the moving elements. In one embodiment using a ram or shelf, cooling within the ram or shelf can be provided. Such cooling could be by fluid (air or water) circulated inside the ram or shelf from outside of the chamber.

In one embodiment, for example as shown in Figures 47, 51 and 52, the lateral transfer system can be a movable shelf / platform by which material is predominantly moved through the gasifier by sitting on top of the shelf / platform. A fraction of material may also be pushed by the leading edge of the movable shelf / platform.

Power to propel the lateral transfer system is provided by a motor and drive system and is controlled by actuators. The individual lateral transfer units may optionally be powered by dedicated motor and have individual actuators or one or more lateral transfer units may be powered by a single motor and shared actuators.

The gasification process requires heat. Heat addition can occur directly by partial oxidation of the feedstock or indirectly by the use of one or more heat sources known in the art. In one embodiment, the heat source can be circulating hot air. The hot air can be supplied from, for example, air boxes, air heaters or heat exchangers, all of which are known in the art. In one embodiment, hot air is provided to each level by independent air feed and distribution systems. Appropriate air feed and distribution systems are known in the art and include separate air boxes for each level from which hot air can pass through perforations in the floor of each level to that level or via independently controlled spargers for each floor level.

In one embodiment, each floor level has one or more grooves running the length of individual steps. The grooves being sized to accommodate hot air and/or steam pipes.

The pipes optionally being perforated on their lower third to half to facilitate the uniform distribution of hot air or steam over the length of the step. Alternatively, the sparger pipes can be perforated towards the top of the pipes.

5 In order to facilitate initial start up of the gasifier, the gasifier can include access ports sized to accommodate various conventional burners, for example natural gas, oil/gas or propane burners, to pre-heat the chamber. Also, wood/biomass sources, engine exhausts, electric heaters could be used to preheat the chamber.

Process additives may optionally be added to the gasifier to facilitate efficient conversion of feedstock into specified gases. Steam input can be used to ensure
10 sufficient free oxygen and hydrogen to maximize the conversion of decomposed elements of the input feedstock into product gas and/or non-hazardous compounds. Air input can be used to assist in processing chemistry balancing to maximize carbon conversion to a fuel gas (minimize free carbon) and to maintain the optimum processing temperatures while minimizing the cost of input heat. Optionally, other
15 additives may be used to optimize the process and thereby improve emissions.

The invention, therefore, can include one or more process additive inputs. These include inputs for steam injection and/or air injection. The steam inputs can be strategically located to direct steam into high temperature regions and into the product gas mass just prior to its exit from the gasifier. The air inputs can be strategically
20 located in and around the gasifier chamber to ensure full coverage of process additives into the processing zone. In one embodiment, the process additive inputs are located proximal to the floor of the gasifier.

In one embodiment, the process additive inputs located proximal to the floor are half-pipe air spargers trenched into the refractory floor. Such air spargers may be designed
25 to facilitate replacement, servicing or modification while minimizing interference with the lateral transfer of reactant material. The number, diameter and placement of the air holes in the air spargers can be varied according to system requirements or lateral transfer system design.

In one embodiment, the gasification chamber can further comprise one or more ports.

These ports can include service ports allow for entry into the chamber for maintenance and repair. Such ports are known in the art and can include sealable port holes of various sizes. In one embodiment, access to the inside of the gasifier is provided by a manhole at one end which can be closed by a sealable refractory lined cover during operation. In one embodiment, further access is available by removing one or more air boxes. The gasifier can optionally include a flanged lower section which is connected to a flanged main section of the gasification chamber to facilitate opening of the gasification chamber for refractory inspection and repair.

The residual solids (ash) after gasification is complete can optionally be removed from the gasifier and passed to a handling system. The gasifier may therefore optionally include a controllable solids removal system to facilitate solid residue or ash removal. In one embodiment, the controllable solids removal system comprises a ram mechanism to push the ash out of the chamber. In one embodiment, the controllable solids removal system consists of a system of conveying rams. Optionally, the length of the ram stroke can be controlled so that the amount of material fed into a solid residue processing chamber with each stroke can be controlled. In a further embodiment of the invention, the controllable solids removal system may comprise of a controllable rotating arm mechanism.

As the material is processed and is moved from region to region in the gasifier the heat generated within the pile can cause melting which will result in agglomeration of the ash. Agglomerated ash has been shown to cause jamming in drop port type exits. The gasifier therefore can optionally comprise a means for breaking up ash agglomerates. In one embodiment, in order to ensure that any agglomerations do not create jamming at the exit from the chamber, a screw conveyor concept is used to extract the ash from the gasifier. The ram motion will push the ash into the extractor and the extractor will pull the ash out of the gasifier and feed it into an ash conveyor system. Rotation of the extractor screw breaks up agglomerations before the ash is fed into the conveyor system. This breaking up action can be enhanced by having serrations on the edge of the extractor screw flights.

A Gas Reformulating System

The invention further comprises a gas reformulating system for the reformulating of gas from the gasifier into reformulated gas of a desired chemical composition. In particular, the reformulating system uses torch heat from a plasma torch to dissociate the gaseous molecules and allow their recombination into smaller molecules useful
5 for downstream application, such as energy generation. The system also comprises gas mixing means, process additive units, and a feedback control system with one or more sensors, one or more process effectors and computing means to monitor and/or regulate the reformulating reaction.

The gas reformulating system (GRS) comprises a gas reformulating chamber having
10 one or more input gas inlets, one or more reformulated gas outlets, one or more plasma torches, an oxygen source and control system.

The GRS is capable of converting raw input gas comprising volatile molecules that can include, for example, carbon monoxide, hydrogen, light hydrocarbons, and carbon dioxide and contaminating particulate matter such as soot and carbon black produced
15 during the gasification of carbonaceous feedstock. This GRS provides a sealed environment for containing and controlling the process. It uses plasma torch heat to disassociate the volatile molecules into their constituent elements that then recombine as a reformulated gas of a desired chemical composition. Process additives such as air and/or oxygen and optionally steam are used to provide the necessary molecular
20 species for recombination. The plasma torch heat also removes unwanted substances such as paraffins, tars, chlorinated compounds among others, by decomposing and converting these unwanted substances to smaller molecules such as H₂ and CO. The GRS further comprises a control system that regulates the process and thereby enables the process to be optimized.

25 Downstream of the GRS an induction blower in gaseous communication with the gas reformulating chamber may be provided to maintain the pressure of the gas reformulating chamber at a pressure of about 0 to -5 mbar.

The GRS is in gaseous communication with the gasifier and, therefore, receives input gas directly from the gasifier. The GRS may further comprise a mounting flange or
30 connector for coupling the gas reformulating chamber to the gasifier. To facilitate

maintenance or repair, the GRS may optionally be reversibly coupled to the gasifier such that the GRS, if necessary, may be removed.

The gas reformulating chamber has one or more input gas inlets, one or more reformulated gas outlets, one or more ports for heating devices and one or more inputs
5 for oxygen sources. Input gas enters the plasma-torch heated gas reformulating chamber through one or more input gas inlets or ports in the chamber and is optionally blended by gas mixing elements. Ports or inputs are provided through which the oxygen source is injected into the gas reformulating chamber. The one or more reformulated gas outlets or ports enable the reformed reformulated gas to exit
10 the GRS and to be transferred to downstream processes for further refinement or to storage facilities.

The gas reformulating chamber is a chamber with a sufficient internal volume to accommodate the residence time required for the reformulating reaction to take place. The gas residence time is the amount of the time that the gas is required to remain in
15 the gas reformulating chamber to allow the reformulating of input gas to reformulated gas to occur.

Accordingly, in designing the gas reformulating chamber, the required gas residence time can be considered. Gas residence time is a function of the gas reformulating chamber volume and geometry, gas flow rate, the distance the gas travels and/or the
20 path of the gas through the chamber (i.e., a straight linear passage or a swirling or cyclonic path). The gas reformulating chamber must, therefore, be shaped and sized in such a manner that the flow dynamics of the gas through the chamber allows for an adequate gas residence time. The gas residence time can be modified by the use of air jets that promote a swirling flow of the gas through the gas reformulating chamber,
25 such that the passage of the gas is non-linear and therefore has a longer residence time.

In one embodiment, the gas residence time is about 0.5 to about 2.0 seconds. In one embodiment, the gas residence time is about 0.75 to about 1.5 seconds. In a further embodiment, the gas residence time is about 1 to about 1.25 seconds. In a still further
30 embodiment, the gas residence time is about 1.2 seconds.

The gas reformulating chamber may be any shape so long as it allows for the appropriate residence time to enable sufficient chemical reformulating of the input gas into reformulated gas. The gas reformulating chamber may be disposed in a variety of positions so long as appropriate mixing of the input gas and residence time is maintained. The gas reformulating chamber can be oriented substantially vertically, substantially horizontally or angularly and have a wide range of length-to-diameter ratios ranging from about 2:1 to about 6:1. In one embodiment, the length-to-diameter ratio of the gas reformulating chamber is 3:1.

In one embodiment, the gas reformulating chamber is a straight, substantially, vertical refractory-lined blind or capped tubular or cylindrical structure having the open bottom (upstream) end in direct gaseous communication with the gasifier and one reformulated gas outlet proximal to or at the top (downstream) end of the chamber. Optionally, the tubular or cylindrical chamber is formed by capping the top (downstream) end of a refractory-lined tube or cylinder with a refractory-lined lid. In order to facilitate maintenance or repair, the lid may, optionally, be removeably sealed to the tube or cylinder.

The wall of the gas reformulating chamber can be lined with refractory material and/or a water jacket can encapsulate the gas reformulating chamber for cooling and/or generation of steam or recovery of usable torch heat. The gas reformulating chamber may have multiple walls, along with a cooling mechanism for heat recovery, and the system may also include heat exchangers for high pressure/high temperature steam production, or other heat recovery capability. Optionally, the gas reformulating chamber can include one or more chambers, can be vertically or horizontally oriented, and can have internal components, such as baffles, to promote back mixing and turbulence of the gas.

The gas reformulating chamber may optionally include a collector for solid particulate matter formed during the reformulating process that can be collected and optionally fed into the gasifier for further processing or the solid residue compartments of a gasification system, such as a solid residue conditioning chamber, for further processing.

The gas reformulating chamber comprises one or more input gas inlets or ports to feed input gas into the chamber for processing and one or more reformulated gas outlets or ports to transfer the reformulated gas produced in the reformulating reactions to downstream processing or storage. The inlet(s) for input gas is located at or near the first or upstream end. The inlet may comprise an opening or, alternatively, may comprise a controller to control the flow of input gas into the gas reformulating chamber and/or an injector to inject the input gas into the gas reformulating chamber.

In one embodiment, the one or more input gas inlets for delivering the input gas to the gas reformulating chamber can be incorporated in a manner to promote concurrent, countercurrent, radial, tangential, or other feed flow directions. In one embodiment, there is provided a single input gas inlet with an increasing conical shape. In one embodiment, the inlet comprises the open first end of the gas reformulating chamber, whereby it is in direct communication with the gasifier.

The attachment site on the gasifier for the GRS may be strategically located to optimize gas flow and/or maximize mixing of the input gas prior to entering the gas reformulating chamber. In one embodiment, the gas reformulating chamber is located at the center of the gasifier, thereby optimizing mixing of the input gas prior to entering the gas reformulating chamber. In one embodiment, the inlet comprises an opening located in the closed first (upstream) end of the gas reformulating chamber. This embodiment uses an input gas inlet port to deliver the volatiles generated during gasification of carbonaceous feedstock into the chamber. In one embodiment, the inlet comprises one or more openings in the wall of the gas reformulating chamber proximal to the first (upstream) end.

In embodiments in which the gas reformulating chamber is connected to one or more gasifiers, one or more inlets in the gas reformulating chamber may be in direct communication with the one or more gasifier through a common opening or may be connected to the gasifier via piping or via appropriate conduits. One embodiment having this configuration is shown in Figure 54.

The reformulated gas produced in the reformulating reaction exits the gas reformulating chamber through one or more reformulated gas outlets or ports. One or

more outlets or ports for the reformulated gas produced in the gas reformulating chamber are located at or near the second or downstream end. The outlet may comprise an opening or, alternatively, may comprise a means to control the flow of the reformulated gas out of the gas reformulating chamber. In one embodiment, the
5 outlet comprises the open second (downstream) end of the gas reformulating chamber. In one embodiment, the outlet comprises one or more openings located in the closed second (downstream) end of the gas reformulating chamber. In one embodiment, the outlet comprises an opening in the wall of the gas reformulating chamber near the second (downstream) end.

10 The gas reformulating chamber comprises various ports including one or more ports for heaters, one or more process additive ports, and optionally one or more access ports, view ports and/or instrumentation ports. Heater ports include ports for primary heat sources and optional secondary sources. In one embodiment, the gas reformulating chamber comprises one or more ports for mounting plasma torches. In
15 one embodiment, the gas reformulating chamber comprises two or more ports for mounting plasma torches heat. In one embodiment, the gas reformulating chamber comprises three or more ports for mounting plasma torches. In one embodiment, the gas reformulating chamber comprises four or more ports for mounting plasma torches.

In one embodiment, there is provided two ports for plasma sources positioned at
20 diametric locations along the circumference of the gas reformulating chamber. In one embodiment, two ports are provided for tangentially mounting two plasma torches. In one embodiment, the ports for the tangentially mounted plasma torches are located above the air ports or inlets to provide maximum exposure to plasma torch heat.

Optionally, ports for mounting plasma torches may be fitted with a sliding mounting
25 mechanism to facilitate the insertion and removal of the plasma torch(es) from the gas reformulating chamber and may include an automatic gate valve for sealing the port following retraction of the plasma torch(es).

Optionally, one or more process additive ports or inlets are included to enable process
30 additives, such as carbon dioxide, other hydrocarbons or additional gases to be injected into the gas reformulating chamber. Optionally, ports or inlets are provided

such that reformulated gas not meeting quality standards may be re-circulated into the gas reformulating chamber for further processing. Ports or inlets may be located at various angles and/or locations to promote turbulent mixing of the materials within the gas reformulating chamber. One or more ports can be included to allow
5 measurements of process temperatures, pressures, gas composition and other conditions of interest.

In addition, the gas reformulating chamber may further include one or more ports for secondary torch heat sources to assist in the pre-plasma torch heating or plasma torch heating of the gas reformulating chamber. Optionally, plugs, covers, valves and/or
10 gates are provided to seal one or more of the ports or inlets in the gas reformulating chamber. Appropriate plugs, covers, valves and/or gates are known in the art and can include those that are manually operated or automatic. The ports may further include appropriate seals such as sealing glands.

As noted above, the GRS comprises one or more inputs for one or more oxygen
15 sources, the oxygen source(s) include, but are not limited to, oxygen, oxygen-enriched air, air, oxidizing medium and steam, therefore the gas conversion chamber comprises one or more ports for oxygen source inputs. In one embodiment, the gas conversion chamber comprises one or more ports for air and/or oxygen inputs and optionally one or more ports for steam inputs. In one embodiment, the gas reformulating chamber
20 comprises one or more oxygen source ports. In one embodiment, the gas reformulating chamber comprises two or more oxygen source ports. In one embodiment, the gas reformulating chamber comprises four or more oxygen source ports. In one embodiment, the gas reformulating chamber comprises six oxygen source ports. In one embodiment, there is provided nine oxygen source ports
25 arranged in three layers around the circumference of the gas reformulating chamber. The oxygen source ports may be in various arrangements so long as the arrangements provide sufficient mixing of the oxygen source with the input gas.

The gas reformulating chamber may further optionally include additional or supplementary gas mixers at or near the input gas inlet to mix the input gas such that
30 the input gas is of more uniform composition and/or temperature and/or to mix the

input gas with process additives. In one embodiment, the mixers comprises two or more air swirl jets at or near the input gas inlet which inject a small amount of air into the input gas and create a swirling motion or turbulence in the input gas stream and thereby mix the input gas by taking advantage of the injected air's velocity. In one
5 embodiment, the mixer comprises three or more air swirl jets at or near the inlet which inject a small amount of air into the input gas and create a swirling motion or turbulence in the input gas stream and thereby mix the input gas. In one embodiment, the mixer comprises four or more air swirl jets at or near the inlet which inject a small amount of air into the input gas and create a swirling motion or turbulence in the input
10 gas stream and thereby mix the input gas. The number of air swirl jets is designed to provide maximum mixing and swirl based on the designed air flow and exit velocity, so that the jet could penetrate to the center of the chamber.

Baffles may also be used to induce mixing of the input gas by creating turbulence in the input gas. A baffle is a mechanical obstruction to the normal flow pattern. Baffles
15 serve to block a section of the combustion chamber cross section, resulting in a rapid increase in flow velocity and a corresponding rapid decrease on the downstream side of the baffle. This generates a high level of turbulence and speeds local mixing.

Baffles may be located at various locations in the gas reformulating chamber. Baffle arrangements are known in the art and, include but are not limited, to cross bar
20 baffles, bridge wall baffles and choke ring baffle arrangements. Accordingly, in one embodiment, the gas mixing mixing comprises baffles. Figure 55A and B show embodiments comprising baffles.

As noted above, the GRS comprises a oxygen source, the oxygen source can include but or not limited to oxygen, oxygen-enriched air, air, oxidizing medium and steam,
25 therefore the gas conversion chamber comprises one or more oxygen source inputs. In one embodiment, the air and/or oxygen and steam inputs comprise high temperature resistance atomizing nozzles or jets. Appropriate air nozzles are known in the art and can include any commercially available type. The type of nozzles being chosen based on functional requirements, where a type A nozzle is for changing the
30 direction of air flows for creating the desired swirls and a type B nozzle is for creating

high velocity of air flow to achieve certain penetrations, and maximum mixing.

The nozzles can direct the air to whatever angle is effective for mixing the gas. In one embodiment, the air jets are positioned tangentially. In one embodiment, angular blowing is achieved by having a deflector at the tip of the input nozzle, thus allowing
5 the inlet pipes and flanges to be square with the gas reformulating chamber.

The arrangement of air and/or oxygen inputs is based on the diameter of gas reformulating chamber, the designed flow and jet velocity, so that adequate penetration, maximum swirl and mixing can be achieved. Various arrangements of the oxygen inputs or ports, steam inputs or ports and ports for plasma torches which
10 provide sufficient mixing of the input gas with the injected oxygen and steam and sufficient residence time for the reformulating reaction to occur are contemplated by the invention. For example, the oxygen inputs or ports, steam inputs or ports and ports for the plasma torches may be arranged in layers around the circumference of the gas reformulating chamber. This arrangement allows for the tangential and layered
15 injection of plasma gases, oxygen and steam which results in a swirling motion and adequate mixing of the input gas with the oxygen and steam and provides a sufficient residence time for the reformulating reaction to occur. In embodiments in which the air and/or oxygen input ports are arranged in layers, the air and/or oxygen jets can optionally be arranged to maximize the mixing effects.

20 The arrangements of steam inputs or ports is flexible in number, levels, orientations and angle as long as they are located in a position to provide optimized capabilities to the temperature control. In one embodiment, the gas reformulating chamber comprises one or more steam inputs or ports. In one embodiment, the gas reformulating chamber comprises two or more steam inputs or ports. The steam inputs
25 or ports may be in various arrangements so long as the arrangements provide sufficient mixing with the input gas. In one embodiment there is provided two steam input ports arranged in two layers around the circumference of the gas reformulating chamber and positioned at diametric locations.

The oxygen and/or steam input ports may also be positioned such that they inject
30 oxygen and steam into the gas reformulating chamber at an angle to the interior wall

of the gas reformulating chamber which promotes turbulence or a swirling of the gases. The angle is chosen to achieve enough jet penetration and maximum mixing based on chamber diameter and designed air jet flow and velocity.

5 In one embodiment, the oxygen and/or steam inputs inject air and steam at an angle between about 50-70° from the interior wall of the gas reformulating chamber. In one embodiment, the oxygen and steam inputs inject air and steam at an angle between about 55-65° from the interior wall of the gas reformulating chamber. In one embodiment, the oxygen and steam inputs inject oxygen and steam at an about 60° angle from the interior wall of the gas reformulating chamber.

10 The air jets can be arranged such that they are all in the same plane, or they can be arranged in sequential planes. The arrangement of air jets is designed to achieve maximum mixing effects. In one embodiment the air jets are arranged in lower and upper levels. In one embodiment, there are four jets at the lower level and another six jets at upper level in which three jets are slightly higher than the other three to create
15 cross-jet mixing effects to achieve better mixing.

In one embodiment, the gas reformulating chamber includes oxygen inputs, steam input ports, and ports for plasma torches that are arranged such that there is adequate mixing of the gases and steam throughout the chamber. Optionally, the process air can be blown into the chamber angularly so that the air creates a rotation or cyclonic
20 movement of the gases passing through the chamber. The plasma torches may also be angled to provide further rotation of the stream.

In order for the reformulating reaction to occur, the gas reformulating chamber must be torch heated to a sufficiently high temperature. A worker skilled in the art could readily determine an adequate temperature for the reformulating reaction. In one
25 embodiment, the temperature is about 800°C to about 1200°C. In one embodiment, the temperature is about 950°C to about 1050°C. In one embodiment the temperature is about 1000°C to 1200°C. The GRS therefore further comprises one or more non-transferred arc plasma torches. Non-transferred arc plasma torches are known in the art and include non-transferred arc A.C. and D.C. plasma torches. A variety of gases
30 have been used with plasma torches including but not limited to air, O₂, N₂, Ar, CH₄,

C₂H₂ and C₃H₆. A worker skilled in the art could readily determine the type of plasma torches that may be used in the GRS.

In one embodiment, the plasma torch is one or more non-transferred arc A.C. plasma torch(es). In one embodiment, the plasma torch is one or more non-transferred D.C. plasma torch(es). In one embodiment, the plasma torch is two non-transferred, reverse polarity D.C. plasma torches. In one embodiment, there are two plasma torches that are positioned tangentially to create same swirl directions as air and/or oxygen inputs do. In one embodiment, the plasma torch is two 300 kW plasma torches each operating at the (partial) capacity required. In one embodiment, the gas reformulating apparatus comprises one or more plasma torch(es). In one embodiment, the gas reformulating apparatus comprises two or more plasma torches. In one embodiment, the gas reformulating apparatus comprises two water cooled, copper electrode, NTAT DC plasma torches.

In one embodiment, the use of plasma torch heat is minimized by maximizing the release of torch heat that occurs during the reformulating of carbon or multi-carbon molecules to mainly CO and H₂ by optimizing the amount of air and/or oxygen injected into the gas reformulating chamber.

A Heat Recycling System

The invention further comprises a system for optimizing the efficiency of gasifying carbonaceous feedstock by recovering sensible heat from the gasification process and recycling it for use within the system and optionally for external applications. Various embodiments of the heat recycling system of the invention are shown in Figures 60 to 67.

In one embodiment, the system recycles heat recovered from hot product gas, transferring it back to a gasifier. In particular the system comprises means to transfer the hot product gas to a gas-to-air heat exchanger, where the heat from the hot product gas is transferred to ambient air to produce heated exchange-air and cooled product gas, and means to transfer the heated exchange-air to the exchange-air inlet means in the gasifier. The heated exchange-air is passed into the gasifier to provide the heat

required to drive the gasification reaction. The heated exchange-air may also optionally be used to preheat or pretreat, directly or indirectly, the feedstock to be gasified.

5 Optionally, the system additionally comprises one or more heat recovery steam generators to generate steam, which can be used to drive a steam turbine, as a process additive in the gasification reaction, or in some other application. According to one embodiment of the invention, the system also comprises a control subsystem comprising sensing elements for monitoring operating parameters of the system, and response elements for adjusting operating conditions within the system to optimize
10 the gasification process, wherein the response elements adjust the operating conditions within the system according to the data obtained from the sensing elements, thereby optimizing the efficiency of a gasification process by minimizing energy consumption of the process, while also maximizing energy production.

In one embodiment of the present invention, the heat exchanging system for
15 transferring heat produced during the gasification process back to a gasifier to drive the gasification reaction. In this embodiment, this is accomplished by heating ambient air with the heat from a hot gasifier/reformulating system in a product gas-to-air heat exchanger to produce a heated air product (hereinafter referred to as exchange-air), and passing the heated exchange-air produced in the gas-to-air heat
20 exchanger back into the gasifier.

Energy efficiencies are therefore optimized by this system, since the recycling of recovered sensible heat back to the gasification process reduces the amount of energy inputs required from external sources for the steps of drying, volatilizing and gasifying the feedstock. The recovered sensible heat may also serve to minimize the
25 amount of plasma heat required to achieve a desired quality of syngas. Thus, the heat exchange system allows for the efficient gasification of a carbonaceous feedstock, wherein the heat required for gasification is provided by hot exchange-air, where the exchange-air has been heated using sensible heat recovered from the hot product gas.

The sensible heat transferred from the product gas to the heated exchange-air can also
30 be used for external heating applications, as well as heating applications elsewhere in

- the gasification process. For example, the heated exchange-air can be used directly or indirectly to preheat or pretreat the feedstock to be gasified. In the case of a direct heating/pretreating step, the exchange-air is directly passed through the feedstock to heat and/or remove moisture. In the case of an indirect heating/pretreating step, heat is transferred from the heated exchange-air to oil (or to water to produce steam), wherein the heated oil (or steam product) is used to heat the wall of a feedstock dryer/preheater. In all cases, the recycling of sensible heat minimizes the amount of energy inputs required for these heating applications. Thus, the heat recycling system can transfer the heat from the heated exchange-air to any working fluid of interest.
- Such working fluids of interest include, but are not limited to, oil, water, or another gas such as nitrogen or carbon dioxide. It is also within the scope of the present invention to transfer heat from the converter gas directly to the working fluid of interest. Where heat is transferred to a working fluid other than air, an appropriate heat exchanging system is used.
- After heat is recovered in the product gas-to-air heat exchanger, the product gas, although cooled, typically still contains too much heat to undergo filtering and conditioning steps as are known in the art. The present invention therefore also optionally provides for the further cooling of the product gas prior to such subsequent filtering and conditioning steps.
- Accordingly, the system may optionally include a subsystem for recovering additional heat from the partially cooled product gas after it has passed through the gas-to-air heat exchanger. In one embodiment, the system further comprises a heat recovery steam generator, whereby additional heat recovered from the product gas is used to convert water to steam (referred to as exchange-steam).
- The exchange-steam produced in the heat recovery steam generator can be used to drive downstream energy generators such as steam turbines and/or be used in direct-drive turbines and/or can be added to the gasification process. The exchange-steam can also be used in other systems, for example, for the extraction of oil from tar sands or in local heating applications, or it can be supplied to local industrial clients for their purposes. In one embodiment, the steam produced using heat from the product gas is

saturated steam. In another embodiment, the steam produced using heat from the product gas is superheated steam, which can be produced either directly through heat exchange between water and product gas or between saturated steam and product gas.

Where the system does not include a system for recovering additional heat from the partially cooled product gas after it has passed through the gas-to-air heat exchanger, another system for further cooling the product gas prior to conditioning is provided. In one embodiment, there is provided a dry quench step for further cooling the product gas prior to conditioning. The dry quench step is provided to remove excess heat from the product gas to provide a cooled product gas as may be required for the subsequent filtering and conditioning steps. Selection of an appropriate system for further cooling of the product gas prior to conditioning is within the knowledge of a worker skilled in the art. In some embodiments, the further cooling system is considered to be a part of the gas conditioning system (GCS) described in more detail below.

The control subsystem may also be used to optimize the composition (i.e., heating value) of the product gas produced, and optionally to ensure that the system is maintained within safe operational parameters.

The functional requirements for the product gas-to-air heat exchanger are where the hot product gas and the ambient air are each passed through the gas-to-air heat exchanger, whereby sensible heat is transferred from the hot product gas to the ambient air to provide the heated exchange-air and the cooled product gas. Different classes of heat exchangers may be used in the present system, including shell and tube heat exchangers, both of straight, single-pass design and of U-tube, multiple pass design, as well as plate-type heat exchangers. The selection of appropriate heat exchangers is within the knowledge of a worker of ordinary skill in the art.

Some particulate matter will be present in the product gas, thus the gas-to-air heat exchanger is designed specifically for a high level of particulate loading. The particle size is typically between 0.5 to 100 micron. In one embodiment, the heat exchanger is a single pass vertical flow heat exchanger, wherein the product gas flows in the tubes rather than on the shell side. In the single pass vertical flow embodiment, the product

gas flows vertically in a "once through" design, which minimizes areas where build up or erosion from particulate matter could occur.

The product gas velocities should be maintained to be high enough for self-cleaning, while still minimizing erosion. In one embodiment, gas velocities are between 3000
5 to 5000 m/min. Under normal flow conditions, gas velocities are from about 3800 m/min to about 4700 m/min.

Due to the significant difference in the ambient air input temperature and hot product gas, each tube in the gas-to-air heat exchanger preferably has an individual expansion bellows to avoid tube rupture. Tube rupture may occur where a single tube becomes
10 plugged and is therefore no longer expanding/contracting with the rest of the tube bundle. In those embodiments where the process air pressure is greater than the product gas pressure, tube rupture presents a high hazard due to problems resulting from air entering gas mixture.

In one embodiment of the present invention, the system is run intermittently, i.e.,
15 subject to numerous start-up and shut down cycles as desired. Therefore, it is important that the equipment must be designed to withstand repeated thermal expansion and contraction.

In order to minimize the hazard potential from a tube leak, the heat exchange system further comprises one or more individual temperature transmitters, for example, at the
20 product gas inlet and product gas outlet of the gas-to-air heat exchanger, as well as at the exchange-air outlet. Where the temperature transmitters are associated with the product gas outlet of the gas-to-air heat exchanger, these temperature transmitters are positioned to detect a temperature rise resulting from combustion in the event of having exchange-air leak into the product gas conduit. Detection of such a
25 temperature rise will result in the automatic shut down of the process air blower so as to eliminate the source of oxygen. In addition, the heat exchangers are provided, as required, with ports for instrumentation, inspection and maintenance, as well as repair and/or cleaning of the conduits.

In accordance with the present invention, the heated exchange-air may be provided as

required to different regions of the gasifier through independent exchange-air feed and distribution systems. The exchange-air feed and distribution systems comprise exchange-air inlets that allow for the introduction of heated exchange-air to the gasification region. These inlets are positioned within the converter to distribute the heated exchange-air throughout the converter to initiate and drive the gasification of the feedstock. In one embodiment, the exchange-air inlets comprise perforations located in the floor of the gasifier. In one embodiment, the exchange-air inlets comprise perforations located in the walls of the gasifier.

In one embodiment, the exchange-air inlets comprise separate air boxes for each region from which hot exchange-air can pass through perforations in the floor of the converter to that region. In one embodiment, the exchange-air inlets are independently controlled spargers for each region.

The present invention, in addition to the gas-to-air heat exchanger, optionally includes a system for further cooling the product gas prior to a conditioning step. In one embodiment, the system for further cooling the product gas prior to cleaning and conditioning also provides for the recovery of additional heat from the product gas. Where recovery of further sensible heat from the product gas is an objective, the heat is transferred from the product gas to another working fluid, for example water, oil, or air. The products of such embodiments can include, respectively, heated water (or steam), heated oil, or additional hot air.

In one embodiment, the system of the present invention recovers further sensible heat from the product gas using a heat exchanger to transfer the heat from the partially cooled product gas to water, thereby producing either heated water or steam, and a product gas that has been further cooled. In one embodiment, the heat exchanger employed in this step is a heat recovery steam generator, which uses the recovered heat to generate exchange-steam. In one embodiment, the water is provided into the heat exchanger in the form of low temperature steam. In another embodiment, the exchange-steam produced is saturated or superheated steam.

Steam that is not used within the conversion process or to drive rotating process equipment, may be used for other commercial purposes, such as the production of

electricity through the use of steam turbines, or in local heating applications or it can be supplied to local industrial clients for their purposes, or it can be used for improving the extraction of oil from the tar sands. The exchange-steam produced may also be passed through a turbine, thereby driving rotating process equipment, for example, an exchange-air blower or a syngas blower. The exchange-steam can also be used to indirectly heat feedstock, thereby drying the feedstock prior to gasification in the converter.

In one embodiment, where cooling of different systems or processes is required, the excess heat can be removed (and recovered) by a water cooling step. The resulting heated water can be, in turn, used to pre-heat the water prior to its use in the HRSG. Heated water streams come from various sources including, but not limited to, syngas cooling processes in the GQCS system, plasma heat source cooling systems. Heated water can also be used to preheat oil for various applications.

The heat exchanger for the HRSG is designed with the understanding that some particulate matter will be present in the product gas. Again, product gas velocities here are also maintained at a level high enough for self-cleaning of the tubes, while minimizing erosion. In one embodiment where the system for further cooling the product gas prior to conditioning does not include the recovery of additional heat, the cooling step comprises a dry quench step.

Conduit systems are employed to transfer gases from one component of the system to another. Accordingly, the system comprises a syngas conduit system to transfer the hot product gas to a heat exchanger for recovery of the product gas sensible heat. The system also comprises an exchange-air conduit system to transfer the heated exchange-air to the converter, where it is introduced to the converter via exchange-air inlets. The conduit systems typically employ one or more pipes, or lines, through which the gases are transported.

Where the system comprises a heat recovery steam generator, the system will also comprise an exchange-steam conduit system to transfer the heated exchange-steam for use in one or more of the applications previously listed. The exchange-steam conduit system may comprise multiple pipes running in parallel, or a system of branching

conduits, where a given branch is designated for a specific application.

The exchange-air conduit system will optionally employ one or more flow regulating devices, flow meters and/or blower, located throughout the system to provide a means for controlling the flow rate of the exchange-air. In one embodiment, there are a plurality of exchange-air flow control valves (one for each level) to control the flow of exchange-air to the gasifier. After each of the control valves, the air is again split to the air boxes for the gasifier and to three distribution rings around to the reformer, each with various injection points. In one embodiment, there is one exchange-air flow control valve to control the flow of exchange-air to the GRS. In this embodiment, the exchange-air is provided as a process additive.

The exchange-air conduits also optionally comprise means for diverting exchange-air, for example, to venting outlets or to optional additional heat exchange systems. The flow regulating devices, and/or blowers, and/or diversion means are optionally controlled by a control subsystem, as is discussed in detail below.

The conduit system will also optionally comprise service ports to provide access to the system for the purpose of carrying out routine maintenance, as well as repair and/or cleaning of the conduits.

A Gas Conditioning System

The gas conditioning system (GCS) conditions cooled product gas in a two-stage conditioning process and provides a final conditioned gas that has an appropriate composition for the desired downstream application. Stage One comprises one or more initial dry/solid phase separation steps followed by Stage Two, comprising one or more further processing steps. In general, in the dry/solid phase separation steps, a substantial proportion of the particulate matter and a large proportion of heavy metal contaminants are removed. In Stage Two, additional amounts of particulate matter and heavy metal contaminants as well as optionally other contaminants present in the gas are removed. Thus, the GCS comprises various components that carry out processing steps, separate particulate matter, acid gases, and/or heavy metals from the input gas and that, optionally, adjust the humidity and temperature of the gas as it

passes through the GCS. The GCS further comprises a control system to control and optimize the overall conditioning process.

The GCS comprises two integrated subsystems: a Converter GC and a Solid Residue GC, both of which carry out Stage One and Stage Two processing. The GCS is also
5 integrated with the residue conditioner and solid residue produced in Stage One processing by the Converter GC is passed into the residue conditioner. The Converter GC and the Solid Residue GC can operate in parallel wherein both subsystems are capable of independently conducting both Stage One and Stage two processes, or the two subsystems can operate in a convergent manner, wherein they share some or all
10 of the components for Stage Two processing.

Figures 68, 70 and 72 depict embodiments of the GCS in which the two subsystems operate in a convergent manner.

In one embodiment, the components of the GCS and the order of each of the processing steps are selected to minimize generation of hazardous waste that must be
15 treated and/or disposed of. The presence and sequence of the processing steps can be selected, for example, based on the composition of the input gas and the composition of the conditioned gas required for the selected downstream application.

In one embodiment of the present invention, the amount of hazardous waste produced by the GCS is less than about 5% of the weight of carbonaceous feedstock used. In
20 one embodiment, the amount of hazardous waste produced is less than about 2% of the weight of carbonaceous feedstock used. In one embodiment, the amount of hazardous waste produced is less than 1% of the weight of carbonaceous feedstock used. In one embodiment, the amount of hazardous waste produced is between about 1 kg and about 5 kg per 1 tonne of carbonaceous feedstock used. In one embodiment,
25 the amount of hazardous waste produced is between about 1 kg and about 3 kg per 1 tonne of carbonaceous feedstock used. In one embodiment, the amount of hazardous waste produced is between about 1 kg and about 2 kg per 1 tonne of carbonaceous feedstock used.

Stage One of the GCS comprises components for implementing one or more dry or

solid phase processing steps that remove at least a portion of the heavy metals and a majority of the particulate matter from the input gas. Suitable solid phase processing steps are known in the art.

For example, heavy metal removal can be achieved using one or more solid phase separation components known in the art. Non-limiting examples of such solid phase separation components include dry injection systems, particle removal units, activated carbon filtration components, and components that allow contact with specialized sorbents, such as zeolites and nanostructures. Selected representative examples are described in additional detail below. As is known in the art, these particulate separation components can be used to remove or separate particulate matter/heavy metals in the solid/dry phase, for example, in dry injection processes, activated carbon filtration, dry scrubbing, various particle removal processing steps and other dry or solid phase processing steps known in the art.

In one embodiment of the present invention, Stage One of the Converter GC comprises a dry injection system and one or more particle removal units and Stage One of the Solid Residue GC comprises one or more particle removal units.

Selection of the appropriate Stage One processing steps can be readily determined by one skilled in the art based on, for example, the composition of the input gas, the temperature of the input gas, the desired composition of the final conditioned gas, the end use of the composition gas, as well as cost considerations and equipment availability. Stage One of the GCS can optionally comprise one or more gas coolers if required.

As noted above, Stage One of the GCS provides for removal of the majority of the particulate matter and at least a portion of the heavy metal contaminants present in the input gas. In one embodiment, at least about 70% of the particulate matter present in the input gas is removed in Stage One. In one embodiment, at least about 80% of the particulate matter present in the input gas is removed in Stage One. In one embodiment, at least about 90% of the particulate matter present in the input gas is removed in Stage One. In one embodiment, at least about 95% of the particulate matter present in the input gas is removed in Stage One. In one embodiment, at least

about 98% of the particulate matter present in the input gas is removed in Stage One. In one embodiment, at least about 99% of the particulate matter present in the input gas is removed in Stage One. In one embodiment, 99.5% of the particulate matter present in the input gas is removed in Stage One.

- 5 In one embodiment, at least about 50% of the heavy metal contaminants present in the input gas are removed in Stage One. In one embodiment, at least about 60% of the heavy metal contaminants present in the input gas are removed in Stage One. In one embodiment, at least about 70% of the heavy metal contaminants present in the input gas are removed in Stage One. In one embodiment, at least about 80% of the heavy metal contaminants present in the input gas are removed in Stage One. In one embodiment, about 90% of the heavy metal contaminants present in the input gas are removed in Stage One.

Dry injection processes are known in the art and generally utilize a calculated amount of a suitable sorbent which is injected in the gas stream with enough residence time so that fine heavy metal particles and fumes can adsorb on the surface of the sorbent. Heavy metals adsorbed on sorbent can be captured by a particle removal such as those described below, which removes heavy metals/particulate matter in the dry/solid phase and prevent it from moving through the GCS along with the input gas.

Examples of suitable sorbents include, but are not limited to, activated carbon; promoted-activated carbon impregnated with iodine, sulphur, or other species; feldspar; lime; zinc-based sorbents; sodium-based sorbents; metal oxide based sorbents; and other physical and chemical adsorbents known in the art that are capable of effectively removing heavy metals such as mercury, arsenic, selenium and the like. The sorbents may be a mesh size varying between a maximum size of about a 60 mesh size and minimum size of about a 325 mesh size.

Injection is generally through a sorbent input, such as a port, nozzle or tube, and can be achieved by gravity, locked hopper, or screw conveyor. The present invention also contemplates that the sorbent can be provided within pipes that make up the GCS, for example in a pipe leading to a particle removal means, to be mixed with the input gas as it passes through the pipe. Other methods known in the art are also included. The

GCS can comprise multiple sorbent inputs or a single sorbent input.

The sorbents can be stored in one or more holding containers from which the sorbent(s) are delivered to the input(s). The sorbent holding containers can be part of the GCS or can be external to the GCS.

- 5 As noted above, various combinations of sorbents can be injected into the input gas by dry injection and suitable combinations can be readily determined by one of skill in the art based on, for example, the composition of the input gas. In one embodiment, feldspar is injected into the input gas. In one embodiment, activated carbon is injected into the input gas. In one embodiment, feldspar is used as a pre-coat for the
10 particle removal means. In one embodiment, activated carbon is injected into the input gas, and the particle removal means are precoated with feldspar. In one embodiment, feldspar is continuously injected into the system.

- In one embodiment, the GCS of the present invention includes one or more particle removal units which act to remove particulate matter from the input gas. Particle
15 removal means can also remove heavy metals, such as elemental mercury, from the input gas. In embodiments where dry injection is employed in the GCS, the one or more particle removal units also serve to remove contaminant-laden sorbents from the input gas. Examples of suitable particle removal units include, but are not limited to, cyclone separators or filters, high temperature ceramic filters, moving bed granular
20 filters, baghouse filters, and electrostatic precipitators (ESP).

- As is known in the art, the choice of particle removal unit will depend on, for example, the temperature of the input gas, the size of the particulate matter to be removed, and, when applicable, the type of sorbent injected into the gas stream. Suitable particle removal units can be readily selected by one of skill in the art. In one
25 embodiment of the present invention, Stage One of the GCS comprises one or more particle removal units selected from a cyclone filter, a high temperature ceramic filter and a baghouse filter. In one embodiment, each of Stage One of the Converter GC and the Solid residue GC comprise a baghouse.

Cloth collectors such as baghouse filters can collect particles of a size down to about

0.01 microns, depending on the type of filter employed. Baghouse filters are typically fabric filters, cellulose filters or organic polymer-based filters. Other examples of filters that can be used in a baghouse context include, but are not limited to, lined and unlined fiberglass bags, Teflon lined bags and P84 basalt bags. Suitable filters can be readily selected by those of skill in the art based on considerations such as, one or more of the temperature of the input gas, the moisture levels in the baghouse and in the input gas, the electrostatic nature of the particles in the input gas, acid and/or alkali chemical resistance of the filter, the ability of the filter to release the filter cake, filter permeability and the size of the particles.

10 In one embodiment of the present invention, the GCS comprises a baghouse filter and is configured such that the temperature of the gas entering the baghouse is between about 180°C and about 280°C. As is known in the art, operating a baghouse filter at a higher temperature can decrease the risk of tars in the input gas plugging the filters and reducing efficiencies. Higher temperatures can reduce the efficiency of particle removal by the baghouse filters, for example, increasing the operating temperature from 200°C to 260°C decreases particle removal efficiency from 99.9% to 99.5%. Thus, when higher operating temperatures are selected for a baghouse filter comprised by the GCS, the GCS can comprise additional downstream components, either in Stage One or Stage Two, to capture remaining particulates. For example, wet scrubbers and activated carbon beads can be included for removal of particulates in addition to other contaminants. In one embodiment of the present invention in which the GCS comprises a baghouse filter, the GCS is configured such that the temperature of the gas entering the baghouse is between about 250°C and about 260°C. In another embodiment in which the GCS comprises a baghouse filter, the GCS is configured such that the temperature of the gas entering the baghouse is between about 190°C and about 210°C.

In one embodiment, a gas cooling system may be used to cool the input gas before it enters the particle removal unit. For example, as is known in the art, cooling of the input gas may be of particular importance when a baghouse type filter is used for particulate removal, since baghouse type filters often cannot withstand extremely high temperatures.

In accordance with one embodiment of the present invention, the GCS is configured to process input gas for which the temperature has been reduced by passing the input gas through a gas cooler prior to entry into the GCS. In another embodiment of the present invention, the GCS comprises one or more gas coolers for reducing the temperature of the input gas prior to entry into Stage One processing. Suitable gas coolers for incorporation into the GCS are known in the art and include, but are not limited to, dry quenchers, evaporative cooling towers, gas coolers, chillers, recuperators, heat exchangers, indirect air to gas heat exchangers, and heat recovery steam generators (HRSGs). In one embodiment, the GCS comprises a heat exchanger and/or a dry quencher.

In one embodiment, the GCS incorporates an evaporative cooling tower in Stage One to cool the temperature of the syngas from about 740°C to about 150-200°C, for example, by adiabatic saturation, which involves direct injection of water into the gas stream in a controlled manner. The evaporating cooling process is a dry quench process, and can be monitored to ensure that the cooled gas is not wet, i.e. that the relative humidity of the cooled gas is still below 100% at the cooled temperature.

Suitable residue conditioning chambers for incorporation into the GCS are described in detail below. The residue conditioning chamber can be shared with the converter of the facility, or the GCS may include a dedicated residue conditioning chamber.

Figure 78A depicts the configuration in one embodiment of the present invention for a solid residue conditioner, a converter and a Stage One baghouse of the GCS.

Stage Two of the GCS comprises one or more components for implementing further processing steps that remove additional amounts of particulate matter and heavy metal contaminants, and other contaminants present in the input gas. Stage Two processes can include dry phase separation steps as described for Stage One and/or other separation steps, including wet processing steps. Non-limiting examples of other processing steps that may be implemented in Stage Two include processes that remove acid gases, heavy metals and particulate matter, and other contaminants such as dioxin, furan, CO₂, and ammonia. As is known in the art, various components can be used to carry out these processes, including various wet scrubbers (such as venturi

scrubbers and impinjet scrubbers), chloride guard beds, wet ESP and the like. Stage Two can also include cooling units and/or humidity controllers, as well as gas moving units for ensuring that the input gas moves through the system. Examples of Stage Two processing steps, other than those already described in Stage One, are described
5 below.

Input gases to be processed in the GCS include as contaminants acid gases such as HCl and H₂S. The concentrations of these acid gases in syngas can range from about 0.05 to about 0.5% for HCl, and from about 100 ppm to about 1000 ppm for H₂S, depending on the carbonaceous feedstock used in the gasification process. In one
10 embodiment, the GCS is configured to process input gas comprising about 0.178 % of HCl and about 666 ppm (0.07%) of H₂S. In one embodiment, the GCS is configured such that the conditioned gas exiting the GCS contains between about 20 ppm and about 5 ppm HCl and between about 30 ppm and about 20 ppm H₂S.

Acid gas removal or separation can be achieved by dry scrubbing or wet scrubbing
15 processes. In one embodiment, Stage Two of the GCS comprises a wet scrubbing process to remove acid gases.

In addition to dry and wet scrubbing processes as described above, a number of processing steps are known in the art for removing HCl vapor from gases. Non-limiting examples of such processing steps include: adsorption of the HCl on
20 activated carbon or alumina, reaction with alkali or alkaline earth carbonates or oxides, the use of chloride guards, and the use of high temperature sorbents such as alkali and alkaline earth compounds, shortite (Na₂CO₃, 2CaCO₃) and trona (Na₂CO₃, NaHCO₃, 2H₂O), eutectic melts of Li₂CO₃ and Na₂CO₃, and flue gas sorbents such as alkalized alumina. In one embodiment, Stage Two of the GCS
25 comprises an HCl scrubber for removal of HCl from the input gas using alkaline solution.

H₂S may be removed from the input gas using various processes known in the art including wet and dry scrubbing processes as outlined above. Suitable methods include for example, wet absorption with NaOH or triazine, dry adsorption with
30 Sufatreat, biological processes such as the use of Thiopaq® scrubbers, or selective

oxidation, including liquid redox (Low CAT). Physical solvent processes can also be used to separate H₂S from the input gas. Non-limiting examples of such physical solvent that can be used include polyethylene glycol derivatives such as Selexol®; fluor solvents such as anhydrous propylene carbonate; methanol as used in a Rectisol
5 process. In one embodiment, Stage two of the GCS comprises a Thiopaq® scrubber for removal of the H₂S from the input gas.

Processes and particle removal units suitable for use in Stage One processes can also be used in Stage Two processes and have been described above. Activated carbon filtration employing an activated carbon filter bed or a fluidized bed can also be used
10 as remove heavy metals and/or particulate matter from the input gas. In one embodiment, the GCS comprises a carbon bed filter or mercury polisher as a particle removal unit in Stage Two.

As is known in the art, at a relative humidity (R.H.) of greater than 50%, water will start to adsorb on the carbon of the carbon bed filter and obstruct diffusion, which
15 affects removal performance. This can be corrected, however, by increasing bed depth. Carbon bed filters can also be used at higher relative humidities, for example between ~70% R.H and 100% R.H., when lower performance is acceptable as the performance effect is only seen when the desired final content of mercury in the conditioned gas is in the 0.001 to 0.01 ug/Nm³ mercury range. For example, when
20 mercury concentrations of about 19ug/Nm³ are acceptable, the higher R.H. ranges can be used.

In one embodiment, the GCS comprises an activated carbon filter with 7-8 inches of Water Column pressure drop to achieve about 99.8 % removal of mercury.

In embodiments where the input gas comprises dioxin and furan, the GCS can
25 optionally comprise an activated carbon injection step which will result in the dioxin and furan present in the gas being adsorbed to the carbon surface. The carbon can then be removed by a suitable particle removal unit. In one embodiment, the GCS comprises a spray dryer absorber that decreases the residence time at the relevant temperature range to minimise the possibility of dioxin/furan formation.

The GCS can optionally include components for the removal of carbon dioxide and/or ammonia if removal of these compounds is required. Suitable components are known in the art. As is also known in the art, ammonia can be removed from the input gas during the HCl scrubbing step.

- 5 Figures 69, 71, 73, 74 and 75 depict various non-limiting options for Stage One and Stage Two processing steps for the GCS in one embodiment of the present invention.

Cooling units and/or humidity controllers can optionally be included in the GCS as part of Stage One (as described above) or Stage Two. Suitable components are known in the art and include, but are not limited to, evaporative cooling towers, gas
10 coolers, chillers, recuperators, heat exchangers, indirect air to gas heat exchangers, and heat recovery steam generators (HRSGs). Recuperators and HRSGs can be used to cool the gas while utilizing the heat instead of dissipating it as is done by evaporative cooling towers, gas coolers, and chillers.

Demisters/reheaters may be incorporated in the GCS for moisture removal and/or
15 prevention of condensation as is known in the art. Heat exchangers can be included to reheat the final conditioned gas to the required temperature or relative humidity for the desired downstream application. A compressor can also optionally be included to compress the final conditioned gas to the required pressures for the desired downstream application.

20 In one embodiment, a gas cooler may be included in Stage Two of the GCS. The gas cooler (water cooled) functions to cool input gas that is pressurized through a gas moving unit (see below) and concomitantly heated. In one embodiment, the gas cooler cools the gas to about 35°C.

In one embodiment, the GCS comprises a humidity controller. The humidity
25 controller functions to ensure that the humidity of the output gas is appropriate for the downstream application desired. For example, a humidity controller may include a chiller to cool the gas stream and thus condense some water out of the gas stream. This water can be removed by a gas/liquid separator. In one embodiment, the GCS comprises a humidity controller for treatment of the conditioned gas to provide a

humidity of about 80% at 26°C. In one embodiment, the GCS is configured to first cool the conditioned gas to approximately 26°C and then reheat the gas to 40°C. The conditioned gas may then be stored.

5 In one embodiment, the GCS includes one or more gas moving units which supply a driving force for the gas throughout the GCS and move the input gas from the exit of the gasification system up to exit of the GCS.

Suitable gas moving units are known in the art and include, for example, process gas blowers, pressure blowers, vacuum pumps, positive displacement rotary blowers, reciprocating compressors, and rotary screw compressors and the like. In one
10 embodiment, the GCS comprises a process gas blower as a gas moving unit. In one embodiment, the GCS comprises a gas moving unit that additionally pressurizes the gas passing through the blower.

The optimal placement of the gas moving unit within the GCS can be determined by one of skill in the art. In one embodiment, the gas moving unit is located so as to
15 increase the efficiency of one or more of the processing steps of the GCS. For example, in one embodiment, the gas moving unit is located upstream of a heavy metal polisher such as a mercury polisher to optimise mercury removal, as this occurs most efficiently under pressure, and can also allow a reduced size mercury polisher vessel to be used.

20 **A Residue Conditioning System**

The invention further comprises a system for the conversion of residual matter from the converter into an inert slag product and a gas having a heating value. In particular, the system comprises a refractory-lined residue conditioning chamber comprising a residue inlet, a gas outlet, a slag outlet, a plasma heat source, and a
25 control subsystem for monitoring operating parameters and adjusting operating conditions within the system to optimize the conversion reaction. The plasma heat causes the residue to melt, and converts unreacted carbon present in the residue to a residue gas, which exits the chamber through the gas outlet, and optionally into a gas conditioning subsystem for cooling and conditioning as required for downstream

considerations.

Various embodiments of the residue conditioning system of the invention are shown in Figures 76 to 85.

5 The chamber may also optionally comprise one or more inlets for introducing air (or other oxygen containing additives) into the residue conditioning chamber to control the conditioning process. The chamber may also optionally comprise one or more additive inlets for introducing additives to control the composition of the resulting slag product.

10 The residue conditioning system of the present invention comprises a residue conditioning chamber which is adapted to i) input the residue to be conditioned, ii) input heat and condition the residue to form a molten slag material and a gaseous product having a heating value, and iii) output the molten slag and gaseous product. Accordingly, the residue conditioning chamber is a refractory-lined chamber comprising a residue inlet, a gas outlet, a slag outlet, and a plasma heat source port.
15 The residue conditioning chamber further optionally includes one or more air and/or steam inlets.

The residue conditioning chamber is designed to ensure that the residue conditioning process is carried out efficiently and completely, in order to use a minimum amount of energy to effect complete conditioning of the residue. Accordingly, factors such as
20 efficient heat transfer, adequate heat temperatures, residence time, molten slag flow, input residue volume and composition, and size and insulation of the chamber are taken into account when designing the residue conditioning chamber. The chamber is also designed to ensure that the residue conditioning process is carried out in a safe manner. Accordingly, the system is designed to isolate the residue conditioning
25 environment from the external environment.

The residue conditioning chamber is provided with a plasma heat source that meets the required temperature for heating the residue to levels required to convert any remaining volatiles and carbon to a gaseous product having a heating value and to melt and homogenize the residue to provide a molten slag at a temperature sufficient

to flow out of the chamber. The chamber is also designed to ensure highly efficient heat transfer between the plasma gases and the residue, to minimize the amount of sensible heat that is lost via the product gas. Therefore, the type of plasma heat source used, as well as the position and orientation, of the plasma heating means are
5 additional factors to be considered in the design of the residue conditioning chamber.

The residue conditioning chamber is also designed to ensure that the residue residence time is sufficient to bring the residue up to an adequate temperature for melting and homogenization, and to fully convert the carbon to the gaseous product. Accordingly, the chamber is provided with a reservoir in which the residue accumulates while
10 being heated by the plasma heat source. The reservoir also allows mixing of the solid and molten materials during the conditioning process. Sufficient residence time and adequate mixing ensures that the conditioning process is completely carried out, and that the resulting slag and gaseous products have the desired composition.

The chamber is designed for continuous or intermittent output of the molten slag material. Continuous slag removal allows the conditioning process to be carried out
15 on a continual basis, wherein the residue to be conditioned may be continuously input and processed by the plasma heat, without interruption for periodic slag removal.

In one embodiment, continuous slag exhaust is achieved by using a reservoir bounded on one side by a weir that allows the slag pool to accumulate until it exceeds a certain
20 level, at which point the molten slag runs over the weir and out of the chamber. In this embodiment, the residue drops through a residue inlet located at the top of the conditioning chamber into a reservoir, where it is conditioned by a plasma torch plume. The molten materials are held in the reservoir by a weir until the pool reaches the top of the weir. Thereafter, as additional residue enters the system and is
25 conditioned, a corresponding amount of molten material overflows the weir and out of the chamber through a slag outlet.

Where the residue being conditioned contains a significant amount of metal, and the residue conditioning chamber comprises a reservoir bounded by a weir, the metals, due to their higher melting temperature and density, typically accumulate in the
30 reservoir until such time as they are removed. Accordingly, in one embodiment of the

present invention, the reservoir is optionally provided with a metal tap port, whereby the tap port is plugged with a soft refractory paste which may be periodically removed using the heat from an oxygen lance. Once the tap port has been opened and the chamber temperature has been raised sufficiently to melt the accumulated metals, the
5 molten metals are tapped off from the bottom of the reservoir.

In one embodiment, the reservoir itself may also be provided with a slag outlet adapted for continuous exhaust of the molten slag. In one embodiment, the reservoir may also provide for intermittent slag removal, wherein the reservoir is designed to allow the accumulation of molten materials until the conditioning process is complete,
10 at which point the molten slag is exhausted.

Due to the very high temperatures needed to melt the residue, and particularly to melt any metals that may be present, the residue conditioning chamber wall is lined with a refractory material that will be subjected to very severe operational demands. The selection of appropriate materials for the design of a residue conditioning chamber is
15 made according to a number of criteria, such as the operating temperature that will be achieved during typical residue conditioning processes, resistance to thermal shock, and resistance to abrasion and erosion/corrosion due to the molten slag and/or hot gases that are generated during the conditioning process.

The inner refractory is selected to provide an inner lining having very high resistance
20 to corrosion and erosion, particularly at the slag waterline, in addition to resistance to the high operating temperatures. The porosity and slag wetting capability of the inner refractory material must be considered to ensure that the refractory material selected will be resistant to penetration of the molten slag into the hot face. The materials are also selected such that secondary reactions of the refractory material with hydrogen
25 are minimized, thereby avoiding a possible loss of integrity in the refractory and contamination of the product gas.

The residue conditioning chamber is typically manufactured with multiple layers of materials as are appropriate. For example, the outer layer, or shell, of the chamber is typically steel. Moreover, it may be beneficial to provide one or more insulating
30 layers between the inner refractory layer and the outer steel shell to reduce the

temperature of the steel casing. Where a second layer (for example, an insulating firebrick layer) is provided, it may also be necessary to select a material that does not react with hydrogen. An insulating board around the outer surface of the slag reservoir may also be provided to reduce the temperature of the steel casing. When
5 room for expansion of the refractory without cracking is required, a compressible material, such as a ceramic blanket, can be used against the steel shell. The insulating materials are selected to provide a shell temperature high enough to avoid acid gas condensation if such an issue is relevant, but not so high as to compromise the integrity of the outer shell.

10 The refractory material can therefore be one, or a combination of, conventional refractory materials known in the art which are suitable for use in a chamber for extremely high temperature (e.g., a temperature of about 1100°C to 1800°C) non-pressurized reaction. Examples of such refractory materials include, but are not limited to, high temperature fired ceramics (such as aluminum oxide, aluminum
15 nitride, aluminum silicate, boron nitride, chromic oxide, zirconium phosphate), glass ceramics and high alumina brick containing principally, silica, alumina and titania.

Due to the severe operating conditions, it is anticipated that the reservoir refractory will require periodic maintenance. Accordingly, in one embodiment, the residue conditioning chamber is provided in separable upper and lower portions, wherein the
20 chamber lower portion (where the reservoir is located) is removable from the chamber upper portion. In one embodiment, the chamber is suspended from a support structure such that the lower portion can be dropped away from the upper portion to facilitate maintenance. This embodiment provides for removing the lower portion without disturbing any connections between the chamber upper portion and upstream or
25 downstream components of the system.

The residue conditioning chamber may also include one or more ports to accommodate additional structural elements or instruments that may optionally be required. The chamber may also include service ports to allow for entry or access into the chamber for scrubbing/cleaning, maintenance, and repair. Such ports are known
30 in the art and can include sealable port holes of various sizes. In one embodiment, the

port may be a viewport that optionally includes a closed circuit television to maintain operator full visibility of aspects of the residue processing, including monitoring of the slag outlet for formation of blockages.

5 In one embodiment, the residue conditioning chamber may be tubular in shape. This embodiment comprises a torch mounting port, a residue inlet, a reservoir bounded on one side by a weir, a slag outlet, and a metal tap port.

The system comprises a residue input means in association with the residue inlet of the conditioning chamber. The residue inlet is adapted to receive the residue into the residue conditioning chamber. The residue input means conveys the residue from a
10 source of the residue material to the inlet of the conditioning chamber.

Residue material entering the chamber may come from one or multiple sources. Sources of the residue may include, but are not limited to, a low temperature or high temperature gasifier, a hopper in which the residue is stored, or upstream gas conditioning systems, for example, a baghouse filter.

15 Where the residue to be conditioned is provided in more than one input stream, or from more than one source, the different streams may each be passed into the conditioning chamber through a dedicated residue inlet, or they may be combined prior to introduction into the residue conditioning chamber. In the latter embodiment, there is provided one residue inlet through which all residues are provided.
20 Accordingly, the chamber may comprise a common inlet or multiple inlets to cater to any physical characteristics of the input residue material.

The source of the residue may be provided in direct communication with the conditioning chamber, i.e., each residue input is fed directly from the source into the residue conditioning chamber. Alternatively, the source may be provided in indirect
25 communication with the residue conditioning chamber, wherein the residue inputs are conveyed from the source into the residue conditioning chamber via a system of conveyor means.

Where the residue conditioning chamber is indirectly connected to the source of the residue, the residue input means comprises one or more means for conveying the

residue from the source into the residue conditioning chamber. For example, the residue input means may include a single screw conveyor or a series of screw conveyors.

5 In embodiments wherein the residue conditioning chamber is directly connected to the source of the residue, the residue source and residue conditioning chamber employed may be the same as those of the indirectly connected embodiment, with the exception that the source of residue communicates directly with conditioning chamber, without the need for an intermediate conveying means. In this arrangement the residue passes directly from the source of residue into the adjoining (and integral) residue
10 conditioning chamber. In such a "contiguous" embodiment, the residue may be conveyed actively or passively (i.e., by gravity) from the residue source into the chamber.

In directly connected (or contiguous) embodiments where the residue is actively conveyed into the residue conditioning chamber, the residue input means is typically
15 located within the residue source. Such conveyance means may include screw conveyors, rotating arms, rotating chains, traveling grates and pusher rams.

The residue input means optionally include a control mechanism such that the input rate of the residue can be controlled to ensure optimal melting and homogenization of the residue material.

20 In one embodiment of the invention, solid process additives are added to the residue to be conditioned in order to adjust the composition of the slag product. These solid process additives may be added to the residue prior to introduction into the residue conditioning chamber, or they may be added directly to the residue conditioning chamber through a dedicated additive inlet. In one embodiment, the solid process
25 additive is added directly to the conditioning chamber via a dedicated additive feed inlet. In one embodiment, the additive is introduced to the residue prior to introduction to the conditioning chamber.

Where the residue conditioning system is associated with a carbonaceous feedstock gasification process, it is also possible to add the solid process additive to the

feedstock prior to gasification.

The residue conditioning system employs one or more plasma heating sources to convert the residue material produced by the upstream processes. The plasma heat sources may be movable, fixed or a combination thereof.

- 5 The plasma heat sources may comprise a variety of commercially available plasma torches develop suitably high flame temperatures for sustained periods at the point of application. In general, such plasma torches are available in sizes from about 100 kW to over 6 MW in output power. The plasma torch can employ one or a combination of suitable working gases. Examples of suitable working gases include, but are not
- 10 limited to, argon, helium, neon, hydrogen, methane, ammonia, carbon monoxide, oxygen, nitrogen, and carbon dioxide. In one embodiment of the present invention, the plasma heating means is continuously operating so as to produce a temperature in excess of about 900°C to about 1800°C as required for converting the residue material to the inert slag product.
- 15 In this respect, a number of alternative plasma technologies are suitable for use in the present system. For example, it is understood that transferred arc and non-transferred arc torches (both AC and DC), using appropriately selected electrode materials, may be employed. It is also understood that inductively coupled plasma torches (ICP) may also be employed. Selection of an appropriate plasma heat source is within the
- 20 ordinary skills of a worker in the art.

The use of transferred arc torches instead of non-transferred arc torches may improve the efficiency of the residue conditioning process due to their higher electrical to thermal efficiency, as well as the higher heat transfer efficiency between the hot plasma gases and the material being melted because the arc passes directly through

25 the melt. Where transferred arc torches are used, it is necessary to ensure that the conditioning chamber is electrically isolated since the chamber outer shell will be connected to the negative of the power supply. In one embodiment, the plasma heat source is a DC non-transferred arc torch.

In one embodiment of the present invention, the residue conditioning system

comprises one or more plasma heat sources positioned to optimize the conversion of the residue material to inert slag. The position of the plasma heat source(s) is selected according to the design of the residue conditioning chamber. For example, where a single plasma heat source is employed, the plasma heat source may be mounted in the top of the chamber and disposed in a position relative to the slag pool collecting at the bottom of the chamber to ensure sufficient heat exposure to melt the residue material and force the slag to flow. In one embodiment, the plasma heat source is a plasma torch vertically mounted in the top of the chamber.

All plasma heat sources are controllable for power and optionally (where movable heat sources are used) position. In one embodiment, the plasma heat rate is varied to accommodate varying residue input rate. The plasma heat rate can also be varied to accommodate varying residue melting temperature properties.

The plasma heat sources may be operated on a continuous or non-continuous basis at the discretion of the operator to accommodate varying residue input rate and melting temperature properties.

The residue being conditioned will typically contain a proportion of unreacted or unconverted carbon. Accordingly, air and/or steam may optionally be added to the residue conditioning chamber to ensure complete conversion of the carbon, as required by the varying carbon content of the residue material being conditioned. Since the carbon reacts with oxygen in an exothermic reaction, air inputs may also be used and adjusted to maintain optimum processing temperatures while minimizing the cost of plasma heat required in the conditioning process. As such, the amount of air injection is maintained to ensure the maximum conversion of carbon to carbon monoxide with the minimum plasma heat requirement to carry out the process.

If the temperature within the conditioning chamber is too high and/or the gaseous product of the conditioning process has a high carbon particle (soot) content, steam can be injected to control the temperature and/or convert the solid carbon to carbon monoxide and hydrogen.

The chamber, therefore, can include one or more air input ports for air injection, and

optionally one or more steam input ports for steam injection. The air and steam input ports are strategically located in and around the residue conditioning chamber to ensure full coverage of the air and steam inputs into the chamber.

5 The system of the present invention comprises a slag output in association with the conditioning chamber. The slag output includes an outlet on the residue conditioning chamber through which molten slag is exhausted. The outlet is typically located at or near the bottom of the chamber to facilitate the gravity flow of the molten slag pool out of the chamber. The slag output also includes a slag cooling subsystem to facilitate the cooling of the molten slag to its solid form.

10 The molten slag can be output from the chamber intermittently, e.g., through a batch pour or periodic exhausting at the end of a processing period. The molten slag can also be output in a continuous manner throughout the full duration of processing. The molten slag from either method can be cooled and collected in a variety of ways that will be apparent to a person skilled in the art, to form a dense, non-leachable, solid slag.
15 The slag output means may further be adapted to minimize heating requirements and to avoid contact of the product gas with external air by keeping the residue conditioning chamber sealed. According to the present invention, as the residue is conditioned by the plasma heat, the resulting molten slag accumulates in a reservoir. As discussed previously, in one embodiment of the invention, the molten slag is
20 extracted in a continuous manner, i.e., as the volume of molten slag in the reservoir increases, it passes over a weir and exits the conditioning chamber through an outlet.

In one embodiment of the residue conditioning chamber, the molten slag is exhausted through an S-trap outlet. In this embodiment, the slag output means may optionally comprise a burner or other heating means located at or near the outlet in order to
25 maintain the temperature of the molten slag at the outlet high enough to ensure that the outlet remains open through the complete slag extraction period. This embodiment also ensures that the level of the slag pool does not go below a predetermined level, thereby keeping the melt environment sealed to avoid gaseous contact with the external environment.

30 Continuous pour embodiments are particularly suitable for systems that are designed

to operate on a continuous basis, for example, where the residue conditioning system is provided in association with a continuous feedstock gasification facility.

In one embodiment, the molten slag accumulates in a reservoir until the reservoir is periodically emptied. In such an embodiment, the reservoir may be emptied by a tipping mechanism, or through an outlet in the reservoir as may be provided to controllably exhaust the molten slag.

In one embodiment a mechanism is provided to controllably exhaust the molten slag from a reservoir by a tipping mechanism. In this embodiment, the residue conditioning chamber has a tiltable crucible comprising reservoir, a spout, a counterweight and a lever arm provided as a mechanism for tilting the crucible.

In different embodiments, there are different design options that may be provided for controlled exhaust of the molten slag through an appropriately adapted outlet in the reservoir or chamber. The molten slag exhaust may be controlled to ensure that the level of the molten slag is not allowed to reach below the top of the outlet, so that gases from the external atmosphere do not enter the interior melt region.

In one embodiment, a reservoir or chamber has an outlet in a side wall near the bottom of the reservoir/chamber. The outlet is surrounded by an induction heater enclosed in the refractory that can control the temperature of the refractory in the region surrounding the outlet. Increasing the temperature sufficiently to maintain the slag in the molten state allows the slag to flow through the outlet. When the level of the slag pool reaches the desired level, the induction heater is turned off, and the slag is allowed to solidify in the outlet.

In one embodiment, the outlet is "plugged" with a soft refractory paste. An oxygen lance is provided in a position suitable to "burn" a hole into the soft refractory paste allowing molten slag to pour out. The flow is stopped by placing refractory or other suitable material back into the outlet. In one embodiment the outlet is covered by a movable water cooled plug. The plug is movable from a closed position to an open position, thereby exposing the outlet to allow the molten slag to exhaust through the outlet. The molten material should not adhere to the smooth surface of the plug

because of the water cooling effect. In one embodiment the outlet is plugged by a wedge-type device. The "wedge" is pushed in and out of outlet as required to control the exhaust of the molten slag.

In one embodiment, the slag output means also comprises a slag cooling subsystem for cooling the molten slag to provide a solid slag product. In one embodiment, the molten slag is poured into a quench water bath. The water bath provides an efficient system for cooling the slag and causing it to shatter into granules suitable for commercial uses, such as for the manufacture of concrete making or for road building. The water bath may also provide a seal to the environment in the form of a water seal duct that extends from the base of the slag chamber down into the water bath, thereby providing a barrier preventing outside gases from entering the residue conditioning chamber.

In one embodiment of the slag cooling subsystem, the molten slag is dropped into a thick walled steel catch container for cooling. In one embodiment, the molten slag is received in an environmentally sealed bed of silica sand or into moulds to provide solid slag suitable for small scale processing or for testing certain parameters whenever such testing is performed. The small moulds can be control cooled in a preheated oven. In one embodiment of the slag cooling subsystem, the molten slag is converted to a commercial product such as glass wool.

Where the residue conditioning system is provided to condition the residue remaining after the gasification of a material that may contains a significant amount of metals, such as municipal solid waste, it is likely that a proportion of the metal will be passed through the gasification system and into the residue conditioning chamber. These metals will not necessarily melt at the normal slag vitrification temperature, therefore, the slag reservoir could become clogged with metal over time as it is of higher density than the molten slag. In order to remove accumulated metals, the chamber temperature may be periodically raised to melt any metals and the molten metals may be tapped off from the bottom of the reservoir through a metal tap port as required.

Where the residue being conditioned contains a proportion of unreacted carbon, a product of the residue conditioning process will be a gas having a potentially useful

heating value, and may be appropriate for uses in downstream applications. This gas is referred to herein as "residue gas". Gases that are produced in the residue conditioning chamber during conversion of the residue material to inert slag exit the chamber via a gas outlet. The residue gas may then be further treated in gas cooling and/or pollution abatement systems known in the art.

Accordingly, in one embodiment of the invention, the residue gas is directed to a system provided for cooling and cleaning the gas, which is referred to as a "solid residue gas conditioning system". The solid residue gas conditioning system is described in more detail above in the "Gas Conditioning System" section above. After the residue gas has been treated, it is ready for use in downstream applications.

A Gas Homogenization System

The invention further comprises a gas homogenization system for homogenizing the chemical composition of an input gas and adjusting other characteristics such as flow rate, pressure, and temperature of the gas, thereby creating a regulated gas to meet downstream requirements. This system enables a continual and steady stream of gas of defined characteristics to be delivered to downstream applications, for example, a gas turbine, engine or other suitable applications.

In particular, the gas homogenization system provides a gas homogenization chamber having dimensions that are designed to accommodate a gas residence time sufficient to attain a homogeneous gas of a consistent output composition. Other elements of the gas homogenization system are designed and configured such that the regulated gas meets the performance requirements of a downstream application. The system may also comprise a feedback control system to optimize the energetics and output of the process.

The composition of the gas, which will enter the homogenization system from the GCS, is determined by the gasification process and the GCS as described above. The gas leaving the GCS, may be within a defined range of a target composition, however, over time the gas may fluctuate in its characteristics due to variability in the gasification process such as feedstock composition and feed rate, airflow and

temperature fluctuations. Despite various controls to control the composition of the final conditioned gas as described above, fluctuations in both the pressure and temperature of the gas will typically occur over time. In the case of pressure, fluctuations may occur on a per second basis; and with temperature, on a per minute basis. In one embodiment of the invention, the pressure variance limit is selected to be less than about 0.145 psi/second.

As noted above, the regulated gas exiting the gas homogenization system has substantially stabilized characteristics that meet the specifications of a downstream application. Typically, machine manufacturers will provide the requirements and tolerances allowed by specific machinery; such gas parameters for a gas engine or gas turbine would be known to a person skilled in the art. In one embodiment of the invention, a gas engine may require a regulated gas composition LHV to have a maximum of about 1% change in about 30 seconds. In one embodiment of the invention, gas engines can accept gas with HHV as low as about 50BTU/scf, so long as it contains a minimum of about 12% Hydrogen. In one embodiment of the invention, the regulated gas requires the Wobbe Index (defined as $T(\text{degrees R})/\text{sq.rt}(\text{specific gravity})$) to be +/- 4% of the design value for use with turbine engines. In addition, a turbine engine may also require a minimum LHV of about 300 Btu/scf and a minimum pressure of about 475 psig. In one embodiment of the invention, the engine will require a regulated gas temperature greater than or equal to the dew point temperature plus about 20°F where relative humidity is at a maximum of about 80%.

A gas homogenization system configured in accordance with one embodiment of the invention for the production of a regulated gas comprises: a chiller; a gas/liquid separator; a homogenization chamber, to which a relief valve and a pressure control valve are connected; a gas conditioning skid, comprising a gas/liquid separator and a heater; a filter; and a pressure regulating valve. The regulated gas may subsequently be directed through a suitable conduit to an engine.

Figures 86 and 87 depict various embodiments of the gas homogenization system configured for the production of a regulated gas. In Figure 86, for example, the gas homogenization system 1 comprises: a chiller 10; a gas/liquid separator 12; a

homogenization chamber **14**, to which a relief valve **16** and a pressure control valve **18** are connected; a gas conditioning skid **20**, comprising a gas/liquid separator **22** and a heater **24**; a filter **26**; and a pressure regulating valve **28**. The regulated gas may subsequently be directed through a suitable conduit to an engine **30**.

5 A substantially clean gas enters the homogenization system from the GCS at the chiller, where the temperature of the gas is appropriately adjusted. The gas is then delivered to the separator, by suitable conduit means, where the humidity of the gas is regulated. Following this, the gas enters the homogenization chamber, by way of gas inlet conduit means. Once in the homogenization chamber, the gas is mixed or
10 blended, resulting in a gas having a stabilized composition. The gas flow rate and pressure of the mixed or blended gas are further regulated upon exit of the mixed or blended gas from the homogenization chamber. Suitable conduit means then carry the mixed or blended gas to the gas conditioning skid, where regulation of the temperature and humidity of the mixed or blended gas is undertaken. The mixed or
15 blended gas, carried by suitable conduit means, is then filtered and regulated for pressure. The resulting regulated gas, now meeting the desired requirements for a downstream application, may be directed through suitable conduit means to the engine.

The homogenization system can be configured to direct regulated gas to one
20 downstream application or to multiple downstream applications in parallel. Figures 88, 89 and 90 depict configurations of the homogenization in various embodiments of the invention in which the homogenization system delivers regulated gas to a plurality of downstream applications.

Typically, gas will be conveyed from a GCS to the homogenization chamber as it is
25 generated. To ensure a uniform input gas flow rate, a draft induction device may also be employed. Similarly, to ensure that factors such as gas composition, flow rate, temperature and pressure of the input gas stream are compliant with the desired range of target characteristics, the input gas may be monitored by a monitoring system, as would be known to the skilled technician, prior to homogenization. Given the
30 outcome of the analysis of these factors, gas may then be directed to the

homogenization chamber.

The gas homogenization chamber receives conditioned gas from a GCS and encourages mixing or blending of the gas to attenuate fluctuations in the chemical composition of the gas within the homogenization chamber. Fluctuations in other gas
5 characteristics, such as pressure, temperature and flow rate, can also be reduced during mixing of the gas.

In one embodiment of the invention, the dimensions of the chamber are designed according to the performance characteristics of an upstream gasification system and the requirements of a downstream application, with the objective of substantially
10 minimizing the size of the chamber as much as possible. The gas homogenization chamber is designed to receive gas from a gasification process and retain the gas for a certain residence time to allow for sufficient mixing or blending of the gas in order to dampen disturbances and/or fluctuations and achieve a volume of gas with a substantially consistent chemical composition.

15 In one embodiment of the invention, the dimensions of a homogenization chamber can be calculated based on the total system response time which includes the process residence time between the converter and the analyzer sample probe, plus the total system response time for the sample system, analysis and transmission time to a plant control system (PCS).

20 The residence time is the average amount of time that gas remains in the homogenization chamber before being directed to a downstream application. The residence time is substantially proportional to the response time of the related gasification system to dampen the effect of the rate of change of the fluctuations in the gasification reaction in order to achieve gas characteristics that fall within
25 accepted tolerance values. For example, the gas composition is retained in the homogenization chamber long enough to determine whether it falls within the gas composition tolerance allowed for the particular downstream application as well as to make any adjustments to the gasification process to adjust for the deviance. In this way, the system can affect the rate of change in gas characteristics so that upstream
30 controls with fast process lags will be able to meet the specifications of a downstream

application. In one embodiment, the residence time is determined by about 1% maximum change in the lower heating value (LHV) per 30 seconds and a maximum change in pressure of about 0.145psi/second.

5 Residence time of the gas in the homogenization chamber is determined by the amount of variance in the gas characteristics. That is, the smaller the variance in gas characteristics, the shorter the residence time required in the homogenization chamber to correct for this variance.

Depending on the different embodiments of the present invention, the residence time can vary from less than about one minute to about 20 minutes. In one embodiment, the residence time ranges from about 15 to about 20 minutes. In one embodiment the
10 residence time ranges from about 10 to about 15 minutes. In one embodiment, the residence time ranges from about 5 to about 10 minutes. In one embodiment of the invention, the residence time ranges from about 3 to about 5 minutes. In one embodiment of the invention, the residence time ranges from about 1 to about 3
15 minutes. In one embodiment of the invention, the residence time ranges from amounts less than about one minute.

In one embodiment, the residence time is about 20 minutes. In one embodiment the residence time is about 18 minutes. In one embodiment, the residence time is about 15 minutes. In one embodiment, the residence time is about 13 minutes. In one
20 embodiment, the residence time is about 10 minutes. In one embodiment, the residence time is about 8 minutes. In one embodiment, the residence time is about 6 minutes. In one embodiment, the residence time is about 4 minutes. In one embodiment, the residence time is about 3 minutes. In one embodiment, the residence time is about 2 minutes. In one embodiment, the residence time is about 1 minute. In
25 one embodiment, the residence time is less than about 1 minute.

The volume capacity of the homogenization chamber is related to the residence time required for a specific downstream application and fluctuations that are expected because of heterogeneity of the feedstock. In one embodiment of the invention, the variable gas volume ranges from about 0-290 m³. In one embodiment, the variable
30 gas volume ranges from about 0-1760 m³. In one embodiment, the variable gas

volume ranges from about 0-2050 m³. In one embodiment, the variable gas volume ranges from about 0-30,000 m³. In one embodiment of the invention, the homogenization chamber has a maximum capacity of about 290 m³. In one embodiment, the homogenization chamber has a maximum capacity of about 1800 m³. In one embodiment of the invention, the homogenization chamber has a maximum capacity of about 2300 m³. In one embodiment of the invention, the homogenization chamber has a maximum capacity of about 30,000 m³.

The downstream application selected can directly impact the operating pressure of the homogenization chamber. For example, a gas engine will require a gas pressure of about 1.2-3.0 psig while a gas turbine will require a gas pressure of about 250-600 psig. The mechanical design pressure of the homogenization chamber is correspondingly calculated to accommodate the required operating pressure for a selected application. In one embodiment, the homogenization chamber has a mechanical design pressure suitable for maintaining the gas pressure for use in a gas engine. In one embodiment, the homogenization chamber has a mechanical design pressure suitable for maintaining the gas pressure for use in a gas turbine. In one embodiment the homogenization chamber has a mechanical design pressure of about 5.0 psig. In one embodiment of the invention, the homogenization chamber has a mechanical design pressure of about 10.0 psig. In one embodiment of the invention, the homogenization chamber has a mechanical design pressure of about 25.0 psig. In one embodiment of the invention, the homogenization chamber has a mechanical design pressure in the range of about 100 to about 600 psig.

One skilled in the art can also appreciate that to meet the requirements of downstream applications, such as a gas engine, a lower pressure system would be more advantageous than for other applications, such as a gas turbine, where a higher pressure gas stream would be more appropriate.

The homogenization chamber has a mechanical design temperature tolerance that will accommodate the gas being contained and the specifications of the downstream application. Typically, these temperatures will range from about -40°C to about 300°C. In one embodiment of the invention, the mechanical design temperature of the

chamber ranges from about -37°C to about 93°C .

A person skilled in the art will appreciate that the homogenization chamber can be formed in a variety of shapes provided functional requirements of the homogenization system, discussed above, are satisfied. One skilled in the art will also appreciate that
5 the shape and size of the chamber will depend on the gas throughput and residence time required for a specific design, as discussed above. Cost and maintenance are additional considerations in selecting a type of homogenization chamber.

Different types of homogenization chambers include, but are not limited to gasometers, gas holders, variable volume and fixed volume tanks, such as standard
10 fuel tanks and surge tanks. Thus, in accordance with one embodiment of the invention, the homogenization chamber is a standard fuel tank. In accordance with one embodiment of the invention, the homogenization chamber is a fixed volume tank such as a surge tank. In accordance with one embodiment of the invention, the homogenization chamber is a variable volume tank. In accordance with one
15 embodiment of the invention, the homogenization chamber is a gasometer or gas holder.

Figure 6 depict a homogenization chamber in one embodiment of the invention which is a fixed-volume tank, a gas inlet, a gas outlet, a relief gas outlet, a drain, one or more pressure/temperature nozzles and one or more level switch nozzles. The drain of the
20 tank is a feature of the conical bottom drainage system.

Figures 92 to 94 depict various embodiments of the homogenization chamber. In the embodiment depicted in Figure 92, the gas inlet is connected to a compressor, which functions to compress the gas prior to storage in the pressure vessel. In the embodiment depicted in Figure 93, the gas holding chamber is defined by an inner
25 membrane and an outer membrane. When gas exits the holding chamber, a blower, associated with the outer membrane, provides inflation to the region between the membranes. When gas is added to the holding chamber, a regulator, adjusts the pressure of the inflated region. In the embodiment depicted in Figure 94, the homogenization chamber is an absorption type gas holder comprising a constant
30 volume tank. A cross sectional view of the tank, which acts to absorb gas molecules,

is also shown.

Typically the homogenization chamber will be located above ground. However, it is contemplated that for aesthetic reasons, or in those jurisdictions which do not allow above ground containment of fuel, a homogenization chamber may be located
5 underground. Thus, in one embodiment, the homogenization chamber is underground. In one embodiment, the homogenization chamber is above ground. In one embodiment of the invention, the homogenization chamber is positioned such that a portion thereof is underground.

It is further contemplated that a homogenization chamber can be configured as a
10 homogenization system with more than one chamber or may be configured as one or more single homogenization chambers fluidly interconnected in parallel. Figure 95 depicts a configuration of homogenization chambers in one embodiment of the invention in which the chambers are interconnected in parallel.

A worker skilled in the art will readily appreciate that each of the fixed-volume,
15 homogenization chamber could be independently selected as one of the above-mentioned embodiments, for example, a pressure vessel, a double-membrane gas holder, a multiple-absorption type gas holder etc., provided there is a single gas inlet and a single gas outlet for the entire system. A worker skilled in the art would be able to ascertain the suitability of such designs for a given purpose.

20 It is known that gas from a gasification system can be highly toxic and flammable, and in most cases will be contained outdoors exposed to various environmental conditions such as extreme temperature changes, rain, sun, snow, wind and the like. Accordingly, a homogenization chamber will be manufactured from a suitably safe material. Non-limiting examples of materials include plastics (PVC), steel, composite
25 materials such as fiberglass reinforced plastic or steel, and steel alloys. Gas homogenization chambers comprising a combination of these materials are also herein contemplated, as are metals comprising suitable internal coatings. Coated metals, for example, can be useful for those chambers located underground due to the added environmental protection provided by such a coating. Coated metals may also be
30 required to satisfy governmental regulations.

One skilled in the art will appreciate that the gas characteristics of the input conditioned gas will be monitored during the gas homogenization process in order to determine whether the gas meets the downstream requirements and what adjustments are required in order to satisfy such requirements. Monitoring of the gas characteristics may occur within the homogenization chamber or prior to gas delivery to the homogenization chamber. The gas monitoring equipment may take the form of sensing elements, response elements, and controllers that can monitor and/or regulate the composition, flow rate, temperature and pressure of the gas.

In one embodiment of the invention, a feedback loop can be implemented in which the gas produced is analyzed in real-time and the operation of the gasification system is adjusted accordingly in order to make the necessary adjustments. In one embodiment, the homogenization chamber comprises one or more sensing elements for analyzing gas characteristics such as gas composition, temperature, flow rate and pressure, the configuration of each sensing element would be readily understood by a worker skilled in the art. For example, temperature can be measured using a thermocouple, or other temperature sensor format; pressure can be measured using an absolute pressure sensor, a gauge pressure sensor, vacuum pressure sensor, differential pressure sensor or other pressure sensor; flow rate can be measured using a flowmeter or other flow rate sensor; gas composition can be measured using a gas composition sensor based on acoustic properties, or other gas composition sensor as would be readily understood.

In one embodiment, a particular sensing element can be configured to measure multiple characteristics of the gas, wherein these types of sensors would be readily understood by a worker skilled in the art. In one embodiment, the homogenization chamber further includes one or more controllers configured to generate instructions for transmission to one or more response elements in order to regulate gas characteristics such as gas composition, temperature, flow rate and pressure.

In one embodiment of the invention, multiple sensing elements are positioned within the homogenization chamber in order to provide the capability of gas characteristic sampling at different locations within the chamber, thereby providing a means for

evaluation of homogeneity of the gas therein. Furthermore, one or more redundant sensing elements can be positioned within the homogenization chamber in order to ensure accurate operation of the one or more sensing elements, for example fault detection. In addition, in one embodiment, two or more sensing elements are used to
5 evaluate the same parameter and the measured value of the parameter is defined as a correlation between the readings determined by the two or more sensing elements.

Inlets comprising of one or more conduits is used to carry the gas from the gasification system to the homogenization chamber. As noted above, the upstream components of the system may optionally include one or more chillers, gas/liquid
10 separators, induced draft devices, gas monitoring systems, which may include temperature and pressure controllers, and control valves.

The gas is transferred from the GCS to the homogenization chamber of the invention by way of conduits that are designed to carry the gas at predetermined temperatures and pressures. One skilled in the art will appreciate that these conduits can take the
15 form of tubes, pipes, hoses, or the like.

As the gas is typically extracted from the GCS as it is generated, the gas flow is typically non-uniform. When the GCS is operating at less than atmospheric pressure, an induced draft device may convey the gas through the homogenization chamber. The induced draft device may be located anywhere preceding the homogenization
20 chamber. As would be understood in the field, suitable draft devices include, but are not limited to blower fans and vacuum pumps, or other suitable flow inducing devices.

As discussed above, the gas characteristics of the input gas may be monitored within the homogenization chamber or prior to input. In one embodiment, the monitoring
25 system may be part of the inlet means and may comprise automated equipment, such as one or more sensing elements, capable of providing a detailed assessment of the characteristics of the gas. For example, these characteristics can include continuous gas pressure and temperature monitoring plus continuous product gas flow rate and composition monitoring. A worker skilled in the art would readily understand the
30 sampling devices required to collect the above information regarding the gas. For

example, temperature can be measured using a thermocouple, or other temperature sensor format; pressure can be measured using an absolute pressure sensor, a gauge pressure sensor, vacuum pressure sensor, differential pressure sensor or other pressure sensor; flow rate can be measured using a flowmeter or other flow rate sensor; gas
5 composition can be measured using a gas composition sensor based on acoustic properties, or other gas composition sensor as would be readily understood.

In one embodiment, a particular sensing element can be configured to measure multiple characteristics of the gas, wherein these types of sensing elements would be readily understood by a worker skilled in the art.

10 Furthermore, in one embodiment, the monitoring system may include a means for the analysis of gas operatively connected with a feedback system as an integrated, on-line part of a process control system (PCS). The advantages provided by such an integrated on-line gas analysis are finer tuning capabilities of process control and enhanced control and homogenization capabilities for a variety of applications of the
15 gas.

In some embodiments of the invention, the gas inlet may further comprise a means for controlling the flow rate of the gas into the homogenization chamber, thus controlling the pressure of the gas in the chamber. This pressure control subsystem may comprise conventional valves or shut off systems known in the art. Several non-
20 limiting examples of pressure regulating devices are shown for example. The pressure control system responds to signals from the monitoring system and may control the flow rate of the gas as well as direct the gas appropriately. In one embodiment, the pressure control system includes a valve by which compliant and non-compliant gas can be directed to the homogenization chamber and combustor or
25 incinerator, respectively.

The regulated gas is transferred from the homogenization chamber to the downstream application by way of regulated gas conduits that are designed to carry the gas at predetermined temperatures and pressures. One skilled in the art will appreciate that these conduits can take the form of tubes, pipes, hoses, or the like.

As already discussed, a monitoring system is used to monitor/control the gas either prior to its entry into the homogenization chamber or during its residence in the homogenization chamber. Similarly, a monitoring system can be used to monitor the regulated gas before it is delivered for the downstream application. This can serve to
5 confirm and control the characteristics

The regulated gas outlet may further comprise a means for controlling the flow rate of the regulated gas from the homogenization chamber and to a downstream application. Working alternately to, or in conjunction with, the control system operative in the inlet, the pressure of the homogenization chamber may be controlled. The pressure
10 control in the outlet may comprise conventional valves or shut off systems known in the art. As discussed above, the flow and pressure control system responds to signals from the monitoring system employed to monitor the characteristics of the regulated gas as it exits the homogenization chamber. For example, the control system may comprise a pressure regulator valve that may be adjusted to control gas flow rate and
15 pressure by way of one or more response elements.

The regulated gas outlet may further comprise a means for heating the regulated gas as it exits the homogenization chamber. One skilled in the art would also appreciate when it is advantageous to incorporate a gas/liquid separator into the system of the invention.

20 Typically downstream applications such as gas engines and gas turbines are sensitive to trace elements that may enter the gas during any point of the gas production process. In this regard, the system may comprise one or more filters of an appropriate pore size to screen out these potentially interfering contaminants, while substantially limiting the impact that the filter has on gas flow rate. In one embodiment, a filter is
25 associated with the common header to the engines. In one embodiment, each engine gas train has its own filter. In one embodiment, both of the above-mentioned filtering approaches are used and may be configured as a two stage filtering process.

The regulated gas outlet device may further comprise pressure regulating valve device for controlling the pressure of the regulated gas prior to delivery to the downstream
30 application.

One skilled in the art will appreciate that a downstream application will dictate the specific gas characteristics required for the regulated gas. For example, the required gas pressure for the efficient operation of a gas engine will differ from those of a gas turbine. As discussed above, a gas turbine will require a relatively high gas pressure.

5 It is contemplated, therefore, that in those embodiments requiring a high gas pressure, a means for gas pressurization can be included in the homogenization system. Gas pressurization devices are well known in the art and may include a gas compressor of a variety of designs such as axial-flow compressor, reciprocating compressor, rotary screw compressor, centrifugal compressors. Other implementations include the

10 diagonal or mixed-flow compressor, the scroll compressor, or other gas pressurization devices, as would be known to a worker skilled in the art.

The pressure control system may additionally comprise one or more emergency exit ports with control valves. When gas flow cannot be reduced fast enough, for instance due to an up-stream operational malfunction, or a downstream failure of a gas engine,

15 an emergency control valve may be opened to release gas through an emergency exit port.

The emergency valve may be opened rapidly so that no significant change (about <1%) in gas pressure may occur. One skilled in the art will appreciate that the emergency exit port and corresponding valve may be located at any point in the

20 homogenization system of the invention. In one embodiment, the emergency port is located in the homogenization chamber. In one embodiment, the emergency port is located in the inlet means. In one embodiment, the emergency port is located in the outlet means.

Control System

25 The present invention provides a control system for the conversion of carbonaceous feedstock into a gas. In particular, the control system is designed to be configurable for use in controlling one or more processes implemented in, and/or by, a gasification system, or one or more components thereof, for the conversion of such feedstock into a gas, which may be used for one or more downstream applications. Gasification

30 processes controllable by different embodiments of the disclosed control system may

include in various combinations, a converter, a residue conditioner, a recuperator and/or heat exchanger system, one or more gas conditioners, a gas homogenization system and one or more downstream applications. Examples of these components and subsystems will be described in greater detail below, which depict exemplary
5 embodiments of gasification systems that may be controlled by the present control system.

In general, the gasification process controlled by the present invention generally takes place in a converter comprising one or more processing zones and one or more heat sources, which may include in some embodiments one or more plasma heat sources.
10 The converter also generally comprises one or more feedstock feed mechanisms and/or devices for inputting the feedstock, which may include a single feedstock (e.g. municipal solid waste (MSW), high carbon feedstock (HCF), coal, plastics, liquid wastes, hazardous wastes, etc.), distinct feedstocks, and/or a mixed feedstock into the converter, as well as means, for adding one or more process additives, such as steam,
15 oxidant, and/or carbon-rich material additives (the latter of which is optionally provided as a secondary feedstock). The gaseous products exit the converter via one or more output gas outlets. As will be described further below, the converter main comprise a single zone and/or chamber converter, or a multi-zone and/or chamber converter, for instance comprising a gassifier and reformer wherein gasification and
20 reformulation processes are implemented respectively.

In one embodiment, the application of plasma heat (e.g. via a plasma heat source such as a plasma torch or the like), in conjunction with the input of additives, such as steam and/or oxygen and/or carbon-rich material, helps in controlling the gas characteristics, such as flow, temperature, pressure and composition. The gasification system may
25 also utilize plasma heat to provide the high temperature heat required to gasify the feedstock, reformulate the off-gas produced thereby, and/or to melt the by-product ash and convert it to a glass-like product with commercial value.

The gasification process controlled by the present invention may further comprise means for means for managing and controlling processing of the solid by-product of
30 the gasification process. In particular, a gasification system may include a solid

residue conditioner for the conversion of the solid by-products, or residue, resulting from feedstock-to-energy conversion processes, into a vitrified, homogenous substance having low leachability. The solid by-products of the gasification process may take the form of char, ash, slag, or some combination thereof.

- 5 The gasification process controlled by the present invention may also comprise means for the recovery of heat from the hot product gas. Such heat recuperation may be implemented by various heat exchangers, such as gas-to-gas heat exchangers, whereby the hot product gas is used to heat air or other oxidant, such as oxygen or oxygen enriched air, which may then optionally be used to provide heat to the
- 10 gasification process. The recovered heat may also be used in industrial heating applications, for example. Optionally, one or more steam generator heat exchangers may be controlled as part of the gasification process to generate steam which can, for example, be used as an additive in the gasification and/or reformulation reaction(s), or to drive a steam turbine to generate electricity, for example.
- 15 The gasification process controlled by the present invention may further include a converter gas conditioner, or other such gas conditioning means, to condition the product gas produced by the gasification process for downstream use. For instance, the product gas may be directed to a converter gas conditioner, as can gas generated from processing of the residue in the residue converter discussed above, where it is
- 20 subjected to a particular sequence of processing steps to produce an output gas suitable for downstream use.

- The gasification process controlled by the present invention may further comprise a gas homogenization system for providing at least a first level homogenization of the product gas. For instance, by subjecting the product gas to a given residence time
- 25 within the homogenization system, various characteristics of the gas may be at least partially homogenized to reduce fluctuations of such characteristics. For example, the chemical composition of the product gas, as well as other characteristics such as flow, pressure, and/or temperature may be at least partially stabilized by the homogenization system to meet downstream requirements. In one embodiment, the
- 30 homogenization system of a gasification system provides a gas homogenization

chamber or the like having dimensions that are designed to accommodate a gas residence time sufficient to attain a gas of a sufficiently consistent output composition, pressure, temperature and/or flow. In general, characteristics of the homogenization system will be designed in accordance requirements of the downstream application(s), and, with respect to a capacity of the control system to attenuate fluctuations in product gas characteristics when the control system is designed with such intentions.

The control system operatively controls various local, regional and/or global processes related to the overall gasification process, and thereby adjusts various control parameters thereof adapted to affect these processes for a selected result. Various sensing elements and response elements are therefore distributed throughout the controlled system, or in relation to one or more components thereof, and used to acquire various process, reactant and/or product characteristics, compare these characteristics to suitable ranges of such characteristics conducive to achieving the desired result, and respond by implementing changes in one or more of the ongoing processes via one or more controllable process devices.

In one embodiment, the control system is used for controlling a gasification process for converting a carbonaceous feedstock into a gas suitable for use in a selected downstream application. In one example, the gasification process is controlled such that the product gas thereof may be used in a continuous manner and/or in real-time for immediate use. Accordingly, the control system may comprise, for example, one or more sensors for sensing one or more characteristics of the gas to be used in the downstream application. One or more computing platforms are communicatively linked to these sensing elements for accessing a characteristic value representative of the sensed characteristic(s), and configured to compare the characteristic value(s) with a predetermined range of such values defined to characterise the gas as suitable for the selected downstream application and compute one or more process control parameters conducive to maintaining the characteristic value with this predetermined range. A plurality of response elements may thus be operatively linked to one or more process devices operable to affect the process and thereby adjust the sensed characteristic of the gas, and communicatively linked to the computing platform(s) for accessing the

computed process control parameter(s) and operating the process device(s) in accordance therewith.

For example, the control system may be configured to control the conversion of a carbonaceous feedstock into a gas having one or more characteristics appropriate for downstream application(s), wherein the product gas is intended for use in the generation of electricity through combustion in a gas turbine or use in a fuel cell application. In such applications, it is desirable to obtain products which can be most effectively used as fuel in the respective energy generators. Alternatively, if the product gas is for use as a feedstock in further chemical processes, the composition will be that most useful for a particular synthetic application.

In one embodiment, the control system provides a feedback, feedforward and/or predictive control of process energetics to substantially maintain a reaction set point, thereby allowing the gasification processes to be carried out under optimum reaction conditions to produce a gas having a specified composition. For instance, the overall energetics of the conversion of feedstock to gas can be determined and achieved using an appropriately configured gasification system, wherein various process characteristics may be evaluated and controllably adjusted to influence the determination of the net overall energetics. Such characteristics may include, but are not limited to, the heating value and/or composition of the feedstock, the characteristics of the product gas (e.g. heating value, temperature, pressure, flow, composition, carbon content, etc.), the degree of variation allowed for such characteristics, and the cost of the inputs versus the value of the outputs. Continuous and/or real-time adjustments to various control parameters, which may include, but are not limited to, heat source power, additive feed rate(s) (e.g. oxygen, steam, etc.), feedstock feed rate(s) (e.g. one or more distinct and/or mixed feeds), gas and/or system pressure/flow regulators (e.g. blowers, relief and/or control valves, flares, etc.), and the like, can be executed in a manner whereby the net overall energetics are assessed and optimized according to design specifications.

Alternatively, or in addition thereto, the control system may be configured to monitor operation of the various components of a gasification system for assuring proper

operation, and optionally, for ensuring that the process(es) implemented thereby are within regulatory standards, when such standards apply.

In accordance with one embodiment, the control system may further be used in monitoring and controlling the total energetic impact of a gasification system. For instance, a gasification system for the conversion of a feedstock may be operated such that an energetic impact thereof is reduced, or again minimized, for example, by optimising one or more of the processes implemented thereby, or again by increasing the recuperation of waste heat generated by these processes. Alternatively, or in addition thereto, the control system may be configured to adjust a composition and/or other characteristics (e.g. temperature, pressure, flow, etc.) of a product gas generated via the controlled process(es) such that such characteristics are not only suitable for downstream use, but also substantially optimised for efficient and/or optimal use. For example, in an embodiment where the product gas is used for driving a gas engine of a given type for the production of electricity, the characteristics of the product gas may be adjusted such that these characteristics are best matched to optimal input characteristics for such engines.

In one embodiment, the control system may be configured to adjust a gasification process such that limitations or performance guidelines with regards to reactant and/or product residence times in various components, or with respect to various processes of the overall gasification process are met and/or optimised for. For instance, in an embodiment where municipal waste is used a feedstock, it may be considered important to adjust the gasification process of such waste to account for a maximum residence time of the waste in a pre-processing and/or storage phase. For example, the waste and/or other feedstock may be transported to the controlled system facility periodically or on an on-going basis, wherein processing of such feedstock must be controlled so to avoid and overstocking thereof (e.g. increased pre-processing residence time) while allowing for continuous operation (e.g. reduced or avoided down-times). In such an example, a processing rate of a given feedstock may be controlled so to substantially match a delivery rate of such feedstock, thereby allowing for a substantially constant residence time of the delivered feedstock in a storage or pre-processing stage (e.g. a number of hours, days, weeks, etc.).

Similarly, the residence time of the feedstock within the converter of a gasification system may be controlled to allow for sufficient processing, without depleting resources and thereby unduly reducing and/or limiting downstream processes and/or applications. For example, a given converter configuration may allow for a relatively
5 stable residence time for which suitable processing of the feedstock is achieved (e.g. minutes, hours, etc.). Downstream components of the converter may equally be controlled such that a residence time appropriate therefor is also substantially respected. For example, streaming gas through a heat-exchange system, conditioning system and/or homogenisation system may be best processed by such components for
10 a given gas flow and/or residence time. Similarly, variations in the gas flow and/or residence time may be addressed and compensated for by controlling various elements of such system components.

The person of skill in the art will understand that the gasification system and control system, in their various embodiments, may be used in a number of processing systems
15 having numerous independent and/or combined downstream applications. The control system is further capable, in various embodiments, of simultaneously controlling various aspects of a process in a continuous and/or real time manner.

Referring to Figures 98 and 99 the control system may comprise any type of control system architecture suitable for the application at hand. For example, the control
20 system may comprise a substantially centralized control system (e.g. see Figure 98), a distributed control system (e.g. see Figure 99), or a combination thereof. A centralized control system will generally comprise a central controller configured to communicate with various local and/or remote sensing devices and response elements configured to respectively sense various characteristics relevant to the controlled process, and
25 respond thereto via one or more controllable process devices adapted to directly or indirectly affect the controlled process. Using a centralized architecture, most computations are implemented centrally via a centralized processor or processors, such that most of the necessary hardware and/or software for implementing control of the process is located in a same location.

30 A distributed control system will generally comprise two or more distributed

controllers which may each communicate with respective sensing and response elements for monitoring local and/or regional characteristics, and respond thereto via local and/or regional process devices configured to affect a local process or sub-process. Communication may also take place between distributed controllers via
5 various network configurations, wherein a characteristics sensed via a first controller may be communicated to a second controller for response thereat, wherein such distal response may have an impact on the characteristic sensed at the first location. For example, a characteristic of a downstream product gas may be sensed by a downstream monitoring device, and adjusted by adjusting a control parameter
10 associated with the converter that is controlled by an upstream controller. In a distributed architecture, control hardware and/or software is also distributed between controllers, wherein a same but modularly configured control scheme may be implemented on each controller, or various cooperative modular control schemes may be implemented on respective controllers.

15 Alternatively, the control system may be subdivided into separate yet communicatively linked local, regional and/or global control subsystems. Such an architecture could allow a given process, or series of interrelated processes to take place and be controlled locally with minimal interaction with other local control subsystems. A global master control system could then communicate with each
20 respective local control subsystems to direct necessary adjustments to local processes for a global result.

The control system of the present invention may use any of the above architectures, or any other architecture commonly known in the art, which are considered to be within the general scope and nature of the present disclosure.

25 The control system comprises response elements for controlling the reaction conditions and to manage the chemistry and/or energetics of the conversion of the carbonaceous feedstock to the output gas. In addition, the control system can determine and maintain operating conditions to maintain ideal, optimal or not, gasification reaction conditions. The determination of ideal operating conditions
30 depends on the overall energetics of the process, including factors such as the

composition of the carbonaceous feedstock and the specified characteristics of the product gases. The composition of the feedstock may range from substantially homogeneous to completely inhomogeneous. When the composition of the feedstock varies, then certain control parameters may require continuous adjustment, via
5 response elements, to maintain the ideal operating conditions.

The control system can comprise a number of response elements, each of which can be designed to perform a dedicated task, for example, control of the flow rate of one of the additives, control of the position or power output of one of the one or more heat sources of the gasification system, or control of the withdrawal of by-product. The
10 control system can further comprise a processing system, as in processor(s). In one embodiment, the processing system can comprise a number of sub-processing systems.

The control system may be further enhanced by interactively performing various system and/or process calculations defined to reflect a current implementation of a
15 given gasification system. Such calculations may be derived from various system and/or process models, wherein simulation of process and/or system characteristics and control parameters may be used in a predictive and/or corrective manner to control the system or subsystem so modeled. US patent 6,817,388 provides an example of such a system model, which may be used in conjunction with the control
20 system to define various operational parameters, and predicted results based thereon, for use as starting points in implementing the various processes of system 10. In one embodiment, these and other such models are used occasionally or regularly to reevaluate and/or update various system operating ranges and/or parameters of the system 10 on an ongoing basis. In one embodiment, the NRC HYSYS simulation
25 platform is used and can consider as inputs, waste type, any combination of input chemical composition, thermo-chemical characteristics, moisture content, feed rate, process additive(s), etc. The model may also provide various optional interactive process optimizations to consider, for example, site and feedstock type specifics, maximization of energy recovery, minimization of emissions, minimization of capital
30 and costs, etc. Ultimately, based on the selected model options, the model may then provide, for example, various operational characteristics, achievable throughputs,

system design characteristics, product gas characteristics, emission levels, recoverable energy, recoverable byproducts and optimum low cost designs. Various exemplary representations are provided in US patent 6,817,388 which are readily applicable in the present context, as would be apparent to a person skilled in the art.

- 5 The processing system and any one of the sub-processing systems can comprise exclusively hardware or any combination of hardware and software. Any of the sub-processing systems can comprise any combination of none or more proportional (P), integral (I) or differential (D) controllers, for example, a P-controller, an I-controller, a PI-controller, a PD controller, a PID controller etc. It will be apparent to a person skilled in the art that the ideal choice of combinations of P, I, and D controllers depends on the dynamics and delay time of the part of the reaction process of the gasification system and the range of operating conditions that the combination is intended to control, and the dynamics and delay time of the combination controller.

15 Important aspects in the design of the combination controller can be short transient periods and little oscillation during transient times when adjusting a respective control variable or control parameter from an initial to a specified value. It will be apparent to a person skilled in the art that these combinations can be implemented in an analog hardwired form which can continuously monitor, via sensing elements, the value of a characteristic and compare it with a specified value to influence a respective control element to make an adequate adjustment, via response elements, to reduce the difference between the observed and the specified value.

25 It will further be apparent to a person skilled in the art that the combinations can be implemented in a mixed digital hardware software environment. Relevant effects of the additionally discretionary sampling, data acquisition, and digital processing are well known to a person skilled in the art. P, I, D combination control can be implemented in feed forward and feedback control schemes.

30 In corrective, or feedback, control the value of a control parameter or control variable, monitored via an appropriate sensing elements, is compared to a specified value or range. A control signal is determined based on the deviation between the two values and provided to a control element in order to reduce the deviation. For example, when

the output gas exceeds a predetermined H₂:CO ratio, a feedback control means can determine an appropriate adjustment to one of the input variables, such as increasing the amount of additive oxygen to return the H₂:CO ratio to the specified value. The delay time to affect a change to a control parameter or control variable via an appropriate response elements is sometime called loop time. The loop time, for example, to adjust the power of the plasma heat source(s), the pressure in the system, the carbon-rich additive input rate, or the oxygen or steam flow rate, can amount to about 30 to about 60 seconds, for example.

In one embodiment, the product gas composition is the specified value used for comparison in the feedback control scheme described above, whereby fixed values (or ranges of values) of the amount of CO and H₂ in the product gas are specified. In another embodiment, the specified value is a fixed value (or range of values) for the product gas heating value (e.g. low heating value (LHV)).

Feedback control can be used for any number of control variables and control parameters which require direct monitoring or where a model prediction is satisfactory. There are a number of control variables and control parameters of the gasification system that lend themselves towards use in a feedback control scheme. Feedback schemes can be effectively implemented in aspects of the control system for system and/or process characteristics which can be directly or indirectly sensed, and/or derived from sensed values, and controlled via responsive action using adjusted control parameters for operating one or more process devices adapted to affect these characteristics.

It will be appreciated that a conventional feedback or responsive control system may further be adapted to comprise an adaptive and/or predictive component, wherein response to a given condition may be tailored in accordance with modeled and/or previously monitored reactions to provide a reactive response to a sensed characteristic while limiting potential overshoots in compensatory action. For instance, acquired and/or historical data provided for a given system configuration may be used cooperatively to adjust a response to a system and/or process characteristic being sensed to be within a given range from an optimal value for which

previous responses have been monitored and adjusted to provide a desired result. Such adaptive and/or predictive control schemes are well known in the art, and as such, are not considered to depart from the general scope and nature of the present disclosure.

- 5 Feed forward control processes input parameters to influence, without monitoring, control variables and control parameters. The gasification system can use feed forward control for a number of control parameter such as the amount of power which is supplied to one of the one or more plasma heat sources, for example. The power output of the arcs of the plasma heat sources can be controlled in a variety of different
- 10 ways, for example, by pulse modulating the electrical current which is supplied to the torch to maintain the arc, varying the distance between the electrodes, limiting the torch current, or affecting the composition, orientation or position of the plasma.

The rate of supply of additives that can be provided to the converter in a gaseous or liquid modification or in a pulverized form or which can be sprayed or otherwise

15 injected via nozzles, for example can be controlled with certain control elements in a feed forward way. Effective control of an additive's temperature or pressure, however, may require monitoring and closed loop feedback control.

Fuzzy logic control as well as other types of control can equally be used in feed forward and feedback control schemes. These types of control can substantially

20 deviate from classical P, I, D combination control in the ways the plasma reformulating reaction dynamics are modeled and simulated to predict how to change input variables or input parameters to affect a specified outcome. Fuzzy logic control usually only requires a vague or empirical description of the reaction dynamics (in general the system dynamics) or the operating conditions of the system. Aspects and

25 implementation considerations of fuzzy logic and other types of control are well known to a person skilled in the art.

Modularity Of The System

One embodiment of this design is a modular plant design. Modulated plants are facilities where each function block is pre-built components. This allows for the

components to be built in a factory setting and then sent out to the facility site. These components (or modules) include all the equipment and controls to be functional and are tested before leaving the factory. Modules are often built with a steel frame and generally incorporate a variety of possible sections, such as: Gasifier Block, Gas
5 Quality Control System, Power Block, etc. Once on-site, these modules would only need to be connected to other modules and the control system to be ready for plant's commissioning. This design allows for shorter construction time and economic savings due to reduced on-site construction costs.

There are different types of modular plants set-ups. Larger modular plants incorporate
10 a 'backbone' piping design where most of the piping is bundled together to allow for smaller footprint. Modules can also be placed in series or parallel in an operation standpoint. Here similar tasked equipment can share the load or successively provide processing to the product stream.

One possible application of modular design in this technology is it allows more
15 options in the gasification of multiple wastes. This technology can allow for multiple gasifiers to be used in a single high-capacity facility. This would allow the option of having each gasifier co-process wastes together or separately; the configuration can be optimized depending on the wastes.

If an expansion is required due to increasing loads, a modular design allows this
20 technology to replace or add modules to the plant to increase its capacity, rather than building a second plant. Modules and modular plants can be relocated to other sites where they can be quickly integrated into a new location.

Function Combination

It is possible to combine the functions of different gasification trains (series of
25 equipment) so that common functions can be carried out in vessels that take in gasses or solid material from more than one stream. The following diagrams demonstrate this concept as applied to MSW/Coal/Biomass Gasification.

In these embodiments there are two trains shown although this set-up of combined functions between trains can occur for any number of trains and for any feedstock per

train (even if one train has a combined feedstock). Once a stream has been combined one may still choose parallel handling equipment downstream; the parallel streams do not need to be of the same size even if handling the same gases.

Each Function Group Represents the Following Systems

- 5 1. Primary Gasification Chamber
2. Slag Chamber
3. Refining Chamber

None Combined, Figure 107

10 In this embodiment there are two separate systems that can have the gas streams mixed for downstream system; like the homogenization tank or engines.

GCS Combined, Figure

15 In this embodiment the gases from function vessels 2 & 3 from each train are fed together into a single GCS which has been sized appropriately for the gas flow.

Function 2 Combined, Figure 108

In this embodiment the trains differ only in function vessel 1, with all other functions being handled by the same combined train of equipment.

Function 3 Combined, Figure 109

20 In this embodiment gases from function vessels 1 go to a combined function vessel 3; which is sized appropriately.

Function 2 & 3 Combined, Figure 110

25 In this embodiment gases from function vessels 1 go to a combined 2 and material from function vessels 1 go to a combined function vessel 3; which are sized appropriately. Gases from combined function vessels 2 & 3 then travel to a combined GQCS.

A worker skilled in the art will readily understand that while in the above section we have mentioned the gasification system as comprising of the function blocks 1, 2 & 3 and the GCS, it can be further subdivided into other smaller function blocks. In this case, a worker skilled in the art will readily appreciate that the trains can be combined
5 in a larger family of schemes depending on where the combination of the trains is effected.

Combined Control

When there are combined streams control of the gas quality can be done by having one gasification train run on feed-back control (operation is corrected to maintain
10 syngas quality to downstream applications). The rest of the trains run on feed-forward control (run within specific bounds of gas quality). Only if the first feed-back controlled train cannot correct the syngas quality when running at optimal conditions it is switched to the optimum condition in a feed-forward control and another train (not optimal) is switched to feed-back control to improve the gas quality.

15 To gain a better understanding of the invention described herein, the following examples are set forth. It will be understood that these examples are intended to describe illustrative embodiments of the invention and are not intended to limit the scope of the invention in any way.

EXAMPLES

20 EXAMPLE I: A SYSTEM FOR THE CONVERSION OF MUNICIPAL SOLID WASTE

In this example, with reference to Figures 1 to 46, details of one embodiment of the invention, including various options, are provided. This example presents details for each subsystem of the invention and demonstrates how they work together to function
25 as an integrated system for the conversion of municipal solid waste (MSW) into electricity. One skilled in the art can appreciate, however, that each subsystem on its own can be considered a system. The subsystems comprising this embodiment are: a Municipal Solid Waste Handling System; a Plastics Handling System; a Horizontally Oriented Gasifier with Lateral Transfer Units System; a Gas Reformulating System; a

Heat Recycling System; a Gas Conditioning System; a Residue Conditioning System; a Gas Homogenization System and a Control System.

Figures 1 & 2 show the flow diagram and representation, for the gasification process in the different regions of the gasifier respectively. Figure 3 show a functional block
 5 diagram overview of the entire system **120** designed primarily for the conversion of MSW to syngas, with the associated use of reformulated, conditioned, and homogenized syngas in gas engines **9260** for the generation of electricity.

Municipal Solid Waste (MSW) Handling System

The initial MSW handling system **9200** is designed to take into account: (a) storage
 10 capability for supply of four days; (b) avoidance of long holding periods and excess decomposition of MSW; (c) prevention of debris being blown around; (d) control of odour; (e) access and turning space for garbage trucks to unload; (f) minimization of driving distance and amount of turning required by the loader **9218** transporting MSW from the MSW stockpile **9202** to the MSW shredding system **9220**; (g) avoidance of
 15 operational interference between loader **9218** and garbage trucks; (h) possibility of additional gasification streams to allow for plant expansion; (i) minimum intrusion by trucks into the facility, especially into hazardous areas; (j) safe operation with minimum personnel; (k) indication for the loader operator of the fill levels in the conveyor input hoppers **9221**; (l) shredding the as-received waste to a particle size
 20 suitable for processing; and (m) remote controllability of MSW flow rate into the processor and independent control of the plastics feed rate rate (described below).

The MSW handling system **9200** comprises a MSW storage building **9210**, a loader **9218**, a MSW shredding system **9220**, a magnetic separator **9230** and a feed conveyor **9240**. A separate system **9250** is also designed for storing, shredding, stockpiling and
 25 feeding a high carbon material (non-recyclable plastics in this example), the feed-rate of which is used as an additive in the gasification process. Figure 4 shows an overall layout of the entire system site. All storage and handling of MSW until it is fed into the gasification system **120** is confined in MSW storage building **9210** to contain debris and odor.

A first-in-first-out (FIFO) scheduling approach is used to minimize excessive decomposition of the MSW. FIFO is enabled by having access for trucks and loaders **9218** at both ends of the MSW storage building **9210**. MSW is unloaded from the trucks at one end of the building while the material is being transferred by the loader **9218** at the other end of the MSW storage building **9210**, thus also allowing the loader **9218** to operate safely and without interference by the trucks. When the loader **9218** has removed the material back to the approximate mid point **9203** of the MSW stockpile **9202** i.e. the 'old' material has all been used, the operations are then changed to the opposite ends of the MSW storage building **9210**.

To minimize the size of MSW storage building **9210**, space for maneuvering the garbage trucks is outside the MSW storage building **9210**. This also minimizes the size of door **9212** required as it needs only to allow a truck to reverse straight in, thus providing the best control of the escape of debris and odor. Only one door **9212** needs to be open at any time and then only when trucks are actually unloading. Receipt of MSW will normally take place during one period per day so that a door **9212** will only be open for about one hour per day.

Figure 5 shows a layout of the MSW storage building **9210**. The MSW storage building **9210** has a bunker wall **9214** to separate the MSW stockpile **9202** from the aisle **9216** where the loader **9218** must drive to access the input conveyor **9222** leading to the MSW shredding system **9220**. The bunker wall **9214** stops short of the ends of the MSW storage building **9210** to allow the loader **9218** to travel from the MSW stockpile **9202** to the input conveyor **9222** without leaving the MSW storage building **9210**. Thus, the doors **9212** at one end of the MSW storage building **9210** can be kept closed at all times while the other end is open only when trucks are unloading or when a loader (described below) for transferring material from the stockpile to the shredding system needs to exit to move plastic.

By having the MSW storage building **9210** located adjacent and parallel to the road **9204** and allowing for truck maneuvering at both ends of the MSW storage building **9210**, as shown in Figure 2, both space requirements and truck movements within the facility is reduced. The space layout design allows a truck to drive into the facility,

reverse into the MSW storage building **9210**, dump its load and drive directly back onto the road **9204**. At no times do they get near any of the process equipment or personnel. The two road entrance concept also avoids the need for an additional roadway within the facility to enable the trucks to access both ends of the MSW storage building **9210**.

A mechanized, bucket-based loader **9218** is used to transfer material from the stockpile to the shredding system. A skid steer loader design is used due to its compact size, maneuverability, ease of operation etc. A standard commercially available skid steer has adequate capacity to feed the MSW, clean up the stockpile floor after the trucks have unloaded and also handle the waste plastics system shredder and process feed.

The input conveyor **9222** transports the MSW from inside the MSW storage building **9210** upwards and drops it into the MSW shredding system **9220**. The feed hopper **9221** for this conveyor **9222** is located entirely inside the MSW storage building **9210** to prevent debris being blown around outdoors. The conveyor **9222** has a deep trough which, combined with the capacity of the feed hopper **9221** holds sufficient material for one hour of operation. The portion of the trough outside the MSW storage building **9210** is covered to control escape of debris and odor. The conveyor **9222** is controlled remotely by the process controller to match process demands. Mirrors are provided to allow the loader operator to see the level of MSW in the hopper **9221** from either side. Detectors provided in the trough alert the process controller that material is absent.

The MSW shredding system **9220** consists of an input hopper **9223**, a shredder **9224** and a pick conveyor and is followed by a magnetic pick-up conveyor. The shredder **9224** ensures that the as-received MSW is suitable for processing, by breaking any bags and cutting the larger pieces of waste into a size able to be processed. As the received MSW may include materials too large and hard for the shredder **9224** to handle, thus causing the shredder to jam, the shredder **9224** is equipped to automatically stop when a jam is sensed, automatically reverse to clear the jam and then restart. If a jam is still detected the shredder **9224** will shut-down and send a

warning signal to the controller.

The shredded waste is dropped onto a belt conveyor to be transported under a magnetic pick-up system and then to be dropped into the feed hopper **9239** of a screw conveyor **9240** which will feed the waste into the gasifier **2200**. To avoid inadvertent
5 feeding of excessive amounts of ferrous metals through the gasifier **2200**, a magnetic pick-up system **9230** is located above the pick conveyor, which attracts ferrous metals that may be present in the shredded waste. A non-magnetic belt runs across the direction of the pick conveyor, between the magnet and the waste so that ferrous metals attracted to the magnet get moved laterally away from the waste stream. The
10 ferrous metal is later removed from the magnet and dropped onto a pile for disposal.

The MSW feed system consists of a feed hopper **9239** and screw conveyor **9240** to transport shredded waste from the MSW shredder system **9220** to the gasification chamber **2202**. Shredded waste is dropped from the MSW shredder system **9220** into the feed hopper **9239**, which provides a buffer of material ready to feed into the
15 processor. The hopper has high and low level indicators which are used to control flow from the shredding system into the hopper. The conveyor **9240** is under the control of the process controller to match waste feed rate to meet process demands. The use of a screw conveyor **9240** with integral feed hopper **9239** also provides gas sealing for the processor. The feed hopper **9239** is connected to the MSW shredder
20 system with covers to control debris and odor. The screw conveyor **9240** has an additional entry to accept shredded plastic.

Plastics Handling System

The gasification system **120** provides for the addition of plastics as a process additive. The plastics are handled separately from the MSW, before being fed to the gasifier
25 **2200**.

The plastics handling system **9250** is designed to provide storage for as-received bales of plastic, shred it, place it into a stockpile **9254** and feed it under independent control into the processor. The plastics handling system **9250** comprises a plastics storage building **9255** storage facility, a shredder **9252** with input hopper **9251**, a take-away

conveyor **9253** and a stockpile **9254**, all located in a common building **9255** to control debris. A feed conveyor **9240** moves the shredded plastic into the processor.

5 The plastics storage building **9255** has the capacity to store two truck loads of plastic bales. It is closed on three sides and opens on one side, thus providing containment of the material with access for stacking and removing bales. The building also provides protection for the shredder **9252** and debris control and protection for the shredded material.

10 The shredder facilitates the plastic material meeting the process requirements. As-received plastic is loaded into the feed hopper **9251** of the shredder **9252** with a loader. The shredded material drops onto a take-away conveyor **9253** that transports it up and drops it into a stockpile **9254**.

15 The shredded plastic is picked up by a loader and dropped into the input hopper of the feed conveyor. As the conveyor is outdoors, the hopper incorporates an integral roof and upwardly extended walls to minimize escape of plastic during filling of the hopper. The conveyor trough is sealed to the trough of the MSW conveyor such that the plastic is introduced into the gasifier **2200** via the MSW conveyor to reduce openings into the gasifier **2200**. The conveyor is a screw conveyor with the hopper sealed to it to provide gas sealing when it contains material. Detectors are located in the hopper to indicate high and low levels and a mirror is provided for the skid steer operator to monitor fill level. Motion of this conveyor is under the control of the process controller.

Converter

25 The converter **1200** comprises a gasifier **2200** and a Gas Reformulating System (GRS) **3200**. The MSW and plastics are fed into the gasifier **2200** and the resulting gas is sent to the GRS **3200** where it is reformulated. Any resulting residue from the gasifier **2200** is sent to the residue conditioning system **4200**.

The gasifier **2200** is designed to take into account the requirements to: (a) provide a sealed, insulated space for primary processing of the waste; (b) introduce hot air and steam in a controlled and distributed manner throughout the gasifier **2200**; (c) enable

control of the height and movement of the waste pile through the gasifier **2200**; (d) provide instrumentation for controlling the gasification process; (e) transfer the gas to the GRS **3200**; (f) remove residue for further processing; and (g) provide access to the interior for inspection and maintenance.

- 5 Referring to Figures 6 to 9, the gasifier **2200** comprises a horizontally oriented refractory-lined gasification chamber **2202** having a feedstock input **2204**, inputs for hot air used for heating the gasification chamber, input for steam which serves as a process additive, a centrally-located gas outlet **2206** to which the GRS is directly coupled, a residue outlet **2208** and various service **2220** and access **2222** ports. The
- 10 gasification chamber **2202** is built as a steel weldment having a stepped floor with a plurality of floor steps **2212**, **2214**, **2216**. A system comprising carrier rams **2228**, **2230**, **2232** is used to facilitate the lateral movement of the material through the gasifier **2200**. Provision is also made for installation of instrumentation, such as thermocouples, material height detectors, pressure sensors and viewports.
- 15 The refractory lining of the gasification chamber **2202** protects it from high temperatures, corrosive gases and also minimizes the unnecessary loss of heat from the process. Referring to Figure 10, the refractory is a multilayer design with a high density chromia layer **2402** on the inside, a middle high density alumina layer **2404** and an outer very low density insulboard material **2406**. The refractory lines the metal
- 20 shell **2408** of the gasification chamber. The gasification chamber **2402** is further lined with a membrane to further protect it from the corrosive gases.

Each step **2212**, **2214**, **2216** of the stepped floor of gasification chamber **2402** has a perforated floor **2270** through which heated air is introduced. The air hole size is selected such that it creates a restriction and thus a pressure drop across each hole

25 sufficient to prevent waste materials from entering the holes. The holes are tapered outwards towards the upper face to preclude particles becoming stuck in a hole.

Referring to Figures 1 & 2, the conditions at the three individual steps are designed for different degrees of drying, volatilization and carbon conversion. The feedstock is introduced into the gasification chamber **2202**, onto the first stage via the feedstock

30 input **2204**. The targeted temperature range for this stage (as measured at the bottom

of the material pile) lies between 300 and 900°C. Stage II is designed to have a bottom temperature range between 400 and 950°C. Stage III is designed to have a temperature range between 600 and 1000°C.

The three steps **2212, 2214 & 2216** of the stepped-floor, that separate the gasification chamber **2202** into three stages of processing have their own independently controllable air feed mechanism. The independence is achieved by using separate airboxes **2272, 2274, and 2276** which form the perforated floor **2270** at each stage. The system of carrier rams **2228, 2230 & 2232** used for movement of material in the gasification chamber **2202** prevents access from below steps 1 & 2, **2212 & 2214**. Thus for these stages, the airboxes **2272 & 2274** are inserted from the side. The third stage airbox **2276** is however inserted from below, as shown in Figures 7 & 8.

The perforated top plate **2302** of the airboxes **2272, 2274, 2276**, in this design and referring to Figures 11 & 12, is a relatively thin sheet, with stiffening ribs or structural support members **2304** to prevent bending or buckling. To minimize stress on the flat front and bottom sheets of the boxes, perforated webs are attached between both sheets. To allow for thermal expansion in the boxes they are attached only at one edge and are free to expand at the other three edges.

As shown in Figure 11, the fixed edge of the Step 1 & 2 airboxes **2272 and 2274** is also the connection point of the input air piping **2278**. Thus, the connection flange **2280** will be at high temperature and must be sealed to the cool wall of the gasifier **2200**. A shroud is used, as shown in Figure 11, to achieve this without creating stress and without using a complex expansion joint. The hot air box **2272** and pipe **2278** are attached to one end of the shroud **2282** and the other end of the shroud **2282** is connected to the cool gasifier **2200**. As a temperature gradient will occur across the length of the shroud **2282**, there is little or no stress at either connection. The other advantage of this arrangement is that it positions the airbox rigidly in the required position without causing stress. The space between the shroud **2282** and the internal duct of the air box **2272** is filled with insulation to retain heat and to ensure the temperature gradient occurs across the shroud. When the airbox is in its operating location in the gasification chamber **2202**, the top plate opposite to the air connection

is extended beyond the airbox to rest on a shelf of refractory. This provides support to the airbox during operation and also acts as a seal to prevent material from falling below the airbox. It also allows free movement to allow for expansion of the airbox, as shown in Figure 13.

- 5 The downstream edge of the airbox is also dealt with in the same way. The upstream edge of the airbox is sealed with a resilient sheet sealing **2306** between the carrier ram and the top plate of the airbox **2302**.

The airbox is connected to the hot air supply piping using a horizontal flange. Therefore, only the flange has to be disconnected to remove an airbox.

- 10 The third stage airbox **2276** is inserted from below and also uses the shroud concept for sealing and locating the box to the gasifier **2200**.

Sealing against dust falling around the edges of the third stage airbox **2276** is achieved by having it set underneath a refractory ledge at the edge of the second stage **2214**. The sides can be sealed by flexible seals protruding from below recesses in the
15 sides of the refractory. These seals sit on the top face of the box, sealing between the walls and the box. The downstream edge of the air box is dust sealed to the side of an extractor trough using a flexible seal. The box is reinforced with stiffeners and perforated webs between the flat faces of the air boxes to permit the use of thin sheet metal for the boxes.

- 20 The hot air pipe connection is vertical to permit removal of the third stage airbox **2276** after disconnecting the pipe connection.

Referring to Figure 16, a series of a system of carrier rams **2228**, **2230**, **2232** is used to ensure that the MSW is moved laterally along the gasifier **2200** for appropriate processing in each of the three steps **2212**, **2214** & **2216**, and that the spent residue is
25 moved to the residue outlet **2208**. Each of the three stage floors is serviced by its own carrier ram. The carrier rams control both the height of the pile at each stage as well as the total residence time in the gasification chamber. Each carrier ram is capable of movement over the full or partial length of that step, at variable speeds. Thus, the stage can also be completely cleared if required.

Each carrier ram comprises an externally mounted guide portion, a carrier ram having optional guide portion engagement members, externally mounted drive system and an externally mounted control system. The carrier ram design comprises multiple fingers that allow the air-box air-hole pattern to be arranged such that operation of the carrier
5 rams does not interfere with the air passing through the air-holes.

In the multiple finger carrier ram design, the carrier ram is a structure in which fingers are attached to the body of the carrier ram, with individual fingers being of different widths depending on location. The gap between the fingers in the multiple finger carrier ram design is selected to avoid particles of reactant material from bridging.
10 The individual fingers are about 2 to about 3 inches wide, about 0.5 to about 1 inch thick with a gap between about 0.5 to about 2 inches wide.

The air box airhole pattern is arranged such that operation of the carrier rams does not interfere with the air passing through the airholes. For example, the pattern of the airholes can be such that when heated they are between the fingers (in the gaps) and
15 are in arrow pattern with an offset to each other. Alternatively, the airhole pattern can also be hybrid where some holes are not covered and others are covered, such that even distribution of air is maximized (ie. areas of floor with no air input at all are minimized). In choosing the pattern of the airholes, factors to consider include avoiding high velocity which would fluidize the bed, avoiding holes too close to
20 gasifier walls and ends so that channeling of air along refractory wall is avoided, and ensuring spacing between holes was no more than approximately the nominal feed particle size (2") to ensure acceptable kinetics.

A multi-finger carrier ram can have independent flexibility built-in so that the tip of each finger can more closely comply with any undulations in the air-box top face.
25 This compliance has been provided by attaching the fingers to the carrier ram main carriage using shoulder bolts, which do not tighten on the finger. This concept also permits easy replacement of a finger.

The end of the carrier ram finger is bent down to ensure that the tip contacts the top of the air in the event that the relative locations of the carrier ram and airbox changes
30 (for example, due to expansions). This features also lessens any detrimental effect on

the process due to air holes being covered by the carrier ram, the air will continue to flow through the gap between the carrier ram and the airbox.

Referring to Figure 13, the guide portion comprises a pair of generally horizontal, generally parallel elongated tracks **2240** mounted on a frame. Each of the tracks has a substantially L-shaped cross-section. The moving element comprises a carrier ram body **2326** and one or more elongated, substantially rectangular carrier ram fingers **2328** sized to slide through corresponding sealable opening in the gasification chamber wall.

The carrier ram fingers are constructed of material suitable for use at high temperature. Such materials are well-known to those skilled in the art and can include stainless steel, mild steel, or mild steel partially protected or fully protected with refractory. Optionally, specific individual carrier ram fingers or all carrier ram fingers can be partially or fully covered with refractory. Optionally, cooling can be provided within the carrier ram fingers by fluid (air or water) circulated inside the carrier ram fingers from outside the gasification chamber **2202**.

The carrier ram fingers are adapted to sealingly engage the gasification chamber wall to avoid uncontrolled air from entering the gasifier **2200**, which would interfere with the process or could create an explosive atmosphere. It is also necessary to avoid escape of hazardous toxic and flammable gas from the gasification chamber **2202**, and excessive escape of debris. Gas escape to atmosphere is prevented by containing the carrier ram mechanisms in a sealed box. This box has a nitrogen purge facility to prevent formation of an explosive gas mixture within the box. Debris sealing and limited gas sealing is provided for each finger of the carrier ram, using a flexible strip **2308** pressing against each surface of each finger of the carrier rams, as shown in Figure 14. Alternatively, the seal can be a packing gland seal providing gas and debris sealing for each finger.

The design of this sealing provides a good gas and debris seal for each carrier ram finger while tolerating vertical and lateral movements of the carrier ram. The seals at the sides of the fingers were the greatest challenge as they must be compliant to the vertical and lateral motions of the carrier ram while remaining in close contact with

the carrier ram and the seals of the upper and lower surfaces of the carrier ram. Leakage of debris can be monitored by means of windows in the sealed box and a dust removal facility is provided if the debris build-up becomes excessive. This removal can be accomplished without breaking the seal integrity of the carrier ram box, as shown in Figure 15.

Referring to Figure 15, the dust removal facility **2310** comprises a metal tray **2312** having a dust outlet **2314** equipped with a shutter **2316** and attachment site **2318** for a dust can **2332**, and a manual-operated, chain **2320** driven dust pusher **2322**. Dust is pushed to the dust outlet **2314** by the pusher **2322** when the operator handle **2324** is used.

Referring to Figure 16, power for moving the carrier rams **2228**, **2230** & **2232** is provided by electric motors which drive the carrier ram via a gearbox and roller chain system. Briefly, the power to propel the carrier rams along the tracks is supplied by an externally mounted electric variable speed motor **2256** which drives a motor output shaft **2258** selectably in the forward or reverse direction allowing for extension and retraction of the carrier ram at a controlled rate. Position sensor **2269** transmit the carrier ram position information to the control system. *Optionally, the motor may further comprise a gear box.* Two driver sprocket gears **2260** are mounted on the motor output shaft. The driver sprockets **2260** and corresponding driven sprockets **2262** mounted on an axle **2264** operatively mesh with chain members **2266** which are secured by brackets **2268** to the elongated rectangular block **2244**.

The motors are controlled by the overall system control means which can command start and stop position, speed of movement and frequency of movement. Each carrier ram can be controlled independently. Roller chain is used for this implementation as it provides high strength and tolerates a severe duty environment. The use of two chains per carrier ram provides a means of keeping the carrier rams angularly aligned without the need for precision guides. There is a tendency for the material on top of the carrier ram to be pulled back when the carrier ram is withdrawn. This can be dealt with by sequencing the carrier rams where the lowest carrier ram **2232** is extended first; the middle carrier ram **2230** is then extended which pushes material down onto

the lowest carrier ram **2232** filling the void created by that carrier rams movement; the lowest carrier ram **2232** is then retracted; the upper carrier ram **2228** is then extended filling the void at the back of the middle carrier ram **2230**; the middle carrier ram **2230** is then retracted; new material dropping from the feed port fills any void on the top carrier ram **2228** and the top carrier ram **2228** is retracted. All these motions are controlled automatically and independently by the system control means in response to system instrumentation data.

Referring to Figures 16 & 17, a staggered carrier ram sequence control strategy was implemented to facilitate movement of the carrier rams, as summarized below:

10 carrier ram C **2232** move fixed distance (with adjustable setpoint), creating a pocket at the start of step C **2216**.
 carrier ram B **2230** follows as soon as carrier ram C **2232** passes a trigger distance (trigger distance has adjustable setpoint) carrier ram B pushes/carries material to immediately fill the pocket at the start of step C **2230**. Feedback control is to stroke as far as necessary to block level switch C **2217**, or
 15 minimum setpoint distance if already blocked, or maximum setpoint distance if blocking does not occur. At the same time as carrier ram B **2230** is filling the pocket at the start of Step C **2216**, it is creating a pocket at the start of Step B **2230**.
 20 carrier ram A **2228** follows as soon as carrier ram B **2228** passes a trigger distance. carrier ram A **2228** pushes/carries material to immediately fill the pocket at the start of Step B **2214**. Feedback control is to stroke as far necessary to block level switch B **2215**, or minimum setpoint distance if already blocked, or maximum setpoint distance if blocking does not occur. At
 25 the same time as carrier ram A **2228** is filling the pocket at the start of Step B **2214**, it is also creating a pocket at the start of Step A **2212**. This typically triggers the feeder to run and fill the gasifier **2200** until level switch A **2213** is blocked again.

All carrier rams reverse to home position simultaneously.

30 Access is provided to the gasifier **2200** using a manhole at one end. During operation,

this is closed using a sealable refractory lined cover. Further access is also possible by removing the third stage air-box **2276**.

The residue (e.g. char or ash) remaining after gasification must be removed from the gasifier **2200** and passed to the residue conditioning system (RCS) **4220**. As the material is processed and moved in the gasifier **2200**, the heat generated within the pile can cause melting, which will result in agglomeration of the residue. Agglomerated residue has been shown to cause jamming in drop port type exits. In order to ensure that any agglomerations do not create jamming at the exit from the gasification chamber **2202**, a screw conveyor **2209** is used to extract the residue from the gasification chamber **2202**. The carrier ram motion pushes the residue into the extractor screw **2209** which pushes the residue out of the gasification chamber **2202** and feed it into a residue conveyor system. Rotation of the extractor screw **2209** breaks up agglomerations before the residue is fed into the conveyor system. This breaking up action is enhanced by having serrations on the edge of the extractor screw flights.

For implementing process control, various parameters have to be monitored within the gasification chamber **2202**. For example, the temperature needs to be monitored at different points along each stage and at various heights at each stage. This is achieved using thermocouples, which tend to need replacement during operation. In order to accomplish this without shutting down the process, each thermocouple is inserted into the gasification chamber **2202** via a sealed end tube which is then sealed to the vessel shell. This design allows the use of flexible wire thermocouples which are procured to be longer than the sealing tube so that the junction (the temperature sensing point) of the thermocouple is pressed against the end of the sealed tube to assure accurate and quick response to temperature change. The sealed tube is sealed to the gasification chamber **2202** and mechanically held in place by means of a compression gland, which can also accommodate protrusion adjustment into the gasification chamber **2202**. For temperature measurements within the MSW pile, the sealed tube can result in the pile being held back when its movement is needed. To avoid this problem the end of the sealed tube is fitted with a deflector which prevents the MSW pile from getting blocked by the thermocouple tube.

Referring to Figures 18 & 19, the off-gas produced in the gasifier **2200** then moves into the Gas Reformulating System (GRS) **3200**. The GRS **3200** is designed to satisfy a wide range of requirements: (a) provide necessary volume for the required gas reformulation residence time; (b) provide insulation for heat conservation and protection of the outer steel vessel; (c) provide inlets for addition of air and steam; (d) enable mixing of the gases; (e) process the gases at high temperature using plasma torches **3208**; (f) provide instrumentation for monitoring the gas composition for process control and for enhanced performance of the plasma torch **3208**; and (g) output the processed gas to a downstream heat exchanger **5200**.

10 The gas reformulating system (GRS) **3200** provides a sealed environment with mounting and connection features for process air, steam, plasma torches **3208** and torch handling mechanisms, instrumentation and exhaust of the output syngas. As shown in Figure 20, the GRS **3200** comprises a substantially vertically mounted refractory-lined cylindrical or pipe-like reformulating chamber **3202** having a single
15 conically shaped off-gas inlet **3204** to which the gasifier **2200** is connected to via a mounting flange **3214**. The GRS **3200** has a length-to-diameter ratio of about 3:1. The residence time within the GRS **3200** is 1.2 seconds. The GRS **3200** further comprises three levels of tangentially positioned air nozzles, two tangentially located plasma torches **3208**, six thermocouple ports, two burner ports, two pressure transmitter ports
20 and several spare ports. The high temperatures created in the GRS **3200** by the plasma torches **3208** ensure that the molecules within the off-gas disassociate into their constituent elements, and then combines together to form syngas. The hot crude syngas exits the GRS **3200** via the syngas outlet **3206**.

Referring to Figure 21, and as mentioned earlier, the GRS **3200** incorporates supports
25 for refractory lining. The major support feature for the refractory is a series of shelves **3222** around the interior of the GRS **3200**. During operation, these shelves **3222** will be at considerably higher temperature than the shell of the reformulating chamber **3202**. Therefore, it is necessary to avoid any waste of heat by conduction to the GRS **3200**, while providing allowance for differential expansion. Also, the shelves **3222**
30 must be capable of supporting the considerable weight of the refractory. These requirements were met by making the shelves **3222** segmented with expansion gaps

between segments to allow for the expansion. Also, there is a gap between the shelf 3222 and the wall to avoid heat transfer. To take the weight of the refractory, each shelf segment is supported by a number of gussets 3224 welded to the wall, as shown in Figure 21. Expansion of the shelf 3222 along its length would create stress and possibly failure in the gussets 3224 if they were welded to the gussets 3224. However, by resting the shelf 3222 on the gussets 3224 without welding, the shelf 3222 is allowed to expand freely. To hold the segment into its correct location, it is welded to the center gussets 3224 only where the expansion is small and even then only the outer portion is welded. This minimizes any stress on the gussets 3224 and potential buckling of the shelf 3222.

The top of the reformulating chamber 3202 is capped with a refractory-lined lid 3203 thereby creating a sealed enclosure. The whole GRS 3200 is coated with a high temperature resistant membrane internally to prevent corrosion by the unrefined off-gas. It is painted on the exterior surfaces with a thermo-chromic paint to reveal hot spots due to refractory failure or other causes.

The refractory used is a multilayer design with a high density layer on the inside to resist the high temperature, erosion and corrosion that is present in the GRS 3200. Outside the high density material is a lower density material with lower resistance properties but higher insulation factor. Outside this layer, a very low density foam board material with very high insulation factor is used because it will not be exposed to abrasion or erosion. The outside layer, between the foam board and the vessel steel shell is a ceramic blanket material to provide a compliant layer to allow for differential expansion between the solid refractory and the vessel shell. Vertical expansion of the refractory is provided for by means of a compressible refractory layer separating sections of the non-compressible refractory. The compressible layer is protected from erosion by overlapping but extendible high density refractory.

As shown in Figures 22, 23 & 25, air is injected into the off-gas stream by three levels of air nozzles that include four jets at the lower level, and another six jets at upper level, in which three jets are slightly higher than other three to create cross-jet mixing effects to achieve better mixing. Angular blowing of the air into the GRS 3200,

achieved using deflector at the tip of the input nozzle, also results in better mixing while allowing the inlet pipes and flanges to be square with the reformulating chamber **3202**. The improved mixing of the gases in the GRS **3200** improves the reformulation of the syngas. This is achieved by inducing a swirling action at the base
5 of the reformulating chamber **3202** by making use of the process air velocity. Air is injected into the off-gas stream through swirl ports **3212** to create a swirling motion or turbulence in the off-gas stream thereby mixing the off-gas and creating a re-circulating vortex pattern within the GRS **3200**.

As mentioned earlier, the GRS **3200** also includes two tangentially mounted 300kW,
10 water cooled, copper electrode, NTAT, DC plasma torches **3208** mounted on a sliding mechanism, as shown in Figure 24. The DC plasma torches **3208** are powered from a DC power supply. Thermocouples are positioned at various locations within the GRS **3200** to ensure that the temperature of the syngas is maintained at about 1000°C.

The plasma torches **3208** require periodic maintenance and it is most desirable that
15 they are replaceable with the process still running. As mentioned earlier, this implementation uses two torches **3208** in the GRS **3200** when strictly only one is needed for operation. Removal and replacement of the plasma torches **3208** have to be done in the presence of high temperature toxic and flammable gas in the GRS **3200**. In addition, the torch **3208** will also need to be removed in the event of failure of the
20 torch cooling system to protect it from the heat in the GRS **3200**.

These challenges are met by mounting the torch **3208** on a sliding mechanism that can move the torch **3208** into and out of the reformulating chamber **3202**. The torch **3208** is sealed to the reformulating chamber **3202** by means of a sealing gland. This gland is sealed against a gate valve **3209**, which is, in turn, mounted on and sealed to the
25 vessel. To remove a torch **3208**, it is pulled out of the reformulating chamber **3202** by the slide mechanism. Initial movement of the slide disables the high voltage torch power supply for safety purposes. The gate valve **3209** shuts automatically when the torch **3208** has retracted past the gate valve **3209** and the coolant circulation is stopped. The hoses and cable are disconnected from the torch **3208**, the gland is
30 released from the gate valve **3209** and the torch **3208** is lifted away by a hoist.

Replacement of a torch **3208** is done using the reverse of the above procedure; the slide mechanism can be adjusted to permit variation of the insertion depth of the torch **3208**.

For the sake of simplicity and safety, all the above operations except for the closing of the gate valve **3209** are carried out manually. The gate valve **3209** is operated mechanically so that operation is automatic. A pneumatic actuator **3210** is used to automatically withdraw the torch in the event of cooling system failure. Compressed *air* for operating the pneumatic actuator **3210** is supplied from a dedicated air reservoir so that power is always available even in the event of electrical power failure. The same air reservoir provides the air for the gate valve **3209**. An electrically interlocked cover is used a further safety feature by preventing access to the high voltage torch connections.

Residue Conditioning System

The residue remaining after the gasification must be rendered inert and usable before disposal. Referring to Figure 26, this is done by extracting it from the gasifier **2200** into a plasma-based residue conditioning chamber (RCC) **4220**, melting it and rendering it into an inert molten slag **4202**, cooling and shattering the molten slag **4202** into granules using a quench tank **4240** before transfer to a slag stockpile **4204** ready for removal from the site. The final by-product is suitable for use as road fill or concrete manufacture.

As mentioned earlier, the movement of residue from the gasifier **2200** is complicated by the potential for agglomeration caused due to the heat generated within the pile. This problem is solved by using a screw type conveyor **2209** at the outlet end of the gasifier **2200**. The conveyor has serrated edges on the screw flights to break up any agglomerated material.

Referring to Figure 27, the residue is then taken to the RCC **4220** by means of a main conveyor **4210** system comprising a series of screw conveyors. This conveyor system **4210** also takes the residue from the GCS baghouse filter **6230** downstream and

passes it onto the RCC 4220. To minimize the number of entry ports to the RCC 4220, the residue from all sources is combined before introduction to the RCC 4220. This avoids enlarging the RCC 4220 to cater to multiple feed sources. In order for gasification to continue during RCC 4220 downtime the residue may be diverted. In
5 which case it must be re-introduced into the RCC feed system. The overall schematic of the residue conditioning system is shown in Figure 26.

As shown in Figure 28, the residue is dropped into the RCC 4220, where it accumulates in a reservoir 4222 whose depth is determined by the height of a weir 4224, and undergoes heating by a plasma torch 4230. As the level of the molten slag
10 rises within the reservoir 4222 it runs over the weir 4224, dropping into a quench tank 4240. The water tank 4240 ensures that the RCC 4220 is sealed to the atmosphere. Any metals which have not been removed during the MSW handling system stage is transferred to the RCC 4220 and will not necessarily be melted at the slag's normal vitrification temperature. Thus, the reservoir 4222 could become clogged with metal
15 as it is of higher density than the molten slag. To avoid this, the *reservoir* temperature is periodically raised to melt any metals and the molten metals are tapped off from the bottom of the crucible.

Due to the very high temperatures needed to melt the residue and particularly the constituent metals in it, the refractory is subjected to very severe operational demands.
20 These include corrosion and erosion, particularly at the slag waterline, in addition to the high temperature. Also the refractory must provide good insulation to conserve heat and the RCC 4220 must be as small as possible. The refractory is selected to provide an inner lining of very high resistance to heat, corrosion and erosion. The layers of refractory outside the lining are then selected to greater insulation.

It is anticipated that the crucible refractory in particular will require periodic maintenance. To allow for this, the bottom of the RCC 4229 with the crucible can be removed without disturbing any connections to the top of the RCC 4221. This is accomplished by suspending the RCC from its support structure 4270 rather than setting it onto a structure, as shown in Figures 29 & 31. Thus the bottom of the RCC
25 4229 with the reservoir can be dropped away from the top of the RCC 4221 without
30

having to disconnect any connections. Also the entire RCC can be removed by disconnecting the connections and lowering it. This avoids the need to lift the conveyor **4260** and piping out of the way.

When the molten slag drops into the quench tank **4240** it is cooled and shattered into granular form. A slag conveyor **4260** then removes the granular slag **4203** from the quench **4240** and places it into a stockpile **4204** for disposal or further use, as shown in Figure 30. The slag drop port is sealed to the environment by means of a water trap consisting of a shroud sealed to the RCC **4220** at the top and with its lower edge submerged in the quench medium. The same quench medium seals the slag conveyor **4260** from the RCC **4220**.

The gases produced in the RCC **4220** are treated similarly to the gases produced in the converter **1200**. Referring to Figures 28, 32 & 32A, the residue gas exits the RCC **4220** via the gas outlet **4228** and is directed to a residue gas conditioner (RGCS) **4250**. It undergoes a pre-cooling step in an indirect air-to-gas heat exchanger **4252** prior to being passed through a baghouse filter **4254** that removes particulates and heavy metal contaminants. The residue gas is then cooled using a second heat exchanger **4256** before it is passed through an activated carbon bed **4258** for the further removal of heavy metals and particulate matter. Referring to Figure 3, the cleaned and conditioned residue gas is diverted back to the downstream GCS **6200** to feed back with the syngas stream from the converter **1200**.

Referring to Figures 33 & 35, the raw syngas exits the converter **1200** and passes through a Heat Recycling System. In this embodiment, the heat recycling system is implemented using a syngas-to-air Heat Exchanger (HX) **5200** where the heat is transferred from the syngas stream to a stream of air. Thus, the syngas is cooled while the resulting hot stream of air is fed back to the converter **1200** as process air. The cooled syngas then flows into a Gas Conditioning System (GCS) **6200**, where the syngas is further cooled and cleaned of particulates, metals and acid gases sequentially. The cleaned and conditioned syngas (with desired humidity) is sent to the SRS **7200** before being fed to gas engines **9260** where electricity is generated. The functions of the major components (equipment) in the system after the converter **1200**

and RCS 4200 are outlined in Table 1, in the sequence in which the syngas is processed. These major components are shown in Figure 34.

Table 1 Steps after Converter 1200 and RCS 4200

Subsystem or equipment	Main Function
Heat Exchanger 5200	Cool down syngas and recover sensible heat
Evaporative Cooler 6210	Further cooling down of syngas prior to baghouse
Dry Injection System 6220	Heavy metal adsorption
Baghouse 6230	Particle or dust collection
HCL Scrubber 6240	HCl removal and syngas cooling/conditioning
Carbon Filter Bed 6260	Further mercury removal
H ₂ S Removal System 6270	H ₂ S removal and elemental sulfur recovery
RGCS 4250	RCC off-gas cleaning and cooling
Syngas Storage 7230	Syngas storage and homogenization
Chiller 7210; Gas/Liquid Separator 7220	Humidity control
Gas Engines 9260	Primary driver for electricity generation
Flare Stack 9299	Burning syngas during start-up

Syngas-to-air Heat Exchanger

- 5 The output syngas leaving the GRS 3200 is at a temperature of about 900°C to 1100°C. In order to recover the heat energy in the syngas, the raw syngas exiting from GRS 3200 is sent to a shell-tube type syngas-to-air heat exchanger (HX) 5200. Air enters the HX 5200 at ambient temperature, i.e., from about -30 to about 40 °C. The air is circulated using air blowers 5210, and enters the HX 5200 at a rate between
- 10 1000 Nm³/hr to 5150 Nm³/hr, typically at a rate of about 4300 Nm³/hr.

Referring to Figure 35, the syngas flows vertically through the tube side and the air flows in a counter-clockwise fashion through the shell side. The syngas temperature is reduced from 1000°C to between 500°C and 800°C, (preferably about 740°C) while the air temperature is increased from ambient temperature to between 500°C and 625°C (preferably about 600°C). Referring to Figure 3, the heated exchange-air is recirculated back into the converter **1200** for gasification.

The HX **5200** is designed specifically for high level of particulates in the syngas. The flow directions of the syngas and the air are designed to minimize the areas where build up or erosion from particulate matter could occur. Also, the gas velocities are designed to be high enough for self cleaning while still minimizing erosion.

Due to the significant temperature difference between the air and syngas, each tube **5220** in the HX **5200** has its individual expansion bellows. This is essential to avoid tube rupture, which can be extremely hazardous since the air will enter the syngas mixture. Possibility for tube rupture is high when a single tube becomes plugged and therefore no longer expands/contracts with the rest of the tube bundle.

Multiple temperature transmitters are placed on the gas outlet box of the gas-to-air heat-exchanger **5200**. These are used to detect any possible temperature raise that occurs due to combustion in the event of an air leak into the syngas. The air blower **5210** is automatically shut down in such a case.

The material for the gas tubes in the HX **5210** has to be carefully selected to ensure that corrosion is not an issue, due to concerns about sulphur content in the syngas and its reaction at high temperatures. In our implementation, Alloy 625 was selected.

Gas Conditioning System (GCS)

In general, a gas conditioning system (GCS) **6200** refers to a series of steps which converts the crude syngas obtained after the heat exchanger **5200** into a form suitable for downstream end applications. In our implementation, the GCS **6200** can be broken down into two main stages. Stage 1 comprises of: (a) an evaporative cooler (dry quench) **6210**; (b) a dry injection system **6220**; and (c) a baghouse filter (used for particular matter/heavy metal removal) **6230**. Stage 2 comprises of (d) a HCl scrubber

6240; (e) a syngas (process gas) blower **6250**; (f) a carbon filter bed (mercury polisher) **6260**; (g) a H₂S (sulphur) removal system **6270**; and (h) humidity control using a chiller **7210** and gas/liquid separator **7220**.

5 The heat exchanger **5200** before the GCS **6200** is sometimes considered as part of Stage 1 of the GCS **6200**. The syngas (process gas) blower **6250** typically includes a gas cooler **6252** which is sometimes mentioned separately in Stage 2 of the GCS **6200**. Also, humidity control mentioned here as part of Stage 2 of the GCS **6200** is often considered part of the SRS **7200** further downstream to the GCS **6200**.

10 Figure 33 shows a block diagram of the GCS **6200** implemented in our system. This is also an example of a converging process in which the GCS **6200** is integrated with the RGCS **4250**. Figure 34 shows a view of the layout of the GCS.

After initial cooling in the heat exchanger **5200**, the input syngas is further cooled by dry quenching **6210**, which lowers the syngas temperature and also prevents condensation. This is achieved using an evaporative cooling tower (a.k.a 'dry quench') **6210** by direct injection of water into the gas stream in a controlled manner (adiabatic saturation). The water is atomized before it is sprayed co-currently into the syngas stream. As no liquid is present in the cooling, the process is also called dry quench. When the water is evaporated, it absorbs the sensible heat from syngas thus reducing its temperature from 740°C to between 150°C and 300°C (typically about 250°C).
15 20 Controls are added to ensure that water is not present in the exiting gas. The relative humidity at the exiting gas temperature is therefore still below 100%.

Referring to Figure 36 & 37, once the gas stream exits the evaporative cooling tower **6210**, activated carbon, stored in a hopper, is pneumatically injected into the gas stream. Activated carbon has a very high porosity, a characteristic that is conducive to the surface adsorption of large molecular species such as mercury and dioxin.
25 Therefore, most of the heavy metals (cadmium, lead, mercury etc.) and other contaminants in the gas stream are adsorbed on the activated carbon surface. The spent carbon granules are collected by the baghouse **6230** and recycled back to the RCS **4200** for further energy recovery as described in the next step. For obtaining
30 efficient adsorption, it is necessary to ensure that the syngas has sufficient residence

time in this stage. Other materials such as feldspar, lime, and other absorbents can also be used instead of, or in addition to, activated carbon in this dry injection stage **6220** to capture heavy metals and tars in the syngas stream without blocking it.

Referring to Figure 37, particulate matter and activated carbon with heavy metal on its surface is then removed from the syngas stream in the baghouse **6230**, with extremely high efficiency. The operating parameters are adjusted to avoid any water vapour condensation. All particulate matter removed from the syngas stream forms a filter cake which further enhances the efficiency of the baghouse **6230**. So while new non-coated bags have a removal efficiency of 99.5%, the baghouse **6230** is typically designed for 99.9 % particulate matter removal efficiency. The baghouse **6230** employs lined fiber glass bags, unlined fibre glass bags or P84 basalt bags and is operated at a temperature between 200°C and 260°C.

When the pressure drop across the baghouse **6230** increases to a certain set limit, nitrogen pulse-jets are used to clean the bags. Nitrogen is preferred to air for safety reasons. The residue falling from the outside surface of the bags are collected in the bottom hopper and are sent to the residue conditioner **4200** for further conversion or disposal. Special reagents can be used to absorb the high molecular weight hydrocarbon compounds (tars) in order to protect the baghouse **6230**. Figure 37 shows the schematic of the baghouse respectively. The baghouse uses cylindrical filters which do not require support.

A typical operational specification of the baghouse **6230** (assuming the input is fly-ash with heavy metals) is as follows:

	Design Gas flow rate	9500 Nm ³ /hr
	Dust loading	7.4 g/Nm ³
25	Cadmium	2.9 mg/ Nm ³
	Lead	106.0 mg/Nm ³
	Mercury	1.3mg/ Nm ³
	Guaranteed filtration system outlet:	
	Particulate matter	11mg/Nm ³ (about 99.9% removal)
30	Cadmium	15µg/Nm ³ (about 99.65% removal)

Lead	159 $\mu\text{g}/\text{Nm}^3$ (about 99.9% removal)
Mercury	190 $\mu\text{g}/\text{Nm}^3$ (about 90% removal)

The quantity of residue contaminated with heavy metals exiting the baghouse **6230** is large. Therefore, as shown in Figures 27 & 33, this residue is sent to the plasma-based RCC **4220** for conversion into vitreous slag **4203**. Referring to Figure 32 & 33, the secondary gas stream created in the RCC **4220** is then treated in a separate residue gas conditioner (RGCS) **4250** with the following Stage 1 processes: cooling in an indirect air-to-gas heat exchanger **4252** and removal of particulate matter and heavy metals in a smaller baghouse **4254**. The smaller baghouse **4254** is dedicated to treating the secondary gas stream generated in the RCC **4220**. As shown in Figure 33, additional steps carried out by the RGCS **4250** include cooling the gas further using a gas cooler **4256**, and removing heavy metals and particulate matter in a carbon bed **4258**. Referring to Figure 3, the processed secondary syngas stream is then diverted back to the GCS **6200** to feed back into the primary input syngas stream prior to the baghouse filter **6230**.

The quantity of residue removed from the bag-house **4254** of the RGCS **4250** is significantly less compared to the baghouse **6230** in the GCS **6200**. The small baghouse **4254** acts as a purge for the heavy metals. The amount of heavy metals purged out of the RGCS **4250** will vary depending on MSW feed composition. A periodic purge is required to move this material to hazardous waste disposal, when the heavy metals build-up to a specified limit.

Below is a typical design specification for the smaller RGCS baghouse **4254**, once again assuming that the input is fly-ash with heavy metals:

Design Gas flow rate	150 Nm^3/hr
Dust loading	50g/ Nm^3
Cadmium	440mg/ Nm^3
Lead	16.6 mg/ Nm^3
Mercury	175mg/ Nm^3
Guaranteed filtration system outlet:	
Particulate matter	10mg/ Nm^3 (about 99.99% removal)

Cadmium	13µg/Nm ³ (about 99.997% removal)
Lead	166 µg/Nm ³ (about 99.999% removal)
Mercury	175 µg/Nm ³ (about 99.9% removal)

The GCS **6200** may comprise direct and indirect feedback or monitoring systems. In our implementation, both the GCS and RGCS baghouse filters have a dust sensor on the exit (direct monitoring) to notify of a bag rupture. If a bag rupture occurs, the system is shutdown for maintenance. Optionally, the water stream in the HCl scrubber **6240** can be analyzed at start-up to confirm particulate matter removal efficiency.

Referring to Figure 38, the particulate-free syngas stream exiting from the baghouse **6230** is scrubbed in a packed tower using a re-circulating alkaline solution to remove any HCl present. This HCl scrubber **6240** also provides enough contact area to cool down the gas to about 35°C. A carbon bed filter **6260** is used to separate the liquid solution from potential soluble water contaminants, such as metals, HCN, ammonia etc. The HCl scrubber **6240** is designed to keep the output HCl concentration at about 5ppm. A waste water bleed stream is sent to a waste water storage tank **6244** for disposal, as shown in Figure 39.

For metallurgical considerations, the HCl scrubber **6240** is located upstream of the gas blower **6250**. An exemplary schematic diagram of an HCl scrubber **6240** including associated components such as heat exchangers **6242** is shown in Figure 38. Figure 39 shows an exemplary system for collecting and storing waste water from the GCS **6200**. A carbon bed is added to the water blowdown to remove tars and heavy metals from the wastewater. Typical specification for the HCl scrubber **6240** is as follows:

Design Gas flow rate	9500 Nm ³ /hr
Normal Inlet / Max HCl loading to scrubber	0.16 % / 0.29 %
HCl outlet concentration	5 ppm

After HCl removal, a gas blower **6250** is employed which provides the driving force for the gas through the entire system **120** from the converter **1200** to the gas engines **9260** downstream. The blower **6250** is located upstream of the mercury polisher **6260** as the latter has a better mercury removal efficiency under pressure. This also reduces

the size of the mercury polisher **6260**. Figure 3 show schematic of the entire gasification system **120** including the position of the process gas blower **6250**.

The blower **6250** is designed using all upstream vessel design pressure drops. It is also designed to provide the required pressure for downstream equipment pressure losses to have a final pressure of ~2.1 to 3.0 psig (typically 2.5psig) in the HC **7230**. As the gas is pressurized when passing through the blower **6250**, its temperature rises to about 77°C. A built-in gas cooler **6252** is used to reduce the temperature back to 35°C, as maximum operating temperature of the H₂S removal system **6270** is about 40°C.

A carbon bed filter **6260** is used as a final polishing device for any heavy metal remaining in the syngas stream. Its efficiency is improved when the system is under pressure instead of vacuum, is at lower temperature, gas is saturated, and when the HCl is removed so that it does not deteriorate the carbon. This process is also capable of absorbing other organic contaminants, such as dioxins from the syngas stream if present. The carbon bed filter **6260** is designed for over 99% mercury removal efficiency.

The performance of this system is measured by periodically analyzing the gas for mercury. Corrections are made by modifying the carbon feed rate and monitoring the pressure drop across the polisher **6260**, and by analyzing the carbon bed efficiency via sampling.

Typical specification for the carbon bed filter **6260** is as follows:

Design Gas flow rate	9500 Nm ³ /hr
Normal/Max Mercury loading	190 µg/Nm ³ / 1.3mg/Nm ³
Carbon bed life	3-5 years
Guaranteed mercury carbon bed outlet	19 µg/Nm ³ (99%)

The H₂S removal system **6270** was based on SO₂ emission limitation outlined in A7 guide lines of the Ministry of Environment, Ontario, Canada, which states that syngas being combusted in the gas engines will produce SO₂ emission below 15ppm. The H₂S removal system **6270** was designed for an output H₂S concentration of about

20ppm. Figure 40 shows the details of the H₂S removal system **6270**.

The Shell Paques Biological technology was selected for H₂S removal **6270**. This technique consists of two steps: First, syngas from the carbon bed filter **6260** passes through a scrubber **6272** where H₂S is removed from syngas by re-circulating an alkaline solution. Next, the sulphur containing solution is sent to a bioreactor **6274** for regeneration of alkalinity, oxidation of sulfide into elemental sulphur, filtration of sulphur, sterilization of sulphur and bleed stream to meet regulatory requirements. The H₂S removal system **6270** is designed for 20 ppm H₂S outlet concentration.

Thiobacillus bacteria are used in the bioreactor **6274** to convert sulfides into elemental sulphur by oxidation with air. A control system controls the air flow rate into the bio-reactor to maintain sulphur inventory in the system. A slip stream of the bio reactor **6274** is filtered using a filter press **6276**. Filtrate from filter-press **6276** is sent back to the process, a small stream from this filtrate is sent as a liquid bleed stream. There are two sources of discharge; one solid discharge – sulphur with some biomass and one liquid discharge – water with sulphate, carbonate and some biomass. Both streams are sterilized before final disposal.

Typical specification for the H₂S removal system **6270** is as follows:

Design Gas flow rate	8500 Nm ³ /hr
Normal / Max H ₂ S loading	353 ppm/666 ppm
Guaranteed H ₂ S outlet for system	20ppm

After the H₂S removal, a chiller **7210** is used to condense the water out of the syngas and reheat it to a temperature suitable for use in the gas engines **9260**. The chiller **7210** sub-cools the gas from 35°C to 26°C. The water condensed out from the input gas stream is removed by a gas/liquid separator **7220**. This ensures that the gas has a relative humidity of 80% once reheated to 40°C (engine requirement) after the gas storage prior to being sent to the gas engines **9260**.

The following table gives the major specifications of the entire GCS **6200**:

Quench Tower 6210	quench gas from 740°C to 200°C in 2 sec residence time
--------------------------	--

Dry Injection 6220	90 % mercury removal efficiency
Baghouse Filter 6230	99.9 % Particulate removal efficiency 99.65% Cadmium removal efficiency 99.9% Lead removal efficiency
HCl Scrubber 6240	99.8 % HCl removal efficiency
Gas Blower 6250	Zero leak seal rotary blower
Gas Cooler 6252	0.5 MBtu/hr cooling load
Carbon Bed Filter 6260	99 % mercury removal efficiency
H ₂ S Scrubber 6270	H ₂ S at scrubber outlet – 20 ppm
Bioreactor 6274	Maximum regeneration efficiency with minimum blow-down
Filter Press 6276	2 days sulphur removal capacity
Homogenization Chamber 7230	2 min gas storage capacity

As noted above, the GCS **6200** converts an input gas to an output gas of desired characteristics. Figure 33 depicts an overview process flow diagram of this GCS system **6200** which is integrated with a gasification system **120** and downstream application. Here, the secondary gas stream generated in the RCS **4200** is fed into the GCS **6200**.

The Residue Gas Conditioner (RGCS)

As mentioned earlier, the residue from the GCS baghouse **6230** which may contain activated carbon and metals is purged periodically by nitrogen and conveyed to the RCC **4220**, where it is vitrified. The gas coming out of the RCC **4220** is directed through a residue gas conditioner (RGCS) **4250** baghouse **4254** to remove particulates and is cooled by a heat exchanger **4256** before entering an activated carbon bed **4258**. The baghouse **4254** is also periodically purged based on pressure drop across the system. The residue collected in the RGCS baghouse **4254** is disposed by appropriate means. The combustible gas exiting from the RGCS **4250** as a secondary gas stream is sent back to the main GCS system **6200** to fully utilize the recovered energy.

SynGas Regulation System

The cleaned and cooled syngas from the GCS **6200** enters a gas regulation system. In this example, the gas regulation system is a syngas regulation system (SRS) **7200** designed to ensure that the syngas flowing to the downstream gas engines **9260** is of
5 consistent gas quality. The SRS **7200** serves to smooth out short-term variations in gas composition (primarily its low heating value –LHV) and its pressure. While the downstream gas engines **9260** will continue to run and produce electricity even with short-term variations in the LHV or pressure of the syngas, it may deviate from its threshold emission limits due to poor combustion or poor fuel to air ratio.

10 Referring to Figure 41, the SRS **7200** comprises a chiller **7210**, a gas/liquid separator **7220** and a homogenization chamber (HC) **7230**. The gas is heated on the exit of the gas storage prior to the gas engines **9260** to meet engine temperature requirements.

Two types of homogenization chambers (HC) are available: a fixed volume HC and a variable volume HC. The latter is typically more useful to reduce flow and pressure
15 fluctuation while the former is more useful to reduce LHV fluctuations. LHV fluctuations are more prominent in our application due to the nature of the MSW feedstock. A fixed volume HC is also typically more reliable than variable volume in terms of its construction and maintenance.

Figure 42 show the schematic of the homogenization chamber (HC) **7230** used in this
20 implementation. It is designed to hold about 2 minutes of syngas flow. This hold up time meets the gas engine guaranteed norms on LHV fluctuation specifications of about 1% LHV fluctuation/30 sec. The residence time up to the gas analyzer **8130** is typically about 30 sec (including analysis and feedback). The maximum LHV fluctuation is typically about 10%. Thus, to average this out and get 3% LHV
25 fluctuation, >1.5 min storage is needed. The 2 min storage allows for some margin.

The HC **7230** is operated at a range of 2.2 to 3.0 psig to meet the fuel specifications of the downstream gas engines **9260**. The exiting gas pressure is kept constant using a pressure control valve. The HC **7230** is designed for a maximum pressure of 5psig and a relief valve is installed to handle unusual overpressure scenarios.

The 2 min hold up time of the HC **7230** also provides enough storage to reduce pressure fluctuations. For our design, the allowable pressure fluctuation for the gas engine **9260** is 0.145 PSI/sec. In the case of a downstream failure of the gas engine **9260**, a buffer may be required (depending on control system response time and 30-
 5 35 sec gas resident times) to provide time to slow down the process or to flare the excess gas.

Typical syngas flow rate into the HC **7230** is at ~ 8400 Nm³/hr. Therefore, for a hold up time of 2 min, the HC's volume has to be about 280 m³.

The HC **7230** is free-standing and is located outside where it will be exposed to snow,
 10 rain and wind. Therefore, the dimensions of the HC **7230** are designed to meet mechanical engineering requirements. Its support structure interfaces with a concrete foundation.

As some water will condense out of the syngas, a bottom drain nozzle is included in the design of the HC **7230**. To assist in the drainage of the HC **7230**, its bottom is
 15 intentionally designed to not be flat, but as a conical bottom with a skirt. Traced/insulated drain piping is used to form the drain flange. As the water within the HC **7230** has to gravity drain to the floor drain, the HC **7230** is kept slightly elevated.

The HC **7230** is designed to meet the following design requirements.

Normal / Maximum Inlet Temperature	35°C / 40°C
Normal / Maximum Operating Pressure	1.2 psig / 3.0 psig
Normal / Maximum Gas Inlet Flow Rate	7000 Nm ³ /hr / 8400 Nm ³ /hr
Normal / Maximum Gas Outlet Flow Rate	7000 Nm ³ /hr / 8400 Nm ³ /hr

Relative Humidity	60% - 100%
Storage Volume	290 m ³
Mechanical Design Temperature	-40°C to 50°C
Mechanical Design Pressure	5.0 psig

The material used for the HC **7230** has to take into account both the mechanical design requirements above and the typical gas composition given below. Corrosion is particularly a concern due to the presence of water, HCl, and H₂S.

N ₂	47.09%
CO ₂	7.44%
H ₂ S	20 ppm
H ₂ O	3.43%
CO	18.88%
H ₂	21.13%
CH ₄	0.03%
HCl	5 ppm

The following openings are provided in the HC **7230**:

- 5 One 36" manhole near the bottom for accessibility;
- One 6" flange at the top for relief;
- One 16" flange on the shell for gas inlet;
- One 16" flange on the shell for gas outlet;
- Six 1" flanges on the shell (2 for pressure, 1 for temperature and 3 as spares);

One 2" flange at the bottom of HC (drain); and
 One 1" flange on the bottom cone for level switches.

In addition to satisfying the design requirements, the HC **7230** also provides:

- Openings, manhole covers, and blind flanges for all spare nozzles.
- 5 A ladder allowing safe access, (e.g. with railing) to the roof and relief valve.
- Required lifting hooks and anchor bolts.
- A concrete ring wall.
- Interior and exterior coatings of the HC **7230**, if required.
- Insulation and heat tracing of the bottom of the HC **7230**.
- 10 A concrete slab for support.

The gas engine **9260** design requires that the inlet gas be of a specific composition range at a specified relative humidity. Therefore, the cleaned gas that exits the H₂S scrubber **6270** is sub-cooled from 35°C to 26°C using a chiller **7210**. Any water that is formed due to the condensation of the gas stream is removed by the gas/liquid
 15 separator **7220**. This ensures that the syngas has a relative humidity of 80% once reheated to 40°C, a typical requirement for gas engines **9260**.

A gas blower **6250** is used to withdraw syngas from the system by providing adequate suction through all the equipment and piping as per specifications below. The blower design took heed to good engineering practice and all applicable provincial and
 20 national codes, standards and OSHA guidelines. Operation of the blower **6250** was at about 600 Volts, 3 phase, and 60 Hz.

The gas blower **6250** was designed to meet following functional requirements.

Normal gas inlet temperature	35 C
Normal gas suction pressure	-1.0 psig
Normal gas flow rate	7200 Nm ³ /hr
Maximum gas flow rate	9300 Nm ³ /hr

Maximum gas suction temperature	40C
Normal discharge pressure	3.0 psig
Normal discharge temperature (after gas cooler)	<35 C
Mechanical design pressure	5.0 psig
Relative Humidity of gas at blower inlet	100 %
Gas Molecular Weight	23.3
Cooling water supply temperature (product gas cooler)	29.5 C
Maximum acceptable gas discharge temperature (after product gas cooler)	40 C
Turn down ratio	10%

The typical gas composition (wet basis) drawn is as follows:

CH ₄	0.03%
CO	18.4%
CO ₂	7.38%
H ₂	20.59%
Normal / Max H ₂ S	354 / 666 ppm
H ₂ O	5.74%
Normal / Max HCl	5 ppm / 100 ppm
N ₂	47.85%

As the syngas is flammable and creates an explosive mixture with air, the blower **6250** is configured such that there is minimal to no air intake from the atmosphere, and minimal to no gas leak to the atmosphere. All service fluids, i.e., seal purges are done with nitrogen and a leak-free shaft seal is used. Advanced leak detection systems are employed to monitor leaks in either direction.

In addition to the design criteria above, the blower **6250** also provides:

An explosion proof motor with leak-free blower shaft seal.

A gas cooler **6252**.

A silencer with acoustic box to meet noise regulation of 80 dBA at 1m.

A common base plate for the blower and motor.

5 An auxiliary oil pump with motor, and all required instrumentations for blower auxiliary system.

All instruments and controls (i.e. low and high oil pressure switch, high discharge pressure and temperature switch, differential temperature and pressure switch). All switches are CSA approved discharge pressure gauge,
10 discharge temperature gauge, oil pressure and temperature gauge. All instruments are wired at a common explosion proof junction box and the VFD is controlled by a pressure transmitter installed upstream of the blower.

A zero leaks discharge check valve.

Equipment safety system to prevent blower from excessive pressure /vacuum/
15 shut off discharge (e.g. systems like PRV and recycle line).

As the gas blower **6250** is located outside the building, exposed to rain, snow and wind. The gas blower **6250** is configured to withstand the following environmental conditions.

	Elevation above mean sea level	80 m
20	Latitude	45° 24' N
	Longitude	75° 40' W
	Average atmospheric pressure	14.5 psia
	Maximum summer dry bulb temperature	38°C
	Design summer dry bulb temperature	35°C
25	Design summer wet bulb temperature	29.4°C
	Minimum winter dry bulb temperature	36.11°C
	Mean wind velocity	12.8 ft/sec
	Maximum wind velocity	123 ft/sec
	Design wind velocity	100 mph/ 160 kph
30	Prevailing wind direction	Mainly from south and west
	Seismic Information	Zone 3

Since the blower **6250** works in an environment where explosive gases may be present, all instruments and electrical devices installed on syngas pipes or within about 2 meter distance are designed for the classification of Class 1, zone 2.

For ensuring reliability, proper access for inspection and maintenance is provided, as
5 is access to isolate and correct faults quickly. While the blower **6250** can be operated continuously (24/7), frequent start/stop operation is more common during process stabilization are contemplated.

The material of construction was chosen based on design conditions and gas composition. For example, electrical circuit boards, connectors and external
10 components were coated or otherwise protected to minimize potential problems from dirt, moisture and chemicals. Control panels and switches are of robust construction, designed to be operated by personnel with work gloves.

Generally, variable speed drive (VSD) with a flow range of 10% to 100% is employed for motor control. Over-voltage and overload protection are included. The motor
15 status, on/off operation and change of speed are monitored and controlled remotely through the distributed control system (DCS).

Once the regulated gas exits the HC **7230**, it is heated to the engine requirement and directed to the gas engines **9260**.

Gas Engines

20 Five reciprocating GE Jenbacher gas engines **9260** with 1MW capacity each are used to produce electricity. So, the full capacity of electricity generation is 5 MW. Optionally, any of the gas engines **9260** can be turned off depending on the overall requirements. The gas engine **9260** is capable of combusting low or medium heating value syngas with high efficiency and low emissions. However, due to the relatively
25 low gas heating value (as compared to fuels such as natural gas) the gas engines **9260** have been de-rated to operate around 700kW at their most efficient operating point. Optionally, the downstream application can be expanded to include another gas engines **9260** to make a total of six.

Flare Stack

An enclosed flare stack **9299** will be used to burn syngas during start-up, shut-down and process stabilization phases. Once the process has been stabilized the flare stack **9299** will be used for emergency purposes only. The flare stack **9299** is designed to
5 achieve a destruction efficiency of about 99.99%.

Control System

In this implementation, the gasification system **120** of the present example comprises an integrated control system for controlling the gasification process implemented therein, which may include various independent and interactive local, regional and
10 global processes. The control system may be configured to enhance, and possibly optimize the various processes for a desired front end and/or back end result.

A front-to-back control scheme could include facilitating the constant throughput of feedstock, for example in a system configured for the gasification of MSW, while meeting regulatory standards for this type of system. Such front-to-back control
15 scheme could be optimized to achieve a given result for which the system is specifically designed and/or implemented, or designed as part of a subset or simplified version of a greater control system, for instance upon start-up or shut-down of the process or to mitigate various unusual or emergency situations.

A back-to-front control scheme could include the optimization of a product gas
20 quality or characteristic for a selected downstream application, namely the generation of electricity via downstream gas engines **9260**. While the control system could be configured to optimize such back-end result, monitoring and regulation of front-end characteristics could be provided in order to ensure proper and continuous function of the system in accordance with regulatory standards, when such standards apply.

25 The control system may also be configured to provide complimentary results which may be best defined as a combination of front-end and back-end results, or again as a result flowing from any point within the gasification system **120**.

In this implementation, the control system is designed to operate as a front-to-back

control system upon start-up of the gasification process, and then progress to a back-to-front control system when initial start-up perturbations have been sufficiently attenuated. In this particular example, the control system is used to control the gasification system **120** in order to convert feedstock into a gas suitable for a selected downstream application, namely as a gas suitable for consumption by a gas engine **9260** in order to generate electricity. In general, the control system generally comprises one or more sensing elements for sensing various characteristics of the gasification system **120**, one or more computing platforms for computing one or more process control parameters conducive to maintaining a characteristic value representative of the sensed characteristic within a predetermined range of such values suitable for the downstream application, and one or more response elements for operating process devices of the gasification system **120** in accordance with these parameters.

For example, one or more sensing elements could be distributed throughout the gasification system **120** for sensing characteristics of the syngas at various points in the process. One or more computing platforms communicatively linked to these sensing elements could be configured to access characteristic values representative of the sensed characteristics, compare the characteristic values with predetermined ranges of such values defined to characterize the product gas as suitable for the selected downstream application, and compute the one or more process control parameters conducive to maintaining these characteristic values within these predetermined ranges. The plurality of response elements, operatively linked to one or more process devices and/or modules of the gasification system operable to affect the process and thereby adjust the one or more characteristics of the product gas, can be communicatively linked to the one or more computing platforms for accessing the one or more computed process control parameters, and configured to operate the one or more processing devices in accordance therewith.

The control system may also be configured to provide for an enhanced front-end result, for example, for an enhanced or constant consumption and conversion rate of the input feedstock, or again as part of start-up, shut-down and/or emergency procedure, or again, configured to implement the process of the gasification system

120 so to achieve a predetermined balance between front-end benefits and back-end benefits, for instance enabling the conversion of the feedstock to produce a product gas suitable for a selected downstream application, while maximizing throughput of feedstock through the converter. Alternative or further system enhancements could
5 include, but are not limited to, optimising the system energy consumption, for instance to minimise an energetic impact of the system and thereby maximise energy production via the selected downstream application, or for favouring the production of additional or alternative downstream products such as consumable product gas(es), chemical compounds, residues and the like.

10 A high-level process control schematic is provided for this example in Figure 43, wherein the process to be controlled is provided by the gasification system 120 described above. Figure 44 provides an alternative depiction of the gasification system 120 and control system of Figure 3 to identify exemplary characteristics and sensing elements associated therewith. As described above, the gasification system
15 120 comprises a converter 1200, comprising a gasifier 2200 and GRS 3200 in accordance with the present example, for converting the one or more feedstocks (*e.g.* MSW and plastics) into a syngas and a residue product. The system 120 further comprises a residue conditioning system (RCS) 4200 and a *heat exchanger* 5200 conducive to recuperating heat from the syngas and, in this example, using this
20 recuperated heat for heating the air input additive used in the converter 1200. A gas conditioning system (GCS) 6200 for conditioning (*e.g.* cooling, purifying and/or cleaning) the syngas is also provided, and a SRS 7200 used for at least partially homogenizing the syngas for downstream use. As depicted herein, residue may be provided to the RCS 4200 from both the converter 1200 and the GCS 6200, the
25 combination of which being conditioned to yield a solid product (*e.g.* vitrified slag 4203) and a syngas to be conditioned and combined with the converter syngas for further conditioning, homogenization and downstream use.

In Figures 43 and 44, various sensing and response elements are depicted and configured to provide various levels of control for the gasification system 120. As
30 discussed hereinabove, certain control elements may be used for local and/or regional system controls, for example in order to affect a portion of the process and/or

subsystem thereof, and therefore, may have little or no effect on the overall performance of the system. For example, while the GCS **6200** may provide for the conditioning and preparation of the syngas for downstream use, its implementation, and variations absorbed thereby, may have little effect on the general performance and output productivity of the gasification system **120**.

On the other hand, certain control elements may be used for regional and/or global system controls, for example in order to substantially affect the process and/or gasification system **120** as a whole. For example, variation of the feedstock input via the MSW handling system **9200** and/or plastics handling means **9250** may have a significant downstream effect on the product gas, namely affecting a change in composition and/or flow, as well as affect local processes within the converter **1200**. Similarly, variation of the additive input rate, whether overall or discretely for different sections of the converter **1200**, may also have a significant downstream effect on the product gas, namely to the gas composition and flow. Other controlled operations, such as reactant transfer sequences within the converter **1200**, airflow distribution adjustments, plasma heat source power variations and other such elements may also effect characteristics of the product gas and may thus be used as a control to such characteristics, or again be accounted for by other means to reduce their impact on downstream application.

In Figures 43 and 44, various sensing elements are depicted and used in the present example to control various local, regional and global characteristics of the gasification process. For instance, the gasification system **120** comprises various temperature sensing elements for sensing a process temperature at various locations throughout the process. In Figure 43, one or more temperature sensing elements are provided for respectively detecting temperature variations within the converter **1200**, in relation to the plasma heat source **3208**, and in relation to the residue conditioning process in RCS **4200**. For example, independent sensing elements (commonly identified by temperature transmitter and indicator control **8102** of Figure 43) may be provided for sensing temperatures T1, T2 and T3 associated with the processes taking place within Stages 1, 2 and 3 of the gasifier **2200** (*e.g.* see Figure 44). An additional temperature sensing element **8104** may be used to sense temperature T4 (*e.g.* see Figure 44)

associated with the reformulating process of the GRS **3200** and particularly associated with the output power of the plasma heat source **3208**. In this example, a temperature sensing element **8106** is also provided for sensing a temperature within the RCC **4220** (e.g. temperature T5 of Figure 44), wherein this temperature is at least partially associated with the output power of the residue conditioner plasma heat source **4230**. It will be appreciated that other temperature sensing elements may also be used at various points downstream of the converter **1200** for participating in different local, regional and/or global processes. For example, temperature sensing elements can be used in conjunction with the heat exchanger **5200** to ensure adequate heat transfer and provide a sufficiently heated air additive input to the converter **1200**. Temperature monitors may also be associated with the GCS **6200** to ensure gases conditioned thereby are not too hot for a given sub-process, for example. Other such examples should be apparent to the person skilled in the art.

The gasification system **120** further comprises various pressure sensing elements operatively disposed throughout the gasification system **120**. For instance, a pressure sensing element (depicted as pressure transmitter and indicator control **8110** in Figure 1) is provided for sensing a pressure within the converter **1200** (depicted in the example of Figure 2 as particularly associated with GRS **3200**), and operatively associated with blower **6500** via speed indicator control, variable frequency drive and motor assembly **8113** for maintaining an overall pressure within the converter **1200** below atmospheric pressure; in this particular example, the pressure within the converter **1200**, in one embodiment, is continuously monitored at a frequency of about 20Hz and regulated accordingly. In another embodiment, the blower is maintained at a frequency of about 20Hz or above in accordance with operational requirements; when blower rates are required below 20Hz an override valve may be used temporarily. A pressure sensing element **8112** is also provided in operative association with the RCC **4220** and operatively linked to a control valve leading residue conditioner gas from the RCC **4220** to the GCS **6200**. Pressure sensing element **8116**, is also provided for monitoring input air pressure to the heat exchanger **5200** and is operatively linked to blower **5210** for regulating same via speed indicator control, variable frequency drive and motor assembly **8120**. A pressure control valve **8115** is provided as a secondary control to override and adjust pressure within the

system when the syngas blower speed **6250** falls below the blower's minimum operating frequency

Another pressure sensing element **8114** is further provided with the SRS **7200** and operatively linked to control valve **7500** for controlled and/or emergency release of
5 syngas via flare stack **9299** due to excess pressure, for example during start-up and/or emergency operations. This pressure sensing element **8114** is further operatively linked to control valve **8122** via flow transmitter and control indicator **8124** to increase a process additive input flow to the converter **1200** in the event that insufficient syngas is being provided to the SRS **7200** to maintain continuous
10 operation of the gas engines **9260**, for example. This is particularly relevant when the control system is operated in accordance with a back-to-front control scheme, as will be described in greater detail below. Note that in Figure 44, the air flow sensing element **8124** and control valve **8122** are used to regulate the additive air flows to Stages 1, 2 and 3 of the gasifier **2200**, as depicted by respective flows F1, F2 and F3,
15 and additive air flow to the GRS **3200**, as depicted by flow F4, wherein relative flows are set in accordance with a pre-set ratio defined to substantially maintain pre-set temperature ranges at each of the process stages. For example, a ratio F1:F2:F3:F4 of about 36:18:6:40 can be used to maintain relative temperatures T1, T2 and T3 within ranges of about 300-600 °C, 500-900 °C and 600-1000 °C respectively, or optionally
20 within ranges of about 500-600 °C, 700-800 °C and 800-900 °C, respectively, particularly upon input of additional feedstock to compensate for increased combustion due to increased volume, as described below.

The system **120** also comprises various flow sensing elements operatively disposed throughout the system **120**. For instance, as introduced above, a flow sensing element
25 **8124** is associated with the air additive input to the converter **1200** and operatively linked to the control valve **8122** for adjusting this flow, for example in response to a detected pressure drop within the SRS **7200** via sensing element **8114**. A flow sensing element **8126** is also provided to detect a syngas flow to the SRS **7200**, values derived from which being used to regulate both an air additive input rate as a fast response to
30 a decrease in flow, and adjust a feedstock input rate, for example in accordance with the currently defined fuel to air ratio (*e.g.* the (MSW+plastics):(Total additive air

input) ratio currently in use), via MSW and/or plastics feeding mechanisms **9200** and **9250** respectively, for longer term stabilisation; this again is particularly useful when the system is operated in accordance with a back-to-front control scheme, as described below. In this example the air to fuel ratio is generally maintained between
5 about 0 to 4 kg/kg, and during normal operation is generally at about 1.5 kg/kg. A flow sensing element **8128** may also be provided to monitor flow of excess gas to the flare stack **9299**, for example during start-up, emergency and/or front-to-back control operation, as described below.

Figures 43 and 44 also depict a gas analyser **8130** for analyzing a composition of the syngas as it reaches the SRS **7200**, the control system being configured to use this gas
10 composition analysis to determine a syngas fuel value and carbon content and adjust the fuel to air ratio and MSW to plastics ratio respectively and thereby contribute to regulate respective input rates of MSW and plastics. Once again, this feature is particularly useful in the back-to-front control scheme implementation of the control
15 system, described in greater detail below.

Not depicted in Figures 43 and 44, but described above with reference to an exemplary embodiment of the gasifier **2200**, is the inclusion of various sensing elements configured for detecting a height of reactant within the gasifier **2200** at various locations, namely at steps 1, 2 and 3 **2212**, **2214** & **2216**. These sensing
20 elements may be used to control the motion of the lateral transfer means, such as carrier rams **2228**, **2230** & **2232** to enhance effective processing within the gasifier **2200**. In such an example, a carrier ram sequence controller would both affect computation of an actual feedstock input rate, as would variation in the desired feedstock input rate need to be communicated to the carrier ram sequence controller.
25 Namely, the carrier ram sequence controller can be used to adjust a feedstock input rate, and the control system, in communication with the carrier ram sequence controller, may be used to compensate for variations induced by changes in the carrier ram sequence (*e.g.* to address issues raised due to various detected reactant distributions) in downstream processes.

30 Figure 45 provides a control flow diagram depicting the various sensed characteristic

values, controllers (*e.g.* response elements) and operating parameters used by the control system of the present example, and interactions there between conducive to promoting proper and efficient processing of the feedstock. In this figure:

- 5 a converter solids levels detection module **8250** is configured to cooperatively control a transfer unit controller **8252** configured to control motion of the transfer unit(s) **8254** and cooperatively control a total MSW+HCF feed rate **8256**;
- a syngas (product gas) carbon content detection module **8258** (*e.g.* derived from gas analyser **8130**) is operatively coupled to a MSW:HCF ratio controller **8260**
- 10 configured to cooperatively control an MSW/HCF splitter **8262** for controlling respective MSW and HCF feed rates **8264** and **8266** respectively;
- a syngas (product gas) fuel value determination module **8268** (*e.g.* $LHV = c1*[H_2] + c2*[CO]$, where $c1$ and $c2$ are constants and where $[H_2]$ and $[CO]$ are obtained from the syngas analyser **8130**) is operatively coupled to a Fuel:Air ratio controller **8270**
- 15 for cooperatively controlling the total MSW+HCF feed rate **8256** directed to the MSW/HCF splitter **8262** and the transfer unit controller **8252**;
- a syngas flow detection module **8272** is operatively coupled to a total airflow controller **8274** for controlling a total airflow **8276** and cooperatively control the total MSW+HCF feed rate **8256**; and
- 20 a process temperature detection module **8278** is operatively coupled to a temperature controller(s) **8280** for controlling an airflow distribution **8282** (*e.g.* F1, F2, F3 and F4 of Figure 2) and plasma heat **8284** (*e.g.* via PHS **1002**).

In this configuration, in order to determine the amount of air additive to input into the gasification system **120** to obtain a syngas composition within an appropriate range

25 for the downstream application, or again within a range conducive to increasing the energetic efficiency and/or consumption of product gas, the control system may be configured to compute a control parameter based on an acquired characteristic value for the LHV (*e.g.* from analysis of $[H_2]$ and $[CO]$ of syngas). For instance, by setting the temperature and pressure constant, or at a desired set point, a global system

30 parameter may be defined empirically such that the air input parameter may be

estimated with sufficient accuracy using a linear computation of the following format:

$$[LHV] = a[Air]$$

wherein a is an empirical constant for a particular system design and desired output characteristics. Using this method, it has been demonstrated that the gasification system **120** of the present example may be operated efficiently and continuously to meet regulatory standards while optimising for process efficiency and consistency.

Figure 46 provides an alternative control flow diagram depicting the various sensed characteristic values, controllers (*e.g.* response elements) and operating parameters that can be used by a slightly modified configuration of the control system and interactions there between conducive to promoting proper and efficient processing of the feedstock. In this figure:

a converter solids levels detection module **8350** is configured to cooperatively control a transfer unit controller **8352** configured to control motion of the transfer unit(s) **8354** and cooperatively control a total MSW+HCF feed rate **8356**;

a syngas (product gas) carbon content detection module **8358** (*e.g.* derived from gas analyser **8130**) is operatively coupled to a MSW:HCF ratio controller **8360** configured to cooperatively control an MSW/HCF splitter **8362** for controlling respective MSW and HCF feed rates **8364** and **8366** respectively;

a syngas (product gas) [H₂] content detection module **8367** (*e.g.* obtained from the syngas analyser **8130**) is operatively coupled to a Fuel:Air ratio controller **8370** for cooperatively controlling the total MSW+HCF feed rate **8356** for cooperatively controlling the transfer unit controller, the MSW/HCF splitter **8362**, the steam flow calculation and the total airflow;

a syngas (product gas) [CO] content detection module **8369** (*e.g.* obtained from the syngas analyser **8130**) is operatively coupled to a Fuel:Steam ratio controller **8371** for cooperatively controlling the steam flow calculation for controlling the steam addition rate (note: steam additive input mechanism may be operatively coupled to the converter **1200** (not shown in Figures 1 and 2) and provided to compliment air additive and participate in refining the chemical composition of the syngas);

a syngas flow detection module **8372** is operatively coupled to a total airflow

controller **8374** for cooperatively controlling a total airflow **8376** and cooperatively controlling the total MSW+HCF feed rate **8356**; and

a process temperature detection module **8378** is operatively coupled to a temperature controller **8380** for controlling an airflow distribution **8382** (e.g. F1, F2, F3 and F4 of

5 Figure 44) and plasma heat **8384** (e.g. via PHS **1002**).

In this configuration, in order to determine the amount of air additive and steam additive to input into the gasification system **120** to obtain a syngas composition within an appropriate range for the downstream application, or again within a range conducive to increasing the energetic efficiency and/or consumption of product gas,

10 the control system may be configured to compute control parameters based on acquired characteristic values for $[H_2]$ and $[CO]$. For instance, by setting the temperature and pressure constant, or at a desired set point, global system parameters may be defined empirically such that the air and steam input parameters may be estimated with sufficient accuracy using a linear computation of the following format:

$$15 \quad \begin{bmatrix} H_2 \\ CO \end{bmatrix} = \begin{bmatrix} a & b \\ c & d \end{bmatrix} \begin{bmatrix} Air \\ Steam \end{bmatrix}$$

wherein a, b, c and d are empirical constants for a particular system design and desired output characteristics. The person of skill in the art will appreciate that although simplified to a linear system, the above example may be extended to include additional characteristic values, and thereby provide for the linear computation of

20 additional control parameters. Higher order computations may also be considered to refine computation of control parameters as needed to further restrict process fluctuations for more stringent downstream applications. Using the above, however, it has been demonstrated that the gasification system **120** of the present example may be operated efficiently and continuously to meet regulatory standards while optimizing

25 for process efficiency and consistency.

It will be appreciated that the various controllers of the control system generally operate in parallel to adjust their respective values, which can include both absolute (e.g. total air flow) and relative values (e.g. feed to air ratio), although it is also possible for some or all of the controllers to operate sequentially.

As discussed above, a front-to-back (or supply-driven) control strategy is used in the present example during start-up operation of the system **120** where the converter **1200** is run at a fixed feed rate of MSW. Using this control scheme, the gasification system **120** allows for process variations to be absorbed by the downstream equipment such as gas engines **9260** and flare stack **9299**. A small buffer of excess syngas is produced, and a small continuous flare is hence used. Any extra syngas production beyond this normal amount can be sent to the flare, increasing the amount flared. Any deficiency in syngas production first eats into the buffer, and may eventually require generator power output to be reduced (generators can be operated from 50 – 100% power output via an adjustable power set point) or further system adjustments to be implemented by the control system, as described below. This control scheme is particularly amenable to start-up and commissioning phases.

The main process control goals of this front-to-back control scheme comprise stabilizing the pressure in the HC **7230**, stabilizing the composition of the syngas being generated, controlling pile height of material in the gasification chamber **2202**, stabilizing temperatures in the gasification chamber **2202**, controlling temperatures in the reformulating chamber **3202**, and controlling converter process pressure.

When using GE/Jenbacher gas engines **9260**, the minimum pressure of product gas is about 150 mbar (2.18 psig), the maximum pressure is about 200 mbar (2.90 psig), the allowed fluctuation of fuel gas pressure is about +/- 10% (+/- 17.5 mbar, +/- 0.25 psi) while the maximum rate of product gas pressure fluctuation is about 10 mbar/s (0.145 psi/s). The gas engines **9260** have an inlet regulator that can handle small disturbances in supply pressure, and the holdup in the piping and HC act somewhat to deaden these changes. The control system however still uses a fast acting control loop to act to maintain suitable pressure levels. As mentioned above, the converter **1200** in this control scheme is run at sufficient MSW feed rate to generate a small buffer of excess syngas production, which is flared continuously. Therefore the HC **7230** pressure control becomes a simple pressure control loop where the pressure control valves in the line from HC **7230** to the flare stack **9299** are modulated as required to keep the HC pressure within a suitable range.

The control system generally acts to stabilize the composition of the syngas being generated. The gas engines **9260** can operate over a wide range of fuel values, provided that the rate of change is not excessive. The allowable rate of change for Lower Heating Value (LHV) relevant in this example is less than 1% fluctuation in
5 syngas LHV per 30 second. For hydrogen based fuels, the fuel gas is adequate with as little as 15% hydrogen by itself, and the LHV can be as low as 50 btu/scf (1.86 MJ/Nm³). The system volume and HC **7230** aid in stabilizing the rate of change of LHV by providing about 2 minutes of syngas production.

In this control scheme, the product gas composition can be measured by the gas
10 analyzer **8130** installed at the inlet of the HC **7230**, or proximal thereto. Based on this measurement, the control system can adjust the fuel-to-air ratio (i.e. slightly increase/decrease MSW feed rate relative to air additive input air) in order to stabilize the gas fuel value. Increasing either the MSW or plastics feed relative to the air addition increases the fuel value of the gas. It will be appreciated, however, that this
15 control action may have a relatively long response time depending on the overall implementation of the gasification system **120**, and as such, may be tuned to prevent long-term drift rather than respond to short-term variation.

While the plastics feed is by itself a much richer fuel source (*e.g.* LHV of about twice that of MSW), it is typically added in a ratio of about 1:20 (0 to 14%) with the MSW,
20 and therefore, in accordance with this example, it is not the dominant player in terms of fuel being added to the system. Since it can be uneconomical to add too much plastics to the gasification system **120**, the plastics feed may be used as a trim rather than as a primary control. In general, the plastics feed is ratioed to the total feed with the ratio optionally adjusted to stabilize the total carbon exiting the gasification
25 system **120** in the syngas, as measured by the gas analyzer **8130**. This may thus have for affect to dampen fluctuations in MSW fuel value.

In addition, a reactant pile level control system may be used to aid in maintaining a stable pile height inside the converter **1200**. Stable level control may prevent fluidization of the material from process air injection which could occur at low level
30 and to prevent poor temperature distribution through the pile owing to restricted

airflow that would occur at high level. Maintaining a stable level may also help maintain consistent converter residence time. A series of level switches in the gasification chamber **2202** may be used, for example, to measure pile depth. The level switches in this example could include, but are not limited to, microwave devices with an emitter on one side of the converter and a receiver on the other side, which detects either presence or absence of material at that point inside the converter **1200**. The inventory in the gasifier **2200** is generally a function of feed rate and carrier ram motion (*e.g.* carrier ram motion), and to a lesser degree, the conversion efficiency.

10 In this example, the Stage 3 carrier ram(s) sets the converter throughput by moving at a fixed stroke length and frequency to discharge residue from the gasifier **2200**. The Stage 2 carrier ram(s) follows and moves as far as necessary to push material onto Stage 3 and change the Stage 3 start-of-stage level switch state to "full". The Stage 1 carrier ram(s) follows and moves as far as necessary to push material onto Stage 2 and
15 change the Stage 2 start-of-stage level switch state to "full". All carrier rams are then withdrawn simultaneously, and a scheduled delay is executed before the entire sequence is repeated. Additional configuration may be used to limit the change in consecutive stroke lengths to less than that called for by the level switches to avoid excess carrier ram-induced disturbances. The carrier rams may be moved fairly
20 frequently in order to prevent over-temperature conditions at the bottom of the converter. In addition, full extension carrier ram strokes to the end of each stage may be programmed to occur occasionally to prevent stagnant material from building up and agglomerating near the end of the stage. It will be apparent to the person skilled in the art that other carrier ram sequences may be considered herein without departing
25 from the general scope and nature of the present disclosure.

In order to optimize conversion efficiency, in accordance with one embodiment of the present invention, the material is maintained at as high a temperature as possible, for as long as possible. Upper temperature limits are set to avoid the material beginning to melt and agglomerate (*e.g.* form clinkers), which reduces the available surface area
30 and hence the conversion efficiency, causes the airflow in the pile to divert around the chunks of agglomeration, aggravating the temperature issues and accelerating the

formation of agglomeration, interferes with the normal operation of the carrier rams, and potentially causes a system shut down due to jamming of the residue removal screw **2209**. The temperature distribution through the pile may also be controlled to prevent a second kind of agglomeration from forming; in this case, plastic melts and acts as a binder for the rest of the material.

In one embodiment, temperature control within the pile is achieved by changing the flow of process air into a given stage (ie. more or less combustion). For instance, the process air flow provided to each stage in the bottom chamber may be adjusted by the control system to stabilize temperatures in each stage. Temperature control utilizing extra carrier ram strokes may also be used to break up hot spots. In one embodiment, the air flow at each stage is pre-set to maintain substantially constant temperatures and temperature ratios between stages. For example, about 36% of the total air flow may be directed to stage 1, about 18 % to Stage 2, and about 6% to Stage 3, the remainder being directed to the GRS (e.g. 40% of total air flow). Alternatively, air input ratios may be varied dynamically to adjust temperatures and processes occurring within each stage of the gasifier **2200** and/or GRS **3200**.

Plasma heat source power (e.g. plasma torch power) may also be adjusted to stabilize exit temperatures of the GRS **3200** (e.g. reformulating chamber output) at the design set point of about 1000 degrees C. This may be used to ensure that the tars and soot formed in the gasification chamber **2202** are fully decomposed. Addition of process air into the reformulating chamber **3202** may also bear a part of the heat load by releasing heat energy with combustion of the syngas. Accordingly, the control system may be configured to adjust the flow rate of process air to keep torch power in a good operating range.

Furthermore, converter pressure may be stabilized by adjusting the syngas blower's **6250** speed, in the embodiment of Figure 1, depicted proximal to the homogenization subsystem input. At speeds below the blower's minimum operating frequency, a secondary control may override and adjust a recirculation valve instead. Once the recirculation valve returns to fully closed, the primary control re-engages. In general, a pressure sensor **8110** is operatively coupled to the blower **6250** via the control

system, which is configured to monitor pressure within the system, for example at a frequency of about 20Hz, and adjust the blower speed via an appropriate response element **8113** operatively coupled thereto to maintain the system pressure within a desired range of values.

- 5 A residue melting operation is also performed in a continuous operation in a separate vessel (*e.g.* RCC **4220**) which is directly connected to the outlet of the converter **1200**. The *residue* is removed from the gasification chamber **2202** by a toothed screw conveyor (residue extraction screw) or the like mounted at the end of the gasifier **2200** and fed into the top of the RCS **4200** via a series of screw conveyors, for example. A
10 small stream of particulate from the bag house **6230** may also join the main stream of residue via screw conveyors, for example, for further processing.

- The RCS **4200** is a small, refractory-lined residue conditioning chamber (RCC) **4220** with a 300 kW plasma torch **4230** mounted into the top, a process gas outlet **4228** connecting a gas treatment skid, and a molten slag outlet **4226**. The gas exiting the
15 gas treatment skid may be directed to join the main stream of syngas from the converter **1200** at the inlet to the main baghouse **6230**, or directed alternatively for further processing. In this example, the residue drops directly into the top of the RCC **4220** where it is melted by close contact with the plasma torch plume **4230**. The molten slag is held-up, for example, by a vee-notch weir **4224** inside the RCC **4220**.
20 As additional residue particles flow into the RCC **4220** and are melted, a corresponding amount of molten material overflows the weir **4224** and drops into a water-filled quench tank **4240** integral with a screw conveyor where it solidifies, shatters into small pieces of glass-like slag, and is conveyed to a storage container.

- In controlling the residue processing, the power of the plasma torch **4230** may be
25 adjusted as needed to maintain temperatures adequate for the melting operation. The RCC **4220** temperature instrumentation (*e.g.* temperature sensing element **8106**) may include, for example, two optical thermometers (OT's) which measure the surface temperature of the surface upon which they are aimed, 3 vapour space thermocouples mounted in ceramic thermo wells above the melt pool, and 5 external skin mounted
30 thermocouples mounted on the outer metal shell. The RCC **4220** may also include a

pressure transmitter for measuring process pressure (e.g. pressure sensing element **8112**) inside the RCC **4220**.

One melt temperature control strategy contemplated herein is to measure the delta temperature being observed by the two optical thermometers. One OT is aimed at the melt pool below the torch **4230**, the other at the melt pool near the weir **4224**. If the temperature near the weir **4224** is cooling off compared to the temperature below the torch **4230**, then more torch power is applied. An alternative is to use the OT temperatures directly. A set point in the range of 1400 - 1800°C, known to be above the melting temperature of most MSW components is entered into the controller.

10 Torch power is then adjusted as required to meet this set point.

In general, the level is not measured directly, but is inferred by both OT temperature and vapour space thermocouples. If the temperature falls below the temperature set point, this is an indication of un-melted material and interlocks will be used to momentarily slow the feed rate of residue, or to shut down the RCS **4200** as a last resort. The rate of material flow may be controlled by adjusting the RCC feed screw conveyor speed via drive motor variable frequency drives (VFD's), for example. The feed rate may be adjusted as required to ensure acceptable temperature control, within capability of melting rate of plasma torches **4230**, and to prevent high levels in the RCC **4220** due to un-melted material. In general, there may be some hold-up capacity for residue beyond Stage 3 in the gasification chamber **2202**, but sustained operation will depend on the RCC **4220** having adequate melting capacity matching the steady-state production of residue.

15
20

The pressure in the RCC **4220** may be monitored by a pressure transmitter tapped into the vapour space of the vessel (e.g. element **8112**). In general, the operating pressure of the RCC **4220** is somewhat matched to that of the converter gasification chamber **2202** such that there is minimal driving force for flow of gas through the screw conveyors in either direction (flow of solid residue particles only). A control valve **8134** is provided in the gas outlet line which can restrict the flow of gas that is being removed by the downstream vacuum producer (syngas blower). A DCS PID controller calculates the valve position needed to achieve the desired operating

25
30

pressure.

Beyond the start-up phase, a back-to-front control, or demand-driven control can be used where the gas engines **9260** at the back-end of the gasification system **120** drive the process. The gas engines **9260** consume a certain volume/hr of fuel depending on the energy content of the fuel gas (*i.e.* product gas) and the electrical power being generated. Therefore the high level goal of this control system is to ensure that adequate MSW/plastics feed enters the gasification system **120** and is converted to syngas of adequate energy content to run the generators at full power at all times, while adequately matching syngas production to syngas consumption such that flaring of syngas is reduced, or even eliminated, and the electrical power produced per ton of MSW consumed is enhanced, and preferably optimized.

In general, the front-to-back control scheme described above comprises a sub-set of the back-to-front control scheme. For instance, most if not all process control goals listed in the above scheme are substantially maintained, however the control system is further refined to reduce flaring of syngas while increasing the amount of electrical power produced per ton of MSW, or other such feedstock, consumed. In order to provide enhanced control of the process and achieve increased process efficiency and utility for a downstream application, the flow of syngas being produced is substantially matched to the fuel being consumed by the gas engines **9260**; this thus reduces reduce flaring or otherwise disposition of excess product gas from the gasification system **120**, and reduces the likelihood of insufficient gas production to maintain operation of the downstream application. Conceptually, the control system therefore becomes a back-to-front control (or demand-driven control) implemented such that the downstream application (*e.g.* gas engines/generators) drive the process.

In general, in order to stabilize syngas flow out of the converter **1200** in the short term, the air additive input flow into the converter **1200** may be adjusted, providing a rapid response to fluctuations in gas flow, which are generally attributed to variations in feedstock quality variations (*e.g.* variation in feedstock humidity and/or heating value). In general, effects induced by an adjustment of airflow will generally propagate within the system at the speed of sound. Contrarily, though adjustment of

the MSW and/or plastics feed rate may also significantly affect system output (*e.g.* syngas flow), the feedstock having a relatively long residence time within the converter **1200** (*e.g.* up to 45 minutes or more for this particular example), system response times associated with such adjustment will generally range at about 10 to 15 minutes, which on the short term, may not be sufficient to effect the product gas in a timely manner to avoid unwanted operating conditions (*e.g.* flared excess gas, insufficient gas supply for optimal operation, insufficient gas supply for continuous operation, *etc.*). While still having a slower response than an increase in airflow, an increase in MSW feed rate may result in a faster response than an increase in PLASTICS FEED because the moisture content of MSW may produce steam in about 2 to 3 minutes.

Accordingly, adjusting total airflow generally provides the fastest possible acting loop to control pressure and thereby satisfy input flow requirements for the downstream application. In addition, due to the large inventory of material in the converter **1200**, adding more air, or other such additive, to the bottom chamber does not necessarily dilute the gas proportionately. The additional air penetrates further into the pile, and reacts with material higher up. Conversely, adding less air will immediately enrich the gas, but eventually causes temperatures to drop and reaction rates/syngas flow to decrease.

Therefore, total airflow is generally ratioed to material feed rate (MSW+plastics) as presented in Figure 45, whereby an increase in additive input will engender an increase in feedstock input rate. Accordingly, the control system is tuned such that the effect of increased air is seen immediately, whereas the effect of the additional feed is eventually observed to provide a longer term solution to stabilizing syngas flow. Temporarily reducing generator power output may also be considered depending on system dynamics to bridge the dead time between increasing the MSW/plastics feed rate and seeing increased syngas flow, however, this may not be necessary or expected unless faced with unusual feedstock conditions. While adjustments to airflow (the fastest acting control loop) and adjustments to the fuel to air ratio and the total fuel rate (both longer term responses) are preferred in this example to maintain suitable gas characteristics for the downstream application, the

MSW to plastics feed ratio control is not necessary, but may act as an additional control used to help smooth out long term variability.

In this example, MSW moisture content generally varies between 0 and 80%, and heating values vary between about 3000 and 33000kJ/kg, and the HC has a 2 minute
5 residency time and generally a pressure of about 210 mbar. A variation of about +/- 60 mbar is possible without exceeding the minimum supply pressure for the engine of about 150 mbar. Without the control system, the pressure can vary by up to about 1000 mbar, hence the long term flow fluctuations are actively reduced by the control system by up to 4 times (or 75%) in order to run the gas engine **9260** at constant load
10 as desired. Furthermore, pressure fluctuations of the converter gas can reach about 25 mbar/s without the control system, which is about 2.5 times the maximum of about 10 mbar/s for the engine of this example (or about 60%). Hence, the control system of the present invention may reduce short time process variability by at least 2.5 times (60%) and long term process variability by about 4 times (75%). Use of the HC **7230**
15 in this example can help reduce the short term variations.

The disclosure of all patents, publications, including published patent applications, and database entries referenced in this specification are expressly incorporated by reference in their entirety to the same extent as if each such individual patent, publication, and database entry were expressly and individually indicated to be
20 incorporated by reference.

Although the invention has been described with reference to certain specific embodiments, various modifications thereof will be apparent to those skilled in the art without departing from the spirit and scope of the invention. All such modifications as would be apparent to one skilled in the art are intended to be included within the
25 scope of the following claims.

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A low-temperature system for the conversion of carbonaceous feedstock into syngas of a defined composition, said system comprising:
 - 5 a horizontally oriented gasifier for conversion of carbonaceous feedstock into off-gas and residue, said gasifier having a feedstock inlet, gas outlet and a residue outlet, and comprising a stepped floor, wherein each step is provided with a lateral transfer unit for moving material through said gasifier during processing;
 - 10 a gas reformulating subsystem for the conversion of off-gas produced in said gasifier into syngas containing CO and H₂,
a residue conditioning subsystem for melting and homogenizing said residue, and
a control system to regulate the operation of the system.
- 15 2. The low-temperature system of claim 1 further comprising a heat recycling subsystem for reclaiming heat from said reformulated gas and recycling said heat to the gasifier.
- 20 3. The low-temperature system of claim 1 or 2 further comprising a gas conditioning subsystem for removal of a majority of particulate matter and at least a portion of heavy metal contaminants from said syngas to provide conditioned syngas.
- 25 4. The low-temperature system of claim 3 further comprising a gas homogenization system for receiving said conditioned syngas and providing substantially homogeneous conditioned syngas.
5. The low-temperature system of claim 1, wherein the control system is

configured to sense a composition of the syngas, compare said composition with said defined composition, and operate one or more process devices of the system in a manner conducive to adjusting said composition within a range of said defined composition.

5

6. The low-temperature system of claim 5, said gasifier comprising one or more inlets for the input of one or more process additives therein, wherein the control system is configured to sense a composition of the syngas, compare said composition with said defined composition, and adjust said input of process additives to adjust said composition within a range of said defined composition.

10

7. The system of claim 1, wherein each said lateral transfer unit comprises a carrier ram.

15

8. A method for the low-temperature conversion of carbonaceous feedstock into syngas, the method comprising the steps of:

providing a horizontally oriented gasifier comprising two or more laterally distributed processing zones;

20

feeding the feedstock to a first zone of said gasifier;

laterally transferring said fed feedstock through each of said zones for enhancing conversion of the feedstock into off-gas;

reformulating said off-gas into syngas containing CO and H₂,

conditioning a residue produced from the conversion process by melting and homogenizing said residue.

25

9. The method of claim 7, wherein the laterally transferring step of feedstock is operated and controlled by a control system adapted to monitor a transfer of the feedstock and adjust a lateral transfer of said feedstock in response thereto.

10. The method of claim 8, wherein said control system monitors said transfer via feedstock height sensors disposed within the gasifier.